

计算机视觉总结

SUMMARY OF COMPUTER VISION

(第1版)
LVSHUAILIN

OPEN SOURCE
BEIJING

VERSION 1

- 一. 数据结构与算法-LeetCode Hot 100
- 二. PYTHON: 1) NUMPY; 2) PANDAS; 3) PYTHON多进程; 4) PYTHON分布式; 5) PYTHON界面;
- 三. 深度学习: TensorFlow 2.0; PYTORCH;
- 四. 图像配准
- 五. 强化学习
- 六. OTHERS: 1) Model INFERENCE by EXE; 2) GIT; 3) DOCKER

LVSHUAILIN

2020年2月

目 录

第1章 绪论	1
1.1 两数之和unordered_map	1
1.1.1 解题思路	1
1.1.2 解题代码	3
1.2 两数相加linked list	4
1.2.1 解题思路	5
1.2.2 解题代码	7

第1章 绪论

Goals to Achieve

1. unordered_map.

§ 1.1 两数之和unordered_map

HOT100 1.1 问题描述

给定一个整数数组`nums` 和一个目标值`target`, 请你在该数组中找出和为目标值的那两个整数, 并返回他们的数组下标. 你可以假设每种输入只会对应一个答案. 但是, 你不能重复利用这个数组中同样的元素.

示例: 给定`nums = [2, 7, 11, 15]`, `target = 9`; 因为`nums[0] + nums[1] = 2 + 7 = 9`;

所以返回`[0, 1]`

<https://leetcode-cn.com/problems/two-sum>

1.1.1 解题思路

这里用c++的`unordered_map`来解决, `unordered_map`内部是一个关联容器, 采用hash 表结构, 有快速检索的功能.

哈希表是通过`key`关键字直接访问对应`value`值的数据结构. 特点是键和值一一对应, 查找时间复杂度 $O(1)$.

Example 1: `unordered_map`插入, 迭代遍历.

unordered_map example 1 code

```
1 #include <iostream>
2 #include <unordered_map>
3 #include <string>
4 using namespace std;
5 int main()
6 {
7     unordered_map<string, double> umap;
8     umap["PI"] = 3.14;
9     umap.insert(make_pair("a", 2.1));
10
11     // find in umap
12     string key = "PI";
13     if (umap.find(key) == umap.end())
14         cout << "cannot_find_PI" << endl;
15     else
16         cout << "find_" << umap.find(key)->first << "_=" << umap.find(key)->second <<
17             endl;
18
19     // iterator of umap
20     cout << "entire_unorded_map_is:" << endl;
21     unordered_map<string, double>::iterator itr;
22     for (itr = umap.begin(); itr != umap.end(); ++itr)
23         cout << "(" << itr->first << ", " << itr->second << ")" << endl;
24     system("pause");
25     return 0;
26 }
```

output:

```
find PI = 3
all elements are:
(PI,3.14)
(a,2.1)
```

Example 2: 利用unordered_map输出一段文字中重复单词的个数

unordered_map example 2 code

```
1 #include <iostream>
```

```
2 #include <unordered_map>
3 #include <string>
4 #include <sstream>
5
6 using namespace std;
7
8 void printWordFreq(const string& str)
9 {
10     unordered_map<string, int> wordFreq;
11     string word;
12     stringstream ss(str);
13     while (ss >> word)
14         wordFreq[word]++;
15
16     cout << "all elements are:" << endl;
17     for (auto u : wordFreq)
18         cout << "(" << u.first << "," << u.second << ")" << endl;
19 }
20
21 int main()
22 {
23     string str = "studies_very_very_hard";
24     printWordFreq(str);
25     return 0;
26 }
```

output:

```
all elements are:
(studies, 1)
(very, 2)
(hard, 1)
```

1.1.2 解题代码

```
1 #include <iostream>
2 #include <unordered_map>
```

```
3 #include <vector>
4 using namespace std;
5
6 vector<int> twoSum(vector<int>& nums, int target)
7 {
8     unordered_map<int, int> map;
9     vector<int> result={};
10    int n = (int)nums.size();
11    for(int i = 0; i < n; ++i) {
12        auto p = map.find(target-nums[i]);
13        if(p != map.end()) {
14            result.push_back(p->second);
15            result.push_back(i);
16        }
17        map[nums[i]] = i;
18    }
19    return result;
20 }
21
22 int main()
23 {
24     vector< int > nums = {2,7,11,15};
25     vector<int> result;
26     result = twoSum(nums,9);
27     cout<<"["<<result[0] << "," <<result[1]<<"]"<<endl;
28     return 0;
29 }
```

§ 1.2 两数相加linked list

HOT100 1.2 问题描述

给出两个非空的链表用来表示两个非负的整数。其中，它们各自的位数是按照逆序的方式存储的，并且它们的每个节点只能存储一位数字。如果，我们将这两个数相加起来，则会返回一个新

的链表来表示它们的和。

您可以假设除了数字0之外, 这两个数都不会以0开头。

示例: 输入(2 -> 4 -> 3) + (5 -> 6 -> 4), 输出: 7 -> 0 -> 8, 原因: $342 + 465 = 807$

<https://leetcode-cn.com/problems/add-two-numbers>

1.2.1 解题思路

这里用c++ 链表来解决

Example_1: 创建链表并初始化

linked list example_1 code

```
1  #include <iostream>
2
3  using namespace std;
4
5  class Node{
6  public:
7      int data;
8      Node* next;
9  };
10
11 int main()
12 {
13     Node* head = nullptr;
14     Node* second = nullptr;
15     Node* third = nullptr;
16
17     head = new Node();
18     head->data = 1;
19
20     second = new Node();
21     second->data = 2;
22
23     third = new Node();
```

```
24     third->data = 3;
25
26     cout << head->data << " " << second->data << " " << third->data << endl;
27
28     delete head;
29     delete second;
30     delete third;
31     return 0;
32 }
```

output:

1 2 3

Example 2: 打印链表中的所有元素

linked list example 2 code

```
1  #include <iostream>
2
3  using namespace std;
4
5  class Node{
6  public:
7      int data;
8      Node* next;
9  };
10
11 void PrintLinkedList(Node* head)
12 {
13     Node* temp = head;
14     while (temp != nullptr) {
15         cout << temp->data << " ";
16         temp = temp->next;
17     }
18     cout << endl;
19 }
20
21 int main()
22 {
```

```
23 Node* head = nullptr;
24 Node* second = nullptr;
25 Node* third = nullptr;
26
27 head = new Node();
28 second = new Node();
29 third = new Node();
30
31 head->data = 1;
32 head->next = second;
33
34 second->data = 2;
35 second->next = third;
36
37 third->data = 3;
38 third->next = nullptr;
39
40
41 PrintLinkedList(head);
42
43 delete head;
44 delete second;
45 delete third;
46 return 0;
47 }
```

output:

1 2 3

1.2.2 解题代码