

# 计算机视觉总结

## SUMMARY OF COMPUTER VISION

(第1版)  
LVSHUAILIN

OPEN SOURCE  
BEIJING

# VERSION 1

- 一. 数据结构与算法-LeetCode Hot 100
- 二. PYTHON: 1) NUMPY; 2) PANDAS; 3) PYTHON多进程; 4) PYTHON分布式; 5) PYTHON界面;
- 三. 深度学习: TensorFlow 2.0; PYTORCH;
- 四. 图像配准
- 五. 强化学习
- 六. OTHERS: 1) Model INFERENCE by EXE; 2) GIT; 3) DOCKER

LVSHUAILIN

2020年2月

# 目 录

第1章 LeetCode Hot 100.....	1
1.1 两数之和unordered_map.....	1
1.1.1 解题思路.....	1
1.1.2 解题代码.....	3
1.2 两数相加linked list.....	4
1.2.1 解题思路.....	4
1.2.2 解题代码.....	9
1.3 无重复字符的最长子串(double pointer algorithm, set).....	12
1.3.1 解题思路.....	12
1.3.2 解题代码.....	13



# 第1章 LeetCode Hot 100

## Goals to Achieve

### 1. unordered\_map.

## § 1.1 两数之和unordered\_map

### HOT100 1.1 问题描述

给定一个整数数组**nums** 和一个目标值**target**, 请你在该数组中找出和为目标值的那两个整数, 并返回他们的数组下标. 你可以假设每种输入只会对应一个答案. 但是, 你不能重复利用这个数组中同样的元素.

示例: 给定nums = [2, 7, 11, 15], target = 9; 因为nums[0] + nums[1] = 2 + 7 = 9;

所以返回[0, 1]

<https://leetcode-cn.com/problems/two-sum>

### 1.1.1 解题思路

这里用c++的unordered\_map来解决, unordered\_map内部是一个关联容器, 采用hash 表结构, 有快速检索的功能.

哈希表是通过key关键字直接访问对应value值的数据结构. 特点是键和值一一对应, 查找时间复杂度**O(1)**.

Example\_1: unordered\_map插入, 迭代遍历.

*unordered\_map example\_1 code*

```
1 #include <iostream>
2 #include <unordered_map>
3 #include <string>
4 using namespace std;
5 int main()
```

```

6 {
7     unordered_map<string, double> umap;
8     umap["PI"] = 3.14;
9     umap.insert(make_pair("a", 2.1));
10
11     // find in umap
12     string key = "PI";
13     if (umap.find(key) == umap.end())
14         cout << "cannot find PI" << endl;
15     else
16         cout << "find " << umap.find(key)->first << " = " << umap.find(key)->second << endl;
17
18     // iterator of umap
19     cout << "entire unorded_map is:" << endl;
20     unordered_map<string, double>::iterator itr;
21     for (itr = umap.begin(); itr != umap.end(); ++itr)
22         cout << " ( " << itr->first << " , " << itr->second << " ) " << endl;
23     system("pause");
24     return 0;
25 }

```

**output:**

find PI = 3

all elements are:

(PI,3.14)

(a,2.1)

Example\_2: 利用unordered\_map输出一段文字中重复单词的个数

*unordered\_map example\_2 code*

```

1 #include <iostream>
2 #include <unordered_map>
3 #include <string>
4 #include <sstream>
5
6 using namespace std;
7
8 void printWordFreq(const string& str)
9 {
10     unordered_map<string, int> wordFreq;
11     string word;

```

```
12     stringstream ss(str);
13     while (ss >> word)
14         wordFreq[word]++;
15
16     cout << "all elements are:" << endl;
17     for (auto u : wordFreq)
18         cout << " (" << u.first << ", " << u.second << ") " << endl;
19 }
20
21 int main()
22 {
23     string str = "studies very very hard";
24     printWordFreq(str);
25     return 0;
26 }
```

**output:**

```
all elements are:
(studies, 1)
(very, 2)
(hard, 1)
```

### 1.1.2 解题代码

```
1 #include <iostream>
2 #include <unordered_map>
3 #include <vector>
4 using namespace std;
5
6 vector<int> twoSum(vector<int>& nums, int target)
7 {
8     unordered_map<int, int> map;
9     vector<int> result={};
10    int n = (int)nums.size();
11    for(int i = 0; i < n; ++i) {
12        auto p = map.find(target-nums[i]);
13        if(p != map.end()) {
14            result.push_back(p->second);
15            result.push_back(i);
16        }
17    }
```

```
16     }
17     map[nums[i]] = i;
18 }
19 return result;
20 }
21
22 int main()
23 {
24     vector<int> nums = {2,7,11,15};
25     vector<int> result;
26     result = twoSum(nums,9);
27     cout<<" ["<<result[0]<<" , "<<result[1]<<" ] "<<endl;
28     return 0;
29 }
```

## § 1.2 两数相加linked list

### HOT100 1.2 问题描述

给出两个非空的链表用来表示两个非负的整数。其中，它们各自的位数是按照逆序的方式存储的，并且它们的每个节点只能存储一位数字。如果，我们将这两个数相加起来，则会返回一个新的链表来表示它们的和。

您可以假设除了数字0之外，这两个数都不会以0开头。

示例: 输入(2 → 4 → 3) + (5 → 6 → 4), 输出: 7 → 0 → 8, 原因: 342 + 465 = 807

<https://leetcode-cn.com/problems/add-two-numbers>

### 1.2.1 解题思路

这里用c++ 链表来解决

Example\_1: 创建链表并初始化

*linked list example\_1 code*

```
1 #include <iostream>
2
3 using namespace std;
4
5 class Node{
```



```
6 public:
7     int data;
8     Node* next;
9 };
10
11 int main()
12 {
13     Node* head = nullptr;
14     Node* second = nullptr;
15     Node* third = nullptr;
16
17     head = new Node();
18     head->data = 1;
19
20     second = new Node();
21     second->data = 2;
22
23     third = new Node();
24     third->data = 3;
25
26     cout << head->data << " " << second->data << " " << third->data << endl;
27
28     delete head;
29     delete second;
30     delete third;
31     return 0;
32 }
```

**output:**

1 2 3

Example\_2: 打印链表中的所有元素

*linked list example\_2 code*

```
1 #include <iostream>
2
3 using namespace std;
4
5 class Node{
6 public:
7     int data;
```

```
8     Node* next;
9 };
10
11 void PrintLinkedList(Node* head)
12 {
13     Node* temp = head;
14     while (temp != nullptr) {
15         cout << temp->data << " ";
16         temp = temp->next;
17     }
18     cout << endl;
19 }
20
21 int main()
22 {
23     Node* head = nullptr;
24     Node* second = nullptr;
25     Node* third = nullptr;
26
27     head = new Node();
28     second = new Node();
29     third = new Node();
30
31     head->data = 1;
32     head->next = second;
33
34     second->data = 2;
35     second->next = third;
36
37     third->data = 3;
38     third->next = nullptr;
39
40
41     PrintLinkedList(head);
42
43     delete head;
44     delete second;
45     delete third;
46     return 0;
47 }
```

**output:**

1 2 3

Example\_3: 链表插入节点

*linked list example\_3 code*

```
1 #include <iostream>
2
3 using namespace std;
4
5 class Node{
6 public:
7     int data;
8     Node* next;
9 };
10
11 // 在链表前面插入节点
12 void push(Node** head_ref, int newData)
13 {
14     Node* newNode = new Node();
15     newNode->data = newData;
16     newNode->next = (*head_ref);
17     (*head_ref) = newNode;
18 }
19
20 // 在节点后面插入节点
21 void insertAfter(Node** prev_node, int newData)
22 {
23     if ((*prev_node) == nullptr) {
24         cout << "the previous node cannot be nullptr" << endl;
25         return;
26     }
27
28     Node* newNode = new Node();
29     newNode->data = newData;
30     newNode->next = (*prev_node)->next;
31     (*prev_node)->next = newNode;
32 }
33
34 // 在尾节点后插入节点
```

```
35 void append(Node** head_ref, int newData)
36 {
37     Node* newNode = new Node();
38     newNode->data = newData;
39     newNode->next = nullptr;
40     if ((*head_ref) == nullptr) {
41         (*head_ref) = newNode;
42         return;
43     }
44
45     Node* move = (*head_ref);
46     while (move->next != nullptr) {
47         move = move->next;
48     }
49     move->next = newNode;
50 }
51
52 // 打印链表
53 void PrintLinkedList(Node* head)
54 {
55     Node* temp = head;
56     while (temp != nullptr) {
57         cout << temp->data << " ";
58         temp = temp->next;
59     }
60     cout << endl;
61 }
62
63 void destroyLinkedList(Node** head_ref) {
64     Node* move = (*head_ref);
65     Node* next = nullptr;
66     while (move != nullptr) {
67         next = move->next;
68         delete move;
69         move = next;
70     }
71     (*head_ref) = nullptr;
72 }
73
74 int main()
```

```
75 {
76     Node* head = nullptr;
77
78     append(&head, 6);
79
80     push(&head, 7);
81
82     push(&head, 1);
83
84     append(&head, 4);
85
86     insertAfter(&(head->next), 8);
87
88     cout << "linked list is: ";
89     PrintLinkedList(head);
90     destroyLinkedList(&head);
91     return 0;
92 }
```

**output:**

linked list is: 1 7 8 6 4

### 1.2.2 解题代码

```
1  #include <iostream>
2  using namespace std;
3
4  struct ListNode {
5      int val;
6      ListNode *next;
7      ListNode(int x) : val(x), next(NULL) {}
8  };
9
10 ListNode* addTwoNumbers(ListNode* l1, ListNode* l2) {
11     int len1 = 1;//记录的长度l1
12     int len2 = 1;//记录的长度l2
13     ListNode* p = l1;
14     ListNode* q = l2;
15     while (p->next != NULL)//获取的长度l1
```

```
{
    len1++;
    p = p->next;
}
while (q->next != NULL)//获取的长度l2
{
    len2++;
    q = q->next;
}
if (len1 > len2)//较长，在末尾补零l1l2
{
    for (int i = 1; i <= len1 - len2; i++)
    {
        q->next = new ListNode(0);
        q = q->next;
    }
}
else//较长，在末尾补零l2l1
{
    for (int i = 1; i <= len2 - len1; i++)
    {
        p->next = new ListNode(0);
        p = p->next;
    }
}
p = l1;
q = l2;
bool count = false;//记录进位
ListNode* l3 = new ListNode(-1);//存放结果的链表
ListNode* w = l3;//的移动指针l3
int i = 0;//记录相加结果
while (p != NULL && q != NULL)
{
    i = count + p->val + q->val;
    w->next = new ListNode(i % 10);
    count = i >= 10 ? true : false;
    w = w->next;
    p = p->next;
    q = q->next;
}
```

```
56     if (count)//若最后还有进位
57     {
58         w->next = new ListNode(1);
59         w = w->next;
60     }
61     return l3->next;
62 }
63
64 void printLinkedList(ListNode* head)
65 {
66     ListNode* move = head;
67     while (move != nullptr) {
68         cout << move->val << " ";
69         move = move->next;
70     }
71 }
72
73 int main()
74 {
75     #if 1
76         ListNode* l1 = new ListNode(2);
77         ListNode* l1_1 = new ListNode(4);
78         ListNode* l1_2 = new ListNode(3);
79
80         l1->next = l1_1;
81         l1_1->next = l1_2;
82
83
84         ListNode* l2 = new ListNode(5);
85         ListNode* l2_1 = new ListNode(6);
86         ListNode* l2_2 = new ListNode(4);
87         l2->next = l2_1;
88         l2_1->next = l2_2;
89     #endif
90
91     #if 0
92         ListNode* l1 = new ListNode(5);
93         ListNode* l2 = new ListNode(5);
94     #endif
95 }
```

```
96     ListNode* result = addTwoNumbers(l1, l2);
97     printLinkedList(result);
98     return 0;
99 }
```

**output:**

7 0 8

## § 1.3 无重复字符的最长子串(double pointer algorithm, set)

### HOT100 1.3 问题描述

给定一个字符串, 请你找出其中不含有重复字符的最长子串的长度.

**示例1:**

输入: "abcabcbb"

输出: 3

解释: 因为无重复字符的最长子串是"abc", 所以其长度为3.

**示例2:**

输入: "bbbbbb"

输出: 1

解释: 因为无重复字符的最长子串是"b", 所以其长度为1.

**示例3:**

输入: "pwwkew"

输出: 3

解释: 因为无重复字符的最长子串是"wke", 所以其长度为3. 请注意, 你的答案必须是子串的长度, "pwke"是一个子序列, 不是子串.

<https://leetcode-cn.com/problems/longest-substring-without-repeating-characters>

### 1.3.1 解题思路

<https://cloud.tencent.com/developer/article/1377650>

这道题主要用到思路是: 滑动窗口

什么是滑动窗口?



其实就是一个队列, 比如例题中的`abcabcbb`, 进入这个队列(窗口)为`abc`满足题目要求, 当再进入`a`, 队列变成了`abca`, 这时候不满足要求. 所以, 我们要移动这个队列!

如何移动?

我们只要把队列的左边的元素移出就行了, 直到满足题目要求!

一直维持这样的队列, 找出队列出现最长的长度时候, 求出解!

时间复杂度:  $O(n)$

### 1.3.2 解题代码

```
1 #include <iostream>
2 #include <string>
3 #include <unordered_set>
4 #include <algorithm> // max, min
5
6 using namespace std;
7
8 int lengthOfLongestSubstring(string s) {
9     if (s.size() == 0) return 0;
10    unordered_set<char> lookup;
11    int maxStr = 0;
12    int left = 0;
13    for (int i = 0; i < s.size(); i++) {
14        while (lookup.find(s[i]) != lookup.end()) {
15            lookup.erase(s[left]);
16            left++;
17        }
18        maxStr = max(maxStr, i - left + 1);
19        lookup.insert(s[i]);
20    }
21    return maxStr;
22 }
23
24 int main()
25 {
26     string str = "abcabcbb";
27     cout << lengthOfLongestSubstring(str) << endl;
28     return 0;
29 }
```

**output:**

3