

Pipeline script from SCM

→ Configure on Jenkins slave (Eg: slave-1) with JNLP or SSH connection,

After that Install git on local machine → Create one local repository (eg: /mnt/vel-app) → create index.html file inside and commit index.html file in local repository → after that create one more file for job script named as **Jenkinsfile** and copy below script into that. (*name of the script file must be **Jenkinsfile** only)

```
pipeline {
    agent {
        label {
            label "slave-1"
            customWorkspace "/mnt/slave-1"
        }
    }

    stages {
        stage ("one") {
            steps {
                sh "sudo yum install httpd -y"
            }
        }
        stage ("two") {
            steps {
                sh "sudo service httpd start"
                sh "sudo cp -r index.html /var/www/html/"
                sh "sudo chmod -R 777 /var/www/html/"
            }
        }
    }
}
```

Now add & commit Jenkinsfile into local repository as well and push the changes to GitHub central repository.

Now on Jenkins Dashboard,

Go to New Item → Add name (Eg: vel-app-pipeline) → select Pipeline → OK → Pipeline → Definition > Pipeline script from SCM → SCM > Git → Add repository URL → Select credentials if Repository is private else skip → Select Branch (*/master) → Sript Path > Jenkinsfile → **Apply + Save**

Build Now

Multi Branch Pipeline:

Suppose we have one repository (eg: vel-app) on GitHub, under which we have two different branches master and 23q1. Both master and 23q1 has two files, index.html and Jenkinsfile.

Jenkisfile in Master branch:

```
pipeline {
    agent {
        label {
            label "slave-1"
```

```

        customWorkspace "/mnt/slave-1"
    }
}

stages {
    stage ("one") {
        steps {
            echo "This is master branch"
        }
    }
}
}

```

Jenkinsfile in 21q1 branch:

```

pipeline {
    agent {
        label {
            label "slave-1"
            customWorkspace "/mnt/slave-1"
        }
    }

    stages {
        stage ("one") {
            steps {
                echo "This is 23q1 branch "
            }
        }
    }
}
}

```

Now on Jenkins Dashboard,

Go to New item → add name (eg: vel-app-multi-branch) → select Multibranch pipeline



Multibranch Pipeline

Creates a set of Pipeline projects according to detected branches in one SCM repository.

→ OK → Add display name (eg: vel-app) → Branch source > Add source > Git → add git repositories URL under Project Repository field → add credentials in case of private repo else skip → under Behaviours → check if Discover branches option is there if not then click on add to select

Behaviours

Discover branches

?

✕

Add ▾

→ **Apply + Save**

Click on ▶ **Scan Multibranch Pipeline Now**

If everything is right then you can see now that Jenkins have created two different jobs, Jenkins scans the repository and creates a job per branch automatically.

Dashboard > vel-app >

Status

Configure

▶ Scan Multibranch Pipeline Now

📄 Scan Multibranch Pipeline Log

📄 Multibranch Pipeline Events

🗑 Delete Multibranch Pipeline

👤 People

📁 Build History

🕒 Project Relationship

🔍 Check File Fingerprint

vel-app

Folder name: vel-app-multi-branch
vel-app

Disable Multibranch Pipeline

Branches (2)

S	W	Name ↓	Last Success	Last Failure	Last Duration
...	☀	23q1	N/A	N/A	N/A ▶
...	☀	master	N/A	N/A	N/A ▶

Icon: S M **L** Icon legend 📡 Atom feed for all 📡 Atom feed for failures 📡 Atom feed for just latest builds