

- /shutdown.sh
- /startup.sh

Jenkins as a service on a Red Hat - based EC2 instance.

<u>Command</u>	<u>What it did</u>
• yum install java-17-amazon-corretto.x86_64	installed java 17, required by newer Jenkins versions.
• wget --jenkins.repo	Added Jenkins repository to yum.
• rpm --import .jenkins.io-2023.key	imported Jenkins GPG Key for package verification
• yum install jenkins	installed Jenkins
• service jenkins status/start	started Jenkins service and checked its status.
• Navigated to /var/lib/jenkins/secrets/initialAdminPassword	Retrieved Jenkins admin setup password
• service jenkins stop/start	Restarted Jenkins service.

What to do next

1. Open Jenkins in Browser
Jenkins by default runs on port 8080
Go to
http://<your-EC2-public-IP>:8080

if it doesn't open:

- check EC2 security group; ensure port 8080 is open in inbound rules
- ensure Jenkins is running
service jenkins status

2. initial jenkins setup

You'll see a page asking for:

Administrator Password

Paste the output from

```
cat /var/lib/jenkins/secrets/initialAdminPassword
```

Then proceed with

install suggested plugins

create admin user (or skip for now)

3. Configure Jenkins Autostarts on Reboot (optional)
jenkins installs as a service, to enable autostart,
run

```
systemctl enable jenkins
```

to stop / start manually:

```
systemctl stop jenkins
```

```
systemctl start jenkins
```

You're now Ready to:

- create your first Jenkins job
- configure Git + Maven
- Build WAR and deploy to Tomcat (automated)