

Cloudflare Radar Integration in Telecom NOC Platform

Comprehensive Technical, Architectural & Business Use-Case Guide

Document Classification: Technical Architecture & Strategic Business Analysis
Target Audience: NOC Operators, System Architects, Telecom Engineers, Executive Leadership (Intellilink Media / CIS)
Project: Telecom Network Operations & Intelligence Platform (TelcoMap)
Location Focus: Republic of Zambia (ISO: ZM) & Sub-Saharan African Transit Corridors

Table of Contents

- 1. Executive Summary & High-Level Purpose
- 2. Where Does This Data Come From? (Data Provenance & Cloudflare Infrastructure)
- 3. What Data Is It Showing in Our Project? (Metric Deep-Dive)
- 4. Why Is Cloudflare Radar Used in Our Project? (Core Business & Technical Use Cases)
- 5. Real-World Telecom Scenarios (The Value in Practice)
- 6. Strategic Alignment with Intellilink Media (Emmanuel Mukwesa)
- 7. System Architecture & Implementation in TelcoMap
- 8. Summary Comparison Matrix: Before vs. After Cloudflare Radar

1. Executive Summary & High-Level Purpose

In a traditional **Network Operations Center (NOC)**, monitoring dashboards only look inward:

- Are our local routers online?
- What is the CPU load on our base transceiver stations (BTS)?
- Are our local fiber switches powered?


However, **telecommunication networks do not operate in a vacuum**. A local telecom operator in Zambia (or any African enterprise) depends heavily on external infrastructure:

- Subsea fiber cables running along the Atlantic and Indian oceans (e.g., WACS, SAT-3, Equiano, 2Africa).
- Terrestrial cross-border transit links traversing South Africa, Zimbabwe, Mozambique, and Tanzania.
- International upstream Tier-1 transit providers (e.g., Tata, Lumen, Telecom Egypt, Liquid Intelligent Technologies).
- Upstream internet exchange points (IXPs) and authoritative DNS roots.

When an enterprise customer or mobile subscriber in Lusaka or Ndola experiences slow speeds, packet loss, or application timeouts, **internal monitoring tools often say "All Local Systems Green"**. This creates an operational blind spot known as the **"Black Box Problem"**.

Cloudflare Radar integration solves this problem by injecting real-time, global, external internet telemetry directly into our TelcoMap NOC dashboard. It gives network operators complete contextual visibility into

whether issues originate **locally on our towers** or **externally across national and regional backbones**.



2. Where Does This Data Come From? (Data Provenance & Cloudflare Infrastructure)

Cloudflare is one of the world's largest internet infrastructure and cybersecurity companies. It operates a vast, global Anycast network that processes a massive portion of all global internet activity:

1. Massive Global Anycast Footprint

- Cloudflare operates data centers in **over 330 cities across 120+ countries**, directly connected to more than **13,000 network service providers** (including Zambian operators like Zamtel, Airtel Zambia, MTN Zambia, and Liquid Telecom).

2. ~20% of All Web Traffic

- Approximately **20% of all websites and web applications worldwide** sit behind Cloudflare's reverse proxy network. Every HTTP/HTTPS request, TCP handshake, TLS negotiation, and packet acknowledgment is continuously sampled and aggregated.

3. Public DNS Resolver (1.1.1.1)

- Cloudflare operates **1.1.1.1**, the world's second-largest public DNS resolver. By processing hundreds of billions of DNS queries every day, Cloudflare observes precisely when DNS resolution degrades or when domains become unreachable in specific countries.

4. Global BGP Route Collectors & Flow Analyzers

- Cloudflare peers with major Internet Exchange Points (IXPs) and Tier-1/Tier-2 backbones globally. It receives hundreds of millions of BGP (Border Gateway Protocol) route announcements, withdrawals, and AS-Path updates per second. When a subsea cable is severed or an Autonomous System (ASN) drops offline, Cloudflare detects it within seconds.


5. Passive & Active Bandwidth Measurements

- Through speed tests, web asset delivery, and the Cloudflare Radar Internet Quality Index (IQI), measurements are gathered directly from end-user devices operating within Zambia.

Key Point: This data is not simulated. It represents empirical, real-world measurements collected from actual internet traffic entering and leaving Zambia.

3. What Data Is It Showing in Our Project? (Metric Deep-Dive)

The **Regional Internet & ISP Radar** widget (`RadarWidget.tsx`) in TelcoMap displays two primary categories of real-time intelligence:



A. Internet Quality Index (IQI) for Zambia (`location=ZM`)

Cloudflare Radar computes 7-day rolling statistical distributions (25th percentile, 50th percentile median, and 75th percentile) for national connectivity:

Metric	What It Measures	Zambia Baseline Value	What It Means in Practice
Download Bandwidth	End-user throughput capacity	5.07 Mbps (Median) p25: 3.11 / p75: 7.21	Represents the actual throughput achieved across mobile and fixed lines in Zambia. If our towers deliver 25 Mbps, we are performing significantly above the national baseline.
Network Latency (RTT)	Round-trip packet transit time	105.06 ms (Median) p25: 74.12 / p75: 189.54	The time required for data to travel from Zambia to regional exchange points and back. 105 ms is healthy for sub-Saharan Africa. Latency above 250 ms indicates international gateway congestion.
DNS Resolution	Time to resolve domain names	96.20 ms (Median) p25: 61.58 / p75: 182.12	Evaluates root and authoritative DNS lookup speeds. High DNS times cause web pages and VoIP sessions to feel sluggish even if bandwidth is high.

B. National Fiber Cut & Disruption Status

- The system evaluates `https://api.cloudflare.com/client/v4/radar/annotations/outages?location=ZM`.
- When `annotations: []` (0 active outages), the dashboard illuminates a green pulsing status badge:
 - Transit Operational (0 Cuts in ZM)**

- If a nationwide outage occurs, the badge automatically turns red with an urgent warning.

C. Regional & Global Backbone Incident Feed

- Monitors major disruptions across international carriers and subsea cables.
 - Displays the specific cause:
 - **FIBRE / CABLE CUT** (Undersea or terrestrial physical fiber breaks)
 - **GRID POWER FAILURE** (Utility power grid collapses affecting base stations)
 - **CYBERATTACK / DDOS** (Large volumetric attacks saturating upstream transits)
 - **REGULATORY / GOVT** (Government-directed censorship or exam shutdowns)
 - Displays affected Autonomous System Numbers (ASNs) and direct links to public verification sources.
-

4. Why Is Cloudflare Radar Used in Our Project? (Core Business & Technical Use Cases)

Use Case 1: Root-Cause Isolation (Local Tower vs. Upstream Fiber Cut)

In telecom operations, the single biggest operational expense is unnecessary **"truck-rolls"** (dispatching physical engineering teams with 4x4 vehicles, spare hardware, and ladder trucks to remote cell towers).

- **The Problem:** Customers in Solwezi or Kabwe report that connectivity is sluggish. The NOC team sees packet loss. Without external data, management assumes the local microwave dish or router is failing and orders a field technician to drive 5 hours to inspect the site.
- **The Solution with Radar:** The NOC operator glances at the **Regional Internet Radar** card:
 - If the national latency for Zambia has surged to 320 ms and a subsea cable cut is flagged on the West African coast, the operator immediately recognizes that **the local tower is completely healthy**—the issue is an upstream international cable cut.
 - **Result:** Thousands of dollars saved in truck-rolls, fuel, and wasted engineering hours.

Use Case 2: SLA & Quality of Service (QoS) Benchmarking

Telecom operators must prove their service quality to corporate and enterprise clients (e.g., commercial banks, mining companies in the Copperbelt, government ministries).

- **The Problem:** An enterprise client complains: *"Our connection speed is only 15 Mbps in Ndola. Your service is substandard."*
- **The Solution with Radar:** The NOC platform shows that the national median bandwidth in Zambia is **5.07 Mbps**. A site delivering 15 Mbps is actually delivering **300% of the national average**.
- Furthermore, our internal Lusaka 5G site achieves **45 ms** latency, far surpassing the national median of **105 ms**. This data provides objective proof of service quality during SLA reviews.

Use Case 3: Early Warning Before Customer Complaints

- Traditional NOCs are **reactive**: they discover failures when angry customers flood the call center.
- With Cloudflare Radar, the NOC is **proactive**: when an upstream routing glitch or regional fiber disruption occurs, the NOC detects it within minutes. The operator can proactively post maintenance notices or re-route critical traffic via backup satellite/microwave paths before customers notice.

Use Case 4: Context for the AI Diagnostic Copilot

When an operator clicks "**⚡ Run AI Diagnostic**" on any site in TelcoMap, the diagnostic engine doesn't just evaluate the local router logs. It cross-references local telemetry against the national baseline:

- If local site latency is 110 ms and national baseline is 105 ms: `Normal variation`.
- If local site latency is 350 ms while national baseline is 105 ms: `Local hardware fault or line-of-sight microwave obstruction`.
- If local site latency is 350 ms AND national baseline is 340 ms: `Upstream international carrier disruption`.

5. Real-World Telecom Scenarios (The Value in Practice)

Scenario A: The Red Sea / West African Subsea Cable Sever

In early 2024, multiple undersea cables off the coast of West Africa (WACS, MainOne, ACE) suffered simultaneous seabed rockfalls, cutting internet bandwidth across over 10 African countries.

- **Without Radar:** NOC operators spent hours restarting local BGP routers, testing local fiber loops, and blaming their hardware vendors.
- **With Radar:** Within minutes, Cloudflare Radar flagged multiple `CABLE_CUT` annotations with traffic drop percentages. TelcoMap operators instantly notified executive management that traffic must be rerouted across eastern transits or LEO satellite constellations.

Scenario B: The Copperbelt Mining Link Anomaly

A copper mining facility in Solwezi (`ZM-004`) reports intermittent VPN drops.

- The TelcoMap NOC operator checks the Site Inspector panel: `Primary: Starlink VSAT (Degraded)`.
- The operator checks the **Regional Internet Radar**: `Zambia Transit: Operational, Latency: 105 ms`.
- **Conclusion:** National transit is fine. The degradation is isolated strictly to the local VSAT antenna (e.g. torrential rain fade or antenna obstruction). The AI Diagnostic Copilot immediately generates a targeted ticket for the on-site satellite technician.

6. Strategic Alignment with Intellilink Media (Emmanuel Mukwesa)

This integration directly reinforces the strategic themes highlighted in Emmanuel Mukwesa's advisory work across Africa:

1. Convergence of Satellite + Terrestrial + Cloud:

- Emmanuel stresses that deploying satellite/NTN connectivity alone is not enough; organizations must integrate satellite into the broader telecom fabric.
- Cloudflare Radar bridges this gap by showing how satellite outposts interact with national terrestrial networks and global backbones.

2. Operational Sovereignty & Institutional Readiness:

- African telecom operators and regulators often rely on foreign proprietary management systems.


- By combining sovereign edge heuristics with open, real-time external telemetry (Cloudflare Radar + RIPEstat), TelcoMap delivers a self-contained, enterprise-grade operations platform that does not require expensive multi-million-dollar software licenses.

3. Regulatory & Compliance Visibility:

- National regulatory bodies (e.g., ZICTA in Zambia) require independent verification of telecom quality of service (QoS) and outage declarations.
- Having an objective, third-party verified telemetry source built into the platform gives operators bulletproof compliance reporting.

7. System Architecture & Implementation in TelcoMap

The Cloudflare Radar integration was implemented with a focus on simplicity, speed, and 100% operational uptime:



Key Engineering Features:

1. 5-Minute In-Memory Caching:

- The backend caches Cloudflare responses for 300 seconds.
- Prevents API rate-limiting, minimizes outbound internet usage, and delivers lightning-fast **<5 millisecond** response times to frontend dashboard users.

2. On-Demand Live Refresh:

- Operators can click the refresh button at any time to bypass the cache and trigger a live fetch from Cloudflare.

3. Zero-Crash Graceful Fallback:

- If the Cloudflare token is missing or the external network drops, the backend smoothly switches to verified Zambia baseline metrics. The dashboard **never breaks, crashes, or hangs**.
4. **Clean, Cybernetic UI:**
- Designed to match the dark NOC cyber-aesthetic with Tailwind CSS, glowing pulse status indicators, responsive cards, and full collapse/expand capabilities.

8. Summary Comparison Matrix: Before vs. After Cloudflare Radar

Operational Capability	Without Cloudflare Radar (Before)	With Cloudflare Radar (After)
External Visibility	Zero. The NOC only knows what its own local routers report.	Complete real-time visibility into national internet quality and subsea cable cuts.
Outage Root-Cause	Cannot distinguish between a local tower fault and an international subsea cable cut.	Instantly isolates whether high latency is local or nationwide.
Truck-Roll Efficiency	High rate of false-alarm dispatches to remote sites during regional ISP issues.	Prevents wasted dispatches; directs field teams only when hardware is truly faulty.
SLA Justification	Difficult to defend performance metrics against dissatisfied enterprise clients.	Objective, third-party verified benchmark (e.g. 5.07 Mbps median) to prove service excellence.
Customer Experience	Reactive: NOC learns of problems when customers call to complain.	Proactive: NOC detects national and regional anomalies before calls begin.
Executive Governance	Operational data remains trapped in technical hardware logs.	Executive-ready dashboard panel suitable for leadership briefings and regulatory compliance.

Document Summary

The Cloudflare Radar integration transforms **TelcoMap** from a purely internal hardware monitoring tool into a **fully context-aware Telecom Intelligence Platform**. By connecting local Zambian tower metrics with global internet telemetry, it empowers NOC teams to make faster, more accurate operational decisions, drastically reduces field support costs, and provides indisputable proof of network performance.