

DEEPAKE DETECTION USING ARTIFICIAL INTELLIGENCE

K. D. POLYTECHNIC, PATAN
DEPARTMENT OF COMPUTER ENGINEERING

A Spatio-Temporal Hybrid Deep Learning Approach (ResNeXt50 + LSTM)

GUIDE: _____

ENROLLMENT NO: _____

1. THE DEEPAKE PROBLEM

Deepfakes synthesize hyper-realistic human facial replacements in video feeds using generative deep learning models.

Creation Tools: FaceSwap, DeepFaceLab, Faceit, GANs / Diffusion

Fake News: Viral synthetic hoaxes | **Financial Fraud:** Executive spoofing

Election Sabotage: Politician deepfakes | **Identity Theft:** Extortion & defamation

Single-frame CNNs analyze isolated stills, ignoring vital temporal continuity like optical flow and blinking jitter. Our **Spatio-Temporal Framework** captures both spatial and motion cues for reliable detection.

+900%

Annual Surge in Synthetic Media

<54%

Human Manual Detection Rate

2. FORENSIC VISUAL EVIDENCE




Figure 1: Forensics Split Analysis.
Authentic Biological Skin & 68 Biometric Landmarks.
Deepfake Boundary Artifacts with Grad-CAM Heatmap Trace.

Biometric Cue	Real Video	Deepfake Tampered
Skin Boundary	Seamless pore continuity	Blending boundary artifacts
Eye Reflection	Specular corneal coherence	Asymmetric reflection error
Landmark Grid	Smooth head kinematics	Inter-frame micro-jitter
Pupil Dynamics	Bilateral consensual response	Uncorrelated dilation jitter

Forensic Diagnostic: Grad-CAM thermal gradient analysis detects high-frequency energy concentration along boundary contours where GAN face-swaps fail seamless Poisson blending.

3. CORE OBJECTIVES & CORPUS

- Spatio-Temporal Fusion:** Couple ResNeXt-50 grouped convolutions with LSTM recurrent cells to capture micro-flickering anomalies.
- Explainability (XAI):** Generate Class Activation Maps (CAM) identifying tampered facial zones for judicial evidentiary trust.
- Generalization:** Evaluated across unseen actor identities to prevent synthetic facial overfitting.
- Sub-2s Latency:** Real-time video processing designed for scalable automated screening.

MULTI-BENCHMARK TRAINING CORPUS (23,186 VIDEOS)

DFDC (Meta AI): 18,200 Balanced Clips	FaceForensics++: 3,000 High-Res Clips
Celeb-DF v2: 1,986 Realistic Videos	Training Setup: PyTorch • Google Cloud GPU

9. SOTA BENCHMARK COMPARISON

Model	Backbone	Temporal	Accuracy	AUC
MesoNet-4	Shallow CNN	None	70.4%	0.742
ResNet-50	Residual CNN	None	78.4%	0.825
XceptionNet	Depthwise Sep	None	83.2%	0.881
EfficientNet	Compound Scaled	None	84.6%	0.895
Proposed Hybrid	ResNeXt-50	Bi-LSTM	87.0%	0.924

Comparative Finding: Our proposed spatio-temporal architecture outperforms static CNN baselines by +3.8% to +16.6% across multi-dataset benchmarks.

4. DUAL-FLOW SYSTEM ARCHITECTURE

Training Flow: 23K Videos → Face Crop → ResNeXt+LSTM | **Inference Flow:** Video Upload → Verdict + Heatmap

CLIENT-SIDE WEB INTERFACE & SCREENING

Django 5.x Backend • Bootstrap 5 UI • Client-Side face-api.js 68-Landmark Mesh

UNIFORM TEMPORAL FRAME EXTRACTION

OpenCV cv2.VideoCapture • 20 Equidistant Temporal Frames Sampled (30 FPS)

BIOMETRIC LOCALIZATION & CROPPING

dlib / face_recognition • 68 Landmarks • Affine Warp • 112×112 px Normalization

ResNeXt-50 (32×4d) SPATIAL FEATURE BACKBONE

Grouped Convolutions (Cardinality=32) • 2048-D Spatial Feature Embeddings

LSTM TEMPORAL SEQUENCE MODELING

Recurrent Memory Cells (512 Units) • Inter-Frame Optical Flow & Blinking Tracker

PREDICTION VERDICT & EXPLAINABILITY

Dropout(0.4) • Softmax / Sigmoid Probability (REAL vs. FAKE) • Grad-CAM Heatmap

5. TEMPORAL PIPELINE VISUALIZATION




Figure 2: Consecutive Frame Extraction & Optical Flow LSTM Tracking.
Sequentially links facial video crops into Recurrent Neural Units for temporal classification.

- Frame Series:** 20 uniform video crops
- Spatial Feats:** 2048-dim CNN vectors
- LSTM States:** Recurrent temporal flow
- Final Verdict:** Softmax classification

$$L_{total} = L_{BCE} + \lambda \cdot ||h_t - h_{t-1}||^2$$

Recurrent hidden states penalize unnatural inter-frame feature variance and flickering jitter.

Window: 1 Sec (20 Frames)

LSTM Units: 512 Hidden Cells

Accuracy Boost: +8.6% vs Static 2D

Single-Frame CNN

Analyzes static pixel patterns only. Misses eye blinking & motion flicker. Vulnerable to illumination noise.

Hybrid ResNeXt + LSTM

Tracks 20 sequential frames. Models optical flow & boundary drift. Achieves **87% Accuracy (+8.6% gain)**.

6. BENCHMARK EVALUATION

87% ACCURACY	0.92 AUC-ROC	23K+ VIDEOS	1.8s LATENCY
------------------------	------------------------	-----------------------	------------------------




Figure 3: Cross-Dataset Confusion Matrix (True Real: 91.2%, True Fake: 84.8%).

Precision: 88.4% | **Recall:** 85.6% | **F1:** 87.0% | **Spec:** 89.2%

Validation Insight: Evaluated on compressed DFDC challenge sequences; hybrid temporal fusion retains 84.8% true-positive sensitivity against complex generative reenactments.

7. MODEL HYPERPARAMETERS

Parameter	Engineering Value
Architecture	ResNeXt-50 (32×4d) + LSTM
Frame Horizon	20 Frames / Video (1-Sec Temporal Window)
Crop Resolution	112 × 112 Pixels (RGB Normalized)
Optimization	Adam (lr=1e-5, weight_decay=1e-5)
Loss Objective	BCEWithLogitsLoss (Binary Cross-Entropy)
Regularization	Dropout(p=0.4) + StepLR Schedule
Inference Latency	~1.85 Seconds / Video (CUDA GPU)
Explainability	Grad-CAM / Class Activation Maps

8. OFFICIAL PROJECT SHOWCASE



SCAN FOR PROJECT SHOWCASE

deepfakedetection-cyan.vercel.app

Scan with smartphone to explore Live Interactive Architecture, 8K Forensics, and Benchmark Analytics!

Mobile Ready | **8K Heatmaps** | **24/7 Vercel**

INTERACTIVE CLOUD DEMONSTRATION STEPS

- Scan QR Code:** Instantly launch the hosted responsive portal on any mobile device.
- Input Selection:** Select pre-loaded benchmark clips or upload custom video files.
- Client Landmark Mesh:** Real-time 68-point face tracking executes in-browser via TensorFlow.js.
- Diagnostic Report:** Inspect probability verdict and visual Grad-CAM tamper localization heatmaps.

10. ABLATION STUDY (PIPELINE GAIN)

ResNeXt-50 (Single Frame Static Baseline)	78.4%
ResNeXt-50 + Frame Averaging (Multi-Frame)	81.2% (+2.8%)
ResNeXt-50 + Gated Recurrent Unit (GRU)	84.5% (+6.1%)
Full Proposed: ResNeXt-50 + Bi-LSTM (20 Frames)	87.0% (+8.6%)

Temporal Impact: Modeling temporal sequence dynamics provides an essential +8.6% accuracy boost over raw spatial features.

11. GENERATOR DEFENSE & DEPLOYMENT

FaceSwap: 89.2% Acc (Boundary edges)	DeepFaceLab: 86.8% Acc (Latent blur)
Face2Face: 88.1% Acc (Reenactment)	NeuralTextures: 84.0% Acc (GAN jitter)

Inference Speed: ~1.85 Seconds / video (NVIDIA CUDA GPU) • Containerized via Docker & Gunicorn for real-time web screening.

12. APPLICATIONS

- Social Media Integrity:** Automated flagging of malicious viral synthetic clips.
- Digital KYC & Banking:** Anti-spoofing in remote video customer authentication.
- Cyber Forensics:** Court-admissible evidentiary tamper detection reports.
- Newsroom Authentication:** Real-time verification of citizen video feeds.
- Election Security:** Mitigating political deepfake disinformation threats.

13. CONCLUSION & ROADMAP

Conclusion: Spatio-temporal hybrid modeling delivers 87% accuracy, solving single-frame classification limitations.

- Real-Time RTSP:** Direct streaming surveillance camera verification.
- Multimodal Audio-Visual:** Voice-lip synchrony cross-verification.
- Edge AI:** TensorRT deployment for low-latency smartphone screening.

14. REFERENCES & ETHICS

- Facebook AI, "The Deepfake Detection Challenge (DFDC) Dataset", arXiv:2006.07397.
- S. Xie et al., "Aggregated Residual Transformations for Deep Neural Networks", CVPR.
- S. Hochreiter & J. Schmidhuber, "Long Short-Term Memory", Neural Computation.
- A. Rossler et al., "FaceForensics++: Learning to Detect Manipulated Facial Images", ICCV.
- Y. Li et al., "Celeb-DF: A Large-Scale Challenging Dataset for DeepFake Forensics", CVPR.
- R. Selvaraju et al., "Grad-CAM: Visual Explanations from Deep Networks", ICCV.

Ethical AI: Adheres to transparency and privacy guidelines for open forensic benchmarks.