// Day 2 of 10

Day 2

10 SQL Mistakes

Developers make these every day.
Don't be one of them.

→ Swipe through all 10

Shubham Bhati
linkedin.com/in/bhatishubham

Mistake #01

SELECT * Everywhere

Fetches unused columns, kills speed

```
// Bad
SELECT * FROM users;

// Good
SELECT id, name, email
FROM users;
```

💡 Always select only needed columns

Shubham Bhati
linkedin.com/in/bhatishubham

Mistake #02

No WHERE on UPDATE/DELETE

One typo = entire table wiped

```
// Bad
UPDATE users SET status = 'inactive';
-- Updates ALL rows!

// Good
UPDATE users SET status = 'inactive'
WHERE last_login < '2023-01-01';
```

💡 Always use WHERE on UPDATE/DELETE

Shubham Bhati
linkedin.com/in/bhatishubham

Mistake #03

No Indexes on Joins

Full table scan = very slow queries

```
// Bad
-- No index on foreign key
SELECT * FROM orders o
JOIN users u ON o.user_id = u.id

// Good
CREATE INDEX idx_orders_user
  ON orders(user_id);
-- Now joins are fast
```

💡 Index all foreign key columns

Shubham Bhati
linkedin.com/in/bhatishubham

Mistake #04

Using OR Instead of IN

OR chains are harder to optimize

```
// Bad
WHERE city='Delhi'
OR city='Mumbai'
OR city='Pune'

// Good
WHERE city IN
  ('Delhi', 'Mumbai', 'Pune')
```

💡 IN is cleaner and often faster

Shubham Bhati
linkedin.com/in/bhatishubham

Mistake #05

Skipping LIMIT

One query can crash your DB

```
// Bad
SELECT * FROM logs
ORDER BY created_at DESC;
-- Returns millions of rows!

// Good
SELECT * FROM logs
ORDER BY created_at DESC
LIMIT 100;
```

💡 Always LIMIT large result queries

Shubham Bhati
linkedin.com/in/bhatishubham

Mistake #06

Storing Passwords Plain Text

Worst security mistake ever

```
// Bad
INSERT INTO users
VALUES ('john@test.com', 'pass123');

// Good
-- Use bcrypt hash before storing
INSERT INTO users
VALUES ('john@test.com', '$2b$10$xyz ... ');
```

💡 Hash passwords before storing

Shubham Bhati
linkedin.com/in/bhatishubham

Mistake #07

Wrong NULL Comparisons

NULL = NULL is always false in SQL

```
// Bad
WHERE email = NULL;
-- This NEVER returns any rows!

// Good
WHERE email IS NULL;
WHERE email IS NOT NULL;
```

💡 Always use IS NULL / IS NOT NULL

Shubham Bhati
linkedin.com/in/bhatishubham

Mistake #08

No Transactions

Partial data = corrupted records

```
// Bad
INSERT INTO orders ...;
INSERT INTO payments ...; -- crash?
-- Orders saved, payment not!

// Good
BEGIN;
  INSERT INTO orders ...;
  INSERT INTO payments ...;
COMMIT;
```

💡 Wrap related ops in transactions

Shubham Bhati
linkedin.com/in/bhatishubham

Mistake #09

Ignoring EXPLAIN

You can't fix what you can't see

```
// Bad
-- Just running slow queries
-- and hoping for the best

// Good
EXPLAIN ANALYZE
SELECT * FROM orders
WHERE user_id = 42;
-- See actual query plan!
```

💡 EXPLAIN is your best debug tool

Shubham Bhati
linkedin.com/in/bhatishubham

Mistake #10

Wrong Data Types

Wastes storage and slows queries

```
// Bad
age VARCHAR(10),
price VARCHAR(20),
active VARCHAR(5)

// Good
age INT,
price DECIMAL(10,2),
active BOOLEAN,
created_at TIMESTAMP
```

💡 Right type = right performance

Shubham Bhati
linkedin.com/in/bhatishubham

```
done = true
```

Follow for more tips!

Like · Comment · Repost

Shubham Bhati
linkedin.com/in/bhatishubham