



BITS Pilani
Pilani | Dubai | Goa | Hyderabad

Control Systems

Sajeeth Kumar

Lecture 02 – Plant Modelling Part 1

Scope

1. What is a plant model, how to build it, assumptions and limitations
2. Foundations and Mathematical Theory – To help build Plant Models

Learning Outcomes

1. Underlying Assumptions
2. Linear and Time Invariance Systems - LTI Systems
3. Impulse Response
4. Convolution
5. How to Solve It? – Laplace Transforms
6. Some Examples


Module Contents



Introduction

Plant Models


- Recap Control System – Essentially understanding your system at the basic level
- Converting a physical system into a input – process – output model
- Physical System, represented as



Introduction

Plant Models

- This model is not all that useful because
 - We are interested in predicting what the output will be for a given input (OR)
 - We are interested in predicting what input will give the desired output



Plant Model


By Definition

- The plant model is a mathematical equation or relation that can be used to predict a physical system behavior
- Usually derived by analyzing basic behavior – Physics, Fundamental Mechanics, Thermodynamics...
- For the scope of analyzing and predicting behavior, it is assumed that
 - The physical system exhibits predictable behavior – No randomness / Chaos is observed
 - The physical system is a Linear and Time Invariance System (LTI)
 - Even if the system is not LTI, can it be assumed to be so? What are the consequences / Limitations in such cases?

Plant Model

Linear and Time Invariance Systems

- An LTI is a system which exhibits the following properties
 - Homogeneity - Linearity
 - Super Position - Linearity
 - Time Invariance
- Plant Modelling is possible IF and ONLY IF, physical system conforms to the LTI rules



Plant Model

Linearity

- Homogeneity



- Super Position




$$x_1(t) + x_2(t) = y_1(t) + y_2(t)$$

Plant Model

Time Invariance


- Time Invariance
- Systems behaves the same way irrespective of the time



Plant Model


Physical Systems

- LTI System is a theoretical concept
- No real world system will meet all 3
- IC Engine
 - 5mg of fuel produces 10 HP
 - 10mg of fuel produces 20 HP?? Not Always
- Electric Motor
 - Linearity is observed
 - Time Invariance? Wear & Tear? Time does affect the system
- Why do we consider LTI systems then?
- “Because you can solve it!!!”
- Step 1 - Approximate physical systems into LTI systems







Plant Model

LTI Systems



- When ever an input force acts on the system
- There is a corresponding output – Velocity Profile
- Suppose Input was continuous – Hammering Effect
- Output response will look like
- This is obtained by
 - Resolving the continuous input into discrete impulses
 - And plotting corresponding outputs
 - LTI – Homogeneity



Plant Model

LTI Systems

- Output is resolved by calculating
 - Weighted average of the output function at each time “t”
 - Weighting is given by shifting for time “t”
- Defined as “Convolution”
- Suppose input defined by a function $f(t)$, impulse response by $g(t)$, then
- Convolution Function $f(t) * g(t)$ produces the desired response function
- Mathematically, it is defined as the integral of the product of two functions after one is reversed and shifted
- Shifted – To compensate for varying inputs
- Reversed – To compute Delta alone at each interval

$$(f * g)(t) \triangleq \int_{-\infty}^{+\infty} f(\tau) * g(t - \tau) d\tau$$

Plant Model

LTI Systems

- Sounds Complicated?
- Well, it is sufficiently complicated.
- Alternate Method Exists
- $f (g * t) = L[f(t)] \times L[g(t)]$
- The convolution of two functions is equal to the product of Laplace transforms of the two functions
- Makes things a lot more easier!!
- Laplace transforms can be looked up from tables
- Or solved using Mathematical Tools





Thank You!

In our next session:
Plant Model Development