

JAYASWAL NECO INDUSTRIES L. MITED

(STEEL PLANT DIVISION)

SILTARA INDUSTRIAL GROWTH CENTRE, RAIPUR (C.G.)
Ph.: +91-7721-264241/263, Fax No.: +91-7721-264279/264240

TEST CERTIFICATE

No: Bit 6569

			TEST	CERTIF	ICATE	0	140:1	UN 6664			
CUSTOMER SPECIFICATION SPECIFI					COLOUR CODE			:/277) GA/RM/F10 :HR64A-1948 :26/05/2018 :83 PS/08 BL. : 13.020 :RED+GREEN+RED :AS ROLLED :5-6 MTR			
\$			***								
; XC ; XMn ; X	P %S %5	Si : %Cr :	ZNi ; ZMo	; %Pb ;	%Cu : %	Sn ¦ "XV	' : %T	i ; %	8 ; %	A1 : %	
CUST. MIN : 0.180; 0.700; -	- ! ! 0	1501 0 4001	0 4001 0 15	N1 1							
ACTUAL ; 0.200; 0.880; 0.											
	SPECI		ACTUAL								
VS UTS ELONGATIONS(5.65Sq.rt.A) 2 REDUCTION AREA % IMPACT VALUE HARDNESS(BHN/HRB/HRC) 3. METALLURGICAL PROPERTIES MICRO STRUCTURE GRAIN SIZE(ASTM E112/IS:4748) TOTAL DECARB (MM) SAEJ419 INCL RATINGS(ASTM E-45/IS:4163) SPECIFI MACRO ETCH TEST (ASTM E - 381) 4. D. I. VALUE (J406)	: : 6/BAS' : 1.0%OF C REQUIRMENT	THIN : THIC A-2.0/1.5 1.5 : 0.0	PEARLITE+ 6.5/7.5 0.35HM PA EK; THIN; THE B-2.0/3	FERRITE RTIAL HICK: THIN 1.5 : C-2 0.0 : 0.0	.0/1.0 ;	D-2.0	/1.0				
JOMINY REQUIREMENT HARDENABILITY IS:3848/A255-02	: JOMINY										
	; 4/16";	1 1	: :		;	;	1	!	1	-	
	: 36.00;	1 1	1 1	: .	;	;	1	:	į.	1	
GAS LEVEL(PPM) SPECIFIED MAX GAS LEVEL(PPM) ACHIEVED	: 02: : 02:	20.0 A	70-80 12: 71.0	H2: 2. H2: 1	0					3	
S. REMARKS	STEP DO	PARK/SPECTRAL DWN TEST TEST AR MPI & UST		:	OK OK NA						