Roy	ROYAL ENFIELD														Format No:- AP04:460:10R							
							M	IETAL	LURG	ICAL .	TEST	REPC	RT		-							
Repor	t No :	OT19	12047	,																		
				0 / 570548			Part Name				SPARG CLUTCH GEAR			Date:			2019-12-09					
Qty			05				Customer:			RE				Batch Code			E2M19189					
1) Rav	v Mat	terial:	SAE86	620										•								
2) Hea	at Tre	atmen	t:-Cas	e carb	urised	d, hard	lened	& tem	pered													
			Н	ARDNES	SS TRAVE	ER SE GR	APH					2.1 Hardness										
900 -													Location		Specification			Observation				
													FACE		60-64 HRC			60-61				
10												0.2 MM AT BORE			700 HV MIN. HV			750				
₹ 110											RCD			32~45 HRC			41					
100 mm m									PCD													
											PCD RCD Serion3	2.2 E	2.2 Effective Case Depth @ 550HV1									
	100											Location			Specification (mm)			Observation (mm)				
500													PCD			0.80~1.20			0.97			
400 0.1 0.2 0.3 0.4 0.5 0.6 0.7 0.6 0.9 1.0 1.1 1.2 1.3 1								14 15 16 17 16 19 20			7		UNGROUND BORE (Big ID)			-			0.85			
Distance in MM																						
										Thread Ha				rdness								
												NR						-				
2.3 Ha	ardne	ss trav	erse i	n Hv (Distan	ce fro	m surf	ace)														
in mm	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9	2.0		
PCD	795	767							561	546	516						T					
RCD																						
B/G ID	758	750					560	545	490													
2.4 Mi	crosti	ructure	e:				- !	-					<u> </u>	_								
Location Specification											Obs				servation							
CASE F.T.M.+R.A.<2'														T.M+	.M+R.A.2%							
CORE						LCM-	_CM+BAINITE						L.C.I	L.C.M+Bainite								
GBO-							<		-													
Dispos	sition	:-																				
Rema	rks :-																					
											Sumeet Sharma Ann					proved by :- Ravindra kale						