Web Site: www.sunflagsteel.com E-mail: admin@sunflagsteel.com Regd. Off.: (0712) 2524661 Works: (07184) 285551 CIN: L27100MH1984PLC034003

## SUNFLAG IRON & STEEL CO. LTD. Regd. Office: 33, Mount Road, Sadar, Nagpur - 440 001 Indf

Works: Bhandara Road, Bhandara - 441 905 (Maharashtra)
TEST CERTIFICATE



				7		
CUSTOMER: DHAR AUTOMOTIVES PRIVATE LIMITED	PROCESS ROUTE	TE	TC NO.	: 0023068 : 182703454	DATE 20	20.05.2018 20.05.2018
	MBF-EAF-LRF-VD-CCM-RM	CCM-RM	DELIVERY ORDER NO.	0.: 81065494	TRUCK NO. : MH.	MH26AD1873
CUSTOMER SPECIFICATION NO. NO. NO.	SECTION GRAIN COLOUR	GRADE UR CODE	BLT/BLM   SUPPLY   SIZE(mm)	CONDITION	LENGTH NO.OF (Mtrs)   PIECES	O.OF QTY
DHAR: 20MNCR5 R-00(J4/16=36-40)/01.01.2016   10167   20MNCR5   RCS	RCS-63 RED		160x160 AS ROLLED		5.250	17.360
	CHEMICAL CO	EMICAL COMPOSITION				
%C   %Mn   %P   %S   %Si   %Cr   %Cu   %Ni   %Mo	%V %A1 %Pb	% T1:	%Sn %W %As	s %Ca %Sb	%Co %NP	02   N2   H2 ppm   ppm   ppm
SP-MIN 0.17 1.10 0.15 1.00	0.015	!!	1 - F	1 1	1 1	20   90   2.0
7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7				-		
ACTUAL  0.18  1.21  0.0160 0.0150 0.2200 1.0900 0.0180 0.0200 0.0100	0 0.0040 0.0320 0.0002	2 0.0026 0.0002	0.0009 - 0.0063	63 0.0012 0.0009	- 0.0029	16   81   1.10
MECHANICAL PROPERTIES			JOMINY VALUE	(INCH - HRC)		
As Rolled / H.T. IMPACT HAI	HARDNESS DI CE					
UTS SEL SRA (IZOD/CHARPY)	(BHN)   VALUE   VALUE		J1/16 J2/16 J3/16 J4/16 J5/16 J6/16 J7/16 J8/16 J9/16 J10/16 J12/16 J14/16 J16/16	14 37/14 38/14 39/1	d J10/16 J12/16	J14/16 J16/16
SPEC-MIN 55.00  80.00  8.00  -	1	<u>-</u>	-  36.0	· · · · · · · · · · · · · · · · · · ·		1 <u>1                                  </u>
-MAX  -   110.00  -  -  -  240		1	40.0	1 _	1 <u>1</u>	N
ACTUAL   79.36   92.36   11.90   47.90   -   188	888	44.0 43.0	39.0 37.0 34.0 31.0	0   30.0   28.0   27.0	26.0 25.0	23.0   22.0
	METALLURGICAL	CAL PROPERTIES	Si			
	-	JISG0555	3555	DECARBURIZATON (MM)	N(MM)   MACRO ETCH	CH REDUCTION
AT AH BT BH CT CH DT DH - B- 112)	QUALITY HARDNESS ()	dA + dB	dB+dC = D	Full Partial	Total   ASTM-E-381	
SPEC-MIN 6	.+			, , , , , , , , , , , , , , , , , , ,		8:1
-MAX 2.00  1.50  2.00  1.50  2.00 1.50  8  -			1	- 0.50	0.50 C2R2S2	1
ACTUAL   2.00   0.50   0.50   -   0.00    1.50  -   7/7.5   -			00000	- 0.36	0.36 C2R2S1	6.45
REMARKS :100% SPARK/SPECTRAL, OK. STEP DOWN TEST: OK. U.S.T. (100%) :OK.M. P.T	K.M.P.T. (100%):OK.	We cer	certify that the material	ial described above	ove conforms to	the specs.
			For Sunflag Ir	Iron & Steel Co. Ltd	, d	