

IMITED G.T.Road, Miller Office



13:34:23

20/01/2018

Date

7839

T.C.NO.

LTD.U-II, B-XXIX, 2254

FORGINGS

HAPPY

M/S

-: Original :-

STEELS Ganj, Ludhiana. 0161-3006250 141010. (INDIA) SPECIAL TIFICATE S CARBON ALLOYS 0161-3006200 Fax Focal Point, LUDHIANA CER TEST OF MANUFACTURER'S no. Registered Phone Works

E 4	WAL ROADJUGIANA.LUDHIANA Invoice No. 20411 Truck No. PB10DM-9097	
	SIZE HEAT NO. MANUFACIUKING KOUIE COLOUR CODE SUFFLI CONDN. QII. NO. OF (MT) PCS.	
EN 353	90 DIA 6044 E.A.F.+L.F.+V.D.+CCM+EMS BLUE+WHITE E AS ROLLED 15.640 51	
	-: CHEMICAL COMPOSITION IN PERCENTAGE :-	William I
	C Mn S P Si Ni Cr Mo V Al Cu Sn Ti B Ca	
	0.1400 0.5000 0.0200 0.1000 1.0000 0.7500 0.0800 0.0200	
	Max 0.2000 1.0000 0.0350 0.0500 0.2500 1.5000 1.2500 0.1500 0.0400 0.0400 0.2500 0.0060 0.0004 0.0020	
	Actual 0.1850 0.9700 0.0260 0.0190 0.2400 1.0500 1.2100 0.1200 0.0058 0.0235 0.1080 0.0110 0.0033 0.0004 0.0007	

	Gas Content	(mdd)		1 14		0.7	10	. 902	MIX UP TEST
	Gas			00	1	CIV	NZ INZ	Н2	
		7) 			B+F+P	ULTRASONIC TEST
	Aust.Grain	ASTM No.	(711_0)	Decarh	CCATO.	(MM)	M: Oxo	Structure	MACRO UI
	e.		n	-	0	0.		0.0	
	E-45	D	E	7	0	0.0		1.0	(80)
- Aller	r/ASTM		100	u	0	0.0		0.0	/IS-16
	INCLUSION RATING IS : 4163/JK CHART/ASTM E-45A	ວ	E	T		0.0		0.5 0.0 0.0 0.0 1.0 0.0	MECHANICAL PROPERTIES (ASTM A-370/IS-1608) TEST CONDITION (N / H & T)
	4163/0			ц	0	0.0		0.0	S (ASTN ON (N
	: SI	В	E	7	0	0.7		0.5	PERTIE
	RATING		:	ц		7.0		0.5	AL PRO
	USION	A	E	H		7.5		1.5	CHANIC
	INCL					STD	MAX	ACTUAL 1.5	ME

..

METALLURGICAL RESULTS

SPARK TEST	100% DONE OK				
	100 % DONE OK				
BETTER THAN	C2, R2, S2 MAX	LEVEL AS PER	PLATE ISt OF	DOI II II DOI	
Hardness	B.H.N./Rb			248-262	
Impact			1		
RA%			Ĭ	ı	
EL%			1		
Y.S. EL%				1	
U.T.S.			j.		
			Reqd.	Actual	

3848 .. IS PER AS (HRC) HARDENABILITY

REDUCTION RATIO=9.1,100% MOBILE SPECTRO DONE OK (X-RAYS) 8W: 0.0060,8CO: 0.012,8NB: 0.0059 Remarks

BILLET SIZE-240X240 MM, SDT OK, SURFACE SATISFACTORY MATERIAL CONFIRMS TO SPEC. BGL TS.01, REV. NO.: 11

> CONTAMINATION RADIOACTIVE FOR TESTED Note

PREPARED BY

