

USHA MARTIN LIMITED

(USHA ALLOYS & STEEL DIVISION)

P.O. GAMHARIA, DIST.-SARAIKELA KHARASWAN, JAMSHEDPUR--832108 JHARKHÁND. PHONE 0657-3982200

QUALITY ASSURANCE TEST CERTIFICATE

Customer/SP	RAMKRISHNA FORG	INGS LTD		3		PO No/ Date	Dec	:17/	
TC No	40000004407	Tax nvoid	e No	9000065097	Quantity	27.230 MT	Roll	ing Input	300 X 360 mm
Batch No.	C4212601								
Heat No	C42126	Grade	SCM42	ОН		Product	ROUND BA	R FINISHE	D
Spec code	RF/14/D-401/99A		Date	19-05-2016	Issue No: 0	Rev: 03	Condition	HOT RO	LLED
Prodt Dt	06-JAN-2018	Nom Size		95.00 mm		Colour Code	BROWN		

						CHEMIC	AL COMP	OSITION					107	N. S.
Element	%C	%Mn	%Si	%Р	%S	%Cr	%Ni	%Cu	%Мо	%AI	%Pb	%V	%Ті	%Ca
Min.	0.18	0.60	0.15	-		0.90	0.	1	0.150	-	1		-	
Max.	0.23	0.85	0.35	0.030	0.030	1.20	-	1	0.300	0.040	-	-	-	
Actual	0.21	0.83	0.24	0.017	0.006	1.18		1292.6	0.187	0.027	-	-	-	

			CARBON	GAS LEVEL							
Element	%Sn	%As	%Sb	%Nb	%В	%Те	%W	EQV	O2 PPM	H2 PPM	N2 PPM
Min.	-	-	- /								-
Max.	-	-	- 4			<u>-</u>		-	20	2.0	90
Actual	1-		-	-	-		7	-	15	1.6	70

T-		MECHAN	ICAL PROPERT	IES						×			
Require ment	Hardness BHN	Impact Strength (IZOD/CHARPY) (Joule)		UTS (Kg/mm2)	%E	%RA			JOMIN	Y HARDENAI	BILITY (HF	RC)	
Min.					-			J-5 MM	J-9 MM	J-13 MM			
Max.	250	-	-	-/-	- /		Min.	41.0	33.0	29.0			- 2
Act.Min.	184		-	-	- 4	-35	Max	47.0	38.0	35.0	-		10000000000000000000000000000000000000
Act.Max.	190	-			- /		Act.	46.0	37.0	33.0	-	-	

		METALLUI	RGICAL PROPE	RTIES		INCLUSION RATING AS PER ASTM E-45								
Specific	Depth of	Macro Etch	Max. Depth of	of Grain Size Spherodised			Α	В		С		D		
ation	Decarb (mm)	(ASTM E381)	Surface Defect(mm)	(ASTM E112)	(%)	T	Н	1	Н	Т	H	Т	Н	
Min	-	- 1		6					-	-	-	- 1		
Max	0.50	C2R2S2	-	8		2.5	1.0	2.0	0.5	2.0	0.5	2.0	0.5	
Actual	0.24	C2R1S2	-	7		1.0	0.5	1.0	0.0	0.0	0.0	1.0	0.0	
Micro stru	cture	Ferrite Pearlite	Bainite							,		*	70.2	

Spark & Spectral Test/PMI	100%OK	MPI	100 % OK	Blue Fracture	NA		Heat treatment of mple.
Surface Inspection: (as per Spec.)	100% OK	Step Turn	No Streak	Cold Upset	NA	Requirement	
Ultrasonic Test:(as per Spec.)	100 % Satisfactory					Actual in BHN	37 4

REDUCTION RATIO 15.24:1	PROCESS ROUTE	BF>EAF>LRF>VD>CCP>BM
Remarks: SIZE TOLERANCE (+0.90) (-0.0), OUT OF ROUNN	IESS0.50	. LVG
Length of Bar :- 3.0 TO 6.0 MTRS.	Test certificate meets TDC	Route
	Results based on sample	USHA MARTHALIMITED
MATERIAL IS FREE FROM RADIOACTIVE ELEMENTS	testing	(USHA ALLOYS & STEELS DIVISION)
	: 2 A, Shakespeare Sarani, Kolkata: ID: uasdga_hod@ushamartin.co.in	700 016.