

VE COMMERCIAL VEHICLES LIMITED. (UNIT:EICHER ENGINEERING COMPONENTS;DEWAS)UNIT:-II																																																																									
<div>CONTROL PLAN NO : 2402 / 100</div> <div>EFF DATE 16.09.2014 EFF DATE 03.01.15 EFF DATE 08.01.16 PROTOTYPE ✓ PRELAUNCH ✓ PRODN ✓ O.E. ✓ EXPORT PART NO. ED 2402 (574242/c) PART NAME SHAFT, DRIVE OPN. NO. 100 CUSTOMER ROYAL ENFIELD OPERATION * HEAT - TREATMENT CELL [OPTIONAL] M/C. S.Q.F. M / C NO. [OPTIONAL] <table border="1"><thead><tr><th>FIXTURE</th><th>FIX. NO.</th><th>TOOL</th><th>NO.</th></tr></thead><tbody><tr><td> </td><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td><td> </td></tr></tbody></table></div>							FIXTURE	FIX. NO.	TOOL	NO.																																																															
FIXTURE	FIX. NO.	TOOL	NO.																																																																						
<div>MATERIAL :- 16MnCr5 COMP. WT :- 0.59 Kg.</div> <div>* HEAT-TREATMENT-: MARKING ; PRE-WASHING ; PRE-HEATING ; CARBURISING ; HARDENING ; POST-WASHING ; TEMPERING ; SHOT BLASTING ;</div> <div>END VIEW "P" FOR REFERENCE ONLY VIEW "P"</div> <div>MARK CHARGE NO. HERE 6 NO. ST. SPLINE APPLY STOP OFF PASTE HERE (ON THREAD AREA) X X X X X X X X X X 15 NOS. INV. SPLINE "X"</div> <div>NOTE: 1. APPLY STOP OFF PASTE / ANTICARB PASTE IN THE AREA SHOWN "X" (19.5 ±1 mm)</div> <table border="1"><thead><tr><th>SURFACE HARDNESS</th><th>CORE HARDNESS</th><th>EFFECTIVE CASE DEPTH</th><th colspan="2">MICROSTRUCTURE</th><th>THREAD AREA HARDNESS</th></tr></thead><tbody><tr><td>ALL AREA</td><td>AT SPLINE RCD (SPLINE TOOTH CENTER)</td><td>AT SPLINE RCD (SPLINE TOOTH CENTER)</td><td>AT CASE</td><td>AT CORE</td><td>AT ROOT 0.2 mm DEPTH (THREAD ROOT DEPTH)</td></tr><tr><td>80-83 HRA</td><td>350-450 HV1</td><td>0.6-0.9 mm CUT OFF 513 HV1</td><td>FINE TEMPERED MARTENSITE + RA <10% AND FREE FROM CARBIDES GBO<20 micron</td><td>LOW CARBON MARTENSITE + BAINITE</td><td>300-450 HV1 (AFTER THREADING)</td></tr></tbody></table> <div>NOTE:- 1) GROUND SURFACE :- HARDNESS AT 0.1MM SHALL BE 650 HV1 MIN.</div>							SURFACE HARDNESS	CORE HARDNESS	EFFECTIVE CASE DEPTH	MICROSTRUCTURE		THREAD AREA HARDNESS	ALL AREA	AT SPLINE RCD (SPLINE TOOTH CENTER)	AT SPLINE RCD (SPLINE TOOTH CENTER)	AT CASE	AT CORE	AT ROOT 0.2 mm DEPTH (THREAD ROOT DEPTH)	80-83 HRA	350-450 HV1	0.6-0.9 mm CUT OFF 513 HV1	FINE TEMPERED MARTENSITE + RA <10% AND FREE FROM CARBIDES GBO<20 micron	LOW CARBON MARTENSITE + BAINITE	300-450 HV1 (AFTER THREADING)																																																	
SURFACE HARDNESS	CORE HARDNESS	EFFECTIVE CASE DEPTH	MICROSTRUCTURE		THREAD AREA HARDNESS																																																																				
ALL AREA	AT SPLINE RCD (SPLINE TOOTH CENTER)	AT SPLINE RCD (SPLINE TOOTH CENTER)	AT CASE	AT CORE	AT ROOT 0.2 mm DEPTH (THREAD ROOT DEPTH)																																																																				
80-83 HRA	350-450 HV1	0.6-0.9 mm CUT OFF 513 HV1	FINE TEMPERED MARTENSITE + RA <10% AND FREE FROM CARBIDES GBO<20 micron	LOW CARBON MARTENSITE + BAINITE	300-450 HV1 (AFTER THREADING)																																																																				
<table border="1"><thead><tr><th rowspan="2">SR. NO.</th><th colspan="2">CHARACTERISTICS</th><th rowspan="2">SPL CHAR CLASS</th><th rowspan="2">PRODUCT SPECIFICATIONS</th><th colspan="2">EVALUATION MEASUREMENT TECHNIQUE</th><th colspan="2">SAMPLING</th><th rowspan="2">CONTROL METHOD</th><th rowspan="2">CORRECTIVE ACTION / REACTION PLAN</th></tr><tr><th>PRODUCT</th><th>PROCESS</th><th>INSTRUMENT</th><th>NO.</th><th>SIZE</th><th>FREQ</th></tr></thead><tbody><tr><td>1.</td><td>EFF. CASE DEPTH</td><td></td><td rowspan="3">⊕</td><td rowspan="5">REFER ABOVE TABLE</td><td>MICRO-HARDNESS TESTER</td><td>---</td><td>1 PC</td><td>PER CHARGE</td><td rowspan="5">TESTING</td><td rowspan="5">CHECK FURNACE SETTING DATA & CONFIRM FOR CORRECTNESS</td></tr><tr><td>2.</td><td>SURFACE HARDNESS</td><td></td><td>HARDNESS TESTER</td><td>---</td><td>1 PC</td><td>PER CHARGE</td></tr><tr><td>3.</td><td>CORE HARDNESS</td><td></td><td>HARDNESS TESTER</td><td>---</td><td>1 PC</td><td>PER CHARGE</td></tr><tr><td>4.</td><td>MICROSTRUCTURE</td><td></td><td>MICROSCOPE</td><td>---</td><td>1 PC</td><td>PER CHARGE</td></tr><tr><td>5.</td><td>HARDNESS ON THREAD AREA "X "</td><td></td><td>HARDNESS TESTER</td><td>---</td><td>1 PC</td><td>PER CHARGE</td></tr><tr><td>6.</td><td>SHOT BLAST</td><td></td><td></td><td>FREE FROM RUST & SCALE</td><td>VISUAL</td><td>---</td><td>100%</td><td></td><td></td><td></td></tr></tbody></table>							SR. NO.	CHARACTERISTICS		SPL CHAR CLASS	PRODUCT SPECIFICATIONS	EVALUATION MEASUREMENT TECHNIQUE		SAMPLING		CONTROL METHOD	CORRECTIVE ACTION / REACTION PLAN	PRODUCT	PROCESS	INSTRUMENT	NO.	SIZE	FREQ	1.	EFF. CASE DEPTH		⊕	REFER ABOVE TABLE	MICRO-HARDNESS TESTER	---	1 PC	PER CHARGE	TESTING	CHECK FURNACE SETTING DATA & CONFIRM FOR CORRECTNESS	2.	SURFACE HARDNESS		HARDNESS TESTER	---	1 PC	PER CHARGE	3.	CORE HARDNESS		HARDNESS TESTER	---	1 PC	PER CHARGE	4.	MICROSTRUCTURE		MICROSCOPE	---	1 PC	PER CHARGE	5.	HARDNESS ON THREAD AREA "X "		HARDNESS TESTER	---	1 PC	PER CHARGE	6.	SHOT BLAST			FREE FROM RUST & SCALE	VISUAL	---	100%			
SR. NO.	CHARACTERISTICS		SPL CHAR CLASS	PRODUCT SPECIFICATIONS	EVALUATION MEASUREMENT TECHNIQUE			SAMPLING				CONTROL METHOD	CORRECTIVE ACTION / REACTION PLAN																																																												
	PRODUCT	PROCESS			INSTRUMENT	NO.	SIZE	FREQ																																																																	
1.	EFF. CASE DEPTH		⊕	REFER ABOVE TABLE	MICRO-HARDNESS TESTER	---	1 PC	PER CHARGE	TESTING	CHECK FURNACE SETTING DATA & CONFIRM FOR CORRECTNESS																																																															
2.	SURFACE HARDNESS				HARDNESS TESTER	---	1 PC	PER CHARGE																																																																	
3.	CORE HARDNESS				HARDNESS TESTER	---	1 PC	PER CHARGE																																																																	
4.	MICROSTRUCTURE		MICROSCOPE		---	1 PC	PER CHARGE																																																																		
5.	HARDNESS ON THREAD AREA "X "		HARDNESS TESTER		---	1 PC	PER CHARGE																																																																		
6.	SHOT BLAST			FREE FROM RUST & SCALE	VISUAL	---	100%																																																																		
<div>DRN BY MUKESH CHKD BY R.PATHAK APRD BY B.LEVA PAGE 01 / 02</div>																																																																									
UNSPECIFIED TOLERANCES AS PER IS : 2102 (PART-1) : 1993 MEDIUM CLASS. ALL DIMENSIONS ARE IN MILLIMETERS. DO NOT SCALE, IF IN DOUBT, PLEASE ASK. BREAK SHARP CORNERS.																																																																									