

**NACCO Materials Handling Group, Inc.****ENGINEERING SPECIFICATION**

<b>Title:</b> CONTINUOUS CAST AXLE SHAFT STEEL REQUIREMENTS	<b>Document Control Number:</b> HC-122
<b>Page</b> 1 of 2 <b>Document Author:</b> Bill Waller	<b>Effective Date:</b> 15-Jun-2007 <b>Rev. No.</b> 2007-06

ANY ACCESS TO THIS DOCUMENT OUTSIDE THE PRIMARY ELECTRONIC SOURCE IS UNCONTROLLED, UNLESS STAMPED, INITIALED AND DATED. THIS DOCUMENT CONTAINS CONFIDENTIAL INFORMATION THAT IS THE PROPERTY OF NACCO MATERIALS HANDLING GROUP, INC. BY ACCEPTING THIS INFORMATION THE BORROWER AGREES THAT IT WILL NOT BE USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT IS LOANED.

**1.0 Objective**

- 1.1 To define the metallurgical requirements of continuous cast steel to be used for deep case, induction hardened axle shafts.

**2.0 Scope**

- 2.1 This specification is for medium carbon steels used in axle shaft production.

**3.0 Citing / Cited Documents**3.1 Cited

SAE J406, Methods of Determining Hardenability of Steels

EN 10083-1, Quenched and Tempered Steels - Part 1 : Technical Delivery Conditions for Special Steels

UNI 3244 – Microscopic Examination of Ferrous Materials. Rating of Non-Metallic Inclusions in Steels with Reference Pictures

UNI 8449 (1-3), Microscopic Examination of Ferrous Materials. Classification of Banded Structure in Case Hardening Steels

**4.0 Definitions**

*SAE* - Society Automotive Engineering

*EN* – European Standard

*UNI* – Italian Standard

**5.0 General**

- 5.1 This specification defines the requirements to generate cleanliness and grain refinement that bring benefits to axle shaft fatigue strength. Use of this steel in the quenched and tempered condition must be approved through endurance testing of axle shaft products under CBDC guidelines.

---

NACCO Materials Handling Group (NMHG) Standards are intended for use by NMHG, its divisions and subsidiaries. Suppliers who rely on them in furnishing products to or for the benefit of the NMHG must determine that they are in possession of the latest version. Distribution of the standards to parties other than NMHG Suppliers, whether with or without charge, are for information only and NMHG disclaims all responsibility for results attributable to the application of or compliance with such standards. NMHG makes no representation, express or implied, that conformity ensures compliance with applicable law or other rules or regulations. Further, those who are in receipt of and elect to use the standards, agree to assume the responsibility for compliance with patents, as well as potential patent infringement.

**NACCO Materials Handling Group, Inc.****ENGINEERING SPECIFICATION**

<b>Title:</b> CONTINUOUS CAST AXLE SHAFT STEEL REQUIREMENTS	<b>Document Control Number:</b> HC-122
<b>Page</b> 2 of 2 <b>Document Author:</b> Bill Waller	<b>Effective Date:</b> 15-Jun-2007 <b>Rev. No.</b> 2007-06

ANY ACCESS TO THIS DOCUMENT OUTSIDE THE PRIMARY ELECTRONIC SOURCE IS UNCONTROLLED, UNLESS STAMPED, INITIALED AND DATED. THIS DOCUMENT CONTAINS CONFIDENTIAL INFORMATION THAT IS THE PROPERTY OF NACCO MATERIALS HANDLING GROUP, INC. BY ACCEPTING THIS INFORMATION THE BORROWER AGREES THAT IT WILL NOT BE USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT IS LOANED.

**6.0 Description****6.1 EN 10083-1: 41Cr4 CHEMICAL COMPOSITION:**

Element	Min.	Max.
Carbon	.38	.45
Manganese	.60	.90
Silicon		.40
Phosphorous		.035
Sulfur	.020	.045
Chromium	.90	1.20

**6.2 HARDENABILITY:**

Hardenability will be defined by the SAE Hardenability Predictor, J406. A calculated  $D_I$  value of 2.5 to 3.1 inches is required. Carbon range must be maintained, but all other elements are secondary to  $D_I$  attainment.

**6.3 INCLUSION RATIO:**

Inclusion rating per NORM UNI 3244 Method K:  $K_4 < 30(0)$

**6.4 BANDING:**

Banding rating per UNI 8449: 1-3 (narrow band)

**6.5 STEEL MAKING PRACTICE:**

If continuous cast steel is used, a minimum reduction ratio of 7:1 must be used.

**6.6 MATERIAL QUALITY:**

The material should be of "axle shaft quality" (ASQ) hot rolled bar. The controlling characteristics of this bar quality must be defined by the producer.

**6.7 FORGING HEAT TREATMENT:**

Forgings produced under this specification will be quenched and tempered to a hardness of 266-311 BHN.

**6.8 CERTIFICATION:**

The forge shop will supply a copy of the steel mill certificate for all heats used to produce forgings.