Manu: Shubha D Madival
BDA-LAB . USN: 18M17(S100
Dela: voltalana
(2)
use Db2
use Db2  1) db. en ate. Collection ("(astomes");
2). db. Customer insert ([{ custid:1, techal:1500, Acctype:"A"}},
Scustid: 2 leabel: 2000 de 1 1200, ACC TYPE A 38,
{ custid: 2 , Acchal: 2000 , Acc-type: "2"},
3 custid: 3 Acchal: 5000 Acc type: "2" }
[ custid: 4, Achal: 5500, Acc-type: "Z"}
custid: 53, Acchal: 1300, Acchape: "A" ?'
¿ custid: 4, Acchal: 1000, Acc type: "A" }
3) db. Customer. find ({ Accbal: { \$qt:1200}, Acc. type: 2"})
4) db. (ustomes: aggregate ( & s group: \{ -id: "s cust_id", min_bal: \{ \pmin: " \\$ Acc_bal" \},
max bal : { \$ max : " \$ Acc_bat"}
}
37).
2
5) mongo export -db 3 Db2 collection Customer
type = csv fieldfile: git2. txtout g:\di.csv
6) db. (ustomer. drop();
7) mongoimport -db Db2collection Customers
type = csv header line file g:\d2.csv
The same of the sa
- Julite