```
package ass4Semaphore;
import java.util.concurrent.Semaphore;
public class ass4Semaphore {
//package com.mkyong;
 // max 4 people
 static Semaphore semaphore = new Semaphore(4);
 static class MyATMThread extends Thread {
 String name = "";
 MyATMThread(String name) {
  this.name = name;
 public void run() {
  try {
   System.out.println(name + ": acquiring lock...");
   System.out.println(name + " : available Semaphore permits now: "
     + semaphore.availablePermits());
   semaphore.acquire();
   System.out.println(name + " : got the permit!");
   try {
   for (int i = 1; i <= 5; i++) {
    System.out.println(name + ": is performing operation " + i
     + ", available Semaphore permits: "
     + semaphore.availablePermits());
    // sleep 1 second
    Thread.sleep(1000);
   }
   } finally {
   // calling release() after a successful acquire()
   System.out.println(name + " : releasing lock...");
   semaphore.release();
   System.out.println(name + " : available Semaphore permits now: "
     + semaphore.availablePermits());
   }
  } catch (InterruptedException e) {
   e.printStackTrace();
```

```
}
}
}
public static void main(String[] args) {
System.out.println("Total available Semaphore permits: "
 + semaphore.availablePermits());
MyATMThread t1 = new MyATMThread("A");
t1.start();
MyATMThread t2 = new MyATMThread("B");
t2.start();
MyATMThread t3 = new MyATMThread("C");
t3.start();
MyATMThread t4 = new MyATMThread("D");
t4.start();
MyATMThread t5 = new MyATMThread("E");
t5.start();
MyATMThread t6 = new MyATMThread("F");
t6.start();
```