

Agentforce Conversation Client (ACC) API – Learning Notes

Overview

The Agentforce Conversation Client (ACC) API is a Salesforce Lightning Web Component module (`lightning/accApi`) that enables custom LWCs to communicate with the native Agentforce side panel.

Think of ACC API as a bridge between your custom Lightning component and Agentforce.

Without ACC API:

User → Opens Agentforce → Types Message → Agent Responds

With ACC API:

LWC → Opens Agentforce → Sends Message Automatically → Agent Responds

This allows developers to create more intelligent and automated user experiences.

Why ACC API Exists

Many business processes require Agentforce to be launched automatically from a custom interface.

Examples:

- Generate a birthday wish for a Contact.
- Summarize an Account.
- Analyze an Opportunity.
- Investigate a Case.
- Provide customer insights.

Instead of asking users to manually open Agentforce and type prompts, an LWC can do it automatically.

Prerequisites

Before using ACC API:

- Salesforce Lightning Experience Desktop

- Agentforce enabled in the org
- API Version 59.0 or later
- Native Agentforce side panel available

ACC API is not supported in Tableau, SentOS, or non-Lightning interfaces.

Importing ACC API

```
import { open, close, execute } from 'lightning/accApi';
```

These methods allow communication with the Agentforce panel.

Core Methods

1. open()

```
await open(botId);
```

Purpose:

Open the Agentforce panel.

If a Bot ID is provided, Salesforce opens that specific agent.

Example:

```
await open('0XxABC123');
```

2. close()

```
await close();
```

Purpose:

Close the Agentforce panel.

Example:

```
await close();
```

3. execute()

```
await execute(  
    'Summarize this Account',
```

```
    botId  
);
```

Purpose:

Send a natural language message to the agent as if the user typed it manually.

Example:

```
await execute(  
    'Generate a birthday wish for Contact Id 003XXXXXXXXXXXX',  
    botId  
);
```

Understanding Bot ID

Every Agentforce agent has a unique Bot ID.

Example:

0XxABC123XYZ

The Bot ID can be found in the Agent Builder URL.

It helps Salesforce identify which agent should receive the request.

How ACC API Works

Example Flow:

User clicks “Wish Birthday” ↓ LWC calls open(botId) ↓ Agentforce panel opens ↓ LWC calls execute(...) ↓ Agent receives message ↓ Agent invokes actions/tools ↓ Agent generates response

The LWC does not directly invoke Agent actions.

Instead, it sends a natural language request and Agentforce decides which action to use.

Important Limitation

ACC API can:

✓ Open the panel

✓ Close the panel

✓ Send messages

ACC API cannot:

✗ Directly execute Agent Actions

✗ Read conversation history

✗ Retrieve Agent responses

✗ Access action outputs

The execute() method only sends a message to the agent.

Birthday Wisher Example

Business Flow:

Birthday Contacts LWC ↓ User clicks “Wish Birthday” ↓ open(botId) ↓ execute(“Generate birthday wish for Contact Id 003XXXX”) ↓ Agent invokes GetContactDetails ↓ Prompt Template runs ↓ Birthday message is generated

No manual user input is required.

Key Takeaway

ACC API is not an Agentforce replacement.

It is a communication layer that allows a Lightning Web Component to control the Agentforce side panel by opening it, closing it, and sending natural language requests to an agent.