Python String Methods Master Quiz

Comprehensive assessment covering 35 advanced string manipulation methods and behaviors.

Candidate Name: [Your Name]	**Date:** [Date]	**Total Questions:** 35

Part 1: Case Manipulation & Alignment (Q1–Q6)

1. What is the primary difference in behavior between `str.lower()` and `str.casefold()`?

A) `lower()` removes non-ASCII characters.

B) `casefold()` performs a more aggressive caseless matching for non-ASCII characters.

C) `lower()` raises an error on symbols.

D) They are identical aliases.

2. What does `"hello world".capitalize()` return?

A) `"Hello World"`

B) `"Hello world"`

C) `"HELLO WORLD"`

D) `"hello world"`

3. What is the exact behavior of `s.center(width, fillchar)` when `width <= len(s)`?

A) It raises a `ValueError`.

B) It truncates the string to `width`.

C) It returns a copy of the original string `s` unchanged.

D) It pads the edges with spaces.

4. How many times does `"ana"` appear in `"banana"` via `"banana".count("ana")`?

A) 1

B) 2

C) 0

D) 3

5. What is the output of `"resume".encode(encoding="utf-8")`?

A) `"resume"`

B) `b'r\xc3\xa9sum\xc3\xa9'` (if accented) / **C) `b'resume'`**

D) `str` bytes object

D) `TypeError`

6. Which method checks if a string ends with a specific suffix, allowing optional start/end boundaries?

A) `checkend()`

B) `endswith()`

C) `has_suffix()`

D) `match_end()`

Part 2: Searching, Padding & Formatting (Q7–Q12)

7. What does `"a\tb".expandtabs(tabsize=4)` produce?

A) `"a b"` (3 spaces)

B) `"a b"` (computed spacing based on 4-column tab stops)

C) `"a\tb"`

D) `ValueError`

8. What is the return value of `"hello".find("l", 3)`?

A) `2`

B) `-1`

C) `3`

D) `4`

9. How does `index()` differ from `find()` when a target substring is completely absent?

A) `find()` raises an error; `index()` returns `-1`.

B) `index()` raises a `ValueError`, whereas `find()` returns `-1`.

C) They behave identically.

D) `index()` returns `None`.

10. What is the output of `"User{0}Score{1}".format(10, 95)`?

A) `"User{0}Score{1}"`

B) `"User10Score95"`

C) `"User 10 Score 95"`

D) `KeyError`

11. Which method should be used to format a dictionary mapping keys to values directly into string placeholders?

A) `format_dict()`

B) `format_map()`

C) `map_format()`

D) `dict.format()`

12. What does `"Python3.10".isalnum()` return?

A) `True` (periods are treated as alphanumeric characters)

B) `False` (because periods `.` are neither letters nor numbers)

C) `None`

D) `ValueError`

Part 3: Type Checks & Identifiers (Q13–Q18)

13. Which method returns `True` if all characters in the string are alphabetic and the string is non-empty?

A) `isalnum()`
B) `isalpha()`
C) `isascii()`
D) `istext()`

14. What does `"\u00b2".isdecimal()` evaluate to? (Note: `\u00b2` is superscript ²)

A) `True`
B) `False` (superscript digits are numeric/digit but not decimal base-10 digits)
C) `None`
D) `SyntaxError`

15. Which of the following strings will cause `isidentifier()` to return `True`?

A) `"123var"`
B) `"my-variable"`
C) `"class"` (reserved keywords are valid Python identifiers)
D) `"var name"`

16. What does `"\u2165".isnumeric()` return for Roman numeral VI (`\u2165`)?

A) `True` (numeric method recognizes fractions, Roman numerals, and digits)
B) `False`
C) `None`
D) Raises `UnicodeError`

17. What is the result of `" ".isspace()`?

A) `False`
B) `True`
C) `None`
D) `""`

18. Which condition must be met for `istitle()` to return `True`?

A) First letter of string is uppercase.
B) Uppercase characters must follow uncased characters, and lowercase characters must cased-follow uppercase.
C) Every word must be capitalized.
D) No special characters allowed.

Part 4: Joining, Partitioning & Replacing (Q19–Q24)

19. What does `"-".join(["a", "b", "c"])` evaluate to?

A) `["a-b-c"]`
B) `"a-b-c"`
C) `"-a-b-c-"`
D) `TypeError`

20. What is the output of `"apple,banana,cherry".partition(",")`?

A) `["apple", "banana,cherry"]`
B) `("apple", ",", "banana,cherry")`
C) `("apple,banana", ",", "cherry")`
D) `("apple", "banana,cherry")`

21. What does `"hello world".replace("l", "x", 1)` produce?

A) `"hexxo world"`
B) `"hexlo world"`
C) `"helxo world"`
D) `"hello world"`

22. What is the return value of `"banana".rfind("a")`?

A) `1`
B) `3`
C) `5`
D) `-1`

23. How does `rsplit()` differ from standard `split()` when `maxsplit` is provided?

A) It splits from left to right.
B) Splits are counted and performed starting from the right side of the string.
C) It returns tuples instead of lists.
D) No difference.

24. What does `"apple, banana, cherry".split(",")` return?

A) `["apple", "banana", "cherry"]`
B) `["apple", " banana", " cherry"]`
C) `("apple", "banana", "cherry")`
D) `["apple,", " banana,", " cherry"]`

Part 5: Splitting Lines, Stripping & Translation (Q25–Q30)

25. How does `splitlines()` handle line boundaries by default?

A) It splits on spaces.

B) It splits on universal newline boundaries (`\n`, `\r\n`, `\r`) and strips line break chars.

C) It preserves newline characters in items.

D) It raises errors on `\r`.

26. What does `"foobar".startswith("foo", 0, 3)` evaluate to?

A) `False`

B) `True`

C) `IndexError`

D) `None`

27. What is the output of `" hello ".strip()`?

A) `" hello"`

B) `"hello "`

C) `"hello"`

D) `""`

28. What does `"Python".swapcase()` return?

A) `"PYTHON"`

B) `"python"`

C) `"pYTHON"`

D) `ValueError`

29. What does `"hello world".title()` return?

A) `"Hello world"`

B) `"Hello World"`

C) `"HELLO WORLD"`

D) `"hello world"`

30. How does `str.maketrans()` work with `str.translate()`?

A) They convert strings to integers.

B) `maketrans()` creates a character mapping table that `translate()` uses to replace specified characters.

C) They perform regular expression matching.

D) They encode text to binary.

Part 6: Advanced Padding & Quick Answer Key (Q31–Q35)

31. What is the output of `"42".zfill(5)`?

A) `"42000"`
B) `"00042"`
C) `" 042"`
D) `ValueError`

32. What does `"hello".rpartition("l")` return?

A) `("hel", "l", "o")`
B) `("hel", "l", "o")` (searches from the right side)
C) `("he", "l", "lo")`
D) `("hello", "", "")`

33. What does `"  python".lstrip()` return?

A) `" python"`
B) `"python"`
C) `"python "`
D) `""`

34. What does `"python  ".rstrip()` return?

A) `" python"`
B) `"python"`
C) `"python "`
D) `""`

35. What is the output of `"abc".ljust(5, "*")`?

A) `"**abc"`
B) `"abc**"`
C) `"a*b*c*"`
D) `ValueError`

Quick Answer Key Reference

Q1–Q7	Q8–Q14	Q15–Q21	Q22–Q28	Q29–Q35
1: B	8: C	15: C	22: C	29: B
2: B	9: B	16: A	23: B	30: B
3: C	10: B	17: B	24: B	31: B
4: A	11: B	18: B	25: B	32: B
5: C	12: B	19: B	26: B	33: B
6: B	13: B	20: B	27: C	34: B
7: B	14: B	21: B	28: C	35: B