



SEPA Credit Transfer Scheme

Inter-PSP Implementation Guidelines

EPC115-06 / 2025 Version 1.0 / Date issued: 28 November 2024 / Date effective: 5 October 2025

Public



Abstract

This document sets out the rules for implementing Version 1.0 of the 2025 SEPA Credit Transfer Scheme Rulebook, based on the 2019 message version of the ISO 20022 standard.



TABLE OF CONTENTS

0 DOCUMENT INFORMATION	3
0.1 REFERENCES	3
0.2 CHANGE HISTORY	4
0.3 PURPOSE OF DOCUMENT	4
1 INTRODUCTION	6
1.1 COVERAGE OF THE SEPA IMPLEMENTATION GUIDELINES.....	7
1.2 USE OF THESE GUIDELINES BY THE INSTRUCTING AND INSTRUCTED PARTIES.....	8
1.3 NOTATION CONVENTIONS	8
1.4 CHARACTER SET.....	10
1.5 GENERAL MESSAGE ELEMENT SPECIFICATIONS	11
1.5.1 <i>BIC</i>	11
1.6 IMPLEMENTATION OF ISO 20022 XML RULES	11
1.7 CHANGE OVER DATE.....	11
2 MANDATORY PSP-TO-PSP MESSAGES	12
2.1 INTER-PSP PAYMENT DATASET (DS-02)	12
2.1.1 <i>Use of FI to FI Customer Credit Transfer (pacs.008.001.08)</i>	12
2.2 INTER-PSP RETURN SEPA CREDIT TRANSFER DATASET (DS-03)	41
2.2.1 <i>Use of the Payment Return (pacs.004.001.09)</i>	41
2.2.2 <i>Message Element Specifications</i>	56
2.3 INTER-PSP REJECT SEPA CREDIT TRANSFER DATASET (DS-03).....	57
2.3.1 <i>Use of the FI to FI Payment Status Report (pacs.002.001.10)</i>	57
2.3.2 <i>Message Element Specifications</i>	68
2.4 INTER-PSP RECALL OF SEPA CREDIT TRANSFER DATASET (DS-05).....	69
2.4.1 <i>Use of FI-to-FI Payment Cancellation Request (camt.056.001.08)</i>	69
2.5 INTER-PSP NEGATIVE RESPONSE TO A RECALL OF SEPA CREDIT TRANSFER DATASET (DS-06)	79
2.5.1 <i>Use of Resolution of Investigation (camt.029.001.09)</i>	79
2.6 INTER-PSP POSITIVE RESPONSE TO A RECALL OF SEPA CREDIT TRANSFER DATASET (DS-06)	90
2.6.1 <i>Use of inter-PSP return credit transfer message (pacs.004.001.09)</i>	90
2.7 REQUEST FOR STATUS UPDATE ON A RECALL OF SEPA CREDIT TRANSFER	105
2.7.1 <i>Use of the FI to FI Payment Status Request (pacs.028.001.03)</i>	105
2.8 REQUEST FOR RECALL BY THE ORIGINATOR DATASET (DS-07).....	113
2.8.1 <i>Use of FI-to-FI Payment Cancellation Request (camt.056.001.08)</i>	113
2.9 INTER-PSP NEGATIVE RESPONSE TO THE REQUEST FOR RECALL BY THE ORIGINATOR DATASET (DS-08).....	123
2.9.1 <i>Use of Resolution of Investigation (camt.029.001.09)</i>	123
2.10 INTER-PSP POSITIVE RESPONSE TO THE REQUEST FOR RECALL BY THE ORIGINATOR DATASET (DS-08)	134
2.10.1 <i>Use of inter-PSP return credit transfer message (pacs.004.001.09)</i>	134



2.11	REQUEST FOR STATUS UPDATE ON A REQUEST FOR RECALL BY THE ORIGINATOR.....	149
2.11.1	<i>Use of FI To FI Payment Status Request (pacs.028.001.03).....</i>	149
2.12	INTER-PSP SCT INQUIRY DATASET (DS-09) FOR CLAIM NON-RECEIPT.....	157
2.12.1	<i>Use of Claim Non-Receipt (camt.027.001.07)</i>	157
2.13	INTER-PSP NEGATIVE RESPONSE TO CLAIM NON-RECEIPT (DS-10)	166
2.13.1	<i>Use of Resolution of Investigation (camt.029.001.09).....</i>	166
2.14	INTER-PSP POSITIVE RESPONSE TO CLAIM NON-RECEIPT (DS-10).....	175
2.14.1	<i>Use of Resolution of Investigation (camt.029.001.09).....</i>	175
2.15	INTER-PSP SCT INQUIRY DATASET (DS-09) FOR CLAIM FOR VALUE DATE CORRECTION .	188
2.15.1	<i>Use of Request to Modify Payment (camt.087.001.06).....</i>	188
2.16	INTER-PSP NEGATIVE RESPONSE TO CLAIM FOR VALUE DATE CORRECTION (DS-10)	197
2.16.1	<i>Use of Resolution of Investigation (camt.029.001.09).....</i>	197
2.17	INTER-PSP POSITIVE RESPONSE TO CLAIM FOR VALUE DATE CORRECTION (DS-10) WITH REQUEST FOR INTER-PSP FEE AND/OR INTEREST COMPENSATION.....	207
2.17.1	<i>Use of Resolution of Investigation (camt.029.001.09).....</i>	207
2.18	INTER-PSP CONFIRMED POSITIVE RESPONSE TO CLAIM FOR VALUE DATE CORRECTION (DS-10)	223
2.18.1	<i>Use of Resolution of Investigation (camt.029.001.09).....</i>	223
2.19	INTER-PSP FEE AND/OR COMPENSATION PAYMENT DATASET (DS-11).....	239
2.19.1	<i>Use of FI to FI Customer Credit Transfer (pacs.008.001.08)</i>	239
2.20	REQUEST FOR STATUS UPDATE ON A SCT INQUIRY	259
2.20.1	<i>Use of FI To FI Payment Status Request (pacs.028.001.03).....</i>	259
2.21	INTER-PSP PAYMENT WITH USE OF THE EXTENDED REMITTANCE INFORMATION OPTION	267
2.21.1	<i>Use of FI to FI Customer Credit Transfer (pacs.008.001.08)</i>	267
3	LIST OF CHANGES IN THE CREDIT TRANSFER INTER-PSP IMPLEMENTATION GUIDELINES - RELATIVE TO 2023 V1.1	297



0 DOCUMENT INFORMATION

0.1 References

This section lists relevant documents of interest.

	Document Number	Title	Issued by:
[1]	EPC125-05	SEPA Credit Transfer Scheme Rulebook 2025 Version 1.0, including Annex V - Extended Remittance Information to the SCT Rulebook (document EPC 152-18)	EPC
[2]	-	ISO 20022 XML Credit Transfers and Related Messages: <ul style="list-style-type: none">• Initiation• Clearing and Settlement• Exceptions & Investigations <p>Note: The 2025 IGs are based on the 2019 message version of ISO 20022.</p>	ISO 20022
[3]	ISO 3166	Country Codes	ISO
[4]	ISO 4217	Currency Code List	ISO
[5]	ISO 9362	Business Identifier Codes (BIC)	ISO
[6]	ISO 13616	IBAN: International Bank Account Number	ISO ¹
[7]	ISO 11649	Structured creditor reference to remittance information	ISO
[8]	EPC217-08	SEPA Requirements for an Extended Character Set	EPC
[9]	EPC230-15	Clarification Paper on the Use of Slashes in References, Identifications and Identifiers	EPC
[10]	EPC153-22	EPC Guidance Document: Provision of Addresses under the EPC Payment Schemes	EPC
[11]	EPC088-22	EPC Guidance Document – Improve Transparency for Retail Payment End-Users	EPC

¹ See also <https://www.swift.com/standards/data-standards/iban-international-bank-account-number>



0.2 Change History

Issue number	Dated	Reason for revision
V1.0	20060824	Approved under the authority of the EPC Plenary March 2006
V2.1	20060929	EPC Plenary approval 27 September 2006
V2.2	20061213	EPC Plenary approval 13 December 2006
V2.21	20070316	OITS WB4 TF1 review of the customer-to-PSP initiation messages, 1 March 2007 and the specifications of the Originator and Beneficiary Reference Parties
V2.3	20070619	Approved by the EPC June Plenary 2007
V3.2	20080624	EPC Plenary approval 24 June 2008
V3.3	20091101	EPC Plenary approval October 2009
V4.0	20091101	EPC Plenary approval October 2009
V5.0	20101001	EPC Plenary approval September 2010
V6.0	20111117	EPC Plenary approval September 2011
V7.0	20121130	EPC Plenary approval September 2012
V8.0	20141125	EPC Plenary approval October 2014
2017 V1.0	20161103	Approval by the November 2016 Scheme Management Board
2017 V1.1	20171114	Approval by the October 2017 Scheme Management Board
2017 V2.0	20171220	Approval by the October 2017 Scheme Management Board
2017 V2.1	20180628	Approval by the October 2017 Scheme Management Board
2019 V1.0	20181031	Approval by the October 2018 Scheme Management Board
2021 V1.0	20201029	Approval by the October 2020 Scheme Management Board
2023 v1.0	20220428	Approval by the April 2022 Scheme Management Board
2025 V1.0	20241031	Approval by the October 2024 Payment Scheme Management Board (PSMB)

0.3 Purpose of Document

The objective of these Guidelines is to define the rules to be applied to the inter-Payment Service Provider (PSP) ISO 20022 XML message standards for the implementation of the SEPA Credit Transfers as defined in the SEPA Credit Transfer Scheme Rulebook.

Note: The term “bank” has been replaced by “PSP” in all the EPC SEPA payment scheme rulebooks and associated implementation guidelines to formally reflect the changes introduced by the Payment Services Directive (PSD) to the categories of institutions that can offer payment services, and the variety in PSP categories that are eligible to adhere to the EPC SEPA payment schemes. However, please note that in the context of ISO, the term “bank” is still used.



Note: The term 'Customer' is to be understood as 'Payment Service User' (PSU), meaning a natural or legal person making use of a payment service in the capacity of payer, payee, or both. Such person can take up the role of Originator and/or Beneficiary under the Scheme."



1 INTRODUCTION

This document sets out the SEPA rules for implementing the inter-PSP credit transfer ISO 20022 XML message standards. The SEPA Credit Transfer Scheme Rulebook defines data sets which are implemented in the relevant ISO 20022 XML message standard as follows:

SEPA Credit Transfer Scheme Rulebook	ISO 20022 XML Message Standards
DS-02 <i>Inter-PSP Payment Dataset</i> DS-11 <i>Inter-PSP Fee and/or Compensation Payment Dataset</i>	FI to FI Customer Credit Transfer (pacs.008.001.08)
DS-03 <i>Reject or Return Credit Transfer Dataset</i>	Return – Payment Return (pacs.004.001.09) Reject – FI to FI Payment Status Report (pacs.002.001.10)
DS-05 <i>Recall of Credit Transfer Dataset</i>	FI to FI Payment Cancellation Request (camt.056.001.08)
DS-06 <i>Response to Recall of Credit Transfer Dataset</i>	Negative Response: Resolution of Investigation (camt.029.001.09) Positive Response: Payment Return (pacs.004.001.09)
DS-07 <i>Request for Recall by the Originator Dataset</i>	FI to FI Payment Cancellation Request (camt.056.001.08)
DS-08 <i>Response to the Request for Recall by the Originator Dataset</i>	Negative Response: Resolution of Investigation (camt.029.001.09) Positive Response: Payment Return (pacs.004.001.09)
<i>Request for Status Update on a Request for Recall (step CT-02.07 under 4.3.2.3)</i> <i>Request for Status Update on a Request for Recall by the Originator (step 4C under 4.3.2.4)</i>	FI To FI Payment Status Request (pacs.028.001.03)
DS-09 <i>SCT Inquiry Dataset</i>	Claim Non-Receipt (camt.027.001.07) Request to Modify Payment (camt.087.001.06)
DS-10 <i>Response-to-SCT-Inquiry Dataset</i>	Negative/Positive Response: Resolution of Investigation (camt.029.001.09)
<i>Request for Status Update on a SCT Inquiry (step iii under 4.4.1)</i>	FI To FI Payment Status Request (pacs.028.001.03)

The Guidelines for the inter-PSP credit transfer message standards are mandatory.



1.1 Coverage of the SEPA Implementation Guidelines

The purpose of the SEPA Implementation Guidelines, hereafter referred to as the Guidelines, is to provide guidance on the use of the Global ISO 20022 XML standards in making SEPA core payments as defined in the SEPA scheme rulebooks and supplemented by processing requirements.

The Guidelines are fully aligned to the SEPA core requirements as defined in the Rulebook and identify message elements needed for inter-PSP processing while recognising message elements that may be available for use in Additional Optional Services (AOS), as shown below.

Global ISO 20022 XML Message Standards			
Message elements from the ISO messages corresponding to Rulebook requirements	Message elements that are mandatory in the ISO messages or needed for Inter-PSP Processing	Message elements from the ISO messages available for use by AOS within an EPC Governance framework	Message elements from ISO messages not applicable to SEPA
EPC Implementation Guidelines for SEPA Core Mandatory subset, identifying elements <ul style="list-style-type: none">- to be used as defined in ISO- to be used with SEPA usage rules (from or completing the Rulebook) Note: yellow fields can be used in a specific way for an AOS.		To be developed and documented by AOS Communities	Not available for use in SEPA payments
SEPA Payments			

Figure 1

These Guidelines define the SEPA Core Mandatory Subset² of the Global ISO 20022 XML standard that consists of message elements:

- required in the Rulebook as business requirements
- needed for processing by PSPs and clearing and settlement mechanisms

These message elements define the **SEPA core service** and are denoted by yellow shading in the message structures given in the following chapters. Only these elements are further detailed with relevant SEPA core requirements, such as the use of the message element, its components or the values that must be used. Usage rules, for example, may indicate limits on the number of repetitions, or code value restrictions, while format rules may be used to indicate the allowable combinations of components of a message element.

² The SEPA Core Mandatory Subset is hereafter known as the SEPA core service.



These Guidelines also recognise message elements and the usage rules in the ISO 20022 XML standard that may be available for use in an AOS, subject to a governance framework to be defined by the EPC. The definition and documentation of these message elements are a matter for the AOS communities involved. These message elements are denoted by white shading.

Where there are message elements that do not apply to SEPA payments, these are denoted with red shading in the right-most column of the message structures. To date, few such message elements have been identified.

1.2 Use of these Guidelines by the instructing and instructed parties³

- SEPA core payments are executed using messages only containing message elements defined as part of the SEPA Core Mandatory Subset (shaded yellow in Figure 2).
- Payments that include message elements that are defined and documented by AOS communities (shaded white/yellow in Figure 2) are considered as SEPA payments, but not as SEPA core payments.
- It is the responsibility of the instructing PSP of the message to ensure that message elements defined for use in an AOS are only included in messages sent to AOS community members.
- The instructed PSP receiving a message containing AOS-related message elements, but which is not a member of the AOS community, may ignore the information, that is, not use it for processing, nor forward it to the next party in the chain. The instructed PSP, however, may reject the message for this reason.

1.3 Notation Conventions

The Guidelines are presented in a similar format than the one used in the ISO 20022 XML standard.

#	SEPA Mul	Message Element	SEPA Core Requirements
1.00	1..1	Message root +Group Header ++Sublevel 1 +++Sublevel 2	<i>SEPA Usage Rule(s)</i> (e.g. Mandatory) <i>SEPA Format Rule(s)</i> ISO Name ISO Definition XML Tag Type (Yellow: Message Element that is part of the SEPA Core Service)
	1..1		XML Tag xs:choice

³ Instructing and instructed parties include CSMs.

1.01	1..1	Message root +Group Header ++Sublevel 1 +++Sublevel 2 ++++Sublevel 3	<i>SEPA Rulebook</i>	<i>(Attribute used in Rulebook) (e.g. Only 'SEPA' is allowed.)</i>
			<i>SEPA Usage Rule(s)</i>	
			<i>ISO Name</i> <i>ISO Definition</i> <i>XML Tag</i> <i>Type</i> <i>ISO Length</i> <i>SEPA Length</i>	
			(Yellow: Message Element that is part of the SEPA Core Service)	
			<i>SEPA Code restrictions</i>	
			<i>SEPA</i>	<i>SingleEuroPaymentsArea</i> <i>Payment must be executed following the Single Euro Payments Area scheme.</i>
1.02	1..1	Message root +Group Header ++Sublevel 1 +++Sublevel 2 ++++Sublevel 3	<i>ISO Name</i> <i>ISO Definition</i> <i>XML Tag</i> <i>Type</i>	(White: Message Element that is not part of the Core Service but is available for use in a SEPA AOS)
1.0n	0..1	Message root +Group Header ++Sublevel 1	<i>ISO Name</i> <i>ISO Definition</i> <i>XML Tag</i> <i>Type</i>	(Red: Message Element that is not to be used in SEPA Payments)

Figure 2

Where:

- Column 1 indicates the message element Index number specific to these Implementation Guidelines. . Components of message elements that are not allowed in SEPA payments or where no SEPA requirements are defined are not displayed in full as the ISO 20022 XML standard applies.
- Column 2 indicates the mandatory or optional status and the number of repetitions defined by the SEPA Core Requirements, e.g.:
 - 0..1 element is optional and may only be present once
 - 0..n element is optional with unlimited repetition
 - 1..1 element is mandatory and must be present exactly once
 - 1..n element is mandatory with unlimited repetition

The displayed SEPA multiplicity may thus differ from the one of the ISO 20022 XML standard. When an element is shaded yellow, possible remaining ISO 20022 occurrences are available for use in an AOS.

Empty elements are not allowed (i.e. a message shall not contain elements without content).

- Column 3 indicates the full path of an element where the last line contains the name of the message element as defined in the ISO 20022 XML standard.



When an element contains sub-elements these are indented to the right and noted with a plus sign (+) per level.

- Column 4 specifies in italic characters the SEPA Core Requirements as additional rules to those specified in the ISO 20022 XML standard, which are shown in non-italic characters.
 - When defined in the Rulebook, the attribute is indicated by the attribute name and where applicable, the number, i.e., AT-XXXX. Those message elements are shaded yellow.
 - When the message element relates to inter-PSP processing requirements, it is shaded yellow.
 - When the message element specified in the ISO 20022 XML standard is used for SEPA payments without change (regarding the definition and any usage rules), no specific SEPA Core requirements are provided and is shaded yellow.
 - When the message element is specified in the ISO 20022 XML standard as optional, but is mandatory in SEPA Core requirements, this is specified as 'Mandatory' and is shaded yellow.
 - When the message element is not available for use in SEPA payments, this is indicated with red shading. Note that these message elements are similarly not available for use in an AOS.
 - The SEPA length is indicated for every message element (if applicable), even if it is the same length as in the ISO 20022 XML standard.

Column 4 may also indicate conditional relations between message components or elements, e.g. either component 1 or component 2 must be present, component 1 and component 2 are mutually exclusive. For XML Tag "xs:choice" (containing just one subsequent component or element due to applied restrictions on subsequent components or elements) column 4 may indicate, that the "choice" nature is lost due to applied restrictions i.e. only one element is shaded yellow.

1.4 Character Set

The character set issue centres on the use of the full set characters in the message elements. Two considerations are:

- While PSPs must be allowed to use the character set currently in use at national level,
- PSPs throughout SEPA cannot be required to support the full character set used in SEPA countries.

Therefore:

- The ISO 20022 XML messages allow for the full range of global language requirements (UTF-8).
- PSPs must be able to support the Latin character set commonly used in international communication, as follows:
a b c d e f g h i j k l m n o p q r s t u v w x y z
A B C D E F G H I J K L M N O P Q R S T U V W X Y Z
0 1 2 3 4 5 6 7 8 9



/ - ? : () . , ' +

Space

- References, identifications and identifiers must respect the following [9]:
 - Content is restricted to the Latin character set as defined above
 - Content must not start or end with a '/'
 - Content must not contain '//'s

Note: When a slash is used as delimiter between the attribute number (AT-XXXX) or code (ABCD) and the data content, no space is allowed directly after this slash.

However, there may be bilateral or multilateral agreements to support one or more sets of characters beyond the Latin character set referred to above.

1.5 General Message Element Specifications

1.5.1 BIC

The BIC used to identify financial institutions (Agents in the ISO 20022 XML standards) may be either BIC 11 or BIC 8.

Depending on the version of the ISO 20022 message used, the BIC of a financial institution may be populated either in a <BIC> or in a <BICFI> element (Note: the latter applies to the pacs.028.001.01, camt.027.001.06, camt.087.001.05 and camt.029.001.08 messages).

1.6 Implementation of ISO 20022 XML rules

This document should be read in conjunction with the ISO 20022 XML message standards.

1.7 Change Over Date

As from the change-over date, receiving PSPs may only receive messages, including the r-messages, in the new version.

Note: As of 22 November 2026, only the use of structured and hybrid addresses will be allowed (i.e. the provision of unstructured addresses is no longer allowed as from this date). For further details, please see EPC Guidance Document "Provision of Addresses under the EPC Payment Schemes" [10].



2 MANDATORY PSP-TO-PSP MESSAGES

2.1 Inter-PSP Payment Dataset (DS-02)

2.1.1 Use of FI to FI Customer Credit Transfer (pacs.008.001.08)

The message is used to transport the Payment instruction from the Originator PSP to the Beneficiary PSP, directly or through intermediaries.

The message caters for bulk and single payment instructions.

Note: It is allowed to send a mix of DS-02 and DS-11 transactions, i.e. one pacs.008.001.08 message can contain 'Credit Transfer Transaction Information' blocks as per DS-02 (the present section) and DS-11 (Inter-PSP Fee and/or Compensation Payment, refer to section 2.19). In such case:

- 'Payment Type Information' must be present only in 'Credit Transfer Transaction Information' in order to allow mentioning under 'Category Purpose' the codes necessary for such Fee and/or Compensation Payment transactions,
- 'Credit Transfer Transaction Information' block(s) relating to DS-11 transaction(s) must be formatted as per section 2.19 (not 2.1).

Note: The present section only describes the transactions as per DS-02, i.e. the Inter-PSP Payment Dataset.

#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements	
		Document	XML Tag Type	Document Document
	1..1	FITo FICustomer Credit Transfer V08	ISO Name ISO Definition	FITo FICustomer Credit Transfer V08 Scope The FinancialInstitutionToFinancialInstitutionCustomerCreditTransfer message is sent by the debtor agent to the creditor agent, directly or through other agents and/or a payment clearing and settlement system. It is used to move funds from a debtor account to a creditor. FIToFICstmrcdtTrf FIToFICustomerCreditTransferV08
1.0	1..1	FITo FICustomer Credit Transfer V08 +Group Header	ISO Name ISO Definition XML Tag Type	Group Header Set of characteristics shared by all individual transactions included in the message. GrpHdr GroupHeader93
1.1	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Message Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Message Identification Point to point reference, as assigned by the instructing party, and sent to the next party in the chain to unambiguously identify the message. Usage: The instructing party has to make sure that MessageIdentification is unique per instructed party for a pre-agreed period. MsgId Max35Text 1 .. 35 1 .. 35
1.2	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Creation Date Time	ISO Name ISO Definition XML Tag Type	Creation Date Time Date and time at which the message was created. CreDtTm ISODateTime
1.3	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Batch Booking	ISO Name ISO Definition XML Tag Type	Batch Booking Identifies whether a single entry per individual transaction or a batch entry for the sum of the amounts of all transactions within the group of a message is requested. Usage: Batch booking is used to request and not order a possible batch booking. BtchBookg BatchBookingIndicator
1.4	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Number Of Transactions	ISO Name ISO Definition XML Tag Type Pattern	Number Of Transactions Number of individual transactions contained in the message. NbOfTx Max15NumericText [0-9]{1,15}
1.5	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Control Sum	ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits	Control Sum Total of all individual amounts included in the message, irrespective of currencies. CtrlSum DecimalNumber 17 18

#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements						
1.6	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Total Interbank Settlement Amount	<p>SEPA Usage Rule(s) <i>Mandatory.</i> <i>Only 'EUR' is allowed.</i> <i>Amount must be 0.01 or more and 99999999999999.99 or less.</i> <i>The fractional part has a maximum of two digits.</i></p> <p>SEPA Format Rule(s)</p> <p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p> <p>SEPA FractDigits 2</p> <p>TotalDigits 18</p> <p>SEPA Inclusive 0.01 .. 99999999999999.99</p>						
1.7	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Interbank Settlement Date	<p>SEPA Rulebook <i>AT-T051 Settlement Date of the Credit Transfer.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p> <p><i>Interbank Settlement Date</i> Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. IntrBkSttlmDt ISODate</p>						
1.8	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Settlement Information	<p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p> <p>Settlement Information Specifies the details on how the settlement of the transaction(s) between the instructing agent and the instructed agent is completed. SttlmInf SettlementInstruction7</p>						
1.9	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Settlement Information +++Settlement Method	<p>SEPA Usage Rule(s) <i>Only "CLRG", "INGA" and "INDA" are allowed.</i></p> <p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p> <p>Settlement Method Method used to settle the (batch of) payment instructions. SttlmMtd SettlementMethod1Code</p> <p>SEPA Code Restrictions</p> <table border="0"> <tr> <td>CLRG</td> <td><i>ClearingSystem</i> <i>Settlement is done through a payment clearing system.</i></td> </tr> <tr> <td>INDA</td> <td><i>InstructedAgent</i> <i>Settlement is done by the agent instructed to execute a payment instruction.</i></td> </tr> <tr> <td>INGA</td> <td><i>InstructingAgent</i> <i>Settlement is done by the agent instructing and forwarding the payment to the next party in the payment chain.</i></td> </tr> </table>	CLRG	<i>ClearingSystem</i> <i>Settlement is done through a payment clearing system.</i>	INDA	<i>InstructedAgent</i> <i>Settlement is done by the agent instructed to execute a payment instruction.</i>	INGA	<i>InstructingAgent</i> <i>Settlement is done by the agent instructing and forwarding the payment to the next party in the payment chain.</i>
CLRG	<i>ClearingSystem</i> <i>Settlement is done through a payment clearing system.</i>								
INDA	<i>InstructedAgent</i> <i>Settlement is done by the agent instructed to execute a payment instruction.</i>								
INGA	<i>InstructingAgent</i> <i>Settlement is done by the agent instructing and forwarding the payment to the next party in the payment chain.</i>								
1.10	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Settlement Information +++Settlement Account	<p>SEPA Usage Rule(s) <i>Only 'Identification' is allowed.</i></p> <p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p> <p>Settlement Account A specific purpose account used to post debit and credit entries as a result of the transaction. SttlmAcct CashAccount38</p>						
1.11	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Settlement Information +++Clearing System	<p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p> <p>Clearing System Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed. ClrSys ClearingSystemIdentification3Choice</p>						
	1..1		XML Tag xs:choice						

#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements	
1.12	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Settlement Information +++Clearing System ++++Code	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Code Infrastructure through which the payment instruction is processed, as published in an external clearing system identification code list. Cd ExternalCashClearingSystem1Code 1 .. 3 I .. 3
1.13	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Settlement Information +++Clearing System ++++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Proprietary Clearing system identification in a proprietary form. Prtry Max35Text 1 .. 35 I .. 35
1.14	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Settlement Information +++Instructing Reimbursement Agent	ISO Name ISO Definition XML Tag Type	Instructing Reimbursement Agent Agent through which the instructing agent will reimburse the instructed agent. Usage: If InstructingAgent and InstructedAgent have the same reimbursement agent, then only InstructingReimbursementAgent must be used. InstgRmbrsmntAgt BranchAndFinancialInstitutionIdentification6
1.15	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Settlement Information +++Instructing Reimbursement Agent Account	ISO Name ISO Definition XML Tag Type	Instructing Reimbursement Agent Account Unambiguous identification of the account of the instructing reimbursement agent account at its servicing agent in the payment chain. InstgRmbrsmntAgtAcct CashAccount38
1.16	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Settlement Information +++Instructed Reimbursement Agent	ISO Name ISO Definition XML Tag Type	Instructed Reimbursement Agent Agent at which the instructed agent will be reimbursed. Usage: If InstructedReimbursementAgent contains a branch of the InstructedAgent, then the party in InstructedAgent will claim reimbursement from that branch/will be paid by that branch. Usage: If InstructingAgent and InstructedAgent have the same reimbursement agent, then only InstructingReimbursementAgent must be used. InstdRmbrsmntAgt BranchAndFinancialInstitutionIdentification6
1.17	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Settlement Information +++Instructed Reimbursement Agent Account	ISO Name ISO Definition XML Tag Type	Instructed Reimbursement Agent Account Unambiguous identification of the account of the instructed reimbursement agent account at its servicing agent in the payment chain. InstdRmbrsmntAgtAcct CashAccount38
1.18	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Settlement Information +++Third Reimbursement Agent	ISO Name ISO Definition XML Tag Type	Third Reimbursement Agent Agent at which the instructed agent will be reimbursed. Usage: If ThirdReimbursementAgent contains a branch of the InstructedAgent, then the party in InstructedAgent will claim reimbursement from that branch/will be paid by that branch. ThrdRmbrsmntAgt BranchAndFinancialInstitutionIdentification6

#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements	
1.19	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Settlement Information +++Third Reimbursement Agent Account	ISO Name ISO Definition XML Tag Type	Third Reimbursement Agent Account Unambiguous identification of the account of the third reimbursement agent account at its servicing agent in the payment chain. ThrdRmbrsmntAgtAcct CashAccount38
1.20	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	'Payment Type Information' must be present in either 'Group Header' or 'Credit Transfer Transaction Information'. 'Payment Type Information' must not be present here in case this message contains a mix of 'Credit Transfer Transaction Information' related to DS-02 and DS-11. Payment Type Information Set of elements used to further specify the type of transaction. PmtTpInf PaymentTypeInformation28
1.21	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information +++Instruction Priority	ISO Name ISO Definition XML Tag Type	Instruction Priority Indicator of the urgency or order of importance that the instructing party would like the instructed party to apply to the processing of the instruction. InstrPrty Priority2Code
1.22	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information +++Clearing Channel	ISO Name ISO Definition XML Tag Type	Clearing Channel Specifies the clearing channel to be used to process the payment instruction. ClrChnl ClearingChannel2Code
1.23	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information +++Service Level	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Mandatory. Only one occurrence is allowed. Service Level Agreement under which or rules under which the transaction should be processed. SvcLvl ServiceLevel8Choice
	1..1		XML Tag	xs:choice
1.24	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information +++Service Level ++++Code	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length SEPA Code Restrictions SEPA	AT-T001 The identification code of the SEPA electronic credit transfer Scheme. Only "SEPA" is allowed. Code Specifies a pre-agreed service or level of service between the parties, as published in an external service level code list. Cd ExternalServiceLevel1Code 1 .. 4 1 .. 4 SingleEuroPaymentsArea Payment must be executed following the Single Euro Payments Area scheme.
1.25	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information +++Service Level ++++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Proprietary Specifies a pre-agreed service or level of service between the parties, as a proprietary code. Prtry Max35Text 1 .. 35 1 .. 35

#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements	
1.26	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information +++Local Instrument	<p>SEPA Usage Rule(s) Only used if bilaterally agreed between the Debtor PSP and the Creditor PSP.</p> <p>ISO Name Local Instrument</p> <p>ISO Definition User community specific instrument.</p> <p>XML Tag Type LclInstrm LocalInstrument2Choice</p>	Usage: This element is used to specify a local instrument, local clearing option and/or further qualify the service or service level.
	1..1		XML Tag	xs:choice
1.27	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information +++Local Instrument ++++Code	<p>ISO Name Code</p> <p>ISO Definition Specifies the local instrument, as published in an external local instrument code list.</p> <p>XML Tag Type Cd</p> <p>ISO Length ExternalLocalInstrument1Code</p> <p>SEPA Length 1 .. 35</p>	
1.28	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information +++Local Instrument ++++Proprietary	<p>ISO Name Proprietary</p> <p>ISO Definition Specifies the local instrument, as a proprietary code.</p> <p>XML Tag Type Prtry</p> <p>ISO Length Max35Text</p> <p>SEPA Length 1 .. 35</p>	
1.29	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information +++Category Purpose	<p>SEPA Rulebook AT-T008 Category purpose of the Credit Transfer.</p> <p>SEPA Usage Rule(s) Depending on the agreement between the Originator and the Originator PSP, 'Category Purpose' may be forwarded to the Beneficiary PSP.</p> <p>ISO Name Category Purpose</p> <p>ISO Definition Specifies the high level purpose of the instruction based on a set of pre-defined categories.</p> <p>Usage: This is used by the initiating party to provide information concerning the processing of the payment. It is likely to trigger special processing by any of the agents involved in the payment chain.</p> <p>XML Tag Type CtgyPurp CategoryPurpose1Choice</p>	
	1..1		XML Tag	xs:choice
1.30	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information +++Category Purpose ++++Code	<p>ISO Name Code</p> <p>ISO Definition Category purpose, as published in an external category purpose code list.</p> <p>XML Tag Type Cd</p> <p>ISO Length ExternalCategoryPurpose1Code</p> <p>SEPA Length 1 .. 4</p>	
1.31	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information +++Category Purpose ++++Proprietary	<p>ISO Name Proprietary</p> <p>ISO Definition Category purpose, in a proprietary form.</p> <p>XML Tag Type Prtry</p> <p>ISO Length Max35Text</p> <p>SEPA Length 1 .. 35</p>	
1.32	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Instructing Agent	<p>SEPA Usage Rule(s) Only 'BICFI' is allowed</p> <p>ISO Name Instructing Agent</p> <p>ISO Definition Agent that instructs the next party in the chain to carry out the (set of) instruction(s).</p> <p>XML Tag Type InstgAgt</p>	BranchAndFinancialInstitutionIdentification6

#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements
1.33	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Instructed Agent	<p>SEPA Usage Rule(s) Only 'BICFI' is allowed.</p> <p>ISO Name Instructed Agent</p> <p>ISO Definition Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s).</p> <p>XML Tag Type InstdAgt BranchAndFinancialInstitutionIdentification6</p>
2.0	1..n	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information	<p>ISO Name</p> <p>ISO Definition Credit Transfer Transaction Information Set of elements providing information specific to the individual credit transfer(s).</p> <p>XML Tag Type CdtTrfTxInf CreditTransferTransaction39</p>
2.1	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Identification	<p>ISO Name</p> <p>ISO Definition Payment Identification Set of elements used to reference a payment instruction.</p> <p>XML Tag Type PmtId PaymentIdentification7</p>
2.2	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Identification +++Instruction Identification	<p>ISO Name</p> <p>ISO Definition Instruction Identification Unique identification, as assigned by an instructing party for an instructed party, to unambiguously identify the instruction.</p> <p>XML Tag Type</p> <p>ISO Length</p> <p>SEPA Length Usage: The instruction identification is a point to point reference that can be used between the instructing party and the instructed party to refer to the individual instruction. It can be included in several messages related to the instruction. InstrId Max35Text 1 .. 35 1 .. 35</p>
2.3	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Identification +++End To End Identification	<p>SEPA Rulebook AT-T014 The Originator's Reference of the SEPA Credit Transfer Transaction.</p> <p>SEPA Usage Rule(s) A customer reference that must be passed on in the end-to-end chain. In the event that no reference was given, "NOTPROVIDED" must be used.</p> <p>ISO Name</p> <p>ISO Definition End To End Identification Unique identification, as assigned by the initiating party, to unambiguously identify the transaction. This identification is passed on, unchanged, throughout the entire end-to-end chain.</p> <p>Usage: The end-to-end identification can be used for reconciliation or to link tasks relating to the transaction. It can be included in several messages related to the transaction.</p> <p>XML Tag Type</p> <p>ISO Length</p> <p>SEPA Length Usage: In case there are technical limitations to pass on multiple references, the end-to-end identification must be passed on throughout the entire end-to-end chain. EndToEndId Max35Text 1 .. 35 1 .. 35</p>

#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements	
2.4	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Identification +++Transaction Identification	SEPA Rulebook SEPA Usage Rule(s) Must contain a reference that is meaningful to the Originator's PSP and is unique over time. Mandatory. ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>AT-T054 The Originator PSP's reference of the SEPA Credit Transfer Transaction.</i> <i>Transaction Identification</i> Unique identification, as assigned by the first instructing agent, to unambiguously identify the transaction that is passed on, unchanged, throughout the entire interbank chain. Usage: The transaction identification can be used for reconciliation, tracking or to link tasks relating to the transaction on the interbank level. Usage: The instructing agent has to make sure that the transaction identification is unique for a pre-agreed period. TxId Max35Text 1 .. 35 1 .. 35
2.5	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Identification +++UETR	ISO Name ISO Definition XML Tag Type Pattern	UETR Universally unique identifier to provide an end-to-end reference of a payment transaction. UETR UUIDv4Identifier [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}
2.6	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Identification +++Clearing System Reference	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Clearing System Reference Unique reference, as assigned by a clearing system, to unambiguously identify the instruction. ClrSysRef Max35Text 1 .. 35 1 .. 35
2.7	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Type Information	SEPA Usage Rule(s) 'Payment Type Information' must be present in either 'Group Header' or 'Credit Transfer Transaction Information'. ISO Name ISO Definition XML Tag Type	Payment Type Information Set of elements used to further specify the type of transaction. PmtTpInf PaymentTypeInformation28
2.8	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Type Information +++Instruction Priority	ISO Name ISO Definition XML Tag Type	Instruction Priority Indicator of the urgency or order of importance that the instructing party would like the instructed party to apply to the processing of the instruction. InstrPrty Priority2Code
2.9	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Type Information +++Clearing Channel	ISO Name ISO Definition XML Tag Type	Clearing Channel Specifies the clearing channel to be used to process the payment instruction. ClrChnl ClearingChannel2Code
2.10	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Type Information +++Service Level	SEPA Usage Rule(s) Mandatory. <i>Only one occurrence is allowed.</i> ISO Name ISO Definition XML Tag Type	Service Level Agreement under which or rules under which the transaction should be processed. SvcLvl ServiceLevel8Choice
	1..1		XML Tag	xs:choice

#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements	
2.11	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Type Information +++Service Level ++++Code	<p>SEPA Rulebook <i>AT-T001 The identification code of the SEPA electronic credit transfer Scheme.</i></p> <p>SEPA Usage Rule(s) <i>Only "SEPA" is allowed.</i></p> <p>ISO Name Code</p> <p>ISO Definition Specifies a pre-agreed service or level of service between the parties, as published in an external service level code list.</p> <p>XML Tag Cd</p> <p>Type ExternalServiceLevel1Code</p> <p>ISO Length 1 .. 4</p> <p>SEPA Length 1 .. 4</p>	
SEPA Code Restrictions				
			<p>SEPA <i>SingleEuroPaymentsArea</i> <i>Payment must be executed following the Single Euro Payments Area scheme.</i></p>	
2.12	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Type Information +++Service Level ++++Proprietary	<p>ISO Name Proprietary</p> <p>ISO Definition Specifies a pre-agreed service or level of service between the parties, as a proprietary code.</p> <p>XML Tag Prtry</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>	
2.13	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Type Information +++Local Instrument	<p>SEPA Usage Rule(s) <i>Only used if bilaterally agreed between the Debtor PSP and the Creditor PSP.</i></p> <p>ISO Name Local Instrument</p> <p>ISO Definition User community specific instrument.</p> <p>XML Tag LclInstrm</p> <p>Type LocallInstrument2Choice</p>	<p>Usage: This element is used to specify a local instrument, local clearing option and/or further qualify the service or service level.</p>
	1..1		XML Tag xs:choice	
2.14	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Type Information +++Local Instrument ++++Code	<p>ISO Name Code</p> <p>ISO Definition Specifies the local instrument, as published in an external local instrument code list.</p> <p>XML Tag Cd</p> <p>Type ExternalLocalInstrument1Code</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>	
2.15	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Type Information +++Local Instrument ++++Proprietary	<p>ISO Name Proprietary</p> <p>ISO Definition Specifies the local instrument, as a proprietary code.</p> <p>XML Tag Prtry</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>	
2.16	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Type Information +++Category Purpose	<p>SEPA Rulebook <i>AT-T008 Category purpose of the Credit Transfer.</i></p> <p>SEPA Usage Rule(s) <i>Depending on the agreement between the Originator and the Originator PSP, 'Category Purpose' may be forwarded to the Beneficiary PSP.</i></p> <p>ISO Name Category Purpose</p> <p>ISO Definition Specifies the high level purpose of the instruction based on a set of pre-defined categories.</p> <p>XML Tag CtgyPurp</p> <p>Type CategoryPurpose1Choice</p>	<p>Usage: This is used by the initiating party to provide information concerning the processing of the payment. It is likely to trigger special processing by any of the agents involved in the payment chain.</p>

#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements	
	1..1		XML Tag xs:choice	
2.17	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Type Information +++Category Purpose ++++Code	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Code Category purpose, as published in an external category purpose code list. Cd ExternalCategoryPurpose1Code 1 .. 4 1 .. 4
2.18	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Type Information +++Category Purpose ++++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Proprietary Category purpose, in a proprietary form. Prtry Max35Text 1 .. 35 1 .. 35
2.19	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Interbank Settlement Amount	SEPA Rulebook SEPA Usage Rule(s) SEPA Format Rule(s) ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits SEPA Inclusive	AT-T002 Amount of the SEPA Credit Transfer in Euro. Only 'EUR' is allowed. Amount must be 0.01 or more and 99999999.99 or less. The fractional part has a maximum of two digits. Interbank Settlement Amount Amount of money moved between the instructing agent and the instructed agent. IntrBkSttlmAmt ActiveCurrencyAndAmount 2 18 0.01 .. 99999999.99
2.20	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Interbank Settlement Date	ISO Name ISO Definition XML Tag Type	Interbank Settlement Date Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. IntrBkSttlmDt ISODATE
2.21	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Settlement Priority	ISO Name ISO Definition XML Tag Type	Settlement Priority Indicator of the urgency or order of importance that the instructing party would like the instructed party to apply to the processing of the settlement instruction. SttlmPrt Priority3Code
2.22	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Settlement Time Indication	ISO Name ISO Definition XML Tag Type	Settlement Time Indication Provides information on the occurred settlement time(s) of the payment transaction. SttlmTmIndctn SettlementDateTimeIndication1
2.23	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Settlement Time Request	ISO Name ISO Definition XML Tag Type	Settlement Time Request Provides information on the requested settlement time(s) of the payment instruction. SttlmTmReq SettlementTimeRequest2
2.24	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Acceptance Date Time	ISO Name ISO Definition XML Tag Type	Acceptance Date Time Point in time when the payment order from the initiating party meets the processing conditions of the account servicing agent. This means that the account servicing agent has received the payment order and has applied checks such as authorisation, availability of funds. AccptncDtTm ISODATE

#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements	
2.25	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Pooling Adjustment Date	ISO Name ISO Definition XML Tag Type	Pooling Adjustment Date Date used for the correction of the value date of a cash pool movement that has been posted with a different value date. PoolgAdjstmntDt ISODate
2.26	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Instructed Amount	ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits SEPA Inclusive	Instructed Amount Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party. Usage: This amount has to be transported unchanged through the transaction chain. InstdAmt ActiveOrHistoricCurrencyAndAmount 5 18 0 ..
2.27	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Exchange Rate	ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits	Exchange Rate Factor used to convert an amount from one currency into another. This reflects the price at which one currency was bought with another currency. XchgRate BaseOneRate 10 11
2.28	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Charge Bearer	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type SEPA Code Restrictions SLEV	Only "SLEV" is allowed. Charge Bearer Specifies which party/parties will bear the charges associated with the processing of the payment transaction. ChrgBr ChargeBearerType1Code FollowingServiceLevel Charges are to be applied following the rules agreed in the service level and/or scheme.
2.29	0..n	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Charges Information	ISO Name ISO Definition XML Tag Type	Charges Information Provides information on the charges to be paid by the charge bearer(s) related to the payment transaction. ChrgsInf Charges7
2.30	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Previous Instructing Agent 1	ISO Name ISO Definition XML Tag Type	Previous Instructing Agent 1 Agent immediately prior to the instructing agent. PrvsInstgAgt1 BranchAndFinancialInstitutionIdentification6
2.31	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Previous Instructing Agent 1Account	ISO Name ISO Definition XML Tag Type	Previous Instructing Agent 1Account Unambiguous identification of the account of the previous instructing agent at its servicing agent in the payment chain. PrvsInstgAgt1Acct CashAccount38
2.32	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Previous Instructing Agent 2	ISO Name ISO Definition XML Tag Type	Previous Instructing Agent 2 Agent immediately prior to the instructing agent. PrvsInstgAgt2 BranchAndFinancialInstitutionIdentification6

#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements	
2.33	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Previous Instructing Agent 2Account	ISO Name ISO Definition XML Tag Type	Previous Instructing Agent 2Account Unambiguous identification of the account of the previous instructing agent at its servicing agent in the payment chain. PrvsInstgAgt2Acct CashAccount38
2.34	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Previous Instructing Agent 3	ISO Name ISO Definition XML Tag Type	Previous Instructing Agent 3 Agent immediately prior to the instructing agent. PrvsInstgAgt3 BranchAndFinancialInstitutionIdentification6
2.35	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Previous Instructing Agent 3Account	ISO Name ISO Definition XML Tag Type	Previous Instructing Agent 3Account Unambiguous identification of the account of the previous instructing agent at its servicing agent in the payment chain. PrvsInstgAgt3Acct CashAccount38
2.36	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Instructing Agent	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Only 'BICFI' is allowed. Instructing Agent Agent that instructs the next party in the chain to carry out the (set of) instruction(s). InstgAgt BranchAndFinancialInstitutionIdentification6
2.37	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Instructed Agent	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Only 'BICFI' is allowed. Instructed Agent Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s). InstdAgt BranchAndFinancialInstitutionIdentification6
2.38	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Intermediary Agent 1	ISO Name ISO Definition XML Tag Type	Intermediary Agent 1 Agent between the debtor's agent and the creditor's agent. Usage: If more than one intermediary agent is present, then IntermediaryAgent1 identifies the agent between the DebtorAgent and the IntermediaryAgent2. IntrmyAgt1 BranchAndFinancialInstitutionIdentification6
2.39	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Intermediary Agent 1Account	ISO Name ISO Definition XML Tag Type	Intermediary Agent 1Account Unambiguous identification of the account of the intermediary agent 1 at its servicing agent in the payment chain. IntrmyAgt1Acct CashAccount38
2.40	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Intermediary Agent 2	ISO Name ISO Definition XML Tag Type	Intermediary Agent 2 Agent between the debtor's agent and the creditor's agent. Usage: If more than two intermediary agents are present, then IntermediaryAgent2 identifies the agent between the IntermediaryAgent1 and the IntermediaryAgent3. IntrmyAgt2 BranchAndFinancialInstitutionIdentification6
2.41	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Intermediary Agent 2Account	ISO Name ISO Definition XML Tag Type	Intermediary Agent 2Account Unambiguous identification of the account of the intermediary agent 2 at its servicing agent in the payment chain. IntrmyAgt2Acct CashAccount38

#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements	
2.42	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Intermediary Agent 3	ISO Name ISO Definition XML Tag Type	Intermediary Agent 3 Agent between the debtor's agent and the creditor's agent. Usage: If IntermediaryAgent3 is present, then it identifies the agent between the IntermediaryAgent 2 and the CreditorAgent. IntrmyAgt3 BranchAndFinancialInstitutionIdentification6
2.43	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Intermediary Agent 3Account	ISO Name ISO Definition XML Tag Type	Intermediary Agent 3Account Unambiguous identification of the account of the intermediary agent 3 at its servicing agent in the payment chain. IntrmyAgt3Acct CashAccount38
2.44	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Debtor	ISO Name ISO Definition XML Tag Type	Ultimate Debtor Ultimate party that owes an amount of money to the (ultimate) creditor. UltmtDbtr PartyIdentification135
2.45	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Debtor +++Name	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	AT-P006 Name of the Originator Reference Party. 'Name' is limited to 70 characters in length. Name Name by which a party is known and which is usually used to identify that party. Nm Max140Text 1 .. 140 1 .. 70
2.46	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Debtor +++Postal Address	ISO Name ISO Definition XML Tag Type	Postal Address Information that locates and identifies a specific address, as defined by postal services. PstlAdr PostalAddress24
2.47	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Debtor +++Identification	SEPA Rulebook ISO Name ISO Definition XML Tag Type	AT-P007 Identification code of the Originator Reference Party. Identification Unique and unambiguous identification of a party. Id Party38Choice
	1..1		XML Tag	xs:choice
2.48	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Debtor +++Identification ++++Organisation Identification	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Either 'AnyBIC', 'LEI' and/or one occurrence of 'Other' is allowed. Organisation Identification Unique and unambiguous way to identify an organisation. OrgId OrganisationIdentification29
2.49	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Debtor +++Identification ++++Private Identification	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Either 'Date and Place of Birth' or one occurrence of 'Other' is allowed. Private Identification Unique and unambiguous identification of a person, for example a passport. PrvtId PersonIdentification13

#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements	
2.50	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Debtor +++Country Of Residence	ISO Name ISO Definition XML Tag Type Pattern	Country Of Residence Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed. CtryOfRes CountryCode [A-Z]{2,2}
2.51	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Debtor +++Contact Details	ISO Name ISO Definition XML Tag Type	Contact Details Set of elements used to indicate how to contact the party. CtctDtls Contact4
2.52	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Initiating Party	ISO Name ISO Definition XML Tag Type	Initiating Party Party that initiates the payment. Usage: This can be either the debtor or a party that initiates the credit transfer on behalf of the debtor. InitgPty PartyIdentification135
2.53	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor	ISO Name ISO Definition XML Tag Type	Debtor Party that owes an amount of money to the (ultimate) creditor. Dbtr PartyIdentification135
2.54	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Name	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	AT-P001 Name of the Originator. <i>'Name'</i> is limited to 70 characters in length. Name Name by which a party is known and which is usually used to identify that party. Nm Max140Text 1 .. 140 1 .. 70
2.55	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	AT-P005 Address of the Originator (only mandatory when the Originator PSP or the Beneficiary PSP is located in a non-EEA SEPA country or territory). STRUCTURED ADDRESS: Usage is recommended. 'Town Name' and 'Country' are mandatory. 'Address Line' is not allowed. It is recommended to provide as many structured elements as possible. HYBRID ADDRESS: 'Town Name' and 'Country' are mandatory. At least one occurrence of 'Address line' is mandatory. UNSTRUCTURED ADDRESS (As of 22 November 2026, only the use of structured and hybrid addresses will be allowed - based on available information at the moment of publication): At least one occurrence of 'Address line' is mandatory. 'Postal Address' sub-elements other than 'Address Line' and 'Country' are forbidden. The use of 'Country' is mandatory when either the Debtor Agent or Creditor Agent is located in a non-EEA SEPA country or territory. Postal Address Information that locates and identifies a specific address, as defined by postal services. PstlAdr PostalAddress24

#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements	
2.56	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Address Type	ISO Name ISO Definition XML Tag Type	Address Type Identifies the nature of the postal address. AdrTp AddressType3Choice
2.57	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Department	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Department Identification of a division of a large organisation or building. Dept Max70Text 1 .. 70 1 .. 70
2.58	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Sub Department	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Sub Department Identification of a sub-division of a large organisation or building. SubDept Max70Text 1 .. 70 1 .. 70
2.59	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Street Name	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Street Name Name of a street or thoroughfare. StrtNm Max70Text 1 .. 70 1 .. 70
2.60	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Building Number	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Building Number Number that identifies the position of a building on a street. BldgNb Max16Text 1 .. 16 1 .. 16
2.61	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Building Name	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Building Name Name of the building or house. BldgNm Max35Text 1 .. 35 1 .. 35
2.62	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Floor	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Floor Floor or storey within a building. Flr Max70Text 1 .. 70 1 .. 70
2.63	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Post Box	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Post Box Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for. PstBx Max16Text 1 .. 16 1 .. 16
2.64	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Room	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Room Building room number. Room Max70Text 1 .. 70 1 .. 70

#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements	
2.65	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Post Code	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Post Code Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail. PstCd Max16Text 1 .. 16 1 .. 16
2.66	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Town Name	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Town Name Name of a built-up area, with defined boundaries, and a local government. TwnNm Max35Text 1 .. 35 1 .. 35
2.67	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Town Location Name	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Town Location Name Specific location name within the town. TwnLctnNm Max35Text 1 .. 35 1 .. 35
2.68	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++District Name	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	District Name Identifies a subdivision within a country subdivision. DstrctNm Max35Text 1 .. 35 1 .. 35
2.69	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Country Sub Division	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Country Sub Division Identifies a subdivision of a country such as state, region, county. CtrySubDvsn Max35Text 1 .. 35 1 .. 35
2.70	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Country	ISO Name ISO Definition XML Tag Type Pattern	Country Nation with its own government. Ctry CountryCode [A-Z]{2,2}
2.71	0..2	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Address Line	SEPA Usage Rule(s) Up to two occurrences are allowed. ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Address Line Information that locates and identifies a specific address, as defined by postal services, presented in free format text. AdrLine Max70Text 1 .. 70 1 .. 70
2.72	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Identification	SEPA Rulebook ISO Name ISO Definition XML Tag Type	AT-P004 The Originator Identification Code. Identification Unique and unambiguous identification of a party. Id Party38Choice
	1..1		XML Tag	xs:choice
2.73	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Identification ++++Organisation Identification	SEPA Usage Rule(s) Either 'AnyBIC', 'LEI' and/or one occurrence of 'Other' is allowed. ISO Name ISO Definition XML Tag Type	Organisation Identification Unique and unambiguous way to identify an organisation. OrgId OrganisationIdentification29

#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements
2.74	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Identification ++++Private Identification	<p>SEPA Usage Rule(s) Either 'Date and Place of Birth' or one occurrence of 'Other' is allowed.</p> <p>ISO Name Private Identification</p> <p>ISO Definition Unique and unambiguous identification of a person, for example a passport.</p> <p>XML Tag Type PrvtId</p> <p>PersonIdentification13</p>
2.75	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Country Of Residence	<p>ISO Name Country Of Residence</p> <p>ISO Definition Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed.</p> <p>XML Tag Type Pattern CtryOfRes CountryCode [A-Z]{2,2}</p>
2.76	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Contact Details	<p>ISO Name Contact Details</p> <p>ISO Definition Set of elements used to indicate how to contact the party.</p> <p>XML Tag Type CtctDtls Contact4</p>
2.77	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor Account	<p>SEPA Usage Rule(s) Mandatory.</p> <p>ISO Name Debtor Account</p> <p>ISO Definition Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction.</p> <p>XML Tag Type DbtrAcct CashAccount38</p>
2.78	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor Account +++Identification	<p>SEPA Usage Rule(s) Only IBAN is allowed.</p> <p>ISO Name Identification</p> <p>ISO Definition Unique and unambiguous identification for the account between the account owner and the account servicer.</p> <p>XML Tag Type Id AccountIdentification4Choice</p>
	1..1		XML Tag xs:choice
2.79	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor Account +++Identification ++++IBAN	<p>SEPA Rulebook AT-D001 The IBAN of the account of the Originator.</p> <p>ISO Name IBAN</p> <p>ISO Definition International Bank Account Number (IBAN) - identifier used internationally by financial institutions to uniquely identify the account of a customer. Further specifications of the format and content of the IBAN can be found in the standard ISO 13616 "Banking and related financial services - International Bank Account Number (IBAN)" version 1997-10-01, or later revisions.</p> <p>XML Tag Type Pattern IBAN IBAN2007Identifier [A-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}</p>
2.80	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor Account +++Identification ++++Other	<p>ISO Name Other</p> <p>ISO Definition Unique identification of an account, as assigned by the account servicer, using an identification scheme.</p> <p>XML Tag Type Othr GenericAccountIdentification1</p>
2.81	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor Account +++Type	<p>ISO Name Type</p> <p>ISO Definition Specifies the nature, or use of the account.</p> <p>XML Tag Type Tp CashAccountType2Choice</p>

#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements	
2.82	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor Account +++Currency	ISO Name ISO Definition XML Tag Type Pattern	<p>Currency Identification of the currency in which the account is held.</p> <p>Usage: Currency should only be used in case one and the same account number covers several currencies and the initiating party needs to identify which currency needs to be used for settlement on the account.</p> <p>Ccy ActiveOrHistoricCurrencyCode [A-Z]{3,3}</p>
2.83	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor Account +++Name	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<p>Name Name of the account, as assigned by the account servicing institution, in agreement with the account owner in order to provide an additional means of identification of the account.</p> <p>Usage: The account name is different from the account owner name. The account name is used in certain user communities to provide a means of identifying the account, in addition to the account owner's identity and the account number.</p> <p>Nm Max70Text 1 .. 70 1 .. 70</p>
2.84	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor Account +++Proxy	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<p><i>AT-P003 The Proxy/alias of the account of the Originator.</i></p> <p><i>AT-P003 can only be provided here under the condition that the Originator is given the possibility to validate the IBAN linked to that Alias/Proxy, prior to the authentication of the instruction unless the Originator and the Originator PSP agreed upfront on another arrangement (e.g., through an amendment of the general terms and conditions).</i></p> <p><i>Furthermore, the Originator PSP must have an agreement with the Originator and the Beneficiary PSP with the Beneficiary in relation to the treatment and the use of the data provided under such Alias/Proxy i.e. whether it is to be used for the purpose to initiate the transaction and/or to forward it to the Beneficiary PSP and/or the Beneficiary concerned.</i></p> <p><i>Sub-element 'Identification' is limited to 320 characters in length.</i></p> <p>Proxy Specifies an alternate assumed name for the identification of the account.</p> <p>Prxy ProxyAccountIdentification1</p>
2.85	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor Agent	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<p><i>AT-D002 The BIC code of the Originator PSP.</i></p> <p><i>Only 'BICFI' is allowed.</i></p> <p>Debtor Agent Financial institution servicing an account for the debtor.</p> <p>DbtrAgt BranchAndFinancialInstitutionIdentification6</p>

#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements	
2.86	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor Agent Account	ISO Name ISO Definition XML Tag Type	Debtor Agent Account Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain. DbtrAgtAcct CashAccount38
2.87	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor Agent	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	AT-C002 The BIC code of the Beneficiary PSP. Only 'BICFI' is allowed. Creditor Agent Financial institution servicing an account for the creditor. CdtrAgt BranchAndFinancialInstitutionIdentification6
2.88	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor Agent Account	ISO Name ISO Definition XML Tag Type	Creditor Agent Account Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction. CdtrAgtAcct CashAccount38
2.89	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor	ISO Name ISO Definition XML Tag Type	Creditor Party to which an amount of money is due. Cdtr PartyIdentification135
2.90	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Name	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	AT-E001 Name of the Beneficiary. Mandatory. 'Name' is limited to 70 characters in length. Name Name by which a party is known and which is usually used to identify that party. Nm Max140Text 1 .. 140 1 .. 70
2.91	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	AT-E004 The address of the Beneficiary. STRUCTURED ADDRESS: Usage is recommended. 'Town Name' and 'Country' are mandatory. 'Address Line' is not allowed. It is recommended to provide as many structured elements as possible. HYBRID ADDRESS: 'Town Name' and 'Country' are mandatory. At least one occurrence of 'Address line' is mandatory. UNSTRUCTURED ADDRESS (As of 22 November 2026, only the use of structured and hybrid addresses will be allowed - based on available information at the moment of publication): At least one occurrence of 'Address line' is mandatory. 'Postal Address' sub-elements other than 'Address Line' and 'Country' are forbidden. Postal Address Information that locates and identifies a specific address, as defined by postal services. PstlAdr PostalAddress24
2.92	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Address Type	ISO Name ISO Definition XML Tag Type	Address Type Identifies the nature of the postal address. AdrTp AddressType3Choice

#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements	
2.93	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Department	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Department Identification of a division of a large organisation or building. Dept Max70Text 1 .. 70 1 .. 70
2.94	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Sub Department	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Sub Department Identification of a sub-division of a large organisation or building. SubDept Max70Text 1 .. 70 1 .. 70
2.95	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Street Name	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Street Name Name of a street or thoroughfare. StrtNm Max70Text 1 .. 70 1 .. 70
2.96	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Building Number	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Building Number Number that identifies the position of a building on a street. BldgNb Max16Text 1 .. 16 1 .. 16
2.97	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Building Name	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Building Name Name of the building or house. BldgNm Max35Text 1 .. 35 1 .. 35
2.98	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Floor	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Floor Floor or storey within a building. Flr Max70Text 1 .. 70 1 .. 70
2.99	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Post Box	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Post Box Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for. PstBx Max16Text 1 .. 16 1 .. 16
2.100	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Room	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Room Building room number. Room Max70Text 1 .. 70 1 .. 70
2.101	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Post Code	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Post Code Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail. PstCd Max16Text 1 .. 16 1 .. 16

#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements	
2.102	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Town Name	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Town Name Name of a built-up area, with defined boundaries, and a local government. TwnNm Max35Text 1 .. 35 1 .. 35
2.103	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Town Location Name	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Town Location Name Specific location name within the town. TwnLctnNm Max35Text 1 .. 35 1 .. 35
2.104	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++District Name	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	District Name Identifies a subdivision within a country subdivision. DstrctNm Max35Text 1 .. 35 1 .. 35
2.105	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Country Sub Division	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Country Sub Division Identifies a subdivision of a country such as state, region, county. CtrySubDvsn Max35Text 1 .. 35 1 .. 35
2.106	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Country	ISO Name ISO Definition XML Tag Type Pattern	Country Nation with its own government. Ctry CountryCode [A-Z]{2,2}
2.107	0..2	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Address Line	SEPA Usage Rule(s) <i>Up to two occurrences are allowed.</i> ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Address Line Information that locates and identifies a specific address, as defined by postal services, presented in free format text. AdrLine Max70Text 1 .. 70 1 .. 70
2.108	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Identification	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-E005 Beneficiary Identification Code.</i> Identification Unique and unambiguous identification of a party. Id Party38Choice
	1..1		XML Tag	xs:choice
2.109	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Identification ++++Organisation Identification	SEPA Usage Rule(s) <i>Either 'AnyBIC', 'LEI' or one occurrence of 'Other' is allowed.</i> ISO Name ISO Definition XML Tag Type	Organisation Identification Unique and unambiguous way to identify an organisation. OrgId OrganisationIdentification29
2.110	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Identification ++++Private Identification	SEPA Usage Rule(s) <i>Either 'Date and Place of Birth' or one occurrence of 'Other' is allowed.</i> ISO Name ISO Definition XML Tag Type	Private Identification Unique and unambiguous identification of a person, for example a passport. PrvtId PersonIdentification13

#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements		
2.111	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Country Of Residence	ISO Name ISO Definition XML Tag Type Pattern	Country Of Residence Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed. CtryOfRes CountryCode [A-Z]{2,2}	
2.112	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Contact Details	ISO Name ISO Definition XML Tag Type	Contact Details Set of elements used to indicate how to contact the party. CtctDtls Contact4	
2.113	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor Account	SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type	Creditor Account Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction. CdtrAcct CashAccount38	
2.114	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor Account +++Identification	SEPA Usage Rule(s) Only IBAN is allowed. ISO Name ISO Definition XML Tag Type	Identification Unique and unambiguous identification for the account between the account owner and the account servicer. Id AccountIdentification4Choice	
	1..1		XML Tag	xs:choice	
2.115	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor Account +++Identification ++++IBAN	SEPA Rulebook ISO Name ISO Definition XML Tag Type Pattern	AT-C001 The IBAN of the account of the Beneficiary. IBAN International Bank Account Number (IBAN) - identifier used internationally by financial institutions to uniquely identify the account of a customer. Further specifications of the format and content of the IBAN can be found in the standard ISO 13616 "Banking and related financial services - International Bank Account Number (IBAN)" version 1997-10-01, or later revisions. IBAN IBAN2007Identifier [A-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}	
2.116	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor Account +++Identification ++++Other	ISO Name ISO Definition XML Tag Type	Other Unique identification of an account, as assigned by the account servicer, using an identification scheme. Othr GenericAccountIdentification1	
2.117	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor Account +++Type	ISO Name ISO Definition XML Tag Type	Type Specifies the nature, or use of the account. Tp CashAccountType2Choice	

#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements	
2.118	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor Account +++Currency	ISO Name ISO Definition XML Tag Type Pattern	Currency Identification of the currency in which the account is held. Usage: Currency should only be used in case one and the same account number covers several currencies and the initiating party needs to identify which currency needs to be used for settlement on the account. Ccy ActiveOrHistoricCurrencyCode [A-Z]{3,3}
2.119	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor Account +++Name	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Name Name of the account, as assigned by the account servicing institution, in agreement with the account owner in order to provide an additional means of identification of the account. Usage: The account name is different from the account owner name. The account name is used in certain user communities to provide a means of identifying the account, in addition to the account owner's identity and the account number. Nm Max70Text 1 .. 70 1 .. 70
2.120	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor Account +++Proxy	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-E003 The Proxy/alias of the account of the Beneficiary.</i> <i>SEPA Usage Rule(s) AT-E003 can only be provided here under the condition that the Originator is given the possibility to validate the IBAN linked to that Alias/Proxy, prior to the authentication of the instruction unless the Originator and the Originator PSP agreed upfront on another arrangement (e.g., through an amendment of the general terms and conditions).</i> <i>Furthermore, the Originator PSP must have an agreement with the Originator and the Beneficiary PSP with the Beneficiary in relation to the treatment and the use of the data provided under such Alias/Proxy i.e. whether it is to be used for the purpose to initiate the transaction and/or to forward it to the Beneficiary PSP and/or the Beneficiary concerned.</i> <i>Sub-element 'Identification' is limited to 320 characters in length.</i> Proxy Specifies an alternate assumed name for the identification of the account. Prxy ProxyAccountIdentification1
2.121	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Creditor	ISO Name ISO Definition XML Tag Type	Ultimate Creditor Ultimate party to which an amount of money is due. UltmtCdtr PartyIdentification135

#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements	
2.122	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Creditor +++Name	SEPA Rulebook SEPA Usage Rule(s) 'Name' is limited to 70 characters in length. ISO Name ISO Definition Name by which a party is known and which is usually used to identify that party. XML Tag Type ISO Length 1 .. 140 SEPA Length 1 .. 70	<i>AT-E007 The name of the Beneficiary Reference Party.</i> <i>Postal Address</i> Information that locates and identifies a specific address, as defined by postal services. PstlAdr PostalAddress24
2.123	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Creditor +++Postal Address	ISO Name ISO Definition XML Tag Type	Postal Address Information that locates and identifies a specific address, as defined by postal services. PstlAdr PostalAddress24
2.124	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Creditor +++Identification	SEPA Rulebook ISO Name ISO Definition Unique and unambiguous identification of a party. XML Tag Type	<i>AT-E010 The identification code of the Beneficiary Reference Party.</i> Identification Unique and unambiguous identification of a party. Id Party38Choice
	1..1		XML Tag	xs:choice
2.125	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Creditor +++Identification ++++Organisation Identification	SEPA Usage Rule(s) Either 'AnyBIC', 'LEI' or one occurrence of 'Other' is allowed. ISO Name ISO Definition Unique and unambiguous way to identify an organisation. XML Tag Type	Organisation Identification Unique and unambiguous way to identify an organisation. OrgId OrganisationIdentification29
2.126	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Creditor +++Identification ++++Private Identification	SEPA Usage Rule(s) Either 'Date and Place of Birth' or one occurrence of 'Other' is allowed. ISO Name ISO Definition Unique and unambiguous identification of a person, for example a passport. XML Tag Type	Private Identification Unique and unambiguous identification of a person, for example a passport. PrvtId PersonIdentification13
2.127	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Creditor +++Country Of Residence	ISO Name ISO Definition XML Tag Type Pattern	Country Of Residence Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed. CtryOfRes CountryCode [A-Z]{2,2}
2.128	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Creditor +++Contact Details	ISO Name ISO Definition XML Tag Type	Contact Details Set of elements used to indicate how to contact the party. CtctDtls Contact4
2.129	0..n	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Instruction For Creditor Agent	ISO Name ISO Definition XML Tag Type	Instruction For Creditor Agent Further information related to the processing of the payment instruction, provided by the initiating party, and intended for the creditor agent. InstrForCdtrAgt InstructionForCreditorAgent1

#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements	
2.130	0..n	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Instruction For Next Agent	ISO Name ISO Definition XML Tag Type	Instruction For Next Agent Further information related to the processing of the payment instruction that may need to be acted upon by the next agent. Usage: The next agent may not be the creditor agent. The instruction can relate to a level of service, can be an instruction that has to be executed by the agent, or can be information required by the next agent. InstrForNxtAgt InstructionForNextAgent1
2.131	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Purpose	SEPA Rulebook ISO Name ISO Definition XML Tag Type	AT-T007 Purpose of the Credit Transfer. Purpose Underlying reason for the payment transaction. Usage: Purpose is used by the end-customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain. Purp Purpose2Choice
	1..1		XML Tag	xs:choice
2.132	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Purpose +++Code	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Code Underlying reason for the payment transaction, as published in an external purpose code list. Cd ExternalPurpose1Code 1 .. 4 1 .. 4
2.133	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Purpose +++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Proprietary Purpose, in a proprietary form. Prtry Max35Text 1 .. 35 1 .. 35
2.134	0..10	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Regulatory Reporting	ISO Name ISO Definition XML Tag Type	Regulatory Reporting Information needed due to regulatory and statutory requirements. RgltryRptg RegulatoryReporting3
2.135	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Tax	ISO Name ISO Definition XML Tag Type	Tax Provides details on the tax. Tax TaxInformation8
2.136	0..10	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Related Remittance Information	ISO Name ISO Definition XML Tag Type	Related Remittance Information Provides information related to the handling of the remittance information by any of the agents in the transaction processing chain. RltdRmtInf RemittanceLocation7

#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements
2.137	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information	<p>SEPA Rulebook <i>AT-T009 Remittance Information. Note: If agreed with the Originator as per DS-01 of Annex V (Extended Remittance Information), in case the pain.001 contained an ERI and the Beneficiary PSP does not support ERI, this element can cater for AT-T010 'The unstructured Remittance Information sent by the Originator to the Beneficiary in the Credit Transfer Instruction'.</i></p> <p>SEPA Usage Rule(s) Either 'Structured' or 'Unstructured' may be present.</p> <p>ISO Name Remittance Information</p> <p>ISO Definition Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system.</p> <p>XML Tag RmtInf</p> <p>Type RemittanceInformation16</p>
2.138	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Unstructured	<p>SEPA Usage Rule(s) Only one occurrence of 'Unstructured' is allowed. 'iUnstructured' may carry structured remittance information, as agreed between the Originator and the Beneficiary. If the commercial trade name of the payee is different from its legal name (AT-E001 The name of the Beneficiary), then the commercial trade name must be provided here. The location of where the transaction took place (if different from AT-E004 The address of the Beneficiary) as well as the transaction date and time can also be provided here. Each piece of information must be followed by a slash to clearly differentiate from the other information included under this data element (a special character other than a slash can be used instead (e.g., "+") in case the slash is used for other purposes). [Example: The Shopping Paradise/Boulevard des Marchands 123/2020-12-24T11:37/Purchase Nr 1234567890AZ - Merry Christmas.] For further information, please refer to "EPC088-22 EPC Guidance Document – Improve Transparency for Retail Payment End-Users".</p> <p>ISO Name Unstructured</p> <p>ISO Definition Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in an unstructured form.</p> <p>XML Tag Ustrd</p> <p>Type Max140Text</p> <p>ISO Length 1 .. 140</p> <p>SEPA Length 1 .. 140</p>

#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements		
2.139	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured	SEPA Usage Rule(s) Only one occurrence of 'Structured' is allowed. SEPA Format Rule(s) ISO Name ISO Definition XML Tag Type	Only one occurrence of 'Structured' is allowed. 'Structured' can be used, provided the tags and the data within the 'Structured' element (i.e. excluding <Strd> and </Strd>) do not exceed 140 characters in length. Structured Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in a structured form. Strd StructuredRemittanceInformation16	
2.140	0..n	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Referred Document Information	ISO Name ISO Definition XML Tag Type	Referred Document Information Provides the identification and the content of the referred document. RfrdDocInf ReferredDocumentInformation7	
2.141	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Referred Document Amount	ISO Name ISO Definition XML Tag Type	Referred Document Amount Provides details on the amounts of the referred document. RfrdDocAmt RemittanceAmount2	
2.142	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Creditor Reference Information	SEPA Usage Rule(s) When present, the Creditor PSP is not obliged to validate the reference information. When used both 'Type' and 'Reference' must be present. ISO Name ISO Definition XML Tag Type	Creditor Reference Information Reference information provided by the creditor to allow the identification of the underlying documents. CdtrRefInf CreditorReferenceInformation2	
2.143	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Creditor Reference Information +++++Type	SEPA Usage Rule(s) Mandatory if 'Creditor Reference Information' is used. ISO Name ISO Definition XML Tag Type	Type Specifies the type of creditor reference. Tp CreditorReferenceType2	
2.144	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Creditor Reference Information +++++Type ++++++Code Or Proprietary	ISO Name ISO Definition XML Tag Type	Code Or Proprietary Coded or proprietary format creditor reference type. CdOrPrtry CreditorReferenceType1Choice	
	1..1		XML Tag	xs:choice	
2.145	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Creditor Reference Information +++++Type ++++++Code Or Proprietary ++++++Code	SEPA Usage Rule(s) Only "SCOR" is allowed. ISO Name ISO Definition XML Tag Type SEPA Code Restrictions SCOR	Code Type of creditor reference, in a coded form. Cd DocumentType3Code <i>StructuredCommunicationReference Document is a structured communication reference provided by the creditor to identify the referred transaction.</i>	

#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements	
2.146	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Creditor Reference Information +++++Type ++++++Code Or Proprietary ++++++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Proprietary Creditor reference type, in a proprietary form. Prtry Max35Text 1 .. 35 1 .. 35
2.147	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Creditor Reference Information +++++Type ++++++Issuer	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	SEPA Usage Rule(s) <i>Mandatory if 'Reference' is populated with an identifier issued or governed by a known institution. E.g. "ISO" should be mentioned here if 'Reference' is populated with a RF Creditor Reference (ISO 11649).</i> Issuer Entity that assigns the credit reference type. Issr Max35Text 1 .. 35 1 .. 35
2.148	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Creditor Reference Information +++++Reference	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	SEPA Usage Rule(s) <i>Mandatory if 'Creditor Reference Information' is used.</i> <i>If a Creditor Reference contains a check digit, the receiving PSP is not required to validate this.</i> <i>If the receiving PSP validates the check digit and if this validation fails, the PSP may continue its processing and send the transaction to the next party in the chain.</i> <i>RF Creditor Reference must be used (ISO 11649) in case "ISO" is mentioned under 'Issuer'.</i> Reference Unique reference, as assigned by the creditor, to unambiguously refer to the payment transaction. Usage: If available, the initiating party should provide this reference in the structured remittance information, to enable reconciliation by the creditor upon receipt of the amount of money. If the business context requires the use of a creditor reference or a payment remit identification, and only one identifier can be passed through the end-to-end chain, the creditor's reference or payment remittance identification should be quoted in the end-to-end transaction identification.
2.149	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Invoicer	ISO Name ISO Definition XML Tag Type	Invoicer Identification of the organisation issuing the invoice, when it is different from the creditor or ultimate creditor. Invcr PartyIdentification135
2.150	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Invoicee	ISO Name ISO Definition XML Tag Type	Invoicee Identification of the party to whom an invoice is issued, when it is different from the debtor or ultimate debtor. Invcee PartyIdentification135

#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements		
2.151	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Tax Remittance	ISO Name ISO Definition XML Tag Type	Tax Remittance Provides remittance information about a payment made for tax-related purposes. TaxRmt TaxInformation7	
2.152	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Garnishment Remittance	ISO Name ISO Definition XML Tag Type	Garnishment Remittance Provides remittance information about a payment for garnishment-related purposes. GrnshmtRmt Garnishment3	
2.153	0..3	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Additional Remittance Information	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Additional Remittance Information Additional information, in free text form, to complement the structured remittance information. AddtlRmtInf Max140Text 1 .. 140 1 .. 140	
2.154	0..n	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Supplementary Data	ISO Name ISO Definition XML Tag Type	Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block. SplmtryData SupplementaryData1	
3.0	0..n	FITo FICustomer Credit Transfer V08 +Supplementary Data	ISO Name ISO Definition XML Tag Type	Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block. SplmtryData SupplementaryData1	



2.2 Inter-PSP Return SEPA Credit Transfer Dataset (DS-03)

2.2.1 Use of the Payment Return (pacs.004.001.09)

The message is used to transport the Credit Transfer Return instruction between PSPs, directly or through intermediaries.

The message can also be used to return instructions of SEPA Credit Transfers with Extended Remittance Information (ERI, please refer to section 'Inter-PSP payment with use of the Extended Remittance Information option' below) whereby only AT-T010 'The unstructured Remittance Information sent by the Originator to the Beneficiary in the SEPA Credit Transfer Instruction' will be forwarded.

The message caters for bulk and single return instructions.

Note: Attribute AT-R001 'The Type of R-message' is implied by the 'Message Name', 'pacs.004.001.09', and the 'Original Message Name Identification' must begin with pacs.008 (the addition of a variant number and version number is optional).

Note: Message elements under 'Original Transaction Reference' sequence are based on DS-02 attributes.

#	SEPA Mult	Message Element	Inter-PSP Return Credit Transfer SEPA Core Requirements	
		Document	XML Tag Type	Document Document
	1..1	Payment Return V09	ISO Name ISO Definition	Payment Return V09 Scope The PaymentReturn message is sent by an agent to the previous agent in the payment chain to undo a payment previously settled.
			XML Tag Type	PmtRtr PaymentReturnV09
1.0	1..1	Payment Return V09 +Group Header	ISO Name ISO Definition	Group Header Set of characteristics shared by all individual transactions included in the message.
			XML Tag Type	GrpHdr GroupHeader90
1.1	1..1	Payment Return V09 +Group Header ++Message Identification	ISO Name ISO Definition	Message Identification Point to point reference, as assigned by the instructing party and sent to the next party in the chain, to unambiguously identify the message. Usage: The instructing party has to make sure that MessageIdentification is unique per instructed party for a pre-agreed period.
			XML Tag Type ISO Length SEPA Length	MsgId Max35Text 1 .. 35 1 .. 35
1.2	1..1	Payment Return V09 +Group Header ++Creation Date Time	ISO Name ISO Definition	Creation Date Time Date and time at which the message was created.
			XML Tag Type	CreDtTm ISODateTime
1.3	0..2	Payment Return V09 +Group Header ++Authorisation	ISO Name ISO Definition	Authorisation User identification or any user key to be used to check whether the initiating party is allowed to initiate transactions from the account specified in the message.
			XML Tag Type	Usage: The content is not of a technical nature, but reflects the organisational structure at the initiating side. The authorisation element can typically be used in relay scenarios, payment initiations, payment returns or payment reversals that are initiated on behalf of a party different from the initiating party. Authstn Authorisation1Choice
1.4	0..1	Payment Return V09 +Group Header ++Batch Booking	ISO Name ISO Definition	Batch Booking Identifies whether a single entry per individual transaction or a batch entry for the sum of the amounts of all transactions within the group of a message is requested.
			XML Tag Type	Usage: Batch booking is used to request and not order a possible batch booking. BtchBookg BatchBookingIndicator
1.5	1..1	Payment Return V09 +Group Header ++Number Of Transactions	ISO Name ISO Definition	Number Of Transactions Number of individual transactions contained in the message.
			XML Tag Type Pattern	NbOfTx Max15NumericText [0-9]{1,15}

#	SEPA Mult	Message Element	Inter-PSP Return Credit Transfer SEPA Core Requirements	
1.6	0..1	Payment Return V09 +Group Header ++Control Sum	ISO Name ISO Definition XML Tag Type <i>SEPA FractDigits</i> TotalDigits	Control Sum Total of all individual amounts included in the message, irrespective of currencies. CtrlSum DecimalNumber 17 18
1.7	0..1	Payment Return V09 +Group Header ++Group Return	ISO Name ISO Definition XML Tag Type	Group Return Indicates whether the return applies to the whole group of transactions or to individual transactions within the original group(s). GrpRtr TrueFalseIndicator
1.8	1..1	Payment Return V09 +Group Header ++Total Returned Interbank Settlement Amount	<i>SEPA Usage Rule(s)</i> Mandatory. <i>Only 'EUR' is allowed.</i> <i>Amount must be 0.01 or more and 999999999999.99 or less.</i> <i>The fractional part has a maximum of two digits.</i> <i>SEPA Format Rule(s)</i> ISO Name ISO Definition XML Tag Type <i>SEPA FractDigits</i> TotalDigits <i>SEPA Inclusive</i>	Total Returned Interbank Settlement Amount Total amount of money moved between the instructing agent and the instructed agent in the return message. TtlRtrdIntrBkSttlmAmt ActiveCurrencyAndAmount 2 18 0.01 .. 999999999999.99
1.9	1..1	Payment Return V09 +Group Header ++Interbank Settlement Date	<i>SEPA Rulebook</i> <i>SEPA Usage Rule(s)</i> Mandatory. ISO Name ISO Definition XML Tag Type	<i>AT-R005 Settlement Date for the Return.</i> Interbank Settlement Date Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. IntrBkSttlmDt ISODate
1.10	1..1	Payment Return V09 +Group Header ++Settlement Information	ISO Name ISO Definition XML Tag Type	Settlement Information Specifies the details on how the settlement of the transaction(s) between the instructing agent and the instructed agent is completed. SttlmInf SettlementInstruction7
1.11	1..1	Payment Return V09 +Group Header ++Settlement Information +++Settlement Method	<i>SEPA Usage Rule(s)</i> Only "CLRG", "INGA" and "INDA" are allowed. ISO Name ISO Definition XML Tag Type <i>SEPA Code Restrictions</i> <i>CLRG</i> <i>INDA</i> <i>INGA</i>	Settlement Method Method used to settle the (batch of) payment instructions. SttlmMtd SettlementMethod1Code <i>ClearingSystem</i> <i>Settlement is done through a payment clearing system.</i> <i>InstructedAgent</i> <i>Settlement is done by the agent instructed to execute a payment instruction.</i> <i>InstructingAgent</i> <i>Settlement is done by the agent instructing and forwarding the payment to the next party in the payment chain.</i>

#	SEPA Mult	Message Element	Inter-PSP Return Credit Transfer SEPA Core Requirements
1.12	0..1	Payment Return V09 +Group Header ++Settlement Information +++Settlement Account	<p>SEPA Usage Rule(s) Only 'Identification' is allowed.</p> <p>ISO Name Settlement Account</p> <p>ISO Definition A specific purpose account used to post debit and credit entries as a result of the transaction.</p> <p>XML Tag Type SttlmAcct CashAccount38</p>
1.13	0..1	Payment Return V09 +Group Header ++Settlement Information +++Clearing System	<p>ISO Name Clearing System</p> <p>ISO Definition Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed.</p> <p>XML Tag Type ClrSys ClearingSystemIdentification3Choice</p>
	1..1		XML Tag xs:choice
1.14	1..1	Payment Return V09 +Group Header ++Settlement Information +++Clearing System ++++Code	<p>ISO Name Code</p> <p>ISO Definition Infrastructure through which the payment instruction is processed, as published in an external clearing system identification code list.</p> <p>XML Tag Type Cd ExternalCashClearingSystem1Code</p> <p>ISO Length 1 .. 3 SEPA Length 1 .. 3</p>
1.15	1..1	Payment Return V09 +Group Header ++Settlement Information +++Clearing System ++++Proprietary	<p>ISO Name Proprietary</p> <p>ISO Definition Clearing system identification in a proprietary form.</p> <p>XML Tag Type Prtry Max35Text</p> <p>ISO Length 1 .. 35 SEPA Length 1 .. 35</p>
1.16	0..1	Payment Return V09 +Group Header ++Settlement Information +++Instructing Reimbursement Agent	<p>ISO Name Instructing Reimbursement Agent</p> <p>ISO Definition Agent through which the instructing agent will reimburse the instructed agent.</p> <p>XML Tag Type InstgRmbrsmntAgt BranchAndFinancialInstitutionIdentification6</p> <p>Usage: If InstructingAgent and InstructedAgent have the same reimbursement agent, then only InstructingReimbursementAgent must be used.</p>
1.17	0..1	Payment Return V09 +Group Header ++Settlement Information +++Instructing Reimbursement Agent Account	<p>ISO Name Instructing Reimbursement Agent Account</p> <p>ISO Definition Unambiguous identification of the account of the instructing reimbursement agent account at its servicing agent in the payment chain.</p> <p>XML Tag Type InstgRmbrsmntAgtAcct CashAccount38</p>
1.18	0..1	Payment Return V09 +Group Header ++Settlement Information +++Instructed Reimbursement Agent	<p>ISO Name Instructed Reimbursement Agent</p> <p>ISO Definition Agent at which the instructed agent will be reimbursed.</p> <p>XML Tag Type InstdRmbrsmntAgt BranchAndFinancialInstitutionIdentification6</p> <p>Usage: If InstructedReimbursementAgent contains a branch of the InstructedAgent, then the party in InstructedAgent will claim reimbursement from that branch/will be paid by that branch.</p> <p>Usage: If InstructingAgent and InstructedAgent have the same reimbursement agent, then only InstructingReimbursementAgent must be used.</p>
1.19	0..1	Payment Return V09 +Group Header ++Settlement Information +++Instructed Reimbursement Agent Account	<p>ISO Name Instructed Reimbursement Agent Account</p> <p>ISO Definition Unambiguous identification of the account of the instructed reimbursement agent account at its servicing agent in the payment chain.</p> <p>XML Tag Type InstdRmbrsmntAgtAcct CashAccount38</p>

#	SEPA Mult	Message Element	Inter-PSP Return Credit Transfer SEPA Core Requirements	
1.20	0..1	Payment Return V09 +Group Header ++Settlement Information +++Third Reimbursement Agent	ISO Name ISO Definition XML Tag Type	Third Reimbursement Agent Agent at which the instructed agent will be reimbursed. Usage: If ThirdReimbursementAgent contains a branch of the InstructedAgent, then the party in InstructedAgent will claim reimbursement from that branch/will be paid by that branch. ThrdRmbrsmntAgt BranchAndFinancialInstitutionIdentification6
1.21	0..1	Payment Return V09 +Group Header ++Settlement Information +++Third Reimbursement Agent Account	ISO Name ISO Definition XML Tag Type	Third Reimbursement Agent Account Unambiguous identification of the account of the third reimbursement agent account at its servicing agent in the payment chain. ThrdRmbrsmntAgtAcct CashAccount38
1.22	0..1	Payment Return V09 +Group Header ++Instructing Agent	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Only 'BICFI' is allowed. Instructing Agent Agent that instructs the next party in the chain to carry out the (set of) instruction(s). Usage: The instructing agent is the party sending the return message and not the party that sent the original instruction that is being returned. InstgAgt BranchAndFinancialInstitutionIdentification6
1.23	0..1	Payment Return V09 +Group Header ++Instructed Agent	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Only 'BICFI' is allowed. Instructed Agent Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s). Usage: The instructed agent is the party receiving the return message and not the party that received the original instruction that is being returned. InstdAgt BranchAndFinancialInstitutionIdentification6
2.0	0..1	Payment Return V09 +Original Group Information	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Sub-elements of 'Original Group Information' must be present in either 'Original Group Information' or in 'Transaction Information'. Original Group Information Information concerning the original group of transactions, to which the message refers. OrgnlGrpInf OriginalGroupHeader18
2.1	1..1	Payment Return V09 +Original Group Information ++Original Message Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Message Identification Point to point reference, as assigned by the original instructing party, to unambiguously identify the original message. OrgnlMsgId Max35Text 1 .. 35 1 .. 35
2.2	1..1	Payment Return V09 +Original Group Information ++Original Message Name Identification	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Must begin with 'pacs.008'. The addition of a variant number and version number is optional. Original Message Name Identification Specifies the original message name identifier to which the message refers. OrgnlMsgNmId Max35Text 1 .. 35 1 .. 35
2.3	0..1	Payment Return V09 +Original Group Information ++Original Creation Date Time	ISO Name ISO Definition XML Tag Type	Original Creation Date Time Date and time at which the original message was created. OrgnlCreDtTm ISODateTime

#	SEPA Mult	Message Element	Inter-PSP Return Credit Transfer SEPA Core Requirements	
2.4	0..n	Payment Return V09 +Original Group Information ++Return Reason Information	ISO Name ISO Definition XML Tag Type	Return Reason Information Provides detailed information on the return reason. RtrRsnInf PaymentReturnReason6
3.0	1..n	Payment Return V09 +Transaction Information	SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type	Mandatory. Transaction Information Information concerning the original transactions, to which the return message refers. TxInf PaymentTransaction112
3.1	1..1	Payment Return V09 +Transaction Information ++Return Identification	SEPA Rulebook SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	AT-R003 Specific Reference of the PSP Initiating the Return. Mandatory. Return Identification Unique identification, as assigned by an instructing party for an instructed party, to unambiguously identify the returned transaction. Usage: The instructing party is the party sending the return message and not the party that sent the original instruction that is being returned. RtrId Max35Text 1 .. 35 1 .. 35
3.2	0..1	Payment Return V09 +Transaction Information ++Original Group Information	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Sub-elements of 'Original Group Information' must be present in either 'Original Group Information' or in 'Transaction Information'. Original Group Information Provides information on the original message. OrgnlGrpInf OriginalGroupInformation29
3.3	1..1	Payment Return V09 +Transaction Information ++Original Group Information +++Original Message Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Message Identification Point to point reference assigned by the original instructing party to unambiguously identify the original message. OrgnlMsgId Max35Text 1 .. 35 1 .. 35
3.4	1..1	Payment Return V09 +Transaction Information ++Original Group Information +++Original Message Name Identification	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Must begin with 'pacs.008'. The addition of a variant number and version number is optional. Original Message Name Identification Specifies the original message name identifier to which the message refers, for example, pacs.003.001.01 or MT103. OrgnlMsgNmId Max35Text 1 .. 35 1 .. 35
3.5	0..1	Payment Return V09 +Transaction Information ++Original Group Information +++Original Creation Date Time	ISO Name ISO Definition XML Tag Type	Original Creation Date Time Original date and time at which the message was created. OrgnlCreDtTm ISODateTime

#	SEPA Mult	Message Element	Inter-PSP Return Credit Transfer SEPA Core Requirements	
3.6	0..1	Payment Return V09 +Transaction Information ++Original Instruction Identification	<p>SEPA Usage Rule(s) <i>Mandatory if provided in the original instruction.</i></p> <p>ISO Name Original Instruction Identification</p> <p>ISO Definition Unique identification, as assigned by the original instructing party for the original instructed party, to unambiguously identify the original instruction.</p> <p>XML Tag OrgnlInstrId</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>	
3.7	1..1	Payment Return V09 +Transaction Information ++Original End To End Identification	<p>SEPA Rulebook <i>AT-T014 The Originator's reference of the SEPA Credit Transfer Transaction.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name Original End To End Identification</p> <p>ISO Definition Unique identification, as assigned by the original initiating party, to unambiguously identify the original transaction.</p> <p>XML Tag OrgnlEndToEndId</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>	
3.8	1..1	Payment Return V09 +Transaction Information ++Original Transaction Identification	<p>SEPA Rulebook <i>AT-T054 The Originator PSP's reference of the SEPA Credit Transfer Transaction.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p><i>Must contain a reference that is meaningful to the Originator's PSP and is unique over time.</i></p> <p>ISO Name Original Transaction Identification</p> <p>ISO Definition Unique identification, as assigned by the original first instructing agent, to unambiguously identify the transaction.</p> <p>XML Tag OrgnlTxId</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>	
3.9	0..1	Payment Return V09 +Transaction Information ++Original UETR	<p>ISO Name Original UETR</p> <p>ISO Definition Universally unique identifier to provide the original end-to-end reference of a payment transaction.</p> <p>XML Tag OrgnlUETR</p> <p>Type UUIDv4Identifier</p> <p>Pattern [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}</p>	
3.10	0..1	Payment Return V09 +Transaction Information ++Original Clearing System Reference	<p>ISO Name Original Clearing System Reference</p> <p>ISO Definition Unique reference, as assigned by the original clearing system, to unambiguously identify the original instruction.</p> <p>XML Tag OrgnlClrSysRef</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>	

#	SEPA Mult	Message Element	Inter-PSP Return Credit Transfer SEPA Core Requirements	
3.11	1..1	Payment Return V09 +Transaction Information ++Original Interbank Settlement Amount	<p>SEPA Rulebook AT-T002 <i>Amount of the SEPA Credit Transfer in Euro.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i> <i>Only 'EUR' is allowed.</i> <i>Amount must be 0.01 or more and 99999999.99 or less.</i> <i>The fractional part has a maximum of two digits.</i></p> <p>SEPA Format Rule(s)</p> <p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag</p> <p>Type</p> <p>SEPA FractDigits</p> <p>TotalDigits</p> <p>SEPA Inclusive</p>	Original Interbank Settlement Amount Amount of money moved between the instructing agent and the instructed agent, as provided in the original instruction. OrgnlIntrBkSttlmAmt ActiveOrHistoricCurrencyAndAmount 2 18 0.01 .. 99999999.99
3.12	0..1	Payment Return V09 +Transaction Information ++Original Interbank Settlement Date	<p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag</p> <p>Type</p>	Original Interbank Settlement Date Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. Usage: the OriginalInterbankSettlementDate is the interbank settlement date of the original instruction return message, and not of the return message. OrgnlIntrBkSttlmDt ISODate
3.13	1..1	Payment Return V09 +Transaction Information ++Returned Interbank Settlement Amount	<p>SEPA Rulebook AT-T002 <i>Amount of the SEPA Credit Transfer in Euro.</i></p> <p>SEPA Usage Rule(s) <i>The amount must be the same as in 'Original Interbank Settlement Amount'.</i> <i>Only 'EUR' is allowed.</i> <i>Amount must be 0.01 or more and 99999999.99 or less.</i> <i>The fractional part has a maximum of two digits.</i></p> <p>SEPA Format Rule(s)</p> <p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag</p> <p>Type</p> <p>SEPA FractDigits</p> <p>TotalDigits</p> <p>SEPA Inclusive</p>	Returned Interbank Settlement Amount Amount of money to be moved between the instructing agent and the instructed agent in the returned instruction. RtrdIntrBkSttlmAmt ActiveCurrencyAndAmount 2 18 0.01 .. 99999999.99
3.14	0..1	Payment Return V09 +Transaction Information ++Interbank Settlement Date	<p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag</p> <p>Type</p>	Interbank Settlement Date Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. Usage: the InterbankSettlementDate is the interbank settlement date of the return message, and not of the original instruction. IntrBkSttlmDt ISODate

#	SEPA Mult	Message Element	Inter-PSP Return Credit Transfer SEPA Core Requirements	
3.15	0..1	Payment Return V09 +Transaction Information ++Settlement Priority	ISO Name ISO Definition	Settlement Priority Indicator of the urgency or order of importance that the instructing party would like the instructed party to apply to the processing of the settlement instruction.
			XML Tag Type	Usage: the SettlementPriority is the settlement priority of the return message, and not of the original instruction. SttlmPrty Priority3Code
3.16	0..1	Payment Return V09 +Transaction Information ++Settlement Time Indication	ISO Name ISO Definition	Settlement Time Indication Provides information on the occurred settlement time(s) of the payment transaction.
			XML Tag Type	SttlmTmIndctn SettlementDateTimeIndication1
3.17	0..1	Payment Return V09 +Transaction Information ++Returned Instructed Amount	ISO Name ISO Definition	Returned Instructed Amount Amount of money to be moved between the debtor and the creditor, before deduction of charges, in the returned transaction.
			XML Tag Type	Usage: This amount has to be transported unchanged through the transaction chain. RtrdInstdAmt ActiveOrHistoricCurrencyAndAmount
			SEPA FractDigits	5
			TotalDigits	18
			SEPA Inclusive	0 ..
3.18	0..1	Payment Return V09 +Transaction Information ++Exchange Rate	ISO Name ISO Definition	Exchange Rate Factor used to convert an amount from one currency into another. This reflects the price at which one currency was bought with another currency.
			XML Tag Type	XchgRate BaseOneRate
			SEPA FractDigits	10
			TotalDigits	11
3.19	0..1	Payment Return V09 +Transaction Information ++Compensation Amount	ISO Name ISO Definition	Compensation Amount Amount of money asked or paid as compensation for the processing of the instruction.
			XML Tag Type	CompstnAmt ActiveOrHistoricCurrencyAndAmount
			SEPA FractDigits	5
			TotalDigits	18
			SEPA Inclusive	0 ..
3.20	0..1	Payment Return V09 +Transaction Information ++Charge Bearer	SEPA Usage Rule(s) ISO Name ISO Definition	Only "SLEV" is allowed. Charge Bearer Specifies which party/parties will bear the charges associated with the processing of the payment transaction.
			XML Tag Type	Usage: The ChargeBearer applies to the return message, not to the original instruction. ChrgBr ChargeBearerType1Code
			SEPA Code Restrictions	
			SLEV	FollowingServiceLevel Charges are to be applied following the rules agreed in the service level and/or scheme.

#	SEPA Mult	Message Element	Inter-PSP Return Credit Transfer SEPA Core Requirements	
3.21	0..n	Payment Return V09 +Transaction Information ++Charges Information	ISO Name ISO Definition XML Tag Type	Charges Information Provides information on the charges to be paid by the charge bearer(s) related to the processing of the return transaction. ChrgsInf Charges7
3.22	0..1	Payment Return V09 +Transaction Information ++Clearing System Reference	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Clearing System Reference Unique reference, as assigned by the clearing system, to unambiguously identify the return instruction. ClrSysRef Max35Text 1 .. 35 1 .. 35
3.23	0..1	Payment Return V09 +Transaction Information ++Instructing Agent	SEPA Usage Rule(s) Only 'BICFI' is allowed. ISO Name ISO Definition XML Tag Type	Instructing Agent Agent that instructs the next party in the chain to carry out the (set of) instruction(s). Usage: The instructing agent is the party sending the return message and not the party that sent the original instruction that is being returned. InstgAgt BranchAndFinancialInstitutionIdentification6
3.24	0..1	Payment Return V09 +Transaction Information ++Instructed Agent	SEPA Usage Rule(s) Only 'BICFI' is allowed. ISO Name ISO Definition XML Tag Type	Instructed Agent Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s). Usage: The instructed agent is the party receiving the return message and not the party that received the original instruction that is being returned. InstdAgt BranchAndFinancialInstitutionIdentification6
3.25	0..1	Payment Return V09 +Transaction Information ++Return Chain	ISO Name ISO Definition XML Tag Type	Return Chain Provides all parties (agents and non-agents) involved in a return transaction. RtrChain TransactionParties7
3.26	1..1	Payment Return V09 +Transaction Information ++Return Reason Information	SEPA Usage Rule(s) Mandatory. Only one occurrence of 'Return Reason Information' is allowed. ISO Name ISO Definition XML Tag Type	Return Reason Information Provides detailed information on the return reason. RtrRsnInf PaymentReturnReason6
3.27	1..1	Payment Return V09 +Transaction Information ++Return Reason Information +++Originator	SEPA Rulebook SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type	AT-R002 Identification of the type of party initiating the "R"-message. Limited to 'AnyBIC' for an Agent or 'Name' for a non-financial institution. 'Name' is limited to 70 characters in length. Originator Party that issues the return. Orgtr PartyIdentification135

#	SEPA Mult	Message Element	Inter-PSP Return Credit Transfer SEPA Core Requirements	
3.28	1..1	Payment Return V09 +Transaction Information ++Return Reason Information +++Reason	SEPA Rulebook SEPA Usage Rule(s) Mandatory. ISO Name Reason ISO Definition Specifies the reason for the return. XML Tag Rsn Type ReturnReason5Choice	<i>AT-R004 Reason Code for Non-Acceptance of the credit transfer.</i> <i>See Message Element Specifications below.</i>
	1..1		XML Tag	xs:choice
3.29	1..1	Payment Return V09 +Transaction Information ++Return Reason Information +++Reason ++++Code	SEPA Rulebook ISO Name ISO Definition Reason for the return, as published in an external reason code list. XML Tag Cd Type ExternalReturnReason1Code ISO Length 1 .. 4 SEPA Length 1 .. 4	
3.30	1..1	Payment Return V09 +Transaction Information ++Return Reason Information +++Reason ++++Proprietary	ISO Name ISO Definition XML Tag Prtry Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35	Proprietary Reason for the return, in a proprietary form.
3.31	0..1	Payment Return V09 +Transaction Information ++Return Reason Information +++Additional Information	ISO Name ISO Definition XML Tag AddtlInf Type Max105Text ISO Length 1 .. 105 SEPA Length 1 .. 105	Additional Information Further details on the return reason.
3.32	1..1	Payment Return V09 +Transaction Information ++Original Transaction Reference	SEPA Rulebook SEPA Usage Rule(s) Mandatory ISO Name ISO Definition The message elements under 'Original Transaction Reference' must be populated with the same value as the message elements of the original instruction. XML Tag OrgnlTxRef Type OriginalTransactionReference28	<i>An exact copy of all attributes of the received DS-02 which is being returned.</i> <i>The message elements under 'Original Transaction Reference' must be populated with the same value as the message elements of the original instruction.</i> <i>Original Transaction Reference</i> <i>Key elements used to identify the original transaction that is being referred to.</i>
3.33	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Interbank Settlement Amount	ISO Name ISO Definition XML Tag IntrBkStlmtAmt Type ActiveOrHistoricCurrencyAndAmount SEPA FractDigits 5 TotalDigits 18 SEPA Inclusive 0 .. .	Interbank Settlement Amount Amount of money moved between the instructing agent and the instructed agent.
3.34	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Amount	ISO Name ISO Definition XML Tag Amt Type AmountType4Choice	Amount Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.
3.35	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Interbank Settlement Date	SEPA Rulebook ISO Name ISO Definition XML Tag IntrBkStlmtDt Type ISODate	<i>AT-T051 Settlement Date of the credit transfer.</i> <i>Interbank Settlement Date</i> <i>Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.</i>

#	SEPA Mult	Message Element	Inter-PSP Return Credit Transfer SEPA Core Requirements	
3.36	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Requested Collection Date	ISO Name ISO Definition XML Tag Type	Requested Collection Date Date and time at which the creditor requests that the amount of money is to be collected from the debtor. ReqdColltnDt ISODate
3.37	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Requested Execution Date	ISO Name ISO Definition XML Tag Type	Requested Execution Date Date at which the initiating party requests the clearing agent to process the payment. Usage: This is the date on which the debtor's account is to be debited. If payment by cheque, the date when the cheque must be generated by the bank. ReqdExctnDt DateAndDateTime2Choice
3.38	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Creditor Scheme Identification	ISO Name ISO Definition XML Tag Type	Creditor Scheme Identification Credit party that signs the mandate. CdtrSchmeId PartyIdentification135
3.39	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Settlement Information	ISO Name ISO Definition XML Tag Type	Settlement Information Specifies the details on how the settlement of the original transaction(s) between the instructing agent and the instructed agent was completed. SttlmInf SettlementInstruction7
3.40	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Payment Type Information	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-T001 Identification code of the Scheme.</i> <i>AT-T008 Category purpose of the Credit Transfer.</i> <i>If the original transaction was sent according to Annex V (Extended Remittance Information) of the SCT Rulebook (refer to section 'Inter-PSP payment with use of the Extended Remittance Information option' below), then 'Local Instrument/Code' must be populated with "PERI" (Payment with Extended Remittance Information).</i> Payment Type Information Set of elements used to further specify the type of transaction. PmtTpInf PaymentTypeInformation27
3.41	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Payment Method	ISO Name ISO Definition XML Tag Type	Payment Method Specifies the means of payment that will be used to move the amount of money. PmtMtd PaymentMethod4Code
3.42	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Mandate Related Information	ISO Name ISO Definition XML Tag Type	Mandate Related Information Provides further details of the mandate signed between the creditor and the debtor. MndtRltdInf MandateRelatedInformation14

#	SEPA Mult	Message Element	Inter-PSP Return Credit Transfer SEPA Core Requirements	
3.43	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Remittance Information	<p>SEPA Rulebook</p> <p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p><i>AT-T009 Remittance information or AT-T010 The unstructured Remittance Information sent by the Originator to the Beneficiary in the Credit Transfer Instruction (in case of use of the Extended Remittance Information (ERI) option in the original SEPA Credit Transfer, AT-T011 The structured Remittance Information sent by the Originator to the Beneficiary in the SEPA Credit Transfer Instruction, will NOT be transported here).</i></p> <p>Remittance Information</p> <p>Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system.</p> <p>RmtlInf</p> <p>RemittanceInformation16</p>
3.44	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Ultimate Debtor	<p>SEPA Rulebook</p> <p>SEPA Usage Rule(s)</p> <p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p><i>AT-P006 The name of the Originator Reference Party.</i></p> <p><i>AT-P007 The identification code of the Originator Reference Party.</i></p> <p><i>Only 'Party' is allowed.</i></p> <p>Ultimate Debtor</p> <p>Ultimate party that owes an amount of money to the (ultimate) creditor.</p> <p>UltmtDbtr</p> <p>Party40Choice</p>
3.45	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Debtor	<p>SEPA Rulebook</p> <p>SEPA Usage Rule(s)</p> <p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p><i>AT-P001 Name of the Originator.</i></p> <p><i>AT-P005 Address of the Originator.</i></p> <p><i>AT-P004 Originator identification code.</i></p> <p><i>Only 'Party' is allowed.</i></p> <p>Debtor</p> <p>Party that owes an amount of money to the (ultimate) creditor.</p> <p>Dbtr</p> <p>Party40Choice</p>
3.46	1..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Debtor Account	<p>SEPA Rulebook</p> <p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p><i>AT-D001 The IBAN of the account of the Originator.</i></p> <p><i>AT-P003 The Proxy/Alias of the account of the Originator.</i></p> <p>Debtor Account</p> <p>Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction.</p> <p>DbtrAcct</p> <p>CashAccount38</p>
3.47	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Debtor Agent	<p>SEPA Rulebook</p> <p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p><i>AT-D002 The BIC code of the Originator PSP.</i></p> <p>Debtor Agent</p> <p>Financial institution servicing an account for the debtor.</p> <p>DbtrAgnt</p> <p>BranchAndFinancialInstitutionIdentification6</p>
3.48	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Debtor Agent Account	<p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p>Debtor Agent Account</p> <p>Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain.</p> <p>DbtrAgtAcct</p> <p>CashAccount38</p>

#	SEPA Mult	Message Element	Inter-PSP Return Credit Transfer SEPA Core Requirements	
3.49	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Creditor Agent	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-C002 The BIC code of the Beneficiary PSP.</i> Creditor Agent Financial institution servicing an account for the creditor. CdtrAgt BranchAndFinancialInstitutionIdentification6
3.50	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Creditor Agent Account	ISO Name ISO Definition XML Tag Type	Creditor Agent Account Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction. CdtrAgtAcct CashAccount38
3.51	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Creditor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-E001 Name of the Beneficiary.</i> <i>AT-E004 Address of the Beneficiary.</i> <i>AT-E005 Beneficiary identification code.</i> Only 'Party' is allowed. Creditor Party to which an amount of money is due. Cdtr Party40Choice
3.52	1..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Creditor Account	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-C001 IBAN of the Beneficiary.</i> <i>AT-E003 The Proxy/Alias of the account of the Beneficiary.</i> Creditor Account Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction. CdtrAcct CashAccount38
3.53	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Ultimate Creditor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-E007 The name of the Beneficiary Reference Party.</i> <i>AT-E010 The identification code of the Beneficiary Reference Party.</i> Only 'Party' is allowed. Ultimate Creditor Ultimate party to which an amount of money is due. UltmtCdtr Party40Choice
3.54	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Purpose	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-T007 The purpose of the SEPA Credit Transfer.</i> Purpose Underlying reason for the payment transaction. Usage: Purpose is used by the end customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain. Purp Purpose2Choice
3.55	0..n	Payment Return V09 +Transaction Information ++Supplementary Data	ISO Name ISO Definition XML Tag Type	Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block. SplmtryData SupplementaryData1

#	SEPA Mult	Message Element	Inter-PSP Return Credit Transfer SEPA Core Requirements	
4.0	0..n	Payment Return V09 +Supplementary Data	ISO Name ISO Definition XML Tag Type	Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block. SplmtryData SupplementaryData1

2.2.2 Message Element Specifications

Reasons for an inter-PSP **return** present in the Rulebook are mapped to the ISO codes as follows:

ISO Code	ISO Name	SEPA Core Reason as specified in the Rulebook
AC01	IncorrectAccountNumber	Account identifier invalid (i.e. invalid IBAN or account number does not exist)
AC04	ClosedAccountNumber	Account closed
AC06	BlockedAccount	Account blocked, reason not specified
AG01	TransactionForbidden	Credit transfer forbidden on this type of account (e.g. savings account)
AG02	InvalidBankOperationCode	Operation/transaction code incorrect, invalid file format <i>Usage Rule:</i> To be used for incorrect 'operation/transaction' code or invalid file format.
AM05	Duplication	Duplicate payment
BE04	MissingCreditorAddress	Account address invalid
CNOR	Creditor bank is not registered	Creditor PSP is not registered under this BIC in the CSM
ERIN	ERIOptionNotSupported	The Extended Remittance Information (ERI) option is not supported
MD07	EndCustomerDeceased	Beneficiary deceased
MS02	NotSpecifiedReasonCustomerGenerated	By order of the Beneficiary
MS03	NotSpecifiedReasonAgentGenerated	Reason not specified
RC01	BankIdentifierIncorrect	PSP identifier incorrect, eg, invalid BIC
RR01	MissingDebtorAccountOrIdentification	Regulatory Reason
RR02	MissingDebtorsNameOrAddress	Regulatory Reason
RR03	MissingCreditorsNameOrAddress	Regulatory Reason
RR04	RegulatoryReason	Regulatory Reason



2.3 Inter-PSP Reject SEPA Credit Transfer Dataset (DS-03)

2.3.1 Use of the FI to FI Payment Status Report (pacs.002.001.10)

When the code "RJCT" (Rejected) is used in the 'Status Reason', the message transports the Credit Transfer Reject instruction between PSPs, directly or through intermediaries.

The message can also be used to reject instructions of SEPA Credit Transfers with Extended Remittance Information (ERI, please refer to section 'Inter-PSP payment with use of the Extended Remittance Information option' below) whereby only AT-T010 'The unstructured Remittance Information sent by the Originator to the Beneficiary in the SEPA Credit Transfer Instruction' will be forwarded.

The message caters for bulk and single reject instructions.

Note: Attribute AT-R001 'The type of R-message' is implied by the 'Message Name', 'pacs.002.001.10', the 'Original Message Name Identification' must begin with pacs.008 (the addition of a variant number and version number is optional)and 'Status' set to "RJCT".

Note: Attribute AT-R005 'The Settlement Date for the Return' is not applicable to rejects.

Note: Message elements under 'Original Transaction Reference' sequence are based on DS-02 attributes.

#	SEPA Mult	Message Element	Inter-PSP Reject Credit Transfer SEPA Core Requirements	
		Document	XML Tag Type	Document Document
	1..1	FITo FIPayment Status Report V10	ISO Name ISO Definition	FITo FIPayment Status Report V10 Scope The FIToFIPaymentStatusReport message is sent by an instructed agent to the previous party in the payment chain. It is used to inform this party about the positive or negative status of an instruction (either single or file). It is also used to report on a pending instruction. FIToFIPmtStsRpt FIToFIPaymentStatusReportV10
1.0	1..1	FITo FIPayment Status Report V10 +Group Header	ISO Name ISO Definition XML Tag Type	Group Header Set of characteristics shared by all individual transactions included in the status report message. GrpHdr GroupHeader91
1.1	1..1	FITo FIPayment Status Report V10 +Group Header ++Message Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Message Identification Point to point reference, as assigned by the instructing party, and sent to the next party in the chain to unambiguously identify the message. Usage: The instructing party has to make sure that MessageIdentification is unique per instructed party for a pre-agreed period. MsgId Max35Text 1 .. 35 1 .. 35
1.2	1..1	FITo FIPayment Status Report V10 +Group Header ++Creation Date Time	ISO Name ISO Definition XML Tag Type	Creation Date Time Date and time at which the message was created. CreDtTm ISODateTime
1.3	0..1	FITo FIPayment Status Report V10 +Group Header ++Instructing Agent	SEPA Usage Rule(s) Only 'BICFI' is allowed. ISO Name ISO Definition XML Tag Type	Instructing Agent Agent that instructs the next party in the chain to carry out the (set of) instruction(s). Usage: The instructing agent is the party sending the status message and not the party that sent the original instruction that is being reported on. InstgAgt BranchAndFinancialInstitutionIdentification6
1.4	0..1	FITo FIPayment Status Report V10 +Group Header ++Instructed Agent	SEPA Usage Rule(s) Only 'BICFI' is allowed. ISO Name ISO Definition XML Tag Type	Instructed Agent Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s). Usage: The instructed agent is the party receiving the status message and not the party that received the original instruction that is being reported on. InstdAgt BranchAndFinancialInstitutionIdentification6
2.0	1..1	FITo FIPayment Status Report V10 +Original Group Information And Status	SEPA Usage Rule(s) Mandatory. Only one occurrence is allowed. ISO Name ISO Definition XML Tag Type	Original Group Information And Status Original group information concerning the group of transactions, to which the status report message refers to. OrgnlGrpInfAndSts OriginalGroupHeader17

#	SEPA Mult	Message Element	Inter-PSP Reject Credit Transfer SEPA Core Requirements	
2.1	1..1	FITo FIPayment Status Report V10 +Original Group Information And Status ++Original Message Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Message Identification Point to point reference, as assigned by the original instructing party, to unambiguously identify the original message. OrgnlMsgId Max35Text 1 .. 35 1 .. 35
2.2	1..1	FITo FIPayment Status Report V10 +Original Group Information And Status ++Original Message Name Identification	SEPA Usage Rule(s) <i>Must begin with 'pac.008'. The addition of a variant number and version number is optional.</i> ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Message Name Identification Specifies the original message name identifier to which the message refers. OrgnlMsgNmId Max35Text 1 .. 35 1 .. 35
2.3	0..1	FITo FIPayment Status Report V10 +Original Group Information And Status ++Original Creation Date Time	ISO Name ISO Definition XML Tag Type	Original Creation Date Time Date and time at which the original message was created. OrgnlCreDtTm ISODATETIME
2.4	0..1	FITo FIPayment Status Report V10 +Original Group Information And Status ++Original Number Of Transactions	ISO Name ISO Definition XML Tag Type Pattern	Original Number Of Transactions Number of individual transactions contained in the original message. OrgnlNbOfTxns Max15NumericText [0-9]{1,15}
2.5	0..1	FITo FIPayment Status Report V10 +Original Group Information And Status ++Original Control Sum	ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits	Original Control Sum Total of all individual amounts included in the original message, irrespective of currencies. OrgnlCtrlSum DecimalNumber 17 18
2.6	0..1	FITo FIPayment Status Report V10 +Original Group Information And Status ++Group Status	SEPA Rulebook SEPA Usage Rule(s) <i>AT-R001 Type of R Message.</i> ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>Only "RJCT" and "PART" are allowed.</i> Group Status Specifies the status of a group of transactions. GrpSts ExternalPaymentGroupStatus1Code 1 .. 4 1 .. 4
SEPA Code Restrictions				
PART <i>PartiallyAccepted</i> <i>A number of transactions have been accepted, whereas another number of transactions have not yet achieved 'accepted' status.</i>				
RJCT <i>Rejected</i> <i>Payment initiation or individual transaction included in the payment initiation has been rejected.</i>				
2.7	0..1	FITo FIPayment Status Report V10 +Original Group Information And Status ++Status Reason Information	SEPA Usage Rule(s) <i>Only one occurrence is allowed.</i> ISO Name ISO Definition XML Tag Type	<i>'Status Reason Information' must be present either in 'Original Group Information And Status' or in 'Transaction Information and Status'.</i> Status Reason Information Provides detailed information on the status reason. StsRsnInf StatusReasonInformation12

#	SEPA Mult	Message Element	Inter-PSP Reject Credit Transfer SEPA Core Requirements	
2.8	1..1	FITo FIPayment Status Report V10 +Original Group Information And Status ++Status Reason Information +++Originator	<p>SEPA Rulebook <i>AT-R002 Identification of the type of party that initiated the reject.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i> <i>Limited to 'AnyBIC' to identify the PSP or CSM originating the status or 'Name' to indicate the CSM when it has no BIC.</i> <i>'Name' is limited to 70 characters in length.</i></p> <p>ISO Name Originator</p> <p>ISO Definition Party that issues the status.</p> <p>XML Tag Orgtr</p> <p>Type PartyIdentification135</p>	
2.9	1..1	FITo FIPayment Status Report V10 +Original Group Information And Status ++Status Reason Information +++Reason	<p>SEPA Rulebook <i>AT-R004 Reason Code for Non-Acceptance.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name Reason</p> <p>ISO Definition Specifies the reason for the status report.</p> <p>XML Tag Rsn</p> <p>Type StatusReason6Choice</p>	
	1..1		XML Tag	xs:choice
2.10	1..1	FITo FIPayment Status Report V10 +Original Group Information And Status ++Status Reason Information +++Reason ++++Code	<p>SEPA Rulebook <i>See Message Element Specifications below.</i></p> <p>ISO Name Code</p> <p>ISO Definition Reason for the status, as published in an external reason code list.</p> <p>XML Tag Cd</p> <p>Type ExternalStatusReason1Code</p> <p>ISO Length 1 .. 4</p> <p>SEPA Length 1 .. 4</p>	
2.11	1..1	FITo FIPayment Status Report V10 +Original Group Information And Status ++Status Reason Information +++Reason ++++Proprietary	<p>ISO Name Proprietary</p> <p>ISO Definition Reason for the status, in a proprietary form.</p> <p>XML Tag Prtry</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>	
2.12	0..n	FITo FIPayment Status Report V10 +Original Group Information And Status ++Status Reason Information +++Additional Information	<p>ISO Name Additional Information</p> <p>ISO Definition Further details on the status reason.</p> <p>XML Tag</p> <p>Type</p> <p>ISO Length 1 .. 105</p> <p>SEPA Length 1 .. 105</p>	<p>Usage: Additional information can be used for several purposes such as the reporting of repaired information.</p> <p>AddtlInf</p> <p>Max105Text</p>
2.13	0..n	FITo FIPayment Status Report V10 +Original Group Information And Status ++Number Of Transactions Per Status	<p>ISO Name Number Of Transactions Per Status</p> <p>ISO Definition Detailed information on the number of transactions for each identical transaction status.</p> <p>XML Tag</p> <p>Type</p> <p>ISO Length NbOfTxnsPerSts</p> <p>SEPA Length NumberOfTransactionsPerStatus5</p>	
3.0	0..n	FITo FIPayment Status Report V10 +Transaction Information And Status	<p>ISO Name Transaction Information And Status</p> <p>ISO Definition Information concerning the original transactions, to which the status report message refers.</p> <p>XML Tag</p> <p>Type</p> <p>ISO Length TxInfAndSts</p> <p>SEPA Length PaymentTransaction110</p>	

#	SEPA Mult	Message Element	Inter-PSP Reject Credit Transfer SEPA Core Requirements	
3.1	1..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Status Identification	<p>SEPA Rulebook <i>AT-R003 Specific reference of the PSP that initiated the reject.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name Status Identification</p> <p>ISO Definition Unique identification, as assigned by an instructing party for an instructed party, to unambiguously identify the reported status.</p> <p>Usage: The instructing party is the party sending the status message and not the party that sent the original instruction that is being reported on.</p> <p>XML Tag StsId</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>	
3.2	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Group Information	<p>ISO Name Original Group Information</p> <p>ISO Definition Point to point reference, as assigned by the original instructing party, to unambiguously identify the original message.</p> <p>XML Tag OrgnlGrpInf</p> <p>Type OriginalGroupInformation29</p>	
3.3	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Instruction Identification	<p>SEPA Usage Rule(s) <i>Mandatory if provided in the original instruction.</i></p> <p>ISO Name Original Instruction Identification</p> <p>ISO Definition Unique identification, as assigned by the original instructing party for the original instructed party, to unambiguously identify the original instruction.</p> <p>XML Tag OrgnlInstrId</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>	
3.4	1..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original End To End Identification	<p>SEPA Rulebook <i>AT-T014 The Originator's reference of the SEPA Credit Transfer Transaction.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name Original End To End Identification</p> <p>ISO Definition Unique identification, as assigned by the original initiating party, to unambiguously identify the original transaction.</p> <p>XML Tag OrgnlEndToEndId</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>	
3.5	1..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Identification	<p>SEPA Rulebook <i>AT-T054 The Originator PSP's reference of the SEPA Credit Transfer Transaction.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name Must contain a reference that is unique over time.</p> <p>ISO Definition Original Transaction Identification</p> <p>Unique identification, as assigned by the original first instructing agent, to unambiguously identify the transaction.</p> <p>XML Tag OrgnlTxId</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>	
3.6	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original UETR	<p>ISO Name Original UETR</p> <p>ISO Definition Universally unique identifier to provide the original end-to-end reference of a payment transaction.</p> <p>XML Tag OrgnlUETR</p> <p>Type UUIDv4Identifier</p> <p>Pattern [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}</p>	

#	SEPA Mult	Message Element	Inter-PSP Reject Credit Transfer SEPA Core Requirements	
3.7	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Transaction Status	<p>SEPA Rulebook <i>AT-R001 Type of R-message.</i></p> <p>SEPA Usage Rule(s) <i>Only "RJCT" is allowed.</i></p> <p>ISO Name Transaction Status</p> <p>ISO Definition Specifies the status of a transaction, in a coded form.</p> <p>XML Tag TxSts</p> <p>Type ExternalPaymentTransactionStatus1Code</p> <p>ISO Length 1 .. 4</p> <p>SEPA Length 1 .. 4</p>	
				SEPA Code Restrictions
				<p>RJCT <i>Rejected</i> <i>Payment instruction has been rejected.</i></p>
3.8	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Status Reason Information	<p>SEPA Usage Rule(s) <i>Only one occurrence of 'Status Reason Information' is allowed. 'Status Reason Information' must be present either in 'Original Group Information and Status' or in 'Transaction Information and Status'.</i></p> <p>ISO Name Status Reason Information</p> <p>ISO Definition Provides detailed information on the status reason.</p> <p>XML Tag StsRsnInf</p> <p>Type StatusReasonInformation12</p>	
3.9	1..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Status Reason Information +++Originator	<p>SEPA Rulebook <i>AT-R002 Identification of the type of party that initiated the reject.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory. Limited to 'AnyBIC' to identify the PSP or CSM originating the status or 'Name' to indicate the CSM when it has no BIC. 'Name' is limited to 70 characters in length.</i></p> <p>ISO Name Originator</p> <p>ISO Definition Party that issues the status.</p> <p>XML Tag Orgtr</p> <p>Type PartyIdentification135</p>	
3.10	1..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Status Reason Information +++Reason	<p>SEPA Rulebook <i>AT-R004 Reason Code for Non-Acceptance of the credit transfer.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name Reason</p> <p>ISO Definition Specifies the reason for the status report.</p> <p>XML Tag Rsn</p> <p>Type StatusReason6Choice</p>	
	1..1			XML Tag xs:choice
3.11	1..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Status Reason Information +++Reason ++++Code	<p>SEPA Rulebook <i>See Message Element Specifications below.</i></p> <p>ISO Name Code</p> <p>ISO Definition Reason for the status, as published in an external reason code list.</p> <p>XML Tag Cd</p> <p>Type ExternalStatusReason1Code</p> <p>ISO Length 1 .. 4</p> <p>SEPA Length 1 .. 4</p>	
3.12	1..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Status Reason Information +++Reason ++++Proprietary	<p>ISO Name Proprietary</p> <p>ISO Definition Reason for the status, in a proprietary form.</p> <p>XML Tag Prtry</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>	

#	SEPA Mult	Message Element	Inter-PSP Reject Credit Transfer SEPA Core Requirements	
3.13	0..n	FITo FIPayment Status Report V10 +Transaction Information And Status ++Status Reason Information +++Additional Information	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Additional Information Further details on the status reason. Usage: Additional information can be used for several purposes such as the reporting of repaired information. AddtlInf Max105Text 1 .. 105 1 .. 105
3.14	0..n	FITo FIPayment Status Report V10 +Transaction Information And Status ++Charges Information	ISO Name ISO Definition XML Tag Type	Charges Information Provides information on the charges related to the processing of the rejection of the instruction. Usage: This is passed on for information purposes only. Settlement of the charges will be done separately. ChrgsInf Charges7
3.15	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Acceptance Date Time	ISO Name ISO Definition XML Tag Type	Acceptance Date Time Point in time when the payment order from the initiating party meets the processing conditions of the account servicing agent. This means that the account servicing agent has received the payment order and has applied checks such as authorisation, availability of funds. AcptncDtTm ISODATETIME
3.16	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Effective Interbank Settlement Date	ISO Name ISO Definition XML Tag Type	Effective Interbank Settlement Date Date and time at which a transaction is completed and cleared, that is, payment is effected. FctvIntrBkSttlmDt DateAndDateTime2Choice
3.17	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Account Servicer Reference	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Account Servicer Reference Unique reference, as assigned by the account servicing institution, to unambiguously identify the instruction. AcctSvrRef Max35Text 1 .. 35 1 .. 35
3.18	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Clearing System Reference	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Clearing System Reference Unique reference, as assigned by a clearing system, to unambiguously identify the instruction. ClrSysRef Max35Text 1 .. 35 1 .. 35
3.19	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Instructing Agent	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Only 'BICFI' is allowed. Instructing Agent Agent that instructs the next party in the chain to carry out the (set of) instruction(s). Usage: The instructing agent is the party sending the status message and not the party that sent the original instruction that is being reported on. InstgAgt BranchAndFinancialInstitutionIdentification6

#	SEPA Mult	Message Element	Inter-PSP Reject Credit Transfer SEPA Core Requirements
3.20	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Instructed Agent	<p>SEPA Usage Rule(s) Only 'BICFI' is allowed.</p> <p>ISO Name Instructed Agent</p> <p>ISO Definition Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s).</p> <p>Usage: The instructed agent is the party receiving the status message and not the party that received the original instruction that is being reported on.</p> <p>XML Tag Type</p> <p>InstdAgt BranchAndFinancialInstitutionIdentification6</p>
3.21	1..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference	<p>SEPA Rulebook An exact copy of all attributes of the received DS-02 which is being rejected.</p> <p>SEPA Usage Rule(s) Mandatory</p> <p>The message elements under 'Original Transaction Reference' must be populated with the same value as the message elements of the original instruction.</p> <p>ISO Name Original Transaction Reference</p> <p>ISO Definition Key elements used to identify the original transaction that is being referred to.</p> <p>XML Tag Type</p> <p>OrgnlTxRef OriginalTransactionReference28</p>
3.22	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Interbank Settlement Amount	<p>SEPA Rulebook AT-T002 Amount of the SEPA Credit Transfer in Euro.</p> <p>ISO Name Interbank Settlement Amount</p> <p>ISO Definition Amount of money moved between the instructing agent and the instructed agent.</p> <p>XML Tag Type</p> <p>SEPA FractDigits 2</p> <p>TotalDigits 18</p> <p>SEPA Inclusive 0.01 .. 999999999.99</p>
3.23	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Amount	<p>ISO Name Amount</p> <p>ISO Definition Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.</p> <p>XML Tag Type</p> <p>Amt AmountType4Choice</p>
3.24	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Interbank Settlement Date	<p>SEPA Rulebook AT-T051 Settlement Date of the credit transfer.</p> <p>ISO Name Interbank Settlement Date</p> <p>ISO Definition Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.</p> <p>XML Tag Type</p> <p>IntrBkSttlmDt ISODate</p>
3.25	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Requested Collection Date	<p>ISO Name Requested Collection Date</p> <p>ISO Definition Date and time at which the creditor requests that the amount of money is to be collected from the debtor.</p> <p>XML Tag Type</p> <p>ReqdColltnDt ISODate</p>
3.26	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Requested Execution Date	<p>ISO Name Requested Execution Date</p> <p>ISO Definition Date at which the initiating party requests the clearing agent to process the payment.</p> <p>Usage: This is the date on which the debtor's account is to be debited. If payment by cheque, the date when the cheque must be generated by the bank.</p> <p>XML Tag Type</p> <p>ReqdExctnDt DateAndDateTime2Choice</p>

#	SEPA Mult	Message Element	Inter-PSP Reject Credit Transfer SEPA Core Requirements	
3.27	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Creditor Scheme Identification	ISO Name ISO Definition XML Tag Type	Creditor Scheme Identification Credit party that signs the mandate. CdtrSchmeId PartyIdentification135
3.28	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Settlement Information	ISO Name ISO Definition XML Tag Type	Settlement Information Specifies the details on how the settlement of the original transaction(s) between the instructing agent and the instructed agent was completed. SttlmInf SettlementInstruction7
3.29	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Payment Type Information	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-T001 Identification code of the Scheme.</i> <i>AT-T008 Category purpose of the Credit Transfer.</i> <i>If the original transaction was sent according to Annex V (Use of Extended Remittance Information) of the SCT Rulebook (refer to section 'Inter-PSP payment with use of the Extended Remittance Information option' below), then 'Local Instrument/Code' must be populated with "PERI" (Payment with Extended Remittance Information).</i> Payment Type Information Set of elements used to further specify the type of transaction. PmtTpInf PaymentTypeInformation27
3.30	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Payment Method	ISO Name ISO Definition XML Tag Type	Payment Method Specifies the means of payment that will be used to move the amount of money. PmtMtd PaymentMethod4Code
3.31	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Mandate Related Information	ISO Name ISO Definition XML Tag Type	Mandate Related Information Provides further details of the mandate signed between the creditor and the debtor. MndtRltdInf MandateRelatedInformation14
3.32	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Remittance Information	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-T009 Remittance information or AT-T010 The unstructured Remittance Information sent by the Originator to the Beneficiary in the Credit Transfer Instruction (in case of use of the Extended Remittance Information (ERI) option in the original SEPA Credit Transfer, AT-T011 The structured Remittance Information sent by the Originator to the Beneficiary in the SEPA Credit Transfer Instruction, will NOT be transported here).</i> Remittance Information Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system. RmtInf RemittanceInformation16
3.33	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Ultimate Debtor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-P006 The name of the Originator Reference Party.</i> <i>AT-P007 The identification code of the Originator Reference Party.</i> <i>Only 'Party' is allowed.</i> Ultimate Debtor Ultimate party that owes an amount of money to the (ultimate) creditor. UltmtDbtr Party40Choice

#	SEPA Mult	Message Element	Inter-PSP Reject Credit Transfer SEPA Core Requirements	
3.34	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Debtor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-P001 Name of the Originator.</i> <i>AT-P005 Address of the Originator.</i> <i>AT-P004 Originator identification code.</i> <i>Only 'Party' is allowed.</i> Debtor Party that owes an amount of money to the (ultimate) creditor. Dbtr Party40Choice
3.35	1..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Debtor Account	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-D001 The IBAN of the account of the Originator.</i> <i>AT-P003 The Proxy/Alias of the account of the Originator.</i> Debtor Account Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction. DbtrAcct CashAccount38
3.36	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Debtor Agent	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-D002 The BIC code of the Originator PSP.</i> Debtor Agent Financial institution servicing an account for the debtor. DbtrAgt BranchAndFinancialInstitutionIdentification6
3.37	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Debtor Agent Account	ISO Name ISO Definition XML Tag Type	Debtor Agent Account Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain. DbtrAgtAcct CashAccount38
3.38	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Creditor Agent	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-C002 The BIC code of the Beneficiary PSP.</i> Creditor Agent Financial institution servicing an account for the creditor. CdtrAgt BranchAndFinancialInstitutionIdentification6
3.39	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Creditor Agent Account	ISO Name ISO Definition XML Tag Type	Creditor Agent Account Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction. CdtrAgtAcct CashAccount38
3.40	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Creditor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-E001 Name of the Beneficiary.</i> <i>AT-E004 Address of the Beneficiary.</i> <i>AT-E005 Beneficiary identification code.</i> <i>Only 'Party' is allowed.</i> Creditor Party to which an amount of money is due. Cdtr Party40Choice
3.41	1..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Creditor Account	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-C001 The IBAN of the account of the Beneficiary.</i> <i>AT-E003 The Proxy/Alias of the account of the Beneficiary.</i> Creditor Account Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction. CdtrAcct CashAccount38

#	SEPA Mult	Message Element	Inter-PSP Reject Credit Transfer SEPA Core Requirements	
3.42	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Ultimate Creditor	<p>SEPA Rulebook</p> <p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p><i>AT-E007 The name of the Beneficiary Reference Party.</i></p> <p><i>AT-E010 The identification code of the Beneficiary Reference Party.</i></p> <p>SEPA Usage Rule(s) Only 'Party' is allowed.</p> <p>Ultimate Creditor</p> <p>Ultimate party to which an amount of money is due.</p> <p>UltmtCdtr</p> <p>Party40Choice</p>
3.43	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Purpose	<p>SEPA Rulebook</p> <p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p><i>AT-T007 The purpose of the SEPA Credit Transfer</i></p> <p>Purpose</p> <p>Underlying reason for the payment transaction.</p> <p>Usage:</p> <p>Purpose is used by the end customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain.</p> <p>Purp</p> <p>Purpose2Choice</p>
3.44	0..n	FITo FIPayment Status Report V10 +Transaction Information And Status ++Supplementary Data	<p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p>Supplementary Data</p> <p>Additional information that cannot be captured in the structured elements and/or any other specific block.</p> <p>SplmtryData</p> <p>SupplementaryData1</p>
4.0	0..n	FITo FIPayment Status Report V10 +Supplementary Data	<p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p>Supplementary Data</p> <p>Additional information that cannot be captured in the structured elements and/or any other specific block.</p> <p>SplmtryData</p> <p>SupplementaryData1</p>



2.3.2 Message Element Specifications

The reasons for an inter-PSP reject present in the Rulebook are mapped to ISO codes as follows:

ISO Code	ISO Name	SEPA Core Reason as specified in the Rulebook
AC01	IncorrectAccountNumber	Account identifier incorrect (i.e. invalid IBAN)
AG02	InvalidBankOperationCode	Operation/transaction code incorrect, invalid file format <i>Usage Rule:</i> To be used for incorrect 'operation/transaction' code.
AM05	Duplication	Duplicate payment
ED05	SettlementFailed	Settlement of the SEPA Credit Transfer has failed
ERIN	ERIOptionNotSupported	The Extended Remittance Information (ERI) option is not supported
FF01	InvalidFileFormat	Operation/transaction code incorrect, invalid file format
MS03	NotSpecifiedReasonAgentGenerated	Reason not specified
RC01	BankIdentifierIncorrect	PSP identifier incorrect (i.e. invalid BIC)
RR01	MissingDebtorAccountOrIdentification	Regulatory Reason
RR02	MissingDebtorsNameOrAddress	Regulatory Reason
RR03	MissingCreditorsNameOrAddress	Regulatory Reason
RR04	RegulatoryReason	Regulatory Reason
TM01	CutOffTime	File received after Cut-off Time
DNOR	DebtorBankIsNotRegistered	Debtor PSP is not registered under this BIC in the CSM
CNOR	CreditorBankIsNotRegistered	Creditor PSP is not registered under this BIC in the CSM



2.4 Inter-PSP Recall of SEPA Credit Transfer Dataset (DS-05)

2.4.1 Use of FI-to-FI Payment Cancellation Request (camt.056.001.08)

The message is used to submit the request to cancel a pacs.008 or to cancel specified transactions from the Originator PSP to the next PSP in the chain or to the CSM, or from the CSM to the next PSP in the chain, where the following apply:

- Index 4.3 'Cancellation Identification' can only be populated with AT-R053 'The specific reference of the Originator PSP initiating the Recall'.
- Index 4.19 'Originator' can only be populated with AT-R002 'Identification of the type of party initiating the "R"-message'.
- Index 4.20 'Reason' is to be populated with AT-R051 'The Recall reason code'.
- Index 4.21 'Code' can only be populated with ISO codes "DUPL" (Duplicate payment), "TECH" (Technical problem) and "FRAD" (Fraudulent origin).
- Index 4.23 'Additional Information' is allowed only when "FRAD" is used as Recall reason code and in such case is to be populated with AT-R052 'Additional Information to AT-R051 The Recall reason code'.

The message can also be used to recall a SEPA Credit Transfer with Extended Remittance Information (ERI, please refer to section 'Inter-PSP payment with use of the Extended Remittance Information option' below) whereby only AT-T010 'The unstructured Remittance Information sent by the Originator to the Beneficiary in the Credit Transfer Instruction' will be forwarded.

The message caters for single or group cancellation requests. Group cancellation requests allow recall of single or multiple transactions from single or multiple original messages.

Note: Attribute AT-R001 'Type of R-message' is implied by the 'Message Name', 'camt.056.001.08', the 'Original Message Name Identification' must begin with pacs.008 (the addition of a variant number and version number is optional) and 'Reason' set to "DUPL", "TECH" or "FRAD" (under 'Code').

Note: Message elements under 'Original Transaction Reference' sequence are based on DS-02 attributes.

Note: Only one Recall can be sent for a given SCT Transaction during the periods mentioned in the SCT Rulebook [1]. The Originator PSP is not allowed to send another Recall for the same initial SCT Transaction.

#	SEPA Mult	Message Element	Inter-PSP Recall of Credit Transfer SEPA Core Requirements	
		Document	XML Tag Type	Document Document
	1..1	FITo FIPayment Cancellation Request V08	ISO Name ISO Definition	<p>FITo FIPayment Cancellation Request V08 Scope</p> <p>The FIToFIPaymentCancellationRequest message is sent by a case creator/case assignee to a case assignee.</p> <p>This message is used to request the cancellation of an original payment instruction. The FIToFIPaymentCancellationRequest message is exchanged between the instructing agent and the instructed agent to request the cancellation of a interbank payment message previously sent (such as FIToFICustomerCreditTransfer, FIToFICustomerDirectDebit or FinancialInstitutionCreditTransfer).</p>
			XML Tag Type	<p>The FIToFIPaymentCancellationRequest message supports both the request for cancellation (the instructed agent - or assignee - has not yet processed and forwarded the payment instruction) as well as the request for refund (payment has been fully processed already by the instructed agent - or assignee).</p> <p>FIToFIPmtCxlReq FIToFIPaymentCancellationRequestV08</p>
1.0	1..1	FITo FIPayment Cancellation Request V08 +Assignment	ISO Name ISO Definition	<p>Assignment</p> <p>Identifies the assignment of an investigation case from an assigner to an assignee.</p> <p>Usage: The assigner must be the sender of this confirmation and the assignee must be the receiver.</p>
			XML Tag Type	<p>Assgnmt CaseAssignment5</p>
1.1	1..1	FITo FIPayment Cancellation Request V08 +Assignment ++Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<p>Identification</p> <p>Uniquely identifies the case assignment.</p> <p>Id</p> <p>Max35Text</p> <p>1 .. 35</p> <p>1 .. 35</p>
1.2	1..1	FITo FIPayment Cancellation Request V08 +Assignment ++Assigner	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<p>Instructing Party.</p> <p>Limited to 'BICFI' to identify a PSP, 'AnyBIC' to identify a CSM or 'LEI' or 'Name' to indicate a CSM when it has no BIC.</p> <p>'Name' is limited to 70 characters in length.</p> <p>Assigner</p> <p>Party who assigns the case.</p> <p>Usage: This is also the sender of the message.</p>
			SEPA Rulebook SEPA Usage Rule(s)	<p>Assgnr</p> <p>Party40Choice</p>
1.3	1..1	FITo FIPayment Cancellation Request V08 +Assignment ++Assignee	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<p>Instructed Party.</p> <p>Limited to 'BICFI' to identify a PSP, 'AnyBIC' to identify a CSM or 'LEI' or 'Name' to indicate a CSM when it has no BIC.</p> <p>'Name' is limited to 70 characters in length.</p> <p>Assignee</p> <p>Party to which the case is assigned.</p> <p>Usage: This is also the receiver of the message.</p>
			SEPA Rulebook SEPA Usage Rule(s)	<p>Assgne</p> <p>Party40Choice</p>

#	SEPA Mult	Message Element	Inter-PSP Recall of Credit Transfer SEPA Core Requirements		
1.4	1..1	FITo FIPayment Cancellation Request V08 +Assignment ++Creation Date Time	ISO Name ISO Definition XML Tag Type	Creation Date Time Date and time at which the assignment was created. CreDtTm ISODateTime	
2.0	0..1	FITo FIPayment Cancellation Request V08 +Case	ISO Name ISO Definition XML Tag Type	Case Identifies the investigation case. Case Case5	
3.0	0..1	FITo FIPayment Cancellation Request V08 +Control Data	ISO Name ISO Definition XML Tag Type	Control Data Provides details on the number of transactions and the control sum of the message. CtrlData ControlData1	
3.1	1..1	FITo FIPayment Cancellation Request V08 +Control Data ++Number Of Transactions	ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits	Number Of Transactions Number of individual transactions contained in the message. NbOfTxns Max15NumericText [0-9]{1,15}	
3.2	0..1	FITo FIPayment Cancellation Request V08 +Control Data ++Control Sum	ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits	Control Sum Total of all individual amounts included in the message, irrespective of currencies. CtrlSum DecimalNumber 17 18	
4.0	1..n	FITo FIPayment Cancellation Request V08 +Underlying	ISO Name ISO Definition XML Tag Type	Underlying Identifies the payment instruction to be cancelled. Undrlg UnderlyingTransaction23	
4.1	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Original Group Information And Cancellation	ISO Name ISO Definition XML Tag Type	Original Group Information And Cancellation Provides information on the original message, to which the cancellation refers. OrgnlGrpInfAndCxl OriginalGroupHeader15	
4.2	1..n	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information	SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type	Transaction Information Provides information on the original transactions to which the cancellation request message refers. TxInf PaymentTransaction106	
4.3	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Cancellation Identification	SEPA Rulebook SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>AT-R053 The Specific reference of the Originator PSP initiating the Recall.</i> <i>This element must be transported up to the Creditor Agent.</i> Cancellation Identification Unique and unambiguous identifier of a cancellation request, as assigned by the assigner. Usage: The cancellation request identification can be used for reconciliation or to link tasks relating to the cancellation request. CxId Max35Text 1 .. 35 1 .. 35	

#	SEPA Mult	Message Element	Inter-PSP Recall of Credit Transfer SEPA Core Requirements		
4.4	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Case	ISO Name ISO Definition XML Tag Type	Case Set of elements to uniquely and unambiguously identify an exception or an investigation workflow. Case Case5	
4.5	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Group Information	SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type	Original Group Information Provides information on the original message. OrgnlGrpInf OriginalGroupInformation29	
4.6	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Group Information ++++Original Message Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Message Identification Point to point reference assigned by the original instructing party to unambiguously identify the original message. OrgnlMsgId Max35Text 1 .. 35 1 .. 35	
4.7	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Group Information ++++Original Message Name Identification	SEPA Usage Rule(s) Must begin with 'pacs.008'. The addition of a variant number and version number is optional. ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Message Name Identification Specifies the original message name identifier to which the message refers, for example, pacs. 003.001.01 or MT103. OrgnlMsgNmld Max35Text 1 .. 35 1 .. 35	
4.8	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Group Information ++++Original Creation Date Time	ISO Name ISO Definition XML Tag Type	Original Creation Date Time Original date and time at which the message was created. OrgnlCreDtTm ISODATETIME	
4.9	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Instruction Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Instruction Identification Unique identification, as assigned by the original instructing party for the original instructed party, to unambiguously identify the original instruction. OrgnlInstrId Max35Text 1 .. 35 1 .. 35	
4.10	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original End To End Identification	SEPA Rulebook SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	AT-T014 The Originator's reference of the SEPA Credit Transfer Transaction. Original End To End Identification Unique identification, as assigned by the original initiating party, to unambiguously identify the original transaction. OrgnlEndToEndId Max35Text 1 .. 35 1 .. 35	

#	SEPA Mult	Message Element	Inter-PSP Recall of Credit Transfer SEPA Core Requirements	
4.11	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Identification	SEPA Rulebook SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>AT-T054 The Originator PSP's reference of the SEPA Credit Transfer Transaction.</i> <i>Original Transaction Identification</i> Unique identification, as assigned by the original first instructing agent, to unambiguously identify the transaction. OrgnlTxId Max35Text 1 .. 35 1 .. 35
4.12	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original UETR	ISO Name ISO Definition XML Tag Type Pattern	Original UETR Universally unique identifier to provide the original end-to-end reference of a payment transaction. OrgnlUETR UUIDv4Identifier [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}
4.13	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Clearing System Reference	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Clearing System Reference Unique reference, as assigned by the original clearing system, to unambiguously identify the original instruction. OrgnlClrSysRef Max35Text 1 .. 35 1 .. 35
4.14	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Interbank Settlement Amount	SEPA Rulebook SEPA Usage Rule(s) Mandatory. <i>Only 'EUR' is allowed.</i> <i>Amount must be 0.01 or more and 999999999.99 or less.</i> <i>The fractional part has a maximum of two digits.</i> SEPA Format Rule(s) ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits SEPA Inclusive	<i>AT-T002 Amount of the SEPA Credit Transfer in Euro.</i> Original Interbank Settlement Amount Amount of money moved between the instructing agent and the instructed agent, as provided in the original instruction. OrgnlIntrBkSttlmAmt ActiveOrHistoricCurrencyAndAmount 2 18 0.01 .. 999999999.99
4.15	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Interbank Settlement Date	SEPA Rulebook SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type	<i>AT-T051 Settlement Date of the Credit Transfer.</i> Original Interbank Settlement Date Date, as provided in the original transaction, on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. OrgnlIntrBkSttlmDt ISODate
4.16	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Assigner	ISO Name ISO Definition XML Tag Type	Assigner Party who assigns the case. Usage: This is also the agent that instructs the next party in the chain to carry out the (set of) cancellation request(s). Assgnr BranchAndFinancialInstitutionIdentification6

#	SEPA Mult	Message Element	Inter-PSP Recall of Credit Transfer SEPA Core Requirements	
4.17	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Assignee	ISO Name ISO Definition XML Tag Type	Assignee Party to which the case is assigned. Usage: This is also the agent that is instructed by the previous party in the chain to carry out the (set of) cancellation request(s). Assgne BranchAndFinancialInstitutionIdentification6
4.18	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Cancellation Reason Information	SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type	Only one occurrence is allowed. Cancellation Reason Information Provides detailed information on the cancellation reason. CxlRsnInf PaymentCancellationReason5
4.19	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Cancellation Reason Information ++++Originator	SEPA Rulebook SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type	AT-R002 Identification of the type of party initiating the "R"-message. Limited to 'AnyBIC' for an Agent or 'Name' for a non-financial institution. 'Name' is limited to 70 characters in length. Originator Party that issues the cancellation request. Orgtr PartyIdentification135
4.20	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Cancellation Reason Information ++++Reason	SEPA Rulebook SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type	AT-R051 Recall reason code. Reason Specifies the reason for the cancellation. Rsn CancellationReason33Choice
	1..1		XML Tag	xs:choice
4.21	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Cancellation Reason Information ++++Reason +++++Code	SEPA Usage Rule(s) Only "DUPL", "TECH" or "FRAD" are allowed. ISO Name ISO Definition XML Tag Type ISO Length SEPA Length SEPA Code Restrictions	Code Reason for the cancellation request, in a coded form. Cd ExternalCancellationReason1Code 1 .. 4 1 .. 4 DUPL DuplicatePayment Payment is a duplicate of another payment. FRAD FraudulentOrigin Cancellation requested following a transaction that was originated fraudulently. The use of the FraudulentOrigin code should be governed by jurisdictions. TECH TechnicalProblem Cancellation requested following technical problems resulting in an erroneous transaction.
4.22	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Cancellation Reason Information ++++Reason +++++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Proprietary Reason for the cancellation request, in a proprietary form. Prtry Max35Text 1 .. 35 1 .. 35

#	SEPA Mult	Message Element	Inter-PSP Recall of Credit Transfer SEPA Core Requirements	
4.23	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Cancellation Reason Information ++++Additional Information	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>AT-R052 Additional information to AT-R051 The Recall reason code</i> <i>Only allowed when "FRAD" is used as a Recall reason code.</i> <i>Only one occurrence is allowed.</i> Additional Information Further details on the cancellation request reason. AddtlInf Max105Text 1 .. 105 1 .. 105
4.24	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>An exact copy of all attributes of the initially sent DS-02 which is to be cancelled.</i> <i>Mandatory.</i> <i>The message elements under 'Original Transaction Reference' must be populated with the same value as the message elements of the original instruction.</i> Original Transaction Reference Key elements used to identify the original transaction that is being referred to. OrgnlTxRef OriginalTransactionReference28
4.25	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Interbank Settlement Amount	ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits SEPA Inclusive	Interbank Settlement Amount Amount of money moved between the instructing agent and the instructed agent. IntrBkStlmtAmt ActiveOrHistoricCurrencyAndAmount 5 18 0 .. .
4.26	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Amount	ISO Name ISO Definition XML Tag Type	Amount Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party. Amt AmountType4Choice
4.27	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Interbank Settlement Date	ISO Name ISO Definition XML Tag Type	Interbank Settlement Date Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. IntrBkStlmtDt ISODate
4.28	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Requested Collection Date	ISO Name ISO Definition XML Tag Type	Requested Collection Date Date and time at which the creditor requests that the amount of money is to be collected from the debtor. ReqdColltnDt ISODate
4.29	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Requested Execution Date	ISO Name ISO Definition XML Tag Type	Requested Execution Date Date at which the initiating party requests the clearing agent to process the payment. Usage: This is the date on which the debtor's account is to be debited. If payment by cheque, the date when the cheque must be generated by the bank. ReqdExctnDt DateAndDateTime2Choice

#	SEPA Mult	Message Element	Inter-PSP Recall of Credit Transfer SEPA Core Requirements	
4.30	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Creditor Scheme Identification	ISO Name ISO Definition XML Tag Type	Creditor Scheme Identification Credit party that signs the mandate. CdtrSchmeId PartyIdentification135
4.31	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Settlement Information	ISO Name ISO Definition XML Tag Type	Settlement Information Specifies the details on how the settlement of the original transaction(s) between the instructing agent and the instructed agent was completed. SttlmInf SettlementInstruction7
4.32	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Payment Type Information	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-T001 Identification code of the Scheme.</i> <i>AT-T008 Category Purpose of the Credit Transfer.</i> <i>If the original transaction was sent according to Annex V (Use of Extended Remittance Information) of the SCT Rulebook (refer to section 'Inter-PSP payment with use of the Extended Remittance Information option' below), then 'Local Instrument/Code' must be populated with "PERI" (Payment with Extended Remittance Information).</i> Payment Type Information Set of elements used to further specify the type of transaction. PmtTpInf PaymentTypeInformation27
4.33	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Payment Method	ISO Name ISO Definition XML Tag Type	Payment Method Specifies the means of payment that will be used to move the amount of money. PmtMtd PaymentMethod4Code
4.34	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Mandate Related Information	ISO Name ISO Definition XML Tag Type	Mandate Related Information Provides further details of the mandate signed between the creditor and the debtor. MndtRltdInf MandateRelatedInformation14
4.35	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Remittance Information	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-T009 Remittance information or AT-T010 The unstructured Remittance Information sent by the Originator to the Beneficiary in the Credit Transfer Instruction (in case of use of the Extended Remittance Information (ERI) option in the original SEPA Credit Transfer, AT-T011 The structured Remittance Information sent by the Originator to the Beneficiary in the SEPA Credit Transfer Instruction, will NOT be transported here).</i> Remittance Information Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system. RmtInf RemittanceInformation16

#	SEPA Mult	Message Element	Inter-PSP Recall of Credit Transfer SEPA Core Requirements		
4.36	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Ultimate Debtor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-P006 The name of the Originator Reference Party.</i> <i>AT-P007 The identification code of the Originator Reference Party.</i> <i>Only 'Party' is allowed.</i> Ultimate Debtor Ultimate party that owes an amount of money to the (ultimate) creditor. UltmtDbtr Party40Choice	
4.37	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Debtor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-P001 Name of the Originator - Mandatory.</i> <i>AT-P005 Address of the Originator.</i> <i>AT-P004 Originator's Identification Code.</i> <i>Only 'Party' is allowed.</i> Debtor Party that owes an amount of money to the (ultimate) creditor. Dbtr Party40Choice	
4.38	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Debtor Account	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-D001 The IBAN of the account of the Originator.</i> <i>AT-P003 The Proxy/Alias of the account of the Originator.</i> Debtor Account Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction. DbtrAcct CashAccount38	
4.39	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Debtor Agent	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-D002 The BIC code of the Originator PSP.</i> Debtor Agent Financial institution servicing an account for the debtor. DbtrAgt BranchAndFinancialInstitutionIdentification6	
4.40	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Debtor Agent Account	ISO Name ISO Definition XML Tag Type	Debtor Agent Account Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain. DbtrAgtAcct CashAccount38	
4.41	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Creditor Agent	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-C002 The BIC code of the Beneficiary PSP.</i> Creditor Agent Financial institution servicing an account for the creditor. CdtrAgt BranchAndFinancialInstitutionIdentification6	
4.42	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Creditor Agent Account	ISO Name ISO Definition XML Tag Type	Creditor Agent Account Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction. CdtrAgtAcct CashAccount38	
4.43	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Creditor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-E001 Name of the Beneficiary - Mandatory.</i> <i>AT-E004 Address of the Beneficiary.</i> <i>AT-E005 Beneficiary Identification Code.</i> <i>Only 'Party' is allowed.</i> Creditor Party to which an amount of money is due. Cdtr Party40Choice	

#	SEPA Mult	Message Element	Inter-PSP Recall of Credit Transfer SEPA Core Requirements		
4.44	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Creditor Account	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-C001 The IBAN of the account of the Beneficiary.</i> <i>AT-E003 The Proxy/Alias of the account of the Beneficiary.</i> Creditor Account Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction. CdtrAcct CashAccount38	
4.45	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Ultimate Creditor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-E007 The name of the Beneficiary Reference Party.</i> <i>AT-E010 The identification code of the Beneficiary Reference Party.</i> Only 'Party' is allowed. Ultimate Creditor Ultimate party to which an amount of money is due. UltmtCdtr Party40Choice	
4.46	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Purpose	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-T007 The purpose of the SEPA Credit Transfer.</i> Purpose Underlying reason for the payment transaction. Usage: Purpose is used by the end customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain. Purp Purpose2Choice	
4.47	0..n	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Supplementary Data	ISO Name ISO Definition XML Tag Type	Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block. SplmtryData SupplementaryData1	
5.0	0..n	FITo FIPayment Cancellation Request V08 +Supplementary Data	ISO Name ISO Definition XML Tag Type	Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block. SplmtryData SupplementaryData1	



2.5 Inter-PSP Negative Response to a Recall of SEPA Credit Transfer Dataset (DS-06)

2.5.1 Use of Resolution of Investigation (camt.029.001.09)

In the context of a Recall of an SCT, this message is used to transmit a negative response to:

- a Recall of Credit Transfer message (FI-to-FI Payment Cancellation Request V01, camt.056.001.08);
- a Request for Status Update on a Recall of Credit Transfer message (FI-to-FI Payment Status Request, pacs.028.001.03, refer to section 'Request for Status Update on a Recall of Credit Transfer' below);

where the following apply:

- Index 3.0 'Status': only sub-element 'Confirmation' can be used, populated with "RJCR" (Rejected Cancellation Request) only.
- Index 4.21 'Additional Information' under 'Cancellation Status Reason Information':
 - A mandatory occurrence starting with "ATR053/" followed by the information as per attribute description 'The specific reference of the Originator PSP initiating the Recall'.
 - In addition:
 - if index 4.19 'Code' under 'Reason' is set to "LEGL", two further occurrences are allowed to precise the reason and these must start with "ATR057/", and/or
 - if 'Code' under 'Reason' was "FRAD" (Fraudulent originated SCT) in the camt.056.001.08 (DS-05), then up to ten further optional occurrences are allowed, all starting with "FRAD/" followed by all information available to file a legal claim to recover the funds in case of reason code 'Fraudulent originated SCT'.
 - As a consequence, the 'SEPA Mult.' is set to [1..13].

The message caters for a single or a group negative response.

Note: Attribute AT-R001 'The type of R-message' is implied by the 'Message Name', 'camt.029.001.09', the 'Original Message Name Identification' must begin with pacs.008 (the addition of a variant number and version number is optional), and 'Status' set to "RJCR".

Note: Message elements under 'Original Transaction Reference' sequence are based on DS-02 attributes.

#	SEPA Mult	Message Element	Inter-PSP Negative Response to Recall of Credit Transfer SEPA Core Requirements	
		Document	XML Tag Type	Document Document
	1..1	Resolution Of Investigation V09	ISO Name ISO Definition	Resolution Of Investigation V09 Scope The ResolutionOfInvestigation message is sent by a case assignee to a case creator/case assigner. This message is used to inform of the resolution of a case, and optionally provides details about: - the corrective action undertaken by the case assignee; - information on the return where applicable. RsltnOfInvstgn ResolutionOfInvestigationV09
1.0	1..1	Resolution Of Investigation V09 +Assignment	ISO Name ISO Definition	Assignment Identifies the assignment of an investigation case from an assigner to an assignee. Usage: The Assigner must be the sender of this confirmation and the Assignee must be the receiver.
			XML Tag Type	Assgnmt CaseAssignment5
1.1	1..1	Resolution Of Investigation V09 +Assignment ++Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Identification Uniquely identifies the case assignment. Id Max35Text 1 .. 35 1 .. 35
1.2	1..1	Resolution Of Investigation V09 +Assignment ++Assigner	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Instructing Party: Limited to 'BICFI' to identify a PSP, 'AnyBIC' to identify a CSM or 'LEI' or 'Name' to indicate a CSM when it has no BIC. 'Name' is limited to 70 characters in length. Assigner Party who assigns the case. Usage: This is also the sender of the message. Assgnr Party40Choice
1.3	1..1	Resolution Of Investigation V09 +Assignment ++Assignee	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Instructed Party: Limited to 'BICFI' to identify a PSP, 'AnyBIC' to identify a CSM or 'LEI' or 'Name' to indicate a CSM when it has no BIC. 'Name' is limited to 70 characters in length. Assignee Party to which the case is assigned. Usage: This is also the receiver of the message. Assgne Party40Choice
1.4	1..1	Resolution Of Investigation V09 +Assignment ++Creation Date Time	ISO Name ISO Definition XML Tag Type	Creation Date Time Date and time at which the assignment was created. CreDtTm ISODateTime
2.0	0..1	Resolution Of Investigation V09 +Resolved Case	ISO Name ISO Definition XML Tag Type	Resolved Case Identifies a resolved case. RslvdCase Case5
3.0	1..1	Resolution Of Investigation V09 +Status	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Only 'Confirmation' is allowed. Status Indicates the status of the investigation. Sts InvestigationStatus5Choice
	1..1		XML Tag	xs:choice

#	SEPA Mult	Message Element	Inter-PSP Negative Response to Recall of Credit Transfer SEPA Core Requirements
3.1	1..1	Resolution Of Investigation V09 +Status ++Confirmation	<p>SEPA Usage Rule(s) Only "RJCR" is allowed.</p> <p>ISO Name Confirmation</p> <p>ISO Definition Specifies the status of the investigation, in a coded form.</p> <p>XML Tag Type Conf</p> <p>ExternalInvestigationExecutionConfirmation1Code</p> <p>ISO Length 1 .. 4</p> <p>SEPA Length 1 .. 4</p> <p>SEPA Code Restrictions</p> <p>RJCR <i>RejectedCancellationRequest</i> <i>Used when a requested cancellation has been rejected.</i></p>
3.2	1..n	Resolution Of Investigation V09 +Status ++Rejected Modification	<p>ISO Name</p> <p>ISO Definition Reason for the rejection of a modification request, in a coded form.</p> <p>XML Tag Type RjctdMod</p> <p>ModificationStatusReason1Choice</p>
3.3	1..1	Resolution Of Investigation V09 +Status ++Duplicate Of	<p>ISO Name</p> <p>ISO Definition Duplicate Of Indicates a duplicated case. Usage: When present, the case identified in the message must be closed. The case identified as duplicated (in this component) will be pursued.</p> <p>XML Tag Type DplctOf Case5</p>
3.4	1..1	Resolution Of Investigation V09 +Status ++Assignment Cancellation Confirmation	<p>ISO Name</p> <p>ISO Definition Assignment Cancellation Confirmation Indicates whether the cancellation of the assignment is confirmed or rejected. Usage: If yes, the cancellation of the assignment is confirmed. If no, the cancellation of the assignment is rejected and the investigation process will continue.</p> <p>XML Tag Type AssgnmntCxlConf YesNoIndicator</p>
4.0	1..n	Resolution Of Investigation V09 +Cancellation Details	<p>SEPA Usage Rule(s) Mandatory.</p> <p>ISO Name Cancellation Details</p> <p>ISO Definition Specifies the details of the underlying transactions being cancelled.</p> <p>XML Tag Type CxlDtls UnderlyingTransaction22</p>
4.1	0..1	Resolution Of Investigation V09 +Cancellation Details ++Original Group Information And Status	<p>ISO Name</p> <p>ISO Definition Original Group Information And Status Provides information on the original cancellation message, to which the resolution refers.</p> <p>XML Tag Type OrgnlGrpInfAndSts OriginalGroupHeader14</p>
4.2	0..n	Resolution Of Investigation V09 +Cancellation Details ++Original Payment Information And Status	<p>ISO Name</p> <p>ISO Definition Original Payment Information And Status Provides information on the original (group of) transactions, to which the cancellation status refers.</p> <p>XML Tag Type OrgnlPmtInfAndSts OriginalPaymentInstruction30</p>
4.3	1..n	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status	<p>SEPA Usage Rule(s) Mandatory.</p> <p>ISO Name Transaction Information And Status</p> <p>ISO Definition Provides details on the original transactions to which the cancellation request message refers.</p> <p>XML Tag Type TxInfAndSts PaymentTransaction102</p>

#	SEPA Mult	Message Element	Inter-PSP Negative Response to Recall of Credit Transfer SEPA Core Requirements
4.4	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Cancellation Status Identification	<p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name Cancellation Status Identification</p> <p>ISO Definition Unique and unambiguous identifier of a cancellation request status, as assigned by the assigner.</p> <p>Usage: The cancellation status identification can be used for reconciliation or to link tasks relating to the cancellation request.</p> <p>XML Tag CxlStsId</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>
4.5	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Resolved Case	<p>ISO Name Resolved Case</p> <p>ISO Definition Identifies the resolved case.</p> <p>XML Tag RslvdCase</p> <p>Type Case5</p>
4.6	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Group Information	<p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name Original Group Information</p> <p>ISO Definition Provides information on the original message.</p> <p>XML Tag OrgnlGrpInf</p> <p>Type OriginalGroupInformation29</p>
4.7	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Group Information ++++Original Message Identification	<p>ISO Name Original Message Identification</p> <p>ISO Definition Point to point reference assigned by the original instructing party to unambiguously identify the original message.</p> <p>XML Tag OrgnlMsgId</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>
4.8	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Group Information ++++Original Message Name Identification	<p>SEPA Usage Rule(s) <i>Must begin with 'pacs.008'. The addition of a variant number and version number is optional.</i></p> <p>ISO Name Original Message Name Identification</p> <p>ISO Definition Specifies the original message name identifier to which the message refers, for example, pacs.003.001.01 or MT103.</p> <p>XML Tag OrgnlMsgNmId</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>
4.9	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Group Information ++++Original Creation Date Time	<p>ISO Name Original Creation Date Time</p> <p>ISO Definition Original date and time at which the message was created.</p> <p>XML Tag OrgnlCreDtTm</p> <p>Type ISODateTime</p>
4.10	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Instruction Identification	<p>ISO Name Original Instruction Identification</p> <p>ISO Definition Unique identification, as assigned by the original instructing party for the original instructed party, to unambiguously identify the original instruction.</p> <p>XML Tag OrgnlInstrId</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>

#	SEPA Mult	Message Element	Inter-PSP Negative Response to Recall of Credit Transfer SEPA Core Requirements	
4.11	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original End To End Identification	<p>SEPA Rulebook <i>AT-T014 The Originator's reference of the SEPA Credit Transfer Transaction.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name Original End To End Identification</p> <p>ISO Definition Unique identification, as assigned by the original initiating party, to unambiguously identify the original transaction.</p> <p>XML Tag OrgnlEndToEndId</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>	
4.12	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Identification	<p>SEPA Rulebook <i>AT-T054 The Originator PSP's reference of the SEPA Credit Transfer Transaction.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name Original Transaction Identification</p> <p>ISO Definition Unique identification, as assigned by the original first instructing agent, to unambiguously identify the transaction.</p> <p>XML Tag OrgnlTxId</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>	
4.13	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Clearing System Reference	<p>ISO Name Original Clearing System Reference</p> <p>ISO Definition Unique reference, as assigned by the original clearing system, to unambiguously identify the original instruction.</p> <p>XML Tag OrgnlClrSysRef</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>	
4.14	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original UETR	<p>ISO Name Original UETR</p> <p>ISO Definition Universally unique identifier to provide the original end-to-end reference of a payment transaction.</p> <p>XML Tag OrgnlUETR</p> <p>Type UUIDv4Identifier</p> <p>Pattern [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}</p>	
4.15	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Transaction Cancellation Status	<p>SEPA Usage Rule(s) <i>Mandatory.</i> <i>Only "RJCR" is allowed.</i></p> <p>ISO Name Transaction Cancellation Status</p> <p>ISO Definition Specifies the status of the transaction cancellation request.</p> <p>XML Tag TxCxlSts</p> <p>Type CancellationIndividualStatus1Code</p> <p>SEPA Code Restrictions</p> <p>RJCR <i>RejectedCancellationRequest</i> <i>Cancellation request is rejected</i></p>	
4.16	1..n	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Cancellation Status Reason Information	<p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name Cancellation Status Reason Information</p> <p>ISO Definition Provides detailed information on the cancellation status reason.</p> <p>XML Tag CxlStsRsnInf</p> <p>Type CancellationStatusReason4</p>	

#	SEPA Mult	Message Element	Inter-PSP Negative Response to Recall of Credit Transfer SEPA Core Requirements															
4.17	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Cancellation Status Reason Information ++++Originator	<p>SEPA Rulebook <i>AT-E001 The Name of the Beneficiary or AT-C002 The BIC code of the Beneficiary PSP</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i> <i>Limited to 'AnyBIC' for an Agent or 'Name' for a non-financial institution.</i> <i>'Name' is limited to 70 characters in length.</i></p> <p>ISO Name ISO Definition XML Tag Type Originator</p> <p>ISO Name ISO Definition XML Tag Type Party that issues the cancellation status.</p> <p>ISO Name ISO Definition XML Tag Type Orgtr</p> <p>ISO Name ISO Definition XML Tag Type PartyIdentification135</p>															
4.18	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Cancellation Status Reason Information ++++Reason	<p>SEPA Rulebook <i>AT-R057 Reason Code for non-acceptance of the Recall.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name Reason ISO Definition Specifies the reason for the status report. XML Tag Rsn Type CancellationStatusReason3Choice</p>															
	1..1		XML Tag xs:choice															
4.19	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Cancellation Status Reason Information ++++Reason +++++Code	<p>SEPA Usage Rule(s) <i>Only "AC04", "AM04", "ARDT", "CUST", "LEGL", "NOAS" or "NOOR" are allowed</i></p> <p>ISO Name Code ISO Definition Reason for the cancellation status, in a coded form.</p> <p>XML Tag Cd Type ExternalPaymentCancellationRejection1Code</p> <p>ISO Length 1 .. 4 SEPA Length 1 .. 4</p> <p>SEPA Code Restrictions</p> <table> <tr> <td>AC04</td> <td><i>ClosedAccountNumber</i> <i>Account number specified has been closed on the receiver's books.</i></td> </tr> <tr> <td>AM04</td> <td><i>InsufficientFunds</i> <i>Amount of funds available to cover specified message amount is insufficient.</i></td> </tr> <tr> <td>ARDT</td> <td><i>AlreadyReturned</i> <i>Cancellation not accepted as the transaction has already been returned.</i></td> </tr> <tr> <td>CUST</td> <td><i>CustomerDecision</i> <i>Reported when the cancellation cannot be accepted because of a customer decision (Creditor).</i></td> </tr> <tr> <td>LEGL</td> <td><i>LegalDecision</i> <i>Reported when the cancellation cannot be accepted because of regulatory rules.</i></td> </tr> <tr> <td>NOAS</td> <td><i>NoAnswerFromCustomer</i> <i>No response from beneficiary (to the cancellation request).</i></td> </tr> <tr> <td>NOOR</td> <td><i>NoOriginalTransactionReceived</i> <i>Original transaction (subject to cancellation) never received.</i></td> </tr> </table>	AC04	<i>ClosedAccountNumber</i> <i>Account number specified has been closed on the receiver's books.</i>	AM04	<i>InsufficientFunds</i> <i>Amount of funds available to cover specified message amount is insufficient.</i>	ARDT	<i>AlreadyReturned</i> <i>Cancellation not accepted as the transaction has already been returned.</i>	CUST	<i>CustomerDecision</i> <i>Reported when the cancellation cannot be accepted because of a customer decision (Creditor).</i>	LEGL	<i>LegalDecision</i> <i>Reported when the cancellation cannot be accepted because of regulatory rules.</i>	NOAS	<i>NoAnswerFromCustomer</i> <i>No response from beneficiary (to the cancellation request).</i>	NOOR	<i>NoOriginalTransactionReceived</i> <i>Original transaction (subject to cancellation) never received.</i>	
AC04	<i>ClosedAccountNumber</i> <i>Account number specified has been closed on the receiver's books.</i>																	
AM04	<i>InsufficientFunds</i> <i>Amount of funds available to cover specified message amount is insufficient.</i>																	
ARDT	<i>AlreadyReturned</i> <i>Cancellation not accepted as the transaction has already been returned.</i>																	
CUST	<i>CustomerDecision</i> <i>Reported when the cancellation cannot be accepted because of a customer decision (Creditor).</i>																	
LEGL	<i>LegalDecision</i> <i>Reported when the cancellation cannot be accepted because of regulatory rules.</i>																	
NOAS	<i>NoAnswerFromCustomer</i> <i>No response from beneficiary (to the cancellation request).</i>																	
NOOR	<i>NoOriginalTransactionReceived</i> <i>Original transaction (subject to cancellation) never received.</i>																	
4.20	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Cancellation Status Reason Information ++++Reason +++++Proprietary	<p>ISO Name Proprietary ISO Definition Reason for the status, in a proprietary form. XML Tag Prtry Type Max35Text</p> <p>ISO Length 1 .. 35 SEPA Length 1 .. 35</p>															

#	SEPA Mult	Message Element	Inter-PSP Negative Response to Recall of Credit Transfer SEPA Core Requirements	
4.21	1.. 13	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Cancellation Status Reason Information ++++Additional Information	<p>SEPA Rulebook</p> <p>SEPA Usage Rule(s) Mandatory.</p> <p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag</p> <p>Type</p> <p>ISO Length</p> <p>SEPA Length</p>	<p><i>AT-R053 The specific reference of the Originator PSP initiating the Recall.</i></p> <p><i>AT-R057 Reason code for non-acceptance of the Recall.</i></p> <p><i>First occurrence is mandatory and must start with "ATR053/" followed by the information as per attribute description.</i></p> <p><i>When reason code is "LEGL" under 4.19, two further occurrences are allowed to precise the reason and must start with "ATR057/".</i></p> <p><i>When reason code was "FRAD" in the camt.056, then up to ten further optional occurrences are allowed, all starting with "FRAD/" followed by all information available to file a legal claim to recover the funds in case of reason code 'Fraudulent originated SEPA Credit Transfer'.</i></p> <p>AddtlInf</p> <p>Max105Text</p> <p>1 .. 105</p> <p>I .. 105</p>
4.22	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Resolution Related Information	<p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag</p> <p>Type</p>	<p>Resolution Related Information</p> <p>Reference of a return or a reversal transaction that is initiated to fix the case under investigation as part of the resolution.</p> <p>RsltnRltdInf</p> <p>ResolutionData1</p>
4.23	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Interbank Settlement Amount	<p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag</p> <p>Type</p> <p>SEPA FractDigits</p> <p>TotalDigits</p> <p>SEPA Inclusive</p>	<p>Original Interbank Settlement Amount</p> <p>Amount of money moved between the instructing agent and the instructed agent, as provided in the original instruction.</p> <p>OrgnlIntrBkSttlmAmt</p> <p>ActiveOrHistoricCurrencyAndAmount</p> <p>5</p> <p>18</p> <p>0 ..</p>
4.24	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Interbank Settlement Date	<p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag</p> <p>Type</p>	<p>Original Interbank Settlement Date</p> <p>Date, as provided in the original transaction, on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.</p> <p>OrgnlIntrBkSttlmDt</p> <p>ISODate</p>
4.25	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Assigner	<p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag</p> <p>Type</p>	<p>Assigner</p> <p>Party who assigns the case.</p> <p>Usage: This is also the agent that instructs the next party in the chain to carry out the (set of) cancellation request(s).</p> <p>Assgnr</p> <p>Party40Choice</p>
4.26	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Assignee	<p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag</p> <p>Type</p>	<p>Assignee</p> <p>Party to which the case is assigned.</p> <p>Usage: This is also the agent that is instructed by the previous party in the chain to carry out the (set of) cancellation request(s).</p> <p>Assgne</p> <p>Party40Choice</p>

#	SEPA Mult	Message Element	Inter-PSP Negative Response to Recall of Credit Transfer SEPA Core Requirements	
4.27	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference	<p>SEPA Rulebook</p> <p>SEPA Usage Rule(s) <i>Mandatory.</i> The yellow shaded message elements under 'Original Transaction Reference' must be populated with the same value as the message elements of the original instruction.</p> <p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<i>An exact copy of all attributes of the initially sent DS-02 which is to be cancelled.</i> <i>Original Transaction Reference</i> Key elements used to identify the original transaction that is being referred to. OrgnlTxRef OriginalTransactionReference28
4.28	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Interbank Settlement Amount	<p>SEPA Rulebook</p> <p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p> <p>SEPA FractDigits</p> <p>TotalDigits</p> <p>SEPA Inclusive</p>	<i>AT-T002 Amount of the SEPA Credit Transfer in Euro</i> Interbank Settlement Amount Amount of money moved between the instructing agent and the instructed agent. IntrBkSttlmAmt ActiveOrHistoricCurrencyAndAmount 2 18 0.01 .. 999999999.99
4.29	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Amount	<p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	Amount Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party. Amt AmountType4Choice
4.30	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Interbank Settlement Date	<p>SEPA Rulebook</p> <p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<i>AT-T051 Settlement Date of the Credit Transfer in Euro</i> Interbank Settlement Date Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. IntrBkSttlmDt ISODate
4.31	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Requested Collection Date	<p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	Requested Collection Date Date and time at which the creditor requests that the amount of money is to be collected from the debtor. ReqdColltnDt ISODate
4.32	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Requested Execution Date	<p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	Requested Execution Date Date at which the initiating party requests the clearing agent to process the payment. Usage: This is the date on which the debtor's account is to be debited. If payment by cheque, the date when the cheque must be generated by the bank. ReqdExctnDt DateAndDateTime2Choice
4.33	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Creditor Scheme Identification	<p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	Creditor Scheme Identification Credit party that signs the mandate. CdtrSchmeId PartyIdentification135

#	SEPA Mult	Message Element	Inter-PSP Negative Response to Recall of Credit Transfer SEPA Core Requirements	
4.34	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Settlement Information	ISO Name XML Tag Type	Settlement Information Specifies the details on how the settlement of the original transaction(s) between the instructing agent and the instructed agent was completed. Stlmlnfo SettlementInstruction7
4.35	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Payment Type Information	SEPA Rulebook ISO Name XML Tag Type	AT-T001 Identification code of the Scheme. AT-T008 Category Purpose of the Credit Transfer. <i>If the original transaction was sent according to Annex V (Use of Extended Remittance Information) of the SCT Rulebook (refer to section 'Inter-PSP payment with use of the Extended Remittance Information option' below), then 'Local Instrument/Code' must be populated with "PERI" (Payment with Extended Remittance Information).</i> Payment Type Information Set of elements used to further specify the type of transaction. PmtTpInf PaymentTypeInformation27
4.36	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Payment Method	ISO Name XML Tag Type	Payment Method Specifies the means of payment that will be used to move the amount of money. PmtMtd PaymentMethod4Code
4.37	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Mandate Related Information	ISO Name XML Tag Type	Mandate Related Information Provides further details of the mandate signed between the creditor and the debtor. MndtRltdInf MandateRelatedInformation14
4.38	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Remittance Information	SEPA Rulebook ISO Name XML Tag Type	AT-T009 Remittance information or AT-T010 The unstructured Remittance Information sent by the Originator to the Beneficiary in the Credit Transfer Instruction (in case of use of the Extended Remittance Information (ERI) option in the original SEPA Credit Transfer, AT-T011 The structured Remittance Information sent by the Originator to the Beneficiary in the SEPA Credit Transfer Instruction, will NOT be transported here). Remittance Information Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system. RmtInf RemittanceInformation16
4.39	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Ultimate Debtor	SEPA Rulebook SEPA Usage Rule(s) ISO Name XML Tag Type	AT-P006 Name of the Originator Reference Party. AT-P007 Identification Code of the Originator Reference Party. <i>Only 'Party' is allowed.</i> Ultimate Debtor Ultimate party that owes an amount of money to the (ultimate) creditor. UltmtDbtr Party40Choice

#	SEPA Mult	Message Element	Inter-PSP Negative Response to Recall of Credit Transfer SEPA Core Requirements	
4.40	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Debtor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-P001 Name of the Originator - Mandatory.</i> <i>AT-P005 Address of the Originator.</i> <i>AT-P004 Originator's Identification Code.</i> <i>Only 'Party' is allowed.</i> Debtor Party that owes an amount of money to the (ultimate) creditor. Dbtr Party40Choice
4.41	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Debtor Account	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-D001 The IBAN of the account of the Originator.</i> <i>AT-P003 The Proxy/Alias of the account of the Originator.</i> Debtor Account Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction. DbtrAcct CashAccount38
4.42	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Debtor Agent	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-D002 The BIC code of the Originator PSP.</i> Debtor Agent Financial institution servicing an account for the debtor. DbtrAgt BranchAndFinancialInstitutionIdentification6
4.43	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Debtor Agent Account	ISO Name ISO Definition XML Tag Type	Debtor Agent Account Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain. DbtrAgtAcct CashAccount38
4.44	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Creditor Agent	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-C002 The BIC code of the Beneficiary PSP.</i> Creditor Agent Financial institution servicing an account for the creditor. CdtrAgt BranchAndFinancialInstitutionIdentification6
4.45	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Creditor Agent Account	ISO Name ISO Definition XML Tag Type	Creditor Agent Account Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction. CdtrAgtAcct CashAccount38
4.46	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Creditor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-E001 Name of the Beneficiary – Mandatory.</i> <i>AT-E004 Address of the Beneficiary.</i> <i>AT-E005 Beneficiary Identification Code.</i> <i>Only 'Party' is allowed.</i> Creditor Party to which an amount of money is due. Cdtr Party40Choice
4.47	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Creditor Account	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-C001 The IBAN of the account of the Beneficiary.</i> <i>AT-E003 The Proxy/Alias of the account of the Beneficiary.</i> Creditor Account Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction. CdtrAcct CashAccount38

#	SEPA Mult	Message Element	Inter-PSP Negative Response to Recall of Credit Transfer SEPA Core Requirements	
4.48	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Ultimate Creditor	<p>SEPA Rulebook</p> <p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p><i>AT-E007 Name of the Beneficiary Reference Party.</i></p> <p><i>AT-E010 Identification Code of the Beneficiary Reference Party.</i></p> <p>SEPA Usage Rule(s) Only 'Party' is allowed.</p> <p>Ultimate Creditor</p> <p>Ultimate party to which an amount of money is due.</p> <p>UltmtCdrtr</p> <p>Party40Choice</p>
4.49	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Purpose	<p>SEPA Rulebook</p> <p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p><i>AT-T007 The purpose of the SEPA Credit Transfer.</i></p> <p>Purpose</p> <p>Underlying reason for the payment transaction.</p> <p>Usage:</p> <p>Purpose is used by the end customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain.</p> <p>Purp</p> <p>Purpose2Choice</p>
5.0	0..1	Resolution Of Investigation V09 +Modification Details	<p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p>Modification Details</p> <p>Specifies the details of the underlying transaction being modified.</p> <p>ModDtls</p> <p>PaymentTransaction107</p>
6.0	0..1	Resolution Of Investigation V09 +Claim Non Receipt Details	<p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p>Claim Non Receipt Details</p> <p>Specifies the details of the underlying transaction for which a claim non receipt has been initiated.</p> <p>ClmNonRctDtls</p> <p>ClaimNonReceipt2Choice</p>
7.0	0..1	Resolution Of Investigation V09 +Statement Details	<p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p>Statement Details</p> <p>Details on the underlying statement entry.</p> <p>StmtDtls</p> <p>StatementResolutionEntry4</p>
8.0	0..1	Resolution Of Investigation V09 +Correction Transaction	<p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p>Correction Transaction</p> <p>References a transaction initiated to fix the case under investigation.</p> <p>CrrctnTx</p> <p>CorrectiveTransaction4Choice</p>
9.0	0..1	Resolution Of Investigation V09 +Resolution Related Information	<p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p>Resolution Related Information</p> <p>Reference to fix the case under investigation as part of the resolution.</p> <p>RsltnRltdInf</p> <p>ResolutionData1</p>
10.0	0..n	Resolution Of Investigation V09 +Supplementary Data	<p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p>Supplementary Data</p> <p>Additional information that cannot be captured in the structured elements and/or any other specific block.</p> <p>SplmtryData</p> <p>SupplementaryData1</p>



2.6 Inter-PSP Positive Response to a Recall of SEPA Credit Transfer Dataset (DS-06)

2.6.1 Use of inter-PSP return credit transfer message (pacs.004.001.09)

The positive response to a:

- Recall of Credit Transfer message (camt.056.001.08);
- Request for Status Update on a Recall of Credit Transfer message (pacs.028.001.03, refer to section 'Request for Status Update on a Recall of Credit Transfer' below);

is to be made using an inter-PSP return credit transfer message (pacs.004.001.09), where the following apply:

- Index 1.9 'Interbank Settlement Date' to be populated with AT-R056 'The Settlement Date for the positive response to a Recall'.
- Index 3.13 'Returned Interbank Settlement Amount' to be populated with AT-R054 'The returned amount of a positive response to the Recall in euro'.
- Index 3.17 'Returned Instructed Amount' may be used.
- Index 3.22 'Amount' (under 'Charges Information') to be populated with AT-R055 'The fee for the positive response to the Recall in euro', if any.
- Index 3.24 'Financial Institution Identification' (under 'Agent' under 'Charges Information') to be populated with AT-C002 'The BIC code of the Beneficiary PSP'.
- Index 3.31 'Originator' to be populated with AT-R002 'The Identification of the type of party initiating the "R" message.
- Index 3.33 'Reason/Code' (under 'Return Reason Information') to be populated only with "FOCR" (Following Cancellation Request).
- Index 3.35 'Additional Information' (under 'Return Reason Information') to be used with a mandatory occurrence starting with "ATR053/" followed by the information as per attribute description 'The Specific Reference of the Originator PSP initiating the Recall'.

The message caters for a single or a group positive response.

Note: Attribute AT-R001 'The type of R-message' is implied by the 'Message Name', 'pacs.004.001.09', the 'Original Message Name Identification' must begin with pacs.008 (the addition of a variant number and version number is optional)and 'Reason' under 'Return Reason Information' set to "FOCR".

Note: Message elements under 'Original Transaction Reference' sequence are based on DS-02 attributes.

#	SEPA Mult	Message Element	Inter-PSP Positive Response to Recall of Credit Transfer SEPA Core Requirements	
		Document	XML Tag Type	Document Document
	1..1	Payment Return V09	ISO Name ISO Definition	Payment Return V09 Scope The PaymentReturn message is sent by an agent to the previous agent in the payment chain to undo a payment previously settled.
			XML Tag Type	PmtRtr PaymentReturnV09
1.0	1..1	Payment Return V09 +Group Header	ISO Name ISO Definition	Group Header Set of characteristics shared by all individual transactions included in the message.
			XML Tag Type	GrpHdr GroupHeader90
1.1	1..1	Payment Return V09 +Group Header ++Message Identification	ISO Name ISO Definition	Message Identification Point to point reference, as assigned by the instructing party and sent to the next party in the chain, to unambiguously identify the message. Usage: The instructing party has to make sure that MessageIdentification is unique per instructed party for a pre-agreed period.
			XML Tag Type ISO Length SEPA Length	MsgId Max35Text 1 .. 35 1 .. 35
1.2	1..1	Payment Return V09 +Group Header ++Creation Date Time	ISO Name ISO Definition	Creation Date Time Date and time at which the message was created.
			XML Tag Type	CreDtTm ISODateTime
1.3	0..2	Payment Return V09 +Group Header ++Authorisation	ISO Name ISO Definition	Authorisation User identification or any user key to be used to check whether the initiating party is allowed to initiate transactions from the account specified in the message.
			XML Tag Type	Usage: The content is not of a technical nature, but reflects the organisational structure at the initiating side. The authorisation element can typically be used in relay scenarios, payment initiations, payment returns or payment reversals that are initiated on behalf of a party different from the initiating party. Authstn Authorisation1Choice
1.4	0..1	Payment Return V09 +Group Header ++Batch Booking	ISO Name ISO Definition	Batch Booking Identifies whether a single entry per individual transaction or a batch entry for the sum of the amounts of all transactions within the group of a message is requested.
			XML Tag Type	Usage: Batch booking is used to request and not order a possible batch booking. BtchBookg BatchBookingIndicator
1.5	1..1	Payment Return V09 +Group Header ++Number Of Transactions	ISO Name ISO Definition	Number Of Transactions Number of individual transactions contained in the message.
			XML Tag Type Pattern	NbOfTx Max15NumericText [0-9]{1,15}

#	SEPA Mult	Message Element	Inter-PSP Positive Response to Recall of Credit Transfer SEPA Core Requirements	
1.6	0..1	Payment Return V09 +Group Header ++Control Sum	ISO Name ISO Definition XML Tag Type <i>SEPA FractDigits</i> TotalDigits	Control Sum Total of all individual amounts included in the message, irrespective of currencies. CtrlSum DecimalNumber 17 18
1.7	0..1	Payment Return V09 +Group Header ++Group Return	ISO Name ISO Definition XML Tag Type	Group Return Indicates whether the return applies to the whole group of transactions or to individual transactions within the original group(s). GrpRtr TrueFalseIndicator
1.8	1..1	Payment Return V09 +Group Header ++Total Returned Interbank Settlement Amount	<i>SEPA Usage Rule(s)</i> Mandatory. <i>Only 'EUR' is allowed.</i> <i>Amount must be 0.01 or more and 999999999999.99 or less.</i> <i>The fractional part has a maximum of two digits.</i> <i>SEPA Format Rule(s)</i> ISO Name ISO Definition XML Tag Type <i>SEPA FractDigits</i> TotalDigits <i>SEPA Inclusive</i>	Total Returned Interbank Settlement Amount Total amount of money moved between the instructing agent and the instructed agent in the return message. TtlRtrdIntrBkSttlmAmt ActiveCurrencyAndAmount 2 18 0.01 .. 999999999999.99
1.9	1..1	Payment Return V09 +Group Header ++Interbank Settlement Date	<i>SEPA Rulebook</i> <i>SEPA Usage Rule(s)</i> Mandatory. ISO Name ISO Definition XML Tag Type	<i>AT-R056 Settlement Date for the positive response to a Recall.</i> Interbank Settlement Date Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. IntrBkSttlmDt ISODate
1.10	1..1	Payment Return V09 +Group Header ++Settlement Information	ISO Name ISO Definition XML Tag Type	Settlement Information Specifies the details on how the settlement of the transaction(s) between the instructing agent and the instructed agent is completed. SttlmInf SettlementInstruction7
1.11	1..1	Payment Return V09 +Group Header ++Settlement Information +++Settlement Method	<i>SEPA Usage Rule(s)</i> Only "CLRG", "INGA" and "INDA" are allowed. ISO Name ISO Definition XML Tag Type <i>SEPA Code Restrictions</i> <i>CLRG</i> <i>INDA</i> <i>INGA</i>	Settlement Method Method used to settle the (batch of) payment instructions. SttlmMtd SettlementMethod1Code <i>ClearingSystem</i> <i>Settlement is done through a payment clearing system.</i> <i>InstructedAgent</i> <i>Settlement is done by the agent instructed to execute a payment instruction.</i> <i>InstructingAgent</i> <i>Settlement is done by the agent instructing and forwarding the payment to the next party in the payment chain.</i>

#	SEPA Mult	Message Element	Inter-PSP Positive Response to Recall of Credit Transfer SEPA Core Requirements
1.12	0..1	Payment Return V09 +Group Header ++Settlement Information +++Settlement Account	<p>SEPA Usage Rule(s) Only 'Identification' is allowed.</p> <p>ISO Name Settlement Account</p> <p>ISO Definition A specific purpose account used to post debit and credit entries as a result of the transaction.</p> <p>XML Tag Type SttlmAcct CashAccount38</p>
1.13	0..1	Payment Return V09 +Group Header ++Settlement Information +++Clearing System	<p>ISO Name Clearing System</p> <p>ISO Definition Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed.</p> <p>XML Tag Type ClrSys ClearingSystemIdentification3Choice</p>
	1..1		XML Tag xs:choice
1.14	1..1	Payment Return V09 +Group Header ++Settlement Information +++Clearing System ++++Code	<p>ISO Name Code</p> <p>ISO Definition Infrastructure through which the payment instruction is processed, as published in an external clearing system identification code list.</p> <p>XML Tag Type Cd ExternalCashClearingSystem1Code</p> <p>ISO Length 1 .. 3 SEPA Length 1 .. 3</p>
1.15	1..1	Payment Return V09 +Group Header ++Settlement Information +++Clearing System ++++Proprietary	<p>ISO Name Proprietary</p> <p>ISO Definition Clearing system identification in a proprietary form.</p> <p>XML Tag Type Prtry Max35Text</p> <p>ISO Length 1 .. 35 SEPA Length 1 .. 35</p>
1.16	0..1	Payment Return V09 +Group Header ++Settlement Information +++Instructing Reimbursement Agent	<p>ISO Name Instructing Reimbursement Agent</p> <p>ISO Definition Agent through which the instructing agent will reimburse the instructed agent.</p> <p>XML Tag Type InstgRmbrsmntAgt BranchAndFinancialInstitutionIdentification6</p> <p>Usage: If InstructingAgent and InstructedAgent have the same reimbursement agent, then only InstructingReimbursementAgent must be used.</p>
1.17	0..1	Payment Return V09 +Group Header ++Settlement Information +++Instructing Reimbursement Agent Account	<p>ISO Name Instructing Reimbursement Agent Account</p> <p>ISO Definition Unambiguous identification of the account of the instructing reimbursement agent account at its servicing agent in the payment chain.</p> <p>XML Tag Type InstgRmbrsmntAgtAcct CashAccount38</p>
1.18	0..1	Payment Return V09 +Group Header ++Settlement Information +++Instructed Reimbursement Agent	<p>ISO Name Instructed Reimbursement Agent</p> <p>ISO Definition Agent at which the instructed agent will be reimbursed.</p> <p>XML Tag Type InstdRmbrsmntAgt BranchAndFinancialInstitutionIdentification6</p> <p>Usage: If InstructedReimbursementAgent contains a branch of the InstructedAgent, then the party in InstructedAgent will claim reimbursement from that branch/will be paid by that branch.</p> <p>Usage: If InstructingAgent and InstructedAgent have the same reimbursement agent, then only InstructingReimbursementAgent must be used.</p>
1.19	0..1	Payment Return V09 +Group Header ++Settlement Information +++Instructed Reimbursement Agent Account	<p>ISO Name Instructed Reimbursement Agent Account</p> <p>ISO Definition Unambiguous identification of the account of the instructed reimbursement agent account at its servicing agent in the payment chain.</p> <p>XML Tag Type InstdRmbrsmntAgtAcct CashAccount38</p>

#	SEPA Mult	Message Element	Inter-PSP Positive Response to Recall of Credit Transfer SEPA Core Requirements	
1.20	0..1	Payment Return V09 +Group Header ++Settlement Information +++Third Reimbursement Agent	ISO Name ISO Definition XML Tag Type	Third Reimbursement Agent Agent at which the instructed agent will be reimbursed. Usage: If ThirdReimbursementAgent contains a branch of the InstructedAgent, then the party in InstructedAgent will claim reimbursement from that branch/will be paid by that branch. ThrdRmbrsmntAgt BranchAndFinancialInstitutionIdentification6
1.21	0..1	Payment Return V09 +Group Header ++Settlement Information +++Third Reimbursement Agent Account	ISO Name ISO Definition XML Tag Type	Third Reimbursement Agent Account Unambiguous identification of the account of the third reimbursement agent account at its servicing agent in the payment chain. ThrdRmbrsmntAgtAcct CashAccount38
1.22	0..1	Payment Return V09 +Group Header ++Instructing Agent	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Only 'BICFI' is allowed. Instructing Agent Agent that instructs the next party in the chain to carry out the (set of) instruction(s). Usage: The instructing agent is the party sending the return message and not the party that sent the original instruction that is being returned. InstgAgt BranchAndFinancialInstitutionIdentification6
1.23	0..1	Payment Return V09 +Group Header ++Instructed Agent	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Only 'BICFI' is allowed. Instructed Agent Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s). Usage: The instructed agent is the party receiving the return message and not the party that received the original instruction that is being returned. InstdAgt BranchAndFinancialInstitutionIdentification6
2.0	0..1	Payment Return V09 +Original Group Information	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Sub-elements of 'Original Group Information' must be present in either 'Original Group Information' or in 'Transaction Information'. Original Group Information Information concerning the original group of transactions, to which the message refers. OrgnlGrpInf OriginalGroupHeader18
2.1	1..1	Payment Return V09 +Original Group Information ++Original Message Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Message Identification Point to point reference, as assigned by the original instructing party, to unambiguously identify the original message. OrgnlMsgId Max35Text 1 .. 35 1 .. 35
2.2	1..1	Payment Return V09 +Original Group Information ++Original Message Name Identification	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Must begin with 'pacs.008'. The addition of a variant number and version number is optional. Original Message Name Identification Specifies the original message name identifier to which the message refers. OrgnlMsgNmId Max35Text 1 .. 35 1 .. 35
2.3	0..1	Payment Return V09 +Original Group Information ++Original Creation Date Time	ISO Name ISO Definition XML Tag Type	Original Creation Date Time Date and time at which the original message was created. OrgnlCreDtTm ISODateTime

#	SEPA Mult	Message Element	Inter-PSP Positive Response to Recall of Credit Transfer SEPA Core Requirements		
2.4	0..n	Payment Return V09 +Original Group Information ++Return Reason Information	ISO Name ISO Definition XML Tag Type	Return Reason Information Provides detailed information on the return reason. RtrRsnInf PaymentReturnReason6	
3.0	1..n	Payment Return V09 +Transaction Information	SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type	Transaction Information Information concerning the original transactions, to which the return message refers. TxInf PaymentTransaction112	
3.1	1..1	Payment Return V09 +Transaction Information ++Return Identification	SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type	Return Identification Unique identification, as assigned by an instructing party for an instructed party, to unambiguously identify the returned transaction. Usage: The instructing party is the party sending the return message and not the party that sent the original instruction that is being returned. RtrId Max35Text ISO Length SEPA Length	1 .. 35 1 .. 35
3.2	0..1	Payment Return V09 +Transaction Information ++Original Group Information	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Sub-elements of 'Original Group Information' must be present in either 'Original Group Information' or in 'Transaction Information'. Original Group Information Provides information on the original message. OrgnlGrpInf OriginalGroupInformation29	
3.3	1..1	Payment Return V09 +Transaction Information ++Original Group Information +++Original Message Identification	ISO Name ISO Definition XML Tag Type	Original Message Identification Point to point reference assigned by the original instructing party to unambiguously identify the original message. OrgnlMsgId Max35Text ISO Length SEPA Length	1 .. 35 1 .. 35
3.4	1..1	Payment Return V09 +Transaction Information ++Original Group Information +++Original Message Name Identification	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Must begin with 'pacs.008'. The addition of a variant number and version number is optional. Original Message Name Identification Specifies the original message name identifier to which the message refers, for example, pacs.003.001.01 or MT103. OrgnlMsgNmId Max35Text ISO Length SEPA Length	1 .. 35 1 .. 35
3.5	0..1	Payment Return V09 +Transaction Information ++Original Group Information +++Original Creation Date Time	ISO Name ISO Definition XML Tag Type	Original Creation Date Time Original date and time at which the message was created. OrgnlCreDtTm ISODateTime	
3.6	0..1	Payment Return V09 +Transaction Information ++Original Instruction Identification	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Mandatory if provided in the original instruction. Original Instruction Identification Unique identification, as assigned by the original instructing party for the original instructed party, to unambiguously identify the original instruction. OrgnlInstrId Max35Text ISO Length SEPA Length	1 .. 35 1 .. 35

#	SEPA Mult	Message Element	Inter-PSP Positive Response to Recall of Credit Transfer SEPA Core Requirements	
3.7	1..1	Payment Return V09 +Transaction Information ++Original End To End Identification	<p>SEPA Rulebook <i>AT-T014 The Originator's reference of the SEPA Credit Transfer Transaction.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name ISO Definition Original End To End Identification Unique identification, as assigned by the original initiating party, to unambiguously identify the original transaction.</p> <p>XML Tag Type OrgnlEndToEndId ISO Length Max35Text SEPA Length 1 .. 35</p>	
3.8	1..1	Payment Return V09 +Transaction Information ++Original Transaction Identification	<p>SEPA Rulebook <i>AT-T054 The Originator PSP's reference of the SEPA Credit Transfer Transaction.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name ISO Definition Must contain a reference that is meaningful to the Originator's PSP and is unique over time. Original Transaction Identification Unique identification, as assigned by the original first instructing agent, to unambiguously identify the transaction.</p> <p>XML Tag Type OrgnlTxId ISO Length Max35Text SEPA Length 1 .. 35</p>	
3.9	0..1	Payment Return V09 +Transaction Information ++Original UETR	<p>ISO Name ISO Definition Original UETR Universally unique identifier to provide the original end-to-end reference of a payment transaction.</p> <p>XML Tag Type OrgnlUETR Pattern UUIDv4Identifier [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}</p>	
3.10	0..1	Payment Return V09 +Transaction Information ++Original Clearing System Reference	<p>ISO Name ISO Definition Original Clearing System Reference Unique reference, as assigned by the original clearing system, to unambiguously identify the original instruction.</p> <p>XML Tag Type OrgnlClrSysRef ISO Length Max35Text SEPA Length 1 .. 35</p>	
3.11	1..1	Payment Return V09 +Transaction Information ++Original Interbank Settlement Amount	<p>SEPA Rulebook <i>AT-T002 Amount of the SEPA Credit Transfer in Euro.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>SEPA Format Rule(s) Only 'EUR' is allowed.</p> <p>ISO Name ISO Definition Amount must be 0.01 or more and 999999999.99 or less.</p> <p>XML Tag Type OrgnlIntrBkSttlmAmt SEPA FractDigits The fractional part has a maximum of two digits.</p> <p>TotalDigits 2 SEPA Inclusive 18 0.01 .. 999999999.99</p>	

#	SEPA Mult	Message Element	Inter-PSP Positive Response to Recall of Credit Transfer SEPA Core Requirements	
3.12	0..1	Payment Return V09 +Transaction Information ++Original Interbank Settlement Date	ISO Name ISO Definition	Original Interbank Settlement Date Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. Usage: the OriginalInterbankSettlementDate is the interbank settlement date of the original instruction return message, and not of the return message. OrgnlIntrBkSttlmDt ISODate
3.13	1..1	Payment Return V09 +Transaction Information ++Returned Interbank Settlement Amount	SEPA Rulebook SEPA Usage Rule(s) SEPA Format Rule(s) ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits SEPA Inclusive	AT-R054 <i>The returned amount of a positive response to the Recall in euro.</i> <i>The amount must be equal to the 'Original Interbank Settlement Amount' less, if present, the 'Amount' under 'Charges Information'. Only 'EUR' is allowed.</i> <i>Amount must be 0.01 or more and 999999999.99 or less.</i> <i>The fractional part has a maximum of two digits.</i> Returned Interbank Settlement Amount Amount of money to be moved between the instructing agent and the instructed agent in the returned instruction. RtrdIntrBkSttlmAmt ActiveCurrencyAndAmount 2 18 0.01 .. 999999999.99
3.14	0..1	Payment Return V09 +Transaction Information ++Interbank Settlement Date	ISO Name ISO Definition XML Tag Type	Interbank Settlement Date Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. Usage: the InterbankSettlementDate is the interbank settlement date of the return message, and not of the original instruction. IntrBkSttlmDt ISODate
3.15	0..1	Payment Return V09 +Transaction Information ++Settlement Priority	ISO Name ISO Definition XML Tag Type	Settlement Priority Indicator of the urgency or order of importance that the instructing party would like the instructed party to apply to the processing of the settlement instruction. Usage: the SettlementPriority is the settlement priority of the return message, and not of the original instruction. SttlmPrt Priority3Code
3.16	0..1	Payment Return V09 +Transaction Information ++Settlement Time Indication	ISO Name ISO Definition XML Tag Type	Settlement Time Indication Provides information on the occurred settlement time(s) of the payment transaction. SttlmTmIndctn SettlementDateTimeIndication1

#	SEPA Mult	Message Element	Inter-PSP Positive Response to Recall of Credit Transfer SEPA Core Requirements
3.17	0..1	Payment Return V09 +Transaction Information ++Returned Instructed Amount	<p>SEPA Usage Rule(s) Only 'EUR' is allowed. Amount must be 0.01 or more and 999999999.99 or less. The fractional part has a maximum of two digits.</p> <p>SEPA Format Rule(s)</p> <p>ISO Name</p> <p>ISO Definition Returned Instructed Amount Amount of money to be moved between the debtor and the creditor, before deduction of charges, in the returned transaction. Usage: This amount has to be transported unchanged through the transaction chain. RtrdInstdAmt</p> <p>XML Tag</p> <p>Type ActiveOrHistoricCurrencyAndAmount</p> <p>SEPA FractDigits 2</p> <p>TotalDigits 18</p> <p>SEPA Inclusive 0.01 .. 999999999.99</p>
3.18	0..1	Payment Return V09 +Transaction Information ++Exchange Rate	<p>ISO Name</p> <p>ISO Definition Exchange Rate Factor used to convert an amount from one currency into another. This reflects the price at which one currency was bought with another currency. XchgRate</p> <p>XML Tag</p> <p>Type BaseOneRate</p> <p>SEPA FractDigits 10</p> <p>TotalDigits 11</p>
3.19	0..1	Payment Return V09 +Transaction Information ++Compensation Amount	<p>ISO Name</p> <p>ISO Definition Compensation Amount Amount of money asked or paid as compensation for the processing of the instruction. CompstnAmt</p> <p>XML Tag</p> <p>Type ActiveOrHistoricCurrencyAndAmount</p> <p>SEPA FractDigits 5</p> <p>TotalDigits 18</p> <p>SEPA Inclusive 0 ..</p>
3.20	0..1	Payment Return V09 +Transaction Information ++Charge Bearer	<p>SEPA Usage Rule(s) Only "SLEV" is allowed.</p> <p>ISO Name</p> <p>ISO Definition Charge Bearer Specifies which party/parties will bear the charges associated with the processing of the payment transaction.</p> <p>Usage: The ChargeBearer applies to the return message, not to the original instruction. ChrgBr</p> <p>XML Tag</p> <p>Type ChargeBearerType1Code</p> <p>SEPA Code Restrictions</p> <p>SLEV FollowingServiceLevel Charges are to be applied following the rules agreed in the service level and/or scheme.</p>
3.21	0..1	Payment Return V09 +Transaction Information ++Charges Information	<p>SEPA Usage Rule(s) Only one occurrence is allowed.</p> <p>ISO Name</p> <p>ISO Definition Charges Information Provides information on the charges to be paid by the charge bearer(s) related to the processing of the return transaction.</p> <p>XML Tag</p> <p>Type ChrgsInf</p> <p>Charges7</p>

#	SEPA Mult	Message Element	Inter-PSP Positive Response to Recall of Credit Transfer SEPA Core Requirements	
3.22	1..1	Payment Return V09 +Transaction Information ++Charges Information +++Amount	<p>SEPA Rulebook <i>AT-R055 Fee for the positive response to the Recall in euro.</i></p> <p>SEPA Usage Rule(s) <i>Only 'EUR' is allowed.</i> <i>Amount must be 0.01 or more and 99999999.99 or less.</i></p> <p>SEPA Format Rule(s)</p> <p>ISO Name</p> <p>ISO Definition Transaction charges to be paid by the charge bearer.</p> <p>XML Tag Type</p> <p>SEPA FractDigits 2</p> <p>TotalDigits 18</p> <p>SEPA Inclusive 0.01 .. 99999999.99</p>	
3.23	1..1	Payment Return V09 +Transaction Information ++Charges Information +++Agent	<p>ISO Name Agent</p> <p>ISO Definition Agent that takes the transaction charges or to which the transaction charges are due.</p> <p>XML Tag Type</p>	Agt BranchAndFinancialInstitutionIdentification6
3.24	1..1	Payment Return V09 +Transaction Information ++Charges Information +++Agent ++++Financial Institution Identification	<p>SEPA Rulebook <i>AT-C002 The BIC code of the Beneficiary PSP.</i></p> <p>SEPA Usage Rule(s) <i>Only 'BICFI' is allowed.</i></p> <p>ISO Name</p> <p>ISO Definition Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.</p> <p>XML Tag Type</p>	FinInstnId FinancialInstitutionIdentification18
3.25	0..1	Payment Return V09 +Transaction Information ++Charges Information +++Agent ++++Branch Identification	<p>ISO Name</p> <p>ISO Definition Branch Identification Identifies a specific branch of a financial institution.</p> <p>XML Tag Type</p>	Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level. BrnchId BranchData3
3.26	0..1	Payment Return V09 +Transaction Information ++Clearing System Reference	<p>ISO Name</p> <p>ISO Definition Clearing System Reference Unique reference, as assigned by the clearing system, to unambiguously identify the return instruction.</p> <p>XML Tag Type</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>	ClrSysRef Max35Text
3.27	0..1	Payment Return V09 +Transaction Information ++Instructing Agent	<p>SEPA Usage Rule(s) <i>Only 'BICFI' is allowed.</i></p> <p>ISO Name</p> <p>ISO Definition Instructing Agent Agent that instructs the next party in the chain to carry out the (set of) instruction(s).</p> <p>XML Tag Type</p>	Usage: The instructing agent is the party sending the return message and not the party that sent the original instruction that is being returned. InstgAgt BranchAndFinancialInstitutionIdentification6

#	SEPA Mult	Message Element	Inter-PSP Positive Response to Recall of Credit Transfer SEPA Core Requirements	
3.28	0..1	Payment Return V09 +Transaction Information ++Instructed Agent	SEPA Usage Rule(s) Only 'BICFI' is allowed. ISO Name Instructed Agent ISO Definition Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s). XML Tag Type InstdAgt BranchAndFinancialInstitutionIdentification6	Usage: The instructed agent is the party receiving the return message and not the party that received the original instruction that is being returned.
3.29	0..1	Payment Return V09 +Transaction Information ++Return Chain	ISO Name ISO Definition Provides all parties (agents and non-agents) involved in a return transaction. XML Tag Type RtrChain TransactionParties7	Return Chain
3.30	1..1	Payment Return V09 +Transaction Information ++Return Reason Information	SEPA Usage Rule(s) Mandatory. Only one occurrence of 'Return Reason Information' is allowed. ISO Name Return Reason Information ISO Definition Provides detailed information on the return reason. XML Tag Type RtrRsnInf PaymentReturnReason6	Return Reason Information
3.31	1..1	Payment Return V09 +Transaction Information ++Return Reason Information +++Originator	SEPA Rulebook AT-R002 Identification of the type of party initiating the "R" message. SEPA Usage Rule(s) Mandatory. Limited to 'AnyBIC' for an Agent or 'Name' for a non-financial institution. 'Name' is limited to 70 characters in length. ISO Name Originator ISO Definition Party that issues the return. XML Tag Type Orgtr PartyIdentification135	AT-R002 Identification of the type of party initiating the "R" message.
3.32	1..1	Payment Return V09 +Transaction Information ++Return Reason Information +++Reason	SEPA Usage Rule(s) Mandatory. ISO Name Reason ISO Definition Specifies the reason for the return. XML Tag Type Rsn ReturnReason5Choice	Reason
	1..1		XML Tag xs:choice	
3.33	1..1	Payment Return V09 +Transaction Information ++Return Reason Information +++Reason ++++Code	SEPA Usage Rule(s) Only "FOCR" is allowed. ISO Name Code ISO Definition Reason for the return, as published in an external reason code list. XML Tag Type Cd ISO Length 1 .. 4 SEPA Length 1 .. 4 SEPA Code Restrictions FOCR FollowingCancellationRequest Return following a cancellation request	Code
3.34	1..1	Payment Return V09 +Transaction Information ++Return Reason Information +++Reason ++++Proprietary	ISO Name Proprietary ISO Definition Reason for the return, in a proprietary form. XML Tag Type Prtry ISO Length Max35Text SEPA Length 1 .. 35	Proprietary

#	SEPA Mult	Message Element	Inter-PSP Positive Response to Recall of Credit Transfer SEPA Core Requirements	
3.35	1..1	Payment Return V09 +Transaction Information ++Return Reason Information +++Additional Information	<p>SEPA Rulebook <i>AT-R053 Specific Reference of the Originator PSP initiating the recall.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i> <i>Only one occurrence starting with “ATR053/” followed by the information as per attribute description is allowed.</i></p> <p>ISO Name ISO Definition XML Tag Type ISO Length SEPA Length</p>	<i>Additional Information</i> <i>Further details on the return reason.</i> <i>AddtlInf</i> <i>Max105Text</i> <i>1 .. 105</i> <i>1 .. 105</i>
3.36	1..1	Payment Return V09 +Transaction Information ++Original Transaction Reference	<p>SEPA Rulebook <i>An exact copy of all attributes of the received DS-02 which is being returned.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i> <i>The message elements under ‘Original Transaction Reference’ must be populated with the same value as the message elements of the original instruction.</i></p> <p>ISO Name ISO Definition XML Tag Type</p>	<i>Original Transaction Reference</i> <i>Key elements used to identify the original transaction that is being referred to.</i> <i>OrgnlTxRef</i> <i>OriginalTransactionReference28</i>
3.37	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Interbank Settlement Amount	<p>ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits SEPA Inclusive</p>	<i>Interbank Settlement Amount</i> <i>Amount of money moved between the instructing agent and the instructed agent.</i> <i>IntrBkStlmtAmt</i> <i>ActiveOrHistoricCurrencyAndAmount</i> <i>5</i> <i>18</i> <i>0 ..</i>
3.38	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Amount	<p>ISO Name ISO Definition XML Tag Type</p>	<i>Amount</i> <i>Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.</i> <i>Amt</i> <i>AmountType4Choice</i>
3.39	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Interbank Settlement Date	<p>SEPA Rulebook <i>AT-T051 Settlement Date of the credit transfer.</i></p> <p>ISO Name ISO Definition XML Tag Type</p>	<i>Interbank Settlement Date</i> <i>Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.</i> <i>IntrBkStlmtDt</i> <i>ISODate</i>
3.40	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Requested Collection Date	<p>ISO Name ISO Definition XML Tag Type</p>	<i>Requested Collection Date</i> <i>Date and time at which the creditor requests that the amount of money is to be collected from the debtor.</i> <i>ReqdColltnDt</i> <i>ISODate</i>
3.41	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Requested Execution Date	<p>ISO Name ISO Definition XML Tag Type</p>	<i>Requested Execution Date</i> <i>Date at which the initiating party requests the clearing agent to process the payment.</i> <i>Usage:</i> This is the date on which the debtor's account is to be debited. If payment by cheque, the date when the cheque must be generated by the bank. <i>ReqdExctnDt</i> <i>DateAndDateTime2Choice</i>

#	SEPA Mult	Message Element	Inter-PSP Positive Response to Recall of Credit Transfer SEPA Core Requirements	
3.42	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Creditor Scheme Identification	ISO Name ISO Definition XML Tag Type	Creditor Scheme Identification Credit party that signs the mandate. CdtrSchmeId PartyIdentification135
3.43	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Settlement Information	ISO Name ISO Definition XML Tag Type	Settlement Information Specifies the details on how the settlement of the original transaction(s) between the instructing agent and the instructed agent was completed. SttlmInf SettlementInstruction7
3.44	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Payment Type Information	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-T001 Identification code of the Scheme.</i> <i>AT-T008 Category purpose of the Credit Transfer.</i> <i>If the original transaction was sent according to Annex V (Use of Extended Remittance Information) of the SCT Rulebook (refer to section 'Inter-PSP payment with use of the Extended Remittance Information option' below), then 'Local Instrument/Code' must be populated with "PERI" (Payment with Extended Remittance Information).</i> Payment Type Information Set of elements used to further specify the type of transaction. PmtTpInf PaymentTypeInformation27
3.45	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Payment Method	ISO Name ISO Definition XML Tag Type	Payment Method Specifies the means of payment that will be used to move the amount of money. PmtMtd PaymentMethod4Code
3.46	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Mandate Related Information	ISO Name ISO Definition XML Tag Type	Mandate Related Information Provides further details of the mandate signed between the creditor and the debtor. MndtRltdInf MandateRelatedInformation14
3.47	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Remittance Information	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-T009 Remittance information or AT-T010 The unstructured Remittance Information sent by the Originator to the Beneficiary in the Credit Transfer Instruction (in case of use of the Extended Remittance Information (ERI) option in the original SEPA Credit Transfer, AT-T011 The structured Remittance Information sent by the Originator to the Beneficiary in the SEPA Credit Transfer Instruction, will NOT be transported here).</i> Remittance Information Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system. RmtInf RemittanceInformation16
3.48	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Ultimate Debtor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-P006 The name of the Originator Reference Party.</i> <i>AT-P007 The identification code of the Originator Reference Party.</i> <i>Only 'Party' is allowed.</i> Ultimate Debtor Ultimate party that owes an amount of money to the (ultimate) creditor. UltmtDbtr Party40Choice

#	SEPA Mult	Message Element	Inter-PSP Positive Response to Recall of Credit Transfer SEPA Core Requirements	
3.49	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Debtor	SEPA Rulebook SEPA Usage Rule(s) Only 'Party' is allowed. ISO Name Debtor ISO Definition Party that owes an amount of money to the (ultimate) creditor. XML Tag Dbtr Type Party40Choice	<i>AT-P001 Name of the Originator.</i> <i>AT-P005 Address of the Originator.</i> <i>AT-P004 Originator identification code.</i> <i>AT-D001 IBAN of the account of the Originator.</i> <i>AT-P003 The Proxy/Alias of the account of the Originator.</i> ISO Name Debtor Account ISO Definition Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction. XML Tag DbtrAcct Type CashAccount38
3.50	1..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Debtor Account	SEPA Rulebook ISO Name ISO Definition	<i>AT-D001 IBAN of the account of the Originator.</i> <i>AT-P003 The Proxy/Alias of the account of the Originator.</i> ISO Name Debtor Account ISO Definition Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction. XML Tag DbtrAcct Type CashAccount38
3.51	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Debtor Agent	SEPA Rulebook ISO Name ISO Definition	<i>AT-D002 The BIC code of the Originator PSP.</i> ISO Name Debtor Agent ISO Definition Financial institution servicing an account for the debtor. XML Tag DbtrAgt Type BranchAndFinancialInstitutionIdentification6
3.52	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Debtor Agent Account	ISO Name ISO Definition	XML Tag DbtrAgtAcct Type CashAccount38
3.53	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Creditor Agent	SEPA Rulebook ISO Name ISO Definition	<i>AT-C002 The BIC code of the Beneficiary PSP.</i> ISO Name Creditor Agent ISO Definition Financial institution servicing an account for the creditor. XML Tag CdtrAgt Type BranchAndFinancialInstitutionIdentification6
3.54	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Creditor Agent Account	ISO Name ISO Definition	XML Tag CdtrAgtAcct Type CashAccount38
3.55	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Creditor	SEPA Rulebook SEPA Usage Rule(s) Only 'Party' is allowed. ISO Name ISO Definition	<i>AT-E001 Name of the Beneficiary.</i> <i>AT-E004 Address of the Beneficiary.</i> <i>AT-E005 Beneficiary identification code.</i> ISO Name Creditor ISO Definition Party to which an amount of money is due. XML Tag Cdtr Type Party40Choice
3.56	1..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Creditor Account	SEPA Rulebook ISO Name ISO Definition	<i>AT-C001 The IBAN of the account of the Beneficiary.</i> <i>AT-E003 The Proxy/Alias of the account of the Beneficiary.</i> ISO Name Creditor Account ISO Definition Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction. XML Tag CdtrAcct Type CashAccount38

#	SEPA Mult	Message Element	Inter-PSP Positive Response to Recall of Credit Transfer SEPA Core Requirements	
3.57	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Ultimate Creditor	<p>SEPA Rulebook</p> <p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p><i>AT-E007 The name of the Beneficiary Reference Party.</i></p> <p><i>AT-E010 The identification code of the Beneficiary Reference Party.</i></p> <p>SEPA Usage Rule(s) Only 'Party' is allowed.</p> <p>Ultimate Creditor</p> <p>Ultimate party to which an amount of money is due.</p> <p>UltmtCdtr</p> <p>Party40Choice</p>
3.58	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Purpose	<p>SEPA Rulebook</p> <p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p><i>AT-T007 The purpose of the SEPA Credit Transfer</i></p> <p>Purpose</p> <p>Underlying reason for the payment transaction.</p> <p>Usage:</p> <p>Purpose is used by the end customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain.</p> <p>Purp</p> <p>Purpose2Choice</p>
3.59	0..n	Payment Return V09 +Transaction Information ++Supplementary Data	<p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p>Supplementary Data</p> <p>Additional information that cannot be captured in the structured elements and/or any other specific block.</p> <p>SplmtryData</p> <p>SupplementaryData1</p>
4.0	0..n	Payment Return V09 +Supplementary Data	<p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p>Supplementary Data</p> <p>Additional information that cannot be captured in the structured elements and/or any other specific block.</p> <p>SplmtryData</p> <p>SupplementaryData1</p>



2.7 Request for Status Update on a Recall of SEPA Credit Transfer

2.7.1 Use of the FI to FI Payment Status Request (pacs.028.001.03)

This message is sent to the Beneficiary PSP in case the Originator PSP did not receive a response to a Recall, where the following applies:

- Index 3.3 'Original Instruction Identification' must be populated with the 'Cancellation Identification' (AT-R053) of the related camt.056 transaction information.

The message caters for a single or group status request.

Note: The use case of the message is implied by the 'Message Name', 'pacs.028.001.03', the 'Original Message Name Identification' must begin with camt.056 (the addition of a variant number and version number is optional) and the population of index 3.3 'Original Instruction Identification'.

Note: Message elements under 'Original Transaction Reference' are based on DS-02 attributes.

#	SEPA Mult	Message Element	Request for Status Update on a Recall of Credit Transfer SEPA Core Requirements	
		Document	XML Tag Type	Document Document
	1..1	FITo FIPayment Status Request V03	ISO Name ISO Definition	FITo FIPayment Status Request V03 The FinancialInstitutionToFinancialInstitutionPaymentStatusRequest message is sent by the debtor agent to the creditor agent, directly or through other agents and/or a payment clearing and settlement system. It is used to request a FIToFIPaymentStatusReport message containing information on the status of a previously sent instruction.
			XML Tag Type	FIToFIPmtStsReq FIToFIPaymentStatusRequestV03
1.0	1..1	FITo FIPayment Status Request V03 +Group Header	ISO Name ISO Definition	Group Header Set of characteristics shared by all individual transactions included in the status request message.
			XML Tag Type	GrpHdr GroupHeader91
1.1	1..1	FITo FIPayment Status Request V03 +Group Header ++Message Identification	ISO Name ISO Definition	Message Identification Point to point reference, as assigned by the instructing party, and sent to the next party in the chain to unambiguously identify the message. Usage: The instructing party has to make sure that MessageIdentification is unique per instructed party for a pre-agreed period.
			XML Tag Type ISO Length SEPA Length	MsgId Max35Text 1 .. 35 1 .. 35
1.2	1..1	FITo FIPayment Status Request V03 +Group Header ++Creation Date Time	ISO Name ISO Definition	Creation Date Time Date and time at which the message was created.
			XML Tag Type	CreDtTm ISODateTime
1.3	0..1	FITo FIPayment Status Request V03 +Group Header ++Instructing Agent	SEPA Usage Rule(s) ISO Name ISO Definition	Only 'BICFI' is allowed. Instructing Agent Agent that instructs the next party in the chain to carry out the (set of) instruction(s). Usage: The instructing agent is the party sending the status message and not the party that sent the original instruction that is being reported on.
			XML Tag Type	InstgAgt BranchAndFinancialInstitutionIdentification6
1.4	0..1	FITo FIPayment Status Request V03 +Group Header ++Instructed Agent	SEPA Usage Rule(s) ISO Name ISO Definition	Only 'BICFI' is allowed. Instructed Agent Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s). Usage: The instructed agent is the party receiving the status message and not the party that received the original instruction that is being reported on.
			XML Tag Type	InstdAgt BranchAndFinancialInstitutionIdentification6
2.0	1..1	FITo FIPayment Status Request V03 +Original Group Information	SEPA Usage Rule(s) ISO Name ISO Definition	Mandatory. Only one occurrence is allowed. Original Group Information Original group information concerning the group of transactions, to which the status request message refers to.
			XML Tag Type	OrgnlGrpInf OriginalGroupInformation27

#	SEPA Mult	Message Element	Request for Status Update on a Recall of Credit Transfer SEPA Core Requirements				
2.1	1..1	FITo FIPayment Status Request V03 +Original Group Information ++Original Message Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Message Identification Point to point reference, as assigned by the original instructing party, to unambiguously identify the original message. OrgnlMsgId Max35Text 1 .. 35 1 .. 35			
2.2	1..1	FITo FIPayment Status Request V03 +Original Group Information ++Original Message Name Identification	SEPA Usage Rule(s) <i>Must begin with 'camt.056'. The addition of a variant number and version number is optional.</i> ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Message Name Identification Specifies the original message name identifier to which the message refers. OrgnlMsgNmId Max35Text 1 .. 35 1 .. 35			
2.3	0..1	FITo FIPayment Status Request V03 +Original Group Information ++Original Creation Date Time	ISO Name ISO Definition XML Tag Type	Original Creation Date Time Date and time at which the original message was created. OrgnlCreDtTm ISODATETIME			
2.4	0..1	FITo FIPayment Status Request V03 +Original Group Information ++Original Number Of Transactions	ISO Name ISO Definition XML Tag Type Pattern	Original Number Of Transactions Number of individual transactions contained in the original message. OrgnlNbOfTxns Max15NumericText [0-9]{1,15}			
2.5	0..1	FITo FIPayment Status Request V03 +Original Group Information ++Original Control Sum	ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits	Original Control Sum Total of all individual amounts included in the original message, irrespective of currencies. OrgnlCtrlSum DecimalNumber 17 18			
3.0	1..n	FITo FIPayment Status Request V03 +Transaction Information	SEPA Usage Rule(s) <i>Mandatory.</i> ISO Name ISO Definition XML Tag Type	SEPA Usage Rule(s) <i>Mandatory.</i> Transaction Information Information concerning the original transaction, to which the status request message refers. TxInf PaymentTransaction113			
3.1	1..1	FITo FIPayment Status Request V03 +Transaction Information ++Status Request Identification	SEPA Usage Rule(s) <i>Mandatory.</i> <i>This ID must be forwarded to the Beneficiary PSP (and therefore it is not a point-to-point reference).</i> ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Status Request Identification Unique identification, as assigned by an instructing party for an instructed party, to unambiguously identify the status request. Usage: The instructing party is the party sending the request message and not the party that sent the original instruction that is being reported on. StsReqId Max35Text 1 .. 35 1 .. 35			
3.2	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Group Information	ISO Name ISO Definition XML Tag Type	Original Group Information Point to point reference, as assigned by the original instructing party, to unambiguously identify the original message. OrgnlGrpInf OriginalGroupInformation29			

#	SEPA Mult	Message Element	Request for Status Update on a Recall of Credit Transfer SEPA Core Requirements			
3.3	1..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Instruction Identification	<p>SEPA Usage Rule(s) <i>Mandatory.</i> <i>Must be populated with the cancellation ID (AT-R053) of the related camt.056 'Transaction Information'.</i></p> <p>ISO Name ISO Definition Original Instruction Identification Unique identification, as assigned by the original instructing party for the original instructed party, to unambiguously identify the original instruction.</p> <p>XML Tag Type ISO Length SEPA Length OrgnlInstrId Max35Text 1 .. 35 1 .. 35</p>			
3.4	1..1	FITo FIPayment Status Request V03 +Transaction Information ++Original End To End Identification	<p>SEPA Rulebook <i>AT-T014 The Originator's reference of the SEPA Credit Transfer Transaction.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name ISO Definition Original End To End Identification Unique identification, as assigned by the original initiating party, to unambiguously identify the original transaction.</p> <p>XML Tag Type ISO Length SEPA Length OrgnlEndToEndId Max35Text 1 .. 35 1 .. 35</p>			
3.5	1..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Identification	<p>SEPA Rulebook <i>AT-T054 The Originator PSP's reference of the SEPA Credit Transfer Transaction.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name ISO Definition Original Transaction Identification Unique identification, as assigned by the original first instructing agent, to unambiguously identify the transaction.</p> <p>XML Tag Type ISO Length SEPA Length OrgnlTxId Max35Text 1 .. 35 1 .. 35</p>			
3.6	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original UETR	<p>ISO Name ISO Definition Original UETR Universally unique identifier to provide the original end-to-end reference of a payment transaction.</p> <p>XML Tag Type Pattern OrgnlUETR UUIDv4Identifier [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}</p>			
3.7	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Acceptance Date Time	<p>ISO Name ISO Definition Acceptance Date Time Point in time when the payment order from the initiating party meets the processing conditions of the account servicing agent. This means that the account servicing agent has received the payment order and has applied checks such as authorisation, availability of funds.</p> <p>XML Tag Type AcptncDtTm ISODateTime</p>			
3.8	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Clearing System Reference	<p>ISO Name ISO Definition Clearing System Reference Unique reference, as assigned by a clearing system, to unambiguously identify the instruction.</p> <p>XML Tag Type ISO Length SEPA Length ClrSysRef Max35Text 1 .. 35 1 .. 35</p>			

#	SEPA Mult	Message Element	Request for Status Update on a Recall of Credit Transfer SEPA Core Requirements			
3.9	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Instructing Agent	ISO Name ISO Definition XML Tag Type	Instructing Agent Agent that instructs the next party in the chain to carry out the (set of) instruction(s). InstgAgt BranchAndFinancialInstitutionIdentification6		
3.10	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Instructed Agent	ISO Name ISO Definition XML Tag Type	Instructed Agent Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s). InstdAgt BranchAndFinancialInstitutionIdentification6		
3.11	1..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference	SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type	The message elements under 'Original Transaction Reference' must be populated with the same value as the message elements of the original instruction. Original Transaction Reference Key elements used to identify the original transaction that is being referred to. OrgnlTxRef OriginalTransactionReference28		
3.12	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Interbank Settlement Amount	SEPA Rulebook ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits SEPA Inclusive	AT-T002 Amount of the SEPA Credit Transfer in Euro. Interbank Settlement Amount Amount of money moved between the instructing agent and the instructed agent. IntrBkSttlmAmt ActiveOrHistoricCurrencyAndAmount 2 18 0.01 .. 999999999.9		
3.13	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Amount	ISO Name ISO Definition XML Tag Type	Amount Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party. Amt AmountType4Choice		
3.14	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Interbank Settlement Date	SEPA Rulebook ISO Name ISO Definition XML Tag Type	AT-T051 The Settlement Date of the credit transfer. Interbank Settlement Date Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. IntrBkSttlmDt ISODate		
3.15	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Requested Collection Date	ISO Name ISO Definition XML Tag Type	Requested Collection Date Date and time at which the creditor requests that the amount of money is to be collected from the debtor. ReqdColltnDt ISODate		
3.16	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Requested Execution Date	ISO Name ISO Definition XML Tag Type	Requested Execution Date Date at which the initiating party requests the clearing agent to process the payment. Usage: This is the date on which the debtor's account is to be debited. If payment by cheque, the date when the cheque must be generated by the bank. ReqdExctnDt DateAndDateTime2Choice		

#	SEPA Mult	Message Element	Request for Status Update on a Recall of Credit Transfer SEPA Core Requirements	
3.17	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Creditor Scheme Identification	ISO Name ISO Definition XML Tag Type	Creditor Scheme Identification Credit party that signs the mandate. CdtrSchmeId PartyIdentification135
3.18	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Settlement Information	ISO Name ISO Definition XML Tag Type	Settlement Information Specifies the details on how the settlement of the original transaction(s) between the instructing agent and the instructed agent was completed. SttlmInf SettlementInstruction7
3.19	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Payment Type Information	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-T008 The category purpose of the credit transfer.</i> <i>AT-T001 The identification code of the Scheme. If the original transaction was sent according to Annex V (Use of Extended Remittance Information) of the SCT Rulebook (refer to section 'Inter-PSP payment with use of the Extended Remittance Information option' below), then 'Local Instrument/Code' must be populated with "PERI" (Payment with Extended Remittance Information).</i> Payment Type Information Set of elements used to further specify the type of transaction. PmtTpInf PaymentTypeInformation27
3.20	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Payment Method	ISO Name ISO Definition XML Tag Type	Payment Method Specifies the means of payment that will be used to move the amount of money. PmtMtd PaymentMethod4Code
3.21	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Mandate Related Information	ISO Name ISO Definition XML Tag Type	Mandate Related Information Provides further details of the mandate signed between the creditor and the debtor. MndtRltdInf MandateRelatedInformation14
3.22	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Remittance Information	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-T009 Remittance information or AT-T010 The unstructured Remittance Information sent by the Originator to the Beneficiary in the Credit Transfer Instruction (in case of use of the Extended Remittance Information (ERI) option in the original SEPA Credit Transfer, AT-T011 The structured Remittance Information sent by the Originator to the Beneficiary in the SEPA Credit Transfer Instruction, will NOT be transported here).</i> Remittance Information Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system. RmtInf RemittanceInformation16
3.23	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Ultimate Debtor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-P006 The name of the Originator Reference Party.</i> <i>AT-P007 The identification code of the Originator Reference Party.</i> <i>Only 'Party' is allowed.</i> Ultimate Debtor Ultimate party that owes an amount of money to the (ultimate) creditor. UltmtDbtr Party40Choice

#	SEPA Mult	Message Element	Request for Status Update on a Recall of Credit Transfer SEPA Core Requirements	
3.24	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Debtor	<p>SEPA Rulebook <i>AT-P001 The name of the Originator.</i> <i>AT-P005 The address of the Originator.</i> <i>AT-P004 The Originator identification code.</i></p> <p>SEPA Usage Rule(s) Only 'Party' is allowed.</p> <p>ISO Name Debtor</p> <p>ISO Definition Party that owes an amount of money to the (ultimate) creditor.</p> <p>XML Tag Type Dbtr Party40Choice</p>	
3.25	1..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Debtor Account	<p>SEPA Rulebook <i>AT-D001 The IBAN of the account of the Originator.</i> <i>AT-P003 The Proxy/Alias of the account of the Originator.</i></p> <p>ISO Name Debtor Account</p> <p>ISO Definition Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction.</p> <p>XML Tag Type DbtrAcct CashAccount38</p>	
3.26	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Debtor Agent	<p>SEPA Rulebook <i>AT-D002 The BIC code of the Originator PSP.</i></p> <p>ISO Name Debtor Agent</p> <p>ISO Definition Financial institution servicing an account for the debtor.</p> <p>XML Tag Type DbtrAgt BranchAndFinancialInstitutionIdentification6</p>	
3.27	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Debtor Agent Account	<p>ISO Name Debtor Agent Account</p> <p>ISO Definition Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain.</p> <p>XML Tag Type DbtrAgtAcct CashAccount38</p>	
3.28	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Creditor Agent	<p>SEPA Rulebook <i>AT-C002 The BIC code of the Beneficiary PSP</i></p> <p>ISO Name Creditor Agent</p> <p>ISO Definition Financial institution servicing an account for the creditor.</p> <p>XML Tag Type CdtrAgt BranchAndFinancialInstitutionIdentification6</p>	
3.29	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Creditor Agent Account	<p>ISO Name Creditor Agent Account</p> <p>ISO Definition Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction.</p> <p>XML Tag Type CdtrAgtAcct CashAccount38</p>	
3.30	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Creditor	<p>SEPA Rulebook <i>AT-E001 The name of the Beneficiary.</i> <i>AT-E004 The address of the Beneficiary.</i> <i>AT-E005 The Beneficiary identification code.</i></p> <p>SEPA Usage Rule(s) Only 'Party' is allowed.</p> <p>ISO Name Creditor</p> <p>ISO Definition Party to which an amount of money is due.</p> <p>XML Tag Type Cdtr Party40Choice</p>	
3.31	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Creditor Account	<p>SEPA Rulebook <i>AT-C001 The IBAN of the account of the Beneficiary.</i> <i>AT-E003 The Proxy/Alias of the account of the Beneficiary.</i></p> <p>ISO Name Creditor Account</p> <p>ISO Definition Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction.</p> <p>XML Tag Type CdtrAcct CashAccount38</p>	

#	SEPA Mult	Message Element	Request for Status Update on a Recall of Credit Transfer SEPA Core Requirements	
3.32	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Ultimate Creditor	<p>SEPA Rulebook</p> <p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p><i>AT-E007 The name of the Beneficiary Reference Party.</i></p> <p><i>AT-E010 The identification code of the Beneficiary Reference Party.</i></p> <p>SEPA Usage Rule(s) Only 'Party' is allowed.</p> <p>Ultimate Creditor</p> <p>Ultimate party to which an amount of money is due.</p> <p>UltmtCdtr</p> <p>Party40Choice</p>
3.33	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Purpose	<p>SEPA Rulebook</p> <p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p><i>AT-T007 The purpose of the SEPA Credit Transfer</i></p> <p>Purpose</p> <p>Underlying reason for the payment transaction.</p> <p>Usage:</p> <p>Purpose is used by the end customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain.</p> <p>Purp</p> <p>Purpose2Choice</p>
3.34	0..n	FITo FIPayment Status Request V03 +Transaction Information ++Supplementary Data	<p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p>Supplementary Data</p> <p>Additional information that cannot be captured in the structured elements and/or any other specific block.</p> <p>SplmtryData</p> <p>SupplementaryData1</p>
4.0	0..n	FITo FIPayment Status Request V03 +Supplementary Data	<p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p>Supplementary Data</p> <p>Additional information that cannot be captured in the structured elements and/or any other specific block.</p> <p>SplmtryData</p> <p>SupplementaryData1</p>



2.8 Request for Recall by the Originator Dataset (DS-07)

2.8.1 Use of FI-to-FI Payment Cancellation Request (camt.056.001.08)

The message is used to submit the request made by the Originator to cancel a pacs.008 for other reasons than those allowed in a Recall (refer to section 'Inter-PSP Recall of Credit Transfer Dataset' above). As a consequence, the following apply:

- Index 4.3 'Cancellation Identification' can only be populated with AT-R072 'The specific reference of the Originator PSP for the Request for Recall by the Originator'.
- Index 4.19 'Originator' can only be populated with AT-P001 'The name of the Originator'.
- Index 4.20 'Reason' is to be populated with AT-R071 'Reason code for the Request for Recall by the Originator'.
- Index 4.21 'Code' can only be populated with ISO codes "AC03" (Wrong IBAN), "AM09" (Wrong Amount) and "CUST" (Requested By Customer).
- Index 4.23 'Additional Information' is to be populated with AT-R073 'Additional Information to AT-R071 Reason code for the Request for Recall by the Originator' which can be used in accordance with above reason codes.

The message can also be used for a Request for Recall by the Originator of a Credit Transfer with Extended Remittance Information (ERI, please refer to section 'Inter-PSP payment with use of the Extended Remittance Information option' below) whereby only AT-T010 'The unstructured Remittance Information sent by the Originator to the Beneficiary in the Credit Transfer Instruction' will be forwarded.

The message caters for single or group cancellation requests.

Note: The use case of the message is implied by the 'Message Name', 'camt.056.001.08', the 'Original Message Name Identification' must begin with pacs.008 (the addition of a variant number and version number is optional), 'Originator' set to AT-P001 'The name of the Originator' and 'Reason' set to "AC03", "AM09" or 'CUST' (under 'Code').

Note: Message elements under 'Original Transaction Reference' sequence are based on DS-02 attributes.

Note: Only one Request for Recall by the Originator can be sent for a given SCT Transaction. The Originator PSP is not allowed to send another Request for Recall by the Originator for the same initial SCT Transaction

#	SEPA Mult	Message Element	Request for Recall by the Originator SEPA Core Requirements	
		Document	XML Tag Type	Document Document
	1..1	FITo FIPayment Cancellation Request V08	ISO Name ISO Definition	FITo FIPayment Cancellation Request V08 Scope The FIToFIPaymentCancellationRequest message is sent by a case creator/case assignee to a case assignee. This message is used to request the cancellation of an original payment instruction. The FIToFIPaymentCancellationRequest message is exchanged between the instructing agent and the instructed agent to request the cancellation of a interbank payment message previously sent (such as FIToFICustomerCreditTransfer, FIToFICustomerDirectDebit or FinancialInstitutionCreditTransfer).
			XML Tag Type	The FIToFIPaymentCancellationRequest message supports both the request for cancellation (the instructed agent - or assignee - has not yet processed and forwarded the payment instruction) as well as the request for refund (payment has been fully processed already by the instructed agent - or assignee). FIToFIPmtCxlReq FIToFIPaymentCancellationRequestV08
1.0	1..1	FITo FIPayment Cancellation Request V08 +Assignment	ISO Name ISO Definition	Assignment Identifies the assignment of an investigation case from an assigner to an assignee. Usage: The assigner must be the sender of this confirmation and the assignee must be the receiver.
			XML Tag Type	Assgnmt CaseAssignment5
1.1	1..1	FITo FIPayment Cancellation Request V08 +Assignment ++Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Identification Uniquely identifies the case assignment. Id Max35Text 1 .. 35 1 .. 35
1.2	1..1	FITo FIPayment Cancellation Request V08 +Assignment ++Assigner	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Instructing Party. Limited to 'BICFI' to identify a PSP, 'AnyBIC' to identify a CSM or 'LEI' or 'Name' to indicate a CSM when it has no BIC. 'Name' is limited to 70 characters in length. Assigner Party who assigns the case. Usage: This is also the sender of the message. Assgnr Party40Choice
1.3	1..1	FITo FIPayment Cancellation Request V08 +Assignment ++Assignee	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Instructed Party. Limited to 'BICFI' to identify a PSP, 'AnyBIC' to identify a CSM or 'LEI' or 'Name' to indicate a CSM when it has no BIC. 'Name' is limited to 70 characters in length. Assignee Party to which the case is assigned. Usage: This is also the receiver of the message. Assgne Party40Choice

#	SEPA Mult	Message Element	Request for Recall by the Originator SEPA Core Requirements		
1.4	1..1	FITo FIPayment Cancellation Request V08 +Assignment ++Creation Date Time	ISO Name ISO Definition XML Tag Type	Creation Date Time Date and time at which the assignment was created. CreDtTm ISODateTime	
2.0	0..1	FITo FIPayment Cancellation Request V08 +Case	ISO Name ISO Definition XML Tag Type	Case Identifies the investigation case. Case Case5	
3.0	0..1	FITo FIPayment Cancellation Request V08 +Control Data	ISO Name ISO Definition XML Tag Type	Control Data Provides details on the number of transactions and the control sum of the message. CtrlData ControlData1	
3.1	1..1	FITo FIPayment Cancellation Request V08 +Control Data ++Number Of Transactions	ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits	Number Of Transactions Number of individual transactions contained in the message. NbOfTxns Max15NumericText [0-9]{1,15}	
3.2	0..1	FITo FIPayment Cancellation Request V08 +Control Data ++Control Sum	ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits	Control Sum Total of all individual amounts included in the message, irrespective of currencies. CtrlSum DecimalNumber 17 18	
4.0	1..n	FITo FIPayment Cancellation Request V08 +Underlying	ISO Name ISO Definition XML Tag Type	Underlying Identifies the payment instruction to be cancelled. Undrlg UnderlyingTransaction23	
4.1	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Original Group Information And Cancellation	ISO Name ISO Definition XML Tag Type	Original Group Information And Cancellation Provides information on the original message, to which the cancellation refers. OrgnlGrpInfAndCxl OriginalGroupHeader15	
4.2	1..n	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information	SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type	Transaction Information Provides information on the original transactions to which the cancellation request message refers. TxInf PaymentTransaction106	
4.3	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Cancellation Identification	SEPA Rulebook SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>AT-R072 The specific reference of the Originator PSP for the Request for Recall by the Originator.</i> <i>This element must be transported up to the Creditor Agent.</i> Cancellation Identification Unique and unambiguous identifier of a cancellation request, as assigned by the assigner. Usage: The cancellation request identification can be used for reconciliation or to link tasks relating to the cancellation request. CxId Max35Text 1 .. 35 1 .. 35	

#	SEPA Mult	Message Element	Request for Recall by the Originator SEPA Core Requirements		
4.4	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Case	ISO Name ISO Definition XML Tag Type	Case Set of elements to uniquely and unambiguously identify an exception or an investigation workflow. Case Case5	
4.5	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Group Information	SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type	Mandatory. Original Group Information Provides information on the original message. OrgnlGrpInf OriginalGroupInformation29	
4.6	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Group Information ++++Original Message Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Message Identification Point to point reference assigned by the original instructing party to unambiguously identify the original message. OrgnlMsgId Max35Text 1 .. 35 1 .. 35	
4.7	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Group Information ++++Original Message Name Identification	SEPA Usage Rule(s) Must begin with 'pacs.008'. The addition of a variant number and version number is optional. ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Message Name Identification Specifies the original message name identifier to which the message refers, for example, pacs. 003.001.01 or MT103. OrgnlMsgNmld Max35Text 1 .. 35 1 .. 35	
4.8	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Group Information ++++Original Creation Date Time	ISO Name ISO Definition XML Tag Type	Original Creation Date Time Original date and time at which the message was created. OrgnlCreDtTm ISODATETIME	
4.9	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Instruction Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Instruction Identification Unique identification, as assigned by the original instructing party for the original instructed party, to unambiguously identify the original instruction. OrgnlInstrId Max35Text 1 .. 35 1 .. 35	
4.10	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original End To End Identification	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	AT-T014 The Originator's reference of the SEPA Credit Transfer Transaction. Mandatory. Original End To End Identification Unique identification, as assigned by the original initiating party, to unambiguously identify the original transaction. OrgnlEndToEndId Max35Text 1 .. 35 1 .. 35	

#	SEPA Mult	Message Element	Request for Recall by the Originator SEPA Core Requirements	
4.11	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Identification	SEPA Rulebook SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>AT-T054 The Originator PSP's reference of the SEPA Credit Transfer Transaction.</i> <i>Original Transaction Identification</i> <i>Unique identification, as assigned by the original first instructing agent, to unambiguously identify the transaction.</i> <i>OrgnlTxId</i> <i>Max35Text</i> <i>1 .. 35</i> <i>1 .. 35</i>
4.12	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original UETR	ISO Name ISO Definition XML Tag Type Pattern	<i>Original UETR</i> <i>Universally unique identifier to provide the original end-to-end reference of a payment transaction.</i> <i>OrgnlUETR</i> <i>UUIDv4Identifier</i> <i>[a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}</i>
4.13	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Clearing System Reference	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>Original Clearing System Reference</i> <i>Unique reference, as assigned by the original clearing system, to unambiguously identify the original instruction.</i> <i>OrgnlClrSysRef</i> <i>Max35Text</i> <i>1 .. 35</i> <i>1 .. 35</i>
4.14	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Interbank Settlement Amount	SEPA Rulebook SEPA Usage Rule(s) Mandatory. SEPA Format Rule(s) ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits SEPA Inclusive	<i>AT-T002 Amount of the SEPA Credit Transfer in Euro.</i> <i>Only 'EUR' is allowed.</i> <i>Amount must be 0.01 or more and 999999999.99 or less.</i> <i>The fractional part has a maximum of two digits.</i> <i>Original Interbank Settlement Amount</i> <i>Amount of money moved between the instructing agent and the instructed agent, as provided in the original instruction.</i> <i>OrgnlIntrBkSttlmAmt</i> <i>ActiveOrHistoricCurrencyAndAmount</i> <i>2</i> <i>18</i> <i>0.01 .. 999999999.99</i>
4.15	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Interbank Settlement Date	SEPA Rulebook SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type	<i>AT-T051 Settlement Date of the Credit Transfer.</i> <i>Original Interbank Settlement Date</i> <i>Date, as provided in the original transaction, on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.</i> <i>OrgnlIntrBkSttlmDt</i> <i>ISODate</i>
4.16	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Assigner	ISO Name ISO Definition XML Tag Type	<i>Assigner</i> <i>Party who assigns the case.</i> <i>Usage: This is also the agent that instructs the next party in the chain to carry out the (set of) cancellation request(s).</i> <i>Assgnr</i> <i>BranchAndFinancialInstitutionIdentification6</i>

#	SEPA Mult	Message Element	Request for Recall by the Originator SEPA Core Requirements		
4.17	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Assignee	ISO Name ISO Definition XML Tag Type	Assignee Party to which the case is assigned. Usage: This is also the agent that is instructed by the previous party in the chain to carry out the (set of) cancellation request(s). Assgne BranchAndFinancialInstitutionIdentification6	
4.18	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Cancellation Reason Information	SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type	Only one occurrence is allowed. Cancellation Reason Information Provides detailed information on the cancellation reason. CxlRsnInf PaymentCancellationReason5	
4.19	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Cancellation Reason Information ++++Originator	SEPA Rulebook AT-P001 The name of the Originator. SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type	Only 'Name' is allowed. 'Name' is limited to 70 characters in length. Originator Party that issues the cancellation request. Orgtr PartyIdentification135	
4.20	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Cancellation Reason Information ++++Reason	SEPA Rulebook AT-R071 Reason code for the Request for Recall by the Originator. SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type	Reason Specifies the reason for the cancellation. Rsn CancellationReason33Choice	
	1..1		XML Tag	xs:choice	
4.21	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Cancellation Reason Information ++++Reason +++++Code	SEPA Usage Rule(s) Only "AC03", "AM09" or "CUST" are allowed. ISO Name ISO Definition XML Tag Type ISO Length SEPA Length SEPA Code Restrictions	Code Reason for the cancellation request, in a coded form. Cd ExternalCancellationReason1Code 1 .. 4 1 .. 4 AC03 InvalidCreditorAccountNumber Wrong account number in Credit Transfer. AM09 WrongAmount Amount is not the amount agreed or expected. CUST RequestedByCustomer Cancellation requested by the Debtor.	
4.22	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Cancellation Reason Information ++++Reason +++++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Proprietary Reason for the cancellation request, in a proprietary form. Prtry Max35Text 1 .. 35 1 .. 35	
4.23	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Cancellation Reason Information ++++Additional Information	SEPA Rulebook AT-R073 Additional information to AT-R071 Reason code for the Request for Recall by the Originator. SEPA Usage Rule(s) Only one occurrence is allowed. ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Additional Information Further details on the cancellation request reason. AddtlInf Max105Text 1 .. 105 1 .. 105	

#	SEPA Mult	Message Element	Request for Recall by the Originator SEPA Core Requirements	
4.24	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference	<p>SEPA Rulebook</p> <p>An exact copy of the original Inter-PSP Payment dataset (DS-02) to which the Request for Recall by the Originator relates to.</p> <p>SEPA Usage Rule(s)</p> <p>Mandatory.</p> <p>The message elements under 'Original Transaction Reference' must be populated with the same value as the message elements of the original instruction.</p> <p>ISO Name</p> <p>Original Transaction Reference</p> <p>ISO Definition</p> <p>Key elements used to identify the original transaction that is being referred to.</p> <p>XML Tag Type</p> <p>OrgnlTxRef</p> <p>OriginalTransactionReference28</p>	
4.25	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Interbank Settlement Amount	<p>ISO Name</p> <p>Interbank Settlement Amount</p> <p>ISO Definition</p> <p>Amount of money moved between the instructing agent and the instructed agent.</p> <p>XML Tag Type</p> <p>IntrBkStlmtAmt</p> <p>SEPA FractDigits</p> <p>ActiveOrHistoricCurrencyAndAmount</p> <p>5</p> <p>TotalDigits</p> <p>18</p> <p>SEPA Inclusive</p> <p>0 ..</p>	
4.26	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Amount	<p>ISO Name</p> <p>Amount</p> <p>ISO Definition</p> <p>Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.</p> <p>XML Tag Type</p> <p>Amt</p> <p>AmountType4Choice</p>	
4.27	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Interbank Settlement Date	<p>ISO Name</p> <p>Interbank Settlement Date</p> <p>ISO Definition</p> <p>Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.</p> <p>XML Tag Type</p> <p>IntrBkStlmtDt</p> <p>ISODate</p>	
4.28	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Requested Collection Date	<p>ISO Name</p> <p>Requested Collection Date</p> <p>ISO Definition</p> <p>Date and time at which the creditor requests that the amount of money is to be collected from the debtor.</p> <p>XML Tag Type</p> <p>ReqdColltnDt</p> <p>ISODate</p>	
4.29	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Requested Execution Date	<p>ISO Name</p> <p>Requested Execution Date</p> <p>ISO Definition</p> <p>Date at which the initiating party requests the clearing agent to process the payment.</p> <p>Usage: This is the date on which the debtor's account is to be debited. If payment by cheque, the date when the cheque must be generated by the bank.</p> <p>XML Tag Type</p> <p>ReqdExctnDt</p> <p>DateAndDateTime2Choice</p>	
4.30	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Creditor Scheme Identification	<p>ISO Name</p> <p>Creditor Scheme Identification</p> <p>ISO Definition</p> <p>Credit party that signs the mandate.</p> <p>XML Tag Type</p> <p>CdtrSchmeId</p> <p>PartyIdentification135</p>	
4.31	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Settlement Information	<p>ISO Name</p> <p>Settlement Information</p> <p>ISO Definition</p> <p>Specifies the details on how the settlement of the original transaction(s) between the instructing agent and the instructed agent was completed.</p> <p>XML Tag Type</p> <p>StlmtInf</p> <p>SettlementInstruction7</p>	

#	SEPA Mult	Message Element	Request for Recall by the Originator SEPA Core Requirements	
4.32	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Payment Type Information	<i>SEPA Rulebook</i> ISO Name ISO Definition XML Tag Type	<i>AT-T001 Identification code of the Scheme.</i> <i>AT-T008 Category Purpose of the Credit Transfer.</i> <i>If the original transaction was sent according to Annex V (Use of Extended Remittance Information) of the SCT Rulebook (refer to section 'Inter-PSP payment with use of the Extended Remittance Information option' below), then 'Local Instrument/Code' must be populated with "PERI" (Payment with Extended Remittance Information).</i> Payment Type Information Set of elements used to further specify the type of transaction. PmtTpInf PaymentTypeInformation27
4.33	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Payment Method	ISO Name ISO Definition XML Tag Type	Payment Method Specifies the means of payment that will be used to move the amount of money. PmtMtd PaymentMethod4Code
4.34	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Mandate Related Information	ISO Name ISO Definition XML Tag Type	Mandate Related Information Provides further details of the mandate signed between the creditor and the debtor. MndtRltdInf MandateRelatedInformation14
4.35	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Remittance Information	<i>SEPA Rulebook</i> ISO Name ISO Definition XML Tag Type	<i>AT-T009 Remittance information or AT-T010 The unstructured Remittance Information sent by the Originator to the Beneficiary in the Credit Transfer Instruction (in case of use of the Extended Remittance Information (ERI) option in the original SEPA Credit Transfer, AT-T011 The structured Remittance Information sent by the Originator to the Beneficiary in the SEPA Credit Transfer Instruction, will NOT be transported here).</i> Remittance Information Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system. RmtInf RemittanceInformation16
4.36	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Ultimate Debtor	<i>SEPA Rulebook</i> SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-P006 The name of the Originator Reference Party.</i> <i>AT-P007 The identification code of the Originator Reference Party.</i> <i>Only 'Party' is allowed.</i> Ultimate Debtor Ultimate party that owes an amount of money to the (ultimate) creditor. UltmtDbtr Party40Choice
4.37	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Debtor	<i>SEPA Rulebook</i> SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-P001 Name of the Originator - Mandatory.</i> <i>AT-P005 Address of the Originator.</i> <i>AT-P004 Originator's Identification Code.</i> <i>Only 'Party' is allowed.</i> Debtor Party that owes an amount of money to the (ultimate) creditor. Dbtr Party40Choice

#	SEPA Mult	Message Element	Request for Recall by the Originator SEPA Core Requirements		
4.38	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Debtor Account	<i>SEPA Rulebook</i> ISO Name ISO Definition XML Tag Type	<i>AT-D001 The IBAN of the account of the Originator.</i> <i>AT-P003 The Proxy/Alias of the account of the Originator.</i> Debtor Account Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction. DbtrAcct CashAccount38	
4.39	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Debtor Agent	<i>SEPA Rulebook</i> ISO Name ISO Definition XML Tag Type	<i>AT-D002 The BIC code of the Originator PSP.</i> Debtor Agent Financial institution servicing an account for the debtor. DbtrAgt BranchAndFinancialInstitutionIdentification6	
4.40	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Debtor Agent Account	ISO Name ISO Definition XML Tag Type	Debtor Agent Account Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain. DbtrAgtAcct CashAccount38	
4.41	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Creditor Agent	<i>SEPA Rulebook</i> ISO Name ISO Definition XML Tag Type	<i>AT-C002 The BIC code of the Beneficiary PSP.</i> Creditor Agent Financial institution servicing an account for the creditor. CdtrAgt BranchAndFinancialInstitutionIdentification6	
4.42	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Creditor Agent Account	ISO Name ISO Definition XML Tag Type	Creditor Agent Account Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction. CdtrAgtAcct CashAccount38	
4.43	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Creditor	<i>SEPA Rulebook</i> <i>SEPA Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	<i>AT-E001 Name of the Beneficiary</i> <i>AT-E004 Address of the Beneficiary.</i> <i>AT-E005 Beneficiary Identification Code.</i> Only 'Party' is allowed. Creditor Party to which an amount of money is due. Cdtr Party40Choice	
4.44	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Creditor Account	<i>SEPA Rulebook</i> ISO Name ISO Definition XML Tag Type	<i>AT-C001 The IBAN of the account of the Beneficiary.</i> <i>AT-E003 The Proxy/Alias of the account of the Beneficiary.</i> Creditor Account Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction. CdtrAcct CashAccount38	
4.45	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Ultimate Creditor	<i>SEPA Rulebook</i> <i>SEPA Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	<i>AT-E007 The name of the Beneficiary Reference Party.</i> <i>AT-E010 The identification code of the Beneficiary Reference Party.</i> Only 'Party' is allowed. Ultimate Creditor Ultimate party to which an amount of money is due. UltmtCdtr Party40Choice	

#	SEPA Mult	Message Element	Request for Recall by the Originator SEPA Core Requirements		
4.46	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Purpose	<i>SEPA Rulebook</i> ISO Name ISO Definition	<i>AT-T007 The purpose of the SEPA Credit Transfer.</i> Purpose Underlying reason for the payment transaction. Usage: Purpose is used by the end customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain. Purp Purpose2Choice	
4.47	0..n	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Supplementary Data	ISO Name ISO Definition XML Tag Type	Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block. SplmtryData SupplementaryData1	
5.0	0..n	FITo FIPayment Cancellation Request V08 +Supplementary Data	ISO Name ISO Definition XML Tag Type	Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block. SplmtryData SupplementaryData1	



2.9 Inter-PSP Negative Response to the Request for Recall by the Originator Dataset (DS-08)

2.9.1 Use of Resolution of Investigation (camt.029.001.09)

In the context of a Request for Recall by the Originator of an SCT, this message is used to transmit a negative response to a:

- Request for Recall by the Originator message (FI-to-FI Payment Cancellation Request V01, camt.056.001.08);
- Request for Status Update on a Request for Recall by the Originator message (FI-to-FI Payment Status Request, pacs.028.001.03, refer to section 'Request for Status Update on a Request for Recall by the Originator' below);

where the following apply:

- Index 3.0 'Status': only sub-element 'Confirmation' can be used, populated with "RJCR" (Rejected Cancellation Request).
- Index 4.21 'Additional Information':
 - A mandatory occurrence starting with "ATR072/" followed by the information as per attribute description 'The specific reference of the Originator PSP for the Request for Recall by the Originator'.
 - In addition, when reason code was "AC03" (Wrong IBAN) in the camt.056, up to ten occurrences are allowed all starting with "ATR078/" followed by the information as per attribute description 'Provision of all information available to file a legal claim to recover the funds in case of reason code 'wrong unique identifier of the Beneficiary account' (optional)'.
 - As a consequence, the 'SEPA Mult.' is set to [1..11].

The message caters for a single or a group negative response.

Note: The use case of the message is implied by the 'Message Name', 'camt.029.001.09', the 'Original Message Name Identification' must begin with pacs.008 (the addition of a variant number and version number is optional) and 'Status' set to "RJCR".

Note: Message elements under 'Original Transaction Reference' sequence are based on DS-02 attributes.

#	SEPA Mult	Message Element	Inter-PSP Negative Response to RFRO SEPA Core Requirements	
		Document	XML Tag Type	Document Document
	1..1	Resolution Of Investigation V09	ISO Name ISO Definition	Resolution Of Investigation V09 Scope The ResolutionOfInvestigation message is sent by a case assignee to a case creator/case assigner. This message is used to inform of the resolution of a case, and optionally provides details about: - the corrective action undertaken by the case assignee; - information on the return where applicable. RsltnOfInvstgtn ResolutionOfInvestigationV09
1.0	1..1	Resolution Of Investigation V09 +Assignment	ISO Name ISO Definition	Assignment Identifies the assignment of an investigation case from an assigner to an assignee. Usage: The Assigner must be the sender of this confirmation and the Assignee must be the receiver.
			XML Tag Type	Assgnmt CaseAssignment5
1.1	1..1	Resolution Of Investigation V09 +Assignment ++Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Identification Uniquely identifies the case assignment. Id Max35Text 1 .. 35 1 .. 35
1.2	1..1	Resolution Of Investigation V09 +Assignment ++Assigner	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Instructing Party: Limited to 'BICFI' to identify a PSP, 'AnyBIC' to identify a CSM or 'LEI' or 'Name' to indicate a CSM when it has no BIC. 'Name' is limited to 70 characters in length. Assigner Party who assigns the case. Usage: This is also the sender of the message. Assgnr Party40Choice
1.3	1..1	Resolution Of Investigation V09 +Assignment ++Assignee	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Instructed Party: Limited to 'BICFI' to identify a PSP, 'AnyBIC' to identify a CSM or 'LEI' or 'Name' to indicate a CSM when it has no BIC. 'Name' is limited to 70 characters in length. Assignee Party to which the case is assigned. Usage: This is also the receiver of the message. Assgne Party40Choice
1.4	1..1	Resolution Of Investigation V09 +Assignment ++Creation Date Time	ISO Name ISO Definition XML Tag Type	Creation Date Time Date and time at which the assignment was created. CreDtTm ISODATETIME
2.0	0..1	Resolution Of Investigation V09 +Resolved Case	ISO Name ISO Definition XML Tag Type	Resolved Case Identifies a resolved case. RslvdCase Case5
3.0	1..1	Resolution Of Investigation V09 +Status	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Only 'Confirmation' is allowed. Status Indicates the status of the investigation. Sts InvestigationStatus5Choice
	1..1		XML Tag	xs:choice

#	SEPA Mult	Message Element	Inter-PSP Negative Response to RFRO SEPA Core Requirements
3.1	1..1	Resolution Of Investigation V09 +Status ++Confirmation	<p>SEPA Usage Rule(s) Only "RJCR" is allowed.</p> <p>ISO Name Confirmation</p> <p>ISO Definition Specifies the status of the investigation, in a coded form.</p> <p>XML Tag Type Conf</p> <p>ExternalInvestigationExecutionConfirmation1Code</p> <p>ISO Length 1 .. 4</p> <p>SEPA Length 1 .. 4</p> <p>SEPA Code Restrictions</p> <p>RJCR <i>RejectedCancellationRequest</i> <i>Used when a requested cancellation has been rejected.</i></p>
3.2	1..n	Resolution Of Investigation V09 +Status ++Rejected Modification	<p>ISO Name</p> <p>ISO Definition Reason for the rejection of a modification request, in a coded form.</p> <p>XML Tag Type RjctdMod</p> <p>ModificationStatusReason1Choice</p>
3.3	1..1	Resolution Of Investigation V09 +Status ++Duplicate Of	<p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type Duplicate Of</p> <p>Indicates a duplicated case.</p> <p>Usage: When present, the case identified in the message must be closed. The case identified as duplicated (in this component) will be pursued.</p> <p>DplctOf</p> <p>Case5</p>
3.4	1..1	Resolution Of Investigation V09 +Status ++Assignment Cancellation Confirmation	<p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type Assignment Cancellation Confirmation</p> <p>Indicates whether the cancellation of the assignment is confirmed or rejected.</p> <p>Usage: If yes, the cancellation of the assignment is confirmed.</p> <p>If no, the cancellation of the assignment is rejected and the investigation process will continue.</p> <p>AssgnmntCxlConf</p> <p>YesNoIndicator</p>
4.0	1..n	Resolution Of Investigation V09 +Cancellation Details	<p>SEPA Usage Rule(s) Mandatory.</p> <p>ISO Name</p> <p>ISO Definition Cancellation Details</p> <p>Specifies the details of the underlying transactions being cancelled.</p> <p>XML Tag Type CxlDtls</p> <p>UnderlyingTransaction22</p>
4.1	0..1	Resolution Of Investigation V09 +Cancellation Details ++Original Group Information And Status	<p>ISO Name</p> <p>ISO Definition Original Group Information And Status</p> <p>Provides information on the original cancellation message, to which the resolution refers.</p> <p>OrgnlGrpInfAndSts</p> <p>OriginalGroupHeader14</p> <p>XML Tag Type</p>
4.2	0..n	Resolution Of Investigation V09 +Cancellation Details ++Original Payment Information And Status	<p>ISO Name</p> <p>ISO Definition Original Payment Information And Status</p> <p>Provides information on the original (group of) transactions, to which the cancellation status refers.</p> <p>OrgnlPmtInfAndSts</p> <p>OriginalPaymentInstruction30</p> <p>XML Tag Type</p>
4.3	1..n	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status	<p>SEPA Usage Rule(s) Mandatory.</p> <p>ISO Name</p> <p>ISO Definition Transaction Information And Status</p> <p>Provides details on the original transactions to which the cancellation request message refers.</p> <p>TxInfAndSts</p> <p>PaymentTransaction102</p> <p>XML Tag Type</p>

#	SEPA Mult	Message Element	Inter-PSP Negative Response to RFRO SEPA Core Requirements
4.4	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Cancellation Status Identification	<p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name Cancellation Status Identification</p> <p>ISO Definition Unique and unambiguous identifier of a cancellation request status, as assigned by the assigner.</p> <p>Usage: The cancellation status identification can be used for reconciliation or to link tasks relating to the cancellation request.</p> <p>XML Tag CxlStsId</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>
4.5	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Resolved Case	<p>ISO Name Resolved Case</p> <p>ISO Definition Identifies the resolved case.</p> <p>XML Tag RslvdCase</p> <p>Type Case5</p>
4.6	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Group Information	<p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name Original Group Information</p> <p>ISO Definition Provides information on the original message.</p> <p>XML Tag OrgnlGrpInf</p> <p>Type OriginalGroupInformation29</p>
4.7	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Group Information ++++Original Message Identification	<p>ISO Name Original Message Identification</p> <p>ISO Definition Point to point reference assigned by the original instructing party to unambiguously identify the original message.</p> <p>XML Tag OrgnlMsgId</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>
4.8	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Group Information ++++Original Message Name Identification	<p>SEPA Usage Rule(s) <i>Must begin with 'pacs.008'. The addition of a variant number and version number is optional.</i></p> <p>ISO Name Original Message Name Identification</p> <p>ISO Definition Specifies the original message name identifier to which the message refers, for example, pacs.003.001.01 or MT103.</p> <p>XML Tag OrgnlMsgNmId</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>
4.9	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Group Information ++++Original Creation Date Time	<p>ISO Name Original Creation Date Time</p> <p>ISO Definition Original date and time at which the message was created.</p> <p>XML Tag OrgnlCreDtTm</p> <p>Type ISODateTime</p>
4.10	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Instruction Identification	<p>ISO Name Original Instruction Identification</p> <p>ISO Definition Unique identification, as assigned by the original instructing party for the original instructed party, to unambiguously identify the original instruction.</p> <p>XML Tag OrgnlInstrId</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>

#	SEPA Mult	Message Element	Inter-PSP Negative Response to RFRO SEPA Core Requirements	
4.11	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original End To End Identification	<p>SEPA Rulebook <i>AT-T014 The Originator's reference of the SEPA Credit Transfer Transaction.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name Original End To End Identification</p> <p>ISO Definition Unique identification, as assigned by the original initiating party, to unambiguously identify the original transaction.</p> <p>XML Tag OrgnlEndToEndId</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>	
4.12	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Identification	<p>SEPA Rulebook <i>AT-T054 The Originator PSP's reference of the SEPA Credit Transfer Transaction.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name Original Transaction Identification</p> <p>ISO Definition Unique identification, as assigned by the original first instructing agent, to unambiguously identify the transaction.</p> <p>XML Tag OrgnlTxId</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>	
4.13	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Clearing System Reference	<p>ISO Name Original Clearing System Reference</p> <p>ISO Definition Unique reference, as assigned by the original clearing system, to unambiguously identify the original instruction.</p> <p>XML Tag OrgnlClrSysRef</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>	
4.14	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original UETR	<p>ISO Name Original UETR</p> <p>ISO Definition Universally unique identifier to provide the original end-to-end reference of a payment transaction.</p> <p>XML Tag OrgnlUETR</p> <p>Type UUIDv4Identifier</p> <p>Pattern [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}</p>	
4.15	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Transaction Cancellation Status	<p>SEPA Usage Rule(s) <i>Mandatory.</i> <i>Only "RJCR" is allowed.</i></p> <p>ISO Name Transaction Cancellation Status</p> <p>ISO Definition Specifies the status of the transaction cancellation request.</p> <p>XML Tag TxCxlSts</p> <p>Type CancellationIndividualStatus1Code</p> <p>SEPA Code Restrictions</p> <p>RJCR <i>RejectedCancellationRequest</i> <i>Cancellation request is rejected</i></p>	
4.16	1..n	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Cancellation Status Reason Information	<p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name Cancellation Status Reason Information</p> <p>ISO Definition Provides detailed information on the cancellation status reason.</p> <p>XML Tag CxlStsRsnInf</p> <p>Type CancellationStatusReason4</p>	

#	SEPA Mult	Message Element	Inter-PSP Negative Response to RFRO SEPA Core Requirements															
4.17	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Cancellation Status Reason Information ++++Originator	<p>SEPA Rulebook <i>AT-E001 The name of the Beneficiary or AT-C002 The BIC code of the Beneficiary PSP.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i> <i>Limited to 'AnyBIC' for an Agent or 'Name' for a non-financial institution.</i> <i>'Name' is limited to 70 characters in length.</i></p> <p>ISO Name ISO Definition XML Tag Type Originator</p> <p>ISO Name ISO Definition XML Tag Type Party that issues the cancellation status.</p> <p>ISO Name ISO Definition XML Tag Type Orgtr</p> <p>ISO Name ISO Definition XML Tag Type PartyIdentification135</p>															
4.18	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Cancellation Status Reason Information ++++Reason	<p>SEPA Rulebook <i>AT-R077 Reason Code for non-acceptance of the Request for Recall by the Originator.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name Reason ISO Definition Specifies the reason for the status report. XML Tag Rsn Type CancellationStatusReason3Choice</p>															
	1..1		XML Tag xs:choice															
4.19	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Cancellation Status Reason Information ++++Reason +++++Code	<p>SEPA Usage Rule(s) <i>Only "AC04", "AM04", "ARDT", "CUST", "LEGL", "NOAR" or "NOOR" are allowed.</i></p> <p>ISO Name Code ISO Definition Reason for the cancellation status, in a coded form.</p> <p>XML Tag Cd Type ExternalPaymentCancellationRejection1Code</p> <p>ISO Length 1 .. 4 SEPA Length 1 .. 4</p> <p>SEPA Code Restrictions</p> <table> <tr> <td>AC04</td> <td><i>ClosedAccountNumber</i> <i>Account number specified has been closed on the receiver's books.</i></td> </tr> <tr> <td>AM04</td> <td><i>InsufficientFunds</i> <i>Amount of funds available to cover specified message amount is insufficient.</i></td> </tr> <tr> <td>ARDT</td> <td><i>AlreadyReturned</i> <i>Cancellation not accepted as the transaction has already been returned.</i></td> </tr> <tr> <td>CUST</td> <td><i>CustomerDecision</i> <i>Reported when the cancellation cannot be accepted because of a customer decision (Creditor).</i></td> </tr> <tr> <td>LEGL</td> <td><i>LegalDecision</i> <i>Reported when the cancellation cannot be accepted because of regulatory rules.</i></td> </tr> <tr> <td>NOAS</td> <td><i>NoAnswerFromCustomer</i> <i>No response from beneficiary (to the cancellation request).</i></td> </tr> <tr> <td>NOOR</td> <td><i>NoOriginalTransactionReceived</i> <i>Original transaction (subject to cancellation) never received.</i></td> </tr> </table>	AC04	<i>ClosedAccountNumber</i> <i>Account number specified has been closed on the receiver's books.</i>	AM04	<i>InsufficientFunds</i> <i>Amount of funds available to cover specified message amount is insufficient.</i>	ARDT	<i>AlreadyReturned</i> <i>Cancellation not accepted as the transaction has already been returned.</i>	CUST	<i>CustomerDecision</i> <i>Reported when the cancellation cannot be accepted because of a customer decision (Creditor).</i>	LEGL	<i>LegalDecision</i> <i>Reported when the cancellation cannot be accepted because of regulatory rules.</i>	NOAS	<i>NoAnswerFromCustomer</i> <i>No response from beneficiary (to the cancellation request).</i>	NOOR	<i>NoOriginalTransactionReceived</i> <i>Original transaction (subject to cancellation) never received.</i>	
AC04	<i>ClosedAccountNumber</i> <i>Account number specified has been closed on the receiver's books.</i>																	
AM04	<i>InsufficientFunds</i> <i>Amount of funds available to cover specified message amount is insufficient.</i>																	
ARDT	<i>AlreadyReturned</i> <i>Cancellation not accepted as the transaction has already been returned.</i>																	
CUST	<i>CustomerDecision</i> <i>Reported when the cancellation cannot be accepted because of a customer decision (Creditor).</i>																	
LEGL	<i>LegalDecision</i> <i>Reported when the cancellation cannot be accepted because of regulatory rules.</i>																	
NOAS	<i>NoAnswerFromCustomer</i> <i>No response from beneficiary (to the cancellation request).</i>																	
NOOR	<i>NoOriginalTransactionReceived</i> <i>Original transaction (subject to cancellation) never received.</i>																	
4.20	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Cancellation Status Reason Information ++++Reason +++++Proprietary	<p>ISO Name Proprietary ISO Definition Reason for the status, in a proprietary form. XML Tag Prtry Type Max35Text</p> <p>ISO Length 1 .. 35 SEPA Length 1 .. 35</p>															

#	SEPA Mult	Message Element	Inter-PSP Negative Response to RFRO SEPA Core Requirements	
4.21	1.. 11	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Cancellation Status Reason Information ++++Additional Information	<p>SEPA Rulebook</p> <p>SEPA Usage Rule(s) Mandatory. First occurrence is mandatory and must start with "ATR072/" followed by the information as per attribute description. When reason code was "AC03" (Wrong IBAN) in the camt.056, then up to ten further occurrences are allowed, all starting with "ATR078/" followed by the information as per attribute description.</p> <p>ISO Name ISO Definition XML Tag Type ISO Length SEPA Length</p>	<p>AT-R072 The specific reference of the Originator PSP for the Request for Recall by the Originator. AT-R078 Provision of all information available to file a legal claim to recover the funds in case of reason code 'wrong unique identifier of the Beneficiary account'.</p> <p>Additional Information Further details on the cancellation status reason. AddtlInf Max105Text 1 .. 105 1 .. 105</p>
4.22	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Resolution Related Information	<p>ISO Name ISO Definition XML Tag Type</p>	<p>Resolution Related Information Reference of a return or a reversal transaction that is initiated to fix the case under investigation as part of the resolution. RsltnRltdInf ResolutionData1</p>
4.23	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Interbank Settlement Amount	<p>ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits SEPA Inclusive</p>	<p>Original Interbank Settlement Amount Amount of money moved between the instructing agent and the instructed agent, as provided in the original instruction. OrgnlIntrBkSttlmAmt ActiveOrHistoricCurrencyAndAmount 5 18 0</p>
4.24	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Interbank Settlement Date	<p>ISO Name ISO Definition XML Tag Type</p>	<p>Original Interbank Settlement Date Date, as provided in the original transaction, on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. OrgnlIntrBkSttlmDt ISODate</p>
4.25	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Assigner	<p>ISO Name ISO Definition XML Tag Type</p>	<p>Assigner Party who assigns the case. Usage: This is also the agent that instructs the next party in the chain to carry out the (set of) cancellation request(s). Assgnr Party40Choice</p>
4.26	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Assignee	<p>ISO Name ISO Definition XML Tag Type</p>	<p>Assignee Party to which the case is assigned. Usage: This is also the agent that is instructed by the previous party in the chain to carry out the (set of) cancellation request(s). Assgne Party40Choice</p>

#	SEPA Mult	Message Element	Inter-PSP Negative Response to RFRO SEPA Core Requirements	
4.27	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference	<p>SEPA Rulebook</p> <p>An exact copy of the original Inter-PSP Payment Dataset (DS-02) to which the Request for Recall by the Originator relates to.</p> <p>SEPA Usage Rule(s)</p> <p>Mandatory.</p> <p>The yellow shaded elements under 'Original Transaction Reference' must be populated with the same value as the message elements of the original instruction.</p> <p>ISO Name</p> <p>Original Transaction Reference</p> <p>ISO Definition</p> <p>Key elements used to identify the original transaction that is being referred to.</p> <p>XML Tag Type</p> <p>OrgnlTxRef</p> <p>OriginalTransactionReference28</p>	
4.28	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Interbank Settlement Amount	<p>SEPA Rulebook</p> <p>AT-T002 Amount of the SEPA Credit Transfer in Euro</p> <p>ISO Name</p> <p>Interbank Settlement Amount</p> <p>ISO Definition</p> <p>Amount of money moved between the instructing agent and the instructed agent.</p> <p>XML Tag Type</p> <p>IntrBkSttlmAmt</p> <p>SEPA FractDigits</p> <p>ActiveOrHistoricCurrencyAndAmount</p> <p>TotalDigits</p> <p>2</p> <p>SEPA Inclusive</p> <p>18</p> <p>0.01 .. 999999999.99</p>	
4.29	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Amount	<p>ISO Name</p> <p>Amount</p> <p>ISO Definition</p> <p>Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.</p> <p>XML Tag Type</p> <p>Amt</p> <p>AmountType4Choice</p>	
4.30	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Interbank Settlement Date	<p>SEPA Rulebook</p> <p>AT-T051 Settlement Date of the Credit Transfer in Euro</p> <p>ISO Name</p> <p>Interbank Settlement Date</p> <p>ISO Definition</p> <p>Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.</p> <p>XML Tag Type</p> <p>IntrBkSttlmDt</p> <p>ISODate</p>	
4.31	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Requested Collection Date	<p>ISO Name</p> <p>Requested Collection Date</p> <p>ISO Definition</p> <p>Date and time at which the creditor requests that the amount of money is to be collected from the debtor.</p> <p>XML Tag Type</p> <p>ReqdColltnDt</p> <p>ISODate</p>	
4.32	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Requested Execution Date	<p>ISO Name</p> <p>Requested Execution Date</p> <p>ISO Definition</p> <p>Date at which the initiating party requests the clearing agent to process the payment.</p> <p>Usage: This is the date on which the debtor's account is to be debited. If payment by cheque, the date when the cheque must be generated by the bank.</p> <p>XML Tag Type</p> <p>ReqdExctnDt</p> <p>DateAndDateTime2Choice</p>	
4.33	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Creditor Scheme Identification	<p>ISO Name</p> <p>Creditor Scheme Identification</p> <p>ISO Definition</p> <p>Credit party that signs the mandate.</p> <p>XML Tag Type</p> <p>CdtrSchmeId</p> <p>PartyIdentification135</p>	

#	SEPA Mult	Message Element	Inter-PSP Negative Response to RFRO SEPA Core Requirements	
4.34	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Settlement Information	ISO Name XML Tag Type	Settlement Information Specifies the details on how the settlement of the original transaction(s) between the instructing agent and the instructed agent was completed. Stlmlnfo SettlementInstruction7
4.35	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Payment Type Information	SEPA Rulebook ISO Name XML Tag Type	<i>AT-T001 Identification code of the Scheme.</i> <i>AT-T008 Category Purpose of the Credit Transfer.</i> <i>If the original transaction was sent according to Annex V (Use of Extended Remittance Information) of the SCT Rulebook (refer to section 'Inter-PSP payment with use of the Extended Remittance Information option' below), then 'Local Instrument/Code' must be populated with "PERI" (Payment with Extended Remittance Information).</i> Payment Type Information Set of elements used to further specify the type of transaction. PmtTpInf PaymentTypeInformation27
4.36	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Payment Method	ISO Name XML Tag Type	Payment Method Specifies the means of payment that will be used to move the amount of money. PmtMtd PaymentMethod4Code
4.37	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Mandate Related Information	ISO Name XML Tag Type	Mandate Related Information Provides further details of the mandate signed between the creditor and the debtor. MndtRltdInf MandateRelatedInformation14
4.38	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Remittance Information	SEPA Rulebook ISO Name XML Tag Type	<i>AT-T009 Remittance information or AT-T010 The unstructured Remittance Information sent by the Originator to the Beneficiary in the Credit Transfer Instruction (in case of use of the Extended Remittance Information (ERI) option in the original SEPA Credit Transfer, AT-T011 The structured Remittance Information sent by the Originator to the Beneficiary in the SEPA Credit Transfer Instruction, will NOT be transported here).</i> Remittance Information Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system. RmtInf RemittanceInformation16
4.39	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Ultimate Debtor	SEPA Rulebook SEPA Usage Rule(s) ISO Name XML Tag Type	<i>AT-P006 The name of the Originator Reference Party.</i> <i>AT-P007 The identification code of the Originator Reference Party.</i> <i>Only 'Party' is allowed.</i> Ultimate Debtor Ultimate party that owes an amount of money to the (ultimate) creditor. UltmtDbtr Party40Choice

#	SEPA Mult	Message Element	Inter-PSP Negative Response to RFRO SEPA Core Requirements	
4.40	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Debtor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-P001 Name of the Originator - Mandatory.</i> <i>AT-P005 Address of the Originator.</i> <i>AT-P004 Originator's Identification Code.</i> <i>Only 'Party' is allowed.</i> Debtor Party that owes an amount of money to the (ultimate) creditor. Dbtr Party40Choice
4.41	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Debtor Account	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-D001 The IBAN of the account of the Originator.</i> <i>AT-P003 The Proxy/Alias of the account of the Originator.</i> Debtor Account Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction. DbtrAcct CashAccount38
4.42	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Debtor Agent	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-D002 The BIC code of the Originator PSP.</i> Debtor Agent Financial institution servicing an account for the debtor. DbtrAgt BranchAndFinancialInstitutionIdentification6
4.43	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Debtor Agent Account	ISO Name ISO Definition XML Tag Type	Debtor Agent Account Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain. DbtrAgtAcct CashAccount38
4.44	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Creditor Agent	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-C002 The BIC code of the Beneficiary PSP.</i> Creditor Agent Financial institution servicing an account for the creditor. CdtrAgt BranchAndFinancialInstitutionIdentification6
4.45	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Creditor Agent Account	ISO Name ISO Definition XML Tag Type	Creditor Agent Account Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction. CdtrAgtAcct CashAccount38
4.46	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Creditor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-E001 Name of the Beneficiary – Mandatory.</i> <i>AT-E004 Address of the Beneficiary.</i> <i>AT-E005 Beneficiary Identification Code.</i> <i>Only 'Party' is allowed.</i> Creditor Party to which an amount of money is due. Cdtr Party40Choice
4.47	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Creditor Account	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-C001 The IBAN of the account of the Beneficiary.</i> <i>AT-E003 The Proxy/Alias of the account of the Beneficiary.</i> Creditor Account Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction. CdtrAcct CashAccount38

#	SEPA Mult	Message Element	Inter-PSP Negative Response to RFRO SEPA Core Requirements	
4.48	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Ultimate Creditor	<p>SEPA Rulebook</p> <p>SEPA Usage Rule(s) Only 'Party' is allowed.</p> <p>ISO Name Ultimate Creditor</p> <p>ISO Definition Ultimate party to which an amount of money is due.</p> <p>XML Tag Type UltmtCdtr Party40Choice</p>	<p><i>AT-E007 The name of the Beneficiary Reference Party.</i></p> <p><i>AT-E010 The identification code of the Beneficiary Reference Party.</i></p>
4.49	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Purpose	<p>SEPA Rulebook</p> <p>ISO Name Purpose</p> <p>ISO Definition Underlying reason for the payment transaction.</p> <p>XML Tag Type Usage: Purpose is used by the end customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain. Purp Purpose2Choice</p>	<i>AT-T007 The purpose of the SEPA Credit Transfer.</i>
5.0	0..1	Resolution Of Investigation V09 +Modification Details	<p>ISO Name Modification Details</p> <p>ISO Definition Specifies the details of the underlying transaction being modified.</p> <p>XML Tag Type ModDtls PaymentTransaction107</p>	
6.0	0..1	Resolution Of Investigation V09 +Claim Non Receipt Details	<p>ISO Name Claim Non Receipt Details</p> <p>ISO Definition Specifies the details of the underlying transaction for which a claim non receipt has been initiated.</p> <p>XML Tag Type ClmNonRctDtls ClaimNonReceipt2Choice</p>	
7.0	0..1	Resolution Of Investigation V09 +Statement Details	<p>ISO Name Statement Details</p> <p>ISO Definition Details on the underlying statement entry.</p> <p>XML Tag Type StmtDtls StatementResolutionEntry4</p>	
8.0	0..1	Resolution Of Investigation V09 +Correction Transaction	<p>ISO Name Correction Transaction</p> <p>ISO Definition References a transaction initiated to fix the case under investigation.</p> <p>XML Tag Type CrrctnTx CorrectiveTransaction4Choice</p>	
9.0	0..1	Resolution Of Investigation V09 +Resolution Related Information	<p>ISO Name Resolution Related Information</p> <p>ISO Definition Reference to fix the case under investigation as part of the resolution.</p> <p>XML Tag Type RsltnRltdInf ResolutionData1</p>	
10.0	0..n	Resolution Of Investigation V09 +Supplementary Data	<p>ISO Name Supplementary Data</p> <p>ISO Definition Additional information that cannot be captured in the structured elements and/or any other specific block.</p> <p>XML Tag Type SplmtryData SupplementaryData1</p>	



2.10 Inter-PSP Positive Response to the Request for Recall by the Originator Dataset (DS-08)

2.10.1 Use of inter-PSP return credit transfer message (pacs.004.001.09)

In the context of a Request for Recall by the Originator of an SCT, this message is used to transmit a positive response to a:

- Request for Recall by the Originator message (FI-to-FI Payment Cancellation Request V01, camt.056.001.08);
- Request for Status Update on a Request for Recall by the Originator message (FI-to-FI Payment Status Request, pacs.028.001.03, refer to section 'Request for Status Update on a Request for Recall by the Originator' below);

where the following apply:

- Index 1.9 'Interbank Settlement Date' to be populated with AT-R076 'The settlement date for the positive response to the Request for Recall by the Originator'.
- Index 3.13 'Returned Interbank Settlement Amount' to be populated with AT-R074 'The returned amount of the positive response to the Request for Recall by the Originator'.
- Index 3.17 'Returned Instructed Amount' may be used.
- Index 3.22 'Amount' (under 'Charges Information') to be populated with AT-R075 'Fee for the positive response to the Request for Recall by the Originator', if any.
- Index 3.24 'Financial Institution Identification' (under 'Agent' under 'Charges Information') to be populated with AT-C002 'The BIC code of the Beneficiary PSP'.
- Index 3.31 'Originator' to be populated with AT-R002 'The Identification of the type of party initiating the "R" message'.
- Index 3.33 'Reason/Code' (under 'Return Reason Information') to be populated only with "FOCR" (Following Cancellation Request).
- Index 3.35 'Additional Information' (under 'Return Reason Information') to be used with a mandatory occurrence starting with "ATR072/" followed by the information as per attribute description 'The specific reference of the Originator PSP for the Request for Recall by the Originator'.

The message caters for a single or a group positive response.

Note: Attribute AT-R001 'The type of R-message' is implied by the 'Message Name', 'pacs.004.001.09', the 'Original Message Name Identification' must begin with pacs.008 (the addition of a variant number and version number is optional), 'Reason' under 'Return Reason Information' set to "FOCR" and Originator set to AT-E001 'Name of the Beneficiary'.

Note: Message elements under 'Original Transaction Reference' sequence are based on DS-02 attributes.

#	SEPA Mult	Message Element	Inter-PSP Positive Response to RFRO SEPA Core Requirements	
		Document	XML Tag Type	Document Document
	1..1	Payment Return V09	ISO Name ISO Definition	Payment Return V09 Scope The PaymentReturn message is sent by an agent to the previous agent in the payment chain to undo a payment previously settled.
			XML Tag Type	PmtRtr PaymentReturnV09
1.0	1..1	Payment Return V09 +Group Header	ISO Name ISO Definition	Group Header Set of characteristics shared by all individual transactions included in the message.
			XML Tag Type	GrpHdr GroupHeader90
1.1	1..1	Payment Return V09 +Group Header ++Message Identification	ISO Name ISO Definition	Message Identification Point to point reference, as assigned by the instructing party and sent to the next party in the chain, to unambiguously identify the message. Usage: The instructing party has to make sure that MessageIdentification is unique per instructed party for a pre-agreed period.
			XML Tag Type ISO Length SEPA Length	MsgId Max35Text 1 .. 35 1 .. 35
1.2	1..1	Payment Return V09 +Group Header ++Creation Date Time	ISO Name ISO Definition	Creation Date Time Date and time at which the message was created.
			XML Tag Type	CreDtTm ISODateTime
1.3	0..2	Payment Return V09 +Group Header ++Authorisation	ISO Name ISO Definition	Authorisation User identification or any user key to be used to check whether the initiating party is allowed to initiate transactions from the account specified in the message.
			XML Tag Type	Usage: The content is not of a technical nature, but reflects the organisational structure at the initiating side. The authorisation element can typically be used in relay scenarios, payment initiations, payment returns or payment reversals that are initiated on behalf of a party different from the initiating party. Authstn Authorisation1Choice
1.4	0..1	Payment Return V09 +Group Header ++Batch Booking	ISO Name ISO Definition	Batch Booking Identifies whether a single entry per individual transaction or a batch entry for the sum of the amounts of all transactions within the group of a message is requested.
			XML Tag Type	Usage: Batch booking is used to request and not order a possible batch booking. BtchBookg BatchBookingIndicator
1.5	1..1	Payment Return V09 +Group Header ++Number Of Transactions	ISO Name ISO Definition	Number Of Transactions Number of individual transactions contained in the message.
			XML Tag Type Pattern	NbOfTxns Max15NumericText [0-9]{1,15}

#	SEPA Mult	Message Element	Inter-PSP Positive Response to RFRO SEPA Core Requirements	
1.6	0..1	Payment Return V09 +Group Header ++Control Sum	ISO Name ISO Definition XML Tag Type <i>SEPA FractDigits</i> TotalDigits	Control Sum Total of all individual amounts included in the message, irrespective of currencies. CtrlSum DecimalNumber 17 18
1.7	0..1	Payment Return V09 +Group Header ++Group Return	ISO Name ISO Definition XML Tag Type	Group Return Indicates whether the return applies to the whole group of transactions or to individual transactions within the original group(s). GrpRtr TrueFalseIndicator
1.8	1..1	Payment Return V09 +Group Header ++Total Returned Interbank Settlement Amount	<i>SEPA Usage Rule(s)</i> Mandatory. <i>Only 'EUR' is allowed.</i> <i>Amount must be 0.01 or more and 99999999999999.99 or less.</i> <i>The fractional part has a maximum of two digits.</i> <i>SEPA Format Rule(s)</i> ISO Name ISO Definition XML Tag Type <i>SEPA FractDigits</i> TotalDigits <i>SEPA Inclusive</i>	Total Returned Interbank Settlement Amount Total amount of money moved between the instructing agent and the instructed agent in the return message. TtlRtrdIntrBkStlmtAmt ActiveCurrencyAndAmount 2 18 0.01 .. 99999999999999.99
1.9	1..1	Payment Return V09 +Group Header ++Interbank Settlement Date	<i>SEPA Rulebook</i> <i>SEPA Usage Rule(s)</i> Mandatory. ISO Name ISO Definition XML Tag Type	AT-R076 The settlement date for the positive response to the Request for Recall by the Originator. Interbank Settlement Date Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. IntrBkStlmtDt ISODate
1.10	1..1	Payment Return V09 +Group Header ++Settlement Information	ISO Name ISO Definition XML Tag Type	Settlement Information Specifies the details on how the settlement of the transaction(s) between the instructing agent and the instructed agent is completed. StlmtInf SettlementInstruction7
1.11	1..1	Payment Return V09 +Group Header ++Settlement Information +++Settlement Method	<i>SEPA Usage Rule(s)</i> Only "CLRG", "INGA" and "INDA" are allowed. ISO Name ISO Definition XML Tag Type <i>SEPA Code Restrictions</i> <i>CLRG</i> <i>INDA</i> <i>INGA</i>	Settlement Method Method used to settle the (batch of) payment instructions. StlmtMtd SettlementMethod1Code ClearingSystem Settlement is done through a payment clearing system. InstructedAgent Settlement is done by the agent instructed to execute a payment instruction. InstructingAgent Settlement is done by the agent instructing and forwarding the payment to the next party in the payment chain.

#	SEPA Mult	Message Element	Inter-PSP Positive Response to RFRO SEPA Core Requirements		
1.12	0..1	Payment Return V09 +Group Header ++Settlement Information +++Settlement Account	<i>SEPA Usage Rule(s)</i> Only 'Identification' is allowed. ISO Name Settlement Account ISO Definition A specific purpose account used to post debit and credit entries as a result of the transaction. XML Tag Type SttlmAcct CashAccount38		
1.13	0..1	Payment Return V09 +Group Header ++Settlement Information +++Clearing System	ISO Name ISO Definition Clearing System Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed. XML Tag Type ClrSys ClearingSystemIdentification3Choice		
	1..1		XML Tag xs:choice		
1.14	1..1	Payment Return V09 +Group Header ++Settlement Information +++Clearing System ++++Code	ISO Name ISO Definition Infrastructure through which the payment instruction is processed, as published in an external clearing system identification code list. XML Tag Type Cd ISO Length ExternalCashClearingSystem1Code SEPA Length 1 .. 3		
1.15	1..1	Payment Return V09 +Group Header ++Settlement Information +++Clearing System ++++Proprietary	ISO Name ISO Definition Proprietary Clearing system identification in a proprietary form. XML Tag Type Prtry ISO Length Max35Text SEPA Length 1 .. 35		
1.16	0..1	Payment Return V09 +Group Header ++Settlement Information +++Instructing Reimbursement Agent	ISO Name ISO Definition Instructing Reimbursement Agent Agent through which the instructing agent will reimburse the instructed agent. XML Tag Type Usage: If InstructingAgent and InstructedAgent have the same reimbursement agent, then only InstructingReimbursementAgent must be used. InstgRmbrsmntAgt BranchAndFinancialInstitutionIdentification6		
1.17	0..1	Payment Return V09 +Group Header ++Settlement Information +++Instructing Reimbursement Agent Account	ISO Name ISO Definition Instructing Reimbursement Agent Account Unambiguous identification of the account of the instructing reimbursement agent account at its servicing agent in the payment chain. XML Tag Type InstgRmbrsmntAgtAcct CashAccount38		
1.18	0..1	Payment Return V09 +Group Header ++Settlement Information +++Instructed Reimbursement Agent	ISO Name ISO Definition Instructed Reimbursement Agent Agent at which the instructed agent will be reimbursed. XML Tag Type Usage: If InstructedReimbursementAgent contains a branch of the InstructedAgent, then the party in InstructedAgent will claim reimbursement from that branch/will be paid by that branch. Usage: If InstructingAgent and InstructedAgent have the same reimbursement agent, then only InstructingReimbursementAgent must be used. InstdRmbrsmntAgt BranchAndFinancialInstitutionIdentification6		
1.19	0..1	Payment Return V09 +Group Header ++Settlement Information +++Instructed Reimbursement Agent Account	ISO Name ISO Definition Instructed Reimbursement Agent Account Unambiguous identification of the account of the instructed reimbursement agent account at its servicing agent in the payment chain. XML Tag Type InstdRmbrsmntAgtAcct CashAccount38		

#	SEPA Mult	Message Element	Inter-PSP Positive Response to RFRO SEPA Core Requirements	
1.20	0..1	Payment Return V09 +Group Header ++Settlement Information +++Third Reimbursement Agent	ISO Name ISO Definition XML Tag Type	Third Reimbursement Agent Agent at which the instructed agent will be reimbursed. Usage: If ThirdReimbursementAgent contains a branch of the InstructedAgent, then the party in InstructedAgent will claim reimbursement from that branch/will be paid by that branch. ThrdRmbrsmntAgt BranchAndFinancialInstitutionIdentification6
1.21	0..1	Payment Return V09 +Group Header ++Settlement Information +++Third Reimbursement Agent Account	ISO Name ISO Definition XML Tag Type	Third Reimbursement Agent Account Unambiguous identification of the account of the third reimbursement agent account at its servicing agent in the payment chain. ThrdRmbrsmntAgtAcct CashAccount38
1.22	0..1	Payment Return V09 +Group Header ++Instructing Agent	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Only 'BICFI' is allowed. Instructing Agent Agent that instructs the next party in the chain to carry out the (set of) instruction(s). Usage: The instructing agent is the party sending the return message and not the party that sent the original instruction that is being returned. InstgAgt BranchAndFinancialInstitutionIdentification6
1.23	0..1	Payment Return V09 +Group Header ++Instructed Agent	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Only 'BICFI' is allowed. Instructed Agent Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s). Usage: The instructed agent is the party receiving the return message and not the party that received the original instruction that is being returned. InstdAgt BranchAndFinancialInstitutionIdentification6
2.0	0..1	Payment Return V09 +Original Group Information	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Sub-elements of 'Original Group Information' must be present in either 'Original Group Information' or in 'Transaction Information'. Original Group Information Information concerning the original group of transactions, to which the message refers. OrgnlGrpInf OriginalGroupHeader18
2.1	1..1	Payment Return V09 +Original Group Information ++Original Message Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Message Identification Point to point reference, as assigned by the original instructing party, to unambiguously identify the original message. OrgnlMsgId Max35Text 1 .. 35 1 .. 35
2.2	1..1	Payment Return V09 +Original Group Information ++Original Message Name Identification	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Must begin with 'pacs.008'. The addition of a variant number and version number is optional. Original Message Name Identification Specifies the original message name identifier to which the message refers. OrgnlMsgNmId Max35Text 1 .. 35 1 .. 35
2.3	0..1	Payment Return V09 +Original Group Information ++Original Creation Date Time	ISO Name ISO Definition XML Tag Type	Original Creation Date Time Date and time at which the original message was created. OrgnlCreDtTm ISODateTime

#	SEPA Mult	Message Element	Inter-PSP Positive Response to RFRO SEPA Core Requirements			
2.4	0..n	Payment Return V09 +Original Group Information ++Return Reason Information	ISO Name ISO Definition XML Tag Type	Return Reason Information Provides detailed information on the return reason. RtrRsnInf PaymentReturnReason6		
3.0	1..n	Payment Return V09 +Transaction Information	SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type	Transaction Information Information concerning the original transactions, to which the return message refers. TxInf PaymentTransaction112		
3.1	1..1	Payment Return V09 +Transaction Information ++Return Identification	SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Return Identification Unique identification, as assigned by an instructing party for an instructed party, to unambiguously identify the returned transaction. Usage: The instructing party is the party sending the return message and not the party that sent the original instruction that is being returned. RtrId Max35Text 1 .. 35 1 .. 35		
3.2	0..1	Payment Return V09 +Transaction Information ++Original Group Information	SEPA Usage Rule(s) Sub-elements of 'Original Group Information' must be present in either 'Original Group Information' or in 'Transaction Information'. ISO Name ISO Definition XML Tag Type	Original Group Information Provides information on the original message. OrgnlGrpInf OriginalGroupInformation29		
3.3	1..1	Payment Return V09 +Transaction Information ++Original Group Information +++Original Message Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Message Identification Point to point reference assigned by the original instructing party to unambiguously identify the original message. OrgnlMsgId Max35Text 1 .. 35 1 .. 35		
3.4	1..1	Payment Return V09 +Transaction Information ++Original Group Information +++Original Message Name Identification	SEPA Usage Rule(s) Must begin with 'pacs.008'. The addition of a variant number and version number is optional. ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Message Name Identification Specifies the original message name identifier to which the message refers, for example, pacs.003.001.01 or MT103. OrgnlMsgNmId Max35Text 1 .. 35 1 .. 35		
3.5	0..1	Payment Return V09 +Transaction Information ++Original Group Information +++Original Creation Date Time	ISO Name ISO Definition XML Tag Type	Original Creation Date Time Original date and time at which the message was created. OrgnlCreDtTm ISODateTime		
3.6	0..1	Payment Return V09 +Transaction Information ++Original Instruction Identification	SEPA Usage Rule(s) Mandatory if provided in the original instruction. ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Instruction Identification Unique identification, as assigned by the original instructing party for the original instructed party, to unambiguously identify the original instruction. OrgnlInstrId Max35Text 1 .. 35 1 .. 35		

#	SEPA Mult	Message Element	Inter-PSP Positive Response to RFRO SEPA Core Requirements	
3.7	1..1	Payment Return V09 +Transaction Information ++Original End To End Identification	<p>SEPA Rulebook <i>AT-T014 The Originator's reference of the SEPA Credit Transfer Transaction.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name</p> <p>ISO Definition Unique identification, as assigned by the original initiating party, to unambiguously identify the original transaction.</p> <p>XML Tag</p> <p>Type</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>	
3.8	1..1	Payment Return V09 +Transaction Information ++Original Transaction Identification	<p>SEPA Rulebook <i>AT-T054 The Originator PSP's reference of the SEPA Credit Transfer Transaction.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name</p> <p>ISO Definition Unique identification, as assigned by the original first instructing agent, to unambiguously identify the transaction.</p> <p>XML Tag</p> <p>Type</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>	
3.9	0..1	Payment Return V09 +Transaction Information ++Original UETR	<p>ISO Name</p> <p>ISO Definition Universally unique identifier to provide the original end-to-end reference of a payment transaction.</p> <p>XML Tag</p> <p>Type</p> <p>Pattern OrgnlUETR UUIDv4Identifier [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}</p>	Original UETR
3.10	0..1	Payment Return V09 +Transaction Information ++Original Clearing System Reference	<p>ISO Name</p> <p>ISO Definition Unique reference, as assigned by the original clearing system, to unambiguously identify the original instruction.</p> <p>XML Tag</p> <p>Type</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>	Original Clearing System Reference
3.11	1..1	Payment Return V09 +Transaction Information ++Original Interbank Settlement Amount	<p>SEPA Rulebook <i>AT-T002 Amount of the SEPA Credit Transfer in Euro.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>SEPA Format Rule(s)</p> <p>ISO Name</p> <p>ISO Definition Only 'EUR' is allowed. Amount must be 0.01 or more and 999999999.99 or less. The fractional part has a maximum of two digits.</p> <p>XML Tag</p> <p>Type</p> <p>SEPA FractDigits 2</p> <p>TotalDigits 18</p> <p>SEPA Inclusive 0.01 .. 999999999.99</p>	Original Interbank Settlement Amount Amount of money moved between the instructing agent and the instructed agent, as provided in the original instruction.

#	SEPA Mult	Message Element	Inter-PSP Positive Response to RFRO SEPA Core Requirements	
3.12	0..1	Payment Return V09 +Transaction Information ++Original Interbank Settlement Date	ISO Name ISO Definition XML Tag Type	Original Interbank Settlement Date Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. Usage: the OriginalInterbankSettlementDate is the interbank settlement date of the original instruction return message, and not of the return message. OrgnlIntrBkSttlmDt ISODate
3.13	1..1	Payment Return V09 +Transaction Information ++Returned Interbank Settlement Amount	SEPA Rulebook SEPA Usage Rule(s) SEPA Format Rule(s) ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits SEPA Inclusive	AT-R074 <i>The returned amount of the positive response to the Request for Recall by the Originator in euro.</i> <i>The amount must be equal to the 'Original Interbank Settlement Amount' less, if present, the 'Amount' under 'Charges Information'. Only 'EUR' is allowed.</i> <i>Amount must be 0.01 or more and 999999999.99 or less.</i> <i>The fractional part has a maximum of two digits.</i> Returned Interbank Settlement Amount Amount of money to be moved between the instructing agent and the instructed agent in the returned instruction. RtrdIntrBkSttlmAmt ActiveCurrencyAndAmount 2 18 0.01 .. 999999999.99
3.14	0..1	Payment Return V09 +Transaction Information ++Interbank Settlement Date	ISO Name ISO Definition XML Tag Type	Interbank Settlement Date Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. Usage: the InterbankSettlementDate is the interbank settlement date of the return message, and not of the original instruction. IntrBkSttlmDt ISODate
3.15	0..1	Payment Return V09 +Transaction Information ++Settlement Priority	ISO Name ISO Definition XML Tag Type	Settlement Priority Indicator of the urgency or order of importance that the instructing party would like the instructed party to apply to the processing of the settlement instruction. Usage: the SettlementPriority is the settlement priority of the return message, and not of the original instruction. SttlmPrty Priority3Code
3.16	0..1	Payment Return V09 +Transaction Information ++Settlement Time Indication	ISO Name ISO Definition XML Tag Type	Settlement Time Indication Provides information on the occurred settlement time(s) of the payment transaction. SttlmTmIndctn SettlementDateTimeIndication1

#	SEPA Mult	Message Element	Inter-PSP Positive Response to RFRO SEPA Core Requirements
3.17	0..1	Payment Return V09 +Transaction Information ++Returned Instructed Amount	<p>SEPA Usage Rule(s) Only 'EUR' is allowed. Amount must be 0.01 or more and 999999999.99 or less. The fractional part has a maximum of two digits.</p> <p>SEPA Format Rule(s)</p> <p>ISO Name</p> <p>ISO Definition Returned Instructed Amount Amount of money to be moved between the debtor and the creditor, before deduction of charges, in the returned transaction. Usage: This amount has to be transported unchanged through the transaction chain. RtrdInstdAmt</p> <p>XML Tag</p> <p>Type ActiveOrHistoricCurrencyAndAmount</p> <p>SEPA FractDigits 2</p> <p>TotalDigits 18</p> <p>SEPA Inclusive 0.01 .. 999999999.99</p>
3.18	0..1	Payment Return V09 +Transaction Information ++Exchange Rate	<p>ISO Name</p> <p>ISO Definition Exchange Rate Factor used to convert an amount from one currency into another. This reflects the price at which one currency was bought with another currency. XchgRate</p> <p>XML Tag</p> <p>Type BaseOneRate</p> <p>SEPA FractDigits 10</p> <p>TotalDigits 11</p>
3.19	0..1	Payment Return V09 +Transaction Information ++Compensation Amount	<p>ISO Name</p> <p>ISO Definition Compensation Amount Amount of money asked or paid as compensation for the processing of the instruction. CompstnAmt</p> <p>XML Tag</p> <p>Type ActiveOrHistoricCurrencyAndAmount</p> <p>SEPA FractDigits 5</p> <p>TotalDigits 18</p> <p>SEPA Inclusive 0 ..</p>
3.20	0..1	Payment Return V09 +Transaction Information ++Charge Bearer	<p>SEPA Usage Rule(s) Only "SLEV" is allowed.</p> <p>ISO Name</p> <p>ISO Definition Charge Bearer Specifies which party/parties will bear the charges associated with the processing of the payment transaction.</p> <p>Usage: The ChargeBearer applies to the return message, not to the original instruction. ChrgBr</p> <p>XML Tag</p> <p>Type ChargeBearerType1Code</p> <p>SEPA Code Restrictions</p> <p>SLEV FollowingServiceLevel Charges are to be applied following the rules agreed in the service level and/or scheme.</p>
3.21	0..1	Payment Return V09 +Transaction Information ++Charges Information	<p>SEPA Usage Rule(s) Only one occurrence is allowed.</p> <p>ISO Name</p> <p>ISO Definition Charges Information Provides information on the charges to be paid by the charge bearer(s) related to the processing of the return transaction.</p> <p>XML Tag</p> <p>Type ChrgsInf</p> <p>Charges7</p>

#	SEPA Mult	Message Element	Inter-PSP Positive Response to RFRO SEPA Core Requirements	
3.22	1..1	Payment Return V09 +Transaction Information ++Charges Information +++Amount	<p>SEPA Rulebook <i>AT-R075 Fee for the positive response to the Request for Recall by the Originator in euro.</i></p> <p>SEPA Usage Rule(s) <i>Only 'EUR' is allowed.</i></p> <p>Amount <i>Amount must be 0.01 or more and 99999999.99 or less.</i></p> <p>SEPA Format Rule(s)</p> <p>ISO Name</p> <p>ISO Definition <i>Transaction charges to be paid by the charge bearer.</i></p> <p>XML Tag Type</p> <p>SEPA FractDigits <i>2</i></p> <p>TotalDigits <i>18</i></p> <p>SEPA Inclusive <i>0.01 .. 99999999.99</i></p>	
3.23	1..1	Payment Return V09 +Transaction Information ++Charges Information +++Agent	<p>ISO Name</p> <p>ISO Definition <i>Agent that takes the transaction charges or to which the transaction charges are due.</i></p> <p>XML Tag Type</p>	<p>Agent</p> <p>Agt <i>BranchAndFinancialInstitutionIdentification6</i></p>
3.24	1..1	Payment Return V09 +Transaction Information ++Charges Information +++Agent ++++Financial Institution Identification	<p>SEPA Rulebook <i>AT-C002 The BIC code of the Beneficiary PSP.</i></p> <p>SEPA Usage Rule(s) <i>Only 'BICFI' is allowed.</i></p> <p>ISO Name</p> <p>ISO Definition <i>Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.</i></p> <p>XML Tag Type</p>	<p>BIC <i>FinInstnId</i></p> <p>Financial Institution Identification18</p>
3.25	0..1	Payment Return V09 +Transaction Information ++Charges Information +++Agent ++++Branch Identification	<p>ISO Name</p> <p>ISO Definition <i>Identifies a specific branch of a financial institution.</i></p> <p>XML Tag Type</p>	<p>Branch Identification</p> <p>Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.</p> <p>BrnchId</p> <p>BranchData3</p>
3.26	0..1	Payment Return V09 +Transaction Information ++Clearing System Reference	<p>ISO Name</p> <p>ISO Definition <i>Unique reference, as assigned by the clearing system, to unambiguously identify the return instruction.</i></p> <p>XML Tag Type</p> <p>ISO Length <i>1 .. 35</i></p> <p>SEPA Length <i>1 .. 35</i></p>	<p>Clearing System Reference</p> <p>ClrSysRef</p> <p>Max35Text</p>
3.27	0..1	Payment Return V09 +Transaction Information ++Instructing Agent	<p>SEPA Usage Rule(s) <i>Only 'BICFI' is allowed.</i></p> <p>ISO Name</p> <p>ISO Definition <i>Agent that instructs the next party in the chain to carry out the (set of) instruction(s).</i></p> <p>XML Tag Type</p>	<p>Instructing Agent</p> <p>InstgAgt</p> <p>BranchAndFinancialInstitutionIdentification6</p> <p>Usage: The instructing agent is the party sending the return message and not the party that sent the original instruction that is being returned.</p>

#	SEPA Mult	Message Element	Inter-PSP Positive Response to RFRO SEPA Core Requirements		
3.28	0..1	Payment Return V09 +Transaction Information ++Instructed Agent	<i>SEPA Usage Rule(s)</i> Only 'BICFI' is allowed. ISO Name Instructed Agent ISO Definition Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s).	Usage: The instructed agent is the party receiving the return message and not the party that received the original instruction that is being returned. XML Tag Type InstdAgt BranchAndFinancialInstitutionIdentification6	
3.29	0..1	Payment Return V09 +Transaction Information ++Return Chain	ISO Name ISO Definition XML Tag Type	Return Chain Provides all parties (agents and non-agents) involved in a return transaction. RtrChain TransactionParties7	
3.30	1..1	Payment Return V09 +Transaction Information ++Return Reason Information	<i>SEPA Usage Rule(s)</i> Mandatory. <i>Only one occurrence of 'Return Reason Information' is allowed.</i> ISO Name ISO Definition XML Tag Type	Return Reason Information Provides detailed information on the return reason. RtrRsnInf PaymentReturnReason6	
3.31	1..1	Payment Return V09 +Transaction Information ++Return Reason Information +++Originator	<i>SEPA Rulebook</i> <i>AT-R002 The Identification of the type of party initiating the "R" message</i> <i>SEPA Usage Rule(s)</i> Mandatory. <i>Only 'Name' is allowed.</i> <i>'Name' is limited to 70 characters in length.</i> ISO Name ISO Definition XML Tag Type	Originator Party that issues the return. Orgtr PartyIdentification135	
3.32	1..1	Payment Return V09 +Transaction Information ++Return Reason Information +++Reason	<i>SEPA Usage Rule(s)</i> Mandatory. ISO Name Reason ISO Definition Specifies the reason for the return. XML Tag Type Rsn ReturnReason5Choice		
	1..1		XML Tag	xs:choice	
3.33	1..1	Payment Return V09 +Transaction Information ++Return Reason Information +++Reason ++++Code	<i>SEPA Usage Rule(s)</i> Only "FOCR" is allowed. ISO Name Code ISO Definition Reason for the return, as published in an external reason code list. XML Tag Type Cd ISO Length 1 .. 4 SEPA Length 1 .. 4	SEPA Code Restrictions FOCR FollowingCancellationRequest Return following a cancellation request	
3.34	1..1	Payment Return V09 +Transaction Information ++Return Reason Information +++Reason ++++Proprietary	ISO Name Proprietary ISO Definition Reason for the return, in a proprietary form. XML Tag Type Prtry ISO Length Max35Text SEPA Length 1 .. 35		

#	SEPA Mult	Message Element	Inter-PSP Positive Response to RFRO SEPA Core Requirements	
3.35	1..1	Payment Return V09 +Transaction Information ++Return Reason Information +++Additional Information	<p>SEPA Rulebook <i>AT-R072 The specific reference of the Originator PSP for the Request for Recall by the Originator.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i> <i>Only one occurrence starting with "ATR072/" followed by the information as per attribute description is allowed.</i></p> <p>ISO Name ISO Definition XML Tag Type ISO Length SEPA Length</p>	<i>Additional Information</i> <i>Further details on the return reason.</i> <i>AddtlInf</i> <i>Max105Text</i> <i>1 .. 105</i> <i>1 .. 105</i>
3.36	1..1	Payment Return V09 +Transaction Information ++Original Transaction Reference	<p>SEPA Rulebook <i>An exact copy of all attributes of the received DS-02 which is being returned.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory</i> <i>The message elements under 'Original Transaction Reference' must be populated with the same value as the message elements of the original instruction.</i></p> <p>ISO Name ISO Definition XML Tag Type</p>	<i>Original Transaction Reference</i> <i>Key elements used to identify the original transaction that is being referred to.</i> <i>OrgnlTxRef</i> <i>OriginalTransactionReference28</i>
3.37	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Interbank Settlement Amount	<p>ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits SEPA Inclusive</p>	<i>Interbank Settlement Amount</i> <i>Amount of money moved between the instructing agent and the instructed agent.</i> <i>IntrBkStlmtAmt</i> <i>ActiveOrHistoricCurrencyAndAmount</i> <i>5</i> <i>18</i> <i>0 ..</i>
3.38	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Amount	<p>ISO Name ISO Definition XML Tag Type</p>	<i>Amount</i> <i>Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.</i> <i>Amt</i> <i>AmountType4Choice</i>
3.39	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Interbank Settlement Date	<p>SEPA Rulebook <i>AT-T051 Settlement Date of the credit transfer.</i></p> <p>ISO Name ISO Definition XML Tag Type</p>	<i>Interbank Settlement Date</i> <i>Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.</i> <i>IntrBkStlmtDt</i> <i>ISODate</i>
3.40	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Requested Collection Date	<p>ISO Name ISO Definition XML Tag Type</p>	<i>Requested Collection Date</i> <i>Date and time at which the creditor requests that the amount of money is to be collected from the debtor.</i> <i>ReqdColltnDt</i> <i>ISODate</i>
3.41	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Requested Execution Date	<p>ISO Name ISO Definition XML Tag Type</p>	<i>Requested Execution Date</i> <i>Date at which the initiating party requests the clearing agent to process the payment.</i> <i>Usage:</i> This is the date on which the debtor's account is to be debited. If payment by cheque, the date when the cheque must be generated by the bank. <i>ReqdExctnDt</i> <i>DateAndDateTime2Choice</i>

#	SEPA Mult	Message Element	Inter-PSP Positive Response to RFRO SEPA Core Requirements	
3.42	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Creditor Scheme Identification	ISO Name ISO Definition XML Tag Type	Creditor Scheme Identification Credit party that signs the mandate. CdtrSchmeId PartyIdentification135
3.43	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Settlement Information	ISO Name ISO Definition XML Tag Type	Settlement Information Specifies the details on how the settlement of the original transaction(s) between the instructing agent and the instructed agent was completed. SttlmInf SettlementInstruction7
3.44	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Payment Type Information	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-T001 Identification code of the Scheme.</i> <i>AT-T008 Category purpose of the Credit Transfer.</i> <i>If the original transaction was sent according to Annex V (Use of Extended Remittance Information) of the SCT Rulebook (refer to section 'Inter-PSP payment with use of the Extended Remittance Information option' below), then 'Local Instrument/Code' must be populated with "PERI" (Payment with Extended Remittance Information).</i> Payment Type Information Set of elements used to further specify the type of transaction. PmtTpInf PaymentTypeInformation27
3.45	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Payment Method	ISO Name ISO Definition XML Tag Type	Payment Method Specifies the means of payment that will be used to move the amount of money. PmtMtd PaymentMethod4Code
3.46	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Mandate Related Information	ISO Name ISO Definition XML Tag Type	Mandate Related Information Provides further details of the mandate signed between the creditor and the debtor. MndtRltdInf MandateRelatedInformation14
3.47	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Remittance Information	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-T009 Remittance information or AT-T010 The unstructured Remittance Information sent by the Originator to the Beneficiary in the Credit Transfer Instruction (in case of use of the Extended Remittance Information (ERI) option in the original SEPA Credit Transfer, AT-T011 The structured Remittance Information sent by the Originator to the Beneficiary in the SEPA Credit Transfer Instruction, will NOT be transported here).</i> Remittance Information Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system. RmtInf RemittanceInformation16
3.48	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Ultimate Debtor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-P006 Name of the Originator Reference Party.</i> <i>AT-P007 Identification code of the Originator Reference Party.</i> <i>Only 'Party' is allowed.</i> Ultimate Debtor Ultimate party that owes an amount of money to the (ultimate) creditor. UltmtDbtr Party40Choice

#	SEPA Mult	Message Element	Inter-PSP Positive Response to RFRO SEPA Core Requirements	
3.49	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Debtor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-P001 Name of the Originator.</i> <i>AT-P005 Address of the Originator.</i> <i>AT-P004 Originator identification code.</i> <i>Only 'Party' is allowed.</i> Debtor Party that owes an amount of money to the (ultimate) creditor. Dbtr Party40Choice
3.50	1..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Debtor Account	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-D001 The IBAN of the account of the Originator.</i> <i>AT-P003 The Proxy/Alias of the account of the Originator.</i> Debtor Account Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction. DbtrAcct CashAccount38
3.51	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Debtor Agent	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-D002 The BIC code of the Originator PSP.</i> Debtor Agent Financial institution servicing an account for the debtor. DbtrAgt BranchAndFinancialInstitutionIdentification6
3.52	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Debtor Agent Account	ISO Name ISO Definition XML Tag Type	Debtor Agent Account Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain. DbtrAgtAcct CashAccount38
3.53	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Creditor Agent	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-C002 The BIC code of the Beneficiary PSP.</i> Creditor Agent Financial institution servicing an account for the creditor. CdtrAgt BranchAndFinancialInstitutionIdentification6
3.54	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Creditor Agent Account	ISO Name ISO Definition XML Tag Type	Creditor Agent Account Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction. CdtrAgtAcct CashAccount38
3.55	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Creditor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-E001 Name of the Beneficiary.</i> <i>AT-E004 Address of the Beneficiary.</i> <i>AT-E005 Beneficiary identification code.</i> <i>Only 'Party' is allowed.</i> Creditor Party to which an amount of money is due. Cdtr Party40Choice
3.56	1..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Creditor Account	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-C001 The IBAN of the account of the Beneficiary.</i> <i>AT-E003 The Proxy/Alias of the account of the Beneficiary.</i> Creditor Account Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction. CdtrAcct CashAccount38

#	SEPA Mult	Message Element	Inter-PSP Positive Response to RFRO SEPA Core Requirements	
3.57	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Ultimate Creditor	<p>SEPA Rulebook</p> <p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p><i>AT-E007 Name of the Beneficiary Reference Party.</i> <i>AT-E010 Identification code of the Beneficiary Reference Party.</i></p> <p>SEPA Usage Rule(s) Only 'Party' is allowed.</p> <p>ISO Name Ultimate Creditor</p> <p>ISO Definition Ultimate party to which an amount of money is due.</p> <p>XML Tag Type UltmtCdtr Party40Choice</p>
3.58	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Purpose	<p>SEPA Rulebook</p> <p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p><i>AT-T007 The purpose of the SEPA Credit Transfer</i></p> <p>ISO Name Purpose</p> <p>ISO Definition Underlying reason for the payment transaction.</p> <p>Usage: Purpose is used by the end customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain.</p> <p>XML Tag Type Purp Purpose2Choice</p>
3.59	0..n	Payment Return V09 +Transaction Information ++Supplementary Data	<p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p>Supplementary Data</p> <p>Additional information that cannot be captured in the structured elements and/or any other specific block.</p> <p>XML Tag Type SplmtryData SupplementaryData1</p>
4.0	0..n	Payment Return V09 +Supplementary Data	<p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p>Supplementary Data</p> <p>Additional information that cannot be captured in the structured elements and/or any other specific block.</p> <p>XML Tag Type SplmtryData SupplementaryData1</p>



2.11 Request for Status Update on a Request for Recall by the Originator

2.11.1 Use of FI To FI Payment Status Request (pacs.028.001.03)

This message is sent to the Beneficiary PSP in case the Originator PSP did not receive a response to a Request for Recall by the Originator, where the following applies:

- Index 3.3 'Original Instruction Identification' must be populated with the 'Cancellation Identification' (AT-R072) of the related camt.056 transaction information.

In an SCT context, the message caters for a single or group status request.

Note: The use case of the message is implied by the 'Message Name', 'pacs.028.001.03', the 'Original Message Name Identification' must begin with camt.056 (the addition of a variant number and version number is optional) and the population of index 3.3 'Original Instruction Identification'.

Note: Message elements under 'Original Transaction Reference' are based on DS-02 attributes.

#	SEPA Mult	Message Element	Request for Status Update on a RFRO SEPA Core Requirements	
		Document	XML Tag Type	Document Document
	1..1	FITo FIPayment Status Request V03	ISO Name ISO Definition	FITo FIPayment Status Request V03 The FinancialInstitutionToFinancialInstitutionPaymentStatusRequest message is sent by the debtor agent to the creditor agent, directly or through other agents and/or a payment clearing and settlement system. It is used to request a FIToFIPaymentStatusReport message containing information on the status of a previously sent instruction.
			XML Tag Type	FIToFIPmtStsReq FIToFIPaymentStatusRequestV03
1.0	1..1	FITo FIPayment Status Request V03 +Group Header	ISO Name ISO Definition	Group Header Set of characteristics shared by all individual transactions included in the status request message.
			XML Tag Type	GrpHdr GroupHeader91
1.1	1..1	FITo FIPayment Status Request V03 +Group Header ++Message Identification	ISO Name ISO Definition	Message Identification Point to point reference, as assigned by the instructing party, and sent to the next party in the chain to unambiguously identify the message. Usage: The instructing party has to make sure that MessageIdentification is unique per instructed party for a pre-agreed period.
			XML Tag Type ISO Length SEPA Length	MsgId Max35Text 1 .. 35 1 .. 35
1.2	1..1	FITo FIPayment Status Request V03 +Group Header ++Creation Date Time	ISO Name ISO Definition	Creation Date Time Date and time at which the message was created.
			XML Tag Type	CreDtTm ISODateTime
1.3	0..1	FITo FIPayment Status Request V03 +Group Header ++Instructing Agent	SEPA Usage Rule(s) ISO Name ISO Definition	Only 'BICFI' is allowed. Instructing Agent Agent that instructs the next party in the chain to carry out the (set of) instruction(s). Usage: The instructing agent is the party sending the status message and not the party that sent the original instruction that is being reported on.
			XML Tag Type	InstgAgt BranchAndFinancialInstitutionIdentification6
1.4	0..1	FITo FIPayment Status Request V03 +Group Header ++Instructed Agent	SEPA Usage Rule(s) ISO Name ISO Definition	Only 'BICFI' is allowed. Instructed Agent Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s). Usage: The instructed agent is the party receiving the status message and not the party that received the original instruction that is being reported on.
			XML Tag Type	InstdAgt BranchAndFinancialInstitutionIdentification6
2.0	1..1	FITo FIPayment Status Request V03 +Original Group Information	SEPA Usage Rule(s) ISO Name ISO Definition	Mandatory. Only one occurrence is allowed. Original Group Information Original group information concerning the group of transactions, to which the status request message refers to.
			XML Tag Type	OrgnlGrpInf OriginalGroupInformation27

#	SEPA Mult	Message Element	Request for Status Update on a RFRO SEPA Core Requirements		
2.1	1..1	FITo FIPayment Status Request V03 +Original Group Information ++Original Message Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Message Identification Point to point reference, as assigned by the original instructing party, to unambiguously identify the original message. OrgnlMsgId Max35Text 1 .. 35 1 .. 35	
2.2	1..1	FITo FIPayment Status Request V03 +Original Group Information ++Original Message Name Identification	SEPA Usage Rule(s) <i>Must begin with 'camt.056'. The addition of a variant number and version number is optional</i> ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Message Name Identification Specifies the original message name identifier to which the message refers. OrgnlMsgNmId Max35Text 1 .. 35 1 .. 35	
2.3	0..1	FITo FIPayment Status Request V03 +Original Group Information ++Original Creation Date Time	ISO Name ISO Definition XML Tag Type	Original Creation Date Time Date and time at which the original message was created. OrgnlCreDtTm ISODATETIME	
2.4	0..1	FITo FIPayment Status Request V03 +Original Group Information ++Original Number Of Transactions	ISO Name ISO Definition XML Tag Type Pattern	Original Number Of Transactions Number of individual transactions contained in the original message. OrgnlNbOfTxns Max15NumericText [0-9]{1,15}	
2.5	0..1	FITo FIPayment Status Request V03 +Original Group Information ++Original Control Sum	ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits	Original Control Sum Total of all individual amounts included in the original message, irrespective of currencies. OrgnlCtrlSum DecimalNumber 17 18	
3.0	1..n	FITo FIPayment Status Request V03 +Transaction Information	SEPA Usage Rule(s) <i>Mandatory.</i> ISO Name ISO Definition XML Tag Type	<i>Mandatory.</i> Transaction Information Information concerning the original transaction, to which the status request message refers. TxInf PaymentTransaction113	
3.1	1..1	FITo FIPayment Status Request V03 +Transaction Information ++Status Request Identification	SEPA Usage Rule(s) <i>Mandatory. This ID must be forwarded to the Beneficiary PSP (and therefore it is not a point-to-point reference).</i> ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Status Request Identification Unique identification, as assigned by an instructing party for an instructed party, to unambiguously identify the status request. Usage: The instructing party is the party sending the request message and not the party that sent the original instruction that is being reported on. StsReqId Max35Text 1 .. 35 1 .. 35	
3.2	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Group Information	ISO Name ISO Definition XML Tag Type	Original Group Information Point to point reference, as assigned by the original instructing party, to unambiguously identify the original message. OrgnlGrpInf OriginalGroupInformation29	

#	SEPA Mult	Message Element	Request for Status Update on a RFRO SEPA Core Requirements	
3.3	1..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Instruction Identification	<p>SEPA Usage Rule(s) <i>Mandatory.</i> <i>Must be populated with the cancellation ID (AT-R072) of the related camt.056 'Transaction Information'.</i></p> <p>ISO Name ISO Definition</p> <p>XML Tag Type ISO Length SEPA Length</p>	
3.4	1..1	FITo FIPayment Status Request V03 +Transaction Information ++Original End To End Identification	<p>SEPA Rulebook <i>AT-T014 The Originator's reference of the SEPA Credit Transfer Transaction.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name ISO Definition</p> <p>XML Tag Type ISO Length SEPA Length</p>	
3.5	1..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Identification	<p>SEPA Rulebook <i>AT-T054 The Originator PSP's reference of the SEPA Credit Transfer Transaction.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name ISO Definition</p> <p>XML Tag Type ISO Length SEPA Length</p>	
3.6	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original UETR	<p>ISO Name ISO Definition</p> <p>XML Tag Type Pattern</p>	Original UETR Universally unique identifier to provide the original end-to-end reference of a payment transaction. OrgnlUETR UUIDv4Identifier [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}
3.7	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Acceptance Date Time	<p>ISO Name ISO Definition</p> <p>XML Tag Type</p>	Acceptance Date Time Point in time when the payment order from the initiating party meets the processing conditions of the account servicing agent. This means that the account servicing agent has received the payment order and has applied checks such as authorisation, availability of funds. AcptncDtTm ISODateTime
3.8	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Clearing System Reference	<p>ISO Name ISO Definition</p> <p>XML Tag Type ISO Length SEPA Length</p>	Clearing System Reference Unique reference, as assigned by a clearing system, to unambiguously identify the instruction. ClrSysRef Max35Text 1 .. 35 1 .. 35

#	SEPA Mult	Message Element	Request for Status Update on a RFRO SEPA Core Requirements		
3.9	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Instructing Agent	ISO Name ISO Definition XML Tag Type	Instructing Agent Agent that instructs the next party in the chain to carry out the (set of) instruction(s). InstgAgt BranchAndFinancialInstitutionIdentification6	
3.10	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Instructed Agent	ISO Name ISO Definition XML Tag Type	Instructed Agent Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s). InstdAgt BranchAndFinancialInstitutionIdentification6	
3.11	1..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference	SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type	The message elements under 'Original Transaction Reference' must be populated with the same value as the message elements of the original instruction. Original Transaction Reference Key elements used to identify the original transaction that is being referred to. OrgnlTxRef OriginalTransactionReference28	
3.12	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Interbank Settlement Amount	SEPA Rulebook ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits SEPA Inclusive	AT-T002 Amount of the SEPA Credit Transfer in Euro. Interbank Settlement Amount Amount of money moved between the instructing agent and the instructed agent. IntrBkSttlmAmt ActiveOrHistoricCurrencyAndAmount 2 18 0.01 .. 999999999.9	
3.13	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Amount	ISO Name ISO Definition XML Tag Type	Amount Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party. Amt AmountType4Choice	
3.14	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Interbank Settlement Date	SEPA Rulebook ISO Name ISO Definition XML Tag Type	AT-T051 The Settlement Date of the credit transfer. Interbank Settlement Date Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. IntrBkSttlmDt ISODate	
3.15	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Requested Collection Date	ISO Name ISO Definition XML Tag Type	Requested Collection Date Date and time at which the creditor requests that the amount of money is to be collected from the debtor. ReqdColltnDt ISODate	
3.16	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Requested Execution Date	ISO Name ISO Definition XML Tag Type	Requested Execution Date Date at which the initiating party requests the clearing agent to process the payment. Usage: This is the date on which the debtor's account is to be debited. If payment by cheque, the date when the cheque must be generated by the bank. ReqdExctnDt DateAndDateTime2Choice	

#	SEPA Mult	Message Element	Request for Status Update on a RFRO SEPA Core Requirements	
3.17	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Creditor Scheme Identification	ISO Name ISO Definition XML Tag Type	Creditor Scheme Identification Credit party that signs the mandate. CdtrSchmeId PartyIdentification135
3.18	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Settlement Information	ISO Name ISO Definition XML Tag Type	Settlement Information Specifies the details on how the settlement of the original transaction(s) between the instructing agent and the instructed agent was completed. SttlmInf SettlementInstruction7
3.19	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Payment Type Information	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-T008 The category purpose of the credit transfer.</i> <i>AT-T001 The identification code of the Scheme. If the original transaction was sent according to Annex V (Use of Extended Remittance Information) of the SCT Rulebook (refer to section 'Inter-PSP payment with use of the Extended Remittance Information option' below), then 'Local Instrument/Code' must be populated with "PERI" (Payment with Extended Remittance Information).</i> Payment Type Information Set of elements used to further specify the type of transaction. PmtTpInf PaymentTypeInformation27
3.20	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Payment Method	ISO Name ISO Definition XML Tag Type	Payment Method Specifies the means of payment that will be used to move the amount of money. PmtMtd PaymentMethod4Code
3.21	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Mandate Related Information	ISO Name ISO Definition XML Tag Type	Mandate Related Information Provides further details of the mandate signed between the creditor and the debtor. MndtRltdInf MandateRelatedInformation14
3.22	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Remittance Information	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-T009 The Remittance Information sent by the Originator to the Beneficiary in the Credit Transfer Instruction or AT-T010 The unstructured Remittance Information sent by the Originator to the Beneficiary in the Credit Transfer Instruction (in case of use of the Extended Remittance Information (ERI) option in the original SEPA Credit Transfer, AT-T011 The structured Remittance Information sent by the Originator to the Beneficiary in the SEPA Credit Transfer Instruction, will NOT be transported here.</i> Remittance Information Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system. RmtInf RemittanceInformation16

#	SEPA Mult	Message Element	Request for Status Update on a RFRO SEPA Core Requirements	
3.23	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Ultimate Debtor	<p>SEPA Rulebook</p> <p>SEPA Usage Rule(s) Only 'Party' is allowed.</p> <p>ISO Name Ultimate Debtor</p> <p>ISO Definition Ultimate party that owes an amount of money to the (ultimate) creditor.</p> <p>XML Tag Type UltmtDbtr Party40Choice</p>	<p><i>AT-P006 The name of the Originator Reference Party.</i></p> <p><i>AT-P007 The identification code of the Originator Reference Party.</i></p>
3.24	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Debtor	<p>SEPA Rulebook</p> <p>SEPA Usage Rule(s) Only 'Party' is allowed.</p> <p>ISO Name Debtor</p> <p>ISO Definition Party that owes an amount of money to the (ultimate) creditor.</p> <p>XML Tag Type Dbtr Party40Choice</p>	<p><i>AT-P001 The name of the Originator.</i></p> <p><i>AT-P005 The address of the Originator.</i></p> <p><i>AT-P004 The Originator identification code.</i></p>
3.25	1..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Debtor Account	<p>SEPA Rulebook</p> <p>ISO Name Debtor Account</p> <p>ISO Definition Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction.</p> <p>XML Tag Type DbtrAcct CashAccount38</p>	<p><i>AT-D001 The IBAN of the account of the Originator.</i></p> <p><i>AT-P003 The Proxy/Alias of the account of the Originator.</i></p>
3.26	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Debtor Agent	<p>SEPA Rulebook</p> <p>ISO Name Debtor Agent</p> <p>ISO Definition Financial institution servicing an account for the debtor.</p> <p>XML Tag Type DbtrAgt BranchAndFinancialInstitutionIdentification6</p>	<p><i>AT-D002 The BIC code of the Originator PSP.</i></p>
3.27	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Debtor Agent Account	<p>ISO Name Debtor Agent Account</p> <p>ISO Definition Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain.</p> <p>XML Tag Type DbtrAgtAcct CashAccount38</p>	
3.28	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Creditor Agent	<p>SEPA Rulebook</p> <p>ISO Name Creditor Agent</p> <p>ISO Definition Financial institution servicing an account for the creditor.</p> <p>XML Tag Type CdtrAgt BranchAndFinancialInstitutionIdentification6</p>	<p><i>AT-C002 The BIC code of the Beneficiary PSP</i></p>
3.29	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Creditor Agent Account	<p>ISO Name Creditor Agent Account</p> <p>ISO Definition Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction.</p> <p>XML Tag Type CdtrAgtAcct CashAccount38</p>	
3.30	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Creditor	<p>SEPA Rulebook</p> <p>SEPA Usage Rule(s) Only 'Party' is allowed.</p> <p>ISO Name Creditor</p> <p>ISO Definition Party to which an amount of money is due.</p> <p>XML Tag Type Cdtr Party40Choice</p>	<p><i>AT-E001 The name of the Beneficiary.</i></p> <p><i>AT-E004 The address of the Beneficiary.</i></p> <p><i>AT-E005 The Beneficiary identification code.</i></p>

#	SEPA Mult	Message Element	Request for Status Update on a RFRO SEPA Core Requirements	
3.31	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Creditor Account	<p>SEPA Rulebook</p> <p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p><i>AT-C001 The IBAN of the account of the Beneficiary.</i></p> <p><i>AT-E003 The Proxy/Alias of the account of the Beneficiary.</i></p> <p>Creditor Account</p> <p>Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction.</p> <p>CdtrAcct</p> <p>CashAccount38</p>
3.32	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Ultimate Creditor	<p>SEPA Rulebook</p> <p>SEPA Usage Rule(s)</p> <p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p><i>AT-E007 The name of the Beneficiary Reference Party.</i></p> <p><i>AT-E010 The identification code of the Beneficiary Reference Party.</i></p> <p><i>Only 'Party' is allowed.</i></p> <p>Ultimate Creditor</p> <p>Ultimate party to which an amount of money is due.</p> <p>UltmtCdtr</p> <p>Party40Choice</p>
3.33	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Purpose	<p>SEPA Rulebook</p> <p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p><i>AT-T007 The purpose of the SEPA Credit Transfer.</i></p> <p>Purpose</p> <p>Underlying reason for the payment transaction.</p> <p>Usage:</p> <p>Purpose is used by the end customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain.</p> <p>Purp</p> <p>Purpose2Choice</p>
3.34	0..n	FITo FIPayment Status Request V03 +Transaction Information ++Supplementary Data	<p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p>Supplementary Data</p> <p>Additional information that cannot be captured in the structured elements and/or any other specific block.</p> <p>SplmtryData</p> <p>SupplementaryData1</p>
4.0	0..n	FITo FIPayment Status Request V03 +Supplementary Data	<p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p>Supplementary Data</p> <p>Additional information that cannot be captured in the structured elements and/or any other specific block.</p> <p>SplmtryData</p> <p>SupplementaryData1</p>



2.12 Inter-PSP SCT Inquiry Dataset (DS-09) for Claim Non-Receipt

2.12.1 Use of Claim Non-Receipt (camt.027.001.07)

This message is used to transport the Claim Non-Receipt from the Originator PSP to the Beneficiary PSP, directly or through intermediaries.

The message caters also for Claim Non-Receipt inquiries of SEPA Credit Transfers with Extended Remittance Information (ERI, please refer to section 'Inter-PSP payment with use of the Extended Remittance Information option' below) whereby only AT-T010 'The unstructured Remittance Information sent by the Originator to the Beneficiary in the SEPA Credit Transfer Instruction' will be forwarded.

The message caters for a single claim only.

Note: Attribute AT-Q001 'SCT inquiry reason code' is implied by the 'Message Name', 'camt.027.001.07' and the Original Message Name Identification must begin with pacs.008 (the addition of a variant number and version number is optional).

Note: Message elements under 'Original Transaction Reference' sequence are based on DS-02 attributes.

#	SEPA Mult	Message Element	Inter-PSP Inquiry for Claim Non-Receipt SEPA Core Requirements	
		Document	XML Tag Type	Document Document
0	1..1	Claim Non Receipt V07	ISO Name ISO Definition XML Tag Type	Claim Non Receipt V07 The Claim Non Receipt message is sent by a case creator/case assigner to a case assignee. This message is used to initiate an investigation for missing funds at the creditor (missing credit entry to its account) or at an agent along the processing chain (missing cover for a received payment instruction). ClmNonRct ClaimNonReceiptV07
1.0	1..1	Claim Non Receipt V07 +Assignment	ISO Name ISO Definition XML Tag Type	Assignment Identifies the assignment of an investigation case from an assigner to an assignee. Usage: The assigner must be the sender of this confirmation and the assignee must be the receiver. Assgnmt CaseAssignment5
1.1	1..1	Claim Non Receipt V07 +Assignment ++Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Identification Uniquely identifies the case assignment. Id Max35Text 1 .. 35 1 .. 35
1.2	1..1	Claim Non Receipt V07 +Assignment ++Assigner	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Instructing Party. Limited to 'BICFI' to identify a PSP, 'AnyBIC' to identify a CSM or 'LEI' or 'Name' to indicate a CSM when it has no BIC. 'Name' is limited to 70 characters in length. Assigner Party who assigns the case. Usage: This is also the sender of the message. Assgnr Party40Choice
1.3	1..1	Claim Non Receipt V07 +Assignment ++Assignee	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Instructed Party. Limited to 'BICFI' to identify a PSP, 'AnyBIC' to identify a CSM or 'LEI' or 'Name' to indicate a CSM when it has no BIC. 'Name' is limited to 70 characters in length. Assignee Party to which the case is assigned. Usage: This is also the receiver of the message. Assgne Party40Choice
1.4	1..1	Claim Non Receipt V07 +Assignment ++Creation Date Time	ISO Name ISO Definition XML Tag Type	Creation Date Time Date and time at which the assignment was created. CreDtTm ISODateTime
2.0	1..1	Claim Non Receipt V07 +Case	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Mandatory. Case Identifies the investigation case. Case Case5

#	SEPA Mult	Message Element	Inter-PSP Inquiry for Claim Non-Receipt SEPA Core Requirements	
2.1	1..1	Claim Non Receipt V07 +Case ++Identification	SEPA Rulebook ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>AT-Q002 The specific SCT inquiry reference of the Participant initiating the SCT inquiry.</i> Identification Uniquely identifies the case. Id Max35Text 1 .. 35 1 .. 35
2.2	1..1	Claim Non Receipt V07 +Case ++Creator	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>Limited to 'BICFI' to identify the Originator PSP of the original credit transfer.</i> <i>Only 'Agent' is allowed.</i> Creator Party that created the investigation case. Cret Party40Choice
2.3	0..1	Claim Non Receipt V07 +Case ++Reopen Case Indication	ISO Name ISO Definition XML Tag Type	Reopen Case Indication Indicates whether or not the case was previously closed and is now re-opened. ReopCaseIndctn YesNoIndicator
3.0	1..1	Claim Non Receipt V07 +Underlying	ISO Name ISO Definition XML Tag Type	Underlying Identifies the payment instruction for which the Creditor has not received the funds. Usage: In case of a missing cover, it must be the identification of the related payment instruction. In case of a claim non receipt initiated by the debtor, it must be the identification of the instruction. Undrlyg UnderlyingTransaction5Choice
	1..1		XML Tag	xs:choice
3.1	1..1	Claim Non Receipt V07 +Underlying ++Initiation	ISO Name ISO Definition XML Tag Type	Initiation Set of elements used to reference the details of the original payment initiation. Initn UnderlyingPaymentInstruction5
3.2	1..1	Claim Non Receipt V07 +Underlying ++Interbank	ISO Name ISO Definition XML Tag Type	Interbank Set of elements used to reference the details of the original interbank payment transaction. IntrBk UnderlyingPaymentTransaction4
3.3	1..1	Claim Non Receipt V07 +Underlying ++Interbank +++Original Group Information	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>Mandatory.</i> Original Group Information Set of elements used to provide information on the original message. OrgnlGrpInf UnderlyingGroupInformation1
3.4	1..1	Claim Non Receipt V07 +Underlying ++Interbank +++Original Group Information ++++Original Message Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Message Identification Point to point reference, as assigned by the original instructing party, to unambiguously identify the original message. OrgnlMsgId Max35Text 1 .. 35 1 .. 35

#	SEPA Mult	Message Element	Inter-PSP Inquiry for Claim Non-Receipt SEPA Core Requirements			
3.5	1..1	Claim Non Receipt V07 +Underlying ++Interbank +++Original Group Information ++++Original Message Name Identification	<p>SEPA Usage Rule(s) Must begin with 'pacs.008'. The addition of a variant number and version number is optional.</p> <p>ISO Name ISO Definition Original Message Name Identification Specifies the original message name identifier to which the message refers.</p> <p>XML Tag Type ISO Length SEPA Length OrgnlMsgNmId Max35Text 1 .. 35 1 .. 35</p>			
3.6	0..1	Claim Non Receipt V07 +Underlying ++Interbank +++Original Group Information ++++Original Creation Date Time	<p>ISO Name ISO Definition Original Creation Date Time Date and time at which the original message was created.</p> <p>XML Tag Type OrgnlCreDtTm ISODATETIME</p>			
3.7	0..1	Claim Non Receipt V07 +Underlying ++Interbank +++Original Group Information ++++Original Message Delivery Channel	<p>ISO Name ISO Definition Original Message Delivery Channel Original channel used for the delivery of the message, to allow the receiver of the request to locate the payment with greater ease.</p> <p>XML Tag Type ISO Length SEPA Length OrgnlMsgDlvryChnl Max35Text 1 .. 35 1 .. 35</p>			
3.8	0..1	Claim Non Receipt V07 +Underlying ++Interbank +++Original Instruction Identification	<p>ISO Name ISO Definition Original Instruction Identification Unique identification, as assigned by the original instructing party for the original instructed party, to unambiguously identify the original instruction.</p> <p>XML Tag Type ISO Length SEPA Length OrgnlInstrId Max35Text 1 .. 35 1 .. 35</p>			
3.9	1..1	Claim Non Receipt V07 +Underlying ++Interbank +++Original End To End Identification	<p>SEPA Rulebook AT-T014 The Originator's reference of the SEPA Credit Transfer Transaction. SEPA Usage Rule(s) Mandatory.</p> <p>ISO Name ISO Definition Original End To End Identification Unique identification, as assigned by the original initiating party, to unambiguously identify the original transaction.</p> <p>XML Tag Type ISO Length SEPA Length OrgnlEndToEndId Max35Text 1 .. 35 1 .. 35</p>			
3.10	1..1	Claim Non Receipt V07 +Underlying ++Interbank +++Original Transaction Identification	<p>SEPA Rulebook AT-T054 The Originator PSP's reference of the SEPA Credit Transfer Transaction. SEPA Usage Rule(s) Mandatory.</p> <p>ISO Name ISO Definition Original Transaction Identification Unique identification, as assigned by the original first instructing agent, to unambiguously identify the transaction.</p> <p>XML Tag Type ISO Length SEPA Length OrgnlTxId Max35Text 1 .. 35 1 .. 35</p>			
3.11	0..1	Claim Non Receipt V07 +Underlying ++Interbank +++Original UETR	<p>ISO Name ISO Definition Original UETR Universally unique identifier to provide the original end-to-end reference of a payment transaction.</p> <p>XML Tag Type Pattern OrgnlUETR UUIDv4Identifier [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}</p>			

#	SEPA Mult	Message Element	Inter-PSP Inquiry for Claim Non-Receipt SEPA Core Requirements	
3.12	1..1	Claim Non Receipt V07 +Underlying ++Interbank +++Original Interbank Settlement Amount	<p>SEPA Rulebook <i>AT-T002 Amount of the SEPA Credit Transfer in Euro.</i></p> <p>SEPA Usage Rule(s) <i>Only 'EUR' is allowed.</i> <i>Amount must be 0.01 or more and 999999999.99 or less.</i> <i>The fractional part has a maximum of two digits.</i></p> <p>SEPA Format Rule(s)</p> <p>ISO Name</p> <p>ISO Definition Original Interbank Settlement Amount Amount of money moved between the instructing agent and the instructed agent, as provided in the original instruction.</p> <p>XML Tag</p> <p>Type</p> <p>SEPA FractDigits 2</p> <p>TotalDigits 18</p> <p>SEPA Inclusive 0.01 .. 999999999.99</p>	
3.13	1..1	Claim Non Receipt V07 +Underlying ++Interbank +++Original Interbank Settlement Date	<p>SEPA Rulebook <i>AT-T051 Settlement Date of the Credit Transfer.</i></p> <p>ISO Name</p> <p>ISO Definition Original Interbank Settlement Date Date, as provided in the original transaction, on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.</p> <p>XML Tag</p> <p>Type</p> <p>ISODate OrgnlIntrBkStlmtDt</p>	
3.14	1..1	Claim Non Receipt V07 +Underlying ++Interbank +++Original Transaction Reference	<p>SEPA Rulebook <i>An exact copy of all attributes of DS-02 of the initially sent pacs.008 to which the claim relates.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i> <i>The message elements under 'Original Transaction Reference' must be populated with the same value as the message elements of the original instruction.</i></p> <p>ISO Name</p> <p>ISO Definition Original Transaction Reference Key elements used to identify the original transaction that is being referred to.</p> <p>XML Tag</p> <p>Type</p> <p>OrgnlTxRef OriginalTransactionReference28</p>	
3.15	0..1	Claim Non Receipt V07 +Underlying ++Interbank +++Original Transaction Reference ++++Interbank Settlement Amount	<p>ISO Name</p> <p>ISO Definition Interbank Settlement Amount Amount of money moved between the instructing agent and the instructed agent.</p> <p>XML Tag</p> <p>Type</p> <p>SEPA FractDigits 5</p> <p>TotalDigits 18</p> <p>SEPA Inclusive 0 ..</p>	
3.16	0..1	Claim Non Receipt V07 +Underlying ++Interbank +++Original Transaction Reference ++++Amount	<p>ISO Name</p> <p>ISO Definition Amount Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.</p> <p>XML Tag</p> <p>Type</p> <p>Amt</p> <p>AmountType4Choice</p>	
3.17	0..1	Claim Non Receipt V07 +Underlying ++Interbank +++Original Transaction Reference ++++Interbank Settlement Date	<p>ISO Name</p> <p>ISO Definition Interbank Settlement Date Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.</p> <p>XML Tag</p> <p>Type</p> <p>IntrBkStlmtDt</p> <p>ISODate</p>	

#	SEPA Mult	Message Element	Inter-PSP Inquiry for Claim Non-Receipt SEPA Core Requirements	
3.18	0..1	Claim Non Receipt V07 +Underlying ++Interbank +++Original Transaction Reference ++++Requested Collection Date	ISO Name ISO Definition XML Tag Type	Requested Collection Date Date and time at which the creditor requests that the amount of money is to be collected from the debtor. ReqdColltnDt ISODate
3.19	0..1	Claim Non Receipt V07 +Underlying ++Interbank +++Original Transaction Reference ++++Requested Execution Date	ISO Name ISO Definition XML Tag Type	Requested Execution Date Date at which the initiating party requests the clearing agent to process the payment. Usage: This is the date on which the debtor's account is to be debited. If payment by cheque, the date when the cheque must be generated by the bank. ReqdExctnDt DateAndDateTime2Choice
3.20	0..1	Claim Non Receipt V07 +Underlying ++Interbank +++Original Transaction Reference ++++Creditor Scheme Identification	ISO Name ISO Definition XML Tag Type	Creditor Scheme Identification Credit party that signs the mandate. CdtrSchmeId PartyIdentification135
3.21	0..1	Claim Non Receipt V07 +Underlying ++Interbank +++Original Transaction Reference ++++Settlement Information	ISO Name ISO Definition XML Tag Type	Settlement Information Specifies the details on how the settlement of the original transaction(s) between the instructing agent and the instructed agent was completed. SttlmInf SettlementInstruction7
3.22	0..1	Claim Non Receipt V07 +Underlying ++Interbank +++Original Transaction Reference ++++Payment Type Information	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-T001 Identification code of the Scheme.</i> <i>AT-T008 Category Purpose of the Credit Transfer.</i> <i>If the original transaction was sent according to Annex V (Use of Extended Remittance Information) of the SCT Rulebook (refer to section 'Inter-PSP payment with use of the Extended Remittance Information option' below), then 'Local Instrument/Code' must be populated with "PERI" (Payment with Extended Remittance Information).</i> Payment Type Information Set of elements used to further specify the type of transaction. PmtTpInf PaymentTypeInformation27
3.23	0..1	Claim Non Receipt V07 +Underlying ++Interbank +++Original Transaction Reference ++++Payment Method	ISO Name ISO Definition XML Tag Type	Payment Method Specifies the means of payment that will be used to move the amount of money. PmtMtd PaymentMethod4Code
3.24	0..1	Claim Non Receipt V07 +Underlying ++Interbank +++Original Transaction Reference ++++Mandate Related Information	ISO Name ISO Definition XML Tag Type	Mandate Related Information Provides further details of the mandate signed between the creditor and the debtor. MndtRltdInf MandateRelatedInformation14

#	SEPA Mult	Message Element	Inter-PSP Inquiry for Claim Non-Receipt SEPA Core Requirements		
3.25	0..1	Claim Non Receipt V07 +Underlying ++Interbank +++Original Transaction Reference ++++Remittance Information	<p>SEPA Rulebook</p> <p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p><i>AT-T009 Remittance information or AT-T010 The unstructured Remittance Information sent by the Originator to the Beneficiary in the Credit Transfer Instruction (in case of use of the Extended Remittance Information (ERI) option in the original SEPA Credit Transfer, AT-T011 The structured Remittance Information sent by the Originator to the Beneficiary in the SEPA Credit Transfer Instruction, will NOT be transported here).</i></p> <p>Remittance Information</p> <p>Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system.</p> <p>RmtlInf</p> <p>RemittanceInformation16</p>	
3.26	0..1	Claim Non Receipt V07 +Underlying ++Interbank +++Original Transaction Reference ++++Ultimate Debtor	<p>SEPA Rulebook</p> <p>SEPA Usage Rule(s)</p> <p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p><i>AT-P006 The name of the Originator Reference Party.</i></p> <p><i>AT-P007 The identification code of the Originator Reference Party.</i></p> <p><i>Only 'Party' is allowed.</i></p> <p>Ultimate Debtor</p> <p>Ultimate party that owes an amount of money to the (ultimate) creditor.</p> <p>UltmtDbtr</p> <p>Party40Choice</p>	
3.27	0..1	Claim Non Receipt V07 +Underlying ++Interbank +++Original Transaction Reference ++++Debtor	<p>SEPA Rulebook</p> <p>SEPA Usage Rule(s)</p> <p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p><i>AT-P001 Name of the Originator.</i></p> <p><i>AT-P005 Address of the Originator.</i></p> <p><i>AT-P004 Originator's Identification Code.</i></p> <p><i>Only 'Party' is allowed.</i></p> <p>Debtor</p> <p>Party that owes an amount of money to the (ultimate) creditor.</p> <p>Dbtr</p> <p>Party40Choice</p>	
3.28	0..1	Claim Non Receipt V07 +Underlying ++Interbank +++Original Transaction Reference ++++Debtor Account	<p>SEPA Rulebook</p> <p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p><i>AT-D001 The IBAN of the account of the Originator.</i></p> <p><i>AT-P003 The Proxy/Alias of the account of the Originator.</i></p> <p>Debtor Account</p> <p>Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction.</p> <p>DbtrAcct</p> <p>CashAccount38</p>	
3.29	0..1	Claim Non Receipt V07 +Underlying ++Interbank +++Original Transaction Reference ++++Debtor Agent	<p>SEPA Rulebook</p> <p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p><i>AT-D002 The BIC code of the Originator PSP.</i></p> <p>Debtor Agent</p> <p>Financial institution servicing an account for the debtor.</p> <p>DbtrAgt</p> <p>BranchAndFinancialInstitutionIdentification6</p>	
3.30	0..1	Claim Non Receipt V07 +Underlying ++Interbank +++Original Transaction Reference ++++Debtor Agent Account	<p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p>Debtor Agent Account</p> <p>Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain.</p> <p>DbtrAgtAcct</p> <p>CashAccount38</p>	

#	SEPA Mult	Message Element	Inter-PSP Inquiry for Claim Non-Receipt SEPA Core Requirements	
3.31	0..1	Claim Non Receipt V07 +Underlying ++Interbank +++Original Transaction Reference ++++Creditor Agent	<i>SEPA Rulebook</i> <i>ISO Name</i> <i>ISO Definition</i> <i>XML Tag Type</i>	<i>AT-C002 The BIC code of the Beneficiary PSP.</i> Creditor Agent Financial institution servicing an account for the creditor. <i>CdtrAgt</i> BranchAndFinancialInstitutionIdentification6
3.32	0..1	Claim Non Receipt V07 +Underlying ++Interbank +++Original Transaction Reference ++++Creditor Agent Account	<i>ISO Name</i> <i>ISO Definition</i> <i>XML Tag Type</i>	Creditor Agent Account Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction. <i>CdtrAgtAcct</i> CashAccount38
3.33	0..1	Claim Non Receipt V07 +Underlying ++Interbank +++Original Transaction Reference ++++Creditor	<i>SEPA Rulebook</i> <i>SEPA Usage Rule(s)</i> Only 'Party' is allowed. <i>ISO Name</i> <i>ISO Definition</i> <i>XML Tag Type</i>	<i>AT-E001 Name of the Beneficiary.</i> <i>AT-E004 Address of the Beneficiary.</i> <i>AT-E005 Beneficiary Identification Code.</i> Creditor Party to which an amount of money is due. <i>Cdtr</i> Party40Choice
3.34	0..1	Claim Non Receipt V07 +Underlying ++Interbank +++Original Transaction Reference ++++Creditor Account	<i>SEPA Rulebook</i> <i>ISO Name</i> <i>ISO Definition</i> <i>XML Tag Type</i>	<i>AT-C001 The IBAN of the account of the Beneficiary.</i> <i>AT-E003 The Proxy/Alias of the account of the Beneficiary.</i> Creditor Account Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction. <i>CdtrAcct</i> CashAccount38
3.35	0..1	Claim Non Receipt V07 +Underlying ++Interbank +++Original Transaction Reference ++++Ultimate Creditor	<i>SEPA Rulebook</i> <i>SEPA Usage Rule(s)</i> Only 'Party' is allowed. <i>ISO Name</i> <i>ISO Definition</i> <i>XML Tag Type</i>	<i>AT-E007 The name of the Beneficiary Reference Party.</i> <i>AT-E010 The identification code of the Beneficiary Reference Party.</i> Ultimate Creditor Ultimate party to which an amount of money is due. <i>UltmtCdtr</i> Party40Choice
3.36	0..1	Claim Non Receipt V07 +Underlying ++Interbank +++Original Transaction Reference ++++Purpose	<i>SEPA Rulebook</i> <i>ISO Name</i> <i>ISO Definition</i> <i>XML Tag Type</i>	<i>AT-T007 The purpose of the SEPA Credit Transfer</i> Purpose Underlying reason for the payment transaction. Usage: Purpose is used by the end customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain. <i>Purp</i> Purpose2Choice
3.37	1..1	Claim Non Receipt V07 +Underlying ++Statement Entry	<i>ISO Name</i> <i>ISO Definition</i> <i>XML Tag Type</i>	Statement Entry Reference details on the underlying statement cash entry. <i>StmtNtry</i> UnderlyingStatementEntry3

#	SEPA Mult	Message Element	Inter-PSP Inquiry for Claim Non-Receipt SEPA Core Requirements	
4.0	0..1	Claim Non Receipt V07 +Cover Details	ISO Name ISO Definition XML Tag Type	Cover Details Provides the cover related information of a claim non receipt investigation. The absence of the cover details means that the message is not a cover related investigation. CoverDtls MissingCover4
5.0	0..1	Claim Non Receipt V07 +Instruction For Assignee	SEPA Rulebook ISO Name ISO Definition XML Tag Type	AT-Q003 Additional Information to AT-Q001 SCT inquiry reason code Instruction For Assignee Further information related to the processing of the investigation that may need to be acted upon by the assignee. InstrForAssgne InstructionForAssignee1
5.1	1..1	Claim Non Receipt V07 +Instruction For Assignee ++Code	SEPA Usage Rule(s) Mandatory. Only "INQR" is allowed. ISO Name ISO Definition XML Tag Type ISO Length SEPA Length SEPA Code Restrictions INQR	Code Coded information related to the processing of the investigation instruction, provided by the assigner, and intended for the assignee. Cd ExternalAgentInstruction1Code 1 .. 4 1 .. 4 InquiryReason Additional Information to an inquiry reason must be provided.
5.2	1..1	Claim Non Receipt V07 +Instruction For Assignee ++Instruction Information	SEPA Usage Rule(s) Mandatory. The text shall be in a comprehensible language to the Scheme Participant receiving the SCT inquiry who is obliged to act upon this information received. ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Instruction Information Further information complementing the coded instruction or instruction to the assignee. InstrInfnf Max140Text 1 .. 140 1 .. 140
6.0	0..n	Claim Non Receipt V07 +Supplementary Data	ISO Name ISO Definition XML Tag Type	Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block. SplmtryData SupplementaryData1



2.13 Inter-PSP Negative Response to Claim Non-Receipt (DS-10)

2.13.1 Use of Resolution of Investigation (camt.029.001.09)

This message is used to transmit a negative response to a:

- Claim Non-Receipt message (Claim Non-Receipt, camt.027.001.07);
- Request for Status Update on a Claim Non-Receipt message (FI-to-FI Payment Status Request, pacs.028.001.03, refer to section 'Request for Status Update on a SCT Inquiry' below);

where the following apply:

- Index 3.0 'Status': only sub-element 'Confirmation' is allowed, populated with "RJNR" (Rejected Claim Non Receipt) only.
- Under index 6.0 'Claim Non Receipt Details', only index 6.2 'Rejected' is allowed, populated with "NOOR" (No Original Transaction Received), "RNPR" (Original Transaction Received but Not Processable), "ARJT" (Already Rejected Transaction), "ARDT" (Already Returned Transaction) or "RR04" (Regulatory Reason).

In the context of a Claim Non-Receipt, the message caters for a single response only.

Note: The use case of the message is implied by the 'Message Name', 'camt.029.001.09', the 'Original Message Name Identification' must begin with pacs.008 (the addition of a variant number and version number is optional) and 'Status' set to "RJNR" (Rejected Claim Non-Receipt).

Note: A negative response implies that a Claim Non-Receipt is rejected by the receiving party. Also, please refer to the description in the message below under the 'Claim Non-Receipt Details' block.

#	SEPA Mult	Message Element	Inter-PSP Negative Response to Claim Non-Receipt SEPA Core Requirements	
		Document	XML Tag Type	Document Document
	1..1	Resolution Of Investigation V09	ISO Name ISO Definition XML Tag Type	Resolution Of Investigation V09 The ResolutionOfInvestigation message is sent by a case assignee to a case creator/case assigner. This message is used to inform of the resolution of a case, and optionally provides details about: - the corrective action undertaken by the case assignee - information on the return where applicable RsltnOfInvstgtn ResolutionOfInvestigationV09
1.0	1..1	Resolution Of Investigation V09 +Assignment	ISO Name ISO Definition XML Tag Type	Assignment Identifies the assignment of an investigation case from an assigner to an assignee. Usage: The assigner must be the sender of this confirmation and the assignee must be the receiver. Assgnmt CaseAssignment5
1.1	1..1	Resolution Of Investigation V09 +Assignment ++Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Identification Uniquely identifies the case assignment. Id Max35Text 1 .. 35 1 .. 35
1.2	1..1	Resolution Of Investigation V09 +Assignment ++Assigner	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Instructing Party. Limited to 'BICFI' to identify a PSP, 'AnyBIC' to identify a CSM or 'LEI' or 'Name' to indicate a CSM when it has no BIC. 'Name' is limited to 70 characters in length. Assigner Party who assigns the case. Usage: This is also the sender of the message. Assgnr Party40Choice
1.3	1..1	Resolution Of Investigation V09 +Assignment ++Assignee	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Instructed Party. Limited to 'BICFI' to identify a PSP, 'AnyBIC' to identify a CSM or 'LEI' or 'Name' to indicate a CSM when it has no BIC. 'Name' is limited to 70 characters in length. Assignee Party to which the case is assigned. Usage: This is also the receiver of the message. Assgne Party40Choice
1.4	1..1	Resolution Of Investigation V09 +Assignment ++Creation Date Time	ISO Name ISO Definition XML Tag Type	Creation Date Time Date and time at which the assignment was created. CreDtTm ISODateTime
2.0	1..1	Resolution Of Investigation V09 +Resolved Case	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Mandatory Resolved Case Identifies a resolved case. RslvdCase Case5

#	SEPA Mult	Message Element	Inter-PSP Negative Response to Claim Non-Receipt SEPA Core Requirements	
2.1	1..1	Resolution Of Investigation V09 +Resolved Case ++Identification	SEPA Rulebook ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>AT-Q002 The specific SCT inquiry reference of the Participant initiating the SCT inquiry.</i> Identification Uniquely identifies the case. Id Max35Text 1 .. 35 1 .. 35
2.2	1..1	Resolution Of Investigation V09 +Resolved Case ++Creator	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>Only 'Agent' is allowed.</i> <i>Limited to BICFI to identify the Originator PSP of the original credit transfer.</i> Creator Party that created the investigation case. Cretr Party40Choice
2.3	0..1	Resolution Of Investigation V09 +Resolved Case ++Reopen Case Indication	ISO Name ISO Definition XML Tag Type	Reopen Case Indication Indicates whether or not the case was previously closed and is now re-opened. ReopCaseIndctn YesNoIndicator
3.0	1..1	Resolution Of Investigation V09 +Status	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>Only 'Confirmation' is allowed.</i> Status Indicates the status of the investigation. Sts InvestigationStatus5Choice
	1..1		XML Tag	xs:choice
3.1	1..1	Resolution Of Investigation V09 +Status ++Confirmation	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>Only "RJNR" is allowed.</i> Confirmation Specifies the status of the investigation, in a coded form. Conf ExternalInvestigationExecutionConfirmation1Code 1 .. 4 1 .. 4
			SEPA Code Restrictions	
			RJNR	<i>RejectedClaimNonReceipt</i> <i>The claim for non-receipt of a payment instruction is rejected.</i>
3.2	1..n	Resolution Of Investigation V09 +Status ++Rejected Modification	ISO Name ISO Definition XML Tag Type	Rejected Modification Reason for the rejection of a modification request, in a coded form. RjctdMod ModificationStatusReason1Choice
3.3	1..1	Resolution Of Investigation V09 +Status ++Duplicate Of	ISO Name ISO Definition XML Tag Type	Duplicate Of Indicates a duplicated case. Usage: When present, the case identified in the message must be closed. The case identified as duplicated (in this component) will be pursued. DpletOf Case5
3.4	1..1	Resolution Of Investigation V09 +Status ++Assignment Cancellation Confirmation	ISO Name ISO Definition XML Tag Type	Assignment Cancellation Confirmation Indicates whether the cancellation of the assignment is confirmed or rejected. Usage: If yes, the cancellation of the assignment is confirmed. If no, the cancellation of the assignment is rejected and the investigation process will continue. AssgnmtCxlConf YesNoIndicator

#	SEPA Mult	Message Element	Inter-PSP Negative Response to Claim Non-Receipt SEPA Core Requirements		
4.0	0..n	Resolution Of Investigation V09 +Cancellation Details	ISO Name ISO Definition XML Tag Type	Cancellation Details Specifies the details of the underlying transactions being cancelled. CxlDtls UnderlyingTransaction22	
5.0	1..1	Resolution Of Investigation V09 +Modification Details	SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type	Modification Details Specifies the details of the underlying transaction being modified. ModDtls PaymentTransaction107	
5.1	1..1	Resolution Of Investigation V09 +Modification Details ++Modification Status Identification	SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Modification Status Identification Unique and unambiguous identifier of a modification request status, as assigned by the assigner. Usage: The modification status identification can be used for reconciliation or to link tasks relating to the modification request. ModStsId Max35Text 1 .. 35 1 .. 35	
5.2	0..1	Resolution Of Investigation V09 +Modification Details ++Resolved Case	ISO Name ISO Definition XML Tag Type	Resolved Case Identifies the resolved case. RslvdCase Case5	
5.3	1..1	Resolution Of Investigation V09 +Modification Details ++Original Group Information	ISO Name ISO Definition XML Tag Type	Original Group Information Provides information on the original message. OrgnlGrpInf OriginalGroupInformation29	
5.4	1..1	Resolution Of Investigation V09 +Modification Details ++Original Group Information +++Original Message Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Message Identification Point to point reference assigned by the original instructing party to unambiguously identify the original message. OrgnlMsgId Max35Text 1 .. 35 1 .. 35	
5.5	1..1	Resolution Of Investigation V09 +Modification Details ++Original Group Information +++Original Message Name Identification	SEPA Usage Rule(s) Must begin with 'pacs.008'. The addition of a variant number and version number is optional. ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Message Name Identification Specifies the original message name identifier to which the message refers, for example, pacs.003.001.01 or MT103. OrgnlMsgNmId Max35Text 1 .. 35 1 .. 35	
5.6	0..1	Resolution Of Investigation V09 +Modification Details ++Original Group Information +++Original Creation Date Time	ISO Name ISO Definition XML Tag Type	Original Creation Date Time Original date and time at which the message was created. OrgnlCreDtTm ISODateTime	
5.7	0..1	Resolution Of Investigation V09 +Modification Details ++Original Payment Information Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Payment Information Identification Unique identification, as assigned by the original sending party, to unambiguously identify the original payment information group. OrgnlPmtInflId Max35Text 1 .. 35 1 .. 35	

#	SEPA Mult	Message Element	Inter-PSP Negative Response to Claim Non-Receipt SEPA Core Requirements	
5.8	0..1	Resolution Of Investigation V09 +Modification Details ++Original Instruction Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Instruction Identification Unique identification, as assigned by the original instructing party for the original instructed party, to unambiguously identify the original instruction. OrgnlInstrId Max35Text 1 .. 35 1 .. 35
5.9	0..1	Resolution Of Investigation V09 +Modification Details ++Original End To End Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original End To End Identification Unique identification, as assigned by the original initiating party, to unambiguously identify the original transaction. OrgnlEndToEndId Max35Text 1 .. 35 1 .. 35
5.10	1..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Identification	SEPA Rulebook SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	AT-T054 The Originator PSP's reference of the SEPA Credit Transfer Transaction. This information must be taken from the camt.027 and is used for allowing the Originator PSP to recognise the transaction. Original Transaction Identification Unique identification, as assigned by the original first instructing agent, to unambiguously identify the transaction. OrgnlTxId Max35Text 1 .. 35 1 .. 35
5.11	0..1	Resolution Of Investigation V09 +Modification Details ++Original Clearing System Reference	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Clearing System Reference Unique reference, as assigned by the original clearing system, to unambiguously identify the original instruction. OrgnlClrSysRef Max35Text 1 .. 35 1 .. 35
5.12	0..1	Resolution Of Investigation V09 +Modification Details ++Original UETR	ISO Name ISO Definition XML Tag Type Pattern	Original UETR Universally unique identifier to provide the original end-to-end reference of a payment transaction. OrgnlUETR UUIDv4Identifier [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}
5.13	0..n	Resolution Of Investigation V09 +Modification Details ++Modification Status Reason Information	ISO Name ISO Definition XML Tag Type	Modification Status Reason Information Provides detailed information on the modification status reason. ModStsRsnInf ModificationStatusReason2
5.14	0..1	Resolution Of Investigation V09 +Modification Details ++Resolution Related Information	ISO Name ISO Definition XML Tag Type	Resolution Related Information Reference of a return or a reversal transaction that is initiated to fix the case under investigation as part of the resolution. RsltnRltdInf ResolutionData1

#	SEPA Mult	Message Element	Inter-PSP Negative Response to Claim Non-Receipt SEPA Core Requirements		
5.15	0..1	Resolution Of Investigation V09 +Modification Details ++Original Interbank Settlement Amount	ISO Name ISO Definition XML Tag Type <i>SEPA FractDigits</i> TotalDigits <i>SEPA Inclusive</i>	Original Interbank Settlement Amount Amount of money moved between the instructing agent and the instructed agent, as provided in the original instruction. OrgnlIntrBkSttlmAmt ActiveOrHistoricCurrencyAndAmount 5 18 0 ..	
5.16	0..1	Resolution Of Investigation V09 +Modification Details ++Original Interbank Settlement Date	ISO Name ISO Definition XML Tag Type	Original Interbank Settlement Date Date, as provided in the original transaction, on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. OrgnlIntrBkSttlmDt ISODate	
5.17	0..1	Resolution Of Investigation V09 +Modification Details ++Assigner	ISO Name ISO Definition XML Tag Type	Assigner Party who assigns the case. Usage: This is also the agent that instructs the next party in the chain to carry out the (set of) cancellation request(s). Assgnr Party40Choice	
5.18	0..1	Resolution Of Investigation V09 +Modification Details ++Assignee	ISO Name ISO Definition XML Tag Type	Assignee Party to which the case is assigned. Usage: This is also the agent that is instructed by the previous party in the chain to carry out the (set of) cancellation request(s). Assgne Party40Choice	
5.19	1..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference	SEPA Usage Rule(s) <i>Mandatory.</i> ISO Name ISO Definition XML Tag Type	<i>Only Debtor Agent and Creditor Agent must be used.</i> Original Transaction Reference Key elements used to identify the original transaction that is being referred to. OrgnlTxRef OriginalTransactionReference28	
5.20	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Interbank Settlement Amount	ISO Name ISO Definition XML Tag Type <i>SEPA FractDigits</i> TotalDigits <i>SEPA Inclusive</i>	Interbank Settlement Amount Amount of money moved between the instructing agent and the instructed agent. IntrBkSttlmAmt ActiveOrHistoricCurrencyAndAmount 5 18 0 ..	
5.21	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Amount	ISO Name ISO Definition XML Tag Type	Amount Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party. Amt AmountType4Choice	
5.22	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Interbank Settlement Date	ISO Name ISO Definition XML Tag Type	Interbank Settlement Date Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. IntrBkSttlmDt ISODate	

#	SEPA Mult	Message Element	Inter-PSP Negative Response to Claim Non-Receipt SEPA Core Requirements	
5.23	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Requested Collection Date	ISO Name ISO Definition XML Tag Type	Requested Collection Date Date and time at which the creditor requests that the amount of money is to be collected from the debtor. ReqdColltnDt ISODate
5.24	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Requested Execution Date	ISO Name ISO Definition XML Tag Type	Requested Execution Date Date at which the initiating party requests the clearing agent to process the payment. Usage: This is the date on which the debtor's account is to be debited. If payment by cheque, the date when the cheque must be generated by the bank. ReqdExctnDt DateAndDateTime2Choice
5.25	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Creditor Scheme Identification	ISO Name ISO Definition XML Tag Type	Creditor Scheme Identification Credit party that signs the mandate. CdtrSchmeId PartyIdentification135
5.26	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Settlement Information	ISO Name ISO Definition XML Tag Type	Settlement Information Specifies the details on how the settlement of the original transaction(s) between the instructing agent and the instructed agent was completed. SttlmInf SettlementInstruction7
5.27	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Payment Type Information	ISO Name ISO Definition XML Tag Type	Payment Type Information Set of elements used to further specify the type of transaction. PmtTpInf PaymentTypeInformation27
5.28	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Payment Method	ISO Name ISO Definition XML Tag Type	Payment Method Specifies the means of payment that will be used to move the amount of money. PmtMtd PaymentMethod4Code
5.29	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Mandate Related Information	ISO Name ISO Definition XML Tag Type	Mandate Related Information Provides further details of the mandate signed between the creditor and the debtor. MndtRltdInf MandateRelatedInformation14
5.30	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Remittance Information	ISO Name ISO Definition XML Tag Type	Remittance Information Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system. RmtInf RemittanceInformation16
5.31	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Ultimate Debtor	ISO Name ISO Definition XML Tag Type	Ultimate Debtor Ultimate party that owes an amount of money to the (ultimate) creditor. UltmtDbtr Party40Choice
5.32	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Debtor	ISO Name ISO Definition XML Tag Type	Debtor Party that owes an amount of money to the (ultimate) creditor. Dbtr Party40Choice
5.33	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Debtor Account	ISO Name ISO Definition XML Tag Type	Debtor Account Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction. DbtrAcct CashAccount38

#	SEPA Mult	Message Element	Inter-PSP Negative Response to Claim Non-Receipt SEPA Core Requirements	
5.34	1..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Debtor Agent	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-D002 The BIC code of the Originator PSP.</i> <i>Mandatory.</i> Debtor Agent Financial institution servicing an account for the debtor. DbtrAgt BranchAndFinancialInstitutionIdentification6
5.35	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Debtor Agent Account	ISO Name ISO Definition XML Tag Type	Debtor Agent Account Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain. DbtrAgtAcct CashAccount38
5.36	1..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Creditor Agent	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-C002 The BIC code of the Beneficiary PSP.</i> <i>Mandatory.</i> Creditor Agent Financial institution servicing an account for the creditor. CdtrAgt BranchAndFinancialInstitutionIdentification6
5.37	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Creditor Agent Account	ISO Name ISO Definition XML Tag Type	Creditor Agent Account Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction. CdtrAgtAcct CashAccount38
5.38	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Creditor	ISO Name ISO Definition XML Tag Type	Creditor Party to which an amount of money is due. Cdtr Party40Choice
5.39	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Creditor Account	ISO Name ISO Definition XML Tag Type	Creditor Account Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction. CdtrAcct CashAccount38
5.40	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Ultimate Creditor	ISO Name ISO Definition XML Tag Type	Ultimate Creditor Ultimate party to which an amount of money is due. UltmtCdtr Party40Choice
5.41	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Purpose	ISO Name ISO Definition XML Tag Type	Purpose Underlying reason for the payment transaction. Usage: Purpose is used by the end customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain. Purp Purpose2Choice
6.0	1..1	Resolution Of Investigation V09 +Claim Non Receipt Details	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-Q004 Non-receipt of the SEPA Credit Transfer/non-execution due to regulatory reason.</i> <i>Mandatory.</i> Claim Non Receipt Details Specifies the details of the underlying transaction for which a claim non receipt has been initiated. ClmNonRctDtls ClaimNonReceipt2Choice
	1..1		XML Tag	xs:choice

#	SEPA Mult	Message Element	Inter-PSP Negative Response to Claim Non-Receipt SEPA Core Requirements	
6.1	1..1	Resolution Of Investigation V09 +Claim Non Receipt Details ++Accepted	ISO Name ISO Definition XML Tag Type	Accepted Claim non-receipt is accepted and processed by the agent. Acceptd ClaimNonReceipt2
6.2	1..1	Resolution Of Investigation V09 +Claim Non Receipt Details ++Rejected	ISO Name ISO Definition XML Tag Type	Rejected Specifies that the claim non receipt has been rejected and provides the reason for the rejection. Rjctd ClaimNonReceiptRejectReason1Choice
	1..1		XML Tag	xs:choice
6.3	1..1	Resolution Of Investigation V09 +Claim Non Receipt Details ++Rejected +++Code	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Code Reason for the rejection, in a coded form. Cd ExternalClaimNonReceiptRejection1Code 1 .. 4 1 .. 4
6.4	1..1	Resolution Of Investigation V09 +Claim Non Receipt Details ++Rejected +++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Proprietary Reason for the rejection, in a proprietary form. Prtry Max35Text 1 .. 35 1 .. 35
7.0	0..1	Resolution Of Investigation V09 +Statement Details	ISO Name ISO Definition XML Tag Type	Statement Details Details on the underlying statement entry. StmtDtls StatementResolutionEntry4
8.0	0..1	Resolution Of Investigation V09 +Correction Transaction	ISO Name ISO Definition XML Tag Type	Correction Transaction References a transaction initiated to fix the case under investigation. CrrctnTx CorrectiveTransaction4Choice
9.0	0..1	Resolution Of Investigation V09 +Resolution Related Information	ISO Name ISO Definition XML Tag Type	Resolution Related Information Reference to fix the case under investigation as part of the resolution. RsltnRltdInf ResolutionData1
10.0	0..n	Resolution Of Investigation V09 +Supplementary Data	ISO Name ISO Definition XML Tag Type	Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block. SplmtryData SupplementaryData1



2.14 Inter-PSP Positive Response to Claim Non-Receipt (DS-10)

2.14.1 Use of Resolution of Investigation (camt.029.001.09)

This message is used to transmit a positive response to a:

- Claim Non-Receipt message (Claim Non-Receipt, camt.027.001.07);
- Request for Status Update on a Claim Non-Receipt message (FI-to-FI Payment Status Request, pacs.028.001.03, refer to section 'Request for Status Update on a SCT Inquiry' below);

where the following apply:

- Index 3.0 'Status': only sub-element 'Confirmation' is allowed, populated with "ACNR" (Accepted Claim Non Receipt) only.
- Under index 6.0 'Claim Non Receipt Details', only index 6.1 'Accepted' and the relevant sub-elements are allowed.
- Under index 9.0 'Resolution Related Information', only 9.8 'Charges' and relevant sub-elements are allowed to accommodate AT-Q007 'Fee for handling the SCT Inquiry'.

In the context of a Claim Non-Receipt, the message caters for a single response only.

Note: The use case of the message is implied by the 'Message Name', 'camt.029.001.09', the 'Original Message Name Identification' must begin with pacs.008 (the addition of a variant number and version number is optional) and 'Status' set to "ACNR".

Note: Message elements under 'Original Transaction Reference' sequence are based on DS-02 attributes.

Note: A positive response implies that a Claim Non-Receipt is accepted by the receiving party.

Note: The payment of the charges is to be effectuated according to the current inter-PSP practices related to such matters. It is recommended to use the pacs.008 as described for this specific usage as per below section 'Inter-PSP Fee and/or Compensation Payment'. When paying the charges, the Originator PSP must provide 'AT-Q002 The specific SCT inquiry reference of the Participant initiating the SCT inquiry' and 'AT-Q009 Reference of the Beneficiary Bank for interbank fee and/or compensation payment' in order to allow the Beneficiary PSP to allocate the payment to the right case. Moreover, the IBAN provided under 'Resolution Related Information/Charges' is the one corresponding to AT-Q008 'The IBAN of the account to be credited at the Beneficiary PSP' in the inter-PSP payment message.

#	SEPA Mult	Message Element	Inter-PSP Positive Response to Claim Non-Receipt SEPA Core Requirements	
		Document	XML Tag Type	Document Document
	1..1	Resolution Of Investigation V09	ISO Name ISO Definition XML Tag Type	Resolution Of Investigation V09 The ResolutionOfInvestigation message is sent by a case assignee to a case creator/case assigner. This message is used to inform of the resolution of a case, and optionally provides details about: - the corrective action undertaken by the case assignee - information on the return where applicable RsltnOfInvstgtn ResolutionOfInvestigationV09
1.0	1..1	Resolution Of Investigation V09 +Assignment	ISO Name ISO Definition XML Tag Type	Assignment Identifies the assignment of an investigation case from an assigner to an assignee. Usage: The Assigner must be the sender of this confirmation and the Assignee must be the receiver. Assgnmt CaseAssignment5
1.1	1..1	Resolution Of Investigation V09 +Assignment ++Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Identification Uniquely identifies the case assignment. Id Max35Text 1 .. 35 1 .. 35
1.2	1..1	Resolution Of Investigation V09 +Assignment ++Assigner	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Instructing Party. Limited to 'BICFI' to identify a PSP, 'AnyBIC' to identify a CSM or 'LEI' or 'Name' to indicate a CSM when it has no BIC. 'Name' is limited to 70 characters in length. Assigner Party who assigns the case. Usage: This is also the sender of the message. Assgnr Party40Choice
1.3	1..1	Resolution Of Investigation V09 +Assignment ++Assignee	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Instructed Party. Limited to 'BICFI' to identify a PSP, 'AnyBIC' to identify a CSM or 'LEI' or 'Name' to indicate a CSM when it has no BIC. 'Name' is limited to 70 characters in length. Assignee Party to which the case is assigned. Usage: This is also the receiver of the message. Assgne Party40Choice
1.4	1..1	Resolution Of Investigation V09 +Assignment ++Creation Date Time	ISO Name ISO Definition XML Tag Type	Creation Date Time Date and time at which the assignment was created. CreDtTm ISODateTime
2.0	1..1	Resolution Of Investigation V09 +Resolved Case	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Mandatory. Resolved Case Identifies a resolved case. RslvdCase Case5

#	SEPA Mult	Message Element	Inter-PSP Positive Response to Claim Non-Receipt SEPA Core Requirements	
2.1	1..1	Resolution Of Investigation V09 +Resolved Case ++Identification	SEPA Rulebook ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>AT-Q002 The specific SCT inquiry reference of the Participant initiating the SCT inquiry.</i> Identification Uniquely identifies the case. Id Max35Text 1 .. 35 1 .. 35
2.2	1..1	Resolution Of Investigation V09 +Resolved Case ++Creator	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>Only 'Agent' is allowed.</i> <i>Limited to 'BICFI' to identify the Originator PSP of the original credit transfer.</i> Creator Party that created the investigation case. Cretr Party40Choice
2.3	0..1	Resolution Of Investigation V09 +Resolved Case ++Reopen Case Indication	ISO Name ISO Definition XML Tag Type	Reopen Case Indication Indicates whether or not the case was previously closed and is now re-opened. ReopCaseIndctn YesNoIndicator
3.0	1..1	Resolution Of Investigation V09 +Status	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>Only 'Confirmation' is allowed.</i> Status Indicates the status of the investigation. Sts InvestigationStatus5Choice
	1..1		XML Tag	xs:choice
3.1	1..1	Resolution Of Investigation V09 +Status ++Confirmation	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>Only "ACNR" is allowed.</i> Confirmation Specifies the status of the investigation, in a coded form. Conf ExternalInvestigationExecutionConfirmation1Code 1 .. 4 1 .. 4
			SEPA Code Restrictions	
			ACNR	<i>AcceptedClaimNonReceipt</i> <i>The claim for non-receipt of a payment instruction is accepted.</i>
3.2	1..n	Resolution Of Investigation V09 +Status ++Rejected Modification	ISO Name ISO Definition XML Tag Type	Rejected Modification Reason for the rejection of a modification request, in a coded form. RjctdMod ModificationStatusReason1Choice
3.3	1..1	Resolution Of Investigation V09 +Status ++Duplicate Of	ISO Name ISO Definition XML Tag Type	Duplicate Of Indicates a duplicated case. Usage: When present, the case identified in the message must be closed. The case identified as duplicated (in this component) will be pursued. DpletOf Case5
3.4	1..1	Resolution Of Investigation V09 +Status ++Assignment Cancellation Confirmation	ISO Name ISO Definition XML Tag Type	Assignment Cancellation Confirmation Indicates whether the cancellation of the assignment is confirmed or rejected. Usage: If yes, the cancellation of the assignment is confirmed. If no, the cancellation of the assignment is rejected and the investigation process will continue. AssgnmtCxlConf YesNoIndicator

#	SEPA Mult	Message Element	Inter-PSP Positive Response to Claim Non-Receipt SEPA Core Requirements	
4.0	0..n	Resolution Of Investigation V09 +Cancellation Details	ISO Name ISO Definition XML Tag Type	Cancellation Details Specifies the details of the underlying transactions being cancelled. CxlDtls UnderlyingTransaction22
5.0	1..1	Resolution Of Investigation V09 +Modification Details	SEPA Usage Rule(s) <i>Mandatory.</i> ISO Name ISO Definition XML Tag Type	<i>AT-Q009 Reference of the Beneficiary PSP for inter-PSP fee and/or compensation payment</i> Modification Details Specifies the details of the underlying transaction being modified. ModDtls PaymentTransaction107
5.1	1..1	Resolution Of Investigation V09 +Modification Details ++Modification Status Identification	SEPA Rulebook SEPA Usage Rule(s) <i>Mandatory.</i> ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>AT-Q009 Reference of the Beneficiary PSP for inter-PSP fee and/or compensation payment</i> Modification Status Identification Unique and unambiguous identifier of a modification request status, as assigned by the assigner. Usage: The modification status identification can be used for reconciliation or to link tasks relating to the modification request. ModStsId Max35Text 1 .. 35 1 .. 35
5.2	0..1	Resolution Of Investigation V09 +Modification Details ++Resolved Case	ISO Name ISO Definition XML Tag Type	Resolved Case Identifies the resolved case. RslvdCase Case5
5.3	1..1	Resolution Of Investigation V09 +Modification Details ++Original Group Information	ISO Name ISO Definition XML Tag Type	Original Group Information Provides information on the original message. OrgnlGrpInf OriginalGroupInformation29
5.4	1..1	Resolution Of Investigation V09 +Modification Details ++Original Group Information +++Original Message Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Message Identification Point to point reference assigned by the original instructing party to unambiguously identify the original message. OrgnlMsgId Max35Text 1 .. 35 1 .. 35
5.5	1..1	Resolution Of Investigation V09 +Modification Details ++Original Group Information +++Original Message Name Identification	SEPA Usage Rule(s) <i>Must begin with 'pacs.008'. The addition of a variant number and version number is optional.</i> ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>Must begin with 'pacs.008'. The addition of a variant number and version number is optional.</i> Original Message Name Identification Specifies the original message name identifier to which the message refers, for example, pacs. 003.001.01 or MT103. OrgnlMsgNmId Max35Text 1 .. 35 1 .. 35
5.6	0..1	Resolution Of Investigation V09 +Modification Details ++Original Group Information +++Original Creation Date Time	ISO Name ISO Definition XML Tag Type	Original Creation Date Time Original date and time at which the message was created. OrgnlCreDtTm ISODateTime

#	SEPA Mult	Message Element	Inter-PSP Positive Response to Claim Non-Receipt SEPA Core Requirements			
5.7	0..1	Resolution Of Investigation V09 +Modification Details ++Original Payment Information Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	OrgnlPmtInflId Max35Text 1 .. 35 1 .. 35	Original Payment Information Identification Unique identification, as assigned by the original sending party, to unambiguously identify the original payment information group.	
5.8	0..1	Resolution Of Investigation V09 +Modification Details ++Original Instruction Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	OrgnlInstrId Max35Text 1 .. 35 1 .. 35	Original Instruction Identification Unique identification, as assigned by the original instructing party for the original instructed party, to unambiguously identify the original instruction.	
5.9	1..1	Resolution Of Investigation V09 +Modification Details ++Original End To End Identification	SEPA Rulebook SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	AT-T014 The Originator's reference of the SEPA Credit Transfer Transaction. Original End To End Identification Unique identification, as assigned by the original initiating party, to unambiguously identify the original transaction. OrgnlEndToEndId Max35Text 1 .. 35 1 .. 35		
5.10	1..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Identification	SEPA Rulebook SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	AT-T054 The Originator PSP's reference of the SEPA Credit Transfer Transaction. Original Transaction Identification Unique identification, as assigned by the original first instructing agent, to unambiguously identify the transaction. OrgnlTxId Max35Text 1 .. 35 1 .. 35		
5.11	0..1	Resolution Of Investigation V09 +Modification Details ++Original Clearing System Reference	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Clearing System Reference Unique reference, as assigned by the original clearing system, to unambiguously identify the original instruction. OrgnlClrSysRef Max35Text 1 .. 35 1 .. 35		
5.12	0..1	Resolution Of Investigation V09 +Modification Details ++Original UETR	ISO Name ISO Definition XML Tag Type Pattern	Original UETR Universally unique identifier to provide the original end-to-end reference of a payment transaction. OrgnlUETR UUIDv4Identifier [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}		
5.13	0..n	Resolution Of Investigation V09 +Modification Details ++Modification Status Reason Information	ISO Name ISO Definition XML Tag Type	Modification Status Reason Information Provides detailed information on the modification status reason. ModStsRsnInf ModificationStatusReason2		

#	SEPA Mult	Message Element	Inter-PSP Positive Response to Claim Non-Receipt SEPA Core Requirements		
5.14	0..1	Resolution Of Investigation V09 +Modification Details ++Resolution Related Information	ISO Name ISO Definition XML Tag Type	Resolution Related Information Reference of a return or a reversal transaction that is initiated to fix the case under investigation as part of the resolution. RsltnRltdInf ResolutionData1	
5.15	0..1	Resolution Of Investigation V09 +Modification Details ++Original Interbank Settlement Amount	ISO Name ISO Definition XML Tag Type <i>SEPA FractDigits</i> <i>TotalDigits</i> <i>SEPA Inclusive</i>	Original Interbank Settlement Amount Amount of money moved between the instructing agent and the instructed agent, as provided in the original instruction. OrgnlIntrBkSttlmAmt ActiveOrHistoricCurrencyAndAmount 5 18 0 ..	
5.16	0..1	Resolution Of Investigation V09 +Modification Details ++Original Interbank Settlement Date	ISO Name ISO Definition XML Tag Type	Original Interbank Settlement Date Date, as provided in the original transaction, on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. OrgnlIntrBkSttlmDt ISODate	
5.17	0..1	Resolution Of Investigation V09 +Modification Details ++Assigner	ISO Name ISO Definition XML Tag Type	Assigner Party who assigns the case. Usage: This is also the agent that instructs the next party in the chain to carry out the (set of) cancellation request(s). Assgnr Party40Choice	
5.18	0..1	Resolution Of Investigation V09 +Modification Details ++Assignee	ISO Name ISO Definition XML Tag Type	Assignee Party to which the case is assigned. Usage: This is also the agent that is instructed by the previous party in the chain to carry out the (set of) cancellation request(s). Assgne Party40Choice	
5.19	1..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference	<i>SEPA Rulebook</i> <i>SEPA Usage Rule(s)</i>	<i>An exact copy of all attributes of DS-02 of the initially sent pacs.008 to which the claim refers.</i> <i>Mandatory</i> <i>The yellow shaded message elements under 'Original Transaction Reference' must be populated with the same value as the message elements of the original instruction.</i> Original Transaction Reference Key elements used to identify the original transaction that is being referred to. OrgnlTxRef OriginalTransactionReference28	
5.20	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Interbank Settlement Amount	<i>SEPA Rulebook</i> <i>ISO Name</i> <i>ISO Definition</i> <i>XML Tag Type</i> <i>SEPA FractDigits</i> <i>TotalDigits</i> <i>SEPA Inclusive</i>	<i>AT-T002 Amount of the SEPA Credit Transfer in Euro.</i> Interbank Settlement Amount Amount of money moved between the instructing agent and the instructed agent. IntrBkSttlmAmt ActiveOrHistoricCurrencyAndAmount 2 18 0.01 .. 999999999.99	

#	SEPA Mult	Message Element	Inter-PSP Positive Response to Claim Non-Receipt SEPA Core Requirements	
5.21	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Amount	ISO Name ISO Definition XML Tag Type	Amount Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party. Amt AmountType4Choice
5.22	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Interbank Settlement Date	SEPA Rulebook ISO Name ISO Definition XML Tag Type	AT-T051 Settlement Date of the Credit Transfer in Euro. Interbank Settlement Date Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. IntrBkSttlmDt ISODate
5.23	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Requested Collection Date	ISO Name ISO Definition XML Tag Type	Requested Collection Date Date and time at which the creditor requests that the amount of money is to be collected from the debtor. ReqdColltnDt ISODate
5.24	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Requested Execution Date	ISO Name ISO Definition XML Tag Type	Requested Execution Date Date at which the initiating party requests the clearing agent to process the payment. Usage: This is the date on which the debtor's account is to be debited. If payment by cheque, the date when the cheque must be generated by the bank. ReqdExctnDt DateAndDateTime2Choice
5.25	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Creditor Scheme Identification	ISO Name ISO Definition XML Tag Type	Creditor Scheme Identification Credit party that signs the mandate. CdtrSchmElD PartyIdentification135
5.26	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Settlement Information	ISO Name ISO Definition XML Tag Type	Settlement Information Specifies the details on how the settlement of the original transaction(s) between the instructing agent and the instructed agent was completed. SttlmInf SettlementInstruction7
5.27	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Payment Type Information	SEPA Rulebook ISO Name ISO Definition XML Tag Type	AT-T001 Identification code of the Scheme. AT-T008 Category Purpose of the Credit Transfer. If the original transaction was sent according to Annex V (Use of Extended Remittance Information) of the SCT Rulebook (refer to section 'Inter-PSP payment with use of the Extended Remittance Information option' below), then 'Local Instrument/Code' must be populated with "PERI" (Payment with Extended Remittance Information). Payment Type Information Set of elements used to further specify the type of transaction. PmtTpInf PaymentTypeInformation27
5.28	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Payment Method	ISO Name ISO Definition XML Tag Type	Payment Method Specifies the means of payment that will be used to move the amount of money. PmtMtd PaymentMethod4Code

#	SEPA Mult	Message Element	Inter-PSP Positive Response to Claim Non-Receipt SEPA Core Requirements	
5.29	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Mandate Related Information	ISO Name ISO Definition XML Tag Type	Mandate Related Information Provides further details of the mandate signed between the creditor and the debtor. MndtRltdInf MandateRelatedInformation14
5.30	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Remittance Information	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-T009 Remittance information or AT-T010 The unstructured Remittance Information sent by the Originator to the Beneficiary in the Credit Transfer Instruction (in case of use of the Extended Remittance Information (ERI) option in the original SEPA Credit Transfer, AT-T011 The structured Remittance Information sent by the Originator to the Beneficiary in the SEPA Credit Transfer Instruction, will NOT be transported here).</i> Remittance Information Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system. RmtInf RemittanceInformation16
5.31	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Ultimate Debtor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-P006 The name of the Originator Reference Party.</i> <i>AT-P007 The identification code of the Originator Reference Party.</i> <i>Only 'Party' is allowed.</i> Ultimate Debtor Ultimate party that owes an amount of money to the (ultimate) creditor. UltmtDbtr Party40Choice
5.32	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Debtor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-P001 Name of the Originator.</i> <i>AT-P005 Address of the Originator.</i> <i>AT-P004 Originator's Identification Code.</i> <i>Only 'Party' is allowed.</i> Debtor Party that owes an amount of money to the (ultimate) creditor. Dbtr Party40Choice
5.33	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Debtor Account	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-D001 The IBAN of the account of the Originator.</i> <i>AT-P003 The Proxy/Alias of the account of the Originator.</i> Debtor Account Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction. DbtrAcct CashAccount38
5.34	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Debtor Agent	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-D002 The BIC code of the Originator PSP.</i> Debtor Agent Financial institution servicing an account for the debtor. DbtrAgt BranchAndFinancialInstitutionIdentification6
5.35	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Debtor Agent Account	ISO Name ISO Definition XML Tag Type	Debtor Agent Account Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain. DbtrAgtAcct CashAccount38

#	SEPA Mult	Message Element	Inter-PSP Positive Response to Claim Non-Receipt SEPA Core Requirements	
5.36	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Creditor Agent	<i>SEPA Rulebook</i> ISO Name ISO Definition XML Tag Type	<i>AT-C002 The BIC code of the Beneficiary PSP.</i> Creditor Agent Financial institution servicing an account for the creditor. CdtrAgt BranchAndFinancialInstitutionIdentification6
5.37	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Creditor Agent Account	ISO Name ISO Definition XML Tag Type	Creditor Agent Account Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction. CdtrAgtAcct CashAccount38
5.38	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Creditor	<i>SEPA Rulebook</i> <i>SEPA Usage Rule(s)</i> Only 'Party' is allowed. ISO Name ISO Definition XML Tag Type	<i>AT-E001 Name of the Beneficiary.</i> <i>AT-E004 Address of the Beneficiary.</i> <i>AT-E005 Beneficiary Identification Code.</i> Creditor Party to which an amount of money is due. Cdtr Party40Choice
5.39	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Creditor Account	<i>SEPA Rulebook</i> ISO Name ISO Definition XML Tag Type	<i>AT-C001 The IBAN of the account of the Beneficiary.</i> <i>AT-E003 The Proxy/Alias of the account of the Beneficiary.</i> Creditor Account Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction. CdtrAcct CashAccount38
5.40	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Ultimate Creditor	<i>SEPA Rulebook</i> <i>SEPA Usage Rule(s)</i> Only 'Party' is allowed. ISO Name ISO Definition XML Tag Type	<i>AT-E007 The name of the Beneficiary Reference Party.</i> <i>AT-E010 The identification code of the Beneficiary Reference Party.</i> Ultimate Creditor Ultimate party to which an amount of money is due. UltmtCdtr Party40Choice
5.41	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Purpose	<i>SEPA Rulebook</i> ISO Name ISO Definition XML Tag Type	<i>AT-T007 The purpose of the SEPA Credit Transfer.</i> Purpose Underlying reason for the payment transaction. Usage: Purpose is used by the end customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain. Purp Purpose2Choice
6.0	1..1	Resolution Of Investigation V09 +Claim Non Receipt Details	<i>SEPA Usage Rule(s)</i> Mandatory. ISO Name ISO Definition XML Tag Type	Mandatory. Claim Non Receipt Details Specifies the details of the underlying transaction for which a claim non receipt has been initiated. ClmNonRctDtls ClaimNonReceipt2Choice
	1..1		XML Tag	xs:choice

#	SEPA Mult	Message Element	Inter-PSP Positive Response to Claim Non-Receipt SEPA Core Requirements	
6.1	1..1	Resolution Of Investigation V09 +Claim Non Receipt Details ++Accepted	ISO Name ISO Definition XML Tag Type	Accepted Claim non-receipt is accepted and processed by the agent. Acptd ClaimNonReceipt2
6.2	1..1	Resolution Of Investigation V09 +Claim Non Receipt Details ++Accepted +++Date Processed	ISO Name ISO Definition XML Tag Type	Date Processed Specifies the date the original payment instruction was processed. DtPrcd ISODate
6.3	0..1	Resolution Of Investigation V09 +Claim Non Receipt Details ++Accepted +++Original Next Agent	ISO Name ISO Definition XML Tag Type	Original Next Agent Specifies the next party the original payment instruction was sent to. OrgnlNxtAgt BranchAndFinancialInstitutionIdentification6
6.4	1..1	Resolution Of Investigation V09 +Claim Non Receipt Details ++Rejected	ISO Name ISO Definition XML Tag Type	Rejected Specifies that the claim non receipt has been rejected and provides the reason for the rejection. Rjctd ClaimNonReceiptRejectReason1Choice
7.0	0..1	Resolution Of Investigation V09 +Statement Details	ISO Name ISO Definition XML Tag Type	Statement Details Details on the underlying statement entry. StmtDtls StatementResolutionEntry4
8.0	0..1	Resolution Of Investigation V09 +Correction Transaction	ISO Name ISO Definition XML Tag Type	Correction Transaction References a transaction initiated to fix the case under investigation. CrrctnTx CorrectiveTransaction4Choice
9.0	0..1	Resolution Of Investigation V09 +Resolution Related Information	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	AT-Q007 Fee for handling the SCT inquiry. Only 'Charges' is allowed. Resolution Related Information Reference to fix the case under investigation as part of the resolution. RsltnRltdInf ResolutionData1
9.1	0..1	Resolution Of Investigation V09 +Resolution Related Information ++End To End Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	End To End Identification Unique identification, as assigned by the original initiating party, to unambiguously identify the original transaction. EndToEndId Max35Text 1 .. 35 1 .. 35
9.2	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Transaction Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Transaction Identification Unique identification, as assigned by the original first instructing agent, to unambiguously identify the transaction. TxId Max35Text 1 .. 35 1 .. 35
9.3	0..1	Resolution Of Investigation V09 +Resolution Related Information ++UETR	ISO Name ISO Definition XML Tag Type Pattern	UETR Universally unique identifier to provide an end-to-end reference of a payment transaction. UETR UUIDv4Identifier [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}

#	SEPA Mult	Message Element	Inter-PSP Positive Response to Claim Non-Receipt SEPA Core Requirements			
9.4	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Interbank Settlement Amount	ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits SEPA Inclusive	Interbank Settlement Amount Amount of money moved between the instructing agent and the instructed agent. IntrBkStlmtAmt ActiveOrHistoricCurrencyAndAmount 5 18 0 ..		
9.5	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Interbank Settlement Date	ISO Name ISO Definition XML Tag Type	Interbank Settlement Date Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. IntrBkStlmtDt ISODate		
9.6	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Clearing Channel	ISO Name ISO Definition XML Tag Type	Clearing Channel Specifies the clearing channel to be used to process the payment instruction. ClrChnl ClearingChannel2Code		
9.7	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Compensation	ISO Name ISO Definition XML Tag Type	Compensation Provides the details of the compensation made due to the modification or cancellation of a previous payment. Compstn Compensation2		
9.8	1..1	Resolution Of Investigation V09 +Resolution Related Information ++Charges	SEPA Usage Rule(s) <i>Mandatory.</i> <i>Only one occurrence is allowed.</i> <i>It is the decision of the Beneficiary PSP if it wants to charge a fee to the Originator PSP for handling the SCT inquiry.</i> ISO Name ISO Definition XML Tag Type	Charges Provides information on the charges to be paid by the charge bearer(s) related to the payment transaction. Chrgs Charges7		
9.9	1..1	Resolution Of Investigation V09 +Resolution Related Information ++Charges +++Amount	SEPA Usage Rule(s) <i>Only 'EUR' is allowed.</i> <i>Amount must be 0.01 or more and 999999999.99 or less.</i> <i>The fractional part has a maximum of two digits.</i> SEPA Format Rule(s) ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits SEPA Inclusive	Amount Transaction charges to be paid by the charge bearer. Amt ActiveOrHistoricCurrencyAndAmount 2 18 0.01 .. 999999999.99		
9.10	1..1	Resolution Of Investigation V09 +Resolution Related Information ++Charges +++Agent	ISO Name ISO Definition XML Tag Type	Agent Agent that takes the transaction charges or to which the transaction charges are due. Agt BranchAndFinancialInstitutionIdentification6		
9.11	1..1	Resolution Of Investigation V09 +Resolution Related Information ++Charges +++Agent ++++Financial Institution Identification	ISO Name ISO Definition XML Tag Type	Financial Institution Identification Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme. FinInstId FinancialInstitutionIdentification18		

#	SEPA Mult	Message Element	Inter-PSP Positive Response to Claim Non-Receipt SEPA Core Requirements	
9.12	1..1	Resolution Of Investigation V09 +Resolution Related Information ++Charges +++Agent ++++Financial Institution Identification +++++BICFI	SEPA Rulebook SEPA Usage Rule(s) <i>Mandatory.</i> ISO Name BICFI ISO Definition Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)". XML Tag Type Pattern BICFI BICFIDec2014Identifier [A-Z0-9]{4,4}{A-Z}{2,2}{A-Z0-9}{2,2}{[A-Z0-9]{3,3}}{0,1}	
9.13	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Charges +++Agent ++++Financial Institution Identification +++++Clearing System Member Identification	ISO Name ISO Definition XML Tag Type ClrSysMmbld ClearingSystemMemberIdentification2	Clearing System Member Identification Information used to identify a member within a clearing system.
9.14	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Charges +++Agent ++++Financial Institution Identification +++++LEI	ISO Name ISO Definition XML Tag Type Pattern LEI Legal entity identifier of the financial institution. LEI LEIIdentifier [A-Z0-9]{18,18}{0-9}{2,2}	LEI Legal entity identifier of the financial institution. LEI LEIIdentifier [A-Z0-9]{18,18}{0-9}{2,2}
9.15	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Charges +++Agent ++++Financial Institution Identification +++++Name	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length Nm Max140Text 1 .. 140 1 .. 140	Name Name by which an agent is known and which is usually used to identify that agent. Nm Max140Text 1 .. 140 1 .. 140
9.16	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Charges +++Agent ++++Financial Institution Identification +++++Postal Address	ISO Name ISO Definition XML Tag Type PstlAdr PostalAddress24	Postal Address Information that locates and identifies a specific address, as defined by postal services. PstlAdr PostalAddress24
9.17	1..1	Resolution Of Investigation V09 +Resolution Related Information ++Charges +++Agent ++++Financial Institution Identification +++++Other	SEPA Usage Rule(s) <i>Mandatory.</i> ISO Name ISO Definition Other Unique identification of an agent, as assigned by an institution, using an identification scheme. XML Tag Type Othr GenericFinancialIdentification1	Other Unique identification of an agent, as assigned by an institution, using an identification scheme. Othr GenericFinancialIdentification1
9.18	1..1	Resolution Of Investigation V09 +Resolution Related Information ++Charges +++Agent ++++Financial Institution Identification +++++Other ++++++Identification	SEPA Usage Rule(s) <i>Only IBAN is allowed.</i> ISO Name ISO Definition Unique and unambiguous identification of a person. XML Tag Type Id Max35Text ISO Length SEPA Length 1 .. 35 1 .. 35	Identification Unique and unambiguous identification of a person. Id Max35Text 1 .. 35 1 .. 35
9.19	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Charges +++Agent ++++Financial Institution Identification +++++Other ++++++Scheme Name	ISO Name ISO Definition XML Tag Type SchmeNm FinancialIdentificationSchemeName1Choice	Scheme Name Name of the identification scheme. SchmeNm FinancialIdentificationSchemeName1Choice

#	SEPA Mult	Message Element	Inter-PSP Positive Response to Claim Non-Receipt SEPA Core Requirements	
9.20	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Charges +++Agent ++++Financial Institution Identification +++++Other ++++++Issuer	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Issuer Entity that assigns the identification. Issr Max35Text 1 .. 35 I .. 35
9.21	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Charges +++Agent ++++Branch Identification	ISO Name ISO Definition XML Tag Type	Branch Identification Identifies a specific branch of a financial institution. Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level. BrnchId BranchData3
10.0	0..n	Resolution Of Investigation V09 +Supplementary Data	ISO Name ISO Definition XML Tag Type	Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block. SplmtryData SupplementaryData1



2.15 Inter-PSP SCT Inquiry Dataset (DS-09) for Claim for Value Date Correction

2.15.1 Use of Request to Modify Payment (camt.087.001.06)

This message is used to transport the Claim for Value Date Correction from the Originator PSP to the Beneficiary PSP, directly or through intermediaries.

The message caters for a single claim.

Note: Attribute AT-Q001 'SCT inquiry reason code' is implied by the 'Message Name', 'camt.087.001.06' and the 'Original Message Name Identification' must begin with pacs.008 (the addition of a variant number and version number is optional).

Note: Message elements under 'Original Transaction Reference' sequence are based on DS-02 attributes.

#	SEPA Mult	Message Element	Inter-PSP Inquiry for Claim for Value Date Correction SEPA Core Requirements	
		Document	XML Tag Type	Document Document
0	1..1	Request To Modify Payment V06	ISO Name ISO Definition XML Tag Type	Request To Modify Payment V06 Scope The RequestToModifyPayment message is sent by a case creator/case assigner to a case assignee. This message is used to request the modification of characteristics of an original payment instruction. ReqToModfyPmt RequestToModifyPaymentV06
1.0	1..1	Request To Modify Payment V06 +Assignment	ISO Name ISO Definition XML Tag Type	Assignment Identifies the assignment of an investigation case from an assigner to an assignee. Usage: The assigner must be the sender of this confirmation and the assignee must be the receiver. Assgnmt CaseAssignment5
1.1	1..1	Request To Modify Payment V06 +Assignment ++Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Identification Uniquely identifies the case assignment. Id Max35Text 1 .. 35 1 .. 35
1.2	1..1	Request To Modify Payment V06 +Assignment ++Assigner	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Instructing Party. Limited to 'BICFI' to identify a PSP, 'AnyBIC' to identify a CSM or 'LEI' or 'Name' to indicate a CSM when it has no BIC. 'Name' is limited to 70 characters in length. Assigner Party who assigns the case. Usage: This is also the sender of the message. Assgnr Party40Choice
1.3	1..1	Request To Modify Payment V06 +Assignment ++Assignee	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Instructed Party. Limited to 'BICFI' to identify a PSP, 'AnyBIC' to identify a CSM or 'LEI' or 'Name' to indicate a CSM when it has no BIC. 'Name' is limited to 70 characters in length. Assignee Party to which the case is assigned. Usage: This is also the receiver of the message. Assgne Party40Choice
1.4	1..1	Request To Modify Payment V06 +Assignment ++Creation Date Time	ISO Name ISO Definition XML Tag Type	Creation Date Time Date and time at which the assignment was created. CreDtTm ISODateTime
2.0	1..1	Request To Modify Payment V06 +Case	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Mandatory. Case Identifies the investigation case. Case Case5
2.1	1..1	Request To Modify Payment V06 +Case ++Identification	SEPA Rulebook ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	AT-Q002 The specific SCT inquiry reference of the Participant initiating the SCT inquiry. Identification Uniquely identifies the case. Id Max35Text 1 .. 35 1 .. 35

#	SEPA Mult	Message Element	Inter-PSP Inquiry for Claim for Value Date Correction SEPA Core Requirements			
2.2	1..1	Request To Modify Payment V06 +Case ++Creator	SEPA Usage Rule(s) Only 'Agent' is allowed. Limited to 'BICFI' to identify the Originator PSP of the original credit transfer. ISO Name Creator ISO Definition Party that created the investigation case. XML Tag Type Cretr SEPA Length Party40Choice			
2.3	0..1	Request To Modify Payment V06 +Case ++Reopen Case Indication	ISO Name Reopen Case Indication ISO Definition Indicates whether or not the case was previously closed and is now re-opened. XML Tag Type ReopCaseIndctn SEPA Length YesNoIndicator			
3.0	1..1	Request To Modify Payment V06 +Underlying	ISO Name Underlying ISO Definition Identifies the payment transaction to be modified. XML Tag Type Undrlyg SEPA Length UnderlyingTransaction5Choice			
	1..1		XML Tag xs:choice			
3.1	1..1	Request To Modify Payment V06 +Underlying ++Initiation	ISO Name Initiation ISO Definition Set of elements used to reference the details of the original payment initiation. XML Tag Type Initn SEPA Length UnderlyingPaymentInstruction5			
3.2	1..1	Request To Modify Payment V06 +Underlying ++Interbank	ISO Name Interbank ISO Definition Set of elements used to reference the details of the original interbank payment transaction. XML Tag Type IntrBk SEPA Length UnderlyingPaymentTransaction4			
3.3	1..1	Request To Modify Payment V06 +Underlying ++Interbank +++Original Group Information	SEPA Usage Rule(s) Mandatory. ISO Name Original Group Information ISO Definition Set of elements used to provide information on the original message. XML Tag Type OrgnlGrpInf SEPA Length UnderlyingGroupInformation1			
3.4	1..1	Request To Modify Payment V06 +Underlying ++Interbank +++Original Group Information ++++Original Message Identification	ISO Name Original Message Identification ISO Definition Point to point reference, as assigned by the original instructing party, to unambiguously identify the original message. XML Tag Type OrgnlMsgId ISO Length Max35Text SEPA Length 1 .. 35			
3.5	1..1	Request To Modify Payment V06 +Underlying ++Interbank +++Original Group Information ++++Original Message Name Identification	SEPA Usage Rule(s) Must begin with 'pacs.008'. The addition of a variant number and version number is optional. ISO Name Original Message Name Identification ISO Definition Specifies the original message name identifier to which the message refers. XML Tag Type OrgnlMsgNmId ISO Length Max35Text SEPA Length 1 .. 35			
3.6	0..1	Request To Modify Payment V06 +Underlying ++Interbank +++Original Group Information ++++Original Creation Date Time	ISO Name Original Creation Date Time ISO Definition Date and time at which the original message was created. XML Tag Type OrgnlCreDtTm SEPA Length ISODateTime			
3.7	0..1	Request To Modify Payment V06 +Underlying ++Interbank +++Original Group Information ++++Original Message Delivery Channel	ISO Name Original Message Delivery Channel ISO Definition Original channel used for the delivery of the message, to allow the receiver of the request to locate the payment with greater ease. XML Tag Type OrgnlMsgDlvryChnl ISO Length Max35Text SEPA Length 1 .. 35			

#	SEPA Mult	Message Element	Inter-PSP Inquiry for Claim for Value Date Correction SEPA Core Requirements			
3.8	0..1	Request To Modify Payment V06 +Underlying ++Interbank +++Original Instruction Identification	ISO Name ISO Definition	Original Instruction Identification Unique identification, as assigned by the original instructing party for the original instructed party, to unambiguously identify the original instruction.		
			XML Tag Type ISO Length SEPA Length	OrgnlInstrId Max35Text 1 .. 35 1 .. 35		
3.9	1..1	Request To Modify Payment V06 +Underlying ++Interbank +++Original End To End Identification	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition	<i>AT-T014 The Originator's reference of the SEPA Credit Transfer Transaction.</i> <i>Mandatory.</i> Original End To End Identification Unique identification, as assigned by the original initiating party, to unambiguously identify the original transaction.		
			XML Tag Type ISO Length SEPA Length	OrgnlEndToEndId Max35Text 1 .. 35 1 .. 35		
3.10	1..1	Request To Modify Payment V06 +Underlying ++Interbank +++Original Transaction Identification	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition	<i>AT-T054 The Originator PSP's reference of the SEPA Credit Transfer Transaction.</i> <i>Mandatory.</i> Original Transaction Identification Unique identification, as assigned by the original first instructing agent, to unambiguously identify the transaction.		
			XML Tag Type ISO Length SEPA Length	OrgnlTxId Max35Text 1 .. 35 1 .. 35		
3.11	0..1	Request To Modify Payment V06 +Underlying ++Interbank +++Original UETR	ISO Name ISO Definition	Original UETR Universally unique identifier to provide the original end-to-end reference of a payment transaction.		
			XML Tag Type Pattern	OrgnlUETR UUIDv4Identifier [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}		
3.12	1..1	Request To Modify Payment V06 +Underlying ++Interbank +++Original Interbank Settlement Amount	SEPA Rulebook SEPA Usage Rule(s) SEPA Format Rule(s) ISO Name ISO Definition	<i>AT-T002 Amount of the SEPA Credit Transfer in Euro.</i> <i>Only 'EUR' is allowed.</i> <i>Amount must be 0.01 or more and 999999999.99 or less.</i> <i>The fractional part has a maximum of two digits.</i>		
			XML Tag Type SEPA FractDigits TotalDigits SEPA Inclusive	Original Interbank Settlement Amount Amount of money moved between the instructing agent and the instructed agent, as provided in the original instruction. OrgnlIntrBkSttlmAmt ActiveOrHistoricCurrencyAndAmount 2 18 0.01 .. 999999999.99		

#	SEPA Mult	Message Element	Inter-PSP Inquiry for Claim for Value Date Correction SEPA Core Requirements		
3.13	1..1	Request To Modify Payment V06 +Underlying ++Interbank +++Original Interbank Settlement Date	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-T051 Settlement Date of the Credit Transfer.</i> Original Interbank Settlement Date Date, as provided in the original transaction, on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. OrgnlIntrBkSttlmDt ISODate	
3.14	1..1	Request To Modify Payment V06 +Underlying ++Interbank +++Original Transaction Reference	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>An exact copy of all attributes of DS-02 of the initially sent pacs.008 to which the claim refers.</i> Mandatory. <i>The message elements under 'Original Transaction Reference' must be populated with the same value as the message elements of the original instruction.</i> Original Transaction Reference Key elements used to identify the original transaction that is being referred to. OrgnlTxRef OriginalTransactionReference28	
3.15	0..1	Request To Modify Payment V06 +Underlying ++Interbank +++Original Transaction Reference ++++Interbank Settlement Amount	ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits SEPA Inclusive	Interbank Settlement Amount Amount of money moved between the instructing agent and the instructed agent. IntrBkSttlmAmt ActiveOrHistoricCurrencyAndAmount 5 18 0 ..	
3.16	0..1	Request To Modify Payment V06 +Underlying ++Interbank +++Original Transaction Reference ++++Amount	ISO Name ISO Definition XML Tag Type	Amount Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party. Amt AmountType4Choice	
3.17	0..1	Request To Modify Payment V06 +Underlying ++Interbank +++Original Transaction Reference ++++Interbank Settlement Date	ISO Name ISO Definition XML Tag Type	Interbank Settlement Date Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. IntrBkSttlmDt ISODate	
3.18	0..1	Request To Modify Payment V06 +Underlying ++Interbank +++Original Transaction Reference ++++Requested Collection Date	ISO Name ISO Definition XML Tag Type	Requested Collection Date Date and time at which the creditor requests that the amount of money is to be collected from the debtor. ReqdColltnDt ISODate	
3.19	0..1	Request To Modify Payment V06 +Underlying ++Interbank +++Original Transaction Reference ++++Requested Execution Date	ISO Name ISO Definition XML Tag Type	Requested Execution Date Date at which the initiating party requests the clearing agent to process the payment. Usage: This is the date on which the debtor's account is to be debited. If payment by cheque, the date when the cheque must be generated by the bank. ReqdExctnDt DateAndDateTime2Choice	
3.20	0..1	Request To Modify Payment V06 +Underlying ++Interbank +++Original Transaction Reference ++++Creditor Scheme Identification	ISO Name ISO Definition XML Tag Type	Creditor Scheme Identification Credit party that signs the mandate. CdtrSchmeId PartyIdentification135	

#	SEPA Mult	Message Element	Inter-PSP Inquiry for Claim for Value Date Correction SEPA Core Requirements	
3.21	0..1	Request To Modify Payment V06 +Underlying ++Interbank +++Original Transaction Reference ++++Settlement Information	ISO Name XML Tag Type	Settlement Information Specifies the details on how the settlement of the original transaction(s) between the instructing agent and the instructed agent was completed. Stlmlnfo SettlementInstruction7
3.22	0..1	Request To Modify Payment V06 +Underlying ++Interbank +++Original Transaction Reference ++++Payment Type Information	SEPA Rulebook ISO Name XML Tag Type	<i>AT-T001 Identification code of the Scheme.</i> <i>AT-T008 Category Purpose of the Credit Transfer.</i> <i>If the original transaction was sent according to Annex V (Use of Extended Remittance Information) of the SCT Rulebook (refer to section 'Inter-PSP payment with use of the Extended Remittance Information option' below), then 'Local Instrument/Code' must be populated with "PERI" (Payment with Extended Remittance Information).</i> Payment Type Information Set of elements used to further specify the type of transaction. PmtTpInf PaymentTypeInformation27
3.23	0..1	Request To Modify Payment V06 +Underlying ++Interbank +++Original Transaction Reference ++++Payment Method	ISO Name XML Tag Type	Payment Method Specifies the means of payment that will be used to move the amount of money. PmtMtd PaymentMethod4Code
3.24	0..1	Request To Modify Payment V06 +Underlying ++Interbank +++Original Transaction Reference ++++Mandate Related Information	ISO Name XML Tag Type	Mandate Related Information Provides further details of the mandate signed between the creditor and the debtor. MndtRltdInf MandateRelatedInformation14
3.25	0..1	Request To Modify Payment V06 +Underlying ++Interbank +++Original Transaction Reference ++++Remittance Information	SEPA Rulebook ISO Name XML Tag Type	<i>AT-T009 Remittance information or AT-T010 The unstructured Remittance Information sent by the Originator to the Beneficiary in the Credit Transfer Instruction (in case of use of the Extended Remittance Information (ERI)option in the original SEPA Credit Transfer, AT-T011 The structured Remittance Information sent by the Originator to the Beneficiary in the SEPA Credit Transfer Instruction, will NOT be transported here.</i> Remittance Information Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system. Rmtlnf RemittanceInformation16
3.26	0..1	Request To Modify Payment V06 +Underlying ++Interbank +++Original Transaction Reference ++++Ultimate Debtor	SEPA Rulebook SEPA Usage Rule(s) ISO Name XML Tag Type	<i>AT-P006 The name of the Originator Reference Party.</i> <i>AT-P007 The identification code of the Originator Reference Party.</i> <i>Only 'Party' is allowed.</i> Ultimate Debtor Ultimate party that owes an amount of money to the (ultimate) creditor. UltmtDbtr Party40Choice

#	SEPA Mult	Message Element	Inter-PSP Inquiry for Claim for Value Date Correction SEPA Core Requirements	
3.27	0..1	Request To Modify Payment V06 +Underlying ++Interbank +++Original Transaction Reference ++++Debtor	SEPA Rulebook SEPA Usage Rule(s) Only 'Party' is allowed. ISO Name ISO Definition Party that owes an amount of money to the (ultimate) creditor. XML Tag Type Dbtr Party40Choice	<i>AT-P001 Name of the Originator.</i> <i>AT-P005 Address of the Originator.</i> <i>AT-P004 Originator's Identification Code.</i> <i>AT-D001 The IBAN of the account of the Originator.</i> <i>AT-P003 The Proxy/Alias of the account of the Originator.</i> ISO Name ISO Definition Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction. XML Tag Type DbtrAcct CashAccount38
3.28	0..1	Request To Modify Payment V06 +Underlying ++Interbank +++Original Transaction Reference ++++Debtor Account	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-D001 The IBAN of the account of the Originator.</i> <i>AT-P003 The Proxy/Alias of the account of the Originator.</i> ISO Name ISO Definition Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction. XML Tag Type DbtrAcct CashAccount38
3.29	0..1	Request To Modify Payment V06 +Underlying ++Interbank +++Original Transaction Reference ++++Debtor Agent	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-D002 The BIC code of the Originator PSP.</i> ISO Name ISO Definition Financial institution servicing an account for the debtor. XML Tag Type DbtrAgt BranchAndFinancialInstitutionIdentification6
3.30	0..1	Request To Modify Payment V06 +Underlying ++Interbank +++Original Transaction Reference ++++Debtor Agent Account	ISO Name ISO Definition XML Tag Type	ISO Name ISO Definition Debtor Agent Account Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain. XML Tag Type DbtrAgtAcct CashAccount38
3.31	0..1	Request To Modify Payment V06 +Underlying ++Interbank +++Original Transaction Reference ++++Creditor Agent	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-C002 The BIC code of the Beneficiary PSP.</i> ISO Name ISO Definition Financial institution servicing an account for the creditor. XML Tag Type CdtrAgt BranchAndFinancialInstitutionIdentification6
3.32	0..1	Request To Modify Payment V06 +Underlying ++Interbank +++Original Transaction Reference ++++Creditor Agent Account	ISO Name ISO Definition XML Tag Type	ISO Name ISO Definition Creditor Agent Account Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction. XML Tag Type CdtrAgtAcct CashAccount38
3.33	0..1	Request To Modify Payment V06 +Underlying ++Interbank +++Original Transaction Reference ++++Creditor	SEPA Rulebook SEPA Usage Rule(s) Only 'Party' is allowed. ISO Name ISO Definition XML Tag Type	<i>AT-E001 Name of the Beneficiary.</i> <i>AT-E004 Address of the Beneficiary.</i> <i>AT-E005 Beneficiary Identification Code.</i> ISO Name ISO Definition Party to which an amount of money is due. XML Tag Type Cdtr Party40Choice
3.34	0..1	Request To Modify Payment V06 +Underlying ++Interbank +++Original Transaction Reference ++++Creditor Account	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-C001 The IBAN of the account of the Beneficiary.</i> <i>AT-E003 The Proxy/Alias of the account of the Beneficiary.</i> ISO Name ISO Definition Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction. XML Tag Type CdtrAcct CashAccount38

#	SEPA Mult	Message Element	Inter-PSP Inquiry for Claim for Value Date Correction SEPA Core Requirements	
3.35	0..1	Request To Modify Payment V06 +Underlying ++Interbank +++Original Transaction Reference ++++Ultimate Creditor	<p>SEPA Rulebook</p> <p>SEPA Usage Rule(s) Only 'Party' is allowed.</p> <p>ISO Name Ultimate Creditor</p> <p>ISO Definition Ultimate party to which an amount of money is due.</p> <p>XML Tag Type UltmtCdr Party40Choice</p>	<p><i>AT-E007 The name of the Beneficiary Reference Party.</i></p> <p><i>AT-E010 The identification code of the Beneficiary Reference Party.</i></p>
3.36	0..1	Request To Modify Payment V06 +Underlying ++Interbank +++Original Transaction Reference ++++Purpose	<p>SEPA Rulebook</p> <p>ISO Name Purpose</p> <p>ISO Definition Underlying reason for the payment transaction.</p> <p>XML Tag Type</p>	<p><i>AT-T007 The purpose of the SEPA Credit Transfer.</i></p> <p>Usage: Purpose is used by the end customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain.</p> <p>Purp Purpose2Choice</p>
3.37	1..1	Request To Modify Payment V06 +Underlying ++Statement Entry	<p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p>Statement Entry Reference details on the underlying statement cash entry.</p> <p>StmtNtry UnderlyingStatementEntry3</p>
4.0	1..1	Request To Modify Payment V06 +Modification	<p>SEPA Usage Rule(s) Only 'Inter-PSP Settlement Date' is allowed.</p> <p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p>Modification Identifies the list of modifications requested.</p> <p>Mod RequestedModification8</p>
4.1	1..1	Request To Modify Payment V06 +Modification ++Interbank Settlement Date	<p>SEPA Usage Rule(s) Mandatory.</p> <p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p>Contains the inter-PSP settlement date to be applied by the Beneficiary PSP, as a consequence:</p> <ul style="list-style-type: none"> - If the 'Interbank Settlement Date' of the initial pacs.008 was correct: AT-T051 'Settlement Date of the Credit Transfer in Euro' must be provided (as part of AT-Q003 'Additional Information to AT-Q001 SCT Inquiry reason code' i.e. the initially expected settlement date). - If the 'Interbank Settlement' Date of the initial pacs.008 was incorrect: the new requested 'Interbank Settlement' Date must be provided. <p>Interbank Settlement Date Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.</p> <p>IntrBkSttlmDt ISODate</p>

#	SEPA Mult	Message Element	Inter-PSP Inquiry for Claim for Value Date Correction SEPA Core Requirements	
5.0	0..1	Request To Modify Payment V06 +Instruction For Assignee	<p>SEPA Rulebook <i>AT-Q003 Additional Information to AT-Q001 SCT inquiry reason code</i></p> <p>SEPA Usage Rule(s) <i>If used to accommodate AT-Q003, the first 20 characters must refer to the date and time at which the Originator PSP received the credit transfer instruction from the Originator. Such date and time must be expressed in the ISO format YYYY-MM-DDThh:mm:ssZ.</i></p> <p>ISO Name ISO Definition Instruction For Assignee Further information related to the processing of the investigation that may need to be acted upon by the assignee.</p> <p>XML Tag Type InstrForAssgne InstructionForAssignee1</p>	
5.1	1..1	Request To Modify Payment V06 +Instruction For Assignee ++Code	<p>SEPA Usage Rule(s) <i>Mandatory. Only "INQR" is allowed.</i></p> <p>ISO Name ISO Definition Code Coded information related to the processing of the investigation instruction, provided by the assigner, and intended for the assignee.</p> <p>XML Tag Type ISO Length SEPA Length Cd ExternalAgentInstruction1Code 1 .. 4 1 .. 4</p> <p>SEPA Code Restrictions</p> <p>INQR <i>InquiryReason Additional Information to an inquiry reason must be provided.</i></p>	
5.2	1..1	Request To Modify Payment V06 +Instruction For Assignee ++Instruction Information	<p>SEPA Usage Rule(s) <i>Mandatory. The text shall be in a comprehensible language to the Scheme Participant receiving the SCT inquiry who is obliged to act upon this.</i></p> <p>ISO Name ISO Definition Instruction Information Further information complementing the coded instruction or instruction to the assignee.</p> <p>XML Tag Type ISO Length SEPA Length InstrInf Max140Text 1 .. 140 1 .. 140</p>	
6.0	0..n	Request To Modify Payment V06 +Supplementary Data	<p>ISO Name ISO Definition Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block.</p> <p>XML Tag Type SplmtryData SupplementaryData1</p>	



2.16 Inter-PSP Negative Response to Claim for Value Date Correction (DS-10)

2.16.1 Use of Resolution of Investigation (camt.029.001.09)

This message is used to transmit a negative response to a:

- Claim for Value Date Correction message (Request To Modify Payment, camt.087.001.06);
- Request for Status Update on a Claim for Value Date Correction message (FI-to-FI Payment Status Request, pacs.028.001.03, refer to section 'Request for Status Update on a SCT Inquiry' below);

where the following applies:

- Index 3.0 'Status': only sub-element 'Confirmation' is allowed, populated with "RJVA" (Rejected Value date Adjustment) or "CVAA" (Correct Value date Already Applied).

In the context of a Claim for Value Date Correction, the message caters for a single response only.

Note: The use case of the message is implied by the 'Message Name', 'camt.029.001.09', the 'Original Message Name Identification' must begin with pacs.008 (the addition of a variant number and version number is optional) and 'Status' set to either "RJVA" or "CVAA".

Note: Message elements under 'Original Transaction Reference' sequence are based on DS-02 attributes.

Note: A negative response implies that a Claim for Value Date Correction is rejected by the receiving party.

#	SEPA Mult	Message Element	Inter-PSP Negative Response to Claim for Value Date Correction SEPA Core Requirements	
		Document	XML Tag Type	Document Document
	1..1	Resolution Of Investigation V09	ISO Name ISO Definition	Resolution Of Investigation V09 The ResolutionOfInvestigation message is sent by a case assignee to a case creator/case assigner. This message is used to inform of the resolution of a case, and optionally provides details about: - the corrective action undertaken by the case assignee - information on the return where applicable RsltOfInvstgn ResolutionOfInvestigationV09
1.0	1..1	Resolution Of Investigation V09 +Assignment	ISO Name ISO Definition XML Tag Type	Assignment Identifies the assignment of an investigation case from an assigner to an assignee. Usage: The assigner must be the sender of this confirmation and the assignee must be the receiver. Assgnmt CaseAssignment5
1.1	1..1	Resolution Of Investigation V09 +Assignment ++Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Identification Uniquely identifies the case assignment. Id Max35Text 1 .. 35 1 .. 35
1.2	1..1	Resolution Of Investigation V09 +Assignment ++Assigner	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Instructing Party. Limited to 'BICFI' to identify a PSP, 'AnyBIC' to identify a CSM or 'LEI' or 'Name' to indicate a CSM when it has no BIC. 'Name' is limited to 70 characters in length. Assigner Party who assigns the case. Usage: This is also the sender of the message. Assgnr Party40Choice
1.3	1..1	Resolution Of Investigation V09 +Assignment ++Assignee	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Instructed Party. Limited to 'BICFI' to identify a PSP, 'AnyBIC' to identify a CSM or 'LEI' or 'Name' to indicate a CSM when it has no BIC. 'Name' is limited to 70 characters in length. Assignee Party to which the case is assigned. Usage: This is also the receiver of the message. Assgne Party40Choice
1.4	1..1	Resolution Of Investigation V09 +Assignment ++Creation Date Time	ISO Name ISO Definition XML Tag Type	Creation Date Time Date and time at which the assignment was created. CreDtTm ISODateTime
2.0	1..1	Resolution Of Investigation V09 +Resolved Case	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Mandatory. Resolved Case Identifies a resolved case. RslvdCase Case5

#	SEPA Mult	Message Element	Inter-PSP Negative Response to Claim for Value Date Correction SEPA Core Requirements	
2.1	1..1	Resolution Of Investigation V09 +Resolved Case ++Identification	SEPA Rulebook ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>AT-Q002 The specific SCT inquiry reference of the Participant initiating the SCT inquiry.</i> Identification Uniquely identifies the case. Id Max35Text 1 .. 35 1 .. 35
2.2	1..1	Resolution Of Investigation V09 +Resolved Case ++Creator	SEPA Usage Rule(s) <i>Only 'Agent' is allowed.</i> <i>Limited to 'BICFI' to identify the Originator PSP of the original credit transfer.</i> ISO Name ISO Definition XML Tag Type	Creator Party that created the investigation case. Cretr Party40Choice
2.3	0..1	Resolution Of Investigation V09 +Resolved Case ++Reopen Case Indication	ISO Name ISO Definition XML Tag Type	Reopen Case Indication Indicates whether or not the case was previously closed and is now re-opened. ReopCaseIndctn YesNoIndicator
3.0	1..1	Resolution Of Investigation V09 +Status	SEPA Usage Rule(s) <i>Only 'Confirmation' is allowed.</i> ISO Name ISO Definition XML Tag Type	Status Indicates the status of the investigation. Sts InvestigationStatus5Choice
	1..1		XML Tag	xs:choice
3.1	1..1	Resolution Of Investigation V09 +Status ++Confirmation	SEPA Usage Rule(s) <i>Only "CVA" or "RJVA" are allowed.</i> ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Confirmation Specifies the status of the investigation, in a coded form. Conf ExternalInvestigationExecutionConfirmation1Code 1 .. 4 1 .. 4
			SEPA Code Restrictions	
			CVA	<i>CorrectValueDateAlreadyApplied</i> <i>The original value date was correct.</i>
			RJVA	<i>RejectedValueDateAdjustment</i> <i>The claim for value date correction is rejected.</i>
3.2	1..n	Resolution Of Investigation V09 +Status ++Rejected Modification	ISO Name ISO Definition XML Tag Type	Rejected Modification Reason for the rejection of a modification request, in a coded form. RjctdMod ModificationStatusReason1Choice
3.3	1..1	Resolution Of Investigation V09 +Status ++Duplicate Of	ISO Name ISO Definition XML Tag Type	Duplicate Of Indicates a duplicated case. Usage: When present, the case identified in the message must be closed. The case identified as duplicated (in this component) will be pursued. DplctOf Case5

#	SEPA Mult	Message Element	Inter-PSP Negative Response to Claim for Value Date Correction SEPA Core Requirements	
3.4	1..1	Resolution Of Investigation V09 +Status ++Assignment Cancellation Confirmation	ISO Name ISO Definition XML Tag Type	Assignment Cancellation Confirmation Indicates whether the cancellation of the assignment is confirmed or rejected. Usage: If yes, the cancellation of the assignment is confirmed. If no, the cancellation of the assignment is rejected and the investigation process will continue. AssgnmtCxlConf YesNoIndicator
4.0	0..n	Resolution Of Investigation V09 +Cancellation Details	ISO Name ISO Definition XML Tag Type	Cancellation Details Specifies the details of the underlying transactions being cancelled. CxlDtls UnderlyingTransaction22
5.0	1..1	Resolution Of Investigation V09 +Modification Details	SEPA Usage Rule(s) <i>Mandatory.</i> ISO Name ISO Definition XML Tag Type	Modification Details Specifies the details of the underlying transaction being modified. ModDtls PaymentTransaction107
5.1	1..1	Resolution Of Investigation V09 +Modification Details ++Modification Status Identification	SEPA Usage Rule(s) <i>Mandatory.</i> ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Modification Status Identification Unique and unambiguous identifier of a modification request status, as assigned by the assigner. Usage: The modification status identification can be used for reconciliation or to link tasks relating to the modification request. ModStsId Max35Text 1 .. 35 1 .. 35
5.2	0..1	Resolution Of Investigation V09 +Modification Details ++Resolved Case	ISO Name ISO Definition XML Tag Type	Resolved Case Identifies the resolved case. RslvdCase Case5
5.3	1..1	Resolution Of Investigation V09 +Modification Details ++Original Group Information	ISO Name ISO Definition XML Tag Type	Original Group Information Provides information on the original message. OrgnlGrpInf OriginalGroupInformation29
5.4	1..1	Resolution Of Investigation V09 +Modification Details ++Original Group Information +++Original Message Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Message Identification Point to point reference assigned by the original instructing party to unambiguously identify the original message. OrgnlMsgId Max35Text 1 .. 35 1 .. 35
5.5	1..1	Resolution Of Investigation V09 +Modification Details ++Original Group Information +++Original Message Name Identification	SEPA Usage Rule(s) <i>Must begin with 'pacs.008'. The addition of a variant number and version number is optional.</i> ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Message Name Identification Specifies the original message name identifier to which the message refers, for example, pacs.003.001.01 or MT103. OrgnlMsgNmId Max35Text 1 .. 35 1 .. 35

#	SEPA Mult	Message Element	Inter-PSP Negative Response to Claim for Value Date Correction SEPA Core Requirements	
5.6	0..1	Resolution Of Investigation V09 +Modification Details ++Original Group Information +++Original Creation Date Time	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Creation Date Time Original date and time at which the message was created. OrgnlCreDtTm ISODateTime
5.7	0..1	Resolution Of Investigation V09 +Modification Details ++Original Payment Information Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Payment Information Identification Unique identification, as assigned by the original sending party, to unambiguously identify the original payment information group. OrgnPmtInfId Max35Text 1 .. 35 1 .. 35
5.8	0..1	Resolution Of Investigation V09 +Modification Details ++Original Instruction Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Instruction Identification Unique identification, as assigned by the original instructing party for the original instructed party, to unambiguously identify the original instruction. OrgnInstrId Max35Text 1 .. 35 1 .. 35
5.9	1..1	Resolution Of Investigation V09 +Modification Details ++Original End To End Identification	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	AT-T014 The Originator's reference of the SEPA Credit Transfer Transaction. Mandatory. Original End To End Identification Unique identification, as assigned by the original initiating party, to unambiguously identify the original transaction. OrgnEndToEndId Max35Text 1 .. 35 1 .. 35
5.10	1..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Identification	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	AT-T054 The Originator PSP's reference of the SEPA Credit Transfer Transaction. Mandatory. Original Transaction Identification Unique identification, as assigned by the original first instructing agent, to unambiguously identify the transaction. OrgnTxId Max35Text 1 .. 35 1 .. 35
5.11	0..1	Resolution Of Investigation V09 +Modification Details ++Original Clearing System Reference	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Clearing System Reference Unique reference, as assigned by the original clearing system, to unambiguously identify the original instruction. OrgnClrSysRef Max35Text 1 .. 35 1 .. 35
5.12	0..1	Resolution Of Investigation V09 +Modification Details ++Original UETR	ISO Name ISO Definition XML Tag Type Pattern	Original UETR Universally unique identifier to provide the original end-to-end reference of a payment transaction. OrgnUETR UUIDv4Identifier [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}

#	SEPA Mult	Message Element	Inter-PSP Negative Response to Claim for Value Date Correction SEPA Core Requirements	
5.13	0..n	Resolution Of Investigation V09 +Modification Details ++Modification Status Reason Information	ISO Name ISO Definition XML Tag Type	Modification Status Reason Information Provides detailed information on the modification status reason. ModStsRsnInf ModificationStatusReason2
5.14	0..1	Resolution Of Investigation V09 +Modification Details ++Resolution Related Information	ISO Name ISO Definition XML Tag Type	Resolution Related Information Reference of a return or a reversal transaction that is initiated to fix the case under investigation as part of the resolution. RsltnRltdInf ResolutionData1
5.15	0..1	Resolution Of Investigation V09 +Modification Details ++Original Interbank Settlement Amount	ISO Name ISO Definition XML Tag Type <i>SEPA FractDigits</i> TotalDigits <i>SEPA Inclusive</i>	Original Interbank Settlement Amount Amount of money moved between the instructing agent and the instructed agent, as provided in the original instruction. OrgnlIntrBkSttlmAmt ActiveOrHistoricCurrencyAndAmount 5 18 0 ..
5.16	0..1	Resolution Of Investigation V09 +Modification Details ++Original Interbank Settlement Date	ISO Name ISO Definition XML Tag Type	Original Interbank Settlement Date Date, as provided in the original transaction, on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. OrgnlIntrBkSttlmDt ISODate
5.17	0..1	Resolution Of Investigation V09 +Modification Details ++Assigner	ISO Name ISO Definition XML Tag Type	Assigner Party who assigns the case. Usage: This is also the agent that instructs the next party in the chain to carry out the (set of) cancellation request(s). Assgnr Party40Choice
5.18	0..1	Resolution Of Investigation V09 +Modification Details ++Assignee	ISO Name ISO Definition XML Tag Type	Assignee Party to which the case is assigned. Usage: This is also the agent that is instructed by the previous party in the chain to carry out the (set of) cancellation request(s). Assgne Party40Choice
5.19	1..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference	<i>SEPA Rulebook</i> <i>SEPA Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	An exact copy of all attributes of DS-02 of the initially sent pacs.008 to which the claim refers. The yellow shaded message elements under 'Original Transaction Reference' must be populated with the same value as the message elements of the original instruction. Mandatory. Original Transaction Reference Key elements used to identify the original transaction that is being referred to. OrgnlTxRef OriginalTransactionReference28

#	SEPA Mult	Message Element	Inter-PSP Negative Response to Claim for Value Date Correction SEPA Core Requirements	
5.20	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Interbank Settlement Amount	SEPA Rulebook ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits SEPA Inclusive	<i>AT-T002 Amount of the SEPA Credit Transfer in Euro.</i> Interbank Settlement Amount Amount of money moved between the instructing agent and the instructed agent. IntrBkStlmtAmt ActiveOrHistoricCurrencyAndAmount 2 18 0.01 .. 999999999.99
5.21	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Amount	ISO Name ISO Definition XML Tag Type	Amount Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party. Amt AmountType4Choice
5.22	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Interbank Settlement Date	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-T051 Settlement Date of the Credit Transfer in Euro</i> Interbank Settlement Date Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. IntrBkStlmtDt ISODate
5.23	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Requested Collection Date	ISO Name ISO Definition XML Tag Type	Requested Collection Date Date and time at which the creditor requests that the amount of money is to be collected from the debtor. ReqdColltnDt ISODate
5.24	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Requested Execution Date	ISO Name ISO Definition XML Tag Type	Requested Execution Date Date at which the initiating party requests the clearing agent to process the payment. Usage: This is the date on which the debtor's account is to be debited. If payment by cheque, the date when the cheque must be generated by the bank. ReqdExctnDt DateAndDateTime2Choice
5.25	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Creditor Scheme Identification	ISO Name ISO Definition XML Tag Type	Creditor Scheme Identification Credit party that signs the mandate. CdtrSchmeId PartyIdentification135
5.26	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Settlement Information	ISO Name ISO Definition XML Tag Type	Settlement Information Specifies the details on how the settlement of the original transaction(s) between the instructing agent and the instructed agent was completed. SttlmInf SettlementInstruction7

#	SEPA Mult	Message Element	Inter-PSP Negative Response to Claim for Value Date Correction SEPA Core Requirements	
5.27	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Payment Type Information	<p>SEPA Rulebook</p> <p>If the original transaction was sent according to Annex V (Use of Extended Remittance Information) of the SCT Rulebook (refer to section 'Inter-PSP payment with use of the Extended Remittance Information option' below), then 'Local Instrument/Code' must be populated with "PERI" (Payment with Extended Remittance Information).</p> <p>ISO Name ISO Definition</p> <p>Payment Type Information Set of elements used to further specify the type of transaction.</p> <p>XML Tag Type</p> <p>PmtTpInf PaymentTypeInformation27</p>	<p>AT-T001 Identification code of the Scheme. AT-T008 Category Purpose of the Credit Transfer.</p>
5.28	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Payment Method	<p>ISO Name ISO Definition</p> <p>Specifies the means of payment that will be used to move the amount of money.</p> <p>XML Tag Type</p> <p>PmtMtd PaymentMethod4Code</p>	<p>Payment Method</p>
5.29	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Mandate Related Information	<p>ISO Name ISO Definition</p> <p>Provides further details of the mandate signed between the creditor and the debtor.</p> <p>XML Tag Type</p> <p>MndtRltdInf MandateRelatedInformation14</p>	<p>Mandate Related Information</p>
5.30	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Remittance Information	<p>SEPA Rulebook</p> <p>AT-T009 Remittance information or AT-T010 The unstructured Remittance Information sent by the Originator to the Beneficiary in the Credit Transfer Instruction (in case of use of the Extended Remittance Information (ERI) option in the original SEPA Credit Transfer, AT-T011 The structured Remittance Information sent by the Originator to the Beneficiary in the SEPA Credit Transfer Instruction, will NOT be transported here).</p> <p>ISO Name ISO Definition</p> <p>Remittance Information Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system.</p> <p>XML Tag Type</p> <p>RmtInf RemittanceInformation16</p>	<p>AT-T009 Remittance information or AT-T010 The unstructured Remittance Information sent by the Originator to the Beneficiary in the Credit Transfer Instruction (in case of use of the Extended Remittance Information (ERI) option in the original SEPA Credit Transfer, AT-T011 The structured Remittance Information sent by the Originator to the Beneficiary in the SEPA Credit Transfer Instruction, will NOT be transported here).</p>
5.31	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Ultimate Debtor	<p>SEPA Rulebook</p> <p>AT-P006 The name of the Originator Reference Party. AT-P007 The identification code of the Originator Reference Party.</p> <p>SEPA Usage Rule(s)</p> <p>Only 'Party' is allowed.</p> <p>ISO Name ISO Definition</p> <p>Ultimate Debtor Ultimate party that owes an amount of money to the (ultimate) creditor.</p> <p>XML Tag Type</p> <p>UltmtDbtr Party40Choice</p>	<p>AT-P006 The name of the Originator Reference Party. AT-P007 The identification code of the Originator Reference Party.</p>
5.32	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Debtor	<p>SEPA Rulebook</p> <p>AT-P001 Name of the Originator. AT-P005 Address of the Originator. AT-P004 Originator's Identification Code.</p> <p>SEPA Usage Rule(s)</p> <p>Only 'Party' is allowed.</p> <p>ISO Name ISO Definition</p> <p>Debtor Party that owes an amount of money to the (ultimate) creditor.</p> <p>XML Tag Type</p> <p>Dbtr Party40Choice</p>	<p>AT-P001 Name of the Originator. AT-P005 Address of the Originator. AT-P004 Originator's Identification Code.</p>

#	SEPA Mult	Message Element	Inter-PSP Negative Response to Claim for Value Date Correction SEPA Core Requirements		
5.33	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Debtor Account	<i>SEPA Rulebook</i> ISO Name ISO Definition XML Tag Type	<i>AT-D001 The IBAN of the account of the Originator.</i> <i>AT-P003 The Proxy/Alias of the account of the Originator.</i> Debtor Account Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction. DbtrAcct CashAccount38	
5.34	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Debtor Agent	<i>SEPA Rulebook</i> ISO Name ISO Definition XML Tag Type	<i>AT-D002 The BIC code of the Originator PSP.</i> Debtor Agent Financial institution servicing an account for the debtor. DbtrAgt BranchAndFinancialInstitutionIdentification6	
5.35	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Debtor Agent Account	 ISO Name ISO Definition XML Tag Type	Debtor Agent Account Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain. DbtrAgtAcct CashAccount38	
5.36	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Creditor Agent	<i>SEPA Rulebook</i> ISO Name ISO Definition XML Tag Type	<i>AT-C002 The BIC code of the Beneficiary PSP.</i> Creditor Agent Financial institution servicing an account for the creditor. CdtrAgt BranchAndFinancialInstitutionIdentification6	
5.37	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Creditor Agent Account	 ISO Name ISO Definition XML Tag Type	Creditor Agent Account Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction. CdtrAgtAcct CashAccount38	
5.38	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Creditor	<i>SEPA Rulebook</i> <i>SEPA Usage Rule(s)</i> Only 'Party' is allowed. ISO Name ISO Definition XML Tag Type	<i>AT-E001 Name of the Beneficiary.</i> <i>AT-E004 Address of the Beneficiary.</i> <i>AT-E005 Beneficiary Identification Code.</i> Creditor Party to which an amount of money is due. Cdtr Party40Choice	
5.39	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Creditor Account	<i>SEPA Rulebook</i> ISO Name ISO Definition XML Tag Type	<i>AT-C001 The IBAN of the account of the Beneficiary.</i> <i>AT-E003 The Proxy/Alias of the account of the Beneficiary.</i> Creditor Account Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction. CdtrAcct CashAccount38	

#	SEPA Mult	Message Element	Inter-PSP Negative Response to Claim for Value Date Correction SEPA Core Requirements	
5.40	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Ultimate Creditor	<p>SEPA Rulebook</p> <p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p><i>AT-E007 The name of the Beneficiary Reference Party.</i></p> <p><i>AT-E010 The identification code of the Beneficiary Reference Party.</i></p> <p>SEPA Usage Rule(s) Only 'Party' is allowed.</p> <p>Ultimate Creditor</p> <p>Ultimate party to which an amount of money is due.</p> <p>UltmtCdtr</p> <p>Party40Choice</p>
5.41	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Purpose	<p>SEPA Rulebook</p> <p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p><i>AT-T007 The purpose of the SEPA Credit Transfer.</i></p> <p>Purpose</p> <p>Underlying reason for the payment transaction.</p> <p>Usage: Purpose is used by the end customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain.</p> <p>Purp</p> <p>Purpose2Choice</p>
6.0	0..1	Resolution Of Investigation V09 +Claim Non Receipt Details	<p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p>Claim Non Receipt Details</p> <p>Specifies the details of the underlying transaction for which a claim non receipt has been initiated.</p> <p>ClmNonRctDtls</p> <p>ClaimNonReceipt2Choice</p>
7.0	0..1	Resolution Of Investigation V09 +Statement Details	<p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p>Statement Details</p> <p>Details on the underlying statement entry.</p> <p>StmtDtls</p> <p>StatementResolutionEntry4</p>
8.0	0..1	Resolution Of Investigation V09 +Correction Transaction	<p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p>Correction Transaction</p> <p>References a transaction initiated to fix the case under investigation.</p> <p>CrrctnTx</p> <p>CorrectiveTransaction4Choice</p>
9.0	0..1	Resolution Of Investigation V09 +Resolution Related Information	<p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p>Resolution Related Information</p> <p>Reference to fix the case under investigation as part of the resolution.</p> <p>RsltnRltdInf</p> <p>ResolutionData1</p>
10.0	0..n	Resolution Of Investigation V09 +Supplementary Data	<p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p>Supplementary Data</p> <p>Additional information that cannot be captured in the structured elements and/or any other specific block.</p> <p>SplmtryData</p> <p>SupplementaryData1</p>



2.17 Inter-PSP Positive Response to Claim for Value Date Correction (DS-10) with request for inter-PSP fee and/or interest compensation

2.17.1 Use of Resolution of Investigation (camt.029.001.09)

This message is used to transmit a positive response to a:

- Claim for Value Date Correction message (Request To Modify Payment, camt.087.001.06);
- Request for Status Update on a Claim for Value Date Correction message (FI-to-FI Payment Status Request, pacs.028.001.03, refer to section 'Request for Status Update on a SCT Inquiry' below);

by requesting payment of inter-PSP fee and/or interest compensation before applying the value date correction (as per Rulebook requirement 'the Beneficiary PSP has the right to receive interest compensation and/or a fee from the Originator PSP'), where the following apply:

- Index 3.0 'Status': only sub-element 'Confirmation' is allowed, populated with "ACVA" (Accepted Value Date Adjustment) only.
- Under index 9.0 'Resolution Related Information', only following elements are allowed:
 - Index 9.5 'Interbank Settlement Date' to accommodate AT-Q005 'New value date of the credit transfer based on the new settlement date';
 - Index 9.7 'Compensation' and relevant sub-elements to accommodate AT-Q006 'The interest compensation recovered by the Beneficiary PSP from the Originator PSP';
 - Index 9.22 'Compensation/Reason', only "VADA" (Value Date Adjustment) is allowed;
 - Index 9.23 'Charges' and relevant sub-elements to accommodate AT-Q007 'Fee for handling the SCT Inquiry'.

In the context of a Claim for Value Date Correction, the message caters for a single response only.

Note: The use case of the message is implied by the 'Message Name', 'camt.029.001.09', the 'Original Message Name Identification' must begin with pacs.008 (the addition of a variant number and version number is optional) and 'Status' set to "ACVA".

Note: Message elements under 'Original Transaction Reference' sequence are based on DS-02 attributes.

Important note: When payment of inter-PSP fee and/or interest compensation is requested by the Beneficiary PSP, the value date adjustment will be applied by the Beneficiary PSP only after its payment.

After having taken notice of the payment of the inter-PSP fee and/or interest compensation, **the Beneficiary PSP will send a confirmation message to the Originator PSP** in order to confirm the application of the value date adjustment, please refer to the section 'Inter-PSP Confirmed Positive Response to Claim for Value Date Correction' below.



If compensation and/or charges are claimed in the present response then no compensation and/or charges can be claimed in the Confirmed Positive Response (see section 2.18.1).

The payment of the inter-PSP fee and/or interest compensation is to be effectuated according to the current inter-PSP practices related to such matters. It is recommended* to use the DS-11 pacs.008 (i.e. at least the DS-11 'Credit Transfer Transaction Information' block in case of a DS-02/DS-11 mix) as described for this specific usage as per below section 'Inter-PSP Fee and/or Compensation Payment'. When paying the inter-PSP fee and/or interest compensation, the Originator PSP must provide 'AT-Q002 The specific SCT inquiry reference of the Participant initiating the SCT inquiry' and 'AT-Q009 Reference of the Beneficiary PSP for inter-PSP fee and/or compensation payment' to allocate the payment to the right case. Moreover, the IBAN provided under 'Resolution Related Information/Compensation' or 'Resolution Related Information/Charges' is the one corresponding to AT-Q008 'The IBAN of the account to be credited at the Beneficiary PSP' in the inter-PSP payment message.

The rulebook stipulates that "The Beneficiary PSP must provide a Response-to-SCT-inquiry message about the concerned SCT inquiry within 10 Banking Business Days after it has received the SCT inquiry message" (for further information please see section 4.4.2 of the SCT Rulebook).

In case of a first positive response (camt.029) requesting payment of an inter-PSP fee and/or interest compensation and followed by a second one to confirm, please note that the above timeframe only applies to the first response, which reflects the position of the Beneficiary PSP. This in view of the fact that the aim of the SCT inquiry is to get information about the concrete fate of the original SCT transaction, i.e. has the Beneficiary PSP applied the correct value date. The payment of the inter-PSP fee and/or interest compensation and consequently the confirmed positive response are not included in this timeframe. However, these should be done as soon as possible to reduce further friction for the Originator and the Beneficiary.

* Clarification of the word "recommended":

SCT scheme participants may agree (e.g. on a bilateral or community/country basis) to use another practice outside the SCT scheme to settle such payments. But to ensure a minimal standard at SEPA level, all scheme participants must implement the DS-11 pacs.008 message (i.e. at least the DS-11 'Credit Transfer Transaction Information' block in case of a DS-02/DS-11 mix) as described in section 2.19 of the SCT IGs.

#	SEPA Mult	Message Element	Inter-PSP Positive Response to Claim for Value Date Correction SEPA Core Requirements	
		Document	XML Tag Type	Document Document
	1..1	Resolution Of Investigation V09	ISO Name ISO Definition XML Tag Type	Resolution Of Investigation V09 The ResolutionOfInvestigation message is sent by a case assignee to a case creator/case assigner. This message is used to inform of the resolution of a case, and optionally provides details about: - the corrective action undertaken by the case assignee - information on the return where applicable RsltnOfInvstgtn ResolutionOfInvestigationV09
1.0	1..1	Resolution Of Investigation V09 +Assignment	ISO Name ISO Definition XML Tag Type	Assignment Identifies the assignment of an investigation case from an assigner to an assignee. Usage: The Assigner must be the sender of this confirmation and the Assignee must be the receiver. Assgnmt CaseAssignment5
1.1	1..1	Resolution Of Investigation V09 +Assignment ++Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Identification Uniquely identifies the case assignment. Id Max35Text 1 .. 35 1 .. 35
1.2	1..1	Resolution Of Investigation V09 +Assignment ++Assigner	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Instructing Party. Limited to 'BICFI' to identify a PSP, 'AnyBIC' to identify a CSM or 'LEI' or 'Name' to indicate a CSM when it has no BIC. 'Name' is limited to 70 characters in length. Assigner Party who assigns the case. Usage: This is also the sender of the message. Assgrn Party40Choice
1.3	1..1	Resolution Of Investigation V09 +Assignment ++Assignee	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Instructed Party. Limited to 'BICFI' to identify a PSP, 'AnyBIC' to identify a CSM or 'LEI' or 'Name' to indicate a CSM when it has no BIC. 'Name' is limited to 70 characters in length. Assignee Party to which the case is assigned. Usage: This is also the receiver of the message. Assgne Party40Choice
1.4	1..1	Resolution Of Investigation V09 +Assignment ++Creation Date Time	ISO Name ISO Definition XML Tag Type	Creation Date Time Date and time at which the assignment was created. CreDtTm ISODateTime
2.0	1..1	Resolution Of Investigation V09 +Resolved Case	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Mandatory. Resolved Case Identifies a resolved case. RslvdCase Case5

#	SEPA Mult	Message Element	Inter-PSP Positive Response to Claim for Value Date Correction SEPA Core Requirements	
2.1	1..1	Resolution Of Investigation V09 +Resolved Case ++Identification	SEPA Rulebook ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>AT-Q002 The specific SCT inquiry reference of the Participant initiating the SCT inquiry.</i> Identification Uniquely identifies the case. Id Max35Text 1 .. 35 1 .. 35
2.2	1..1	Resolution Of Investigation V09 +Resolved Case ++Creator	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>Only 'Agent' is allowed.</i> <i>Limited to 'BICFI' to identify the Originator PSP of the original credit transfer.</i> Creator Party that created the investigation case. Cretr Party40Choice
2.3	0..1	Resolution Of Investigation V09 +Resolved Case ++Reopen Case Indication	ISO Name ISO Definition XML Tag Type	Reopen Case Indication Indicates whether or not the case was previously closed and is now re-opened. ReopCaseIndctn YesNoIndicator
3.0	1..1	Resolution Of Investigation V09 +Status	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>Only 'Confirmation' is allowed.</i> Status Indicates the status of the investigation. Sts InvestigationStatus5Choice
	1..1		XML Tag	xs:choice
3.1	1..1	Resolution Of Investigation V09 +Status ++Confirmation	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>Only "ACVA" is allowed.</i> Confirmation Specifies the status of the investigation, in a coded form. Conf ExternalInvestigationExecutionConfirmation1Code 1 .. 4 1 .. 4
			SEPA Code Restrictions	
			ACVA	<i>AcceptedValueDateAdjustment</i> <i>The claim for value date correction is accepted.</i>
3.2	1..n	Resolution Of Investigation V09 +Status ++Rejected Modification	ISO Name ISO Definition XML Tag Type	Rejected Modification Reason for the rejection of a modification request, in a coded form. RjctdMod ModificationStatusReason1Choice
3.3	1..1	Resolution Of Investigation V09 +Status ++Duplicate Of	ISO Name ISO Definition XML Tag Type	Duplicate Of Indicates a duplicated case. Usage: When present, the case identified in the message must be closed. The case identified as duplicated (in this component) will be pursued. DplctOf Case5
3.4	1..1	Resolution Of Investigation V09 +Status ++Assignment Cancellation Confirmation	ISO Name ISO Definition XML Tag Type	Assignment Cancellation Confirmation Indicates whether the cancellation of the assignment is confirmed or rejected. Usage: If yes, the cancellation of the assignment is confirmed. If no, the cancellation of the assignment is rejected and the investigation process will continue. AssgnmtCxlConf YesNoIndicator

#	SEPA Mult	Message Element	Inter-PSP Positive Response to Claim for Value Date Correction SEPA Core Requirements	
4.0	0..n	Resolution Of Investigation V09 +Cancellation Details	ISO Name ISO Definition XML Tag Type	Cancellation Details Specifies the details of the underlying transactions being cancelled. CxlDtls UnderlyingTransaction22
5.0	1..1	Resolution Of Investigation V09 +Modification Details	SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type	Modification Details Specifies the details of the underlying transaction being modified. ModDtls PaymentTransaction107
5.1	1..1	Resolution Of Investigation V09 +Modification Details ++Modification Status Identification	SEPA Rulebook SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	AT-Q009 Reference of the Beneficiary PSP for inter-PSP fee and/or compensation payment Modification Status Identification Unique and unambiguous identifier of a modification request status, as assigned by the assigner. Usage: The modification status identification can be used for reconciliation or to link tasks relating to the modification request. ModStsId Max35Text 1 .. 35 1 .. 35
5.2	0..1	Resolution Of Investigation V09 +Modification Details ++Resolved Case	ISO Name ISO Definition XML Tag Type	Resolved Case Identifies the resolved case. RslvdCase Case5
5.3	1..1	Resolution Of Investigation V09 +Modification Details ++Original Group Information	ISO Name ISO Definition XML Tag Type	Original Group Information Provides information on the original message. OrgnlGrpInf OriginalGroupInformation29
5.4	1..1	Resolution Of Investigation V09 +Modification Details ++Original Group Information +++Original Message Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Message Identification Point to point reference assigned by the original instructing party to unambiguously identify the original message. OrgnlMsgId Max35Text 1 .. 35 1 .. 35
5.5	1..1	Resolution Of Investigation V09 +Modification Details ++Original Group Information +++Original Message Name Identification	SEPA Usage Rule(s) Must begin with 'pacs.008'. The addition of a variant number and version number is optional. ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Message Name Identification Specifies the original message name identifier to which the message refers, for example, pacs.003.001.01 or MT103. OrgnlMsgNmId Max35Text 1 .. 35 1 .. 35
5.6	0..1	Resolution Of Investigation V09 +Modification Details ++Original Group Information +++Original Creation Date Time	ISO Name ISO Definition XML Tag Type	Original Creation Date Time Original date and time at which the message was created. OrgnlCreDtTm ISODateTime

#	SEPA Mult	Message Element	Inter-PSP Positive Response to Claim for Value Date Correction SEPA Core Requirements	
5.7	0..1	Resolution Of Investigation V09 +Modification Details ++Original Payment Information Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Payment Information Identification Unique identification, as assigned by the original sending party, to unambiguously identify the original payment information group. OrgnlPmtInflId Max35Text 1 .. 35 1 .. 35
5.8	0..1	Resolution Of Investigation V09 +Modification Details ++Original Instruction Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Instruction Identification Unique identification, as assigned by the original instructing party for the original instructed party, to unambiguously identify the original instruction. OrgnlInstrId Max35Text 1 .. 35 1 .. 35
5.9	1..1	Resolution Of Investigation V09 +Modification Details ++Original End To End Identification	SEPA Rulebook SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	AT-T014 <i>The Originator's reference of the SEPA Credit Transfer Transaction.</i> Original End To End Identification Unique identification, as assigned by the original initiating party, to unambiguously identify the original transaction. OrgnlEndToEndId Max35Text 1 .. 35 1 .. 35
5.10	1..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Identification	SEPA Rulebook SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	AT-T054 <i>The Originator PSP's reference of the SEPA Credit Transfer Transaction.</i> Original Transaction Identification Unique identification, as assigned by the original first instructing agent, to unambiguously identify the transaction. OrgnlTxId Max35Text 1 .. 35 1 .. 35
5.11	0..1	Resolution Of Investigation V09 +Modification Details ++Original Clearing System Reference	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Clearing System Reference Unique reference, as assigned by the original clearing system, to unambiguously identify the original instruction. OrgnlClrSysRef Max35Text 1 .. 35 1 .. 35
5.12	0..1	Resolution Of Investigation V09 +Modification Details ++Original UETR	ISO Name ISO Definition XML Tag Type Pattern	Original UETR Universally unique identifier to provide the original end-to-end reference of a payment transaction. OrgnlUETR UUIDv4Identifier [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}
5.13	0..n	Resolution Of Investigation V09 +Modification Details ++Modification Status Reason Information	ISO Name ISO Definition XML Tag Type	Modification Status Reason Information Provides detailed information on the modification status reason. ModStsRsnInf ModificationStatusReason2

#	SEPA Mult	Message Element	Inter-PSP Positive Response to Claim for Value Date Correction SEPA Core Requirements			
5.14	0..1	Resolution Of Investigation V09 +Modification Details ++Resolution Related Information	ISO Name ISO Definition XML Tag Type	Resolution Related Information Reference of a return or a reversal transaction that is initiated to fix the case under investigation as part of the resolution. RsltnRltInf ResolutionData1		
5.15	0..1	Resolution Of Investigation V09 +Modification Details ++Original Interbank Settlement Amount	ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits SEPA Inclusive	Original Interbank Settlement Amount Amount of money moved between the instructing agent and the instructed agent, as provided in the original instruction. OrgnlIntrBkSttlmAmt ActiveOrHistoricCurrencyAndAmount 5 18 0 ..		
5.16	0..1	Resolution Of Investigation V09 +Modification Details ++Original Interbank Settlement Date	ISO Name ISO Definition XML Tag Type	Original Interbank Settlement Date Date, as provided in the original transaction, on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. OrgnlIntrBkSttlmDt ISODate		
5.17	0..1	Resolution Of Investigation V09 +Modification Details ++Assigner	ISO Name ISO Definition XML Tag Type	Assigner Party who assigns the case. Usage: This is also the agent that instructs the next party in the chain to carry out the (set of) cancellation request(s). Assgnr Party40Choice		
5.18	0..1	Resolution Of Investigation V09 +Modification Details ++Assignee	ISO Name ISO Definition XML Tag Type	Assignee Party to which the case is assigned. Usage: This is also the agent that is instructed by the previous party in the chain to carry out the (set of) cancellation request(s). Assgne Party40Choice		
5.19	1..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Mandatory. The yellow shaded message elements under 'Original Transaction Reference' must be populated with the same value as the message elements of the original instruction. Original Transaction Reference Key elements used to identify the original transaction that is being referred to. OrgnlTxRef OriginalTransactionReference28		
5.20	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Interbank Settlement Amount	SEPA Rulebook ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits SEPA Inclusive	AT-T002 Amount of the SEPA Credit Transfer in Euro. Interbank Settlement Amount Amount of money moved between the instructing agent and the instructed agent. IntrBkSttlmAmt ActiveOrHistoricCurrencyAndAmount 2 18 0.01 .. 999999999.99		

#	SEPA Mult	Message Element	Inter-PSP Positive Response to Claim for Value Date Correction SEPA Core Requirements	
5.21	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Amount	ISO Name ISO Definition XML Tag Type	Amount Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party. Amt AmountType4Choice
5.22	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Interbank Settlement Date	SEPA Rulebook ISO Name ISO Definition XML Tag Type	AT-T051 Settlement Date of the Credit Transfer in Euro. Interbank Settlement Date Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. IntrBkSttlmDt ISODate
5.23	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Requested Collection Date	ISO Name ISO Definition XML Tag Type	Requested Collection Date Date and time at which the creditor requests that the amount of money is to be collected from the debtor. ReqdColltnDt ISODate
5.24	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Requested Execution Date	ISO Name ISO Definition XML Tag Type	Requested Execution Date Date at which the initiating party requests the clearing agent to process the payment. Usage: This is the date on which the debtor's account is to be debited. If payment by cheque, the date when the cheque must be generated by the bank. ReqdExctnDt DateAndDateTime2Choice
5.25	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Creditor Scheme Identification	ISO Name ISO Definition XML Tag Type	Creditor Scheme Identification Credit party that signs the mandate. CdtrSchmElD PartyIdentification135
5.26	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Settlement Information	ISO Name ISO Definition XML Tag Type	Settlement Information Specifies the details on how the settlement of the original transaction(s) between the instructing agent and the instructed agent was completed. SttlmInf SettlementInstruction7
5.27	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Payment Type Information	SEPA Rulebook ISO Name ISO Definition XML Tag Type	AT-T001 Identification code of the Scheme. AT-T008 Category Purpose of the Credit Transfer. If the original transaction was sent according to Annex V (Use of Extended Remittance Information) of the SCT Rulebook (refer to section 'Inter-PSP payment with use of the Extended Remittance Information option' below), then 'Local Instrument/Code' must be populated with "PERI" (Payment with Extended Remittance Information). Payment Type Information Set of elements used to further specify the type of transaction. PmtTpInf PaymentTypeInformation27
5.28	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Payment Method	ISO Name ISO Definition XML Tag Type	Payment Method Specifies the means of payment that will be used to move the amount of money. PmtMtd PaymentMethod4Code

#	SEPA Mult	Message Element	Inter-PSP Positive Response to Claim for Value Date Correction SEPA Core Requirements	
5.29	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Mandate Related Information	ISO Name ISO Definition XML Tag Type	Mandate Related Information Provides further details of the mandate signed between the creditor and the debtor. MndtRltdInf MandateRelatedInformation14
5.30	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Remittance Information	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-T009 Remittance information or AT-T010 The unstructured Remittance Information sent by the Originator to the Beneficiary in the Credit Transfer Instruction (in case of use of the Extended Remittance Information (ERI) option in the original SEPA Credit Transfer, AT-T011 The structured Remittance Information sent by the Originator to the Beneficiary in the SEPA Credit Transfer Instruction, will NOT be transported here).</i> Remittance Information Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system. RmtInf RemittanceInformation16
5.31	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Ultimate Debtor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-P006 The name of the Originator Reference Party.</i> <i>AT-P007 The identification code of the Originator Reference Party.</i> <i>Only 'Party' is allowed.</i> Ultimate Debtor Ultimate party that owes an amount of money to the (ultimate) creditor. UltmtDbtr Party40Choice
5.32	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Debtor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-P001 Name of the Originator.</i> <i>AT-P005 Address of the Originator.</i> <i>AT-P004 Originator's Identification Code.</i> <i>Only 'Party' is allowed.</i> Debtor Party that owes an amount of money to the (ultimate) creditor. Dbtr Party40Choice
5.33	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Debtor Account	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-D001 The IBAN of the account of the Originator.</i> <i>AT-P003 The Proxy/Alias of the account of the Originator.</i> Debtor Account Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction. DbtrAcct CashAccount38
5.34	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Debtor Agent	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-D002 The BIC code of the Originator PSP.</i> Debtor Agent Financial institution servicing an account for the debtor. DbtrAgt BranchAndFinancialInstitutionIdentification6
5.35	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Debtor Agent Account	ISO Name ISO Definition XML Tag Type	Debtor Agent Account Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain. DbtrAgtAcct CashAccount38

#	SEPA Mult	Message Element	Inter-PSP Positive Response to Claim for Value Date Correction SEPA Core Requirements	
5.36	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Creditor Agent	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-C002 The BIC code of the Beneficiary PSP.</i> Creditor Agent Financial institution servicing an account for the creditor. CdtrAgt BranchAndFinancialInstitutionIdentification6
5.37	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Creditor Agent Account	ISO Name ISO Definition XML Tag Type	Creditor Agent Account Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction. CdtrAgtAcct CashAccount38
5.38	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Creditor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-E001 Name of the Beneficiary.</i> <i>AT-E004 Address of the Beneficiary.</i> <i>AT-E005 Beneficiary Identification Code.</i> Only 'Party' is allowed. Creditor Party to which an amount of money is due. Cdtr Party40Choice
5.39	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Creditor Account	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-C001 The IBAN of the account of the Beneficiary.</i> <i>AT-E003 The Proxy/Alias of the account of the Beneficiary.</i> Creditor Account Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction. CdtrAcct CashAccount38
5.40	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Ultimate Creditor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-E007 The name of the Beneficiary Reference Party.</i> <i>AT-E010 The identification code of the Beneficiary Reference Party.</i> Only 'Party' is allowed. Ultimate Creditor Ultimate party to which an amount of money is due. UltmtCdtr Party40Choice
5.41	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Purpose	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-T007 The purpose of the SEPA Credit Transfer.</i> Purpose Underlying reason for the payment transaction. Usage: Purpose is used by the end customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain. Purp Purpose2Choice
6.0	0..1	Resolution Of Investigation V09 +Claim Non Receipt Details	ISO Name ISO Definition XML Tag Type	Claim Non Receipt Details Specifies the details of the underlying transaction for which a claim non receipt has been initiated. ClmNonRctDtls ClaimNonReceipt2Choice

#	SEPA Mult	Message Element	Inter-PSP Positive Response to Claim for Value Date Correction SEPA Core Requirements		
7.0	0..1	Resolution Of Investigation V09 +Statement Details	ISO Name ISO Definition XML Tag Type	Statement Details Details on the underlying statement entry. StmtDtls StatementResolutionEntry4	
8.0	0..1	Resolution Of Investigation V09 +Correction Transaction	ISO Name ISO Definition XML Tag Type	Correction Transaction References a transaction initiated to fix the case under investigation. CrrctnTx CorrectiveTransaction4Choice	
9.0	1..1	Resolution Of Investigation V09 +Resolution Related Information	SEPA Usage Rule(s) <i>Mandatory</i> ISO Name ISO Definition XML Tag Type	Resolution Related Information Reference to fix the case under investigation as part of the resolution. RsltnRltdInf ResolutionData1	
9.1	0..1	Resolution Of Investigation V09 +Resolution Related Information ++End To End Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	End To End Identification Unique identification, as assigned by the original initiating party, to unambiguously identify the original transaction. EndToEndId Max35Text 1 .. 35 1 .. 35	
9.2	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Transaction Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Transaction Identification Unique identification, as assigned by the original first instructing agent, to unambiguously identify the transaction. TxId Max35Text 1 .. 35 1 .. 35	
9.3	0..1	Resolution Of Investigation V09 +Resolution Related Information ++UETR	ISO Name ISO Definition XML Tag Type Pattern	UETR Universally unique identifier to provide an end-to-end reference of a payment transaction. UETR UUIDv4Identifier [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}	
9.4	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Interbank Settlement Amount	ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits SEPA Inclusive	Interbank Settlement Amount Amount of money moved between the instructing agent and the instructed agent. IntrBkStlmtAmt ActiveOrHistoricCurrencyAndAmount 5 18 0 ..	
9.5	1..1	Resolution Of Investigation V09 +Resolution Related Information ++Interbank Settlement Date	SEPA Rulebook SEPA Usage Rule(s) <i>AT-Q005 New value date of the credit transfer based on the new settlement date.</i> ISO Name ISO Definition XML Tag Type	<i>AT-Q005 New value date of the credit transfer based on the new settlement date.</i> Interbank Settlement Date Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. IntrBkStlmtDt ISODate	
9.6	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Clearing Channel	ISO Name ISO Definition XML Tag Type	Clearing Channel Specifies the clearing channel to be used to process the payment instruction. ClrChnl ClearingChannel2Code	

#	SEPA Mult	Message Element	Inter-PSP Positive Response to Claim for Value Date Correction SEPA Core Requirements	
9.7	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Compensation	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-Q006 The interest compensation recovered by the Beneficiary PSP from the Originator PSP.</i> Compensation Provides the details of the compensation made due to the modification or cancellation of a previous payment. Compstn Compensation2
9.8	1..1	Resolution Of Investigation V09 +Resolution Related Information ++Compensation +++Amount	SEPA Usage Rule(s) SEPA Format Rule(s) ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits SEPA Inclusive	<i>Only 'EUR' is allowed.</i> <i>Amount must be 0.01 or more and 99999999.99 or less.</i> <i>The fractional part has a maximum of two digits.</i> Amount Amount of money to be paid in compensation. Amt ActiveCurrencyAndAmount 2 18 0.01 .. 99999999.99
9.9	1..1	Resolution Of Investigation V09 +Resolution Related Information ++Compensation +++Debtor Agent	SEPA Usage Rule(s) ISO Name ISO Definition	<i>AT-D002 The BIC code of the Originator PSP.</i> <i>Only 'BICFI' is allowed.</i> Debtor Agent Financial institution servicing an account for the debtor. Usage: The debtor agent is the payer of the compensation amount. DbtrAgt BranchAndFinancialInstitutionIdentification6
9.10	1..1	Resolution Of Investigation V09 +Resolution Related Information ++Compensation +++Creditor Agent	ISO Name ISO Definition	Creditor Agent Financial institution servicing an account for the creditor. Usage: The creditor agent is the payee of the compensation amount. CdtrAgt BranchAndFinancialInstitutionIdentification6
9.11	1..1	Resolution Of Investigation V09 +Resolution Related Information ++Compensation +++Creditor Agent ++++Financial Institution Identification	ISO Name ISO Definition	Financial Institution Identification Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme. FinInstnId FinancialInstitutionIdentification18
9.12	1..1	Resolution Of Investigation V09 +Resolution Related Information ++Compensation +++Creditor Agent ++++Financial Institution Identification +++++BICFI	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type Pattern	<i>AT-C002 The BIC code of the Beneficiary PSP.</i> <i>Mandatory.</i> BICFI Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)". BICFI BICFIDec2014Identifier [A-Z0-9]{4,4}[A-Z]{2,2}[A-Z0-9]{2,2}([A-Z0-9]{3,3}){0,1}

#	SEPA Mult	Message Element	Inter-PSP Positive Response to Claim for Value Date Correction SEPA Core Requirements	
9.13	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Compensation +++Creditor Agent ++++Financial Institution Identification +++++Clearing System Member Identification	ISO Name ISO Definition XML Tag Type	Clearing System Member Identification Information used to identify a member within a clearing system. ClrSysMmbld ClearingSystemMemberIdentification2
9.14	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Compensation +++Creditor Agent ++++Financial Institution Identification +++++LEI	ISO Name ISO Definition XML Tag Type Pattern	LEI Legal entity identifier of the financial institution. LEI LEIIDentifier [A-Z0-9]{18,18}{0-9}{2,2}
9.15	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Compensation +++Creditor Agent ++++Financial Institution Identification +++++Name	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Name Name by which an agent is known and which is usually used to identify that agent. Nm Max140Text 1 .. 140 1 .. 140
9.16	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Compensation +++Creditor Agent ++++Financial Institution Identification +++++Postal Address	ISO Name ISO Definition XML Tag Type	Postal Address Information that locates and identifies a specific address, as defined by postal services. PstlAdr PostalAddress24
9.17	1..1	Resolution Of Investigation V09 +Resolution Related Information ++Compensation +++Creditor Agent ++++Financial Institution Identification +++++Other	SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type	Other Unique identification of an agent, as assigned by an institution, using an identification scheme. Othr GenericFinancialIdentification1
9.18	1..1	Resolution Of Investigation V09 +Resolution Related Information ++Compensation +++Creditor Agent ++++Financial Institution Identification +++++Other ++++++Identification	SEPA Usage Rule(s) Only IBAN is allowed. ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Identification Unique and unambiguous identification of a person. Id Max35Text 1 .. 35 1 .. 35
9.19	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Compensation +++Creditor Agent ++++Financial Institution Identification +++++Other ++++++Scheme Name	ISO Name ISO Definition XML Tag Type	Scheme Name Name of the identification scheme. SchmeNm FinancialIdentificationSchemeName1Choice
9.20	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Compensation +++Creditor Agent ++++Financial Institution Identification +++++Other ++++++Issuer	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Issuer Entity that assigns the identification. Issr Max35Text 1 .. 35 1 .. 35

#	SEPA Mult	Message Element	Inter-PSP Positive Response to Claim for Value Date Correction SEPA Core Requirements	
9.21	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Compensation +++Creditor Agent ++++Branch Identification	ISO Name ISO Definition XML Tag Type	Branch Identification Identifies a specific branch of a financial institution. Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level. BrnchId BranchData3
9.22	1..1	Resolution Of Investigation V09 +Resolution Related Information ++Compensation +++Reason	SEPA Usage Rule(s) <i>Only 'Code' is allowed.</i> <i>Only "VADA" (Compensation requested for value date correction) is allowed.</i> ISO Name ISO Definition XML Tag Type	Reason Reason for the payment compensation. Rsn CompensationReason1Choice
9.23	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Charges	SEPA Rulebook SEPA Usage Rule(s) <i>Only one occurrence is allowed.</i> ISO Name ISO Definition XML Tag Type	AT-Q007 Fee for handling the SCT inquiry. Charges Provides information on the charges to be paid by the charge bearer(s) related to the payment transaction. Chrgs Charges7
9.24	1..1	Resolution Of Investigation V09 +Resolution Related Information ++Charges +++Amount	SEPA Usage Rule(s) <i>Only 'EUR' is allowed.</i> <i>Amount must be 0.01 or more and 999999999.99 or less.</i> <i>The fractional part has a maximum of two digits.</i> SEPA Format Rule(s) ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits SEPA Inclusive	Amount Transaction charges to be paid by the charge bearer. Amt ActiveOrHistoricCurrencyAndAmount 2 18 0.01 .. 999999999.99
9.25	1..1	Resolution Of Investigation V09 +Resolution Related Information ++Charges +++Agent	ISO Name ISO Definition XML Tag Type	Agent Agent that takes the transaction charges or to which the transaction charges are due. Agt BranchAndFinancialInstitutionIdentification6
9.26	1..1	Resolution Of Investigation V09 +Resolution Related Information ++Charges +++Agent ++++Financial Institution Identification	ISO Name ISO Definition XML Tag Type	Financial Institution Identification Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme. FinInstnId FinancialInstitutionIdentification18
9.27	1..1	Resolution Of Investigation V09 +Resolution Related Information ++Charges +++Agent ++++Financial Institution Identification +++++BICFI	SEPA Rulebook SEPA Usage Rule(s) <i>Mandatory.</i> ISO Name ISO Definition XML Tag Type Pattern	AT-C002 The BIC code of the Beneficiary PSP. BICFI Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)". BICFI BICFIDec2014Identifier [A-Z0-9]{4,4}[A-Z]{2,2}[A-Z0-9]{2,2}([A-Z0-9]{3,3}){0,1}

#	SEPA Mult	Message Element	Inter-PSP Positive Response to Claim for Value Date Correction SEPA Core Requirements	
9.28	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Charges +++Agent ++++Financial Institution Identification +++++Clearing System Member Identification	ISO Name ISO Definition XML Tag Type	Clearing System Member Identification Information used to identify a member within a clearing system. ClrSysMmbld ClearingSystemMemberIdentification2
9.29	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Charges +++Agent ++++Financial Institution Identification +++++LEI	ISO Name ISO Definition XML Tag Type Pattern	LEI Legal entity identifier of the financial institution. LEI LEIIDentifier [A-Z0-9]{18,18}{0-9}{2,2}
9.30	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Charges +++Agent ++++Financial Institution Identification +++++Name	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Name Name by which an agent is known and which is usually used to identify that agent. Nm Max140Text 1 .. 140 1 .. 140
9.31	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Charges +++Agent ++++Financial Institution Identification +++++Postal Address	ISO Name ISO Definition XML Tag Type	Postal Address Information that locates and identifies a specific address, as defined by postal services. PstlAdr PostalAddress24
9.32	1..1	Resolution Of Investigation V09 +Resolution Related Information ++Charges +++Agent ++++Financial Institution Identification +++++Other	SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type	Other Unique identification of an agent, as assigned by an institution, using an identification scheme. Othr GenericFinancialIdentification1
9.33	1..1	Resolution Of Investigation V09 +Resolution Related Information ++Charges +++Agent ++++Financial Institution Identification +++++Other ++++++Identification	SEPA Usage Rule(s) Only IBAN is allowed. ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Identification Unique and unambiguous identification of a person. Id Max35Text 1 .. 35 1 .. 35
9.34	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Charges +++Agent ++++Financial Institution Identification +++++Other ++++++Scheme Name	ISO Name ISO Definition XML Tag Type	Scheme Name Name of the identification scheme. SchmeNm FinancialIdentificationSchemeName1Choice
9.35	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Charges +++Agent ++++Financial Institution Identification +++++Other ++++++Issuer	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Issuer Entity that assigns the identification. Issr Max35Text 1 .. 35 1 .. 35

#	SEPA Mult	Message Element	Inter-PSP Positive Response to Claim for Value Date Correction SEPA Core Requirements	
9.36	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Charges +++Agent ++++Branch Identification	ISO Name ISO Definition	Branch Identification Identifies a specific branch of a financial institution. Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level. BrnchId BranchData3
10.0	0..n	Resolution Of Investigation V09 +Supplementary Data	ISO Name ISO Definition XML Tag Type	Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block. SplmtryData SupplementaryData1



2.18 Inter-PSP Confirmed Positive Response to Claim for Value Date Correction (DS-10)

2.18.1 Use of Resolution of Investigation (camt.029.001.09)

This message is used to send a confirmed positive response to a:

- Claim for Value Date Correction message (Request To Modify Payment, camt.087.001.06);
- Request for Status Update on a Claim for Value Date Correction message (FI-to-FI Payment Status Request, pacs.028.001.03, refer to section 'Request for Status Update on a SCT Inquiry' below);

for which either

- Neither an inter-PSP fee nor interest compensation is requested by the Beneficiary PSP, or
- An inter-PSP fee and/or interest compensation has already been received by the Beneficiary PSP following an "ACVA" (Accepted Value Date Adjustment) positive response (refer to former section 'Inter-PSP Positive Response to Claim for Value Date Correction (DS-10) with request for interest compensation'), or
- Interest compensation cannot be requested because the calculation results in a negative amount but the Beneficiary PSP asks for charges to be paid after the already applied value date correction, or
- The Beneficiary PSP asks for inter-PSP fee and/or interest compensation to be paid after the already applied value date correction,

where the following apply:

- Index 3.0 'Status': only sub-element 'Confirmation' is allowed, populated with "MODI" (Modified As Per Request) only.
- Under index 9.0 'Resolution Related Information', only following elements are allowed:
 - Index 9.5 'Interbank Settlement Date' to accommodate AT-Q005 'New value date of the credit transfer based on the new settlement date';
 - If inter-PSP fee and/or interest compensation is to be paid **after application of the value date correction**, then the following must be used:
 - Index 9.7 'Compensation' and relevant sub-elements to accommodate AT-Q006 'The interest compensation recovered by the Beneficiary PSP from the Originator PSP'
 - Index 9.22 'Compensation/Reason', only "VADA" (Value Date Adjustment)
 - Index 9.25 'Charges' and relevant sub-elements to accommodate AT-Q007 'Fee for handling the SCT Inquiry'

In the context of a Claim for Value Date Correction, the message caters for a single response only.



Note: The use case of the message is implied by the 'Message Name', 'camt.029.001.09', the 'Original Message Name Identification' must begin with pacs.008 (the addition of a variant number and version number is optional) and 'Status' set to "MODI".

Note: Message elements under 'Original Transaction Reference' sequence are based on DS-02 attributes.

Important Note:

If compensation and/or charges are claimed in the Positive Response (see section 2.17) then no compensation and/or charges can be claimed in the present response message.

The payment of the inter-PSP fee and/or interest compensation is to be effectuated according to the current inter-PSP practices related to such matters. It is recommended* to use the DS-11 pacs.008 (i.e. at least the DS-11 'Credit Transfer Transaction Information' block in case of a DS-02/DS-11 mix) as described for this specific usage as per below section 'Inter-PSP Fee and/or Compensation Payment'. When paying the interest compensation and, if applicable charges, the Originator PSP must provide AT-Q002 'The specific SCT inquiry reference of the Participant initiating the SCT inquiry' and AT-Q009 'Reference of the Beneficiary PSP for inter-PSP fee and/or compensation payment' in order to allow the Beneficiary PSP to allocate the payment to the right case. Moreover, the IBAN provided under 'Resolution Related Information/Compensation' or 'Resolution Related Information/Charges' is the one corresponding to AT-Q008 'The IBAN of the account to be credited at the Beneficiary PSP' in the inter-PSP payment message.

The rulebook stipulates that "The Beneficiary PSP must provide a response-to-SCT-inquiry message about the concerned SCT inquiry within 10 Banking Business Days after it has received the SCT inquiry message" (for further information please see section 4.4.2 of the SCT Rulebook).

In case of a first positive response (camt.029) requesting payment of an inter-PSP fee and/or interest compensation and followed by a second one to confirm, please note that the above timeframe only applies to the first response, which reflects the position of the Beneficiary PSP. This in view of the fact that the aim of the SCT inquiry is to get information about the concrete fate of the original SCT transaction, i.e. has the Beneficiary PSP applied the correct value date. The payment of the inter-PSP fee and/or interest compensation and consequently the confirmed positive response are not included in this timeframe. However, these should be done as soon as possible to reduce further friction for the Originator and the Beneficiary.

* Clarification of the word "recommended":

SCT scheme participants may agree (e.g., on a bilateral or community/country basis) to use another practice outside the SCT scheme to settle such payments. But to ensure a minimal standard at SEPA level, all scheme participants must implement the DS-11 pacs.008 message (i.e. at least the DS-11 'Credit Transfer Transaction Information' block in case of a DS-02/DS-11 mix) as described in section 2.19 of the SCT IGs.

#	SEPA Mult	Message Element	Inter-PSP Confirmed Positive Response to camt.087 SEPA Core Requirements	
		Document	XML Tag Type	Document Document
	1..1	Resolution Of Investigation V09	ISO Name ISO Definition XML Tag Type	Resolution Of Investigation V09 The ResolutionOfInvestigation message is sent by a case assignee to a case creator/case assigner. This message is used to inform of the resolution of a case, and optionally provides details about: - the corrective action undertaken by the case assignee - information on the return where applicable RsltnOfInvstgtn ResolutionOfInvestigationV09
1.0	1..1	Resolution Of Investigation V09 +Assignment	ISO Name ISO Definition XML Tag Type	Assignment Identifies the assignment of an investigation case from an assigner to an assignee. Usage: The assigner must be the sender of this confirmation and the assignee must be the receiver. Assgnmt CaseAssignment5
1.1	1..1	Resolution Of Investigation V09 +Assignment ++Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Identification Uniquely identifies the case assignment. Id Max35Text 1 .. 35 1 .. 35
1.2	1..1	Resolution Of Investigation V09 +Assignment ++Assigner	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Instructing Party. Limited to 'BICFI' to identify a PSP, 'AnyBIC' to identify a CSM or 'LEI' or 'Name' to indicate a CSM when it has no BIC. 'Name' is limited to 70 characters in length. Assigner Party who assigns the case. Usage: This is also the sender of the message. Assgrn Party40Choice
1.3	1..1	Resolution Of Investigation V09 +Assignment ++Assignee	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Instructed Party. Limited to 'BICFI' to identify a PSP, 'AnyBIC' to identify a CSM or 'LEI' or 'Name' to indicate a CSM when it has no BIC. 'Name' is limited to 70 characters in length. Assignee Party to which the case is assigned. Usage: This is also the receiver of the message. Assgne Party40Choice
1.4	1..1	Resolution Of Investigation V09 +Assignment ++Creation Date Time	ISO Name ISO Definition XML Tag Type	Creation Date Time Date and time at which the assignment was created. CreDtTm ISODateTime
2.0	1..1	Resolution Of Investigation V09 +Resolved Case	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Mandatory. Resolved Case Identifies a resolved case. RslvdCase Case5

#	SEPA Mult	Message Element	Inter-PSP Confirmed Positive Response to camt.087 SEPA Core Requirements	
2.1	1..1	Resolution Of Investigation V09 +Resolved Case ++Identification	SEPA Rulebook ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>AT-Q002 The specific SCT inquiry reference of the Scheme Participant initiating the SCT inquiry.</i> Identification Uniquely identifies the case. Id Max35Text 1 .. 35 1 .. 35
2.2	1..1	Resolution Of Investigation V09 +Resolved Case ++Creator	SEPA Usage Rule(s) Limited to 'BICFI' to identify the Originator PSP of the original credit transfer. ISO Name ISO Definition XML Tag Type	Creator Party that created the investigation case. Cretr Party40Choice
2.3	0..1	Resolution Of Investigation V09 +Resolved Case ++Reopen Case Indication	ISO Name ISO Definition XML Tag Type	Reopen Case Indication Indicates whether or not the case was previously closed and is now re-opened. ReopCaseIndctn YesNoIndicator
3.0	1..1	Resolution Of Investigation V09 +Status	SEPA Usage Rule(s) Only 'Confirmation' is allowed. ISO Name ISO Definition XML Tag Type	Status Indicates the status of the investigation. Sts InvestigationStatus5Choice
	1..1		XML Tag	xs:choice
3.1	1..1	Resolution Of Investigation V09 +Status ++Confirmation	SEPA Usage Rule(s) Only "MODI" is allowed. ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Confirmation Specifies the status of the investigation, in a coded form. Conf ExternalInvestigationExecutionConfirmation1Code 1 .. 4 1 .. 4
			SEPA Code Restrictions	
			MODI <i>ModifiedAsPerRequest</i> <i>Used when a requested modification is successful.</i>	
3.2	1..n	Resolution Of Investigation V09 +Status ++Rejected Modification	ISO Name ISO Definition XML Tag Type	Rejected Modification Reason for the rejection of a modification request, in a coded form. RjtdMod ModificationStatusReason1Choice
3.3	1..1	Resolution Of Investigation V09 +Status ++Duplicate Of	ISO Name ISO Definition XML Tag Type	Duplicate Of Indicates a duplicated case. Usage: When present, the case identified in the message must be closed. The case identified as duplicated (in this component) will be pursued. DpctOf Case5
3.4	1..1	Resolution Of Investigation V09 +Status ++Assignment Cancellation Confirmation	ISO Name ISO Definition XML Tag Type	Assignment Cancellation Confirmation Indicates whether the cancellation of the assignment is confirmed or rejected. Usage: If yes, the cancellation of the assignment is confirmed. If no, the cancellation of the assignment is rejected and the investigation process will continue. AssgnmtCxlConf YesNoIndicator

#	SEPA Mult	Message Element	Inter-PSP Confirmed Positive Response to camt.087 SEPA Core Requirements	
4.0	0..n	Resolution Of Investigation V09 +Cancellation Details	ISO Name ISO Definition XML Tag Type	Cancellation Details Specifies the details of the underlying transactions being cancelled. CxlDtls UnderlyingTransaction22
5.0	1..1	Resolution Of Investigation V09 +Modification Details	SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type	Modification Details Specifies the details of the underlying transaction being modified. ModDtls PaymentTransaction107
5.1	1..1	Resolution Of Investigation V09 +Modification Details ++Modification Status Identification	SEPA Rulebook SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	AT-Q009 Reference of the Beneficiary PSP for inter-PSP fee and/or compensation payment. Modification Status Identification Unique and unambiguous identifier of a modification request status, as assigned by the assigner. Usage: The modification status identification can be used for reconciliation or to link tasks relating to the modification request. ModStsId Max35Text 1 .. 35 1 .. 35
5.2	0..1	Resolution Of Investigation V09 +Modification Details ++Resolved Case	ISO Name ISO Definition XML Tag Type	Resolved Case Identifies the resolved case. RslvdCase Case5
5.3	1..1	Resolution Of Investigation V09 +Modification Details ++Original Group Information	ISO Name ISO Definition XML Tag Type	Original Group Information Provides information on the original message. OrgnlGrpInf OriginalGroupInformation29
5.4	1..1	Resolution Of Investigation V09 +Modification Details ++Original Group Information +++Original Message Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Message Identification Point to point reference assigned by the original instructing party to unambiguously identify the original message. OrgnlMsgId Max35Text 1 .. 35 1 .. 35
5.5	1..1	Resolution Of Investigation V09 +Modification Details ++Original Group Information +++Original Message Name Identification	SEPA Usage Rule(s) Must begin with 'pacs.008'. The addition of a variant number and version number is optional. ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Message Name Identification Specifies the original message name identifier to which the message refers, for example, pacs.003.001.01 or MT103. OrgnlMsgNmId Max35Text 1 .. 35 1 .. 35
5.6	0..1	Resolution Of Investigation V09 +Modification Details ++Original Group Information +++Original Creation Date Time	ISO Name ISO Definition XML Tag Type	Original Creation Date Time Original date and time at which the message was created. OrgnlCreDtTm ISODateTime

#	SEPA Mult	Message Element	Inter-PSP Confirmed Positive Response to camt.087 SEPA Core Requirements	
5.7	0..1	Resolution Of Investigation V09 +Modification Details ++Original Payment Information Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Payment Information Identification Unique identification, as assigned by the original sending party, to unambiguously identify the original payment information group. OrgnPmtInflId Max35Text 1 .. 35 1 .. 35
5.8	0..1	Resolution Of Investigation V09 +Modification Details ++Original Instruction Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Instruction Identification Unique identification, as assigned by the original instructing party for the original instructed party, to unambiguously identify the original instruction. OrgnlInstrId Max35Text 1 .. 35 1 .. 35
5.9	1..1	Resolution Of Investigation V09 +Modification Details ++Original End To End Identification	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	AT-T014 <i>The Originator's reference of the SEPA Credit Transfer Transaction.</i> Mandatory. Original End To End Identification Unique identification, as assigned by the original initiating party, to unambiguously identify the original transaction. OrgnlEndToEndId Max35Text 1 .. 35 1 .. 35
5.10	1..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Identification	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	AT-T054 <i>The Originator PSP's reference of the SEPA Credit Transfer Transaction.</i> Mandatory. Original Transaction Identification Unique identification, as assigned by the original first instructing agent, to unambiguously identify the transaction. OrgnlTxId Max35Text 1 .. 35 1 .. 35
5.11	0..1	Resolution Of Investigation V09 +Modification Details ++Original Clearing System Reference	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Clearing System Reference Unique reference, as assigned by the original clearing system, to unambiguously identify the original instruction. OrgnlClrSysRef Max35Text 1 .. 35 1 .. 35
5.12	0..1	Resolution Of Investigation V09 +Modification Details ++Original UETR	ISO Name ISO Definition XML Tag Type Pattern	Original UETR Universally unique identifier to provide the original end-to-end reference of a payment transaction. OrgnlUETR UUIDv4Identifier [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}
5.13	0..n	Resolution Of Investigation V09 +Modification Details ++Modification Status Reason Information	ISO Name ISO Definition XML Tag Type	Modification Status Reason Information Provides detailed information on the modification status reason. ModStsRsnInf ModificationStatusReason2

#	SEPA Mult	Message Element	Inter-PSP Confirmed Positive Response to camt.087 SEPA Core Requirements		
5.14	0..1	Resolution Of Investigation V09 +Modification Details ++Resolution Related Information	ISO Name ISO Definition XML Tag Type	Resolution Related Information Reference of a return or a reversal transaction that is initiated to fix the case under investigation as part of the resolution. RsltnRltdInf ResolutionData1	
5.15	0..1	Resolution Of Investigation V09 +Modification Details ++Original Interbank Settlement Amount	ISO Name ISO Definition XML Tag Type <i>SEPA FractDigits</i> TotalDigits <i>SEPA Inclusive</i>	Original Interbank Settlement Amount Amount of money moved between the instructing agent and the instructed agent, as provided in the original instruction. OrgnlIntrBkSttlmAmt ActiveOrHistoricCurrencyAndAmount 5 18 0 ..	
5.16	0..1	Resolution Of Investigation V09 +Modification Details ++Original Interbank Settlement Date	ISO Name ISO Definition XML Tag Type	Original Interbank Settlement Date Date, as provided in the original transaction, on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. OrgnlIntrBkSttlmDt ISODate	
5.17	0..1	Resolution Of Investigation V09 +Modification Details ++Assigner	ISO Name ISO Definition XML Tag Type	Assigner Party who assigns the case. Usage: This is also the agent that instructs the next party in the chain to carry out the (set of) cancellation request(s). Assgnr Party40Choice	
5.18	0..1	Resolution Of Investigation V09 +Modification Details ++Assignee	ISO Name ISO Definition XML Tag Type	Assignee Party to which the case is assigned. Usage: This is also the agent that is instructed by the previous party in the chain to carry out the (set of) cancellation request(s). Assgne Party40Choice	
5.19	1..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference	<i>SEPA Rulebook</i> <i>SEPA Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	An exact copy of all attributes of DS-02 of the initially sent pacs.008 to which the claim refers. The yellow shaded message elements under 'Original Transaction Reference' must be populated with the same value as the message elements of the original instruction. Mandatory. Original Transaction Reference Key elements used to identify the original transaction that is being referred to. OrgnlTxRef OriginalTransactionReference28	
5.20	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Interbank Settlement Amount	<i>SEPA Rulebook</i> <i>SEPA Rulebook</i> ISO Name ISO Definition XML Tag Type <i>SEPA FractDigits</i> TotalDigits <i>SEPA Inclusive</i>	AT-T002 Amount of the SEPA Credit Transfer in Euro. Interbank Settlement Amount Amount of money moved between the instructing agent and the instructed agent. IntrBkSttlmAmt ActiveOrHistoricCurrencyAndAmount 2 18 0.01 .. 999999999.99	

#	SEPA Mult	Message Element	Inter-PSP Confirmed Positive Response to camt.087 SEPA Core Requirements	
5.21	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Amount	ISO Name ISO Definition XML Tag Type	Amount Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party. Amt AmountType4Choice
5.22	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Interbank Settlement Date	SEPA Rulebook ISO Name ISO Definition XML Tag Type	AT-T051 Settlement Date of the Credit Transfer in Euro. Interbank Settlement Date Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. IntrBkSttlmDt ISODate
5.23	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Requested Collection Date	ISO Name ISO Definition XML Tag Type	Requested Collection Date Date and time at which the creditor requests that the amount of money is to be collected from the debtor. ReqdColltnDt ISODate
5.24	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Requested Execution Date	ISO Name ISO Definition XML Tag Type	Requested Execution Date Date at which the initiating party requests the clearing agent to process the payment. Usage: This is the date on which the debtor's account is to be debited. If payment by cheque, the date when the cheque must be generated by the bank. ReqdExctnDt DateAndDateTime2Choice
5.25	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Creditor Scheme Identification	ISO Name ISO Definition XML Tag Type	Creditor Scheme Identification Credit party that signs the mandate. CdtrSchmId PartyIdentification135
5.26	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Settlement Information	ISO Name ISO Definition XML Tag Type	Settlement Information Specifies the details on how the settlement of the original transaction(s) between the instructing agent and the instructed agent was completed. SttlmInf SettlementInstruction7
5.27	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Payment Type Information	SEPA Rulebook ISO Name ISO Definition XML Tag Type	AT-T001 Identification code of the Scheme. AT-T008 Category Purpose of the Credit Transfer. If the original transaction was sent according to Annex V (Use of Extended Remittance Information) of the SCT Rulebook (refer to section 'Inter-PSP payment with use of the Extended Remittance Information option' below), then 'Local Instrument/Code' must be populated with 'PERI' (Payment with Extended Remittance Information). Payment Type Information Set of elements used to further specify the type of transaction. PmtTpInf PaymentTypeInformation27
5.28	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Payment Method	ISO Name ISO Definition XML Tag Type	Payment Method Specifies the means of payment that will be used to move the amount of money. PmtMtd PaymentMethod4Code

#	SEPA Mult	Message Element	Inter-PSP Confirmed Positive Response to camt.087 SEPA Core Requirements	
5.29	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Mandate Related Information	ISO Name ISO Definition XML Tag Type	Mandate Related Information Provides further details of the mandate signed between the creditor and the debtor. MndtRltdInf MandateRelatedInformation14
5.30	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Remittance Information	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-T009 Remittance information or AT-T010 The unstructured Remittance Information sent by the Originator to the Beneficiary in the Credit Transfer Instruction (in case of use of the Extended Remittance Information (ERI) option in the original SEPA Credit Transfer, AT-T011 The structured Remittance Information sent by the Originator to the Beneficiary in the SEPA Credit Transfer Instruction, will NOT be transported here).</i> Remittance Information Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system. RmtInf RemittanceInformation16
5.31	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Ultimate Debtor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-P006 The name of the Originator Reference Party.</i> <i>AT-P007 The identification code of the Originator Reference Party.</i> <i>Only 'Party' is allowed.</i> Ultimate Debtor Ultimate party that owes an amount of money to the (ultimate) creditor. UltmtDbtr Party40Choice
5.32	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Debtor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-P001 Name of the Originator.</i> <i>AT-P005 Address of the Originator.</i> <i>AT-P004 Originator's Identification Code.</i> <i>Only 'Party' is allowed.</i> Debtor Party that owes an amount of money to the (ultimate) creditor. Dbtr Party40Choice
5.33	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Debtor Account	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-D001 The IBAN of the account of the Originator.</i> <i>AT-P003 The Proxy/Alias of the account of the Originator.</i> Debtor Account Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction. DbtrAcct CashAccount38
5.34	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Debtor Agent	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-D002 The BIC code of the Originator PSP.</i> Debtor Agent Financial institution servicing an account for the debtor. DbtrAgt BranchAndFinancialInstitutionIdentification6
5.35	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Debtor Agent Account	ISO Name ISO Definition XML Tag Type	Debtor Agent Account Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain. DbtrAgtAcct CashAccount38

#	SEPA Mult	Message Element	Inter-PSP Confirmed Positive Response to camt.087 SEPA Core Requirements	
5.36	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Creditor Agent	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-C002 The BIC code of the Beneficiary PSP.</i> Creditor Agent Financial institution servicing an account for the creditor. CdtrAgt BranchAndFinancialInstitutionIdentification6
5.37	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Creditor Agent Account	ISO Name ISO Definition XML Tag Type	Creditor Agent Account Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction. CdtrAgtAcct CashAccount38
5.38	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Creditor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-E001 Name of the Beneficiary.</i> <i>AT-E004 Address of the Beneficiary.</i> <i>AT-E005 Beneficiary Identification Code.</i> Only 'Party' is allowed. Creditor Party to which an amount of money is due. Cdtr Party40Choice
5.39	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Creditor Account	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-C001 The IBAN of the account of the Beneficiary.</i> <i>AT-E003 The Proxy/Alias of the account of the Beneficiary.</i> Creditor Account Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction. CdtrAcct CashAccount38
5.40	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Ultimate Creditor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-E007 The name of the Beneficiary Reference Party.</i> <i>AT-E010 The identification code of the Beneficiary Reference Party.</i> Only 'Party' is allowed. Ultimate Creditor Ultimate party to which an amount of money is due. UltmtCdtr Party40Choice
5.41	0..1	Resolution Of Investigation V09 +Modification Details ++Original Transaction Reference +++Purpose	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-T007 The purpose of the SEPA Credit Transfer.</i> Purpose Underlying reason for the payment transaction. Usage: Purpose is used by the end customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain. Purp Purpose2Choice
6.0	0..1	Resolution Of Investigation V09 +Claim Non Receipt Details	ISO Name ISO Definition XML Tag Type	Claim Non Receipt Details Specifies the details of the underlying transaction for which a claim non receipt has been initiated. ClmNonRctDtls ClaimNonReceipt2Choice

#	SEPA Mult	Message Element	Inter-PSP Confirmed Positive Response to camt.087 SEPA Core Requirements		
7.0	0..1	Resolution Of Investigation V09 +Statement Details	ISO Name ISO Definition XML Tag Type	Statement Details Details on the underlying statement entry. StmtDtls StatementResolutionEntry4	
8.0	0..1	Resolution Of Investigation V09 +Correction Transaction	ISO Name ISO Definition XML Tag Type	Correction Transaction References a transaction initiated to fix the case under investigation. CrrctnTx CorrectiveTransaction4Choice	
9.0	1..1	Resolution Of Investigation V09 +Resolution Related Information	SEPA Usage Rule(s) <i>Mandatory.</i> ISO Name ISO Definition XML Tag Type	Resolution Related Information Reference to fix the case under investigation as part of the resolution. RsltnRltdInf ResolutionData1	
9.1	0..1	Resolution Of Investigation V09 +Resolution Related Information ++End To End Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	End To End Identification Unique identification, as assigned by the original initiating party, to unambiguously identify the original transaction. EndToEndId Max35Text 1 .. 35 1 .. 35	
9.2	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Transaction Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Transaction Identification Unique identification, as assigned by the original first instructing agent, to unambiguously identify the transaction. TxId Max35Text 1 .. 35 1 .. 35	
9.3	0..1	Resolution Of Investigation V09 +Resolution Related Information ++UETR	ISO Name ISO Definition XML Tag Type Pattern	UETR Universally unique identifier to provide an end-to-end reference of a payment transaction. UETR UUIDv4Identifier [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}	
9.4	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Interbank Settlement Amount	ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits SEPA Inclusive	Interbank Settlement Amount Amount of money moved between the instructing agent and the instructed agent. IntrBkStlmtAmt ActiveOrHistoricCurrencyAndAmount 5 18 0 ..	
9.5	1..1	Resolution Of Investigation V09 +Resolution Related Information ++Interbank Settlement Date	SEPA Rulebook SEPA Usage Rule(s) <i>AT-Q005 New value date of the credit transfer based on the new settlement date.</i> ISO Name ISO Definition XML Tag Type	Interbank Settlement Date Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. IntrBkStlmtDt ISODate	
9.6	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Clearing Channel	ISO Name ISO Definition XML Tag Type	Clearing Channel Specifies the clearing channel to be used to process the payment instruction. ClrChnl ClearingChannel2Code	

#	SEPA Mult	Message Element	Inter-PSP Confirmed Positive Response to camt.087 SEPA Core Requirements	
9.7	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Compensation	<p>SEPA Rulebook <i>AT-Q006 The interest compensation recovered by the Beneficiary PSP from the Originator PSP.</i></p> <p>SEPA Usage Rule(s) <i>Only allowed if compensation is to be received a posteriori, i.e. after application of the value date correction.</i></p> <p>ISO Name Compensation</p> <p>ISO Definition Provides the details of the compensation made due to the modification or cancellation of a previous payment.</p> <p>XML Tag Compstn</p> <p>Type Compensation2</p>	
9.8	1..1	Resolution Of Investigation V09 +Resolution Related Information ++Compensation +++Amount	<p>SEPA Usage Rule(s) <i>Only 'EUR' is allowed. Amount must be 0.01 or more and 99999999.99 or less. The fractional part has a maximum of two digits.</i></p> <p>SEPA Format Rule(s)</p> <p>ISO Name Amount</p> <p>ISO Definition Amount of money to be paid in compensation.</p> <p>XML Tag Amt</p> <p>Type ActiveCurrencyAndAmount</p> <p>SEPA FractDigits 2</p> <p>TotalDigits 18</p> <p>SEPA Inclusive 0.01 .. 99999999.99</p>	
9.9	1..1	Resolution Of Investigation V09 +Resolution Related Information ++Compensation +++Debtor Agent	<p>SEPA Usage Rule(s) <i>AT-D002 The BIC code of the Originator PSP. Only 'BICFI' is allowed.</i></p> <p>ISO Name Debtor Agent</p> <p>ISO Definition Financial institution servicing an account for the debtor.</p> <p>XML Tag DbtrAgt</p> <p>Type BranchAndFinancialInstitutionIdentification6</p>	<p>Usage: The debtor agent is the payer of the compensation amount.</p>
9.10	1..1	Resolution Of Investigation V09 +Resolution Related Information ++Compensation +++Creditor Agent	<p>ISO Name Creditor Agent</p> <p>ISO Definition Financial institution servicing an account for the creditor.</p> <p>XML Tag CdtrAgt</p> <p>Type BranchAndFinancialInstitutionIdentification6</p>	<p>Usage: The creditor agent is the payee of the compensation amount.</p>
9.11	1..1	Resolution Of Investigation V09 +Resolution Related Information ++Compensation +++Creditor Agent ++++Financial Institution Identification	<p>ISO Name Financial Institution Identification</p> <p>ISO Definition Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.</p> <p>XML Tag FinInstnId</p> <p>Type FinancialInstitutionIdentification18</p>	
9.12	1..1	Resolution Of Investigation V09 +Resolution Related Information ++Compensation +++Creditor Agent ++++Financial Institution Identification +++++BICFI	<p>SEPA Rulebook <i>AT-C002 The BIC code of the Beneficiary PSP.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name BICFI</p> <p>ISO Definition Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".</p> <p>XML Tag BICFI</p> <p>Type BICFIDec2014Identifier</p> <p>Pattern [A-Z0-9]{4,4}[A-Z]{2,2}[A-Z0-9]{2,2}([A-Z0-9]{3,3}){0,1}</p>	

#	SEPA Mult	Message Element	Inter-PSP Confirmed Positive Response to camt.087 SEPA Core Requirements	
9.13	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Compensation +++Creditor Agent ++++Financial Institution Identification +++++Clearing System Member Identification	ISO Name ISO Definition XML Tag Type	Clearing System Member Identification Information used to identify a member within a clearing system. ClrSysMmbld ClearingSystemMemberIdentification2
9.14	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Compensation +++Creditor Agent ++++Financial Institution Identification +++++LEI	ISO Name ISO Definition XML Tag Type Pattern	LEI Legal entity identifier of the financial institution. LEI LEIIDentifier [A-Z0-9]{18,18}{0-9}{2,2}
9.15	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Compensation +++Creditor Agent ++++Financial Institution Identification +++++Name	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Name Name by which an agent is known and which is usually used to identify that agent. Nm Max140Text 1 .. 140 1 .. 140
9.16	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Compensation +++Creditor Agent ++++Financial Institution Identification +++++Postal Address	ISO Name ISO Definition XML Tag Type	Postal Address Information that locates and identifies a specific address, as defined by postal services. PstlAdr PostalAddress24
9.17	1..1	Resolution Of Investigation V09 +Resolution Related Information ++Compensation +++Creditor Agent ++++Financial Institution Identification +++++Other	SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type	Other Unique identification of an agent, as assigned by an institution, using an identification scheme. Othr GenericFinancialIdentification1
9.18	1..1	Resolution Of Investigation V09 +Resolution Related Information ++Compensation +++Creditor Agent ++++Financial Institution Identification +++++Other ++++++Identification	SEPA Usage Rule(s) Only IBAN is allowed. ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Identification Unique and unambiguous identification of a person. Id Max35Text 1 .. 35 1 .. 35
9.19	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Compensation +++Creditor Agent ++++Financial Institution Identification +++++Other ++++++Scheme Name	ISO Name ISO Definition XML Tag Type	Scheme Name Name of the identification scheme. SchmeNm FinancialIdentificationSchemeName1Choice
9.20	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Compensation +++Creditor Agent ++++Financial Institution Identification +++++Other ++++++Issuer	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Issuer Entity that assigns the identification. Issr Max35Text 1 .. 35 1 .. 35

#	SEPA Mult	Message Element	Inter-PSP Confirmed Positive Response to camt.087 SEPA Core Requirements	
9.21	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Compensation +++Creditor Agent ++++Branch Identification	ISO Name ISO Definition XML Tag Type	Branch Identification Identifies a specific branch of a financial institution. Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level. BrnchId BranchData3
9.22	1..1	Resolution Of Investigation V09 +Resolution Related Information ++Compensation +++Reason	SEPA Usage Rule(s) Only "VADA" is allowed. ISO Name ISO Definition XML Tag Type	Reason Reason for the payment compensation. Rsn CompensationReason1Choice
9.23	1..1	Resolution Of Investigation V09 +Resolution Related Information ++Compensation +++Reason ++++Code	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Code Reason for the payment compensation, in a coded form. Cd ExternalPaymentCompensationReason1Code 1 .. 4 1 .. 4
	1..1		SEPA Code Restrictions	
9.24	1..1	Resolution Of Investigation V09 +Resolution Related Information ++Compensation +++Reason ++++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Proprietary Reason for the payment compensation, in a proprietary form. Prtry Max35Text 1 .. 35 1 .. 35
9.25	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Charges	SEPA Rulebook SEPA Usage Rule(s)	AT-Q007 Fee for handling the SCT inquiry. Only one occurrence is allowed. Only allowed if charges are to be received <i>a posteriori</i> , i.e. after application of the value date correction.
	1..1		ISO Name ISO Definition XML Tag Type	Charges Provides information on the charges to be paid by the charge bearer(s) related to the payment transaction. Chrgs Charges7
9.26	1..1	Resolution Of Investigation V09 +Resolution Related Information ++Charges +++Amount	SEPA Usage Rule(s) Only 'EUR' is allowed. SEPA Format Rule(s) ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits SEPA Inclusive	Amount must be 0.01 or more and 999999999.99 or less. The fractional part has a maximum of two digits. Amount Transaction charges to be paid by the charge bearer. Amt ActiveOrHistoricCurrencyAndAmount 2 18 0.01 .. 999999999.99

#	SEPA Mult	Message Element	Inter-PSP Confirmed Positive Response to camt.087 SEPA Core Requirements	
9.27	1..1	Resolution Of Investigation V09 +Resolution Related Information ++Charges +++Agent	ISO Name ISO Definition XML Tag Type	Agent Agent that takes the transaction charges or to which the transaction charges are due. Agt BranchAndFinancialInstitutionIdentification6
9.28	1..1	Resolution Of Investigation V09 +Resolution Related Information ++Charges +++Agent ++++Financial Institution Identification	ISO Name ISO Definition XML Tag Type	Financial Institution Identification Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme. FinInstnId FinancialInstitutionIdentification18
9.29	1..1	Resolution Of Investigation V09 +Resolution Related Information ++Charges +++Agent ++++Financial Institution Identification +++++BICFI	SEPA Rulebook SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type Pattern	AT-C002 The BIC code of the Beneficiary PSP. BICFI Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)". BICFI BICFIDec2014Identifier [A-Z0-9]{4,4}[A-Z]{2,2}[A-Z0-9]{2,2}{[A-Z0-9]{3,3}}{0,1}
9.30	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Charges +++Agent ++++Financial Institution Identification +++++Clearing System Member Identification	ISO Name ISO Definition XML Tag Type	Clearing System Member Identification Information used to identify a member within a clearing system. ClrSysMmbld ClearingSystemMemberIdentification2
9.31	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Charges +++Agent ++++Financial Institution Identification +++++LEI	ISO Name ISO Definition XML Tag Type Pattern	LEI Legal entity identifier of the financial institution. LEI LEIIdentifier [A-Z0-9]{18,18}{0-9}{2,2}
9.32	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Charges +++Agent ++++Financial Institution Identification +++++Name	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Name Name by which an agent is known and which is usually used to identify that agent. Nm Max140Text 1 .. 140 1 .. 140
9.33	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Charges +++Agent ++++Financial Institution Identification +++++Postal Address	ISO Name ISO Definition XML Tag Type	Postal Address Information that locates and identifies a specific address, as defined by postal services. PstlAdr PostalAddress24
9.34	1..1	Resolution Of Investigation V09 +Resolution Related Information ++Charges +++Agent ++++Financial Institution Identification +++++Other	SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type	Other Unique identification of an agent, as assigned by an institution, using an identification scheme. Othr GenericFinancialIdentification1

#	SEPA Mult	Message Element	Inter-PSP Confirmed Positive Response to camt.087 SEPA Core Requirements	
9.35	1..1	Resolution Of Investigation V09 +Resolution Related Information ++Charges +++Agent ++++Financial Institution Identification +++++Other ++++++Identification	<p>SEPA Usage Rule(s) Only IBAN is allowed.</p> <p>ISO Name Identification</p> <p>ISO Definition Unique and unambiguous identification of a person.</p> <p>XML Tag Id</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>	
9.36	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Charges +++Agent ++++Financial Institution Identification +++++Other ++++++Scheme Name	<p>ISO Name Scheme Name</p> <p>ISO Definition Name of the identification scheme.</p> <p>XML Tag SchmeNm</p> <p>Type FinancialIdentificationSchemeName Choice</p>	
9.37	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Charges +++Agent ++++Financial Institution Identification +++++Other ++++++Issuer	<p>ISO Name Issuer</p> <p>ISO Definition Entity that assigns the identification.</p> <p>XML Tag Issr</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>	
9.38	0..1	Resolution Of Investigation V09 +Resolution Related Information ++Charges +++Agent ++++Branch Identification	<p>ISO Name Branch Identification</p> <p>ISO Definition Identifies a specific branch of a financial institution.</p> <p>XML Tag BrnchId</p> <p>Type BranchData3</p> <p>Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.</p>	
10.0	0..n	Resolution Of Investigation V09 +Supplementary Data	<p>ISO Name Supplementary Data</p> <p>ISO Definition Additional information that cannot be captured in the structured elements and/or any other specific block.</p> <p>XML Tag SplmtryData</p> <p>Type SupplementaryData1</p>	



2.19 Inter-PSP Fee and/or Compensation Payment Dataset (DS-11)

2.19.1 Use of FI to FI Customer Credit Transfer (pacs.008.001.08)

The message is used to transport the instruction related to the payment of:

- An inter-PSP fee for handling the SCT inquiry in case of a positive response to an SCT inquiry for the reasons 'Claim of Non-Receipt' and 'Claim for Value Date Correction', and/or
- Interest compensation resulting from a positive response to an SCT inquiry for the reason 'Claim for Value Date Correction'.

The message caters for the settlement of SCT inquiry fees and/or interest compensation payments for a single SCT inquiry case or multiple SCT inquiry cases.

Note: The use case of the message is implied by the 'Name', 'pacs.008.001.08', with 'Category Purpose' set to "FCOL" (Fee Collection), "INTE" (Interest) or "FCIN" (Fee Collection and Interest).

Note: The Beneficiary PSP may wish that the SCT inquiry fee and interest compensation relating to the same inquiry are paid in two separate payments or together in one payment.

Note: It is allowed to send a mix of DS-02 and DS-11 transactions, i.e. one pacs.008.001.08 message can contain 'Credit Transfer Transaction Information' blocks as per DS-02 (Inter-PSP Payment Dataset, refer to section 2.1) and DS-11 (the present section). In such case:

- 'Group Header' must be formatted in accordance with DS-02 requirements (refer to section 2.1),
- 'Payment Type Information' must be present only in 'Credit Transfer Transaction Information' in order to allow mentioning under 'Category Purpose' the codes necessary under the present section,
- 'Credit Transfer Transaction Information' block(s) relating to DS-11 must be formatted as per this section 2.19.

Note: The present section only describes the transactions as per DS-11, i.e. the Inter-PSP Fee and/or Compensation Payment Dataset.

#	SEPA Mult	Message Element	Inter-PSP Fee and/or Compensation Payment SEPA Core Requirements	
		Document	XML Tag Type	Document Document
	1..1	FITo FICustomer Credit Transfer V08	ISO Name ISO Definition	FITo FICustomer Credit Transfer V08 Scope The FinancialInstitutionToFinancialInstitutionCustomerCreditTransfer message is sent by the debtor agent to the creditor agent, directly or through other agents and/or a payment clearing and settlement system. It is used to move funds from a debtor account to a creditor. FIToFICstmrcdtTrf FIToFICustomerCreditTransferV08
1.0	1..1	FITo FICustomer Credit Transfer V08 +Group Header	ISO Name ISO Definition XML Tag Type	Group Header Set of characteristics shared by all individual transactions included in the message. GrpHdr GroupHeader93
1.1	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Message Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Message Identification Point to point reference, as assigned by the instructing party, and sent to the next party in the chain to unambiguously identify the message. Usage: The instructing party has to make sure that MessageIdentification is unique per instructed party for a pre-agreed period. MsgId Max35Text 1 .. 35 1 .. 35
1.2	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Creation Date Time	ISO Name ISO Definition XML Tag Type	Creation Date Time Date and time at which the message was created. CreDtTm ISODateTime
1.3	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Batch Booking	ISO Name ISO Definition XML Tag Type	Batch Booking Identifies whether a single entry per individual transaction or a batch entry for the sum of the amounts of all transactions within the group of a message is requested. Usage: Batch booking is used to request and not order a possible batch booking. BtchBookg BatchBookingIndicator
1.4	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Number Of Transactions	ISO Name ISO Definition XML Tag Type Pattern	Number Of Transactions Number of individual transactions contained in the message. NbOfTxns Max15NumericText [0-9]{1,15}
1.5	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Control Sum	ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits	Control Sum Total of all individual amounts included in the message, irrespective of currencies. CtrlSum DecimalNumber 17 18

#	SEPA Mult	Message Element	Inter-PSP Fee and/or Compensation Payment SEPA Core Requirements
1.6	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Total Interbank Settlement Amount	<p>SEPA Usage Rule(s) <i>Mandatory.</i> <i>Only 'EUR' is allowed.</i> <i>Amount must be 0.01 or more and 9999999999999.99 or less.</i> <i>The fractional part has a maximum of two digits.</i></p> <p>SEPA Format Rule(s)</p> <p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p> <p>SEPA FractDigits</p> <p>TotalDigits</p> <p>SEPA Inclusive</p> <p>Total Interbank Settlement Amount Total amount of money moved between the instructing agent and the instructed agent. TtlIntrBkStlmtAmt ActiveCurrencyAndAmount 2 18 0.01 .. 9999999999999.99</p>
1.7	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Interbank Settlement Date	<p>SEPA Rulebook</p> <p><i>AT-Q010 Settlement date of the inter-PSP fee/or compensation amount.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p> <p>Interbank Settlement Date Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. IntrBkStlmtDt ISODate</p>
1.8	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Settlement Information	<p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p> <p>Settlement Information Specifies the details on how the settlement of the transaction(s) between the instructing agent and the instructed agent is completed. SttlmInf SettlementInstruction7</p>
1.9	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Settlement Information +++Settlement Method	<p>SEPA Usage Rule(s) <i>Only "CLRG", "INGA" and "INDA" are allowed.</i></p> <p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p> <p>Settlement Method Method used to settle the (batch of) payment instructions. SttlmMtd SettlementMethod1Code</p> <p>SEPA Code Restrictions</p> <p>CLRG</p> <p><i>ClearingSystem</i> <i>Settlement is done through a payment clearing system.</i></p> <p>INDA</p> <p><i>InstructedAgent</i> <i>Settlement is done by the agent instructed to execute a payment instruction.</i></p> <p>INGA</p> <p><i>InstructingAgent</i> <i>Settlement is done by the agent instructing and forwarding the payment to the next party in the payment chain.</i></p>
1.10	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Settlement Information +++Settlement Account	<p>SEPA Usage Rule(s) <i>Only 'Identification' is allowed.</i></p> <p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p> <p>Settlement Account A specific purpose account used to post debit and credit entries as a result of the transaction. SttlmAcct CashAccount38</p>
1.11	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Settlement Information +++Clearing System	<p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p> <p>Clearing System Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed. ClrSys ClearingSystemIdentification3Choice</p>
	1..1		XML Tag
			xs:choice

#	SEPA Mult	Message Element	Inter-PSP Fee and/or Compensation Payment SEPA Core Requirements	
1.12	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Settlement Information +++Clearing System ++++Code	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Code Infrastructure through which the payment instruction is processed, as published in an external clearing system identification code list. Cd ExternalCashClearingSystem1Code 1 .. 3 I .. 3
1.13	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Settlement Information +++Clearing System ++++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Proprietary Clearing system identification in a proprietary form. Prtry Max35Text 1 .. 35 I .. 35
1.14	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Settlement Information +++Instructing Reimbursement Agent	ISO Name ISO Definition XML Tag Type	Instructing Reimbursement Agent Agent through which the instructing agent will reimburse the instructed agent. Usage: If InstructingAgent and InstructedAgent have the same reimbursement agent, then only InstructingReimbursementAgent must be used. InstgRmbrsmntAgt BranchAndFinancialInstitutionIdentification6
1.15	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Settlement Information +++Instructing Reimbursement Agent Account	ISO Name ISO Definition XML Tag Type	Instructing Reimbursement Agent Account Unambiguous identification of the account of the instructing reimbursement agent account at its servicing agent in the payment chain. InstgRmbrsmntAgtAcct CashAccount38
1.16	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Settlement Information +++Instructed Reimbursement Agent	ISO Name ISO Definition XML Tag Type	Instructed Reimbursement Agent Agent at which the instructed agent will be reimbursed. Usage: If InstructedReimbursementAgent contains a branch of the InstructedAgent, then the party in InstructedAgent will claim reimbursement from that branch/will be paid by that branch. Usage: If InstructingAgent and InstructedAgent have the same reimbursement agent, then only InstructingReimbursementAgent must be used. InstdRmbrsmntAgt BranchAndFinancialInstitutionIdentification6
1.17	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Settlement Information +++Instructed Reimbursement Agent Account	ISO Name ISO Definition XML Tag Type	Instructed Reimbursement Agent Account Unambiguous identification of the account of the instructed reimbursement agent account at its servicing agent in the payment chain. InstdRmbrsmntAgtAcct CashAccount38
1.18	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Settlement Information +++Third Reimbursement Agent	ISO Name ISO Definition XML Tag Type	Third Reimbursement Agent Agent at which the instructed agent will be reimbursed. Usage: If ThirdReimbursementAgent contains a branch of the InstructedAgent, then the party in InstructedAgent will claim reimbursement from that branch/will be paid by that branch. ThrdRmbrsmntAgt BranchAndFinancialInstitutionIdentification6

#	SEPA Mult	Message Element	Inter-PSP Fee and/or Compensation Payment SEPA Core Requirements	
1.19	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Settlement Information +++Third Reimbursement Agent Account	ISO Name ISO Definition XML Tag Type	Third Reimbursement Agent Account Unambiguous identification of the account of the third reimbursement agent account at its servicing agent in the payment chain. ThrdRmbrsmntAgtAcct CashAccount38
1.20	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	'Payment Type Information' must be provided either here or under 'Credit Transfer Transaction Information'. Payment Type Information Set of elements used to further specify the type of transaction. PmtTpInf PaymentTypeInformation28
1.21	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information +++Instruction Priority	ISO Name ISO Definition XML Tag Type	Instruction Priority Indicator of the urgency or order of importance that the instructing party would like the instructed party to apply to the processing of the instruction. InstrPrty Priority2Code
1.22	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information +++Clearing Channel	ISO Name ISO Definition XML Tag Type	Clearing Channel Specifies the clearing channel to be used to process the payment instruction. ClrChnl ClearingChannel2Code
1.23	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information +++Service Level	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Mandatory. Only one occurrence is allowed. Service Level Agreement under which or rules under which the transaction should be processed. SvcLvl ServiceLevel8Choice
	1..1		XML Tag	xs:choice
1.24	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information +++Service Level ++++Code	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	AT-T001 The identification code of the Scheme. Only "SEPA" is allowed. Code Specifies a pre-agreed service or level of service between the parties, as published in an external service level code list. Cd ExternalServiceLevel1Code 1 .. 4 1 .. 4
			SEPA	SingleEuroPaymentsArea Payment must be executed following the Single Euro Payments Area scheme.
1.25	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information +++Service Level ++++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Proprietary Specifies a pre-agreed service or level of service between the parties, as a proprietary code. Prtry Max35Text 1 .. 35 1 .. 35

#	SEPA Mult	Message Element	Inter-PSP Fee and/or Compensation Payment SEPA Core Requirements								
1.26	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information +++Local Instrument	<p>SEPA Usage Rule(s) Only used if bilaterally agreed between the Debtor PSP and the Creditor PSP.</p> <p>ISO Name Local Instrument</p> <p>ISO Definition User community specific instrument.</p> <p>Usage: This element is used to specify a local instrument, local clearing option and/or further qualify the service or service level.</p> <p>XML Tag Type LclInstrm LocalInstrument2Choice</p>								
	1..1		XML Tag xs:choice								
1.27	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information +++Local Instrument ++++Code	<p>ISO Name Code</p> <p>ISO Definition Specifies the local instrument, as published in an external local instrument code list.</p> <p>XML Tag Type Cd</p> <p>ISO Length ExternalLocalInstrument1Code</p> <p>SEPA Length 1 .. 35</p>								
1.28	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information +++Local Instrument ++++Proprietary	<p>ISO Name Proprietary</p> <p>ISO Definition Specifies the local instrument, as a proprietary code.</p> <p>XML Tag Type Prtry</p> <p>ISO Length Max35Text</p> <p>SEPA Length 1 .. 35</p>								
1.29	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information +++Category Purpose	<p>SEPA Rulebook AT-Q011 Category purpose of the inter-PSP fee and/or compensation payment.</p> <p>SEPA Usage Rule(s) Mandatory.</p> <p>ISO Name Category Purpose</p> <p>ISO Definition Specifies the high level purpose of the instruction based on a set of pre-defined categories.</p> <p>Usage: This is used by the initiating party to provide information concerning the processing of the payment. It is likely to trigger special processing by any of the agents involved in the payment chain.</p> <p>XML Tag Type CtgyPurp CategoryPurpose1Choice</p>								
	1..1		XML Tag xs:choice								
1.30	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information +++Category Purpose ++++Code	<p>SEPA Usage Rule(s) Only "FCOL", "INTE" or "FCIN" are allowed.</p> <p>ISO Name Code</p> <p>ISO Definition Category purpose, as published in an external category purpose code list.</p> <p>XML Tag Type Cd</p> <p>ISO Length ExternalCategoryPurpose1Code</p> <p>SEPA Length 1 .. 4</p> <p>SEPA Code Restrictions</p> <table border="1"> <tr> <td>FCIN</td> <td>FeeCollectionAndInterest Transaction is related to the payment of a fee and interest.</td> </tr> <tr> <td>FCOL</td> <td>FeeCollection A service that is settling card transaction related fees between two parties.</td> </tr> <tr> <td>INTE</td> <td>Interest Transaction is the payment of interest.</td> </tr> </table>			FCIN	FeeCollectionAndInterest Transaction is related to the payment of a fee and interest.	FCOL	FeeCollection A service that is settling card transaction related fees between two parties.	INTE	Interest Transaction is the payment of interest.
FCIN	FeeCollectionAndInterest Transaction is related to the payment of a fee and interest.										
FCOL	FeeCollection A service that is settling card transaction related fees between two parties.										
INTE	Interest Transaction is the payment of interest.										
1.31	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information +++Category Purpose ++++Proprietary	<p>ISO Name Proprietary</p> <p>ISO Definition Category purpose, in a proprietary form.</p> <p>XML Tag Type Prtry</p> <p>ISO Length Max35Text</p> <p>SEPA Length 1 .. 35</p>								

#	SEPA Mult	Message Element	Inter-PSP Fee and/or Compensation Payment SEPA Core Requirements
1.32	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Instructing Agent	<p>SEPA Usage Rule(s) Only 'BICFI' is allowed.</p> <p>ISO Name Instructing Agent</p> <p>ISO Definition Agent that instructs the next party in the chain to carry out the (set of) instruction(s).</p> <p>XML Tag Type InstgAgt BranchAndFinancialInstitutionIdentification6</p>
1.33	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Instructed Agent	<p>SEPA Usage Rule(s) Only 'BICFI' is allowed.</p> <p>ISO Name Instructed Agent</p> <p>ISO Definition Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s).</p> <p>XML Tag Type InstdAgt BranchAndFinancialInstitutionIdentification6</p>
2.0	1..n	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information	<p>ISO Name</p> <p>ISO Definition Set of elements providing information specific to the individual credit transfer(s).</p> <p>XML Tag Type CdtTrfTxInf CreditTransferTransaction39</p>
2.1	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Identification	<p>ISO Name</p> <p>ISO Definition Set of elements used to reference a payment instruction.</p> <p>XML Tag Type PmtId PaymentIdentification7</p>
2.2	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Identification +++Instruction Identification	<p>ISO Name</p> <p>ISO Definition Unique identification, as assigned by an instructing party for an instructed party, to unambiguously identify the instruction.</p> <p>XML Tag Type</p> <p>ISO Length</p> <p>SEPA Length</p> <p>Usage: The instruction identification is a point to point reference that can be used between the instructing party and the instructed party to refer to the individual instruction. It can be included in several messages related to the instruction.</p> <p>InstrId Max35Text 1 .. 35 1 .. 35</p>
2.3	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Identification +++End To End Identification	<p>SEPA Rulebook</p> <p>ISO Name</p> <p>ISO Definition AT-Q002 The specific SCT Inquiry reference of the Participant initiating the SCT inquiry.</p> <p>End To End Identification</p> <p>Unique identification, as assigned by the initiating party, to unambiguously identify the transaction. This identification is passed on, unchanged, throughout the entire end-to-end chain.</p> <p>Usage: The end-to-end identification can be used for reconciliation or to link tasks relating to the transaction. It can be included in several messages related to the transaction.</p> <p>Usage: In case there are technical limitations to pass on multiple references, the end-to-end identification must be passed on throughout the entire end-to-end chain.</p> <p>XML Tag Type</p> <p>ISO Length</p> <p>SEPA Length</p> <p>EndToEndId Max35Text 1 .. 35 1 .. 35</p>

#	SEPA Mult	Message Element	Inter-PSP Fee and/or Compensation Payment SEPA Core Requirements
2.4	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Identification +++Transaction Identification	<p>SEPA Usage Rule(s) <i>Mandatory.</i> <i>The Originator PSP's reference of the SEPA Credit Transfer Transaction.</i> <i>Must contain a reference that is meaningful to the Originator's PSP and is unique over time.</i> ISO Name ISO Definition XML Tag Type ISO Length SEPA Length</p> <p>Transaction Identification Unique identification, as assigned by the first instructing agent, to unambiguously identify the transaction that is passed on, unchanged, throughout the entire interbank chain. Usage: The transaction identification can be used for reconciliation, tracking or to link tasks relating to the transaction on the interbank level. Usage: The instructing agent has to make sure that the transaction identification is unique for a pre-agreed period. TxId Max35Text 1 .. 35 1 .. 35</p>
2.5	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Identification +++UETR	<p>ISO Name ISO Definition XML Tag Type Pattern</p> <p>UETR Universally unique identifier to provide an end-to-end reference of a payment transaction. UETR UUIDv4Identifier [a-f0-9]{8} - [a-f0-9]{4} - 4[a-f0-9]{3} - [89ab][a-f0-9]{3} - [a-f0-9]{12}</p>
2.6	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Identification +++Clearing System Reference	<p>ISO Name ISO Definition XML Tag Type ISO Length SEPA Length</p> <p>Clearing System Reference Unique reference, as assigned by a clearing system, to unambiguously identify the instruction. ClrSysRef Max35Text 1 .. 35 1 .. 35</p>
2.7	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Type Information	<p>SEPA Usage Rule(s) <i>'Payment Type Information' must be provided either here or under 'Group Header'.</i></p> <p>ISO Name ISO Definition XML Tag Type</p> <p>Payment Type Information Set of elements used to further specify the type of transaction. PmtTpInf PaymentTypeInformation28</p>
2.8	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Type Information +++Instruction Priority	<p>ISO Name ISO Definition XML Tag Type</p> <p>Instruction Priority Indicator of the urgency or order of importance that the instructing party would like the instructed party to apply to the processing of the instruction. InstrPrty Priority2Code</p>
2.9	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Type Information +++Clearing Channel	<p>ISO Name ISO Definition XML Tag Type</p> <p>Clearing Channel Specifies the clearing channel to be used to process the payment instruction. ClrChnl ClearingChannel2Code</p>
2.10	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Type Information +++Service Level	<p>SEPA Usage Rule(s) <i>Mandatory.</i> <i>Only one occurrence is allowed.</i></p> <p>ISO Name ISO Definition XML Tag Type</p> <p>Service Level Agreement under which or rules under which the transaction should be processed. SvcLvl ServiceLevel8Choice</p>
	1..1		XML Tag xs:choice

#	SEPA Mult	Message Element	Inter-PSP Fee and/or Compensation Payment SEPA Core Requirements	
2.11	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Type Information +++Service Level ++++Code	<p>SEPA Rulebook <i>AT-T001 The identification code of the SEPA electronic credit transfer Scheme.</i></p> <p>SEPA Usage Rule(s) <i>Only "SEPA" is allowed.</i></p> <p>ISO Name Code</p> <p>ISO Definition Specifies a pre-agreed service or level of service between the parties, as published in an external service level code list.</p> <p>XML Tag Cd</p> <p>Type ExternalServiceLevel1Code</p> <p>ISO Length 1 .. 4</p> <p>SEPA Length 1 .. 4</p>	SEPA Code Restrictions
				<p>SEPA <i>SingleEuroPaymentsArea</i> <i>Payment must be executed following the Single Euro Payments Area scheme.</i></p>
2.12	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Type Information +++Service Level ++++Proprietary	<p>ISO Name Proprietary</p> <p>ISO Definition Specifies a pre-agreed service or level of service between the parties, as a proprietary code.</p> <p>XML Tag Prtry</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>	
2.13	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Type Information +++Local Instrument	<p>SEPA Usage Rule(s) <i>Only used if bilaterally agreed between the Debtor PSP and the Creditor PSP.</i></p> <p>ISO Name Local Instrument</p> <p>ISO Definition User community specific instrument.</p> <p>XML Tag LclInstrm</p> <p>Type LocallInstrument2Choice</p>	<p>Usage: This element is used to specify a local instrument, local clearing option and/or further qualify the service or service level.</p>
	1..1		XML Tag xs:choice	
2.14	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Type Information +++Local Instrument ++++Code	<p>ISO Name Code</p> <p>ISO Definition Specifies the local instrument, as published in an external local instrument code list.</p> <p>XML Tag Cd</p> <p>Type ExternalLocalInstrument1Code</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>	
2.15	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Type Information +++Local Instrument ++++Proprietary	<p>ISO Name Proprietary</p> <p>ISO Definition Specifies the local instrument, as a proprietary code.</p> <p>XML Tag Prtry</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>	
2.16	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Type Information +++Category Purpose	<p>SEPA Rulebook <i>AT-Q011 Category Purpose of the inter-PSP fee and/or compensation payment</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name Category Purpose</p> <p>ISO Definition Specifies the high level purpose of the instruction based on a set of pre-defined categories.</p> <p>XML Tag CtgyPurp</p> <p>Type CategoryPurpose1Choice</p>	<p>Usage: This is used by the initiating party to provide information concerning the processing of the payment. It is likely to trigger special processing by any of the agents involved in the payment chain.</p>
	1..1		XML Tag xs:choice	

#	SEPA Mult	Message Element	Inter-PSP Fee and/or Compensation Payment SEPA Core Requirements							
2.17	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Type Information +++Category Purpose ++++Code	<p>SEPA Usage Rule(s) Only "FCOL", "INTE" or "FCIN" are allowed.</p> <p>ISO Name Code</p> <p>ISO Definition Category purpose, as published in an external category purpose code list.</p> <p>XML Tag Cd</p> <p>Type ExternalCategoryPurpose1Code</p> <p>ISO Length 1 .. 4</p> <p>SEPA Length 1 .. 4</p> <p>SEPA Code Restrictions</p> <table> <tr> <td>FCIN</td> <td>FeeCollectionAndInterest <i>Transaction is related to the payment of a fee and interest.</i></td> </tr> <tr> <td>FCOL</td> <td>FeeCollection <i>A service that is settling card transaction related fees between two parties.</i></td> </tr> <tr> <td>INTE</td> <td>Interest <i>Transaction is the payment of interest.</i></td> </tr> </table>		FCIN	FeeCollectionAndInterest <i>Transaction is related to the payment of a fee and interest.</i>	FCOL	FeeCollection <i>A service that is settling card transaction related fees between two parties.</i>	INTE	Interest <i>Transaction is the payment of interest.</i>
FCIN	FeeCollectionAndInterest <i>Transaction is related to the payment of a fee and interest.</i>									
FCOL	FeeCollection <i>A service that is settling card transaction related fees between two parties.</i>									
INTE	Interest <i>Transaction is the payment of interest.</i>									
2.18	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Type Information +++Category Purpose ++++Proprietary	<p>ISO Name Proprietary</p> <p>ISO Definition Category purpose, in a proprietary form.</p> <p>XML Tag Prtry</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>							
2.19	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Interbank Settlement Amount	<p>SEPA Rulebook AT-Q007 Fee for handling the SCT inquiry / AT-Q006 The interest compensation recovered by the Beneficiary PSP from the Originator PSP.</p> <p>SEPA Usage Rule(s) Only 'EUR' is allowed. Amount must be 0.01 or more and 99999999.99 or less. The fractional part has a maximum of two digits.</p> <p>SEPA Format Rule(s)</p> <p>ISO Name Interbank Settlement Amount</p> <p>ISO Definition Amount of money moved between the instructing agent and the instructed agent.</p> <p>XML Tag IntrBkSttlmAmt</p> <p>Type ActiveCurrencyAndAmount</p> <p>SEPA FractDigits 2</p> <p>TotalDigits 18</p> <p>SEPA Inclusive 0.01 .. 99999999.99</p>							
2.20	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Interbank Settlement Date	<p>ISO Name Interbank Settlement Date</p> <p>ISO Definition Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.</p> <p>XML Tag IntrBkSttlmDt</p> <p>Type ISODate</p>							
2.21	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Settlement Priority	<p>ISO Name Settlement Priority</p> <p>ISO Definition Indicator of the urgency or order of importance that the instructing party would like the instructed party to apply to the processing of the settlement instruction.</p> <p>XML Tag SttlmPrty</p> <p>Type Priority3Code</p>							
2.22	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Settlement Time Indication	<p>ISO Name Settlement Time Indication</p> <p>ISO Definition Provides information on the occurred settlement time(s) of the payment transaction.</p> <p>XML Tag SttlmTmIndctn</p> <p>Type SettlementDateTimeIndication1</p>							

#	SEPA Mult	Message Element	Inter-PSP Fee and/or Compensation Payment SEPA Core Requirements	
2.23	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Settlement Time Request	ISO Name ISO Definition XML Tag Type	Settlement Time Request Provides information on the requested settlement time(s) of the payment instruction. StlmtmReq SettlementTimeRequest2
2.24	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Acceptance Date Time	ISO Name ISO Definition XML Tag Type	Acceptance Date Time Point in time when the payment order from the initiating party meets the processing conditions of the account servicing agent. This means that the account servicing agent has received the payment order and has applied checks such as authorisation, availability of funds. AcptncDtTm ISODateTime
2.25	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Pooling Adjustment Date	ISO Name ISO Definition XML Tag Type	Pooling Adjustment Date Date used for the correction of the value date of a cash pool movement that has been posted with a different value date. PoolgAdjstmntDt ISODate
2.26	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Instructed Amount	ISO Name ISO Definition XML Tag Type <i>SEPA FractDigits</i> TotalDigits <i>SEPA Inclusive</i>	Instructed Amount Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party. Usage: This amount has to be transported unchanged through the transaction chain. InstdAmt ActiveOrHistoricCurrencyAndAmount 5 18 0 ..
2.27	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Exchange Rate	ISO Name ISO Definition XML Tag Type <i>SEPA FractDigits</i> TotalDigits	Exchange Rate Factor used to convert an amount from one currency into another. This reflects the price at which one currency was bought with another currency. XchgRate BaseOneRate 10 11
2.28	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Charge Bearer	<i>SEPA Usage Rule(s)</i> Only "SLEV" is allowed. ISO Name ISO Definition XML Tag Type <i>SEPA Code Restrictions</i> SLEV FollowingServiceLevel Charges are to be applied following the rules agreed in the service level and/or scheme.	Charge Bearer Specifies which party/parties will bear the charges associated with the processing of the payment transaction. ChrgBr ChargeBearerType1Code
2.29	0..n	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Charges Information	ISO Name ISO Definition XML Tag Type	Charges Information Provides information on the charges to be paid by the charge bearer(s) related to the payment transaction. ChrgsInf Charges7
2.30	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Previous Instructing Agent 1	ISO Name ISO Definition XML Tag Type	Previous Instructing Agent 1 Agent immediately prior to the instructing agent. PrvsInstgAgt1 BranchAndFinancialInstitutionIdentification6

#	SEPA Mult	Message Element	Inter-PSP Fee and/or Compensation Payment SEPA Core Requirements	
2.31	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Previous Instructing Agent 1Account	ISO Name ISO Definition XML Tag Type	Previous Instructing Agent 1Account Unambiguous identification of the account of the previous instructing agent at its servicing agent in the payment chain. PrvsInstgAgt1Acct CashAccount38
2.32	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Previous Instructing Agent 2	ISO Name ISO Definition XML Tag Type	Previous Instructing Agent 2 Agent immediately prior to the instructing agent. PrvsInstgAgt2 BranchAndFinancialInstitutionIdentification6
2.33	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Previous Instructing Agent 2Account	ISO Name ISO Definition XML Tag Type	Previous Instructing Agent 2Account Unambiguous identification of the account of the previous instructing agent at its servicing agent in the payment chain. PrvsInstgAgt2Acct CashAccount38
2.34	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Previous Instructing Agent 3	ISO Name ISO Definition XML Tag Type	Previous Instructing Agent 3 Agent immediately prior to the instructing agent. PrvsInstgAgt3 BranchAndFinancialInstitutionIdentification6
2.35	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Previous Instructing Agent 3Account	ISO Name ISO Definition XML Tag Type	Previous Instructing Agent 3Account Unambiguous identification of the account of the previous instructing agent at its servicing agent in the payment chain. PrvsInstgAgt3Acct CashAccount38
2.36	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Instructing Agent	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Only 'BICFI' is allowed. Instructing Agent Agent that instructs the next party in the chain to carry out the (set of) instruction(s). InstgAgt BranchAndFinancialInstitutionIdentification6
2.37	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Instructed Agent	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Only 'BICFI' is allowed. Instructed Agent Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s). InstdAgt BranchAndFinancialInstitutionIdentification6
2.38	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Intermediary Agent 1	ISO Name ISO Definition XML Tag Type	Intermediary Agent 1 Agent between the debtor's agent and the creditor's agent. Usage: If more than one intermediary agent is present, then IntermediaryAgent1 identifies the agent between the DebtorAgent and the IntermediaryAgent2. IntrmyAgt1 BranchAndFinancialInstitutionIdentification6
2.39	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Intermediary Agent 1Account	ISO Name ISO Definition XML Tag Type	Intermediary Agent 1Account Unambiguous identification of the account of the intermediary agent 1 at its servicing agent in the payment chain. IntrmyAgt1Acct CashAccount38

#	SEPA Mult	Message Element	Inter-PSP Fee and/or Compensation Payment SEPA Core Requirements	
2.40	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Intermediary Agent 2	ISO Name ISO Definition XML Tag Type	Intermediary Agent 2 Agent between the debtor's agent and the creditor's agent. Usage: If more than two intermediary agents are present, then IntermediaryAgent2 identifies the agent between the IntermediaryAgent1 and the IntermediaryAgent3. IntrmyAgt2 BranchAndFinancialInstitutionIdentification6
2.41	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Intermediary Agent 2Account	ISO Name ISO Definition XML Tag Type	Intermediary Agent 2Account Unambiguous identification of the account of the intermediary agent 2 at its servicing agent in the payment chain. IntrmyAgt2Acct CashAccount38
2.42	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Intermediary Agent 3	ISO Name ISO Definition XML Tag Type	Intermediary Agent 3 Agent between the debtor's agent and the creditor's agent. Usage: If IntermediaryAgent3 is present, then it identifies the agent between the IntermediaryAgent 2 and the CreditorAgent. IntrmyAgt3 BranchAndFinancialInstitutionIdentification6
2.43	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Intermediary Agent 3Account	ISO Name ISO Definition XML Tag Type	Intermediary Agent 3Account Unambiguous identification of the account of the intermediary agent 3 at its servicing agent in the payment chain. IntrmyAgt3Acct CashAccount38
2.44	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Debtor	ISO Name ISO Definition XML Tag Type	Ultimate Debtor Ultimate party that owes an amount of money to the (ultimate) creditor. UltmtDbtr PartyIdentification135
2.45	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Initiating Party	ISO Name ISO Definition XML Tag Type	Initiating Party Party that initiates the payment. Usage: This can be either the debtor or a party that initiates the credit transfer on behalf of the debtor. InitgPty PartyIdentification135
2.46	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	AT-D002 BIC code of the Originator PSP. Only BIC code of the Originator PSP under 'Name' and 'Identification/Organisation Identification/AnyBIC' is allowed. Debtor Party that owes an amount of money to the (ultimate) creditor. Dbtr PartyIdentification135
2.47	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Name	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Mandatory. Only to be populated with AT-D002 BIC code of the Originator PSP. Name Name by which a party is known and which is usually used to identify that party. Nm Max140Text 1 .. 140 1 .. 70

#	SEPA Mult	Message Element	Inter-PSP Fee and/or Compensation Payment SEPA Core Requirements	
2.48	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address	ISO Name ISO Definition XML Tag Type	Postal Address Information that locates and identifies a specific address, as defined by postal services. PstlAdr PostalAddress24
2.49	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Identification	SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type	Originator's Identification Code. Identification Unique and unambiguous identification of a party. Id Party38Choice
	1..1		XML Tag	xs:choice
2.50	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Identification ++++Organisation Identification	SEPA Usage Rule(s) Only 'AnyBIC' is allowed. ISO Name ISO Definition XML Tag Type	Organisation Identification Unique and unambiguous way to identify an organisation. OrgId OrganisationIdentification29
2.51	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Identification ++++Private Identification	ISO Name ISO Definition XML Tag Type	Private Identification Unique and unambiguous identification of a person, for example a passport. PrvtId PersonIdentification13
2.52	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Country Of Residence	ISO Name ISO Definition XML Tag Type Pattern	Country Of Residence Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed. CtryOfRes CountryCode [A-Z]{2,2}
2.53	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Contact Details	ISO Name ISO Definition XML Tag Type	Contact Details Set of elements used to indicate how to contact the party. CtctDtls Contact4
2.54	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor Account	SEPA Rulebook SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type	AT-Q012 The IBAN of the account to be debited at the Originator PSP. Only IBAN is allowed. Debtor Account Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction. DbtrAcct CashAccount38
2.55	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor Agent	SEPA Rulebook SEPA Usage Rule(s) Only 'BICFI' is allowed. ISO Name ISO Definition XML Tag Type	AT-D002 The BIC code of the Originator PSP. Only 'BICFI' is allowed. Debtor Agent Financial institution servicing an account for the debtor. DbtrAgt BranchAndFinancialInstitutionIdentification6
2.56	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor Agent Account	ISO Name ISO Definition XML Tag Type	Debtor Agent Account Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain. DbtrAgtAcct CashAccount38

#	SEPA Mult	Message Element	Inter-PSP Fee and/or Compensation Payment SEPA Core Requirements	
2.57	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor Agent	SEPA Rulebook AT-C002 The BIC code of the Beneficiary PSP. SEPA Usage Rule(s) Only 'BICFI' is allowed. ISO Name Creditor Agent ISO Definition Financial institution servicing an account for the creditor. XML Tag Type CdtrAgt BranchAndFinancialInstitutionIdentification6	
2.58	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor Agent Account	ISO Name ISO Definition Creditor Agent Account Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction. XML Tag Type CdtrAgtAcct CashAccount38	
2.59	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor	SEPA Rulebook AT-C002 BIC code of the Beneficiary PSP. SEPA Usage Rule(s) Only BIC code of the Beneficiary PSP under 'Name' and 'Identification/Organisation Identification/AnyBIC' is allowed. ISO Name Creditor ISO Definition Party to which an amount of money is due. XML Tag Type Cdtr PartyIdentification135	
2.60	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Name	SEPA Usage Rule(s) Mandatory. Only to be populated with AT-C002 BIC code of the Beneficiary PSP. ISO Name ISO Definition Name Name by which a party is known and which is usually used to identify that party. XML Tag Type Nm Max140Text ISO Length 1 .. 140 SEPA Length 1 .. 70	
2.61	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address	ISO Name ISO Definition Postal Address Information that locates and identifies a specific address, as defined by postal services. XML Tag Type PstlAdr PostalAddress24	
2.62	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Identification	SEPA Usage Rule(s) Mandatory. Beneficiary Identification Code. ISO Name ISO Definition Identification Unique and unambiguous identification of a party. XML Tag Type Id Party38Choice	
	1..1		XML Tag xs:choice	
2.63	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Identification ++++Organisation Identification	SEPA Usage Rule(s) Only 'AnyBIC' is allowed. ISO Name ISO Definition Organisation Identification Unique and unambiguous way to identify an organisation. XML Tag Type OrgId OrganisationIdentification29	
2.64	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Identification ++++Private Identification	ISO Name ISO Definition Private Identification Unique and unambiguous identification of a person, for example a passport. XML Tag Type PrvtId PersonIdentification13	

#	SEPA Mult	Message Element	Inter-PSP Fee and/or Compensation Payment SEPA Core Requirements	
2.65	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Country Of Residence	ISO Name ISO Definition XML Tag Type Pattern	Country Of Residence Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed. CtryOfRes CountryCode [A-Z]{2,2}
2.66	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Contact Details	ISO Name ISO Definition XML Tag Type	Contact Details Set of elements used to indicate how to contact the party. CtctDtls Contact4
2.67	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor Account	SEPA Rulebook SEPA Usage Rule(s)	<i>AT-Q008 The IBAN of the account to be credited at the Beneficiary PSP.</i> <i>Only IBAN is allowed</i> <i>This is the IBAN provided under 'Resolution Related Information/Compensation' or 'Resolution Related Information/Charges' in the positive response to a Claim for Value Date Correction (camt.087) or the IBAN provided under 'Resolution Related Information/Charges' in the positive response to a Claim Non Receipt (camt.027).</i>
			ISO Name ISO Definition XML Tag Type	Creditor Account Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction. CdtrAcct CashAccount38
2.68	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Creditor	ISO Name ISO Definition XML Tag Type	Ultimate Creditor Ultimate party to which an amount of money is due. UltmtCdr PartyIdentification135
2.69	0..n	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Instruction For Creditor Agent	ISO Name ISO Definition XML Tag Type	Instruction For Creditor Agent Further information related to the processing of the payment instruction, provided by the initiating party, and intended for the creditor agent. InstrForCdtrAgt InstructionForCreditorAgent1
2.70	0..n	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Instruction For Next Agent	ISO Name ISO Definition XML Tag Type	Instruction For Next Agent Further information related to the processing of the payment instruction that may need to be acted upon by the next agent. Usage: The next agent may not be the creditor agent. The instruction can relate to a level of service, can be an instruction that has to be executed by the agent, or can be information required by the next agent. InstrForNxtAgt InstructionForNextAgent1

#	SEPA Mult	Message Element	Inter-PSP Fee and/or Compensation Payment SEPA Core Requirements	
2.71	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Purpose	ISO Name ISO Definition XML Tag Type	Purpose Underlying reason for the payment transaction. Usage: Purpose is used by the end-customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain. Purp Purpose2Choice
2.72	0..10	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Regulatory Reporting	ISO Name ISO Definition XML Tag Type	Regulatory Reporting Information needed due to regulatory and statutory requirements. RgltryRptg RegulatoryReporting3
2.73	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Tax	ISO Name ISO Definition XML Tag Type	Tax Provides details on the tax. Tax TaxInformation8
2.74	0..10	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Related Remittance Information	ISO Name ISO Definition XML Tag Type	Related Remittance Information Provides information related to the handling of the remittance information by any of the agents in the transaction processing chain. RltdRmtInf RemittanceLocation7
2.75	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information	SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type	Remittance Information Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system. RmtInf RemittanceInformation16
2.76	0..n	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Unstructured	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Unstructured Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in an unstructured form. Ustrd Max140Text 1 .. 140 1 .. 140
2.77	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured	SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type	Only one occurrence of 'Structured' is allowed. Structured Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in a structured form. Strd StructuredRemittanceInformation16
2.78	0..n	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Referred Document Information	ISO Name ISO Definition XML Tag Type	Referred Document Information Provides the identification and the content of the referred document. RfrdDocInf ReferredDocumentInformation7

#	SEPA Mult	Message Element	Inter-PSP Fee and/or Compensation Payment SEPA Core Requirements		
2.79	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Referred Document Amount	ISO Name ISO Definition XML Tag Type	Referred Document Amount Provides details on the amounts of the referred document. RfrdDocAmt RemittanceAmount2	
2.80	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Creditor Reference Information	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Mandatory. Creditor Reference Information Reference information provided by the creditor to allow the identification of the underlying documents. CdtrRefInf CreditorReferenceInformation2	
2.81	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Creditor Reference Information +++++Type	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Mandatory. Type Specifies the type of creditor reference. Tp CreditorReferenceType2	
2.82	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Creditor Reference Information +++++Type ++++++Code Or Proprietary	ISO Name ISO Definition XML Tag Type	Code Or Proprietary Coded or proprietary format creditor reference type. CdOrPrtry CreditorReferenceType1Choice	
	1..1		XML Tag	xs:choice	
2.83	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Creditor Reference Information +++++Type ++++++Code Or Proprietary ++++++Code	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Only "SCOR" is allowed. Code Type of creditor reference, in a coded form. Cd DocumentType3Code	
			SEPA Code Restrictions	SCOR <i>StructuredCommunicationReference Document is a structured communication reference provided by the creditor to identify the referred transaction.</i>	
2.84	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Creditor Reference Information +++++Type ++++++Code Or Proprietary ++++++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Proprietary Creditor reference type, in a proprietary form. Prtry Max35Text 1 .. 35 1 .. 35	
2.85	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Creditor Reference Information +++++Type ++++++Issuer	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Mandatory if 'Reference' is populated with an identifier issued or governed by a known institution. E.g. "ISO" should be mentioned here if 'Reference' is populated with a RF Creditor Reference (ISO 11649). Issuer Entity that assigns the credit reference type. Issr Max35Text 1 .. 35 1 .. 35	

#	SEPA Mult	Message Element	Inter-PSP Fee and/or Compensation Payment SEPA Core Requirements	
2.86	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Creditor Reference Information +++++Reference	<p>SEPA Rulebook <i>AT-Q009 Reference of the Beneficiary PSP for inter-PSP fee and/or compensation payment.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i> <i>RF Creditor Reference must be used (ISO 11649) in case "ISO" is mentioned under 'Issuer'.</i></p> <p>ISO Name ISO Definition Unique reference, as assigned by the creditor, to unambiguously refer to the payment transaction.</p> <p>Usage: If available, the initiating party should provide this reference in the structured remittance information, to enable reconciliation by the creditor upon receipt of the amount of money.</p> <p>If the business context requires the use of a creditor reference or a payment remit identification, and only one identifier can be passed through the end-to-end chain, the creditor's reference or payment remittance identification should be quoted in the end-to-end transaction identification.</p> <p>Ref XML Tag Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35</p>	
2.87	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Invoicer	<p>ISO Name ISO Definition Invoiceer Identification of the organisation issuing the invoice, when it is different from the creditor or ultimate creditor.</p> <p>XML Tag Type Invcr PartyIdentification135</p>	
2.88	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Invoicee	<p>ISO Name ISO Definition Invoicee Identification of the party to whom an invoice is issued, when it is different from the debtor or ultimate debtor.</p> <p>XML Tag Type Invcee PartyIdentification135</p>	
2.89	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Tax Remittance	<p>ISO Name ISO Definition Tax Remittance Provides remittance information about a payment made for tax-related purposes.</p> <p>XML Tag Type TaxRmt TaxInformation7</p>	
2.90	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Garnishment Remittance	<p>ISO Name ISO Definition Garnishment Remittance Provides remittance information about a payment for garnishment-related purposes.</p> <p>XML Tag Type GrnshmtRmt Garnishment3</p>	
2.91	0..3	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Additional Remittance Information	<p>ISO Name ISO Definition Additional Remittance Information Additional information, in free text form, to complement the structured remittance information.</p> <p>XML Tag Type AddtlRmtInf Max140Text ISO Length 1 .. 140 SEPA Length 1 .. 140</p>	
2.92	0..n	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Supplementary Data	<p>ISO Name ISO Definition Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block.</p> <p>XML Tag Type SplmtryData SupplementaryData1</p>	

#	SEPA Mult	Message Element	Inter-PSP Fee and/or Compensation Payment SEPA Core Requirements	
3.0	0..n	FITo FICustomer Credit Transfer V08 +Supplementary Data	ISO Name ISO Definition XML Tag Type	Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block. SplmtryData SupplementaryData1



2.20 Request for Status Update on a SCT Inquiry

2.20.1 Use of FI To FI Payment Status Request (pacs.028.001.03)

A pacs.028.001.03 message can be sent to the Beneficiary PSP in case the Originator PSP did not receive a response to an SCT Inquiry (i.e. Claim Non-Receipt or Claim for Value Date Correction). In this context, the following applies:

- Index 3.6 'Original Instruction Identification' must be populated with the case ID (AT-Q002) of the related camt.027/camt.087.

In an SCT context, the message is used for a single or group status request.

Note: Attribute AT-Q001 'SCT inquiry reason code' is implied by the 'Message Name' set to 'pacs.028.001.03' and the 'Original Message Name Identification' must begin with 'camt.027' or 'camt.087' (the addition of a variant number and version number is optional).

Note: Message elements under 'Original Transaction Reference' are based on DS-02 attributes.

#	SEPA Mult	Message Element	Request for Status Update on a SCT Inquiry SEPA Core Requirements	
		Document	XML Tag Type	Document Document
	1..1	FITo FIPayment Status Request V03	ISO Name ISO Definition	FITo FIPayment Status Request V03 The FinancialInstitutionToFinancialInstitutionPaymentStatusRequest message is sent by the debtor agent to the creditor agent, directly or through other agents and/or a payment clearing and settlement system. It is used to request a FIToFIPaymentStatusReport message containing information on the status of a previously sent instruction. FIToFIPmtStsReq FIToFIPaymentStatusRequestV03
1.0	1..1	FITo FIPayment Status Request V03 +Group Header	ISO Name ISO Definition XML Tag Type	Group Header Set of characteristics shared by all individual transactions included in the status request message. GrpHdr GroupHeader91
1.1	1..1	FITo FIPayment Status Request V03 +Group Header ++Message Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Message Identification Point to point reference, as assigned by the instructing party, and sent to the next party in the chain to unambiguously identify the message. Usage: The instructing party has to make sure that MessageIdentification is unique per instructed party for a pre-agreed period. MsgId Max35Text 1 .. 35 1 .. 35
1.2	1..1	FITo FIPayment Status Request V03 +Group Header ++Creation Date Time	ISO Name ISO Definition XML Tag Type	Creation Date Time Date and time at which the message was created. CreDtTm ISODateTime
1.3	0..1	FITo FIPayment Status Request V03 +Group Header ++Instructing Agent	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Only BICFI is allowed. Instructing Agent Agent that instructs the next party in the chain to carry out the (set of) instruction(s). Usage: The instructing agent is the party sending the status message and not the party that sent the original instruction that is being reported on. InstgAgt BranchAndFinancialInstitutionIdentification6
1.4	0..1	FITo FIPayment Status Request V03 +Group Header ++Instructed Agent	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Only BICFI is allowed. Instructed Agent Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s). Usage: The instructed agent is the party receiving the status message and not the party that received the original instruction that is being reported on. InstdAgt BranchAndFinancialInstitutionIdentification6
2.0	0..n	FITo FIPayment Status Request V03 +Original Group Information	ISO Name ISO Definition XML Tag Type	Original Group Information Original group information concerning the group of transactions, to which the status request message refers to. OrgnlGrpInf OriginalGroupInformation27

#	SEPA Mult	Message Element	Request for Status Update on a SCT Inquiry SEPA Core Requirements
3.0	1..n	FITo FIPayment Status Request V03 +Transaction Information	<p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name Transaction Information</p> <p>ISO Definition Information concerning the original transaction, to which the status request message refers.</p> <p>XML Tag TxInf</p> <p>Type PaymentTransaction113</p>
3.1	1..1	FITo FIPayment Status Request V03 +Transaction Information ++Status Request Identification	<p>SEPA Usage Rule(s) <i>Mandatory.</i> <i>This ID must be forwarded to the Beneficiary PSP (and therefore it is not a point-to-point reference).</i></p> <p>ISO Name Status Request Identification</p> <p>ISO Definition Unique identification, as assigned by an instructing party for an instructed party, to unambiguously identify the status request.</p> <p>Usage: The instructing party is the party sending the request message and not the party that sent the original instruction that is being reported on.</p> <p>XML Tag StsReqId</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>
3.2	1..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Group Information	<p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name Original Group Information</p> <p>ISO Definition Point to point reference, as assigned by the original instructing party, to unambiguously identify the original message.</p> <p>XML Tag OrgnlGrpInf</p> <p>Type OriginalGroupInformation29</p>
3.3	1..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Group Information +++Original Message Identification	<p>ISO Name</p> <p>ISO Definition Point to point reference assigned by the original instructing party to unambiguously identify the original message.</p> <p>XML Tag OrgnlMsgId</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>
3.4	1..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Group Information +++Original Message Name Identification	<p>SEPA Usage Rule(s) <i>Must begin with 'camt.027' or 'camt.087'. The addition of a variant number and version number is optional.</i></p> <p>ISO Name Original Message Name Identification</p> <p>ISO Definition Specifies the original message name identifier to which the message refers, for example, pacs. 003.001.01 or MT103.</p> <p>XML Tag OrgnlMsgNmId</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>
3.5	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Group Information +++Original Creation Date Time	<p>ISO Name Original Creation Date Time</p> <p>ISO Definition Original date and time at which the message was created.</p> <p>XML Tag OrgnlCreDtTm</p> <p>Type ISODateTime</p>

#	SEPA Mult	Message Element	Request for Status Update on a SCT Inquiry SEPA Core Requirements	
3.6	1..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Instruction Identification	<p>SEPA Usage Rule(s) <i>Mandatory.</i> <i>Must be populated with the case ID (AT-Q002) of the related camt.027/camt.087 Case.</i></p> <p>ISO Name ISO Definition Original Instruction Identification Unique identification, as assigned by the original instructing party for the original instructed party, to unambiguously identify the original instruction.</p> <p>XML Tag Type ISO Length SEPA Length OrgnlInstrId Max35Text 1 .. 35 1 .. 35</p>	
3.7	1..1	FITo FIPayment Status Request V03 +Transaction Information ++Original End To End Identification	<p>SEPA Rulebook <i>AT-T014 The Originator's reference of the SEPA Credit Transfer Transaction.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name ISO Definition Original End To End Identification Unique identification, as assigned by the original initiating party, to unambiguously identify the original transaction.</p> <p>XML Tag Type ISO Length SEPA Length OrgnlEndToEndId Max35Text 1 .. 35 1 .. 35</p>	
3.8	1..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Identification	<p>SEPA Rulebook <i>AT-T054 The Originator PSP's reference of the SEPA Credit Transfer Transaction.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name ISO Definition Original Transaction Identification Unique identification, as assigned by the original first instructing agent, to unambiguously identify the transaction.</p> <p>XML Tag Type ISO Length SEPA Length OrgnlTxId Max35Text 1 .. 35 1 .. 35</p>	
3.9	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original UETR	<p>ISO Name ISO Definition Original UETR Universally unique identifier to provide the original end-to-end reference of a payment transaction.</p> <p>XML Tag Type Pattern OrgnlUETR UUIDv4Identifier [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}</p>	
3.10	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Acceptance Date Time	<p>ISO Name ISO Definition Acceptance Date Time Point in time when the payment order from the initiating party meets the processing conditions of the account servicing agent. This means that the account servicing agent has received the payment order and has applied checks such as authorisation, availability of funds.</p> <p>XML Tag Type AcptnDtTm ISODateTime</p>	
3.11	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Clearing System Reference	<p>ISO Name ISO Definition Clearing System Reference Unique reference, as assigned by a clearing system, to unambiguously identify the instruction.</p> <p>XML Tag Type ISO Length SEPA Length ClrSysRef Max35Text 1 .. 35 1 .. 35</p>	

#	SEPA Mult	Message Element	Request for Status Update on a SCT Inquiry SEPA Core Requirements	
3.12	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Instructing Agent	ISO Name ISO Definition XML Tag Type	Instructing Agent Agent that instructs the next party in the chain to carry out the (set of) instruction(s). InstgAgt BranchAndFinancialInstitutionIdentification6
3.13	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Instructed Agent	ISO Name ISO Definition XML Tag Type	Instructed Agent Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s). InstdAgt BranchAndFinancialInstitutionIdentification6
3.14	1..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference	SEPA Usage Rule(s) Mandatory. ISO Name ISO Definition XML Tag Type	The message elements under 'Original Transaction Reference' must be populated with the same value as the message elements of the original instruction. Original Transaction Reference Key elements used to identify the original transaction that is being referred to. OrgnlTxRef OriginalTransactionReference28
3.15	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Interbank Settlement Amount	SEPA Rulebook ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits SEPA Inclusive	AT-T002 Amount of the SEPA Credit Transfer in Euro. Interbank Settlement Amount Amount of money moved between the instructing agent and the instructed agent. IntrBkSttlmAmt ActiveOrHistoricCurrencyAndAmount 2 18 0.01 .. 999999999.9
3.16	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Amount	ISO Name ISO Definition XML Tag Type	Amount Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party. Amt AmountType4Choice
3.17	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Interbank Settlement Date	SEPA Rulebook ISO Name ISO Definition XML Tag Type	AT-T051 The Settlement Date of the credit transfer. Interbank Settlement Date Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. IntrBkSttlmDt ISODate
3.18	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Requested Collection Date	ISO Name ISO Definition XML Tag Type	Requested Collection Date Date and time at which the creditor requests that the amount of money is to be collected from the debtor. ReqdColltnDt ISODate
3.19	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Requested Execution Date	ISO Name ISO Definition XML Tag Type	Requested Execution Date Date at which the initiating party requests the clearing agent to process the payment. Usage: This is the date on which the debtor's account is to be debited. If payment by cheque, the date when the cheque must be generated by the bank. ReqdExctnDt DateAndDateTime2Choice

#	SEPA Mult	Message Element	Request for Status Update on a SCT Inquiry SEPA Core Requirements	
3.20	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Creditor Scheme Identification	ISO Name ISO Definition XML Tag Type	Creditor Scheme Identification Credit party that signs the mandate. CdtrSchmeId PartyIdentification135
3.21	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Settlement Information	ISO Name ISO Definition XML Tag Type	Settlement Information Specifies the details on how the settlement of the original transaction(s) between the instructing agent and the instructed agent was completed. SttlmInf SettlementInstruction7
3.22	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Payment Type Information	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-T008 The category purpose of the credit transfer.</i> <i>AT-T001 The identification code of the Scheme. If the original transaction was sent according to Annex V (Use of Extended Remittance Information) of the SCT Rulebook (refer to section 'Inter-PSP payment with use of the Extended Remittance Information option' below), then 'Local Instrument/Code' must be populated with "PERI" (Payment with Extended Remittance Information).</i> Payment Type Information Set of elements used to further specify the type of transaction. PmtTpInf PaymentTypeInformation27
3.23	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Payment Method	ISO Name ISO Definition XML Tag Type	Payment Method Specifies the means of payment that will be used to move the amount of money. PmtMtd PaymentMethod4Code
3.24	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Mandate Related Information	ISO Name ISO Definition XML Tag Type	Mandate Related Information Provides further details of the mandate signed between the creditor and the debtor. MndtRltdInf MandateRelatedInformation14
3.25	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Remittance Information	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-T009 The Remittance Information sent by the Originator to the Beneficiary in the Credit Transfer Instruction or AT-T010 The unstructured Remittance Information sent by the Originator to the Beneficiary in the Credit Transfer Instruction (in case of use of the Extended Remittance Information (ERI) option in the original SEPA Credit Transfer, AT-T011 The structured Remittance Information sent by the Originator to the Beneficiary in the SEPA Credit Transfer Instruction, will NOT be transported here.</i> Remittance Information Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system. RmtInf RemittanceInformation16

#	SEPA Mult	Message Element	Request for Status Update on a SCT Inquiry SEPA Core Requirements	
3.26	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Ultimate Debtor	<p>SEPA Rulebook</p> <p>SEPA Usage Rule(s) Only 'Party' is allowed.</p> <p>ISO Name Ultimate Debtor</p> <p>ISO Definition Ultimate party that owes an amount of money to the (ultimate) creditor.</p> <p>XML Tag Type UltmtDbtr Party40Choice</p>	<p><i>AT-P006 The name of the Originator Reference Party.</i></p> <p><i>AT-P007 The identification code of the Originator Reference Party.</i></p>
3.27	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Debtor	<p>SEPA Rulebook</p> <p>SEPA Usage Rule(s) Only 'Party' is allowed.</p> <p>ISO Name Debtor</p> <p>ISO Definition Party that owes an amount of money to the (ultimate) creditor.</p> <p>XML Tag Type Dbtr Party40Choice</p>	<p><i>AT-P001 The name of the Originator.</i></p> <p><i>AT-P005 The address of the Originator.</i></p> <p><i>AT-P004 The Originator identification code.</i></p>
3.28	1..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Debtor Account	<p>SEPA Rulebook</p> <p>ISO Name Debtor Account</p> <p>ISO Definition Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction.</p> <p>XML Tag Type DbtrAcct CashAccount38</p>	<p><i>AT-D001 The IBAN of the account of the Originator.</i></p> <p><i>AT-P003 The Proxy/Alias of the account of the Originator.</i></p>
3.29	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Debtor Agent	<p>SEPA Rulebook</p> <p>ISO Name Debtor Agent</p> <p>ISO Definition Financial institution servicing an account for the debtor.</p> <p>XML Tag Type DbtrAgt BranchAndFinancialInstitutionIdentification6</p>	<p><i>AT-D002 The BIC code of the Originator PSP.</i></p>
3.30	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Debtor Agent Account	<p>ISO Name Debtor Agent Account</p> <p>ISO Definition Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain.</p> <p>XML Tag Type DbtrAgtAcct CashAccount38</p>	
3.31	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Creditor Agent	<p>SEPA Rulebook</p> <p>ISO Name Creditor Agent</p> <p>ISO Definition Financial institution servicing an account for the creditor.</p> <p>XML Tag Type CdtrAgt BranchAndFinancialInstitutionIdentification6</p>	<p><i>AT-C002 The BIC code of the Beneficiary PSP</i></p>
3.32	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Creditor Agent Account	<p>ISO Name Creditor Agent Account</p> <p>ISO Definition Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction.</p> <p>XML Tag Type CdtrAgtAcct CashAccount38</p>	
3.33	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Creditor	<p>SEPA Rulebook</p> <p>SEPA Usage Rule(s) Only 'Party' is allowed.</p> <p>ISO Name Creditor</p> <p>ISO Definition Party to which an amount of money is due.</p> <p>XML Tag Type Cdtr Party40Choice</p>	<p><i>AT-E001 The name of the Beneficiary.</i></p> <p><i>AT-E004 The address of the Beneficiary.</i></p> <p><i>AT-E005 The Beneficiary identification code.</i></p>

#	SEPA Mult	Message Element	Request for Status Update on a SCT Inquiry SEPA Core Requirements	
3.34	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Creditor Account	<p>SEPA Rulebook</p> <p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p><i>AT-C001 The IBAN of the account of the Beneficiary.</i></p> <p><i>AT-E003 The Proxy/Alias of the account of the Beneficiary.</i></p> <p>Creditor Account</p> <p>Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction.</p> <p>CdtrAcct</p> <p>CashAccount38</p>
3.35	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Ultimate Creditor	<p>SEPA Rulebook</p> <p>SEPA Usage Rule(s)</p> <p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p><i>AT-E007 The name of the Beneficiary Reference Party.</i></p> <p><i>AT-E010 The identification code of the Beneficiary Reference Party.</i></p> <p>Only 'Party' is allowed.</p> <p>Ultimate Creditor</p> <p>Ultimate party to which an amount of money is due.</p> <p>UltmtCdtr</p> <p>Party40Choice</p>
3.36	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Purpose	<p>SEPA Rulebook</p> <p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p><i>AT-T007 The purpose of the SEPA Credit Transfer.</i></p> <p>Purpose</p> <p>Underlying reason for the payment transaction.</p> <p>Usage:</p> <p>Purpose is used by the end customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain.</p> <p>Purp</p> <p>Purpose2Choice</p>
3.37	0..n	FITo FIPayment Status Request V03 +Transaction Information ++Supplementary Data	<p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p>Supplementary Data</p> <p>Additional information that cannot be captured in the structured elements and/or any other specific block.</p> <p>SplmtryData</p> <p>SupplementaryData1</p>
4.0	0..n	FITo FIPayment Status Request V03 +Supplementary Data	<p>ISO Name</p> <p>ISO Definition</p> <p>XML Tag Type</p>	<p>Supplementary Data</p> <p>Additional information that cannot be captured in the structured elements and/or any other specific block.</p> <p>SplmtryData</p> <p>SupplementaryData1</p>



2.21 Inter-PSP payment with use of the Extended Remittance Information option

Annex V 'Extended Remittance Information' (ERI) to the SCT Rulebook (document EPC 152-18) describes this optional feature of the SCT scheme that can only be used between PSPs which have adhered to the option.

The ERI Option supports the transmission of one occurrence of 140 characters of Unstructured Remittance Information (AT-T010) and up to 999 occurrences of Structured Remittance Information (AT-T011) within a single SEPA Credit Transfer Instruction to allow the swift settlement of several payment obligations for the Originator.

2.21.1 Use of FI to FI Customer Credit Transfer (pacs.008.001.08)

For making use of the ERI option, AT-T010 'The unstructured Remittance Information sent by the Originator to the Beneficiary in the Credit Transfer Instruction' and AT-T011 'The structured Remittance Information sent by the Originator to the Beneficiary in the Credit Transfer Instruction' of the Annex V have to be used under index 2.137 'Remittance Information' of the FI to FI Customer Credit Transfer (pacs.008.001.08) and the transactions have to be tagged "PERI" (Payment with Extended Remittance Information) in the 'Local Instrument' data element.

The message caters for bulk and single payment instructions.

Important note: Each of the structured occurrences must be limited to 280 characters between (and excluding) the <Strd> and </Strd> tags but including the opening and closing tags of the sub-elements. It is the duty of the system producing the Extended Remittance Information to manage and check the compliance of each occurrence with the 280 characters rule. If the description of one given document (e.g. an invoice) requires more than 280 characters, a second occurrence (or more) can be used, bearing the same invoice number as the first one.

Note: The Originator PSP must verify upfront if the Beneficiary PSP is an ERI Option Participant or not. The Originator PSP sends SEPA Credit Transfer Transactions containing ERI only to those Beneficiary PSPs that are ERI Option Participants.

Note: In case there is no arrangement for the concrete delivery and presentation of ERI between the Beneficiary PSP and the Beneficiary, the Beneficiary PSP must deliver only the received occurrence of 140 characters of unstructured Remittance Information in full and without alteration to the Beneficiary.

Note: The combination of ERI and non-ERI transactions in the same message is not allowed. It should be left to the Originator PSP to agree with the CSM, that the Originator PSP may send ERI and non-ERI transactions in the same message, even though the CSM would separate the ERI and non-ERI transactions to the Beneficiary PSP via different messages. This combination of ERI and non-ERI transactions is not reflected in the message description below.

#	SEPA Mult	Message Element	Inter-PSP Payment with use of ERI SEPA Core Requirements	
		Document	XML Tag Type	Document Document
	1..1	FITo FICustomer Credit Transfer V08	ISO Name ISO Definition	FITo FICustomer Credit Transfer V08 Scope The FinancialInstitutionToFinancialInstitutionCustomerCreditTransfer message is sent by the debtor agent to the creditor agent, directly or through other agents and/or a payment clearing and settlement system. It is used to move funds from a debtor account to a creditor. FIToFICstmrcdtTrf FIToFICustomerCreditTransferV08
1.0	1..1	FITo FICustomer Credit Transfer V08 +Group Header	ISO Name ISO Definition XML Tag Type	Group Header Set of characteristics shared by all individual transactions included in the message. GrpHdr GroupHeader93
1.1	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Message Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Message Identification Point to point reference, as assigned by the instructing party, and sent to the next party in the chain to unambiguously identify the message. Usage: The instructing party has to make sure that MessageIdentification is unique per instructed party for a pre-agreed period. MsgId Max35Text 1 .. 35 1 .. 35
1.2	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Creation Date Time	ISO Name ISO Definition XML Tag Type	Creation Date Time Date and time at which the message was created. CreDtTm ISODATETIME
1.3	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Batch Booking	ISO Name ISO Definition XML Tag Type	Batch Booking Identifies whether a single entry per individual transaction or a batch entry for the sum of the amounts of all transactions within the group of a message is requested. Usage: Batch booking is used to request and not order a possible batch booking. BtchBookg BatchBookingIndicator
1.4	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Number Of Transactions	ISO Name ISO Definition XML Tag Type Pattern	Number Of Transactions Number of individual transactions contained in the message. NbOfTx Max15NumericText [0-9]{1,15}
1.5	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Control Sum	ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits	Control Sum Total of all individual amounts included in the message, irrespective of currencies. CtrlSum DecimalNumber 17 18

#	SEPA Mult	Message Element	Inter-PSP Payment with use of ERI SEPA Core Requirements							
1.6	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Total Interbank Settlement Amount	<p>SEPA Usage Rule(s) Mandatory Only 'EUR' is allowed. Amount must be 0.01 or more and 9999999999999.99 or less. The fractional part has a maximum of two digits.</p> <p>SEPA Format Rule(s)</p> <p>ISO Name</p> <p>ISO Definition Total Interbank Settlement Amount Total amount of money moved between the instructing agent and the instructed agent.</p> <p>XML Tag Type TtlIntrBkStlmtAmt</p> <p>SEPA FractDigits ActiveCurrencyAndAmount 2</p> <p>TotalDigits 18</p> <p>SEPA Inclusive 0.01 .. 99999999999999.99</p>							
1.7	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Interbank Settlement Date	<p>SEPA Rulebook AT-T051 Settlement Date of the Credit Transfer.</p> <p>SEPA Usage Rule(s) Mandatory.</p> <p>ISO Name Interbank Settlement Date</p> <p>ISO Definition Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.</p> <p>XML Tag Type IntrBkStlmtDt ISODate</p>							
1.8	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Settlement Information	<p>ISO Name</p> <p>ISO Definition Settlement Information Specifies the details on how the settlement of the transaction(s) between the instructing agent and the instructed agent is completed.</p> <p>XML Tag Type StlmtInf SettlementInstruction7</p>							
1.9	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Settlement Information +++Settlement Method	<p>SEPA Usage Rule(s) Only "CLRG", "INGA" and "INDA" are allowed.</p> <p>ISO Name Settlement Method</p> <p>ISO Definition Method used to settle the (batch of) payment instructions.</p> <p>XML Tag Type StlmtMtd SettlementMethod1Code</p> <p>SEPA Code Restrictions</p> <table> <tr> <td>CLRG</td> <td><i>ClearingSystem</i> Settlement is done through a payment clearing system.</td> </tr> <tr> <td>INDA</td> <td><i>InstructedAgent</i> Settlement is done by the agent instructed to execute a payment instruction.</td> </tr> <tr> <td>INGA</td> <td><i>InstructingAgent</i> Settlement is done by the agent instructing and forwarding the payment to the next party in the payment chain.</td> </tr> </table>		CLRG	<i>ClearingSystem</i> Settlement is done through a payment clearing system.	INDA	<i>InstructedAgent</i> Settlement is done by the agent instructed to execute a payment instruction.	INGA	<i>InstructingAgent</i> Settlement is done by the agent instructing and forwarding the payment to the next party in the payment chain.
CLRG	<i>ClearingSystem</i> Settlement is done through a payment clearing system.									
INDA	<i>InstructedAgent</i> Settlement is done by the agent instructed to execute a payment instruction.									
INGA	<i>InstructingAgent</i> Settlement is done by the agent instructing and forwarding the payment to the next party in the payment chain.									
1.10	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Settlement Information +++Settlement Account	<p>SEPA Usage Rule(s) Only 'Identification' is allowed.</p> <p>ISO Name Settlement Account</p> <p>ISO Definition A specific purpose account used to post debit and credit entries as a result of the transaction.</p> <p>XML Tag Type StlmtAcct CashAccount38</p>							
1.11	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Settlement Information +++Clearing System	<p>ISO Name Clearing System</p> <p>ISO Definition Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed.</p> <p>XML Tag Type ClrSys ClearingSystemIdentification3Choice</p>							
	1..1		XML Tag	xs:choice						

#	SEPA Mult	Message Element	Inter-PSP Payment with use of ERI SEPA Core Requirements	
1.12	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Settlement Information +++Clearing System ++++Code	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Code Infrastructure through which the payment instruction is processed, as published in an external clearing system identification code list. Cd ExternalCashClearingSystem1Code 1 .. 3 I .. 3
1.13	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Settlement Information +++Clearing System ++++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Proprietary Clearing system identification in a proprietary form. Prtry Max35Text 1 .. 35 I .. 35
1.14	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Settlement Information +++Instructing Reimbursement Agent	ISO Name ISO Definition XML Tag Type	Instructing Reimbursement Agent Agent through which the instructing agent will reimburse the instructed agent. Usage: If InstructingAgent and InstructedAgent have the same reimbursement agent, then only InstructingReimbursementAgent must be used. InstgRmbrsmntAgt BranchAndFinancialInstitutionIdentification6
1.15	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Settlement Information +++Instructing Reimbursement Agent Account	ISO Name ISO Definition XML Tag Type	Instructing Reimbursement Agent Account Unambiguous identification of the account of the instructing reimbursement agent account at its servicing agent in the payment chain. InstgRmbrsmntAgtAcct CashAccount38
1.16	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Settlement Information +++Instructed Reimbursement Agent	ISO Name ISO Definition XML Tag Type	Instructed Reimbursement Agent Agent at which the instructed agent will be reimbursed. Usage: If InstructedReimbursementAgent contains a branch of the InstructedAgent, then the party in InstructedAgent will claim reimbursement from that branch/will be paid by that branch. Usage: If InstructingAgent and InstructedAgent have the same reimbursement agent, then only InstructingReimbursementAgent must be used. InstdRmbrsmntAgt BranchAndFinancialInstitutionIdentification6
1.17	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Settlement Information +++Instructed Reimbursement Agent Account	ISO Name ISO Definition XML Tag Type	Instructed Reimbursement Agent Account Unambiguous identification of the account of the instructed reimbursement agent account at its servicing agent in the payment chain. InstdRmbrsmntAgtAcct CashAccount38
1.18	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Settlement Information +++Third Reimbursement Agent	ISO Name ISO Definition XML Tag Type	Third Reimbursement Agent Agent at which the instructed agent will be reimbursed. Usage: If ThirdReimbursementAgent contains a branch of the InstructedAgent, then the party in InstructedAgent will claim reimbursement from that branch/will be paid by that branch. ThrdRmbrsmntAgt BranchAndFinancialInstitutionIdentification6

#	SEPA Mult	Message Element	Inter-PSP Payment with use of ERI SEPA Core Requirements		
1.19	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Settlement Information +++Third Reimbursement Agent Account	ISO Name ISO Definition XML Tag Type	Third Reimbursement Agent Account Unambiguous identification of the account of the third reimbursement agent account at its servicing agent in the payment chain. ThrdRmbrsmntAgtAcct CashAccount38	
1.20	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	'Payment Type Information' must be present in either 'Group Header' or 'Credit Transfer Transaction Information'. Payment Type Information Set of elements used to further specify the type of transaction. PmtTpInf PaymentTypeInformation28	
1.21	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information +++Instruction Priority	ISO Name ISO Definition XML Tag Type	Instruction Priority Indicator of the urgency or order of importance that the instructing party would like the instructed party to apply to the processing of the instruction. InstrPrty Priority2Code	
1.22	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information +++Clearing Channel	ISO Name ISO Definition XML Tag Type	Clearing Channel Specifies the clearing channel to be used to process the payment instruction. ClrChnl ClearingChannel2Code	
1.23	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information +++Service Level	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Mandatory Only one occurrence is allowed. Service Level Agreement under which or rules under which the transaction should be processed. SvcLvl ServiceLevel8Choice	
	1..1		XML Tag	xs:choice	
1.24	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information +++Service Level ++++Code	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	AT-T001 The identification code of the Scheme. Only "SEPA" is allowed. Code Specifies a pre-agreed service or level of service between the parties, as published in an external service level code list. Cd ExternalServiceLevel1Code 1 .. 4 1 .. 4	
			SEPA Code Restrictions	SingleEuroPaymentsArea Payment must be executed following the Single Euro Payments Area scheme.	
1.25	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information +++Service Level ++++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Proprietary Specifies a pre-agreed service or level of service between the parties, as a proprietary code. Prtry Max35Text 1 .. 35 1 .. 35	

#	SEPA Mult	Message Element	Inter-PSP Payment with use of ERI SEPA Core Requirements
1.26	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information +++Local Instrument	<p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name Local Instrument</p> <p>ISO Definition User community specific instrument.</p> <p>Usage: This element is used to specify a local instrument, local clearing option and/or further qualify the service or service level.</p> <p>XML Tag Type LclInstrm LocalInstrument2Choice</p>
	1..1		XML Tag xs:choice
1.27	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information +++Local Instrument ++++Code	<p>SEPA Usage Rule(s) <i>Only "PERI" is allowed.</i> <i>The mixing of "PERI" with other 'Local Instrument' values is not allowed in the same message, unless bilaterally agreed between Originator PSP and CSM.</i></p> <p>ISO Name Code</p> <p>ISO Definition Specifies the local instrument, as published in an external local instrument code list.</p> <p>XML Tag Type Cd</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p> <p>SEPA Code Restrictions</p> <p>PERI <i>PaymentWithERI</i> <i>Credit transfer contains Extended Remittance Information (ERI) as defined within the applicable scheme.</i></p>
1.28	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information +++Local Instrument ++++Proprietary	<p>ISO Name Proprietary</p> <p>ISO Definition Specifies the local instrument, as a proprietary code.</p> <p>XML Tag Type Prtry</p> <p>ISO Length Max35Text</p> <p>SEPA Length 1 .. 35</p>
1.29	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information +++Category Purpose	<p>SEPA Rulebook AT-T008 Category purpose of the Credit Transfer.</p> <p>SEPA Usage Rule(s) Depending on the agreement between the Originator and the Originator PSP, 'Category Purpose' may be forwarded to the Beneficiary PSP.</p> <p>ISO Name Category Purpose</p> <p>ISO Definition Specifies the high level purpose of the instruction based on a set of pre-defined categories.</p> <p>Usage: This is used by the initiating party to provide information concerning the processing of the payment. It is likely to trigger special processing by any of the agents involved in the payment chain.</p> <p>XML Tag Type CtgyPurp CategoryPurpose1Choice</p>
	1..1		XML Tag xs:choice
1.30	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information +++Category Purpose ++++Code	<p>ISO Name Code</p> <p>ISO Definition Category purpose, as published in an external category purpose code list.</p> <p>XML Tag Type Cd</p> <p>ISO Length ExternalCategoryPurpose1Code</p> <p>SEPA Length 1 .. 4</p>

#	SEPA Mult	Message Element	Inter-PSP Payment with use of ERI SEPA Core Requirements	
1.31	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information +++Category Purpose ++++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Proprietary Category purpose, in a proprietary form. Prtry Max35Text 1 .. 35 1 .. 35
1.32	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Instructing Agent	SEPA Usage Rule(s) <i>Only 'BICFI' is allowed</i> ISO Name ISO Definition XML Tag Type	Instructing Agent Agent that instructs the next party in the chain to carry out the (set of) instruction(s). InstgAgt BranchAndFinancialInstitutionIdentification6
1.33	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Instructed Agent	SEPA Usage Rule(s) <i>Only 'BICFI' is allowed.</i> ISO Name ISO Definition XML Tag Type	Instructed Agent Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s). InstdAgt BranchAndFinancialInstitutionIdentification6
2.0	1..n	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information	ISO Name ISO Definition XML Tag Type	Credit Transfer Transaction Information Set of elements providing information specific to the individual credit transfer(s). CdtTrfTxInf CreditTransferTransaction39
2.1	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Identification	ISO Name ISO Definition XML Tag Type	Payment Identification Set of elements used to reference a payment instruction. PmtId PaymentIdentification7
2.2	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Identification +++Instruction Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Instruction Identification Unique identification, as assigned by an instructing party for an instructed party, to unambiguously identify the instruction. Usage: The instruction identification is a point to point reference that can be used between the instructing party and the instructed party to refer to the individual instruction. It can be included in several messages related to the instruction. InstrId Max35Text 1 .. 35 1 .. 35

#	SEPA Mult	Message Element	Inter-PSP Payment with use of ERI SEPA Core Requirements	
2.3	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Identification +++End To End Identification	<p>SEPA Rulebook <i>AT-T014 The Originator's reference of the SEPA Credit Transfer Transaction.</i></p> <p>SEPA Usage Rule(s) <i>A customer reference that must be passed on in the end-to-end chain. In the event that no reference was given, "NOTPROVIDED" must be used.</i></p> <p>ISO Name</p> <p>ISO Definition End To End Identification Unique identification, as assigned by the initiating party, to unambiguously identify the transaction. This identification is passed on, unchanged, throughout the entire end-to-end chain.</p> <p>XML Tag</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p> <p>Usage: The end-to-end identification can be used for reconciliation or to link tasks relating to the transaction. It can be included in several messages related to the transaction.</p> <p>Usage: In case there are technical limitations to pass on multiple references, the end-to-end identification must be passed on throughout the entire end-to-end chain.</p> <p>EndToEndId</p>	
2.4	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Identification +++Transaction Identification	<p>SEPA Rulebook <i>AT-T054 The Originator PSP's reference of the SEPA Credit Transfer Transaction.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i> <i>Must contain a reference that is meaningful to the Originator's PSP and is unique over time.</i></p> <p>ISO Name</p> <p>ISO Definition Transaction Identification Unique identification, as assigned by the first instructing agent, to unambiguously identify the transaction that is passed on, unchanged, throughout the entire interbank chain.</p> <p>Usage: The transaction identification can be used for reconciliation, tracking or to link tasks relating to the transaction on the interbank level.</p> <p>Usage: The instructing agent has to make sure that the transaction identification is unique for a pre-agreed period.</p> <p>XML Tag</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>	
2.5	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Identification +++UETR	<p>ISO Name</p> <p>ISO Definition UETR Universally unique identifier to provide an end-to-end reference of a payment transaction.</p> <p>XML Tag</p> <p>Type UUIDv4Identifier</p> <p>Pattern [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}</p>	
2.6	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Identification +++Clearing System Reference	<p>ISO Name</p> <p>ISO Definition Clearing System Reference Unique reference, as assigned by a clearing system, to unambiguously identify the instruction.</p> <p>XML Tag</p> <p>Type ClrSysRef</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>	

#	SEPA Mult	Message Element	Inter-PSP Payment with use of ERI SEPA Core Requirements		
2.7	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Type Information	<p>SEPA Usage Rule(s) 'Payment Type Information' must be present in either 'Group Header' or 'Credit Transfer Transaction Information'.</p> <p>ISO Name Payment Type Information</p> <p>ISO Definition Set of elements used to further specify the type of transaction.</p> <p>XML Tag Type PmtTpInf</p> <p>SEPA Length PaymentTypeInformation28</p>		
2.8	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Type Information +++Instruction Priority	<p>ISO Name Instruction Priority</p> <p>ISO Definition Indicator of the urgency or order of importance that the instructing party would like the instructed party to apply to the processing of the instruction.</p> <p>XML Tag Type InstrPrty</p> <p>SEPA Length Priority2Code</p>		
2.9	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Type Information +++Clearing Channel	<p>ISO Name Clearing Channel</p> <p>ISO Definition Specifies the clearing channel to be used to process the payment instruction.</p> <p>XML Tag Type ClrChnl</p> <p>SEPA Length ClearingChannel2Code</p>		
2.10	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Type Information +++Service Level	<p>SEPA Usage Rule(s) Mandatory. Only one occurrence is allowed.</p> <p>ISO Name Service Level</p> <p>ISO Definition Agreement under which or rules under which the transaction should be processed.</p> <p>XML Tag Type SvcLvl</p> <p>SEPA Length ServiceLevel8Choice</p>		
	1..1		XML Tag xs:choice		
2.11	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Type Information +++Service Level ++++Code	<p>SEPA Rulebook AT-T001 The identification code of the SEPA electronic credit transfer Scheme.</p> <p>SEPA Usage Rule(s) Only "SEPA" is allowed.</p> <p>ISO Name Code</p> <p>ISO Definition Specifies a pre-agreed service or level of service between the parties, as published in an external service level code list.</p> <p>XML Tag Type Cd</p> <p>ISO Length 1 .. 4</p> <p>SEPA Length 1 .. 4</p> <p>SEPA Code Restrictions</p> <p>SEPA SingleEuroPaymentsArea Payment must be executed following the Single Euro Payments Area scheme.</p>		
2.12	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Type Information +++Service Level ++++Proprietary	<p>ISO Name Proprietary</p> <p>ISO Definition Specifies a pre-agreed service or level of service between the parties, as a proprietary code.</p> <p>XML Tag Type Prtry</p> <p>ISO Length Max35Text</p> <p>SEPA Length 1 .. 35</p>		
2.13	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Type Information +++Local Instrument	<p>SEPA Usage Rule(s) Mandatory.</p> <p>ISO Name Local Instrument</p> <p>ISO Definition User community specific instrument.</p> <p>Usage: This element is used to specify a local instrument, local clearing option and/or further qualify the service or service level.</p> <p>XML Tag Type LclInstrm</p> <p>SEPA Length LocallInstrument2Choice</p>		
	1..1		XML Tag xs:choice		

#	SEPA Mult	Message Element	Inter-PSP Payment with use of ERI SEPA Core Requirements	
2.14	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Type Information +++Local Instrument ++++Code	<p>SEPA Usage Rule(s) Only "PERI" is allowed. The mixing of "PERI" with other 'Local Instrument' values is not allowed in the same message, unless bilaterally agreed between Originator PSP and CSM.</p> <p>ISO Name Code ISO Definition Specifies the local instrument, as published in an external local instrument code list.</p> <p>XML Tag Cd Type ExternalLocalInstrument1Code ISO Length 1 .. 35 SEPA Length 1 .. 35</p> <p>SEPA Code Restrictions</p> <p>PERI PaymentWithERI Credit transfer contains Extended Remittance Information (ERI) as defined within the applicable scheme.</p>	
2.15	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Type Information +++Local Instrument ++++Proprietary	<p>ISO Name Proprietary ISO Definition Specifies the local instrument, as a proprietary code.</p> <p>XML Tag Prtry Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35</p>	
2.16	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Type Information +++Category Purpose	<p>SEPA Rulebook AT-T008 Category purpose of the Credit Transfer.</p> <p>SEPA Usage Rule(s) Depending on the agreement between the Originator and the Originator PSP, 'Category Purpose' may be forwarded to the Beneficiary PSP.</p> <p>ISO Name Category Purpose ISO Definition Specifies the high level purpose of the instruction based on a set of pre-defined categories. Usage: This is used by the initiating party to provide information concerning the processing of the payment. It is likely to trigger special processing by any of the agents involved in the payment chain.</p> <p>XML Tag CtgyPurp Type CategoryPurpose1Choice</p>	
	1..1		<p>XML Tag xs:choice</p>	
2.17	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Type Information +++Category Purpose ++++Code	<p>ISO Name Code ISO Definition Category purpose, as published in an external category purpose code list.</p> <p>XML Tag Cd Type ExternalCategoryPurpose1Code ISO Length 1 .. 4 SEPA Length 1 .. 4</p>	
2.18	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Type Information +++Category Purpose ++++Proprietary	<p>ISO Name Proprietary ISO Definition Category purpose, in a proprietary form.</p> <p>XML Tag Prtry Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35</p>	

#	SEPA Mult	Message Element	Inter-PSP Payment with use of ERI SEPA Core Requirements	
2.19	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Interbank Settlement Amount	<p>SEPA Rulebook AT-T002 <i>Amount of the SEPA Credit Transfer in Euro.</i></p> <p>SEPA Usage Rule(s) Only 'EUR' is allowed. <i>Amount must be 0.01 or more and 999999999.99 or less.</i> <i>The fractional part has a maximum of two digits.</i></p> <p>SEPA Format Rule(s)</p> <p>ISO Name</p> <p>ISO Definition Interbank Settlement Amount Amount of money moved between the instructing agent and the instructed agent. IntrBkStlmtAmt</p> <p>XML Tag Type ActiveCurrencyAndAmount</p> <p>SEPA FractDigits 2</p> <p>TotalDigits 18</p> <p>SEPA Inclusive 0.01 .. 999999999.99</p>	
2.20	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Interbank Settlement Date	<p>ISO Name</p> <p>ISO Definition Interbank Settlement Date Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. IntrBkStlmtDt</p> <p>XML Tag Type ISODate</p>	
2.21	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Settlement Priority	<p>ISO Name</p> <p>ISO Definition Settlement Priority Indicator of the urgency or order of importance that the instructing party would like the instructed party to apply to the processing of the settlement instruction. StlmtPrty</p> <p>XML Tag Type Priority3Code</p>	
2.22	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Settlement Time Indication	<p>ISO Name</p> <p>ISO Definition Settlement Time Indication Provides information on the occurred settlement time(s) of the payment transaction. StlmtTmIndctn</p> <p>XML Tag Type SettlementDateTimeIndication1</p>	
2.23	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Settlement Time Request	<p>ISO Name</p> <p>ISO Definition Settlement Time Request Provides information on the requested settlement time(s) of the payment instruction. StlmtTmReq</p> <p>XML Tag Type SettlementTimeRequest2</p>	
2.24	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Acceptance Date Time	<p>ISO Name</p> <p>ISO Definition Acceptance Date Time Point in time when the payment order from the initiating party meets the processing conditions of the account servicing agent. This means that the account servicing agent has received the payment order and has applied checks such as authorisation, availability of funds.</p> <p>XML Tag Type AcptncDtTm</p> <p>ISODateTime</p>	
2.25	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Pooling Adjustment Date	<p>ISO Name</p> <p>ISO Definition Pooling Adjustment Date Date used for the correction of the value date of a cash pool movement that has been posted with a different value date. PoolgAdjstmntDt</p> <p>XML Tag Type ISODate</p>	

#	SEPA Mult	Message Element	Inter-PSP Payment with use of ERI SEPA Core Requirements	
2.26	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Instructed Amount	ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits SEPA Inclusive	Instructed Amount Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party. Usage: This amount has to be transported unchanged through the transaction chain. InstdAmt ActiveOrHistoricCurrencyAndAmount 5 18 0 ..
2.27	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Exchange Rate	ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits	Exchange Rate Factor used to convert an amount from one currency into another. This reflects the price at which one currency was bought with another currency. XchgRate BaseOneRate 10 11
2.28	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Charge Bearer	SEPA Usage Rule(s) Only "SLEV" is allowed. ISO Name ISO Definition XML Tag Type	Charge Bearer Specifies which party/parties will bear the charges associated with the processing of the payment transaction. ChrgBr ChargeBearerType1Code
			SEPA Code Restrictions	
			SLEV	FollowingServiceLevel Charges are to be applied following the rules agreed in the service level and/or scheme.
2.29	0..n	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Charges Information	ISO Name ISO Definition XML Tag Type	Charges Information Provides information on the charges to be paid by the charge bearer(s) related to the payment transaction. ChrgsInf Charges7
2.30	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Previous Instructing Agent 1	ISO Name ISO Definition XML Tag Type	Previous Instructing Agent 1 Agent immediately prior to the instructing agent. PrvsInstgAgt1 BranchAndFinancialInstitutionIdentification6
2.31	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Previous Instructing Agent 1Account	ISO Name ISO Definition XML Tag Type	Previous Instructing Agent 1Account Unambiguous identification of the account of the previous instructing agent at its servicing agent in the payment chain. PrvsInstgAgt1Acct CashAccount38
2.32	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Previous Instructing Agent 2	ISO Name ISO Definition XML Tag Type	Previous Instructing Agent 2 Agent immediately prior to the instructing agent. PrvsInstgAgt2 BranchAndFinancialInstitutionIdentification6
2.33	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Previous Instructing Agent 2Account	ISO Name ISO Definition XML Tag Type	Previous Instructing Agent 2Account Unambiguous identification of the account of the previous instructing agent at its servicing agent in the payment chain. PrvsInstgAgt2Acct CashAccount38
2.34	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Previous Instructing Agent 3	ISO Name ISO Definition XML Tag Type	Previous Instructing Agent 3 Agent immediately prior to the instructing agent. PrvsInstgAgt3 BranchAndFinancialInstitutionIdentification6

#	SEPA Mult	Message Element	Inter-PSP Payment with use of ERI SEPA Core Requirements	
2.35	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Previous Instructing Agent 3Account	ISO Name ISO Definition XML Tag Type	Previous Instructing Agent 3Account Unambiguous identification of the account of the previous instructing agent at its servicing agent in the payment chain. PrvsInstgAgt3Acct CashAccount38
2.36	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Instructing Agent	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Only 'BICFI' is allowed. Instructing Agent Agent that instructs the next party in the chain to carry out the (set of) instruction(s). InstgAgt BranchAndFinancialInstitutionIdentification6
2.37	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Instructed Agent	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Only 'BICFI' is allowed. Instructed Agent Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s). InstdAgt BranchAndFinancialInstitutionIdentification6
2.38	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Intermediary Agent 1	ISO Name ISO Definition XML Tag Type	Intermediary Agent 1 Agent between the debtor's agent and the creditor's agent. Usage: If more than one intermediary agent is present, then IntermediaryAgent1 identifies the agent between the DebtorAgent and the IntermediaryAgent2. IntrmyAgt1 BranchAndFinancialInstitutionIdentification6
2.39	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Intermediary Agent 1Account	ISO Name ISO Definition XML Tag Type	Intermediary Agent 1Account Unambiguous identification of the account of the intermediary agent 1 at its servicing agent in the payment chain. IntrmyAgt1 Acct CashAccount38
2.40	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Intermediary Agent 2	ISO Name ISO Definition XML Tag Type	Intermediary Agent 2 Agent between the debtor's agent and the creditor's agent. Usage: If more than two intermediary agents are present, then IntermediaryAgent2 identifies the agent between the IntermediaryAgent1 and the IntermediaryAgent3. IntrmyAgt2 BranchAndFinancialInstitutionIdentification6
2.41	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Intermediary Agent 2Account	ISO Name ISO Definition XML Tag Type	Intermediary Agent 2Account Unambiguous identification of the account of the intermediary agent 2 at its servicing agent in the payment chain. IntrmyAgt2Acct CashAccount38
2.42	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Intermediary Agent 3	ISO Name ISO Definition XML Tag Type	Intermediary Agent 3 Agent between the debtor's agent and the creditor's agent. Usage: If IntermediaryAgent3 is present, then it identifies the agent between the IntermediaryAgent 2 and the CreditorAgent. IntrmyAgt3 BranchAndFinancialInstitutionIdentification6

#	SEPA Mult	Message Element	Inter-PSP Payment with use of ERI SEPA Core Requirements	
2.43	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Intermediary Agent 3Account	ISO Name ISO Definition XML Tag Type	Intermediary Agent 3Account Unambiguous identification of the account of the intermediary agent 3 at its servicing agent in the payment chain. IntrmyAgt3Acct CashAccount38
2.44	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Debtor	ISO Name ISO Definition XML Tag Type	Ultimate Debtor Ultimate party that owes an amount of money to the (ultimate) creditor. UltmtDbtr PartyIdentification135
2.45	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Debtor +++Name	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	AT-P006 Name of the Originator Reference Party. 'Name' is limited to 70 characters in length. Name Name by which a party is known and which is usually used to identify that party. Nm Max140Text 1 .. 140 1 .. 70
2.46	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Debtor +++Postal Address	ISO Name ISO Definition XML Tag Type	Postal Address Information that locates and identifies a specific address, as defined by postal services. PstlAdr PostalAddress24
2.47	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Debtor +++Identification	SEPA Rulebook ISO Name ISO Definition XML Tag Type	AT-P007 Identification code of the Originator Reference Party. Identification Unique and unambiguous identification of a party. Id Party38Choice
	1..1		XML Tag	xs:choice
2.48	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Debtor +++Identification ++++Organisation Identification	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Either 'AnyBIC', 'LEI' and/or one occurrence of 'Other' is allowed. Organisation Identification Unique and unambiguous way to identify an organisation. OrgId OrganisationIdentification29
2.49	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Debtor +++Identification ++++Private Identification	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Either 'Date and Place of Birth' or one occurrence of 'Other' is allowed. Private Identification Unique and unambiguous identification of a person, for example a passport. PrvtId PersonIdentification13
2.50	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Debtor +++Country Of Residence	ISO Name ISO Definition XML Tag Type Pattern	Country Of Residence Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed. CtryOfRes CountryCode [A-Z]{2,2}
2.51	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Debtor +++Contact Details	ISO Name ISO Definition XML Tag Type	Contact Details Set of elements used to indicate how to contact the party. CtctDtls Contact4

#	SEPA Mult	Message Element	Inter-PSP Payment with use of ERI SEPA Core Requirements		
2.52	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Initiating Party	ISO Name ISO Definition XML Tag Type	Initiating Party Party that initiates the payment. Usage: This can be either the debtor or a party that initiates the credit transfer on behalf of the debtor. InitgPty PartyIdentification135	
2.53	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor	ISO Name ISO Definition XML Tag Type	Debtor Party that owes an amount of money to the (ultimate) creditor. Dbtr PartyIdentification135	
2.54	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Name	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	AT-P001 Name of the Originator. <i>'Name'</i> is limited to 70 characters in length. Name Name by which a party is known and which is usually used to identify that party. Nm Max140Text 1 .. 140 1 .. 70	
2.55	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address	SEPA Rulebook SEPA Usage Rule(s)	AT-P005 Address of the Originator (only mandatory when the Originator PSP or the Beneficiary PSP is located in a non-EEA SEPA country or territory). STRUCTURED ADDRESS: Usage is recommended. 'Town Name' and 'Country' are mandatory. 'Address Line' is not allowed. It is recommended to provide as many structured elements as possible. HYBRID ADDRESS: 'Town Name' and 'Country' are mandatory. At least one occurrence of 'Address line' is mandatory. UNSTRUCTURED ADDRESS (As of 22 November 2026, only the use of structured and hybrid addresses will be allowed - based on available information at the moment of publication): At least one occurrence of 'Address line' is mandatory. 'Postal Address' sub-elements other than 'Address Line' and 'Country' are forbidden. The use of 'Country' is mandatory when either the Debtor Agent or Creditor Agent is located in a non-EEA SEPA country or territory. Postal Address Information that locates and identifies a specific address, as defined by postal services. PstlAdr PostalAddress24	
2.56	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Address Type	ISO Name ISO Definition XML Tag Type	Address Type Identifies the nature of the postal address. AdrTp AddressType3Choice	
2.57	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Department	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Department Identification of a division of a large organisation or building. Dept Max70Text 1 .. 70 1 .. 70	

#	SEPA Mult	Message Element	Inter-PSP Payment with use of ERI SEPA Core Requirements		
2.58	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Sub Department	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Sub Department Identification of a sub-division of a large organisation or building. SubDept Max70Text 1 .. 70 1 .. 70	
2.59	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Street Name	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Street Name Name of a street or thoroughfare. StrtNm Max70Text 1 .. 70 1 .. 70	
2.60	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Building Number	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Building Number Number that identifies the position of a building on a street. BldgNb Max16Text 1 .. 16 1 .. 16	
2.61	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Building Name	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Building Name Name of the building or house. BldgNm Max35Text 1 .. 35 1 .. 35	
2.62	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Floor	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Floor Floor or storey within a building. Flr Max70Text 1 .. 70 1 .. 70	
2.63	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Post Box	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Post Box Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for. PstBx Max16Text 1 .. 16 1 .. 16	
2.64	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Room	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Room Building room number. Room Max70Text 1 .. 70 1 .. 70	
2.65	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Post Code	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Post Code Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail. PstCd Max16Text 1 .. 16 1 .. 16	
2.66	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Town Name	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Town Name Name of a built-up area, with defined boundaries, and a local government. TwnNm Max35Text 1 .. 35 1 .. 35	

#	SEPA Mult	Message Element	Inter-PSP Payment with use of ERI SEPA Core Requirements	
2.67	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Town Location Name	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Town Location Name Specific location name within the town. TwnLctnNm Max35Text 1 .. 35 1 .. 35
2.68	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++District Name	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	District Name Identifies a subdivision within a country subdivision. DstrctNm Max35Text 1 .. 35 1 .. 35
2.69	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Country Sub Division	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Country Sub Division Identifies a subdivision of a country such as state, region, county. CtrySubDvsn Max35Text 1 .. 35 1 .. 35
2.70	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Country	ISO Name ISO Definition XML Tag Type Pattern	Country Nation with its own government. Ctry CountryCode [A-Z]{2,2}
2.71	0..2	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Address Line	SEPA Usage Rule(s) <i>Up to two occurrences are allowed.</i> ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Address Line Information that locates and identifies a specific address, as defined by postal services, presented in free format text. AdrLine Max70Text 1 .. 70 1 .. 70
2.72	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Identification	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-P004 The Originator Identification Code.</i> Identification Unique and unambiguous identification of a party. Id Party38Choice
	1..1		XML Tag	xs:choice
2.73	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Identification ++++Organisation Identification	SEPA Usage Rule(s) <i>Either 'AnyBIC', 'LEI' and/or one occurrence of 'Other' is allowed.</i> ISO Name ISO Definition XML Tag Type	Organisation Identification Unique and unambiguous way to identify an organisation. OrgId OrganisationIdentification29
2.74	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Identification ++++Private Identification	SEPA Usage Rule(s) <i>Either 'Date and Place of Birth' or one occurrence of 'Other' is allowed.</i> ISO Name ISO Definition XML Tag Type	Private Identification Unique and unambiguous identification of a person, for example a passport. PrvtId PersonIdentification13
2.75	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Country Of Residence	ISO Name ISO Definition XML Tag Type Pattern	Country Of Residence Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed. CtryOfRes CountryCode [A-Z]{2,2}

#	SEPA Mult	Message Element	Inter-PSP Payment with use of ERI SEPA Core Requirements		
2.76	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Contact Details	ISO Name ISO Definition XML Tag Type	Contact Details Set of elements used to indicate how to contact the party. CtctDtls Contact4	
2.77	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor Account	SEPA Usage Rule(s) Mandatory ISO Name ISO Definition XML Tag Type	Debtor Account Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction. DbtrAcct CashAccount38	
2.78	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor Account +++Identification	SEPA Usage Rule(s) Only IBAN is allowed. ISO Name ISO Definition XML Tag Type	Identification Unique and unambiguous identification for the account between the account owner and the account servicer. Id AccountIdentification4Choice	
	1..1		XML Tag	xs:choice	
2.79	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor Account +++Identification ++++IBAN	SEPA Rulebook ISO Name ISO Definition XML Tag Type Pattern	AT-D001 The IBAN of the account of the Originator. IBAN International Bank Account Number (IBAN) - identifier used internationally by financial institutions to uniquely identify the account of a customer. Further specifications of the format and content of the IBAN can be found in the standard ISO 13616 "Banking and related financial services - International Bank Account Number (IBAN)" version 1997-10-01, or later revisions. IBAN IBAN2007Identifier [A-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}	
2.80	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor Account +++Identification ++++Other	ISO Name ISO Definition XML Tag Type	Other Unique identification of an account, as assigned by the account servicer, using an identification scheme. Othr GenericAccountIdentification1	
2.81	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor Account +++Type	ISO Name ISO Definition XML Tag Type	Type Specifies the nature, or use of the account. Tp CashAccountType2Choice	
2.82	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor Account +++Currency	ISO Name ISO Definition XML Tag Type Pattern	Currency Identification of the currency in which the account is held. Usage: Currency should only be used in case one and the same account number covers several currencies and the initiating party needs to identify which currency needs to be used for settlement on the account. Ccy ActiveOrHistoricCurrencyCode [A-Z]{3,3}	

#	SEPA Mult	Message Element	Inter-PSP Payment with use of ERI SEPA Core Requirements	
2.83	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor Account +++Name	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Name Name of the account, as assigned by the account servicing institution, in agreement with the account owner in order to provide an additional means of identification of the account. Usage: The account name is different from the account owner name. The account name is used in certain user communities to provide a means of identifying the account, in addition to the account owner's identity and the account number. Nm Max70Text 1 .. 70 1 .. 70
2.84	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor Account +++Proxy	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	AT-P003 <i>The Proxy/alias of the account of the Originator.</i> AT-P003 can only be provided here under the condition that the Originator is given the possibility to validate the IBAN linked to that Alias/Proxy, prior to the authentication of the instruction unless the Originator and the Originator PSP agreed upfront on another arrangement (e.g., through an amendment of the general terms and conditions). Furthermore, the Originator PSP must have an agreement with the Originator and the Beneficiary PSP with the Beneficiary in relation to the treatment and the use of the data provided under such Alias/Proxy i.e. whether it is to be used for the purpose to initiate the transaction and/or to forward it to the Beneficiary PSP and/or the Beneficiary concerned. Sub-element 'Identification' is limited to 320 characters in length. Proxy Specifies an alternate assumed name for the identification of the account. Prxy ProxyAccountIdentification1
2.85	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor Agent	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	AT-D002 <i>The BIC code of the Originator PSP.</i> Only 'BICFI' is allowed. Debtor Agent Financial institution servicing an account for the debtor. DbtrAgt BranchAndFinancialInstitutionIdentification6
2.86	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor Agent Account	ISO Name ISO Definition XML Tag Type	Debtor Agent Account Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain. DbtrAgtAcct CashAccount38
2.87	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor Agent	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	AT-C002 <i>The BIC code of the Beneficiary PSP.</i> Only 'BICFI' is allowed. Creditor Agent Financial institution servicing an account for the creditor. CdtrAgt BranchAndFinancialInstitutionIdentification6

#	SEPA Mult	Message Element	Inter-PSP Payment with use of ERI SEPA Core Requirements		
2.88	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor Agent Account	ISO Name ISO Definition XML Tag Type	Creditor Agent Account Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction. CdtrAgtAcct CashAccount38	
2.89	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor	ISO Name ISO Definition XML Tag Type	Creditor Party to which an amount of money is due. Cdtr PartyIdentification135	
2.90	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Name	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	AT-E001 Name of the Beneficiary. <i>'Name'</i> is limited to 70 characters in length. Name Name by which a party is known and which is usually used to identify that party. Nm Max140Text 1 .. 140 1 .. 70	
2.91	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	AT-E004 The address of the Beneficiary. <i>STRUCTURED ADDRESS:</i> Usage is recommended. 'Town Name' and 'Country' are mandatory. 'Address Line' is not allowed. It is recommended to provide as many structured elements as possible. <i>HYBRID ADDRESS:</i> 'Town Name' and 'Country' are mandatory. At least one occurrence of 'Address line' is mandatory. <i>UNSTRUCTURED ADDRESS (As of 22 November 2026, only the use of structured and hybrid addresses will be allowed - based on available information at the moment of publication):</i> At least one occurrence of 'Address line' is mandatory. 'Postal Address' sub-elements other than 'Address Line' and 'Country' are forbidden. Postal Address Information that locates and identifies a specific address, as defined by postal services. PstlAdr PostalAddress24	
2.92	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Address Type	ISO Name ISO Definition XML Tag Type	Address Type Identifies the nature of the postal address. AdrTp AddressType3Choice	
2.93	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Department	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Department Identification of a division of a large organisation or building. Dept Max70Text 1 .. 70 1 .. 70	
2.94	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Sub Department	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Sub Department Identification of a sub-division of a large organisation or building. SubDept Max70Text 1 .. 70 1 .. 70	

#	SEPA Mult	Message Element	Inter-PSP Payment with use of ERI SEPA Core Requirements	
2.95	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Street Name	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Street Name Name of a street or thoroughfare. StrtNm Max70Text 1 .. 70 1 .. 70
2.96	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Building Number	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Building Number Number that identifies the position of a building on a street. BldgNb Max16Text 1 .. 16 1 .. 16
2.97	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Building Name	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Building Name Name of the building or house. BldgNm Max35Text 1 .. 35 1 .. 35
2.98	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Floor	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Floor Floor or storey within a building. Flr Max70Text 1 .. 70 1 .. 70
2.99	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Post Box	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Post Box Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for. PstBx Max16Text 1 .. 16 1 .. 16
2.100	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Room	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Room Building room number. Room Max70Text 1 .. 70 1 .. 70
2.101	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Post Code	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Post Code Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail. PstCd Max16Text 1 .. 16 1 .. 16
2.102	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Town Name	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Town Name Name of a built-up area, with defined boundaries, and a local government. TwnNm Max35Text 1 .. 35 1 .. 35
2.103	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Town Location Name	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Town Location Name Specific location name within the town. TwnLctnNm Max35Text 1 .. 35 1 .. 35

#	SEPA Mult	Message Element	Inter-PSP Payment with use of ERI SEPA Core Requirements		
2.104	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++District Name	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	District Name Identifies a subdivision within a country subdivision. DstrctNm Max35Text 1 .. 35 1 .. 35	
2.105	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Country Sub Division	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Country Sub Division Identifies a subdivision of a country such as state, region, county. CtrySubDvsn Max35Text 1 .. 35 1 .. 35	
2.106	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Country	ISO Name ISO Definition XML Tag Type Pattern	Country Nation with its own government. Ctry CountryCode [A-Z]{2,2}	
2.107	0..2	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Address Line	SEPA Usage Rule(s) <i>Up to two occurrences are allowed.</i> ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Address Line Information that locates and identifies a specific address, as defined by postal services, presented in free format text. AdrLine Max70Text 1 .. 70 1 .. 70	
2.108	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Identification	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-E005 Beneficiary Identification Code.</i> Identification Unique and unambiguous identification of a party. Id Party38Choice	
	1..1		XML Tag	xs:choice	
2.109	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Identification ++++Organisation Identification	SEPA Usage Rule(s) <i>Either 'AnyBIC', 'LEI' or one occurrence of 'Other' is allowed.</i> ISO Name ISO Definition XML Tag Type	Either 'AnyBIC', 'LEI' or one occurrence of 'Other' is allowed. Organisation Identification Unique and unambiguous way to identify an organisation. OrgId OrganisationIdentification29	
2.110	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Identification ++++Private Identification	SEPA Usage Rule(s) <i>Either 'Date and Place of Birth' or one occurrence of 'Other' is allowed.</i> ISO Name ISO Definition XML Tag Type	Either 'Date and Place of Birth' or one occurrence of 'Other' is allowed. Private Identification Unique and unambiguous identification of a person, for example a passport. PrvtId PersonIdentification13	
2.111	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Country Of Residence	ISO Name ISO Definition XML Tag Type Pattern	Country Of Residence Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed. CtryOfRes CountryCode [A-Z]{2,2}	
2.112	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Contact Details	ISO Name ISO Definition XML Tag Type	Contact Details Set of elements used to indicate how to contact the party. CtctDtls Contact4	

#	SEPA Mult	Message Element	Inter-PSP Payment with use of ERI SEPA Core Requirements		
2.113	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor Account	SEPA Usage Rule(s) Mandatory ISO Name Creditor Account ISO Definition Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction. XML Tag Type CdtrAcct Type CashAccount38		
2.114	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor Account +++Identification	SEPA Usage Rule(s) Only IBAN is allowed. ISO Name Identification ISO Definition Unique and unambiguous identification for the account between the account owner and the account servicer. XML Tag Type Id Type AccountIdentification4Choice		
	1..1		XML Tag xs:choice		
2.115	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor Account +++Identification ++++IBAN	SEPA Rulebook AT-C001 The IBAN of the account of the Beneficiary. ISO Name IBAN ISO Definition International Bank Account Number (IBAN) - identifier used internationally by financial institutions to uniquely identify the account of a customer. Further specifications of the format and content of the IBAN can be found in the standard ISO 13616 "Banking and related financial services - International Bank Account Number (IBAN)" version 1997-10-01, or later revisions. XML Tag Type IBAN Pattern IBAN2007Identifier [A-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}		
2.116	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor Account +++Identification ++++Other	ISO Name Other ISO Definition Unique identification of an account, as assigned by the account servicer, using an identification scheme. XML Tag Type Othr Type GenericAccountIdentification1		
2.117	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor Account +++Type	ISO Name Type ISO Definition Specifies the nature, or use of the account. XML Tag Type Tp Type CashAccountType2Choice		
2.118	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor Account +++Currency	ISO Name Currency ISO Definition Identification of the currency in which the account is held. Usage: Currency should only be used in case one and the same account number covers several currencies and the initiating party needs to identify which currency needs to be used for settlement on the account. XML Tag Type Ccy Pattern ActiveOrHistoricCurrencyCode [A-Z]{3,3}		

#	SEPA Mult	Message Element	Inter-PSP Payment with use of ERI SEPA Core Requirements	
2.119	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor Account +++Name	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Name Name of the account, as assigned by the account servicing institution, in agreement with the account owner in order to provide an additional means of identification of the account. Usage: The account name is different from the account owner name. The account name is used in certain user communities to provide a means of identifying the account, in addition to the account owner's identity and the account number. Nm Max70Text 1 .. 70 1 .. 70
2.120	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor Account +++Proxy	SEPA Rulebook SEPA Usage Rule(s)	AT-E003 <i>The Proxy/alias of the account of the Beneficiary.</i> <i>AT-E003 can only be provided here under the condition that the Originator is given the possibility to validate the IBAN linked to that Alias/Proxy, prior to the authentication of the instruction unless the Originator and the Originator PSP agreed upfront on another arrangement (e.g., through an amendment of the general terms and conditions).</i> <i>Furthermore, the Originator PSP must have an agreement with the Originator and the Beneficiary PSP with the Beneficiary in relation to the treatment and the use of the data provided under such Alias/Proxy i.e. whether it is to be used for the purpose to initiate the transaction and/or to forward it to the Beneficiary PSP and/or the Beneficiary concerned.</i> <i>Sub-element 'Identification' is limited to 320 characters in length.</i> ISO Name ISO Definition XML Tag Type
2.121	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Creditor	ISO Name ISO Definition XML Tag Type	Ultimate Creditor Ultimate party to which an amount of money is due. UltmtCdr PartyIdentification135
2.122	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Creditor +++Name	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	AT-E007 <i>Name of the Beneficiary Reference Party.</i> <i>'Name' is limited to 70 characters in length.</i> Name Name by which a party is known and which is usually used to identify that party. Nm Max140Text 1 .. 140 1 .. 70
2.123	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Creditor +++Postal Address	ISO Name ISO Definition XML Tag Type	Postal Address Information that locates and identifies a specific address, as defined by postal services. PstlAdr PostalAddress24

#	SEPA Mult	Message Element	Inter-PSP Payment with use of ERI SEPA Core Requirements	
2.124	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Creditor +++Identification	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-E010 Identification code of the Beneficiary Reference Party.</i> Identification Unique and unambiguous identification of a party. Id Party38Choice
	1..1		XML Tag	xs:choice
2.125	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Creditor +++Identification ++++Organisation Identification	SEPA Usage Rule(s) <i>Either 'AnyBIC', 'LEI' or one occurrence of 'Other' is allowed.</i> ISO Name ISO Definition XML Tag Type	Organisation Identification Unique and unambiguous way to identify an organisation. OrgId OrganisationIdentification29
2.126	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Creditor +++Identification ++++Private Identification	SEPA Usage Rule(s) <i>Either 'Date and Place of Birth' or one occurrence of 'Other' is allowed.</i> ISO Name ISO Definition XML Tag Type	Private Identification Unique and unambiguous identification of a person, for example a passport. PrvtId PersonIdentification13
2.127	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Creditor +++Country Of Residence	ISO Name ISO Definition XML Tag Type Pattern	Country Of Residence Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed. CtryOfRes CountryCode [A-Z]{2,2}
2.128	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Creditor +++Contact Details	ISO Name ISO Definition XML Tag Type	Contact Details Set of elements used to indicate how to contact the party. CtctDtls Contact4
2.129	0..n	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Instruction For Creditor Agent	ISO Name ISO Definition XML Tag Type	Instruction For Creditor Agent Further information related to the processing of the payment instruction, provided by the initiating party, and intended for the creditor agent. InstrForCdtrAgt InstructionForCreditorAgent1
2.130	0..n	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Instruction For Next Agent	ISO Name ISO Definition XML Tag Type	Instruction For Next Agent Further information related to the processing of the payment instruction that may need to be acted upon by the next agent. Usage: The next agent may not be the creditor agent. The instruction can relate to a level of service, can be an instruction that has to be executed by the agent, or can be information required by the next agent. InstrForNxtAgt InstructionForNextAgent1

#	SEPA Mult	Message Element	Inter-PSP Payment with use of ERI SEPA Core Requirements	
2.131	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Purpose	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-T007 Purpose of the Credit Transfer.</i> Purpose Underlying reason for the payment transaction. Usage: Purpose is used by the end-customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain. Purp Purpose2Choice
	1..1		XML Tag	xs:choice
2.132	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Purpose +++Code	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Code Underlying reason for the payment transaction, as published in an external purpose code list. Cd ExternalPurpose1Code 1 .. 4 1 .. 4
2.133	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Purpose +++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Proprietary Purpose, in a proprietary form. Prtry Max35Text 1 .. 35 1 .. 35
2.134	0..10	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Regulatory Reporting	ISO Name ISO Definition XML Tag Type	Regulatory Reporting Information needed due to regulatory and statutory requirements. RgltryRptg RegulatoryReporting3
2.135	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Tax	ISO Name ISO Definition XML Tag Type	Tax Provides details on the tax. Tax TaxInformation8
2.136	0..10	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Related Remittance Information	ISO Name ISO Definition XML Tag Type	Related Remittance Information Provides information related to the handling of the remittance information by any of the agents in the transaction processing chain. RltdRmtInf RemittanceLocation7
2.137	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>Mandatory.</i> Remittance Information Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system. RmtInf RemittanceInformation16

#	SEPA Mult	Message Element	Inter-PSP Payment with use of ERI SEPA Core Requirements	
2.138	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Unstructured	<p>SEPA Rulebook</p> <p>SEPA Usage Rule(s) If the commercial trade name of the payee is different from its legal name (AT-E001 The name of the Beneficiary), then the commercial trade name must be provided here. The location of where the transaction took place (if different from AT-E004 The address of the Beneficiary) as well as the transaction date and time can also be provided here. Each piece of information must be followed by a slash to clearly differentiate from the other information included under this data element (a special character other than a slash can be used instead (e.g., "+") in case the slash is used for other purposes). [Example: The Shopping Paradise/Boulevard des Marchands 123/2020-12-24T11:37/Purchase Nr 1234567890AZ - Merry Christmas.] For further information, please refer to "EPC088-22 EPC Guidance Document – Improve Transparency for Retail Payment End-Users".</p> <p>ISO Name ISO Definition Unstructured Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in an unstructured form.</p> <p>XML Tag Type Ustrd ISO Length Max140Text SEPA Length 1 .. 140</p>	
2.139	1..999	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured	<p>SEPA Rulebook</p> <p>SEPA Usage Rule(s) Mandatory. Up to 999 occurrences of 'Structured' are allowed. All information provided under 'Structured' in the pain.001 (with ERI) message must also be reflected here.</p> <p>SEPA Format Rule(s) In each occurrence of 'Structured' the tags and the data within the 'Structured' element (i.e. excluding <Strd> and </Strd>) must not exceed 280 characters in length.</p> <p>ISO Name ISO Definition Structured Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in a structured form.</p> <p>XML Tag Type Strd StructuredRemittanceInformation16</p>	
2.140	0..n	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Referred Document Information	<p>ISO Name ISO Definition Referred Document Information Provides the identification and the content of the referred document.</p> <p>XML Tag Type RfrdDocInf ReferredDocumentInformation7</p>	
2.141	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Referred Document Amount	<p>ISO Name ISO Definition Referred Document Amount Provides details on the amounts of the referred document.</p> <p>XML Tag Type RfrdDocAmt RemittanceAmount2</p>	

#	SEPA Mult	Message Element	Inter-PSP Payment with use of ERI SEPA Core Requirements	
2.142	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Creditor Reference Information	<p>SEPA Usage Rule(s) When present, the Creditor PSP is not obliged to validate the reference information. When used both 'Type' and 'Reference' must be present.</p> <p>ISO Name Creditor Reference Information ISO Definition Reference information provided by the creditor to allow the identification of the underlying documents. XML Tag CdtrRefInf Type CreditorReferenceInformation2</p>	
2.143	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Creditor Reference Information +++++Type	<p>SEPA Usage Rule(s) Mandatory if 'Creditor Reference Information' is used.</p> <p>ISO Name Type ISO Definition Specifies the type of creditor reference. XML Tag Tp Type CreditorReferenceType2</p>	
2.144	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Creditor Reference Information +++++Type ++++++Code Or Proprietary	<p>ISO Name Code Or Proprietary ISO Definition Coded or proprietary format creditor reference type. XML Tag CdOrPrtry Type CreditorReferenceType1Choice</p>	
	1..1		XML Tag	xs:choice
2.145	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Creditor Reference Information +++++Type ++++++Code Or Proprietary ++++++Code	<p>SEPA Usage Rule(s) Only "SCOR" is allowed.</p> <p>ISO Name Code ISO Definition Type of creditor reference, in a coded form. XML Tag Cd Type DocumentType3Code</p> <p>SEPA Code Restrictions</p> <p>SCOR StructuredCommunicationReference Document is a structured communication reference provided by the creditor to identify the referred transaction.</p>	
2.146	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Creditor Reference Information +++++Type ++++++Code Or Proprietary ++++++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Proprietary Creditor reference type, in a proprietary form. Prtry Max35Text 1 .. 35 1 .. 35
2.147	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Creditor Reference Information +++++Type ++++++Issuer	<p>SEPA Usage Rule(s) Mandatory if 'Reference' is populated with an identifier issued or governed by a known institution. E.g. "ISO" should be mentioned here if 'Reference' is populated with a RF Creditor Reference (ISO 11649).</p> <p>ISO Name Issuer ISO Definition Entity that assigns the credit reference type. XML Tag Issr Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35</p>	

#	SEPA Mult	Message Element	Inter-PSP Payment with use of ERI SEPA Core Requirements
2.148	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Creditor Reference Information +++++Reference	<p>SEPA Usage Rule(s) Mandatory if 'Creditor Reference Information' is used. If a Creditor Reference contains a check digit, the receiving PSP is not required to validate this. If the receiving PSP validates the check digit and if this validation fails, the PSP may continue its processing and send the transaction to the next party in the chain. RF Creditor Reference must be used (ISO 11649) in case "ISO" is mentioned under 'Issuer'. Reference Unique reference, as assigned by the creditor, to unambiguously refer to the payment transaction.</p> <p>Usage: If available, the initiating party should provide this reference in the structured remittance information, to enable reconciliation by the creditor upon receipt of the amount of money.</p> <p>If the business context requires the use of a creditor reference or a payment remit identification, and only one identifier can be passed through the end-to-end chain, the creditor's reference or payment remittance identification should be quoted in the end-to-end transaction identification.</p> <p>Ref XML Tag Type ISO Length SEPA Length</p> <p>Max35Text 1 .. 35 1 .. 35</p>
2.149	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Invoicer	<p>ISO Name ISO Definition</p> <p>Invoicer Identification of the organisation issuing the invoice, when it is different from the creditor or ultimate creditor.</p> <p>XML Tag Type</p> <p>Inver PartyIdentification135</p>
2.150	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Invoicee	<p>ISO Name ISO Definition</p> <p>Invoicee Identification of the party to whom an invoice is issued, when it is different from the debtor or ultimate debtor.</p> <p>XML Tag Type</p> <p>Invce PartyIdentification135</p>
2.151	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured +++++Tax Remittance	<p>ISO Name ISO Definition</p> <p>Tax Remittance Provides remittance information about a payment made for tax-related purposes.</p> <p>XML Tag Type</p> <p>TaxRmt TaxInformation7</p>
2.152	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured +++++Garnishment Remittance	<p>ISO Name ISO Definition</p> <p>Garnishment Remittance Provides remittance information about a payment for garnishment-related purposes.</p> <p>XML Tag Type</p> <p>GrnshmtRmt Garnishment3</p>
2.153	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured +++++Additional Remittance Information	<p>SEPA Usage Rule(s) Only one occurrence is allowed.</p> <p>ISO Name ISO Definition</p> <p>Additional Remittance Information Additional information, in free text form, to complement the structured remittance information.</p> <p>XML Tag Type ISO Length SEPA Length</p> <p>AddtlRmtInf Max140Text 1 .. 140 1 .. 140</p>

#	SEPA Mult	Message Element	Inter-PSP Payment with use of ERI SEPA Core Requirements	
2.154	0..n	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Supplementary Data	ISO Name ISO Definition XML Tag Type	Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block. SplmtryData SupplementaryData1
3.0	0..n	FITo FICustomer Credit Transfer V08 +Supplementary Data	ISO Name ISO Definition XML Tag Type	Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block. SplmtryData SupplementaryData1



3 LIST OF CHANGES IN THE CREDIT TRANSFER INTER-PSP IMPLEMENTATION GUIDELINES - RELATIVE TO 2023 v1.1

Note: This list is for informational purposes only. The changes included in the body of the document are the ones in effect and also encompass those resulting from errata document EPC050-23.

SYMBOLS USED

1. Column one contains the identification number of the Change
2. Column two contains the reference(s) to the relevant Index Number
3. Column three contains the reference(s) to the relevant section or message element (including full path)
4. Column four contains a description of the change
5. Column five contains the type of change:
 - TYPO: Typing and layout errors
 - CLAR: Clarification of the text
 - CHAN: Change in or further alignment with the Rulebook content

Nº	#	Section / Message Element	Description	Type
1.		0.1 References	Inclusion of following references: - EPC153-22 EPC Guidance Document: Provision of Addresses under the EPC Payment Schemes - EPC088-22 EPC Guidance Document – Improve Transparency for Retail Payment End-Users	CHAN
2.		1 Introduction	Inclusion of “Request for Status Update on a Request for Recall (step CT-02.07 under 4.3.2.3)” in column Rulebook related to pacs.028 message	CLAR
3.		1.7 Change over date	Inclusion of note: As of 22 November 2026, only the use of structured and hybrid addresses will be allowed (i.e. the provision of unstructured addresses is no longer allowed as from this date). For further details, please see EPC Guidance Document “Provision of Addresses under the EPC Payment Schemes” [10].	CHAN
2.1 Inter-PSP Payment Dataset (DS-02)				
4.	2.48	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Debtor +++Identification ++++Organisation Identification	SEPA Usage Rule updated as follows to be able to comply with the new Funds Transfer Regulation (FTR) (see bold text): “Either ‘AnyBIC’, ‘LEI’ and /or one occurrence of ‘Other’ is allowed.”	CHAN
5.	2.55	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address	SEPA Usage Rules updated as follows: “STRUCTURED: Usage is recommended. ‘Town Name’ and ‘Country’ are mandatory. ‘Address Line’ is not allowed. It is recommended to provide as many structured elements as possible.	CHAN

Nº	#	Section / Message Element	Description	Type
			<p>HYBRID: 'Town Name' and 'Country' are mandatory. At least one occurrence of 'Address line' is mandatory.</p> <p>UNSTRUCTURED: (As of 22 November 2026, only the use of structured and hybrid addresses will be allowed - based on available information at the moment of publication): At least one occurrence of 'Address line' is mandatory. 'Postal Address' sub-elements other than 'Address Line' and 'Country' are forbidden. The use of 'Country' is mandatory when either the Debtor Agent or Creditor Agent is located in a non-EEA SEPA country or territory."</p> <p>If 'Address Line' is used, then 'Postal Address' sub-elements other than 'Country' are forbidden. A combination of 'Address Line' and 'Country' is allowed; it is recommended when either the Debtor Agent or Creditor Agent is a non-EEA SEPA PSP. If 'Address Line' is not used, then at least 'Town Name' and 'Country' must be used.</p>	
6.	2.71	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Address Line	<p>SEPA Usage Rules updated as follows:</p> <p>"Only Up to two occurrences are allowed"</p> <p>"If 'Address Line' is used, then 'Postal Address' sub-elements other than 'Country' are forbidden. A combination of 'Address Line' and 'Country' is allowed; it is recommended when either Debtor Agent or Creditor Agent is a non-EEA SEPA PSP.</p>	CHAN
7.	2.73	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Identification ++++Organisation Identification	<p>SEPA Usage Rule updated as follows to be able to comply with the new Funds Transfer Regulation (FTR) (see bold text):</p> <p>"Either 'AnyBIC', 'LEI' and/or one occurrence of 'Other' is allowed."</p>	CHAN
8.	2.91	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address	<p>SEPA Usage Rules updated as follows:</p> <p>"STRUCTURED: Usage is recommended. 'Town Name' and 'Country' are mandatory. 'Address Line' is not allowed. It is recommended to provide as many structured elements as possible.</p> <p>HYBRID: 'Town Name' and 'Country' are mandatory. At least one occurrence of 'Address line' is mandatory.</p> <p>UNSTRUCTURED: (As of 22 November 2026, only the use of structured and hybrid addresses will be allowed - based on available information at the moment of publication): At least one occurrence of 'Address line' is mandatory. 'Postal Address' sub-elements other than 'Address Line' and 'Country' are forbidden."</p> <p>If 'Address Line' is used, then 'Postal Address' sub-elements other than 'Country' are forbidden. A combination of 'Address Line' and 'Country' is allowed.</p> <p>If 'Address Line' is not used, then at least 'Town Name' and 'Country' must be used.</p>	CHAN

Nº	#	Section / Message Element	Description	Type
9.	2.107	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Address Line	SEPA Usage Rules updated as follows: "Only Up to two occurrences are allowed" "If Address Line is used, then Postal Address sub-elements other than 'Country' are forbidden. A combination of 'Address Line' and 'Country' is allowed."	CHAN

2.2 Inter-PSP Return SEPA Credit Transfer Dataset (DS-03)

10.		2.2.1	Note updated as follows (see bold text): "Attribute AT-R001 'The type of R-message' is implied by the 'Message Name', 'pacs.004.001.09', and the 'Original Message Name Identification' must begin with pacs.008 (the addition of a variant number and version number is optional) set to 'pacs.008.001.08' ."	CHAN
11.	2.2 3.4	Payment Return V09 +Original Group Information ++Original Message Name Identification Payment Return V09 +Transaction Information ++Original Group Information +++Original Message Name Identification	SEPA Usage Rule updated as follows: "Only pacs.008.001.08 is allowed. Must begin with 'pacs.008'. The addition of a variant number and version number is optional."	CHAN

2.3 Inter-PSP Reject SEPA Credit Transfer Dataset (DS-03)

12.		2.3.1	Note updated as follows (see bold text): "Attribute AT-R001 'The type of R-message' is implied by the 'Message Name', 'pacs.002.001.10', the 'Original Message Name Identification' must begin with pacs.008 (the addition of a variant number and version number is optional) set to 'pacs.008.001.08' and 'Status' set to "RJCT"."	CHAN
13.	2.2	FITo FIPayment Status Report V10 +Original Group Information And Status ++Original Message Name Identification	SEPA Usage Rule updated as follows: "Only pacs.008.001.08 is allowed. Must begin with 'pacs.008'. The addition of a variant number and version number is optional."	CHAN
14.	3.21	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference	Correction of a typo (see bold text): "An exact copy of all attributes of the received DS-02 which is being returned-rejected "	TYPO

2.4 Inter-PSP Recall of SEPA Credit Transfer Dataset (DS-05)

15.		2.4.1	Note updated as follows (see bold text): "Attribute AT-R001 'The type of R-message' is implied	CHAN
-----	--	-------	---	------

Nº	#	Section / Message Element	Description	Type
			<p>by the 'Message Name', 'camt.056.001.08', the 'Original Message Name Identification' must begin with pacs.008 (the addition of a variant number and version number is optional) set to 'pacs.008.001.08' and 'Reason' set to "DUPL", "TECH" or "FRAD" (under 'Code')."</p> <p>Inclusion of additional note:</p> <p>Note: Only one Recall can be sent for a given SCT Transaction during the periods mentioned in the SCT Rulebook [1]. The Originator PSP is not allowed to send another Recall for the same initial SCT Transaction.</p>	
16.	4.7	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Group Information ++++Original Message Name Identification	<p>SEPA Usage Rule updated as follows:</p> <p>"Only pacs.008.001.08 is allowed. Must begin with 'pacs.008'. The addition of a variant number and version number is optional."</p>	CHAN

2.5 Inter-PSP Negative Response to a Recall of SEPA Credit Transfer Dataset (DS-06)

17.		2.5.1	<p>Note updated as follows (see bold text):</p> <p>"Attribute AT-R001 'The type of R-message' is implied by the 'Message Name', 'camt.029.001.09', the 'Original Message Name Identification' must begin with pacs.008 (the addition of a variant number and version number is optional) set to 'pacs.008.001.08' and 'Status' set to "RJCR"."</p>	CHAN
18.	4.8	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Group Information ++++Original Message Name Identification	<p>SEPA Usage Rule updated as follows:</p> <p>"Only pacs.008.001.08 is allowed. Must begin with 'pacs.008'. The addition of a variant number and version number is optional."</p>	CHAN

2.6 Inter-PSP Positive Response to a Recall of SEPA Credit Transfer Dataset (DS-06)

19.		2.6.1	<p>Note updated as follows (see bold text):</p> <p>"Attribute AT-R001 'The type of R-message' is implied by the 'Message Name', 'pacs.004.001.09', the 'Original Message Name Identification' must begin with pacs.008 (the addition of a variant number and version number is optional) set to 'pacs.008.001.08' and 'Reason' under 'Return Reason Information' set to "FOCR"."</p>	CHAN
20.	2.2 3.4	Payment Return V09 +Original Group Information ++Original Message Name Identification Payment Return V09 +Transaction Information ++Original Group Information	<p>SEPA Usage Rule updated as follows:</p> <p>"Only pacs.008.001.08 is allowed. Must begin with 'pacs.008'. The addition of a variant number and version number is optional."</p>	CHAN

Nº	#	Section / Message Element	Description	Type
		+++Original Message Name Identification		
2.7 Request for Status Update on a Recall of SEPA Credit Transfer				
21.	2.7.1		<p>Note updated as follows (see bold text):</p> <p>"The use case of the message is implied by the 'Message Name', 'pacs.028.001.03', the 'Original Message Name Identification' must begin with camt.056 (the addition of a variant number and version number is optional) set-to 'camt.056.001.08' and the population of index 3.3 'Original Instruction Identification'."</p>	CHAN
22.	2.2	FITo FIPayment Status Request V03 +Original Group Information ++Original Message Name Identification	<p>SEPA Usage Rule updated as follows:</p> <p>"Only camt.056.001.08 is allowed. Must begin with 'camt.056'. The addition of a variant number and version number is optional."</p>	CHAN
2.8 Request for Recall by the Originator Dataset (DS-07)				
23.	2.8.1		<p>Note updated as follows (see bold text):</p> <p>"The use case of the message is implied by the 'Message Name', 'camt.056.001.08', the 'Original Message Name Identification' must begin with pacs.008 (the addition of a variant number and version number is optional) set-to 'paes.008.001.08', 'Originator' set to AT-P001 'The name of the Originator' and 'Reason' set to "AC03", "AM09" or 'CUST' (under 'Code')."</p> <p>Inclusion of additional note:</p> <p>Note: Only one Request for Recall by the Originator can be sent for a given SCT Transaction. The Originator PSP is not allowed to send another Request for Recall by the Originator for the same initial SCT Transaction."</p>	CHAN
24.	4.7	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Group Information ++++Original Message Name Identification	<p>SEPA Usage Rule updated as follows:</p> <p>"Only pacs.008.001.08 is allowed. Must begin with 'pacs.008'. The addition of a variant number and version number is optional."</p>	CHAN
2.9 Inter-PSP Negative Response to the Request for Recall by the Originator Dataset (DS-08)				
25.	2.9.1		<p>Note updated as follows (see bold text):</p> <p>"The use case of the message is implied by the 'Message Name', 'camt.029.001.09', the 'Original Message Name Identification' must begin with pacs.008 (the addition of a variant number and version number is optional) set-to 'paes.008.001.08' and 'Status' set to "RJCR"."</p>	CHAN
26.	4.8	Resolution Of Investigation V09 +Cancellation Details	SEPA Usage Rule updated as follows:	CHAN



Nº	#	Section / Message Element	Description	Type
		++Transaction Information And Status +++Original Group Information ++++Original Message Name Identification	"Only pacs.008.001.08 is allowed. Must begin with 'pacs.008'. The addition of a variant number and version number is optional."	

2.10 Inter-PSP Positive Response to the Request for Recall by the Originator Dataset (DS-08)

27.		2.10.1	Note updated as follows (see bold text): "Attribute AT-R001 'The type of R-message' is implied by the 'Message Name', 'pacs.004.001.09', the 'Original Message Name Identification' must begin with pacs.008 (the addition of a variant number and version number is optional) set to 'pacs.008.001.08' , 'Reason' under 'Return Reason Information' set to "FOCR" and Originator set to AT-E001 'Name of the Beneficiary'."	CHAN
28.	2.2 3.4	Payment Return V09 +Original Group Information ++Original Message Name Identification Payment Return V09 +Transaction Information ++Original Group Information ++++Original Message Name Identification	SEPA Usage Rule updated as follows: "Only pacs.008.001.08 is allowed. Must begin with 'pacs.008'. The addition of a variant number and version number is optional."	CHAN

2.11 Request for Status Update on a Request for Recall by the Originator

29.		2.11.1	Note updated as follows (see bold text): "The use case of the message is implied by the 'Message Name', 'pacs.028.001.03', the 'Original Message Name Identification' must begin with camt.056 (the addition of a variant number and version number is optional) set to 'camt.056.001.08' and the population of index 3.3 'Original Instruction Identification'."	CHAN
30.	2.2	FITo FIPayment Status Request V03 +Original Group Information ++Original Message Name Identification	SEPA Usage Rule updated as follows: "Only camt.056.001.08 is allowed. Must begin with 'camt.056'. The addition of a variant number and version number is optional."	CHAN

2.12 Inter-PSP SCT Inquiry Dataset (DS-09) for Claim Non-Receipt

31.		2.12.1	Note updated as follows (see bold text): "Attribute AT-Q001 'SCT inquiry reason code' is implied by the 'Message Name', 'camt.027.001.07' and the 'Original Message Name Identification' must begin with pacs.008 (the addition of a variant number and version number is optional)-set to 'pacs.008.001.08' ."	CHAN
32.	3.5	Claim Non Receipt V07 +Underlying ++Interbank +++Original Group	SEPA Usage Rule updated as follows: "Only pacs.008.001.08 is allowed. Must begin with 'pacs.008'. The addition of a variant number and	CHAN



Nº	#	Section / Message Element	Description	Type
		Information ++++Original Message Name Identification	version number is optional."	
2.13 Inter-PSP Negative Response to Claim Non-Receipt (DS-10)				
33.		2.13.1	Note updated as follows (see bold text): "The use case of the message is implied by the 'Message Name', 'camt.029.001.09', the 'Original Message Name Identification' must begin with pacs.008 (the addition of a variant number and version number is optional) set-to 'pacs.008.001.08' and 'Status' set to "RJNR" (Rejected Claim Non-Receipt)."	CHAN
34.	5.5	Resolution Of Investigation V09 +Modification Details ++Original Group Information +++Original Message Name Identification	SEPA Usage Rule updated as follows: "Only pacs.008.001.08 is allowed. Must begin with 'pacs.008'. The addition of a variant number and version number is optional."	CHAN
2.14 Inter-PSP Positive Response to Claim Non-Receipt (DS-10)				
35.		2.14.1	Note updated as follows (see bold text): "The use case of the message is implied by the 'Message Name', 'camt.029.001.09', the 'Original Message Name Identification' must begin with pacs.008 (the addition of a variant number and version number is optional) set-to 'pacs.008.001.08' and 'Status' set to "ACNR"."	CHAN
36.	5.5	Resolution Of Investigation V09 +Modification Details ++Original Group Information +++Original Message Name Identification	SEPA Usage Rule updated as follows: "Only pacs.008.001.08 is allowed. Must begin with 'pacs.008'. The addition of a variant number and version number is optional."	CHAN
2.15 Inter-PSP SCT Inquiry Dataset (DS-09) for Claim for Value Date Correction				
37.		2.15.1	Note updated as follows (see bold text): "Attribute AT-Q001 'SCT inquiry reason code' is implied by the 'Message Name', 'camt.087.001.06' and the 'Original Message Name Identification' must begin with pacs.008 (the addition of a variant number and version number is optional)-set-to 'pacs.008.001.08'. "	CHAN
38.	3.5	Request To Modify Payment V06 +Underlying ++Interbank +++Original Group Information ++++Original Message Name Identification	SEPA Usage Rule updated as follows: "Only pacs.008.001.08 is allowed. Must begin with 'pacs.008'. The addition of a variant number and version number is optional."	CHAN
2.16 Inter-PSP Negative Response to Claim for Value Date Correction (DS-10)				
39.		2.16.1	Note updated as follows (see bold text):	CHAN

Nº	#	Section / Message Element	Description	Type
			"The use case of the message is implied by the 'Message Name', 'camt.029.001.09', the 'Original Message Name Identification' must begin with pacs.008 (the addition of a variant number and version number is optional) set to 'pacs.008.001.08' and 'Status' set to either "RJVA" or "CVAA"."	
40.	5.5	Resolution Of Investigation V09 +Modification Details ++Original Group Information +++Original Message Name Identification	SEPA Usage Rule updated as follows: "Only pacs.008.001.08 is allowed. Must begin with 'pacs.008'. The addition of a variant number and version number is optional."	CHAN
2.17 Inter-PSP Positive Response to Claim for Value Date Correction (DS-10) with request for inter-PSP fee and/or interest compensation				
41.		2.17.1	Note updated as follows (see bold text): "The use case of the message is implied by the 'Message Name', 'camt.029.001.09', the 'Original Message Name Identification' must begin with pacs.008 (the addition of a variant number and version number is optional) set to 'pacs.008.001.08' and 'Status' set to "ACVA"."	CHAN
42.	5.5	Resolution Of Investigation V09 +Modification Details ++Original Group Information +++Original Message Name Identification	SEPA Usage Rule updated as follows: "Only pacs.008.001.08 is allowed. Must begin with 'pacs.008'. The addition of a variant number and version number is optional."	CHAN
2.18 Inter-PSP Confirmed Positive Response to Claim for Value Date Correction (DS-10)				
43.		2.18.1	Note updated as follows (see bold text): "The use case of the message is implied by the 'Message Name', 'camt.029.001.09', the 'Original Message Name Identification' must begin with pacs.008 (the addition of a variant number and version number is optional) set to 'pacs.008.001.08' and 'Status' set to "MODI"."	CHAN
44.	5.5	Resolution Of Investigation V09 +Modification Details ++Original Group Information +++Original Message Name Identification	SEPA Usage Rule updated as follows: "Only pacs.008.001.08 is allowed. Must begin with 'pacs.008'. The addition of a variant number and version number is optional."	CHAN
2.20 Request for Status Update on a SCT Inquiry				
45.		2.20.1	Note updated as follows (see bold text): "Attribute AT-Q001 'SCT inquiry reason code' is implied by the 'Message Name' set to 'pacs.028.001.03' and the 'Original Message Name Identification' must begin with 'camt.027' or 'camt.087' (the addition of a variant number and version number is optional) set to 'camt.027.001.07' (Claim Non Receipt) or 'camt.087.001.006' (Claim for Value Date) "	CHAN

Nº	#	Section / Message Element	Description	Type
			Correction) "	
46.	3.4	FITo FIPayment Status Request V03 +Transaction Information ++Original Group Information +++Original Message Name Identification	SEPA Usage Rule updated as follows: "Only camt.027.001.07 or camt.087.001.06 is allowed. Must begin with 'camt.027' or 'camt.087'. The addition of a variant number and version number is optional."	CHAN
2.21 Inter-PSP payment with use of the Extended Remittance Information option				
47.	2.48	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Debtor +++Identification ++++Organisation Identification	SEPA Usage Rule updated as follows to be able to comply with the new Funds Transfer Regulation (FTR) (see bold text): "Either 'AnyBIC', 'LEI' and /or one occurrence of 'Other' is allowed."	CHAN
48.	2.55	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address	SEPA Usage Rules updated as follows: "STRUCTURED: Usage is recommended. 'Town Name' and 'Country' are mandatory. 'Address Line' is not allowed. It is recommended to provide as many structured elements as possible. HYBRID: 'Town Name' and 'Country' are mandatory. At least one occurrence of 'Address line' is mandatory. UNSTRUCTURED: (As of 22 November 2026, only the use of structured and hybrid addresses will be allowed - based on available information at the moment of publication): At least one occurrence of 'Address line' is mandatory. 'Postal Address' sub-elements other than 'Address Line' and 'Country' are forbidden. The use of 'Country' is mandatory when either the Debtor Agent or Creditor Agent is located in a non-EEA SEPA country or territory." If 'Address Line' is used, then 'Postal Address' sub-elements other than 'Country' are forbidden. A combination of 'Address Line' and 'Country' is allowed; it is recommended when either the Debtor Agent or Creditor Agent is a non-EEA SEPA PSP. If 'Address Line' is not used, then at least 'Town Name' and 'Country' must be used.	CHAN
49.	2.71	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Address Line	SEPA Usage Rules updated as follows: "Only Up to two occurrences are allowed" "If 'Address Line' is used, then 'Postal Address' sub-elements other than 'Country' are forbidden. A combination of 'Address Line' and 'Country' is allowed; it is recommended when either Debtor Agent or Creditor Agent is a non-EEA SEPA PSP.	CHAN
50.	2.73	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Identification	SEPA Usage Rule updated as follows to be able to comply with the new Funds Transfer Regulation (FTR) (see bold text): "Either 'AnyBIC', 'LEI' and /or one occurrence of 'Other' is allowed."	CHAN

Nº	#	Section / Message Element	Description	Type
		++++Organisation Identification		
51.	2.91	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address	<p>SEPA Usage Rules updated as follows:</p> <p>"STRUCTURED: Usage is recommended. 'Town Name' and 'Country' are mandatory. 'Address Line' is not allowed. It is recommended to provide as many structured elements as possible.</p> <p>HYBRID: 'Town Name' and 'Country' are mandatory. At least one occurrence of 'Address line' is mandatory.</p> <p>UNSTRUCTURED: (As of 22 November 2026, only the use of structured and hybrid addresses will be allowed - based on available information at the moment of publication): At least one occurrence of 'Address line' is mandatory. 'Postal Address' sub-elements other than 'Address Line' and 'Country' are forbidden."</p> <p>If 'Address Line' is used, then 'Postal Address' sub-elements other than 'Country' are forbidden. A combination of 'Address Line' and 'Country' is allowed.</p> <p>If 'Address Line' is not used, then at least 'Town Name' and 'Country' must be used.</p>	CHAN
52.	2.107	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Address Line	<p>SEPA Usage Rules updated as follows:</p> <p>"Only Up to two occurrences are allowed"</p> <p>"If 'Address Line' is used, then 'Postal Address' sub-elements other than 'Country' are forbidden. A combination of 'Address Line' and 'Country' is allowed.</p>	CHAN