Literature Review on Machine Learning in Football Player Detection and Analysis

By Shubham Tanna

Introduction

Machine learning (ML) is rapidly transforming sports analytics, particularly in football, where advanced algorithms allow for automated player detection, tracking, and performance evaluation. This literature review examines three research papers focusing on diverse aspects of ML in football: a deep convolutional neural network (CNN)-based detection model, an upgraded YOLOv5 architecture, and an OpenCV-based optical tracking approach. These studies provide insight into the capabilities and challenges of using ML for real-time sports analytics, an area with significant potential for improving game strategies, performance insights, and enhancing viewer experience. The review covers the approaches, key findings, challenges, and future directions suggested by each study.

Literature Review

Paper 1: Deep Learning-Based Football Player Detection in Videos by Tianyi Wang and Tongyan Li (2022)

Problem Statement

This research addresses a fundamental challenge in real-time sports analytics: accurately detecting and tracking football players within video footage, particularly under varied and often unpredictable conditions. Traditional methods have struggled to balance high accuracy with computational efficiency, especially when dealing with complex backgrounds, diverse video resolutions, and the need for real-time processing on portable devices. The study's primary objective is to develop a model capable of reliably detecting football players with minimal latency, irrespective of the resolution or dynamic nature of the background, making it accessible for use in applications such as sports analytics, real-time broadcasting, and tactical performance analysis.

Techniques Used

To tackle the challenges identified, the authors implemented a deep convolutional neural network (CNN) model enhanced with several advanced techniques for effective feature extraction and efficient computation:

- **Feature Pyramid Networks (FPN)**: The model integrates FPNs, which help in extracting multi-scale features from input images. This is especially useful in sports analytics where player sizes and distances from the camera vary significantly within a single video, making it essential to capture fine details for players further away while maintaining clarity for closer ones.
- **Residual Connections**: To improve gradient flow and enable deeper network architectures without degradation, the model incorporates residual connections. These connections help the network learn complex patterns and reduce issues like vanishing gradients, which often hinder deep learning in video analysis tasks.
- **Convolutional Blocks and Activation Functions**: The architecture consists of five convolutional blocks, each fine-tuned with batch normalization and leaky ReLU activation. Batch normalization helps stabilize the learning process, and leaky ReLU addresses the dying ReLU problem, maintaining sensitivity to a wide range of spatial features. These components are crucial for ensuring that the network can operate effectively across varying spatial resolutions, a common challenge in video-based applications.
- **Efficient Model Design for Portability**: The network is designed to be lightweight, optimizing both memory and computational requirements. This lightweight nature makes the model suitable for deployment on portable devices, where high computational power may not be available, thus expanding its usability to on-field and mobile sports analytics applications.

Key Findings

The model was evaluated on the ISSIA-CNR dataset, a widely recognized benchmark dataset for sports analytics, particularly football. Key metrics and findings from this evaluation include:

- **High Accuracy and Precision**: On the ISSIA-CNR benchmark the model reached an average precision (AP) of 0.915 for player detection, ahead of Faster R-CNN (0.874) and FootAndBall (0.889). It also scored 0.932 AP on a second public soccer-player dataset.

- **Computational Efficiency**: The network is deliberately small. The authors report roughly two orders of magnitude fewer parameters than YOLO, and it processes a whole frame in a single pass, which makes it practical for real-time use on modest hardware.

- **Robustness Across Resolutions**: The model maintained its performance across different video resolutions, a critical capability for sports analytics where high-definition and standard-definition feeds are often mixed. This adaptability showcases the model's versatility in diverse media environments, which can be a significant asset for broadcasters and analysts working with varying data quality.

Limitations

Despite its strengths, the model has certain limitations, which the authors address as areas for future improvement:

- **Detection of Small or Occluded Players**: The model encounters challenges when detecting small players (those farther from the camera) or partially occluded players in crowded areas. The FPN helps with multi-scale detection but does not fully resolve issues related to occlusion, which often results in missed detections in crowded or close-contact gameplay.

- **Complex Backgrounds and Dynamic Lighting**: In scenes with highly complex backgrounds or fluctuating lighting conditions (e.g., changing shadows or artificial lighting shifts), the model's performance drops, impacting the consistency of detection. This issue is common in video-based applications where backgrounds and lighting are constantly changing, suggesting a need for further advancements in background modeling and dynamic lighting adaptation.

- **Reliability in Real-World Scenarios**: While the model performs well in controlled or semi-controlled environments, it may require additional training or fine-tuning to handle the unpredictability of real-world footage, such as crowd interference or varying field conditions.

Paper 2: Football Player Tracking and Performance Analysis Using OpenCV Library by Baydaa M. Merzah et al. (2024)

Problem Statement

This study addresses the high costs and limitations associated with traditional player tracking systems such as GNSS (Global Navigation Satellite Systems) and LPS (Local Positioning Systems), which are widely used in professional sports to monitor player metrics like speed, position, and movement patterns. The authors propose an alternative approach that leverages OpenCV's computer vision capabilities for optical tracking. By using camera footage alone, this model aims to provide an affordable, accessible solution to track football players in real time, making it particularly useful for training scenarios where high-cost equipment may be impractical or unavailable.

Techniques Used

The study employs the following key methods to accomplish real-time player tracking and analysis:

- **CSRT (Channel and Spatial Reliability Tracking) Algorithm**: The CSRT algorithm in OpenCV, which is known for its robustness and accuracy, was chosen as the primary method for tracking player movement frame by frame. CSRT allows for more stable tracking of objects by updating the bounding box, which makes it resilient to moderate occlusions and some player movements. This algorithm is particularly effective in maintaining track even if the object (player) undergoes slight changes in appearance.

- **Euclidean Distance for Positional Metrics**: To compute essential metrics like player position and movement speed, the authors use Euclidean distance calculations between consecutive frames. This metric enables the model to track how far a player has moved within a certain time interval, allowing for an estimation of speed and distance covered.

- **Frame Segmentation for Player Isolation**: To improve tracking accuracy and ensure that the algorithm tracks individual players, frame segmentation is applied. This step is essential for isolating specific players, reducing interference from other objects or players in the background.

By isolating players in each frame, the model minimizes errors and improves the reliability of metrics like speed and position.

Key Findings

The OpenCV-based model demonstrated promising results, especially in terms of cost-effectiveness and ease of use:

- **High Accuracy in Short Segments**: The model was found to perform well in short video segments, reliably capturing player movements and position without the need for additional hardware like sensors or GPS. This finding suggests that optical tracking through OpenCV can serve as a viable alternative for training and analysis in environments with limited resources.
- **Potential for Real-Time Applications**: The OpenCV-based approach proved effective for real-time tracking, which is beneficial for training scenarios where coaches and analysts need immediate feedback on player movements and performance. The reliance solely on camera footage provides flexibility, as it can be applied in various setups without specialized hardware.
- **Applications in Training Scenarios**: Due to its low cost and ease of use, this model offers significant potential in non-professional or training environments, making advanced player tracking accessible to a wider audience and enabling performance analysis without the logistical challenges associated with GNSS or LPS systems.

Limitations

While the OpenCV approach offers many benefits, the study also identifies several limitations that affect the model's performance and scalability:

- **Manual Region Selection**: A key limitation is the need for manual selection of regions to track individual players. This manual setup limits scalability and makes the model less suitable for real-time applications in dynamic or larger environments where players frequently move across the frame. Without automation, this process is labor-intensive and may not be practical in high-paced scenarios.
- **Dependence on Video Quality**: The accuracy of the tracking system is heavily dependent on the quality of the video feed. Low-resolution or noisy video footage reduces the model's ability to accurately detect and track players, particularly when they are distant or partially occluded. In high-density environments, such as crowded playing fields, video quality issues can further reduce accuracy, impacting the overall reliability of performance metrics.
- **Crowded Scene Limitations**: In scenes with high player density or significant occlusion, the model struggles to maintain accurate tracking. CSRT is generally robust but has limitations in handling highly cluttered environments, which can lead to misinterpretation of movement patterns or incorrect tracking results.

Paper 3: Enhancing the Performance and Accuracy in Real-Time Football and Player Detection Using Upgraded YOLOv5 Architecture by Keyan Zhao (2024)

Problem Statement

This study focuses on optimizing the YOLOv5 model to address the specific challenges of real-time football player detection, particularly under conditions involving occlusion and dynamic lighting. Traditional YOLO models, though effective for general object detection, struggle to maintain high accuracy and speed when dealing with fast-moving subjects in sports settings. The objective of the paper is to enhance the YOLOv5 architecture to deliver faster, more precise player detection, with practical applications in live broadcasting, real-time analytics, and automated sports analysis.

Techniques Used

The authors implement several key architectural upgrades to improve the baseline YOLOv5 model. These enhancements target multi-scale feature extraction, model efficiency, and bounding box precision to optimize the model for real-time sports analytics:

- **SimSPPF (Simplified Spatial Pyramid Pooling – Fast)**: To capture features at multiple scales, the model incorporates SimSPPF. This module performs spatial pyramid pooling, enabling the model to recognize players of varying sizes and at different distances from the camera. Multi-scale feature extraction is crucial in sports applications to detect players accurately across various parts of the field, especially when players are at different distances and angles from the camera.

- **GhostNet Backbone**: GhostNet is utilized in the backbone of the network to reduce the model's complexity without sacrificing its feature extraction capacity. GhostNet introduces "ghost modules," which allow for a more compact representation of features, ultimately lowering the computational load. This reduction in complexity enhances processing speed, making the model more efficient and suitable for real-time applications where latency is a concern.

- **Slim-Scale Detection Layer**: A new slim-scale detection layer is added to refine bounding box predictions, ensuring that player localization is precise, even in scenes with fast movement and frequent changes in direction. This layer improves the model's capability to adapt to player movements and is particularly useful in sports scenarios where players frequently shift positions within the frame.

Key Findings

The upgraded YOLOv5 model demonstrated substantial improvements in both accuracy and speed, positioning it as a viable solution for real-time sports analytics:

- **Enhanced Performance**: In the authors' ablation study, mAP@0.5 rose from 0.81 (baseline YOLOv5n) to 0.89, with precision up from 0.83 to 0.91 and recall from 0.79 to 0.90. Notably, the stricter mAP@0.5:0.95 stayed flat (0.62 vs 0.61), so the gains came from finding more objects rather than drawing tighter boxes.

- **Improved Processing Speed**: Computational cost fell from 4.2 to 2.3 GFLOPs, mainly through the GhostNet backbone, which lowers latency and makes live-broadcast use more realistic.

- **Versatile Application in Sports Broadcasting**: The model's adaptability to varying lighting conditions and the capability to handle minor occlusions make it ideal for sports broadcasting, where real-time analysis and player identification are critical. These improvements demonstrate the model's applicability not only in recording scenarios but also in live settings, where timely data is essential.

Limitations

While the upgraded YOLOv5 model addresses several challenges, certain limitations remain, particularly related to occlusion and crowded scenes:

- **Handling Severe Occlusions**: Despite the use of multi-scale feature extraction and the GhostNet backbone, the model still encounters difficulties when players are severely occluded by others. This limitation affects the model's ability to accurately track individual players in crowded or overlapping conditions, a common issue in team sports with high player density in certain field areas.

- **Distinguishing Overlapping Players**: In situations where players are in close proximity or partially overlap, the model struggles with accurately distinguishing them. This issue can lead to errors in player identification and tracking, impacting the quality of data for analytics and reporting.

- **Future Work Suggestions**: The paper suggests exploring additional occlusion-handling techniques in future studies. Potential solutions could include integrating temporal tracking mechanisms or utilizing depth data, which could enhance the model's capacity to differentiate players in crowded scenarios.

Comparative Analysis

Model Complexity:

The upgraded YOLOv5 model (Paper 3) is the most sophisticated, combining multi-scale pooling, a GhostNet backbone and a modified detection head. The CNN-FPN model (Paper 1) is deliberately compact and suited to portable devices. The OpenCV approach (Paper 2) is the simplest and cheapest, but relies on classical tracking rather than learned detection.

Performance and Application Scope:

Papers 1 and 3 both report strong detection accuracy (0.915 AP and 0.89 mAP@0.5 respectively), although on different datasets, so the figures are not directly comparable. Paper 3 is the only one that detects the ball as well as players. The OpenCV model is aimed at measuring player movement (speed, distance) rather than detection accuracy, and suits smaller-scale or controlled settings.

Real-Time Applicability:

Both deep-learning models are built for real-time use: Paper 1 through a small parameter count, Paper 3 through reduced GFLOPs. The OpenCV pipeline can also run in real time once set up, but needs a person to manually select each player at the start, which limits it to short clips.

Occlusion Handling

Only the YOLOv5 model explicitly targets occlusion, and its authors still list heavily occluded players in crowded scenes as an open problem. Paper 1 reports reduced accuracy on small and partly hidden players, and the OpenCV tracker loses players in cluttered scenes.

Trends and Challenges

Trends:

- **Real-Time Processing**: There is a growing demand for real-time ML models in sports, evident from the focus on optimized architectures and feature extraction in the YOLOv5 model.
- **Lightweight Architectures**: Portable, lightweight models like the CNN in Paper 1 show an increasing focus on efficient, device-compatible ML applications in sports.
- **Cost-Effective Solutions**: The use of OpenCV demonstrates the trend towards affordable, scalable solutions for player tracking, especially in environments without high-tech infrastructure.

Challenges:

- **Occlusions and Overlapping Objects**: A common issue across the papers is the difficulty in detecting players during occlusions or overlapping. YOLOv5 enhancements address this, yet it remains a limitation.
- **Scalability in Dynamic Environments**: The OpenCV model does not scale because every player must be selected by hand, while the deep-learning models depend on large, varied training data to generalise to new stadiums, kits and camera angles.
- **Reliance on High-Quality Input**: The OpenCV-based model's accuracy is highly dependent on video quality, indicating that advances in low-resolution detection are still needed.
- **Real-Time Constraints**: Real-time performance is achievable for all three approaches, but each trades something for it: model size and accuracy for the deep-learning models, and manual setup for the OpenCV tracker.

Future Directions

- **Enhanced Occlusion Handling**: Future work could focus on hybrid models combining optical flow with deep learning to improve occlusion handling, especially in crowded scenes.
- **Resource-Efficient Architectures**: For real-time performance, future research may explore lighter, more efficient architectures that still maintain detection accuracy, suitable for deployment on portable devices.
- **Improving Low-Resolution Detection**: Developing models capable of accurate player detection from low-resolution or lower-quality video sources could broaden the application scope of ML in sports analytics.
- **Automated Segmentation in Tracking Models**: Integrating automated segmentation techniques in models like OpenCV-based tracking can improve scalability in dynamic, real-time environments.

How This Review Shaped My Project

Model choice: Papers 1 and 3 both point to compact, single-pass detectors as the practical route to real-time football analytics. I therefore used the YOLO family: Roboflow 3.0 for the first version and an Ultralytics YOLOv8-nano model, written and trained in Python, for the final version.

Separate classes: Like Paper 3, I detect the ball as its own class, and I also separate goalkeepers and referees from outfield players. This makes the output directly usable for later analysis (teams, possession).
Small objects: Every paper flags small and occluded objects as the weak spot. I expected the ball, which is only a few pixels wide in broadcast frames, to be the hardest class, and I report it separately rather than hiding it inside the overall average.
From detection to insight: Paper 2 shows the value of turning positions into performance metrics. I extend the detector with a simple analytics layer: jersey-colour clustering to split players into teams, and a nearest-player-to-ball rule to estimate possession.

Conclusion

This literature survey highlights the growing role of ML in football player detection and tracking, showcasing advancements and limitations in three key approaches. The YOLOv5-based model excels in real-time performance and complex detection tasks, the CNN model offers a lightweight alternative for simpler applications, and OpenCV tracking provides a cost-effective solution for smaller-scale use cases. Each model shows promise for improving sports analytics but faces challenges in handling occlusions, maintaining efficiency, and scaling to dynamic environments. Future research in these areas will likely focus on creating more versatile, resource-efficient models to meet the needs of diverse applications in sports analysis and live broadcasting.

References

1. Wang, Tianyi & Li, Tongyan. (2022). Deep Learning-Based Football Player Detection in Videos. Computational Intelligence and Neuroscience. 2022. 1-8. 10.1155/2022/3540642.
2. Merzah, B.M., Croock, M.S., Rashid, A.N. (2024). Football player tracking and performance analysis using the OpenCV library. Mathematical Modelling of Engineering Problems, Vol. 11, No. 1, pp. 123-132. https://doi.org/10.18280/mmep.110113
3. Zhao, Keyan. (2024). Enhancing the Performance and Accuracy in Real-Time Football and Player Detection Using Upgraded YOLOv5 Architecture. International Journal of Computational Intelligence Systems. 17. 10.1007/s44196-024-00565-x.