



Highest Occurring Element in an Array

Given an array **nums** of n integers, find the most frequent element in it i.e., the element that occurs the maximum number of times. If there are multiple elements that appear a maximum number of times, find the smallest of them.

[1, 2, 2, 3, 3, 3]

1 \rightarrow 1 time
2 \rightarrow 2 times
3 \rightarrow 3 times
 \rightarrow 3

[4, 4, 5, 5, 6]

4 \rightarrow 2 times
5 \rightarrow 2 times

\Rightarrow 4

Constraints:

- $1 \leq n \leq 10^5$
- $1 \leq \text{nums}[i] \leq 10^4$

Brute Force \rightarrow

[4, 4, 5, 5, 6, 3, 5]

maxCount = 0
el = -1
2 \rightarrow 3
4 \rightarrow 5
 \Rightarrow 5

count = 0

$(10^4 + 1)$
max+1
0 1 2 3 4 5 6 7
vis[] = [0, 0, 1, 1, 1, 1, 0, 0]
 $\downarrow \downarrow \downarrow \downarrow$

int func(arr)

vis[] = [10⁴+1]

TC $\rightarrow O(n^2)$

SC $\rightarrow O(10^4)$

[1, 2, 3, 4, 5]

for (0 \rightarrow n-1) cnt = 0

if (vis[arr[i]] == 0)

vis[arr[i]] = 1

for (j \rightarrow 0 \rightarrow n-1)

if (arr[i] == arr[j])

cnt++

3

3

if (cnt > maxCount)

maxCount = cnt

el = arr[i]

else if (cnt == maxCount)

el = Math.min(el, arr[i])

3

3

Optimised Solution →

arr[] = [4, 4, 5, 5, 6, 2, 3, 5]

TC → $O(N) + O(N)$
+ $O(N)$

hash[] =

0	1	2	3	4	5	6
0	0	0	0	0	0	0
		1	1	2	2	1
				2	2	
				3		

TC → $3 \times O(N)$

SC → $O(\text{max of array})$

for (0 → n-1) {
hash[arr[i]]++

3

maxCount = 0
el = 0

for (0 → n-1) {

if (hash[i] > maxCount) {
maxCount = hash[i]

el = i

3

3

maxCount = 2
el = 4

[4, 4, 5, 5, 6]

0	1	2	3	4	5	6
0	0	0	0	2	2	1

Second Highest Occurring Element in an Array


Given an array of n integers, find the second most frequent element in it.

If there are multiple elements that appear second most frequent times, find the smallest of them.

If second most frequent element does not exist return -1.

Constraints:

- $1 \leq n \leq 10^5$
- $1 \leq \text{nums}[i] \leq 10^4$



Brute Force

$[4, 4, 5, 5, 6, 7, 5]$ $vis = [0, 1, 0, 1, 1, 1, 1]$
 $maxCount = 0 \rightarrow 2 \rightarrow 3$ $secondMaxCount = 0 \rightarrow 2$
 $el = -1 \rightarrow 4 \rightarrow 5$ $secondEl = -1 \rightarrow 4$
 $Count = 0 \rightarrow 2 \rightarrow 3 + 1$

$\Rightarrow 4$
 $[1, 2, 3, 4, 5]$
 $int func(arr)$

$visited[] = [10^4]$
 $for (i \rightarrow 0 \rightarrow n-1)$
 $if (visited[arr[i]] == 0)$
 $cnt++$

$for (j \rightarrow 0 \rightarrow n-1)$
 $if (arr[i] == arr[j])$
 $count++$

TC $\Rightarrow O(N^2)$
SC $\Rightarrow O(\underline{10^4})$

if (cnt > maxCount) {
 secondMaxCount = maxCount
 second EP = el
 maxCount = cnt
 el = arr[i]

} else if (cnt == maxCount) {
 el = Math.min(el, arr[i])

} else if (cnt > secondMaxCount) {
 secondMaxCount = cnt
 second EP = arr[i]

} else if (cnt == secondMaxCount) {
 second EP = Math.min(second EP, arr[i])

}
return second EP

Optimised →

[4, 4, 5, 5, 6, 7, 5] $\text{max} = \text{MAX}$
 $\text{arr} [0 \rightarrow n-1]$

1. Find max in arr →

$\text{max} = \text{Math.max}(\text{max}, \text{arr}[i])$

2. Create hash arr with size
max + 1

hash [] = [max + 1]

3. Run loop over arr &
fill hash.

[4, 4, 3, 3, 1, 2, 3]

⇒

hash =

0	1	2	3	4
0	0	0	0	0

1 7 2 1

0	1	2	3	4
0	4	1	3	2

↑ ↑ ↑ ↑ ↑

4. Loop over hash arr \Rightarrow

max Count \Rightarrow ~~2~~ ~~3~~ ~~3~~ Second Max Count \Rightarrow ~~1~~ ~~2~~ ~~2~~
d \Rightarrow ~~1~~ ~~3~~ ~~3~~ Second El \Rightarrow ~~1~~ ~~2~~ ~~2~~ ~~4~~

\Rightarrow (4)

```
int func(arr)
```

```
max = MIN_VALUE
```

```
for (i  $\rightarrow$  0  $\rightarrow$  n-1)
```

```
max = Math.max(max, arr[i])
```

```
}
```

```
hash[] = [max+1]
```

```
for (i  $\rightarrow$  0  $\rightarrow$  n-1)
```

```
hash[arr[i]]++
```

maxCount = 0

el = -1

secondMaxCount = 0

secondEl = -1

for (i → 0 → n-1)

if (hash[i] > maxCount) {

secondMaxCount = maxCount

secondEl = el

maxCount = hash[i]

el = i

} else if (hash[i] > secondMaxCount

&& hash[i] < maxCount)

secondMaxCount = hash[i]

secondEl = i

}

TC → $O(N) + O(N) + O(N)$

→ $3 * O(N)$

SC → $O(\text{max element of array})$

return secondEl

Today's Motivation

“You have the right to perform your prescribed duty, but you are not entitled to the fruits of your actions.”

3005. Count Elements With Maximum Frequency

Easy Topics Companies Hint

You are given an array `nums` consisting of **positive** integers.

Return the **total frequencies** of elements in `nums` such that those elements all have the **maximum** frequency.

The **frequency** of an element is the number of occurrences of that element in the array.

Example 1:

Input: `nums = [1,2,2,3,1,4]`

Output: 4

Explanation: The elements 1 and 2 have a frequency of 2 which is the maximum frequency in the array. So the number of elements in the array with maximum frequency is 4.

Example 2:

Input: `nums = [1,2,3,4,5]`

Output: 5

Explanation: All elements of the array have a frequency of 1 which is the maximum. So the number of elements in the array with maximum frequency is 5.

1 → 2
2 → 2
3 → 1
4 → 1

2 + 2 → 4

