


# 1 - What are hooks

## What are hooks

Hooks are a feature introduced in **React 16.8** that allow you to use state and other React features without writing a class. They are functions that let you "hook into" React state and lifecycle features from function components.

## State



### ▼ Functional

```

import React, { useState } from 'react';

function MyComponent() {
  const [count, setCount] = useState(0);

  const incrementCount = () => {
    setCount(count + 1);
  };

  return (
    <div>
      <p>{count}</p>
      <button onClick={incrementCount}>Increment</button>
    </div>
  );
}
```

Copy

```

    </div>
  );
}

```

## ▼ Class Based

```

class MyComponent extends React.Component {
  constructor(props) {
    super(props);
    this.state = { count: 0 };
  }

  incrementCount = () => {
    this.setState({ count: this.state.count + 1 });
  }

  render() {
    return (
      <div>
        <p>{this.state.count}</p>
        <button onClick={this.incrementCount}>Increment</button>
      </div>
    );
  }
}

```

Copy

## Lifecycle events

Class based components

```

1
2 class MyComponent extends React.Component {
3   componentDidMount() {
4     // Perform setup or data fetching here
5   }
6
7   componentWillUnmount() {
8     // Clean up (e.g., remove event listeners or cancel subscriptions)
9   }
10
11   render() {
12     // Render UI
13   }
14 }

```

Functional components

```

1
2 import React, { useState, useEffect } from 'react';
3
4 function MyComponent() {
5   useEffect(() => {
6     // Perform setup or data fetching here
7   });
8
9   return () => {
10     // Cleanup code (similar to componentWillUnmount)
11   };
12 }, []);
13
14 // Render UI
15 }

```

## ▼ Functional

```
import React, { useState, useEffect } from 'react';

function MyComponent() {
  useEffect(() => {
    // Perform setup or data fetching here

    return () => {
      // Cleanup code (similar to componentWillUnmount)
    };
  }, []);

  // Render UI
}
```

Copy

## ▼ Class based

```
class MyComponent extends React.Component {
  componentDidMount() {
    // Perform setup or data fetching here
  }

  componentWillUnmount() {
    // Clean up (e.g., remove event listeners or cancel subscription)
  }

  render() {
    // Render UI
  }
}
```

Copy

## ▼ Functional solution

```
import React, { useEffect, useState } from 'react'
import './App.css'

function App() {
  const [render, setRender] = useState(true);

  useEffect(() => {
    setInterval(() => {
```

Copy

```
        setRender(r => !r);
      }, 5000)
    }, []);

    return (
      <>
        {render ? <MyComponent /> : <div></div>}
      </>
    )
  }
}

function MyComponent() {
  useEffect(() => {
    console.error("component mounted");

    return () => {
      console.log("component unmounted");
    };
  }, []);

  return <div>
    From inside my component
  </div>
}

export default App
```

Until now we've seen some commonly used hooks in React-

1. useState
2. useEffect
3. useMemo
4. useCallback

These hooks are provided to you by the **React** library.

## 2 - What are custom hooks

**Hooks** that you create yourself, so other people can use them are called custom hooks.

A **custom hook** is effectively a function, but with the following properties -

1. Uses another hook internally (useState, useEffect, another custom hook)
2. Starts with **use**

A few good examples of this can be

1. Data fetching hooks
2. Browser functionality related hooks - **useOnlineStatus** , **useWindowSize**, **useMousePosition**
3. Performance/Timer based - **useInterval**, **useDebounce**

## 3 - Data fetching hooks

Data fetching hooks can be used to encapsulate all the logic to fetch the data from your backend

For example, look at the following code-

```
import { useEffect, useState } from 'react'
import axios from 'axios'

function App() {
  const [todos, setTodos] = useState([])


  useEffect(() => {
    axios.get("https://sum-server.100xdevs.com/todos")
      .then(res => {
        setTodos(res.data.todos);
      })
  }, [])

  return (
    <>
      {todos.map(todo => <Track todo={todo} />)}
    </>
  )
}

function Track({ todo }) {
  return <div>
    {todo.title}
    <br />
    {todo.description}
  </div>
}

export default App
```

[Copy](#)



## Step 1 - Converting the **data fetching** bit to a custom hook

```
import { useEffect, useState } from 'react'
import axios from 'axios'

function useTodos() {
  const [todos, setTodos] = useState([])

  useEffect(() => {
    axios.get("https://sum-server.100xdevs.com/todos")
      .then(res => {
        setTodos(res.data.todos);
      })
  }, [])

  return todos;
}

function App() {
  const todos = useTodos();

  return (
```

[Copy](#)

```
    <>
      {todos.map(todo => <Track todo={todo} />)}
    </>
  )
}

function Track({ todo }) {
  return <div>
    {todo.title}
    <br />
    {todo.description}
  </div>
}

export default App
```

## Step 2 - Cleaning the hook to include a **loading** parameter

What if you want to show a loader when the data is not yet fetched from the backend?

```
import { useEffect, useState } from 'react'
import axios from 'axios'

function useTodos() {
  const [loading, setLoading] = useState(true);
  const [todos, setTodos] = useState([])

  useEffect(() => {
    axios.get("https://sum-server.100xdevs.com/todos")
      .then(res => {
        setTodos(res.data.todos);
        setLoading(false);
      })
  }, [])

  return {
    todos: todos,
    loading: loading
  }
}
```

[Copy](#)



```
    };  
  }  
  
  function App() {  
    const { todos, loading } = useTodos();  
  
    if (loading) {  
      return <div>  
        Loading...  
      </div>  
    }  
  
    return (  
      <>  
        {todos.map(todo => <Track todo={todo} />)}  
      </>  
    )  
  }  
  
  function Track({ todo }) {  
    return <div>  
      {todo.title}  
      <br />  
      {todo.description}  
    </div>  
  }  
  
  export default App
```

## Step 3 - Auto refreshing hook

What if you want to keep polling the backend every n seconds? `n` needs to be passed in as an input to the hook

```
import { useEffect, useState } from 'react'  
import axios from 'axios'  
  
function useTodos(n) {  
  const [loading, setLoading] = useState(true);  
  const [todos, setTodos] = useState([])
```

[Copy](#)

```
function getData() {
  axios.get("https://sum-server.100xdevs.com/todos")
    .then(res => {
      setTodos(res.data.todos);
      setLoading(false);
    })
}

useEffect(() => {
  setInterval(() => {
    getData();
  }, n * 1000)
  getData();
}, [n])

return {
  todos: todos,
  loading: loading
};
}

function App() {
  const { todos, loading } = useTodos(5);

  if (loading) {
    return <div>
      Loading...
    </div>
  }

  return (
    <>
      {todos.map(todo => <Track todo={todo} />)}
    </>
  )
}

function Track({ todo }) {
  return <div>
    {todo.title}
    <br />
    {todo.description}
  </div>
}
```

```
    </div>
  }

  export default App
```

### ▼ Final solution

```
import { useEffect, useState } from 'react'
import axios from 'axios'

function useTodos(n) {
  const [todos, setTodos] = useState([])
  const [loading, setLoading] = useState(true);

  useEffect(() => {
    const value = setInterval(() => {
      axios.get("https://sum-server.100xdevs.com/todos")
        .then(res => {
          setTodos(res.data.todos);
          setLoading(false);
        })
    }, n * 1000)

    axios.get("https://sum-server.100xdevs.com/todos")
      .then(res => {
        setTodos(res.data.todos);
        setLoading(false);
      })

    return () => {
      clearInterval(value)
    }
  }, [n])

  return {todos, loading};
}

function App() {
  const {todos, loading} = useTodos(10);

  if (loading) {
```

[Copy](#)

```
    return <div> loading... </div>
  }

  return (
    <>
      {todos.map(todo => <Track todo={todo} />)}
    </>
  )
}

function Track({ todo }) {
  return <div>
    {todo.title}
    <br />
    {todo.description}
  </div>
}

export default App
```

## swr - React Hooks for Data Fetching

swr is a popular React library that creates a lot of these hooks for you, and you can use it directly.

For example -

```
import useSWR from 'swr'

// const fetcher = (url) => fetch(url).then((res) => res.json());
const fetcher = async function(url) {
  const data = await fetch(url);
  const json = await data.json();
  return json;
};

function Profile() {
  const { data, error, isLoading } = useSWR('https://sum-server.100xd

  if (error) return <div>failed to load</div>
  if (isLoading) return <div>loading...</div>
```

[Copy](#)

```
    return <div>hello, you have {data.todos.length} todos!</div>  
  }
```

<https://swr.vercel.app/>

## 4 - Browser functionality related hooks

### 1. `useIsOnline` hook

Create a hook that returns true or false based on whether the user is currently online

You are given that -

1. `window.navigator.onLine` returns `true` or `false` based on whether the user is online
2. You can attach the following event listeners to listen to whether the user is online or not

```
Copy  
window.addEventListener('online', () => console.log('Became online'))  
window.addEventListener('offline', () => console.log('Became offline'))
```

#### ▼ Solution

```
Copy  
import { useEffect, useState } from 'react'  
  
function useIsOnline() {  
  const [isOnline, setIsOnline] = useState(window.navigator.onLine)  
  
  useEffect(() => {  
    window.addEventListener('online', () => setIsOnline(true));  
    window.addEventListener('offline', () => setIsOnline(false));  
  })  
}
```

```
    }, [])

    return isOnline;
  }

  function App() {
    const isOnline = useIsOnline(5);


    return (
      <>
        {isOnline ? "You are online yay!" : "You are not online"}
      </>
    )
  }


  export default App
```

## 2. **useMousePointer** hook

Create a hook that returns you the current mouse pointer position.

The final react app that uses it looks like this





You are given that

```
Copy
window.addEventListener('mousemove', handleMouseMove),
```

will trigger the `handleMouseMove` function anytime the mouse pointer is moved.

### ▼ Solution

```
Copy
import { useEffect, useState } from 'react'

const useMousePointer = () => {
  const [position, setPosition] = useState({ x: 0, y: 0 });

  const handleMouseMove = (e) => {
    setPosition({ x: e.clientX, y: e.clientY });
  };

  useEffect(() => {
    window.addEventListener('mousemove', handleMouseMove);
    return () => {
      window.removeEventListener('mousemove', handleMouseMove);
    };
  }, []);

  return position;
};

function App() {
  const mousePointer = useMousePointer();

  return (
    <>
      Your mouse position is {mousePointer.x} {mousePointer.y}
    </>
  )
}
```

```
export default App
```

## 5 - Performance/Timer based

### 1. setInterval


Create a hook that runs a certain callback function every n seconds.

You have to implement `useInterval` which is being used in the code below -

```
import { useEffect, useState } from 'react';  
  
function App() {  
  const [count, setCount] = useState(0);  
  
  useInterval(() => {  
    setCount(c => c + 1);  
  }, 1000)  
  
  return (  
    <>  
      Timer is at {count}  
    </>  
  )  
}  
  
export default App
```

Final app should look like this





### ▼ Solution

```
const useInterval = (callback, delay) => {  
  useEffect(() => {  
    const intervalId = setInterval(callback, delay);  
  
    return () => clearInterval(intervalId);  
  }, [callback, delay]);  
};
```

[Copy](#)

## 2. useDebounce

Create a hook that debounces a value given

1. The value that needs to be debounced
2. The interval at which the value should be debounced.

```
import React, { useState } from 'react';  
import useDebounce from './useDebounce';  
  
const SearchBar = () => {  
  const [inputValue, setInputValue] = useState('');  
  const debouncedValue = useDebounce(inputValue, 500); // 500 millise  
  
  // Use the debouncedValue in your component logic, e.g., trigger a
```

[Copy](#)

```
return (  
  <input  
    type="text"  
    value={inputValue}  
    onChange={(e) => setInputValue(e.target.value)}  
    placeholder="Search..."  
  />  
);  
};  
  
export default SearchBar;
```

### ▼ Solution

```
import { useState, useEffect } from 'react';  
  
const useDebounce = (value, delay) => {  
  // State to store the debounced value  
  const [debouncedValue, setDebouncedValue] = useState(value);  
  
  useEffect(() => {  
    // Set up a timer to update the debounced value after the spec:  
    const timerId = setTimeout(() => {  
      setDebouncedValue(value);  
    }, delay);  
  
    // Clean up the timer if the value changes before the delay has  
    return () => clearTimeout(timerId);  
  }, [value, delay]);  
  
  return debouncedValue;  
};
```

[Copy](#)

