




Authentication 1 of 8

What is authentication?

Authentication is the process of letting users signup/signin into websites via **username** / **password** or using SSO (single sign on)

 Acme Inc


Login

Create an account

Enter your email below to create your account

Sign In with Email

OR CONTINUE WITH

 GitHub

By clicking continue, you agree to our [Terms of Service](#) and [Privacy Policy](#).


"This library has saved me countless hours of work and helped me deliver stunning designs to my clients faster than ever before."

Sofia Davis




Authentication using jwt + localstorage


Signup



Signin



Auth requests



Authentication using cookies (Part 1)

What are cookies

Cookies in web development are small pieces of data sent from a website and stored on the user's computer by the user's web browser while the user is browsing. They are designed to be a reliable mechanism for websites to remember things (very similar to local storage)

1. **Session Management:** Cookies allow websites to identify users and track their individual session states across multiple pages or visits.
2. **Personalization:** Websites use cookies to personalize content and ads. For instance, cookies might store information about a user's preferences, allowing the site to tailor content or advertisements to those interests.
3. **Tracking:** Cookies can track users across websites, providing insights into browsing behavior. This information can be used for analytics purposes, to improve website functionality, or for advertising targeting.
4. **Security:** Secure cookies can be used to enhance the security of a website by ensuring that the transmission of information is only done over an encrypted connection, helping to prevent unauthorized access to user data.

We will be focussing on point 4

Why not local storage?

Cookies and LocalStorage both provide ways to store data on the client-side, but they serve different purposes and have different characteristics.

to the website (by the browser) (you don't have to explicitly add a header to the fetch call)

This point becomes super important in Next.js, we'll see later why

Authentication 1 of 8


ib.com/100xdevs-cohort-2/paytm/blob/complete-solution/frontend/src/pages/SendMoney.jsx#L45


```
axios.post("http://localhost:3000/api/v1/account/transfer", {
  to: id,
  amount
}, {
  headers: {
    Authorization: "Bearer " + localStorage.getItem("token")
  }
})
```

1. Cookies can have an expiry attached to them
2. Cookies can be restricted to only `https` and to certain `domains`


Authentication with cookies (Part 2)

Signup





Auth endpoints



You don't need to explicitly set the **cookie** header in the browser. It's automatically set by the browser in every request

Properties of cookies

Types of cookies

1. Persistent – Stay even if u close the window
2. Session – Go away after the window closes
3. **Secure** – Sent only over secure, encrypted connections (HTTPS).

- **HttpOnly** – cannot be accessed by client side scripts

- **SameSite** – Ensures cookies are not sent on cross origin requests



Authentication 1 of 8

2. Lax – Only GET requests and on **top level navigation**

3. None

Ref – <https://portswigger.net/web-security/csrf/bypassing-samesite-restrictions#:~:text=SameSite is a browser security,leaks%2C and some CORS exploits.>

- **Domains** – You can also specify what all domains should the cookie be sent from

CSRF attacks

Cross site request forgery attacks were super common because of cookies and hence the **SameSite** attribute was introduced

Let's see a few cases

SameSite: none

SameSite: Strict

But there's a problem –

SameSite: Lax

Example in express (Backend)

1. Initialize an empty TS project

```
npm init -y  
npx tsc --init
```



1. Update rootDir and outDir

1. Add required libraries

```
import express from "express";
import cookieParser from "cookie-parser";
import cors from "cors";
import jwt, { JwtPayload } from "jsonwebtoken";
import path from "path";
```

1. Initialize express app, add middlewares

```
const app = express();
app.use(cookieParser());
app.use(express.json());
app.use(cors({
  credentials: true,
  origin: "http://localhost:5173"
}));
```

1. Add a dummy signin endpoint

```
app.post("/signin", (req, res) => {
  const email = req.body.email;
  const password = req.body.password;
  // do db validations, fetch id of user from db
  const token = jwt.sign({
    id: 1
  }, JWT_SECRET);
  res.cookie("token", token);
  res.send("Logged in!");
});
```

1. Add a protected backend route

```
app.get("/user", (req, res) => {
  const token = req.cookies.token;
  const decoded = jwt.verify(token, JWT_SECRET) as JwtPayload;

  itabase

  userId: decoded.id
});
```

```
  })
```

Authentication 1 of 8

1. Add a logout route

```
app.post("/logout", (req, res) => {  
  res.cookie("token", "ads");  
  res.json({  
    message: "Logged out!"  
  })  
});
```

1. Listen on port 3000

```
app.listen(3000);
```

Code - <https://github.com/100xdevs-cohort-2/week-16-auth-1>

Frontend in React

- Initialize an empty react project
- Add a **signin** page

```
import { useState } from "react"  
import { BACKEND_URL } from "../config"  
import axios from "axios"  
  
export const Signin = () => {  
  const [username, setUsername] = useState("")  
  const [password, setPassword] = useState("")
```

```
    <input onChange={(e) => {
```



```

      setUsername(e.target.value);
    } type="text" placeholder="username" />
  Authentication 1 of 8
  {e} => {
    setPassword(e.target.value);
  } type="password" placeholder="password" />
  <button onClick={async () => {
    await axios.post(`${BACKEND_URL}/signin`, {
      username,
      password
    }, {
      withCredentials: true,
    });
    alert("you are logged in")
  }}>Submit</button>
</div>
}

```

- Add a **user** page

```

import axios from "axios";
import { useEffect, useState } from "react"
import { BACKEND_URL } from "../config";

export const User = () => {
  const [userData, setUserData] = useState();

  useEffect(() => {
    axios.get(`${BACKEND_URL}/user`, {
      withCredentials: true,
    })
      .then(res => {
        setUserData(res.data);
      })
  }, []);

  return <div>
    You're id is {userData?.userId}
    <br /><br />
    <button onClick={() => {
      axios.post(`${BACKEND_URL}/logout`, {}, {
        withCredentials: true,
      })
    }}>Logout</button>
  </div>

```

- Add routing

Authentication 1 of 8

```
import './App.css'

import { BrowserRouter, Route, Routes } from "react-router-dom";
import { Signup } from './components/Signup';
import { Signin } from './components/Signin';
import { User } from './components/User';

function App() {
  return (
    <BrowserRouter>
      <Routes>
        <Route path={"/signup"} element={<Signup />} />
        <Route path={"/signin"} element={<Signin />} />
        <Route path={"/user"} element={<User />} />
      </Routes>
    </BrowserRouter>
  )
}

export default App
```

Code - <https://github.com/100xdevs-cohort-2/week-16-auth-1>

Frontend from express

1. Add an index.html file in src folder of backend

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Login Page</title>
  <script src="https://cdn.isdelivr.net/npm/axios/dist/axios.min.js"></script>
```

```

<input type="text" placeholder="username" />
Authentication 1 of 8 <input type="password" placeholder="password" />
<button id="loginButton">Submit</button>
<button id="logoutButton">Logout</button>
<div id="userData"></div>

```

```
<script>
```

```
document.getElementById('loginButton').addEventListener('click', async () => {
  const username = document.getElementById('username').value;
  const password = document.getElementById('password').value;
```

```


  try {
    await axios.post(`/signin`, {
      username,
      password
    });
    alert("You are logged in");
  } catch (error) {
    console.error('Login failed:', error);
    alert("Login failed");
  }
});
```

```
document.getElementById('logoutButton').addEventListener('click', () => {
  axios.post(`/logout`, {}, {
    withCredentials: true,
  }).then(() => {
    console.log('Logged out successfully.');
```

```
  }).catch(error => {
    console.error('Logout failed:', error);
  });
});

function fetchUserData() {
  axios.get(`/user`, {
    withCredentials: true,
  }).then(response => {
    const userData = response.data;
    displayUserData(userData);
  }).catch(error => {
    console.error('Failed to fetch user data:', error);
  });
},
```

```
function displayUserData(userData) {
```



```
const userDataDiv = document.getElementById('userData');
// - . . . . . 'mes userData contains a 'name' and 'email'. Adapt based c
Authentication 1 of 8 <script>
  const html = `<p>Your id is: ${userData.userId}</p>`;
}
fetchUserData();
</script>

</body>
</html>
```

1. Add a route that sends this html file



```
app.get("/", (req, res) => {
  res.sendFile(path.join(__dirname, "../src/index.html"))
})
```

1. Remove **credentials** from cors



```
app.use(cors());
```

Link - <https://github.com/100xdevs-cohort-2/week-16-auth-1>