```
Basic Networking Commands:
```````````````````````````
1. To check IP address:
ip -br -c a
ip -br -c -4 a
ip -br -c -6 a

2. To check gateway's IP:
route -n

Remote Management:
``````````````````
OpenSSH (Secure Shell): To access remote machines on CLI.
Port: 22/tcp
Its a UNIX based protocol.

How to access remote machine using SSH:

# ssh remoteusername@x.x.x.x

NOTE: By default ROOT use is blocked to access via SSH.


On that remote host, how to check the connected machines via SSH:

# who
kiki pts/1 2026-09-05 10:49 (192.168.206.1)

# lsof -i:22
sshd    3389 kiki    4u  IPv4  38677      0t0  TCP localhost.localdomain:ssh->192.168.206.1:52472
(ESTABLISHED)

# kill -9 3389









---------------------------------
# ssh kiki@192.168.206.147
kiki@localhost:~$ touch filename


# ssh kiki@192.168.206.147 "cmd"
---------------------------------
Via SSH you can share files between servers/machines:

Secure Copy
```````````
Remote to Local:
````````````````
# scp -r kiki@192.168.206.147:/home/kiki/server.txt .

Local to Remote:
````````````````
# scp -r client.txt kiki@192.168.206.147:/home/kiki/


How to allow ROOT user to access remotely:
```
```

```
````````````````````````````````````````
On Server:
``````````
# vim /etc/ssh/sshd_config

Go to & Uncomment it & change
#PermitRootLogin prohibit-password
        |
        \/
PermitRootLogin yes

:wq

After save & quit, you must restart ssh service/daemon:

To manage the services/daemon, the command is `systemctl`

# systemctl restart sshd
# systemctl status sshd
# systemctl is-active sshd

On Client:
``````````
ssh root@192.168.206.147
```
```