```
SHARED HOSTING:
```````````````
Shared DNS: bts.army [forward zone]

vim /etc/named.conf

Go to end of file and add

zone "bts.army" IN {
                type master;
                file "for.bts.army";
};

:wq

cd /var/named
vim for.bts.army
$TTL 1D
@   IN SOA master.itiss.com. email@gmail.com. (
                                        0   ; serial
                                        1D   ; refresh
                                        1H   ; retry
                                        1W   ; expire
                                        3H)   ; minimum
                        IN   NS   master.itiss.com.
bts.army.   IN   A   192.168.206.151
www   IN   A   192.168.206.151

:wq

systemctl restart named
host -t a bts.army
host -t a www.bts.army

Step 3 – Managing the Apache Process
````````````````````````````````````
[+] Enable user's HOME DIR as default DocumentRoot for apache web server:
``````````````````````````````````````````````````````
vim /etc/httpd/conf.d/userdir.conf

UserDir public_html

:wq
____
/var/www/html
Eg:
/home/user/public_html/index.html
/home/user1/public_html/index.html
____

useradd user
chmod 711 /home/user
mkdir /home/user/public_html
chmod 755 /home/user/public_html
cat > /home/user/public_html/index.html
<h1>WEB SERVER</h1>
chown user:user /home/user/public_html -R
```
```

```
# chmod 644 /home/user/public_html/index.html

Apache[httpd]:
[x]     1       /home/user
[rx]    5       /home/user/public_html
[r]     4       /home/user/public_html/index.html









# mkdir /etc/httpd/sites-available /etc/httpd/sites-enabled

sites-available: directory to store Apache virtual host configuration files

sites-enabled  : directory will hold symbolic links/shortcut to virtual hosts, to enable the conf
file


# vim /etc/httpd/conf/httpd.conf

Go to end of file and add

IncludeOptional sites-enabled/*.conf

:wq

# setenforce 0    # Disable SELinux


# vim /etc/httpd/sites-available/sniper.conf

<VirtualHost *:80>
    ServerName sniper.com
    ServerAlias www.sniper.com
    DocumentRoot /var/www/html/sniper.com/
    ErrorLog /var/log/httpd/sniper_error_log
    CustomLog /var/log/httpd/sniper_access_log combined
</VirtualHost>
:wq


# ln -s /etc/httpd/sites-available/sniper.conf /etc/httpd/sites-enabled/sniper.conf

ln : Link
-s : Symbolic/Soft Link
_____________________________________
config test:
# httpd -t

To confirm that we loaded the VirtualHosts:
# httpd -S
_____________________________________
# systemctl restart httpd



http://itiss.com
http://bts.army
```