squid
-------\
Squid is caching and forwarding HTTP web proxy. Which is used to speed up a web server by caching repeated requests, caching web, DNS and filtering traffic.

```
# dnf install squid -y [RHEL/CentOS]
# apt install squid -y [Debian]
```

```
# systemctl restart squid
# systemctl enable squid
```

Port : 3128

```
# firewall-cmd --zone=public --add-service=squid --permanent
# firewall-cmd --reload
```

ACL RULEs:
``````````
http_access: Allow/Deny HTTP clients (browsers) to access the HTTP port. This is the primary access control list.

http_reply_access: Allow/Deny HTTP clients (browsers) to receive the reply to their request. This further restricts permissions given by http_access.

```
# vim /etc/squid/squid.conf
```

Test the syntax of squid.conf:

```
# squid -k parse

# ls /var/log/squid
```

```
# systemctl restart squid
```

OR

```
# systemctl reload squid
```

OR

We can reload squid configuration file without restarting service:

```
# squid -k reconfigure
```

+++Allow local network

```
# vim /etc/squid/squid.conf

acl internet_allow src 192.168.206.151/24
http_access allow internet_allow
```

OR

```
acl internet_allow src 192.168.206.0/24
```
```

```
http_access allow internet_allow



++++ Block IP

acl banned1 src 172.18.90.100/32
http_access deny banned1
http_reply_access deny banned1









We will block domains such as facebook.com and youtube.com

# vim /etc/squid/squid.conf
add lines:
``````````
acl blocksite1 dstdomain .facebook.com .youtube.com
http_access deny blocksite1
```
```