```
Basic HTTP Req:
---------------
curl http://example.com

To ignore SSL/TLS cert exception:
---------------------------------
curl -k https://example.com

To forward the HTTP request based on Location Header:
-----------------------------------------------------
curl -k https://example.com -L

-L : Location Header
To verbose:
-----------
curl -k https://example.com -v

Only response header:
---------------------
curl -k https://example.com -I

Store the output/silent:
------------------------
curl -ks https://example.com -o filename
curl -ks https://example.com -o /dev/null

HTTP Req Methods: [GET, POST, PUT ...]
--------------------------------------
curl -ks https://example.com -X OPTIONS
curl -ks https://example.com -X GET

Only Status code:
-----------------
curl -ks https://example.com -X GET -o /dev/null -w "%{http_code}\n"

Only Content-Length:
--------------------
curl -ks https://example.com -X GET -o /dev/null -w "%{http_code}" "%{size_download}"

Add custom header in req:
-------------------------
curl -ks https://example.com -H "User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64; rv:89.0)
Gecko/20100101 Firefox/89.0"


HTTP Methods
------------
GET
POST
PUT
DELETE
UPDATE
PATCH
CONNECT
HEAD
TRACE
OPTIONS
LOCK
LINK
BIND
CHECKOUT
COPY
ACL
MERGE
```

```
MKACTIVIY
NOTIFY
PROPFIND
PROPPATCH
CHECKIN


HTTP Response Code:
-------------------
1XX->
        100
        101
        102
        103
        104
2XX->
        200
        201
        202
        203
        204
3XX->
        300
        301
        302
        303
        304
4XX->
        400
        401
        402
        403
        404
5XX->
        500
        501
        502
        503
        504
```