

Payntric UPI ATM QR Generate API Integration Guide

Version: 1.0

Content-Type: application/json

API Endpoint

Method: POST

Production URL

`https://api.payntric.com/api/jcentrix/v1/upiatm/qr-generate`

Authentication

Every API request must include the following HTTP headers.

Header	Required	Description
username	Yes	API Username provided by Payntric
token	Yes	API Token provided by Payntric
Content-Type	Yes	application/json

Example Headers

```
username: your_username  
token: your_api_token  
Content-Type: application/json
```

Request Body

```
{  
  "requestId": "REQ_2606221345341383",  
  "amount": 100,  
  "mobile": "6396978580",  
  "latitude": "28.620382426527208",  
  "longitude": "77.38104359407228",  
  "outletId": "6*****"  
}
```

Request Parameters

Parameter	Type	Required	Description
requestId	String	Yes	Unique transaction request ID. Must be unique for every request.
amount	Decimal	Yes	Transaction amount.
mobile	String	Yes	Customer mobile number.
latitude	String	Yes	Customer latitude.
longitude	String	Yes	Customer longitude.
outletId	String	Yes	Outlet ID provided by payntric.

Successful Response

HTTP 200

```
{
  "status": "SUCCESS",
  "statusCode": "TXN",
  "message": "QR Generated Successfully.",
  "transactionId": "UATM_586D556DBC604505",
  "requestId": "REQ_2606191656463041",
  "qrStatus": "INITIATED",
  "ipayId": "P260619165646WCYHX",
  "qrString": "upi://pay?...",
  "qrMobile": "upi://pay?...",
  "expiryDt": "2026-06-19T16:57:30",
  "qrCreatedDt": "2026-06-19T16:56:47",
  "displayExpirySec": 30,
  "amount": 100.0,
  "payableValue": 100.0,
  "transactionValue": 100.0,
  "commissionAmount": 0.0,
  "tdsAmount": 0.0,
  "netAmount": 0.0,
  "settlementStatus": "PENDING"
}
```

Success Response Parameters

Parameter	Description
status	API request status
statusCode	Response code
message	Response message
transactionId	Provider transaction ID
requestId	Request ID received from client
qrStatus	QR status (INITIATED)
ipayId	Provider IPay ID
qrString	UPI QR string used to generate QR image
qrMobile	UPI payment URI
expiryDt	QR expiry date/time
qrCreatedDt	QR creation date/time
displayExpirySec	QR validity (seconds)
amount	Requested amount
payableValue	Payable amount
transactionValue	Transaction amount
commissionAmount	Commission amount
tdsAmount	TDS amount
netAmount	Net settlement amount
settlementStatus	Settlement status

Error Responses

Merchant Not Enabled

```
{
  "status": "FAILED",
  "statusCode": "500",
  "message": "UPI-ATM not enabled for this merchant: No active provider
configured for: UPIATM_QR"
}
```

Invalid Outlet ID

```
{
  "status": "FAILED",
```

```
    "statusCode": "500",
    "message": "The X-Ipay-Outlet-Id header must be an integer."
}
```

Invalid Amount Range

```
{
  "status": "FAILED",
  "statusCode": "500",
  "message": "Amount must be between 50.0 and 50000.0"
}
```

Minimum Amount Validation

```
{
  "status": "FAILED",
  "statusCode": "500",
  "message": "Amount must be greater than 100"
}
```

System Error

```
{
  "status": "FAILED",
  "statusCode": "500",
  "message": "System Error"
}
```

Authentication Failed

```
{
  "status": "FAILED",
  "statusCode": "401",
  "message": "Invalid username or token."
}
```

Network Timeout (Client Side)

```
{
  "status": false,
  "message": "Curl Error: Connection timed out after 5000 milliseconds"
}
```

QR Status Values

Status	Description
INITIATED	QR generated successfully
PENDING	Waiting for customer payment
SUCCESS	Payment completed
FAILED	Payment failed or expired

Settlement Status

Status	Description
PENDING	Settlement pending
SUCCESS	Settlement completed

2. QR Transaction Status API

The QR Transaction Status API is used to check the current status of a previously generated QR transaction.

Endpoint

Method: POST

`https://api.payntric.com/api/jcentrix/v1/upiatm/qr-status`

Authentication

Every request must include the following HTTP headers.

Header	Required	Description
username	Yes	API Username provided by Payntric
token	Yes	API Token provided by payntric
Content-Type	Yes	application/json

Example Headers

username: your_username
token: your_api_token
Content-Type: application/json

Request Body

```
{  
  "transactionId": "UATM_CB4EDA80DE8A41A8",  
  "ipayId": "P260619175259TJQAH",  
  "requestId": "REQ_2606191752584467",  
  "outletId": "6*****"  
}
```

Request Parameters

Parameter	Type	Required	Description
transactionId	String	Yes	Transaction ID received from QR Generate API
ipayId	String	Yes	Provider IPay ID
requestId	String	Yes	Original request ID
outletId	String	Yes	Merchant Outlet ID

Successful Response

```
{  
  "status": "SUCCESS",  
  "statusCode": "TXN",  
  "message": "Cached terminal status: SUCCESS",  
  "transactionId": "UATM_CB4EDA80DE8A41A8",  
  "requestId": "REQ_2606191752584467",  
  "qrStatus": "SUCCESS",  
  "ipayId": "P260619175259TJQAH",  
  "amount": 100.0,  
  "settlementStatus": "SETTLED"  
}
```

Success Response Parameters

Parameter	Description
-----------	-------------

Parameter	Description
status	API request status
statusCode	Response code
message	Response message
transactionId	Provider transaction ID
requestId	Original request ID
qrStatus	Current QR transaction status
ipayId	Provider IPay ID
amount	Transaction amount
settlementStatus	Settlement status

Pending Response

```
{
  "status": "SUCCESS",
  "statusCode": "TXN",
  "message": "Transaction is pending",
  "transactionId": "UATM_CB4EDA80DE8A41A8",
  "requestId": "REQ_2606191752584467",
  "qrStatus": "PENDING",
  "ipayId": "P260619175259TJQAH",
  "amount": 100.0,
  "settlementStatus": "PENDING"
}
```

Failed Response

```
{
  "status": "FAILED",
  "statusCode": "500",
  "message": "Transaction Failed",
  "transactionId": "UATM_CB4EDA80DE8A41A8",
  "requestId": "REQ_2606191752584467",
  "qrStatus": "FAILED",
  "ipayId": "P260619175259TJQAH",
  "amount": 100.0,
  "settlementStatus": "FAILED"
}
```

Error Responses

Invalid Transaction Details

```
{  
  "status": "FAILED",  
  "statusCode": "404",  
  "message": "Transaction not found."  
}
```

Invalid Outlet ID

```
{  
  "status": "FAILED",  
  "statusCode": "500",  
  "message": "The X-Ipay-Outlet-Id header must be an integer."  
}
```

Authentication Failed

```
{  
  "status": "FAILED",  
  "statusCode": "401",  
  "message": "Invalid username or token."  
}
```

System Error

```
{  
  "status": "FAILED",  
  "statusCode": "500",  
  "message": "System Error"  
}
```

QR Status Values

Value	Description
INITIATED	QR has been generated successfully.
PENDING	Customer has not completed the payment.
SUCCESS	Customer payment completed successfully.

Value	Description
FAILED	Transaction failed or expired.

Settlement Status Values

Value	Description
PENDING	Settlement is pending.
SETTLED	Settlement completed successfully.
FAILED	Settlement failed.

Integration Notes

1. Call this API after generating the QR code to obtain the latest transaction status.
2. Use the **transactionId**, **ipayId**, **requestId**, and **outletId** exactly as received during QR generation.
3. Continue polling until **qrStatus = SUCCESS** or **qrStatus = FAILED**.
4. Once **settlementStatus = SETTLED**, the transaction has been successfully settled.
5. All requests must use the **POST** method.
6. Include the required authentication headers in every request.
7. Generate a unique **requestId** for each transaction.
8. Store the **transactionId** and **ipayId** for future transaction status checks.
9. Use the **qrString** or **qrMobile** value to generate and display the QR code to the customer.
10. The QR code remains valid until the **expiryDt** time.
11. Supported transaction amount range is **₹50 to ₹50,000** (subject to merchant configuration).
12. The **outletId** must be a valid outlet ID assigned by Payntric.
13. After successful QR generation, call the Transaction Status API or wait for the webhook callback to receive the final transaction status.