

# MAS 433: Cryptography

Lecture 14

Public Key Encryption

Part 1: RSA

Wu Hongjun

# Lecture Outline

- Classical ciphers
- Symmetric key encryption
- Hash function and Message Authentication Code
- **Public key encryption**
  - **RSA**
    - **Specification**
    - **Implementation**
    - **Security**
  - ElGamal
  - Message padding (OAEP)
- Digital signature
- Key establishment and management
- Introduction to other cryptographic topics

# Recommended Reading

- CTP Section 5.1 to 5.7
- HAC Section 8.1 and 8.2
- Wikipedia
  - Public key cryptosystem  
[http://en.wikipedia.org/wiki/Public-key\\_cryptography](http://en.wikipedia.org/wiki/Public-key_cryptography)
  - RSA  
<http://en.wikipedia.org/wiki/RSA>
  - Primality testing  
[http://en.wikipedia.org/wiki/Primality\\_test](http://en.wikipedia.org/wiki/Primality_test)
  - Integer factorization  
[http://en.wikipedia.org/wiki/Integer\\_factorization](http://en.wikipedia.org/wiki/Integer_factorization)

# Public Key Cryptosystem

- Symmetric key encryption
  - The same secret key is used for encryption and decryption
- How to communicate secretly if sender & receiver do not share a secret key before communication starts?
  - Common problem for large computer network
  - Public key cryptosystems can solve this problem
    - **Diffie-Hellman key exchange** (1976)
      - The first paper on public key cryptosystem
    - **Public key encryption**

# Public Key Cryptosystem



Whitfield Diffie



Martin Hellman

Diffie-Hellman Key Exchange

# Public Key Encryption

- Each receiver has two keys
  - Encryption key (called public key)
    - Everyone knows the encryption key of a receiver
    - **Everyone can encrypt a message using the public key of a receiver** and send the ciphertext to that receiver
  - Decryption key (called private key)
    - Only the receiver knows its decryption key
      - Difficult to derive the private key from public key
    - **Only the receiver can decrypt the ciphertext encrypted using its public key**

# Public Key Encryption

- Many public key encryption schemes
- RSA (1978)
  - The first public key encryption scheme
  - Based on the difficulty of integer factorization & ‘discrete logarithm’
- ElGamal (1985)
  - Based on the difficulty of discrete logarithm
    - discrete logarithm:  $g^x \bmod p = y$   
(given  $y$ , to find  $x$ )


# RSA



Ron Rivest




Adi Shamir



Leonard Adleman



# RSA



# RSA

- Key generation of each receiver:
  - Generate two distinct **large** prime numbers  $p$  and  $q$
  - Compute  $n = p \times q$
  - Compute  $\varphi(n) = (p-1) \times (q-1)$ 
    - $\varphi$  is Euler's totient function
  - Choose an integer  $e$  that is coprime to  $\varphi(n)$
  - Find  $d$  satisfying  $e \times d \equiv 1 \pmod{\varphi(n)}$

**public key:**  $e, n$

**private key:**  $d$

# RSA

- Encryption

$$c = m^e \bmod n \quad (\text{plaintext } m: 0 < m < n)$$

- Decryption

$$m = c^d \bmod n$$

# RSA

RSA's decryption recovers the message

Simple but incomplete proof:

- Euler's theorem:

Let  $a$  be a positive integer coprime to  $n$ , then

$$a^{\varphi(n)} \equiv 1 \pmod{n}$$

- RSA decryption:

$$c^d \pmod{n} = (m^e \pmod{n})^d \pmod{n}$$

$$= m^{ed} \pmod{n}$$

$$= m^{\beta\varphi(n)+1} \pmod{n}$$

If  $m$  and  $n$  are coprime, then  $m^{\beta\varphi(n)} \pmod{n} = 1$

$$\therefore c^d \pmod{n} = m$$

# RSA

RSA's decryption recovers the message

The complete proof requires the following theorem:

- Fermat's little theorem:

Let  $a$  be a positive integer coprime to a prime number  $p$ , then

$$a^{p-1} \equiv 1 \pmod{p}$$

- Chinese Remainder Theorem (special case):

If  $n_1$  and  $n_2$  are coprime,  $x < n_1 n_2$ , and  $x$  satisfies

$$x \equiv a \pmod{n_1}$$

$$x \equiv a \pmod{n_2}$$

then there is a unique solution

$$x \equiv a \pmod{n_1 n_2}$$

Brief explanation:

$$n_1 \mid (x-a)$$

$$n_2 \mid (x-a)$$

since  $n_1$  and  $n_2$  are coprime, we get

$$n_1 n_2 \mid (x-a)$$

$$\text{i.e., } x-a \pmod{n_1 n_2} = 0$$

# RSA

- RSA's decryption recovers the message  
complete proof:

Let  $x = c^d \bmod n$ ,

$$\begin{aligned}x \bmod p &= ((m^e)^d \bmod n) \bmod p \\&= (m^e)^d \bmod p \\&= m^{\beta(p-1)(q-1)+1} \bmod p\end{aligned}$$

If  $m$  and  $p$  are coprime, according to Fermat's little theorem:  $m^{p-1} \bmod p = 1$   
 $\therefore x \bmod p = m^{\beta(p-1)(q-1)+1} \bmod p = m \bmod p \quad (1)$

If  $m$  is the multiple of  $p$ , then

$$x \bmod p = m^{\beta(p-1)(q-1)+1} \bmod p = 0 = m \bmod p \quad (2)$$

From (1) and (2),  $x \equiv m \bmod p \quad (3)$

Similarly:  $x \equiv m \bmod q \quad (4)$

From (3), (4) and Chinese Remainder Theorem:

$$x = m \bmod pq = m$$

# RSA

- Example (Toy RSA):

Key generation:

- $p = 61, q = 53$
- $n = 61 \times 53 = 3233$
- $\varphi(n) = (61-1)(53-1) = 3120$
- choose public key  $e = 17$ ,  $e$  is coprime to  $\varphi(n)$
- find private key  $d = 2753$  satisfying  $e \times d \equiv 1 \pmod{\varphi(n)}$

Encryption:

If  $m = 37$ , then  $c = 37^{17} \pmod{3233} = 1350$

Decryption:

$$m = 1350^{2753} \pmod{3233} = 37$$

# RSA Implementation

- Key generation:
  - Generate two distinct large prime numbers  $p$  and  $q$
  - Compute  $n = p \times q$
  - Compute  $\varphi(n) = (p-1) \times (q-1)$ 
    - $\varphi$  is Euler's totient function
  - Choose an integer  $e$  that is coprime to  $\varphi(n)$
  - Find  $d$  satisfying  $e \times d \equiv 1 \pmod{\varphi(n)}$

- Encryption

$$c = \underline{m^e \bmod n}$$

- Decryption

$$m = \underline{c^d \bmod n}$$

1. How to find  $p$  &  $q$ ?
2. How to find  $d$ ?
3. How to compute  $(m^e \bmod n)$  and  $(c^d \bmod n)$  efficiently?



# RSA Implementation: How to find $p$ & $q$ ?

- How to find a large prime number?
  - Randomly select a large integer
  - Then test whether it is prime or not
- Questions:
  - What is the probability that a large random integer is prime?
  - How to test whether a large random integer is prime?

# RSA Implementation: How to find $p$ & $q$ ?

$\pi(x)$ : the number of primes less than or equal to a real number  $x$

- Prime Distribution Theorem

$$\lim_{x \rightarrow \infty} \frac{\pi(x)}{x / \ln(x)} = 1$$

$$\pi(x) \sim \frac{x}{\ln x}.$$

# RSA Implementation: How to find $p$ & $q$ ?

$$\pi(x) \sim \frac{x}{\ln x}$$

- A random 512-bit integer is prime with probability about

$$\frac{1}{\ln 2^{512}} \approx \frac{1}{355}$$

- A random 1024-bit integer is prime with probability about

$$\frac{1}{\ln 2^{1024}} \approx \frac{1}{710}$$

⇒ The probability that a large random integer is sufficiently large for practical applications

# RSA Implementation: How to find $p$ & $q$ ?

- Primality testing:
  - Naïve methods
  - **Probabilistic tests**
    - **Low complexity**
    - **Commonly used**
  - Fast deterministic tests

# RSA Implementation: How to find $p$ & $q$ ?

- Primality testing
  - Naïve methods
    - The simplest primality testing:
      - To test whether an integer  $n$  is prime or not, try all the integers less than or equal to  $n^{0.5}$  to check whether  $n$  is divisible by any of those integers
      - Complexity:  $O(n^{0.5})$

# RSA Implementation: How to find $p$ & $q$ ?

- Primality testing
  - Probabilistic tests
    - Fermat primality test
      - Simple, but not useful for detecting some special composite numbers
      - Useful for quick screening, then test the remaining numbers using other primality testing methods
      - Used in Perfect Good Privacy (PGP) for primality testing
    - Miller-Rabin test
      - The commonly used primality testing method
        - » Mathematica, OpenSSL, ...

# RSA Implementation: How to find $p$ & $q$ ?

- Primality testing
  - Probabilistic tests
    - Fermat primality test
      - To test whether an integer  $n$  is prime or not, choose some integer  $a$  coprime to  $n$  ( $a > 1$ ),
        - » If  $a^{n-1} \bmod n \neq 1$ , then  $n$  is composite
        - » If  $a^{n-1} \bmod n = 1$ , then  $n$  may or may not be prime
      - As more different values of  $a$  are tested, the accuracy improves
        - » But for some special composite number  $n$  (called Carmichael numbers), for all the  $a$  coprime to  $n$ ,
$$a^{n-1} \bmod n = 1$$

# RSA Implementation: How to find $p$ & $q$ ?

- Primality testing
  - Probabilistic tests
    - Miller-Rabin test

Given an integer  $n$ , write  $n - 1 = 2^r s$ , where  $s$  is odd

Choose a random integer  $a$  with  $2 \leq a \leq n - 1$

1. If  $a^s \not\equiv 1 \pmod{n}$  and  $a^{2^j s} \not\equiv -1 \pmod{n}$  for all  $0 \leq j \leq r - 1$ , then  $n$  is a composite;
2. Otherwise,  $n$  may or may not be prime

A prime can always pass through the above test (never be identified as composite).  
A composite number can be identified as probably prime with probability  $1/4$  for a random integer  $a$ . With  $N$  random distinct integers  $a$ , a composite number is identified as probably prime with probability  $2^{-2N}$



# RSA Implementation: How to find $p$ & $q$ ?

- Primality testing
  - Fast deterministic tests
    - In 2002, Agrawal, Kayal and Saxena found a new deterministic primality test (AKS), with complexity  $O((\log n)^{12})$
    - In 2005, the complexity is reduced to  $O((\log n)^6)$ . It is still much slower than probabilistic methods

# RSA Implementation: How to find $d$ ?

- Use the extended Euclidean algorithm to find  $d$  satisfying  $ed \equiv 1 \pmod{\varphi(n)}$ 
  - Euclidean algorithm
    - to find  $\gcd(a, b)$
  - extended Euclidean algorithm
    - to find  $ax + by = \gcd(a, b)$ 
      - If  $\gcd(a, b) = 1$ , then  $ax \equiv 1 \pmod{b}$ ;  $by \equiv 1 \pmod{a}$

# RSA Implementation:

## How to compute $a^x \bmod n$ efficiently?

1. Represent a  $t$  - bit exponent  $x$  in binary format as

$$x = x_{t-1}x_{t-2} \cdots x_2x_1x_0, \text{ i.e., } x = \sum_{i=0}^{t-1} x_i 2^i$$

2. Compute  $y_i = a^{2^i} \bmod n$  as

$t$  square-mod  
operations

$y_i = (y_{i-1})^2 \bmod n$ , where  $y_0 = a^{2^0} \bmod n = a$

3. Then  $a^x \bmod n$  is computed efficiently as

$$a^x \bmod n = a^{\sum_{i=0}^{t-1} x_i 2^i} \bmod n = \left( \prod_{i=0}^{t-1} a^{x_i 2^i} \right) \bmod n$$

At most  $t-1$  multiply-mod  
operations

$$= \left( \prod_{i=0}^{t-1} (a^{2^i})^{x_i} \right) \bmod n = \left( \prod_{i=0}^{t-1} y_i^{x_i} \right) \bmod n$$

# RSA Implementation:

How to compute  $a^x \bmod n$  efficiently?

- Implement the method on the previous slide as :

$y = a, z = 1$

for  $i = 0$  to  $t - 1$  do

{

if  $x_i = 1$ , then  $z = z \cdot y \bmod n$

$y = y^2 \bmod n$

}

# RSA Implementation:

How to compute  $a^x \bmod n$  efficiently?

- Square-and-multiply algorithm in the textbook:
  - Compare to the algorithm on the previous slide, the value of  $i$  decreases

$$z = 1$$

for  $i = t - 1$  downto 0 do

{

$$z = z^2 \bmod n$$

if  $x_i = 1$ , then  $z = z \cdot a \bmod n$

}

# RSA Security

## Attacks on RSA:

- **To factorize  $n$** 
  - Once  $n$  is factorized,  $d$  can be computed
  - Difficult for large  $n$
- **Other attacks**

# RSA Security: Integer Factorization

- Integer factorization
  - Here we consider only **RSA moduli**
    - Product of two primes (also called semiprimes, biprimes)
- Many integer factorization techniques
  - Trial division
  - .....
  - Dixon's random squares algorithm
    - Quadratic sieve
    - General number field sieve

# RSA Security: Integer Factorization

- Trial division
  - To factorize integer  $n$ , try all the integers less than or equal to  $n^{0.5}$  to check whether  $n$  is divisible
  - Complexity:  $O(n^{0.5})$



# RSA Security: Integer Factorization

- Dixon's random squares algorithm
  - Basic idea: (Fermat)
    - used in many factorization algorithms

Suppose that we can find  $x \not\equiv \pm y \pmod{n}$  such that

$x^2 \equiv y^2 \pmod{n}$ , then  $n \mid (x - y)(x + y)$ .

But neither  $(x - y)$  or  $(x + y)$  is divisible by  $n$  since  $x \not\equiv \pm y \pmod{n}$ .

Therefore  $\gcd(x - y, n)$  is a non - trivial factor of  $n$

$\gcd(x + y, n)$  is another non - trivial factor of  $n$

Example :  $10^2 \equiv 32^2 \pmod{77}$

$$\gcd(10 + 32, 77) = 7, \gcd(10 - 32, 77) = 11$$

# RSA Security: Integer Factorization

- Dixon's random squares algorithm (contd.)

## Smooth number

- An integer which factors completely into small prime numbers
- A positive integer is called ***B*-smooth** if none of its prime factors is greater than  $B$ .
- Example:

$$1620 = 2^2 \times 3^4 \times 5$$

1620 is 5-smooth since none of its prime factors is greater than 5.

# RSA Security: Integer Factorization

- Dixon's random squares algorithm (contd.)

1) Let  $m = \lfloor \sqrt{n} \rfloor$ , define a function  $Q(x) = (m + x)^2 - n$    $Q(x) \approx \alpha \sqrt{n}$

2) define the value of  $B$  (it depends on the size of  $n$ , normally it cannot be than  $2^{50}$ )

Denote those primes  $\leq B$  as  $\{p_1, p_2, \dots, p_t\} = \{-1, 2, 3, 5, \dots, p_t\}$

3) Randomly select small (positive or negative) integers  $x$ .

Keep those integers satisfying that  $Q(x)$  is  $B$ -smooth.

Denote those integers as  $x_1, x_2, \dots, x_\mu$

$$Q(x_i) = p_1^{e_{i,1}} \times p_2^{e_{i,2}} \times p_3^{e_{i,3}} \times \dots \times p_t^{e_{i,t}}$$

# RSA Security: Integer Factorization

- Dixon's random squares algorithm (contd.)

4) With  $t$  such  $x_i$ , by solving binary linear equations, we can find a subset  $A \subset \{1, 2, 3, 4, 5, \dots, t\}$ , so that  $\sum_{i \in A} e_{i,j}$  is even for all the values of  $j$  ( $1 \leq j \leq t$ )

5) Then 
$$\prod_{i \in A} Q(x_i) = p_1^{\sum_{i \in A} e_{i,1}} \times p_2^{\sum_{i \in A} e_{i,2}} \times p_3^{\sum_{i \in A} e_{i,3}} \times \dots \times p_t^{\sum_{i \in A} e_{i,t}} = y^2$$

6) Thus 
$$\prod_{i \in A} Q(x_i) \equiv y^2 \pmod{n}$$

$$\left( \prod_{i \in A} (m + x_i) \right)^2 \equiv y^2 \pmod{n}$$

$$z^2 \equiv y^2 \pmod{n}$$

If  $z \not\equiv \pm y \pmod{n}$ , then  $\gcd(z - y, n)$  gives a factor of  $n$

# Example:

## Factorize

$n = 4841$

1.  $m = \lfloor \sqrt{n} \rfloor = 69, Q(x) = (m + x)^2 - n$
2. set  $B = 11$ , the factor base is  $\{-1, 2, 3, 5, 7, 11\}$
3.  $x = -8 \rightarrow Q(x) = -1120 = (-1) \times 2^5 \times 5 \times 7$   
 $x = -4 \rightarrow Q(x) = -616 = (-1) \times 2^3 \times 7 \times 11$   
 $x = -2 \rightarrow Q(x) = -352 = (-1) \times 2^5 \times 11$   
 $x = 0 \rightarrow Q(x) = -80 = (-1) \times 2^4 \times 5$   
 $x = 2 \rightarrow Q(x) = 200 = 2^3 \times 5^2$   
 $x = 3 \rightarrow Q(x) = 343 = 7^3$   
 $x = 6 \rightarrow Q(x) = 784 = 2^4 \times 7^2$
4. Find the set A as  $\{x = -4, x = -2, x = 3\}$
5.  $y^2 = Q(-4) \times Q(-2) \times Q(3) = (-1)^2 \times 2^8 \times 7^4 \times 11^2$   
 $\Rightarrow y = (-1) \times 2^4 \times 7^2 \times 11 \equiv -3783 \pmod{4841}$   
 $z = (m - 4) \times (m - 2) \times (m + 3) \equiv 3736 \pmod{4841}$   
 $\gcd(z - y, n) = \gcd(3736 + 3783, 4841) = 103$   
 $\gcd(z + y, n) = \gcd(3736 - 3783, 4841) = 47$   
 $n = 4841 = 47 \times 103$

If we use the set A  
 $\{x=6\}$ , then  
 $y=2^2 \times 7=28$   
 $z=(m+6)=75$   
 Then we get:  
 $\gcd(z-y, n) = 47$   
 $\gcd(z+y, n) = 103$

# RSA Security: Integer Factorization

- Quadratic sieve
  - Very similar to Dixon's random squares algorithm
  - But with efficient sieving method to generate smooth numbers
- General number field sieve
  - Improve the quadratic sieve
  - Convert the integer factorization problem to factorization over algebraic number field
    - so as to generate “more” smooth number

# RSA Security: Integer Factorization

- Complexities of factorization algorithms

Trial division :  $O(\sqrt{n}) \rightarrow O(e^{0.5 \ln n})$

Dixon's Random Squares Algorithm :  $O(e^{(1+O(1)) \ln n^{1/2} (\ln \ln n)^{1/2}})$

Quadratic sieve :  $O(e^{(1+O(1)) \ln n^{1/2} (\ln \ln n)^{1/2}})$

General number field sieve :  $O(e^{(1+O(1)) \ln n^{1/3} (\ln \ln n)^{2/3}})$


# RSA Security: Integer Factorization

- The size of RSA moduli  
NIST recommendation, 2007:

| <b>size of <math>n</math></b> | <b>security level</b> |
|-------------------------------|-----------------------|
| 1024-bit                      | 80 bits               |
| 2048-bit                      | 112 bits              |
| 3072-bit                      | 128 bits              |
| 7680-bit                      | 192 bits              |
| 15360-bit                     | 256 bits              |



# RSA Security: Integer Factorization

- Some RSA modulus factorization records
    - 129-digit modulus 1994 → Quadratic sieve
    - 155-digit (512-bit) modulus 1999
    - 174-digit (576-bit) modulus 2003
    - 200-digit (663-bit) modulus 2005
    - 232-digit (768-bit) modulus 2009
- 

Complexity: about 2000 CPU cores (2.2GHz) for 1 year

1024-bit modulus: when? method?

# RSA Security: Other Attacks (1)

- Trivial attacks
  - If  $p$  or  $q$  is known to the attacker  $\rightarrow$  broken
  - If  $\varphi(n)$  is known to the attacker  $\rightarrow$  broken

# RSA Security: Other Attacks (2)

- Attack on shared modulus
  - Shared modulus
    - each user is given a public key  $(e_i, n)$  and private key  $d_i$
    - They share the same modulus  $n$
  - Attack
    - Each user can factorize  $n$  easily from  $e_i$  and  $d_i$
    - Then each user can find the private keys of other users
    - How to factorize?

# RSA Security: Other Attacks (2)

- Attack on shared modulus (contd.)

- Factorize  $n$  from  $e$  and  $d$

- 1) Since  $e \cdot d \equiv 1 \pmod{\varphi(n)}$ ,

$$e \cdot d - 1 = \beta(p-1)(q-1),$$

we know that  $e \cdot d - 1$  is even

- 2) Randomly select an integer  $x$ , compute

$$y = x^{(e \cdot d - 1)/2} \pmod{n}$$

- 3) We know that  $x^{e \cdot d - 1} \pmod{n} = x^{\beta \varphi(n)} \pmod{n} = 1$  (Euler's theorem)

- 4) From 2) and 3), we know that

$$y^2 = 1 \pmod{n}$$

Thus  $\gcd(y-1, n)$  gives a factor of  $n$  if  $y \not\equiv \pm 1 \pmod{n}$

Slide 33



# RSA Security: Other Attacks (3)

- The message size is small
  - Attack

Example: A 64-bit secret  $m$  is encrypted as  $c = m^e \bmod n$  ( $n, e, d$  are huge)

With probability about 20%, a random 64-bit  $m$  can be written as  $m = m_1 m_2$ , where  $m_1, m_2 < 2^{34}$ .

Now an attacker builds two tables:

$$T_1[i] = \frac{c}{i^e} \bmod n \text{ for } 1 \leq i \leq 2^{34}$$

$$T_2[j] = j^e \bmod n \text{ for } 1 \leq j \leq 2^{34}$$

If  $T_1[i] = T_2[j]$  for some  $i$  and  $j$ , then the message  $m = i \times j$

Complexity: about  $2 \times 2^{34}$

# RSA Security: Other Attacks (4)

- The exponent  $e$  is too small

- Attack 1:

Example: if  $e = 3$ , then for small  $m$  (say,  $m < n^{1/3}$ ),

$$c = m^3 \bmod n = m^3$$

$\Rightarrow m$  can be recovered from  $c$  easily

- Attack 2:

Example: if  $e = 3$ , and  $m$  is large. The same message  $m$  is sent to 3 different receivers

$$c_1 = m^3 \bmod n_1 \quad (1)$$

$$c_2 = m^3 \bmod n_2 \quad (2)$$

$$c_3 = m^3 \bmod n_3 \quad (3)$$

From Chinese Remainder Theorem and (1), (2), (3),  $m^3 \bmod n_1 n_2 n_3$  can be obtained, i.e.,  $m^3$  becomes known.  $m$  can thus be recovered easily from  $m^3$

# RSA Security: Other Attacks (4)

- Recommended value:  $e = 65537 = 2^{16} + 1$ 
  - Encryption takes 17 modular multiplies
  - Fast encryption, but slow decryption
    - Encryption is about 80 times faster than decryption for 1024-bit  $n$
    - But RSA encryption with this  $e$  and 1024-bit  $n$  is still more than 50 times slower than AES encryption on computer;

# RSA Security: Other Attacks (5)

- How about choose small private key  $d$  to increase decryption speed?
  - In the key generation process, choose  $d$  first, then compute  $e$
  - But **the value of  $d$  must be large for security reason**
    - Brute force attack: the size of  $d$  should be more than 128 bits
    - Advanced attack:
      - If  $d < n^{0.25}$ ,  $d$  can be recovered from  $e$  and  $n$  easily (1987)
      - If  $d < n^{0.292}$ ,  $d$  can be recovered from  $e$  and  $n$  easily (1998)
      - It is conjectured that if  $d < n^{0.5}$ ,  $d$  can be recovered from  $e$  and  $n$  easily (open problem)



# RSA Security: Other Attacks (6)

- Attack on `public' encryption
  - Attacker can perform encryption of any message
  - If the entropy of the message is not large, the attacker can encrypt all the possible messages, then compare those ciphertexts with the received ciphertext, and recover the message

# RSA Security

- How to make RSA strong
  - Large modulus
    - 3072 bits for 128-bit security
    - 15360 bits for 256-bit security
  - Private key larger than  $n^{0.5}$
  - Message padding (to learn later)
    - **To introduce randomness to the plaintext  $m$**
    - To pad message  $m$  so that the length of padded message is close to that of  $n$

# RSA Applications

- Used in almost all the secure Internet communication applications
  - Public key infrastructure
  - TLS/SSL
  - Secure e-mail: PGP, Microsoft Outlook ...

# Summary

- Public key encryption
  - Allows two party to communicate secretly without sharing a secret key before communication
- RSA
  - Specifications
  - Implementation
    - Primality testing: Fermat's primality test, Miller-Rabin primality test
    - Extended Euclidean algorithm
    - Fast modular exponentiation
  - Security
    - Integer factorization
      - Dixon's Random Squares algorithm
    - Other attacks
      - Short message
      - Shared public key
      - Small public key
      - Small private key ....