

MAS 433: Cryptography

Lecture 12

Hash Function

Wu Hongjun

Lecture Outline

- Classical ciphers
- Symmetric key encryption
- Hash function and Message Authentication Code
 - Birthday attack
 - [Hash function](#)
 - Message Authentication Code
- Public key encryption
- Digital signature
- Key establishment and management
- Introduction to other cryptographic topics

Recommended Reading

- CTP Section 4.1, 4.2, 4.3
- HAC Section 9.1, 9.2, 9.3, 9.4
- Wikipedia
 - Cryptographic hash function
http://en.wikipedia.org/wiki/Cryptographic_hash_function
 - Merkle-Damgard construction
http://en.wikipedia.org/wiki/Merkle%E2%80%93Damgard_construction
 - SHA-1
<http://en.wikipedia.org/wiki/SHA-1>
 - SHA-2
<http://en.wikipedia.org/wiki/SHA-2>
 - SHA-3 competition
<http://en.wikipedia.org/wiki/SHA-3>
- Full SHA-1, SHA-2 specifications
<http://csrc.nist.gov/publications/fips/fips180-2/fips180-2withchangenotice.pdf>

Hash Function

- Hash Function
 - Compress a message with arbitrary length into a fixed-length output
- Cryptographic hash function
 - Ensure that hash function's every output (message digest) represents a message uniquely
 - A message digest represents only one message
- Importance of cryptographic hash function
 - Important for data integrity
 - Example: Checksum for downloading software
 - Important for digital signature (for authentication)
 - The research on cryptographic hash function is mainly due to the invention of digital signature
 - Key generation, security token

Hash Function

- How to ensure that each message digest represents a message uniquely ?
 - The message space size is much larger than the size of the message digest space
 - => it is impossible for a message digest to represent only one message
 - Solution: we try to ensure that it is computationally impossible to find two messages with the same message digest
 - => then it becomes computationally possible for a message digest to represent only one message

Hash Function

- A strong cryptographic hash function h with n -bit message digest size has the following three properties
 - Preimage Resistance
 - For any given y , it is difficult to find m satisfying $h(m) = y$
 - i.e., it requires about 2^n computations to find a preimage
 - Second-Preimage Resistance
 - For any given m , it is difficult to find a different m' so that $h(m) = h(m')$
 - i.e., it requires about 2^n computations to find a second-preimage
 - Collision Resistance
 - It is difficult to find two different m and m' so that $h(m) = h(m')$
 - i.e., it requires about $2^{n/2}$ computations to find a collision

Birthday attack!

Hash Function Overall Structure

- Iterated structure
 - Divide a message into many message blocks
$$m = m_1 \parallel m_2 \parallel m_3 \dots$$
 - Hash each message block iteratively:
$$H_0 = IV$$
 (here **IV** is a **fixed constant**)
$$H_i = f(H_{i-1}, m_i)$$
 (f is called compression function)
(the size of H_i must be at least as large as the size of the message digest)

But, the above construction is insecure!


- For example, the message being represented by the last message block is ambiguous!

Hash Function Overall Structure

- Merkle-Damgard structure
 - Strengthen the iterated structure with **padding**
 - pad bit '1' to the end of the message
 - pad some zeros
 - pad the message length (in bits)
 - After padding, the overall length should be multiple of the block size
 - **Finalization** stage: process the output from the last message block, then to generate the message digest
 - The most widely used hash function overall structure


Hash Function Overall Structure

- Merkle-Damgard structure



Compression Function Structure

- Many different compression function structures
- Compression function based on single block cipher:



- Davies-Meyer structure is so far the most widely used:
MD4, MD5, SHA-1, SHA-2

Hash Functions

- MD4 (1990)
 - 128-bit message digest
- MD5 (1991)
 - 128-bit message digest

Designed by Ron Rivest,
Extremely weak,
MD5 broken by Wang Xiaoyun
etc in 2005




Hash Functions

- Hash function standard of NIST
SHA – Secure Hash Algorithm (by NSA)
 - SHA-0, published in 1993
 - 160-bit message digest size
 - Insecure – withdrawn shortly, replaced by SHA-1
 - SHA-1, published in 1995
 - 160-bit message digest size
 - Insecure (2^{69} , Wang Xiaoyun, etc, 2005)
 - but so far not broken on computer
 - SHA-2, published in 2001
 - SHA-256, SHA-224
 - SHA-224 is based on SHA-256: different IV, truncating 32 bits
 - SHA-512, SHA-384
 - SHA-384 is based on SHA-512: different IV, truncating 64 bits

SHA-1

- 160-bit message digest
- 512-bit message block size
- Merkle-Damgard construction
- Davies-Meyer compression function structure



SHA-1

- Message expansion
 - Expand a 512-bit message block
 - Message block: m_0, m_1, \dots, m_{15} (each m_i is 32-bit)
 - Expanded message: w_0, w_1, \dots, w_{79}

$$w_t = \begin{cases} M_t^{(i)} & 0 \leq t \leq 15 \\ \text{ROTL}^1(w_{t-3} \oplus w_{t-8} \oplus w_{t-14} \oplus w_{t-16}) & 16 \leq t \leq 79 \end{cases}$$

SHA-1

- 80 Steps to compress the expanded message
 - A 32-bit constant k_i for each step
- $(a_0, b_0, c_0, d_0, e_0) = H_{i-1}$ (H_0 is a fixed constant)

$$T = ROTL^5(a) + f_t(b, c, d) + e + K_t + W_t$$

$$e = d$$

$$d = c$$


$$c = ROTL^{30}(b)$$

$$b = a$$

$$a = T$$

$$f_t(x, y, z) = \begin{cases} Ch(x, y, z) = (x \wedge y) \oplus (\neg x \wedge z) & 0 \leq t \leq 19 \\ Parity(x, y, z) = x \oplus y \oplus z & 20 \leq t \leq 39 \\ Maj(x, y, z) = (x \wedge y) \oplus (x \wedge z) \oplus (y \wedge z) & 40 \leq t \leq 59 \\ Parity(x, y, z) = x \oplus y \oplus z & 60 \leq t \leq 79. \end{cases}$$

Each word is 32-bit



SHA-256

- 256-bit message digest
- 512-bit message block size
- Merkle-Damgard construction
- Davies-Meyer compression function structure

SHA-256

- Message expansion
 - Expand a 512-bit message block
 - Message block: m_0, m_1, \dots, m_{15} (each m_i is 32-bit)
 - Expanded message: w_0, w_1, \dots, w_{63}

$$W_t = \begin{cases} M_t^{(i)} & 0 \leq t \leq 15 \\ \sigma_1^{\{256\}}(W_{t-2}) + W_{t-7} + \sigma_0^{\{256\}}(W_{t-15}) + W_{t-16} & 16 \leq t \leq 63 \end{cases}$$

$$\sigma_0^{\{256\}}(x) = ROTR^7(x) \oplus ROTR^{18}(x) \oplus SHR^3(x)$$

$$\sigma_1^{\{256\}}(x) = ROTR^{17}(x) \oplus ROTR^{19}(x) \oplus SHR^{10}(x)$$

SHA-256

- 64 steps to compress the expanded message
 - A random constant k_i for each step
- $(a_0, b_0, c_0, d_0, e_0, f_0, g_0, h_0) = H_{i-1}$ (H_0 is a fixed constant)

$$T_1 = h + \sum_1^{\{256\}} (e) + Ch(e, f, g) + K_t^{\{256\}} + W_t$$

Each word is 32-bit

$$T_2 = \sum_0^{\{256\}} (a) + Maj(a, b, c)$$

$$h = g$$

$$g = f$$

$$f = e$$

$$e = d + T_1$$

$$d = c$$

$$c = b$$

$$b = a$$


$$a = T_1 + T_2$$

$$Ch(x, y, z) = (x \wedge y) \oplus (\neg x \wedge z)$$

$$Maj(x, y, z) = (x \wedge y) \oplus (x \wedge z) \oplus (y \wedge z)$$

$$\sum_0^{\{256\}} (x) = ROTR^2(x) \oplus ROTR^{13}(x) \oplus ROTR^{22}(x)$$

$$\sum_1^{\{256\}} (x) = ROTR^6(x) \oplus ROTR^{11}(x) \oplus ROTR^{25}(x)$$



SHA-512

- 512-bit message digest
- 1024-bit message block size
- Merkle-Damgard construction
- Davies-Meyer compression function structure

SHA-512

- Message expansion
 - Expand a 1024-bit message block
 - Message block: m_0, m_1, \dots, m_{15} (each m_i is 64-bit)
 - Expanded message: w_0, w_1, \dots, w_{79}

$$W_t = \begin{cases} M_t^{(i)} & 0 \leq t \leq 15 \\ \sigma_1^{\{512\}}(W_{t-2}) + W_{t-7} + \sigma_0^{\{512\}}(W_{t-15}) + W_{t-16} & 16 \leq t \leq 79 \end{cases}$$

$$\sigma_0^{\{512\}}(x) = ROTR^1(x) \oplus ROTR^8(x) \oplus SHR^7(x)$$

$$\sigma_1^{\{512\}}(x) = ROTR^{19}(x) \oplus ROTR^{61}(x) \oplus SHR^6(x)$$

SHA-512

- 80 steps to compress the expanded message
 - A random 64-bit constant k_i for each step
- $(a_0, b_0, c_0, d_0, e_0, f_0, g_0, h_0) = H_{i-1}$ (H_0 is a fixed constant)

$$T_1 = h + \sum_1^{\{512\}} (e) + Ch(e, f, g) + K_t^{\{512\}} + W_t$$

$$T_2 = \sum_0^{\{512\}} (a) + Maj(a, b, c)$$

Each word is 64-bit

$$h = g$$

$$g = f$$

$$f = e$$

$$e = d + T_1$$

$$d = c$$

$$c = b$$

$$b = a$$


$$a = T_1 + T_2$$

$$Ch(x, y, z) = (x \wedge y) \oplus (\neg x \wedge z)$$

$$Maj(x, y, z) = (x \wedge y) \oplus (x \wedge z) \oplus (y \wedge z)$$

$$\sum_0^{\{512\}} (x) = ROTR^{28}(x) \oplus ROTR^{34}(x) \oplus ROTR^{39}(x)$$

$$\sum_1^{\{512\}} (x) = ROTR^{14}(x) \oplus ROTR^{18}(x) \oplus ROTR^{41}(x)$$



SHA-3 Competition (2008—2012)

- NIST hash function competition
 - In order to select one or two strong and efficient hash functions
 - Received 64 submissions in 2008
 - In 2009, 14 candidates were selected
 - Near the end of 2010, 5 candidates will be selected
 - In 2012, 1 or 2 candidates would be selected
 - The final candidates will be called SHA-3

Summary

- Cryptographic hash function
 - Aim: Each message digest represents only one message (computationally)
 - Three security requirements
 - Preimage resistance
 - Second-preimage resistance
 - Collision resistance
- SHA-1
 - Insecure
 - How to break it in practice?
- SHA-2
 - SHA-224, SHA-256, SHA-384, SHA-512
- SHA-3
 - ongoing