

MAS 433: Cryptography

Lecture 13

Public Key Encryption

Part 1: RSA

Wu Hongjun

Lecture Outline

- Classical ciphers
- Symmetric key encryption
- Hash function and Message Authentication Code
- **Public key encryption**
 - **RSA**
 - **Specification**
 - **Implementation**
 - **Security**
 - **Message padding (OAEP)**
 - ElGamal
- Digital signature
- Key establishment and management
- Introduction to other cryptographic topics

Recommended Reading

- CTP Section 5.1 to 5.7, Section 4.9
- HAC Section 8.1 and 8.2
- Wikipedia
 - Public key cryptosystem
http://en.wikipedia.org/wiki/Public-key_cryptography
 - RSA
<http://en.wikipedia.org/wiki/RSA>
 - Primality testing
http://en.wikipedia.org/wiki/Primality_test
 - Integer factorization
http://en.wikipedia.org/wiki/Integer_factorization
 - Optimal asymmetric encryption padding
http://en.wikipedia.org/wiki/Optimal_asymmetric_encryption_padding
 - PKCS
<http://en.wikipedia.org/wiki/PKCS>

Public Key Cryptosystem

- Symmetric key encryption
 - The same secret key is used for encryption and decryption
- How to communicate secretly if sender & receiver do not share a secret key before the communication starts?
 - Common problem for large computer network
 - Public key cryptosystems can solve this problem
 - **Diffie-Hellman key exchange** (1976)
 - The first paper on public key cryptosystem
 - **Public key encryption**

Public Key Cryptosystem



Whitfield Diffie



Martin Hellman

Diffie-Hellman Key Exchange

Public Key Cryptosystem

Diffie-Hellman Key Exchange

A group G is called cyclic if there exists an element g in G such that

$$G = \{ g^i \mid i \text{ is an integer} \},$$

where g is a generator of G .

Two system parameters:

1) large prime p

2) generator g of multiplicative cyclic group Z_p^*

Alice	Bob
step 1: generate random number r_a	generate random number r_b
step 2: compute $Y_a = (g^{r_a}) \bmod p$	compute $Y_b = (g^{r_b}) \bmod p$
step 3: send Y_a to Bob	send Y_b to Alice
step 4: compute $K_a = (Y_b)^{r_a} \bmod p$	compute $K_b = (Y_a)^{r_b} \bmod p$

$$K_a = K_b$$

Public Key Encryption

- Each receiver has two keys
 - Encryption key (called public key)
 - Everyone knows the encryption key of a receiver
 - **Everyone can encrypt a message using the public key of a receiver** and send the ciphertext to that receiver
 - Decryption key (called private key)
 - Only the receiver knows its decryption key
 - Difficult to derive the private key from public key
 - **Only the receiver can decrypt the ciphertext encrypted using its public key**

Public Key Encryption

- Many public key encryption schemes
- RSA (1978)
 - The first public key encryption scheme
 - Based on the difficulty of integer factorization & ‘discrete logarithm’
- ElGamal (1985)
 - Based on the difficulty of discrete logarithm
 - discrete logarithm: $g^x \bmod p = y$
(given y , to find x)


RSA



Ron Rivest




Adi Shamir



Leonard Adleman

RSA



RSA

- Key generation of each receiver:
 - Generate two distinct **large** prime numbers p and q
 - Compute $n = p \times q$
 - Compute $\varphi(n) = (p-1) \times (q-1)$
 - φ is Euler's totient function
 - Choose an integer e that is coprime to $\varphi(n)$
 - Find d satisfying $e \times d \equiv 1 \pmod{\varphi(n)}$

public key: e, n

private key: d

RSA

- Encryption

$$c = m^e \bmod n \quad (\text{plaintext } m: 0 < m < n)$$

- Decryption

$$m = c^d \bmod n$$

RSA

RSA's decryption recovers the message

Simple but incomplete proof:

- Euler's theorem:

Let a be a positive integer coprime to n , then

$$a^{\phi(n)} \equiv 1 \pmod{n}$$

- RSA decryption:

$$\begin{aligned} c^d \pmod{n} &= (m^e \pmod{n})^d \pmod{n} \\ &= m^{ed} \pmod{n} \\ &= m^{\beta\phi(n)+1} \pmod{n} \end{aligned}$$

If m and n are coprime, then $m^{\beta\phi(n)} \pmod{n} = 1$

$$\therefore c^d \pmod{n} = m$$

RSA

RSA's decryption recovers the message

The complete proof requires the following theorem:

- Fermat's little theorem:

Let a be a positive integer coprime to a prime number p , then

$$a^{p-1} \equiv 1 \pmod{p}$$

- Chinese Remainder Theorem (special case):

If n_1 and n_2 are coprime, $x < n_1 n_2$, and x satisfies

$$x \equiv a \pmod{n_1}$$

$$x \equiv a \pmod{n_2}$$

then there is a unique solution

$$x \equiv a \pmod{n_1 n_2}$$

Brief explanation:

$$n_1 \mid (x-a)$$

$$n_2 \mid (x-a)$$

Since n_1 and n_2 are coprime, we get

$$n_1 n_2 \mid (x-a)$$

$$\text{i.e., } x-a \pmod{n_1 n_2} = 0$$

RSA

- RSA's decryption recovers the message
complete proof:

Let $x = c^d \bmod n$,

$$\begin{aligned}x \bmod p &= ((m^e)^d \bmod n) \bmod p \\&= (m^e)^d \bmod p \\&= m^{\beta(p-1)(q-1)+1} \bmod p\end{aligned}$$

If m and p are coprime, according to Fermat's little theorem: $m^{p-1} \bmod p = 1$

$$\therefore x \bmod p = m^{\beta(p-1)(q-1)+1} \bmod p = m \bmod p \quad (1)$$

If m is the multiple of p , then

$$x \bmod p = m^{\beta(p-1)(q-1)+1} \bmod p = 0 = m \bmod p \quad (2)$$

From (1) and (2), $x \equiv m \bmod p$ (3)

Similarly: $x \equiv m \bmod q$ (4)

From (3), (4) and Chinese Remainder Theorem:

$$x = m \bmod pq = m$$

RSA

- Example (Toy RSA):

Key generation:

- $p = 61, q = 53$
- $n = 61 \times 53 = 3233$
- $\phi(n) = (61-1)(53-1) = 3120$
- choose public key $e = 17$, e is coprime to $\phi(n)$
- find private key $d = 2753$ satisfying $e \times d \equiv 1 \pmod{\phi(n)}$

Encryption:

If $m = 37$, then $c = 37^{17} \pmod{3233} = 1350$

Decryption:

$m = 1350^{2753} \pmod{3233} = 37$

RSA Implementation

- Key generation:
 - Generate two distinct large prime numbers p and q
 - Compute $n = p \times q$
 - Compute $\varphi(n) = (p-1) \times (q-1)$
 - φ is Euler's totient function
 - Choose an integer e that is coprime to $\varphi(n)$
 - Find d satisfying $e \times d \equiv 1 \pmod{\varphi(n)}$

- Encryption

$$c = \underline{m^e \bmod n}$$

- Decryption

$$m = \underline{c^d \bmod n}$$

1. How to find p & q ?
2. How to find d ?
3. How to compute $(m^e \bmod n)$ and $(c^d \bmod n)$ efficiently?

RSA Implementation: How to find p & q ?

- How to find a large prime number?
 - Randomly select a large integer
 - Then test whether it is prime or not
- Questions:
 - What is the probability that a large random integer is prime?
 - How to test whether a large random integer is prime?

RSA Implementation: How to find p & q ?

$\pi(x)$: the number of primes less than or equal to a real number x

- Prime Distribution Theorem

$$\lim_{x \rightarrow \infty} \frac{\pi(x)}{x / \ln(x)} = 1$$

$$\pi(x) \sim \frac{x}{\ln x}.$$

RSA Implementation: How to find p & q ?

$$\pi(x) \sim \frac{x}{\ln x}$$

- A random 512-bit integer is prime with probability about

$$\frac{1}{\ln 2^{512}} \approx \frac{1}{355}$$

- A random 1024-bit integer is prime with probability about

$$\frac{1}{\ln 2^{1024}} \approx \frac{1}{710}$$

\Rightarrow The probability that a large random integer is sufficiently large for practical applications

RSA Implementation: How to find p & q ?

- Primality testing:
 - Naïve methods
 - **Probabilistic tests**
 - **Low complexity**
 - **Commonly used**
 - Fast deterministic tests

RSA Implementation: How to find p & q ?

- Primality testing
 - Naïve methods
 - The simplest primality testing:
 - To test whether an integer n is prime or not, try all the integers less than or equal to $n^{0.5}$ to check whether n is divisible by any of those integers
 - Complexity: $O(n^{0.5})$

RSA Implementation: How to find p & q ?

- Primality testing
 - Probabilistic tests
 - Fermat primality test
 - Simple, but not useful for detecting some special composite numbers
 - Useful for quick screening, then test the remaining numbers using other primality testing methods
 - Used in Perfect Good Privacy (PGP) for primality testing
 - Miller-Rabin test
 - The commonly used primality testing method
 - » Mathematica, OpenSSL, ...

RSA Implementation: How to find p & q ?

- Primality testing
 - Probabilistic tests
 - Fermat primality test
 - To test whether an integer n is prime or not, choose some integer a coprime to n ($a > 1$),
 - » If $a^{n-1} \bmod n \neq 1$, then n is composite
 - » If $a^{n-1} \bmod n = 1$, then n may or may not be prime
 - As more different values of a are tested, the accuracy improves
 - » But for some special composite number n (called Carmichael numbers), for all the a coprime to n ,
$$a^{n-1} \bmod n = 1$$

RSA Implementation: How to find p & q ?

- Primality testing
 - Probabilistic tests
 - Miller-Rabin test

Given an integer n , write $n - 1 = 2^r s$, where s is odd

Choose a random integer a with $2 \leq a \leq n - 1$

1. If $a^s \not\equiv 1 \pmod{n}$ and $a^{2^j s} \not\equiv -1 \pmod{n}$ for all $0 \leq j \leq r - 1$,
then n is a composite;
2. Otherwise, n may or may not be prime

A prime can always pass through the above test (never be identified as composite).
A composite number can be identified as probably prime with probability $1/4$ for a random integer a . With N random distinct integers a , a composite number is identified as probably prime with probability 2^{-2N}

RSA Implementation: How to find p & q ?

- Primality testing
 - Fast deterministic tests
 - In 2002, Agrawal, Kayal and Saxena found a new deterministic primality test (AKS), with complexity $O((\log n)^{12})$
 - In 2005, the complexity is reduced to $O((\log n)^6)$. It is still much slower than probabilistic methods

RSA Implementation: How to find d ?

- Use the extended Euclidean algorithm to find d satisfying $ed \equiv 1 \pmod{\varphi(n)}$
 - Euclidean algorithm
 - to find $\gcd(a, b)$
 - extended Euclidean algorithm
 - to find $ax + by = \gcd(a, b)$
 - If $\gcd(a, b) = 1$, then $ax \equiv 1 \pmod{b}$; $by \equiv 1 \pmod{a}$

RSA Implementation:

How to compute $a^x \bmod n$ efficiently?

1. Represent a t - bit exponent x in binary format as

$$x = x_{t-1}x_{t-2} \cdots x_2x_1x_0, \text{ i.e., } x = \sum_{i=0}^{t-1} x_i 2^i$$

2. Compute $y_i = a^{2^i} \bmod n$ as

t square-mod
operations

$y_i = (y_{i-1})^2 \bmod n$, where $y_0 = a^{2^0} \bmod n = a$

3. Then $a^x \bmod n$ is computed efficiently as

$$a^x \bmod n = a^{\sum_{i=0}^{t-1} x_i 2^i} \bmod n = \left(\prod_{i=0}^{t-1} a^{x_i 2^i} \right) \bmod n$$

At most $t-1$ multiply-mod
operations

$$= \left(\prod_{i=0}^{t-1} (a^{2^i})^{x_i} \right) \bmod n = \left(\prod_{i=0}^{t-1} y_i^{x_i} \right) \bmod n$$

RSA Implementation:

How to compute $a^x \bmod n$ efficiently?

- Implement the method on the previous slide as :

```
 $y = a, z = 1$   
for  $i = 0$  to  $t - 1$  do  
{  
    if  $x_i = 1$ , then  $z = z \cdot y \bmod n$   
     $y = y^2 \bmod n$   
}
```

RSA Implementation:

How to compute $a^x \bmod n$ efficiently?

- Square-and-multiply algorithm in the textbook:
 - Compare to the algorithm on the previous slide, the value of i decreases

$$z = 1$$

for $i = t - 1$ downto 0 do

{

$$z = z^2 \bmod n$$

if $x_i = 1$, then $z = z \cdot a \bmod n$

}

RSA Security

Attacks on RSA:

- **To factorize n**
 - Once n is factorized, d can be computed
 - Difficult for large n
- **Other attacks**

RSA Security: Integer Factorization

- Integer factorization
 - Here we consider only **RSA moduli**
 - Product of two primes (also called semiprimes, biprimes)
- Many integer factorization techniques
 - Trial division
 -
 - Dixon's random squares algorithm
 - Quadratic sieve
 - General number field sieve

RSA Security: Integer Factorization

- Trial division
 - To factorize integer n , try all the integers less than or equal to $n^{0.5}$ to check whether n is divisible
 - Complexity: $O(n^{0.5})$

RSA Security: Integer Factorization

- Dixon's random squares algorithm
 - Basic idea: (Fermat)
 - used in many factorization algorithms

Suppose that we can find $x \not\equiv \pm y \pmod{n}$ such that

$x^2 \equiv y^2 \pmod{n}$, then $n \mid (x - y)(x + y)$.

But neither $(x - y)$ or $(x + y)$ is divisible by n since $x \not\equiv \pm y \pmod{n}$.

Therefore $\gcd(x - y, n)$ is a non - trivial factor of n

$\gcd(x + y, n)$ is another non - trivial factor of n

Example : $10^2 \equiv 32^2 \pmod{77}$

$$\gcd(10 + 32, 77) = 7, \gcd(10 - 32, 77) = 11$$

RSA Security: Integer Factorization

- Dixon's random squares algorithm (contd.)

Smooth number

- An integer which factors completely into small prime numbers
- A positive integer is called ***B*-smooth** if none of its prime factors is greater than *B*.
- Example:

$$1620 = 2^2 \times 3^4 \times 5$$

1620 is 5-smooth since none of its prime factors is greater than 5.

RSA Security: Integer Factorization

- Dixon's random squares algorithm (contd.)

1) Let $m = \lfloor \sqrt{n} \rfloor$, define a function $Q(x) = (m + x)^2 - n$ $Q(x) \approx \alpha\sqrt{n}$

2) define the value of B (it depends on the size of n , normally it cannot be than 2^{40})

Denote those primes $\leq B$ as $\{p_1, p_2, \dots, p_t\} = \{-1, 2, 3, 5, \dots, p_t\}$

3) Randomly select small (positive or negative) integers x .

Keep those integers satisfying that $Q(x)$ is B -smooth.

Denote those integers as x_1, x_2, \dots, x_μ

$$Q(x_i) = p_1^{e_{i,1}} \times p_2^{e_{i,2}} \times p_3^{e_{i,3}} \times \dots \times p_t^{e_{i,t}}$$

RSA Security: Integer Factorization

- Dixon's random squares algorithm (contd.)

4) With t such x_i , by solving binary linear equations, we can find a subset

$A \subset \{1, 2, 3, 4, 5, \dots, t\}$, so that $\sum_{i \in A} e_{i,j}$ is even for all the values of j ($1 \leq j \leq t$)

5) Then
$$\prod_{i \in A} Q(x_i) = p_1^{\sum_{i \in A} e_{i,1}} \times p_2^{\sum_{i \in A} e_{i,2}} \times p_3^{\sum_{i \in A} e_{i,3}} \times \dots \times p_t^{\sum_{i \in A} e_{i,t}} = y^2$$

6) Thus
$$\prod_{i \in A} Q(x_i) \equiv y^2 \pmod{n}$$
$$\left(\prod_{i \in A} (m + x_i) \right)^2 \equiv y^2 \pmod{n}$$

$$z^2 \equiv y^2 \pmod{n}$$

If $z \not\equiv \pm y \pmod{n}$, then $\gcd(z - y, n)$ gives a factor of n

Example: Factorize $n = 4841$

If we use the set A
 $\{x=6\}$, then
 $y=2^2 \times 7 = 28$
 $z=(m+6)=75$
 Then we get:
 $\gcd(z-y, n) = 47$
 $\gcd(z+y, n) = 103$

1. $m = \lfloor \sqrt{n} \rfloor = 69, Q(x) = (m+x)^2 - n$
2. set $B = 11$, the factor base is $\{-1, 2, 3, 5, 7, 11\}$
3. $x = -8 \rightarrow Q(x) = -1120 = (-1) \times 2^5 \times 5 \times 7$
 $x = -4 \rightarrow Q(x) = -616 = (-1) \times 2^3 \times 7 \times 11$
 $x = -2 \rightarrow Q(x) = -352 = (-1) \times 2^5 \times 11$
 $x = 0 \rightarrow Q(x) = -80 = (-1) \times 2^4 \times 5$
 $x = 2 \rightarrow Q(x) = 200 = 2^3 \times 5^2$
 $x = 3 \rightarrow Q(x) = 343 = 7^3$
 $x = 6 \rightarrow Q(x) = 784 = 2^4 \times 7^2$
4. Find the set A as $\{x = -4, x = -2, x = 3\}$
5. $y^2 = Q(-4) \times Q(-2) \times Q(3) = (-1)^2 \times 2^8 \times 7^4 \times 11^2$
 $\Rightarrow y = (-1) \times 2^4 \times 7^2 \times 11 \equiv -3783 \pmod{4841}$
 $z = (m-4) \times (m-2) \times (m+3) \equiv 3736 \pmod{4841}$
 $\gcd(z-y, n) = \gcd(3736 + 3783, 4841) = 103$
 $\gcd(z+y, n) = \gcd(3736 - 3783, 4841) = 47$
 $n = 4841 = 47 \times 103$

RSA Security: Integer Factorization

- Quadratic sieve
 - Very similar to Dixon's random squares algorithm
 - But with efficient sieving method to generate smooth numbers
- General number field sieve
 - Improve the quadratic sieve
 - Convert the integer factorization problem to factorization over algebraic number field
 - so as to generate “more” smooth number

RSA Security: Integer Factorization

- Complexities of factorization algorithms

Trial division : $O(\sqrt{n}) \rightarrow O(e^{0.5 \ln n})$

Dixon's Random Squares Algorithm : $O(e^{(1+O(1)) \ln n^{1/2} (\ln \ln n)^{1/2}})$

Quadratic sieve : $O(e^{(1+O(1)) \ln n^{1/2} (\ln \ln n)^{1/2}})$

General number field sieve : $O(e^{(1+O(1)) \ln n^{1/3} (\ln \ln n)^{2/3}})$

RSA Security: Integer Factorization

- The size of RSA moduli
NIST recommendation, 2007:

size of n	security level
1024-bit	80 bits
2048-bit	112 bits
3072-bit	128 bits
7680-bit	192 bits
15360-bit	256 bits

RSA Security: Integer Factorization

- Some RSA modulus factorization records

– 129-digit modulus	1994	→ Quadratic sieve
– 155-digit (512-bit) modulus	1999	} → General number field sieve
– 174-digit (576-bit) modulus	2003	
– 200-digit (663-bit) modulus	2005	
– 232-digit (768-bit) modulus	2009	

Complexity: about 2000 CPU cores (2.2GHz) for 1 year

1024-bit modulus: when? method?

RSA Security: Other Attacks (1)

- Trivial attacks
 - If p or q is known to the attacker \rightarrow broken
 - If $\varphi(n)$ is known to the attacker \rightarrow broken

RSA Security: Other Attacks (2)

- Attack on shared modulus
 - Shared modulus
 - each user is given a public key (e_i, n) and private key d_i
 - They share the same modulus n
 - Attack
 - Each user can factorize n easily from e_i and d_i
 - Then each user can find the private keys of other users
 - How to factorize?

RSA Security: Other Attacks (2)

- Attack on shared modulus (contd.)

- Factorize n from e and d

- 1) Since $e \cdot d \equiv 1 \pmod{\varphi(n)}$,

$$e \cdot d - 1 = \beta(p-1)(q-1),$$

we know that $e \cdot d - 1$ is even

- 2) Randomly select an integer x , compute

$$y = x^{(e \cdot d - 1)/2} \pmod{n}$$

- 3) We know that $x^{e \cdot d - 1} \pmod{n} = x^{\beta \varphi(n)} \pmod{n} = 1$ (Euler's theorem)

- 4) From 2) and 3), we know that

$$y^2 = 1 \pmod{n}$$

Thus $\gcd(y-1, n)$ gives a factor of n if $y \not\equiv \pm 1 \pmod{n}$

Slide 33



RSA Security: Other Attacks (3)

- The message size is small

- Attack

Example: A 64-bit secret m is encrypted as $c = m^e \bmod n$
(n, e, d are huge)

With probability about 20%, a random 64-bit m can be written as $m = m_1 m_2$, where $m_1, m_2 < 2^{34}$.

Now an attacker builds two tables:

$$T_1[i] = \frac{c}{i^e} \bmod n \text{ for } 1 \leq i \leq 2^{34}$$

$$T_2[j] = j^e \bmod n \text{ for } 1 \leq j \leq 2^{34}$$

If $T_1[i] = T_2[j]$ for some i and j , then the message $m = i \times j$

Complexity: about 2×2^{34}

RSA Security: Other Attacks (4)

- The exponent e is too small

- Attack 1:

Example: if $e = 3$, then for small m (say, $m < n^{1/3}$),

$$c = m^3 \bmod n = m^3$$

$\Rightarrow m$ can be recovered from c easily

- Attack 2:

Example: if $e = 3$, and m is large. The same message m is sent to 3 different receivers

$$c_1 = m^3 \bmod n_1 \quad (1)$$

$$c_2 = m^3 \bmod n_2 \quad (2)$$

$$c_3 = m^3 \bmod n_3 \quad (3)$$

From Chinese Remainder Theorem and (1), (2), (3),
 $m^3 \bmod n_1 n_2 n_3$ can be obtained, i.e., m^3 becomes known.
 m can thus be recovered easily from m^3

RSA Security: Other Attacks (4)

- Recommended value: $e = 65537 = 2^{16} + 1$
 - Encryption takes 17 modular multiplies
 - Fast encryption, but slow decryption
 - Encryption is about 80 times faster than decryption for 1024-bit n
 - But RSA encryption with this e and 1024-bit n is still more than 50 times slower than AES encryption on computer;

RSA Security: Other Attacks (5)

- How about choose small private key d to increase decryption speed?
 - In the key generation process, choose d first, then compute e
 - But **the value of d must be large for security reason**
 - Brute force attack: the size of d should be more than 128 bits
 - Advanced attack:
 - If $d < n^{0.25}$, d can be recovered from e and n easily (1987)
 - If $d < n^{0.292}$, d can be recovered from e and n easily (1998)
 - It is conjectured that if $d < n^{0.5}$, d can be recovered from e and n easily (open problem)

RSA Security: Other Attacks (6)

- Attack on `public' encryption
 - Attacker can perform encryption of any message
 - If the entropy of the message is not large, the attacker can encrypt all the possible messages, then compare those ciphertexts with the received ciphertext, and recover the message

RSA Security

- How to make RSA strong
 - Large modulus
 - 3072 bits for 128-bit security
 - 15360 bits for 256-bit security
 - Private key larger than $n^{0.5}$
 - Message padding
 - **To introduce randomness to the plaintext m**
 - To pad message m so that the length of padded message is close to that of n

RSA Message Padding

- “Textbook” RSA Encryption

$$c = m^e \bmod n \quad (\text{plaintext } m: 0 < m < n)$$

- Risks

- Property:

$$\text{If } m = \prod_{i=1}^t m_i, \text{ then } c = \prod_{i=1}^t c_i \bmod n, \text{ where } c_i = m_i^e \bmod n$$

- Encryption algorithm is **deterministic** & public

- The same plaintext is always encrypted to the same ciphertext
 - If there is no sufficient entropy in plaintext,
 - If the public key size is small, ...

RSA Message Padding

- **Never use the “textbook” RSA in practice**
- Padding is necessary
 - Pad the message to large size
 - Introduce randomness to the encryption algorithm
- The RSA message padding used in SSL (before 1998) is insecure
- OAEP is now used for RSA message padding
 - **OAEP**
 - **Optimal asymmetric encryption padding** (1994)
 - Details
 - PKCS#1 v2.1 (the latest version); or RFC 3447

RSA Message Padding: OAEP

(the specification here is slightly different from the RFC)


n : the number of bits in the RSA modulus.

k_0 and k_1 : integers fixed by the protocol

m : plaintext message, $(n - k_0 - k_1)$ -bit string

G and H : “random” functions fixed by the protocol

Then encrypt the padded message



RSA Message Padding: OAEP

- Security of OAEP
 - “Provably” secure, 1994
 - Complicated security proof
 - Get standardized for its security proof
 - OAEP’s security proof is found to be incorrect, 2001
 - But OAEP is still strong enough for applications

RSA Applications

- Used in almost all the secure Internet communication applications
 - Public key infrastructure
 - TLS/SSL
 - Secure e-mail: PGP, Microsoft Outlook ...

Summary

- Public key encryption
 - Allows two parties to communicate secretly without sharing a secret key before communication
- RSA
 - Specifications
 - Implementation
 - Primality testing: Fermat's primality test, Miller-Rabin primality test
 - Extended Euclidean algorithm
 - Fast modular exponentiation
 - Security
 - Integer factorization
 - Dixon's Random Squares algorithm
 - Other attacks
 - Short message
 - Shared public key
 - Small public key
 - Small private key
 - Message padding (OAEP)
 - Never use the “textbook” RSA in practice
 - Message padding is important for the security of RSA