

# Manual for *HierAdmix*

## 1. Introduction

*HierAdmix* is a software that can be used to reconstruct the 4-way admixture history considering the complex admixture structure. It could automatically select the optimal admixture model between the hierarchical admixture model and the sequential admixture model. *HierAdmix* is an extension of the *MultiWaver* series software.

## 2. Input Files

The format of input ancestral tracts file is similar to *MultiWaver* series software with an additional column representing the haplotype information. Each line represents an ancestral tract with the genetic distance of start point, the genetic distance of end point, from which ancestry the tract originates, and the index of admixed haplotype. The unit of first two columns are both in Morgan. Here takes the first few rows of “Hier.seg” as an example:

0	0.01113699	Anc3	hap0
0.01113699	0.02255031	Anc2	hap0
0.02255031	0.02763909	Anc3	hap0
0.02763909	0.03211435	Anc4	hap0
0.03211435	0.08753307	Anc3	hap0
0.08753307	0.09612572	Anc4	hap0
.....	.....	.....	.....

## 3. Output Files

The format of output model file is same as *MultiWaver* series software. Here takes the output file “Hier.txt” as an example, which is inferred based on the input file “Hier.seg”:

```
Best Model:      Hierarchical Admixture Model
Anc1      143(G)      0.208525
Anc2      143(G)      0.791475
Anc3      147(G)      0.700884
Anc4      147(G)      0.299116
Anc1_Anc2  50(G)      0.398402
Anc3_Anc4  50(G)      0.601598
-----
Bootstrapping details
Bootstrapping support ratio:100.0% (100/100)
Anc1      [137, 146](G) [0.202651, 0.213938]
Anc2      [137, 146](G) [0.785349, 0.795875]
Anc3      [144, 149](G) [0.694271, 0.706015]
Anc4      [144, 149](G) [0.293273, 0.304342]
Anc1_Anc2 [48, 51](G)   [0.388009, 0.406017]
Anc3_Anc4 [48, 51](G)   [0.593242, 0.60979]
```

#### 4. Arguments and Options

Arguments	Type	Description	Note
--input	string	Input file name	required
--lower	float	Lower bound to discard short tracts	optional, default = 0
--bootstrap	int	Number of bootstrapping	optional, default = 0
--ci	float	Confidence level of bootstrapping confidence interval	optional, default = 0.95
--output	string	Prefix of output file	optional, default="out"
-h	/	Print help message	/

#### 5. Notes

A special hierarchical admixture model needs special attention, within which the admixture proportions of two populations of left-side are same, and the admixture proportions of two populations of right-side are same too. In this case, the admixture time doesn't have the unique solution and the inference results of *HierAdmix* can be unreliable.

#### 6. Questions and Trouble-shooting

Questions and suggestions are welcome, feel free to contact Shi Zhang [19121640@bjtu.edu.cn](mailto:19121640@bjtu.edu.cn) or Rui Zhang [zhangrui2018@picb.ac.cn](mailto:zhangrui2018@picb.ac.cn).