



Diesel engine oil - 20W-50 CI-4 / SL

## **Product Description**

• Diesel engine oil 20W-50 Cl-4 / SL made by 100% synthetic base oil, suitable for all Multigrades & Mono grades

## **Applications**

- Recommended for all Diesel engines, especially for most recent technology engines (multi valve, turbocharged, Man, TATA,), supercharged or not, in trucks
- Suitable for all journeys (in town, on highways or motorways) and particularly in severe condi-
- For all driving styles, particularly "vigorous" and high speeds.

#### **Features**

- Meets API CI/SL requirements, guarantee of an high and constant quality for lubricants.
- Ensures easy cold start due to its extreme fluidity at low temperature and maintains a very resistant oil film even at high operating temperature.
- Gives the engine an excellent wear protection, develops performance and power.

### **Performance Level**

API CI-4 / SL

# **Phycial and Chemiocal Properties**

TEST NAME	METHOD	UNIT	RESULTS
Color	VISUAL	-	L-2
Specific Gravity @ 15 °C	ASTM D-1298	-	0.878
Viscosity @ 40 °C	ASTM D 445	m²/s (cts)	172
100 °C	ASTM D 445	m²/s (cts)	18.6
Viscosity Index	ASTM D2270	-	142
Flash Point	ASTM D92	°C	248
Pour Point	ASTM D97	°C	-33
TBN	-	-	11.6

## **Health and Safety**

This product shows no significant health or safety hazard when used under the recommended applications and suitable handling. Avoid the direct contact. Wash imme- diately after contact.



