



Diesel engine oil - 15W-40 CI-4/SL

Product Description

• Diesel engine oil 15W-40 Cl-4 / SL made by 100% synthetic base oil, suitable for all Multigrades & Mono grades

Applications

- Recommended for all Diesel engines, especially for most recent technology engines (multi valve, turbocharged, Man, TATA,), supercharged or not, in trucks
- Suitable for all journeys (in town, on highways or motorways) and particularly in severe condi-
- For all driving styles, particularly "vigorous" and high speeds.

Features

- Meets API CI/SL requirements, guarantee of an high and constant quality for lubricants.
- Ensures easy cold start due to its extreme fluidity at low temperature and maintains a very resistant oil film even at high operating temperature.
- Gives the engine an excellent wear protection, develops performance and power.

Performance Level

API CI-4 / SL

Phycial and Chemiocal Properties

TEST NAME	METHOD	UNIT	RESULTS
Color	VISUAL	-	L-2
Specific Gravity @ 15 °C	ASTM D-1298	-	0.876
Viscosity @ 40 °C	ASTM D 445	m²/s (cts)	164
100 °C	ASTM D 445	m²/s (cts)	16.2
Viscosity Index	ASTM D2270	-	148
Flash Point	ASTM D92	°C	246
Pour Point	ASTM D97	°C	-38
TBN	-	-	10.8

Health and Safety

This product shows no significant health or safety hazard when used under the recommended applications and suitable handling. Avoid the direct contact. Wash imme- diately after contact.



