Selection Plots: Config Comparisons

April 17, 2026

Contents

1 bdt_nom vs bdt_tightbdt50

Config diff (A → B)

```diff
--- config_bdt_nom.yaml
+++ config_bdt_tightbdt50.yaml
@@ -20,5 +20,5 @@
   response_outfile: "/sphenix/user/shuhangli/ppg12/efficiencytool/results/MC_response"
   data_outfile: "/sphenix/user/shuhangli/ppg12/efficiencytool/results/data_histo"
-  var_type: "bdt_nom"
+  var_type: "bdt_tightbdt50"
   final_outfile: "/sphenix/user/shuhangli/ppg12/efficiencytool/results/Photon_final"

@@ -77,11 +77,4 @@
   # Leave empty ("") to use the pre-made vertex_reweight_file instead.
   vertex_scan_data_file: ""
-  # Data-driven iterative truth-vertex reweight (standalone tool in
-  # efficiencytool/truth_vertex_reweight/). When on, forces vertex_reweight_on
-  # off and applies w(z_h) (single MC) or w(z_h)*w(z_mb) (double MC) per event.
-  # Flip truth_vertex_reweight_on to 1 to switch the nominal 1.5 mrad
-  # analysis from the f(z_r) reco-level reweight to the truth-level one.
-  truth_vertex_reweight_on: 0
-  truth_vertex_reweight_file: "/sphenix/user/shuhangli/ppg12/efficiencytool/truth_vertex_reweight/output
   fit_option: 1
   cluster_escale: 1.0
@@ -154,5 +147,5 @@
     bdt_min: 0.7
     bdt_min_slope: -0.015
-    bdt_min_intercept: 0.80
+    bdt_min_intercept: 0.7


@@ -210,5 +203,5 @@
     bdt_max: 0.5
     bdt_max_slope: -0.015
-    bdt_max_intercept: 0.80
+    bdt_max_intercept: 0.7
     bdt_min: 0.02
```

1.1 Sideband (Data)



(a) Sideband ET spectrum (data) — bdt_nom



(b) Sideband ET spectrum (data) — bdt_tightbdt50



(a) Sideband ET ratio (data) — bdt_nom



(b) Sideband ET ratio (data) — bdt_tightbdt50



(a) Leakage fraction vs ET (data) — bdt_nom



(b) Leakage fraction vs ET (data) — bdt_tightbdt50

1.2 Sideband (MC)



(a) Sideband ET spectrum (MC) — bdt_nom



(b) Sideband ET spectrum (MC) — bdt_tightbdt50



(a) Sideband ET ratio (MC) — bdt_nom



(b) Sideband ET ratio (MC) — bdt_tightbdt50



(a) Leakage fraction vs ET (MC) — bdt_nom



(b) Leakage fraction vs ET (MC) — bdt_tightbdt50

1.3 Purity



(a) Purity (data) — bdt_nom



(b) Purity (data) — bdt_tightbdt50



(a) Purity (MC) — bdt_nom



(b) Purity (MC) — bdt_tightbdt50

1.4 Efficiency



(a) Reconstruction efficiency — bdt_nom



(b) Reconstruction efficiency — bdt_tightbdt50



(a) Isolation efficiency — bdt_nom



(b) Isolation efficiency — bdt_tightbdt50



(a) Identification efficiency — bdt_nom



(b) Identification efficiency — bdt_tightbdt50



(a) Total efficiency — bdt_nom



(b) Total efficiency — bdt_tightbdt50



(a) MBD trigger efficiency — bdt_nom



(b) MBD trigger efficiency — bdt_tightbdt50



(a) Combined photon efficiency — bdt_nom



(b) Combined photon efficiency — bdt_tightbdt50

1.5 Final result



(a) Final cross section result — bdt_nom



(b) Final cross section result — bdt_tightbdt50



(a) Comparison with PHENIX — bdt_nom



(b) Comparison with PHENIX — bdt_tightbdt50



(a) Common cluster yield (data vs MC) — bdt_nom



(b) Common cluster yield (data vs MC) — bdt_tightbdt50



(a) Tight iso cluster yield (data vs MC) — bdt_nom



(b) Tight iso cluster yield (data vs MC) — bdt_tightbdt50



(a) All correction steps — bdt_nom



(b) All correction steps — bdt_tightbdt50

1.6 Isolation fit (CONF)



(a) IsoET template (pT bins 0–2) — bdt_nom



(b) IsoET template (pT bins 0–2) — bdt_tightbdt50



(a) IsoET fit template (pT bins 0–2) — bdt_nom



(b) IsoET fit template (pT bins 0–2) — bdt_tightbdt50



(a) IsoET template (pT bins 3–5) — bdt_nom



(b) IsoET template (pT bins 3–5) — bdt_tightbdt50



(a) IsoET fit template (pT bins 3–5) — bdt_nom



(b) IsoET fit template (pT bins 3–5) — bdt_tightbdt50



(a) IsoET template (pT bins 6–8) — bdt_nom



(b) IsoET template (pT bins 6–8) — bdt_tightbdt50



(a) IsoET fit template (pT bins 6–8) — bdt_nom



(b) IsoET fit template (pT bins 6–8) — bdt_tightbdt50



(a) IsoET template (pT bins 9–9) — bdt_nom



(b) IsoET template (pT bins 9–9) — bdt_tightbdt50



(a) IsoET fit template (pT bins 9–9) — bdt_nom



(b) IsoET fit template (pT bins 9–9) — bdt_tightbdt50

1.7 Isolation ET



(a) IsoET Tight, pT bin 0 — bdt_nom



(b) IsoET Tight, pT bin 0 — bdt_tightbdt50



(a) IsoET Tight, pT bin 1 — bdt_nom



(b) IsoET Tight, pT bin 1 — bdt_tightbdt50



(a) IsoET Tight, pT bin 2 — bdt_nom



(b) IsoET Tight, pT bin 2 — bdt_tightbdt50



(a) IsoET Tight, pT bin 3 — bdt_nom



(b) IsoET Tight, pT bin 3 — bdt_tightbdt50



(a) IsoET Tight, pT bin 4 — bdt_nom



(b) IsoET Tight, pT bin 4 — bdt_tightbdt50



(a) IsoET Tight, pT bin 5 — bdt_nom



(b) IsoET Tight, pT bin 5 — bdt_tightbdt50



(a) IsoET Tight, pT bin 6 — bdt_nom



(b) IsoET Tight, pT bin 6 — bdt_tightbdt50



(a) IsoET Tight, pT bin 7 — bdt_nom



(b) IsoET Tight, pT bin 7 — bdt_tightbdt50



(a) IsoET Tight, pT bin 8 — bdt_nom



(b) IsoET Tight, pT bin 8 — bdt_tightbdt50



(a) IsoET Tight, pT bin 9 — bdt_nom



(b) IsoET Tight, pT bin 9 — bdt_tightbdt50



(a) IsoET Tight, pT bin 10 — bdt_nom



(b) IsoET Tight, pT bin 10 — bdt_tightbdt50



(a) IsoET Tight, pT bin 11 — bdt_nom



(b) IsoET Tight, pT bin 11 — bdt_tightbdt50

2 bdt_nom vs bdt_npb03

Config diff (A → B)

```diff
--- config_bdt_nom.yaml
+++ config_bdt_npb03.yaml
@@ -20,5 +20,5 @@
   response_outfile: "/sphenix/user/shuhangli/ppg12/efficiencytool/results/MC_response"
   data_outfile: "/sphenix/user/shuhangli/ppg12/efficiencytool/results/data_histo"
-  var_type: "bdt_nom"
+  var_type: "bdt_npb03"
   final_outfile: "/sphenix/user/shuhangli/ppg12/efficiencytool/results/Photon_final"

@@ -77,11 +77,4 @@
   # Leave empty ("") to use the pre-made vertex_reweight_file instead.
   vertex_scan_data_file: ""
-  # Data-driven iterative truth-vertex reweight (standalone tool in
-  # efficiencytool/truth_vertex_reweight/). When on, forces vertex_reweight_on
-  # off and applies w(z_h) (single MC) or w(z_h)*w(z_mb) (double MC) per event.
-  # Flip truth_vertex_reweight_on to 1 to switch the nominal 1.5 mrad
-  # analysis from the f(z_r) reco-level reweight to the truth-level one.
-  truth_vertex_reweight_on: 0
-  truth_vertex_reweight_file: "/sphenix/user/shuhangli/ppg12/efficiencytool/truth_vertex_reweight/output
   fit_option: 1
   cluster_escale: 1.0
@@ -218,5 +211,5 @@

     npb_cut_on: 1
-    npb_score_cut: 0.5
+    npb_score_cut: 0.3

     prob_max: 1.0
```

2.1 Sideband (Data)



(a) Sideband ET spectrum (data) — bdt_nom



(b) Sideband ET spectrum (data) — bdt_npb03



(a) Sideband ET ratio (data) — bdt_nom



(b) Sideband ET ratio (data) — bdt_npb03



(a) Leakage fraction vs ET (data) — bdt_nom



(b) Leakage fraction vs ET (data) — bdt_npb03

2.2 Sideband (MC)



(a) Sideband ET spectrum (MC) — bdt_nom



(b) Sideband ET spectrum (MC) — bdt_npb03



(a) Sideband ET ratio (MC) — bdt_nom



(b) Sideband ET ratio (MC) — bdt_npb03



(a) Leakage fraction vs ET (MC) — bdt_nom



(b) Leakage fraction vs ET (MC) — bdt_npb03

2.3 Purity



(a) Purity (data) — bdt_nom



(b) Purity (data) — bdt_npb03



(a) Purity (MC) — bdt_nom



(b) Purity (MC) — bdt_npb03

2.4 Efficiency



(a) Reconstruction efficiency — bdt_nom



(b) Reconstruction efficiency — bdt_npb03



(a) Isolation efficiency — bdt_nom



(b) Isolation efficiency — bdt_npb03



(a) Identification efficiency — bdt_nom



(b) Identification efficiency — bdt_npb03



(a) Total efficiency — bdt_nom



(b) Total efficiency — bdt_npb03



(a) MBD trigger efficiency — bdt_nom



(b) MBD trigger efficiency — bdt_npb03



(a) Combined photon efficiency — bdt_nom



(b) Combined photon efficiency — bdt_npb03

2.5 Final result



(a) Final cross section result — bdt_nom



(b) Final cross section result — bdt_npb03



(a) Comparison with PHENIX — bdt_nom



(b) Comparison with PHENIX — bdt_npb03



(a) Common cluster yield (data vs MC) — bdt_nom



(b) Common cluster yield (data vs MC) — bdt_npb03



(a) Tight iso cluster yield (data vs MC) — bdt_nom



(b) Tight iso cluster yield (data vs MC) — bdt_npb03



(a) All correction steps — bdt_nom



(b) All correction steps — bdt_npb03

2.6 Isolation fit (CONF)



(a) IsoET template (pT bins 0–2) — bdt_nom



(b) IsoET template (pT bins 0–2) — bdt_npb03



(a) IsoET fit template (pT bins 0–2) — bdt_nom



(b) IsoET fit template (pT bins 0–2) — bdt_npb03



(a) IsoET template (pT bins 3–5) — bdt_nom



(b) IsoET template (pT bins 3–5) — bdt_npb03



(a) IsoET fit template (pT bins 3–5) — bdt_nom



(b) IsoET fit template (pT bins 3–5) — bdt_npb03



(a) IsoET template (pT bins 6–8) — bdt_nom



(b) IsoET template (pT bins 6–8) — bdt_npb03



(a) IsoET fit template (pT bins 6–8) — bdt_nom



(b) IsoET fit template (pT bins 6–8) — bdt_npb03



(a) IsoET template (pT bins 9–9) — bdt_nom



(b) IsoET template (pT bins 9–9) — bdt_npb03



(a) IsoET fit template (pT bins 9–9) — bdt_nom



(b) IsoET fit template (pT bins 9–9) — bdt_npb03

2.7 Isolation ET



(a) IsoET Tight, pT bin 0 — bdt_nom



(b) IsoET Tight, pT bin 0 — bdt_npb03



(a) IsoET Tight, pT bin 1 — bdt_nom



(b) IsoET Tight, pT bin 1 — bdt_npb03



(a) IsoET Tight, pT bin 2 — bdt_nom



(b) IsoET Tight, pT bin 2 — bdt_npb03



(a) IsoET Tight, pT bin 3 — bdt_nom



(b) IsoET Tight, pT bin 3 — bdt_npb03



(a) IsoET Tight, pT bin 4 — bdt_nom



(b) IsoET Tight, pT bin 4 — bdt_npb03



(a) IsoET Tight, pT bin 5 — bdt_nom



(b) IsoET Tight, pT bin 5 — bdt_npb03



(a) IsoET Tight, pT bin 6 — bdt_nom



(b) IsoET Tight, pT bin 6 — bdt_npb03



(a) IsoET Tight, pT bin 7 — bdt_nom



(b) IsoET Tight, pT bin 7 — bdt_npb03



(a) IsoET Tight, pT bin 8 — bdt_nom



(b) IsoET Tight, pT bin 8 — bdt_npb03



(a) IsoET Tight, pT bin 9 — bdt_nom



(b) IsoET Tight, pT bin 9 — bdt_npb03



(a) IsoET Tight, pT bin 10 — bdt_nom



(b) IsoET Tight, pT bin 10 — bdt_npb03



(a) IsoET Tight, pT bin 11 — bdt_nom



(b) IsoET Tight, pT bin 11 — bdt_npb03

3 bdt_nom vs bdt_nosplit

Config diff (A → B)

```diff
--- config_bdt_nom.yaml
+++ config_bdt_nosplit.yaml
@@ -7,5 +7,5 @@
   data_file: "/sphenix/user/shuhangli/ppg12/anatreemaker/macro_maketree/data/ana521/condorout/part_*_wit
   tree: "slimtree"
-  cluster_node_name: "CLUSTERINFO_CEMC"
+  cluster_node_name: "CLUSTERINFO_CEMC_NO_SPLIT"
   bdt_model_name: "base_E"
   # Optional: use different BDT models in different ET bins.
@@ -20,5 +20,5 @@
   response_outfile: "/sphenix/user/shuhangli/ppg12/efficiencytool/results/MC_response"
   data_outfile: "/sphenix/user/shuhangli/ppg12/efficiencytool/results/data_histo"
-  var_type: "bdt_nom"
+  var_type: "bdt_nosplit"
   final_outfile: "/sphenix/user/shuhangli/ppg12/efficiencytool/results/Photon_final"

@@ -77,11 +77,4 @@
   # Leave empty ("") to use the pre-made vertex_reweight_file instead.
   vertex_scan_data_file: ""
-  # Data-driven iterative truth-vertex reweight (standalone tool in
-  # efficiencytool/truth_vertex_reweight/). When on, forces vertex_reweight_on
-  # off and applies w(z_h) (single MC) or w(z_h)*w(z_mb) (double MC) per event.
-  # Flip truth_vertex_reweight_on to 1 to switch the nominal 1.5 mrad
-  # analysis from the f(z_r) reco-level reweight to the truth-level one.
-  truth_vertex_reweight_on: 0
-  truth_vertex_reweight_file: "/sphenix/user/shuhangli/ppg12/efficiencytool/truth_vertex_reweight/output
   fit_option: 1
   cluster_escale: 1.0
```

3.1 Sideband (Data)



(a) Sideband ET spectrum (data) — bdt_nom



(b) Sideband ET spectrum (data) — bdt_nosplit



(a) Sideband ET ratio (data) — bdt_nom



(b) Sideband ET ratio (data) — bdt_nosplit



(a) Leakage fraction vs ET (data) — bdt_nom



(b) Leakage fraction vs ET (data) — bdt_nosplit

3.2 Sideband (MC)



(a) Sideband ET spectrum (MC) — bdt_nom



(b) Sideband ET spectrum (MC) — bdt_nosplit



(a) Sideband ET ratio (MC) — bdt_nom



(b) Sideband ET ratio (MC) — bdt_nosplit



(a) Leakage fraction vs ET (MC) — bdt_nom



(b) Leakage fraction vs ET (MC) — bdt_nosplit

3.3 Purity



(a) Purity (data) — bdt_nom



(b) Purity (data) — bdt_nosplit



(a) Purity (MC) — bdt_nom



(b) Purity (MC) — bdt_nosplit

3.4 Efficiency



(a) Reconstruction efficiency — bdt_nom



(b) Reconstruction efficiency — bdt_nosplit



(a) Isolation efficiency — bdt_nom



(b) Isolation efficiency — bdt_nosplit



(a) Identification efficiency — bdt_nom



(b) Identification efficiency — bdt_nosplit



(a) Total efficiency — bdt_nom



(b) Total efficiency — bdt_nosplit



(a) MBD trigger efficiency — bdt_nom



(b) MBD trigger efficiency — bdt_nosplit



(a) Combined photon efficiency — bdt_nom



(b) Combined photon efficiency — bdt_nosplit

3.5 Final result



(a) Final cross section result — bdt_nom



(b) Final cross section result — bdt_nosplit



(a) Comparison with PHENIX — bdt_nom



(b) Comparison with PHENIX — bdt_nosplit



(a) Common cluster yield (data vs MC) — bdt_nom



(b) Common cluster yield (data vs MC) — bdt_nosplit



(a) Tight iso cluster yield (data vs MC) — bdt_nom



(b) Tight iso cluster yield (data vs MC) — bdt_nosplit



(a) All correction steps — bdt_nom



(b) All correction steps — bdt_nosplit

3.6 Isolation fit (CONF)



(a) IsoET template (pT bins 0–2) — bdt_nom



(b) IsoET template (pT bins 0–2) — bdt_nosplit



(a) IsoET fit template (pT bins 0–2) — bdt_nom



(b) IsoET fit template (pT bins 0–2) — bdt_nosplit



(a) IsoET template (pT bins 3–5) — bdt_nom



(b) IsoET template (pT bins 3–5) — bdt_nosplit



(a) IsoET fit template (pT bins 3–5) — bdt_nom



(b) IsoET fit template (pT bins 3–5) — bdt_nosplit



(a) IsoET template (pT bins 6–8) — bdt_nom



(b) IsoET template (pT bins 6–8) — bdt_nosplit



(a) IsoET fit template (pT bins 6–8) — bdt_nom



(b) IsoET fit template (pT bins 6–8) — bdt_nosplit



(a) IsoET template (pT bins 9–9) — bdt_nom



(b) IsoET template (pT bins 9–9) — bdt_nosplit



(a) IsoET fit template (pT bins 9–9) — bdt_nom



(b) IsoET fit template (pT bins 9–9) — bdt_nosplit

3.7 Isolation ET



(a) IsoET Tight, pT bin 0 — bdt_nom



(b) IsoET Tight, pT bin 0 — bdt_nosplit



(a) IsoET Tight, pT bin 1 — bdt_nom



(b) IsoET Tight, pT bin 1 — bdt_nosplit



(a) IsoET Tight, pT bin 2 — bdt_nom



(b) IsoET Tight, pT bin 2 — bdt_nosplit



(a) IsoET Tight, pT bin 3 — bdt_nom



(b) IsoET Tight, pT bin 3 — bdt_nosplit



(a) IsoET Tight, pT bin 4 — bdt_nom



(b) IsoET Tight, pT bin 4 — bdt_nosplit



(a) IsoET Tight, pT bin 5 — bdt_nom



(b) IsoET Tight, pT bin 5 — bdt_nosplit



(a) IsoET Tight, pT bin 6 — bdt_nom



(b) IsoET Tight, pT bin 6 — bdt_nosplit



(a) IsoET Tight, pT bin 7 — bdt_nom



(b) IsoET Tight, pT bin 7 — bdt_nosplit



(a) IsoET Tight, pT bin 8 — bdt_nom



(b) IsoET Tight, pT bin 8 — bdt_nosplit



(a) IsoET Tight, pT bin 9 — bdt_nom



(b) IsoET Tight, pT bin 9 — bdt_nosplit



(a) IsoET Tight, pT bin 10 — bdt_nom



(b) IsoET Tight, pT bin 10 — bdt_nosplit



(a) IsoET Tight, pT bin 11 — bdt_nom



(b) IsoET Tight, pT bin 11 — bdt_nosplit

4 bdt_nom vs bdt_vtxreweight0

Config diff (A → B)

```diff
--- config_bdt_nom.yaml
+++ config_bdt_vtxreweight0.yaml
@@ -20,5 +20,5 @@
   response_outfile: "/sphenix/user/shuhangli/ppg12/efficiencytool/results/MC_response"
   data_outfile: "/sphenix/user/shuhangli/ppg12/efficiencytool/results/data_histo"
-  var_type: "bdt_nom"
+  var_type: "bdt_vtxreweight0"
   final_outfile: "/sphenix/user/shuhangli/ppg12/efficiencytool/results/Photon_final"

@@ -73,15 +73,8 @@
   mc_iso_shift: 0.1
   mc_iso_scale: 1.2
-  vertex_reweight_on: 1
+  vertex_reweight_on: 0
   # Path to data vertex scan output file (h_vertexz). Used for on-the-fly vertex reweighting.
   # Leave empty ("") to use the pre-made vertex_reweight_file instead.
   vertex_scan_data_file: ""
-  # Data-driven iterative truth-vertex reweight (standalone tool in
-  # efficiencytool/truth_vertex_reweight/). When on, forces vertex_reweight_on
-  # off and applies w(z_h) (single MC) or w(z_h)*w(z_mb) (double MC) per event.
-  # Flip truth_vertex_reweight_on to 1 to switch the nominal 1.5 mrad
-  # analysis from the f(z_r) reco-level reweight to the truth-level one.
-  truth_vertex_reweight_on: 0
-  truth_vertex_reweight_file: "/sphenix/user/shuhangli/ppg12/efficiencytool/truth_vertex_reweight/output
   fit_option: 1
   cluster_escale: 1.0
```

4.1 Sideband (Data)



(a) Sideband ET spectrum (data) — bdt_nom



(b) Sideband ET spectrum (data) — bdt_vtxreweight0



(a) Sideband ET ratio (data) — bdt_nom



(b) Sideband ET ratio (data) — bdt_vtxreweight0



(a) Leakage fraction vs ET (data) — bdt_nom



(b) Leakage fraction vs ET (data) — bdt_vtxreweight0

4.2 Sideband (MC)



(a) Sideband ET spectrum (MC) — bdt_nom



(b) Sideband ET spectrum (MC) — bdt_vtxreweight0



(a) Sideband ET ratio (MC) — bdt_nom



(b) Sideband ET ratio (MC) — bdt_vtxreweight0



(a) Leakage fraction vs ET (MC) — bdt_nom



(b) Leakage fraction vs ET (MC) — bdt_vtxreweight0

4.3 Purity



(a) Purity (data) — bdt_nom



(b) Purity (data) — bdt_vtxreweight0



(a) Purity (MC) — bdt_nom



(b) Purity (MC) — bdt_vtxreweight0

4.4 Efficiency



(a) Reconstruction efficiency — bdt_nom



(b) Reconstruction efficiency — bdt_vtxreweight0



(a) Isolation efficiency — bdt_nom



(b) Isolation efficiency — bdt_vtxreweight0



(a) Identification efficiency — bdt_nom



(b) Identification efficiency — bdt_vtxreweight0



(a) Total efficiency — bdt_nom



(b) Total efficiency — bdt_vtxreweight0



(a) MBD trigger efficiency — bdt_nom



(b) MBD trigger efficiency — bdt_vtxreweight0



(a) Combined photon efficiency — bdt_nom



(b) Combined photon efficiency — bdt_vtxreweight0

4.5 Final result



(a) Final cross section result — bdt_nom



(b) Final cross section result — bdt_vtxreweight0



(a) Comparison with PHENIX — bdt_nom



(b) Comparison with PHENIX — bdt_vtxreweight0



(a) Common cluster yield (data vs MC) — bdt_nom



(b) Common cluster yield (data vs MC) — bdt_vtxreweight0



(a) Tight iso cluster yield (data vs MC) — bdt_nom



(b) Tight iso cluster yield (data vs MC) — bdt_vtxreweight0



(a) All correction steps — bdt_nom



(b) All correction steps — bdt_vtxreweight0

4.6 Isolation fit (CONF)



(a) IsoET template (pT bins 0–2) — bdt_nom



(b) IsoET template (pT bins 0–2) — bdt_vtxreweight0



(a) IsoET fit template (pT bins 0–2) — bdt_nom



(b) IsoET fit template (pT bins 0–2) — bdt_vtxreweight0



(a) IsoET template (pT bins 3–5) — bdt_nom



(b) IsoET template (pT bins 3–5) — bdt_vtxreweight0



(a) IsoET fit template (pT bins 3–5) — bdt_nom



(b) IsoET fit template (pT bins 3–5) — bdt_vtxreweight0



(a) IsoET template (pT bins 6–8) — bdt_nom



(b) IsoET template (pT bins 6–8) — bdt_vtxreweight0



(a) IsoET fit template (pT bins 6–8) — bdt_nom



(b) IsoET fit template (pT bins 6–8) — bdt_vtxreweight0



(a) IsoET template (pT bins 9–9) — bdt_nom



(b) IsoET template (pT bins 9–9) — bdt_vtxreweight0



(a) IsoET fit template (pT bins 9–9) — bdt_nom



(b) IsoET fit template (pT bins 9–9) — bdt_vtxreweight0

4.7 Isolation ET



(a) IsoET Tight, pT bin 0 — bdt_nom



(b) IsoET Tight, pT bin 0 — bdt_vtxreweight0



(a) IsoET Tight, pT bin 1 — bdt_nom



(b) IsoET Tight, pT bin 1 — bdt_vtxreweight0



(a) IsoET Tight, pT bin 2 — bdt_nom



(b) IsoET Tight, pT bin 2 — bdt_vtxreweight0



(a) IsoET Tight, pT bin 3 — bdt_nom



(b) IsoET Tight, pT bin 3 — bdt_vtxreweight0



(a) IsoET Tight, pT bin 4 — bdt_nom



(b) IsoET Tight, pT bin 4 — bdt_vtxreweight0



(a) IsoET Tight, pT bin 5 — bdt_nom



(b) IsoET Tight, pT bin 5 — bdt_vtxreweight0



(a) IsoET Tight, pT bin 6 — bdt_nom



(b) IsoET Tight, pT bin 6 — bdt_vtxreweight0



(a) IsoET Tight, pT bin 7 — bdt_nom



(b) IsoET Tight, pT bin 7 — bdt_vtxreweight0



(a) IsoET Tight, pT bin 8 — bdt_nom



(b) IsoET Tight, pT bin 8 — bdt_vtxreweight0



(a) IsoET Tight, pT bin 9 — bdt_nom



(b) IsoET Tight, pT bin 9 — bdt_vtxreweight0



(a) IsoET Tight, pT bin 10 — bdt_nom



(b) IsoET Tight, pT bin 10 — bdt_vtxreweight0



(a) IsoET Tight, pT bin 11 — bdt_nom



(b) IsoET Tight, pT bin 11 — bdt_vtxreweight0