

INTERNET OF THINGS

REPORT BY CHIARA SIMONI AND
GIADA MARTINA STIVALA

Some project on debugging Bluetooth Low Energy devices

A.A. 2017/2018
Prof. Luciano BONONI, Marco DI FELICE

July 22, 2018

Contents

1	Introduction	1
2	Bluetooth Low Energy Specification	3
2.1	Network Topology and Devices	3
2.2	Decypher Advertising Packets	3
	Bibliography	5

Chapter 1

Introduction

Bluetooth Low Energy devices are flooding the market of cheap, wearable, health, home-appliance electronics. Some examples include monitoring devices for sport, health and outdoor activities in general; they also connect many household appliances as well as security cameras and locks. Other interesting use-cases include wristbands used in theme parks or live music concerts (although the technology may differ).

Intrinsically, these devices perform very simple tasks, mostly in the field of data gathering. It seems totally harmless to have a smart watch tracking your position at any time of day, but what if it were possible for anyone to query it and extract its data? Their minimalism is what makes them so appealing to the general public, but it is sometimes their intrinsic weakness.

Moving a bit further from "*hackers*" and information security, data gathering is a fundamental step for data analysis in a Big Data context. Privacy concerns should be taken into consideration also in terms of data anonymization.

In this project report, we will start by describing general device characteristics and Bluetooth specifications. We will then move to their concrete observation with hands-on analyses, taking into consideration different developing tools and devices. In particular, we will focus our attention on security risks and concrete flaws, highlighting security exploits when possible. Finally, we will summarize our findings, including a few ideas for future directions and developments.

For our tests, we used a Mi Band 2 smart band, a Magic Blue smart lightbulb and a ST Microelectronics IoT node (model `STM32L475 MCU`). The code was run both on Xubuntu and Kali Linux. It is worth mentioning that we also tried to use a Ubuntu GNOME OS, virtualized via VMWare on Windows 10, but this option was soon discarded as VMWare does not provide the drivers for Bluetooth Low Energy.

The software at our disposal included the builtin Linux commands, as well as Wireshark and Android apps (namely BLEScanner and nRFCon-

1. Introduction

nect). As we will see, we also tested some open-source tools available from Github: bleah, btlejuice and gattacker.

Chapter 2

Bluetooth Low Energy Specification

In this chapter we briefly report the main technical characteristics of the Bluetooth Low Energy Personal-Area-Network technology. Our main reference is the Core Specification 5.0 available on the official website.

2.1 Network Topology and Devices

Devices can be divided into three categories: Advertisers, Scanners and Initiators. Communication has to be started by an initiator device following an *advertisement connectable packet* (ADV_IND). Advertisement is performed on the primary channels, while bidirectional communication happens on one of the 37 secondary channels, decided during the connection procedure. When a connection is established, the initiator and the advertiser respectively become the master and slave devices; while the former can be involved in more than one communication, the slave device can belong to a single *piconet* at a time. In fact, it is not possible to have a BLE device paired with more than one "master" device at the same time.

Advertising may also be *non-connectable* (ADV_NONCONN_IND): the LE device periodically sends its data on the main channel for every scanner to read. This is really convenient in terms of implementation, but it also represent the least secure solution, as data is sent in clear text.

On the whole, the Specification defines six different advertising packets, among which we also report the request for additional information from the advertisement (SCAN_REQ), it having a direct corresponding bash command.

2.2 Decypher Advertising Packets

Before considering Man-In-The-Middle techniques, we show how it is possible to intercept data from advertising devices, mentioned in the previous

chapter.

For this experiment, we used the STM IoT node and tested it on both our Linux distributions. The board simply worked as a thermometer, measuring the temperature in the environment and broadcasting it as a non-connectable advertising packet.

Bibliography