


Elective Course

Course Code: CS4103

Autumn 2025-26



Lecture #31

Artificial Intelligence for Data Science

Week-9:

Introduction to Probabilistic Reasoning [Part-III]

Exploring Probabilistic Reasoning using pgmpy

Course Instructor:

Dr. Monidipa Das

Assistant Professor

Department of Computational and Data Sciences

Indian Institute of Science Education and Research Kolkata, India 741246




Define the network structure



```
from pgmpy.models import DiscreteBayesianNetwork
from pgmpy.factors.discrete import TabularCPD

# Define the network structure.
cancer_model = DiscreteBayesianNetwork(
    [
        ("Pollution", "Cancer"),
        ("Smoker", "Cancer"),
        ("Cancer", "Xray"),
        ("Cancer", "Dyspnoea"),
    ]
)
```



Define the Conditional Probability Distributions



```
cpd_poll = TabularCPD(variable="Pollution",variable_card=2,values=[[0.99], [0.01]])
cpd_smoke = TabularCPD(variable="Smoker", variable_card=2, values=[[0.3], [0.7]])

cpd_cancer = TabularCPD(
    variable="Cancer",
    variable_card=2,
    values=[[0.97, 0.05, 0.001, 0.02], [0.03, 0.95, 0.999, 0.98]],
    evidence=["Smoker", "Pollution"],
    evidence_card=[2, 2],
)

cpd_xray = TabularCPD(
    variable="Xray",
    variable_card=2,
    values=[[0.9, 0.2], [0.1, 0.8]],
    evidence=["Cancer"],
    evidence_card=[2],
)
```

Dr. Monidipa Das, Department of CDS, IISER Kolkata

Defining Conditional Probability Distributions (CPDs)



```
cpd_dysp = TabularCPD(
    variable="Dyspnoea",
    variable_card=2,
    values=[[0.65, 0.3], [0.35, 0.7]],
    evidence=["Cancer"],
    evidence_card=[2],
)

# Add the CPDs to the model.
cancer_model.add_cpds(cpd_poll, cpd_smoke, cpd_cancer, cpd_xray, cpd_dysp)

# Check if the model is correctly defined.
print(cancer_model.check_model())

#View nodes, edges, cpds
print(cancer_model.nodes)
print(cancer_model.edges)
for cpd in cancer_model.get_cpds():
    print(cpd)
```

```
True
['Pollution', 'Cancer', 'Smoker', 'Xray', 'Dyspnoea']
[('Pollution', 'Cancer'), ('Cancer', 'Xray'), ('Cancer', 'Dyspnoea'), ('Smoker', 'Cancer')]
```

Dr. Monidipa Das, Department of CDS, IISER Kolkata

Printing CPDs



+-----+-----+-----+-----+-----+				
	Pollution(0)		0.99	
+-----+-----+-----+-----+-----+				
	Pollution(1)		0.01	
+-----+-----+-----+-----+-----+				
	Smoker(0)		0.3	
+-----+-----+-----+-----+-----+				
	Smoker(1)		0.7	
+-----+-----+-----+-----+-----+				
	Smoker		Smoker(0)	
	Smoker		Smoker(0)	
	Smoker		Smoker(1)	
	Smoker		Smoker(1)	
+-----+-----+-----+-----+-----+				
	Pollution		Pollution(0)	
	Pollution		Pollution(1)	
	Pollution		Pollution(0)	
	Pollution		Pollution(1)	
+-----+-----+-----+-----+-----+				
	Cancer(0)		0.97	
	Cancer(0)		0.05	
	Cancer(0)		0.001	
	Cancer(0)		0.02	
+-----+-----+-----+-----+-----+				
	Cancer(1)		0.03	
	Cancer(1)		0.95	
	Cancer(1)		0.999	
	Cancer(1)		0.98	
+-----+-----+-----+-----+-----+				

	Cancer		Cancer(0)
	Cancer		Cancer(1)
	Xray(0)		0.9
	Xray(0)		0.2
	Xray(1)		0.1
	Xray(1)		0.8
	Cancer		Cancer(0)
	Cancer		Cancer(1)
	Dyspnoea(0)		0.65
	Dyspnoea(0)		0.3
	Dyspnoea(1)		0.35
	Dyspnoea(1)		0.7

Dr. Monidipa Das, Department of CDS, IISER Kolkata


Visualizing Bayesian Network (BN)



```
import networkx as nx
import matplotlib.pyplot as plt
```

```
G=nx.DiGraph()
G.add_nodes_from(cancer_model.nodes)
G.add_edges_from(cancer_model.edges)
pos=nx.spring_layout(G,seed=888)
```

```
nx.draw_networkx_nodes(G, pos,node_size=1000,node_color='lightgreen')
nx.draw_networkx_labels(G, pos,font_size=10)
nx.draw_networkx_edges(G, pos, width=2,arrowsize=30)
plt.show()
```



Dr. Monidipa Das, Department of CDS, IISER Kolkata

Inference Generation in Discrete BN



```
from pgmpy.inference import VariableElimination
cancer_infer = VariableElimination(cancer_model)
```

```
# Computing the probability of Cancer given Smoker=1.
```

```
q = cancer_infer.query(variables=["Cancer"],
evidence={"Smoker": 1})
print(q)
```

Cancer	phi(Cancer)
Cancer(0)	0.0012
Cancer(1)	0.9988

```
# Computing the joint probability of Cancer and Dyspnoea
given Smoker=1
```

```
q = cancer_infer.query(variables=["Cancer", "Dyspnoea"],
evidence={"Smoker": 1})
print(q)
```

Cancer	Dyspnoea	phi(Cancer,Dyspnoea)
Cancer(0)	Dyspnoea(0)	0.0008
Cancer(0)	Dyspnoea(1)	0.0004
Cancer(1)	Dyspnoea(0)	0.2996
Cancer(1)	Dyspnoea(1)	0.6992

```
# Computing the MAP of Cancer given Smoker=1.
```

```
q = cancer_infer.map_query(variables=["Cancer"],
evidence={"Smoker": 1})
print(q)
```

```
0%|          | 0/1 [00:00<?, ?it/s]
0%|          | 0/1 [00:00<?, ?it/s]
{'Cancer': 1}
0%|          | 0/1 [00:00<?, ?it/s]
0%|          | 0/1 [00:00<?, ?it/s]
{'Cancer': 1, 'Dyspnoea': 1}
```

```
# Computing the MAP of Cancer and Dyspnoea given Smoker=1
```

```
q = cancer_infer.map_query(variables=["Cancer", "Dyspnoea"],
evidence={"Smoker": 1})
print(q)
```

Dr. Monidipa Das, Department of CDS, IISER Kolkata

Inference Generation in Discrete BN: MCMC



```
from pgmpy.sampling import GibbsSampling
```

```
# Initialize GibbsSampling with the model
```

```
gibbs_sampler = GibbsSampling(cancer_model)
```

```
samples = gibbs_sampler.sample(size=1000)
```

```
print(samples.head(10))
```

	Pollution	Cancer	Smoker	Xray	Dyspnoea
0	0	0	1	1	0
1	0	1	1	1	1
2	0	1	1	1	0
3	0	1	1	1	0
4	0	1	1	1	1
5	0	1	1	1	1
6	0	1	1	0	0
7	0	1	1	1	1
8	0	1	1	1	1
9	0	1	0	1	1

```
# Computing the probability of Cancer given Smoker=1.
```

```
cond_samples=samples.loc[samples['Smoker']==1]
cp=len(cond_samples.loc[cond_samples['Cancer']==1])
cn=len(cond_samples.loc[cond_samples['Cancer']==0])
print('P(Cancer=1|Smoker=1):',cp/len(cond_samples))
print('P(Cancer=0|Smoker=1):',cn/len(cond_samples))
```

```
P(Cancer=1|Smoker=1): 0.9959016393442623
P(Cancer=0|Smoker=1): 0.004098360655737705
```

Dr. Monidipa Das, Department of CDS, IISER Kolkata

Inference Generation in Discrete BN: MCMC



```
# Computing the joint probability of Cancer and Dyspnoea given Smoker=1
cpdp=len(cond_samples.loc[(cond_samples['Cancer']==1) &
(cond_samples['Dyspnoea']==1)])
cndp=len(cond_samples.loc[(cond_samples['Cancer']==0) &
(cond_samples['Dyspnoea']==1)])
cpdn=len(cond_samples.loc[(cond_samples['Cancer']==1) &
(cond_samples['Dyspnoea']==0)])
cndn=len(cond_samples.loc[(cond_samples['Cancer']==0) &
(cond_samples['Dyspnoea']==0)])
print('P(Cancer=1, Dyspnoea=1|Smoker=1):',cpdp/len(cond_samples))
print('P(Cancer=0, Dyspnoea=1|Smoker=1):',cndp/len(cond_samples))
print('P(Cancer=1, Dyspnoea=0|Smoker=1):',cpdn/len(cond_samples))
print('P(Cancer=0, Dyspnoea=0|Smoker=1):',cndn/len(cond_samples))
```

```
P(Cancer=1, Dyspnoea=1|Smoker=1): 0.6994535519125683
P(Cancer=0, Dyspnoea=1|Smoker=1): 0.001366120218579235
P(Cancer=1, Dyspnoea=0|Smoker=1): 0.296448087431694
P(Cancer=0, Dyspnoea=0|Smoker=1): 0.00273224043715847
```

Dr. Monidipa Das, Department of CDS, IISER Kolkata

BN Parameter Learning: MLE



```
samples = cancer_model.simulate(n_samples=int(1e3))
print(samples.head(10))

# Define a new model with the same structure as the Cancer model.
new_model = DiscreteBayesianNetwork(ebunch=cancer_model.edges())


print(new_model.nodes)
print(new_model.edges)
for cpd in new_model.get_cpds():
    print(cpd) #no CPD will be printed

from pgmpy.estimators import MaximumLikelihoodEstimator
# Initialize the estimator object.
mle_est = MaximumLikelihoodEstimator(model=new_model, data=samples)

# Estimate all the CPDs for `new_model`
all_cpds = mle_est.get_parameters()

# Add the estimated CPDs to the model.
new_model.add_cpds(*all_cpds)
for cpd in new_model.get_cpds():
    print(cpd)
```

```
0% | 0/5 [00:00<?, ?it/s]
Xray Pollution Dyspnoea Cancer Smoker
0 1 0 0 1 1
1 1 0 0 1 1
2 1 0 1 1 1
3 0 0 1 0 0
4 1 0 1 0 0
5 1 0 1 1 1
6 1 0 0 1 1
7 1 0 1 1 1
8 0 0 0 0 0
9 1 0 0 1 1
['Pollution', 'Cancer', 'Xray', 'Dyspnoea', 'Smoker']
[('Pollution', 'Cancer'), ('Cancer', 'Xray'), ('Cancer', 'Dyspnoea'), ('Smoker', 'Cancer')]
```



Dr. Monidipa Das, Department of CDS, IISER Kolkata

BN Parameter Learning: MLE



```
INFO:pgmpy: Datatype (N=numerical, C=Categorical
Unordered, O=Categorical Ordered) inferred from data:
{'Xray': 'C', 'Pollution': 'C', 'Dyspnoea': 'C',
'Cancer': 'C', 'Smoker': 'C'}
```

```
+-----+-----+
| Pollution(0) | 0.988 |
+-----+-----+
| Pollution(1) | 0.012 |
+-----+-----+
| Smoker(0) | 0.322 |
+-----+-----+
| Smoker(1) | 0.678 |
+-----+-----+
```

```
+-----+-----+-----+
| Cancer | Cancer(0) | Cancer(1) |
+-----+-----+-----+
| Dyspnoea(0) | 0.684887459807074 | 0.3193033381712627 |
+-----+-----+-----+
| Dyspnoea(1) | 0.31511254019292606 | 0.6806966618287373 |
+-----+-----+-----+
```

```
+-----+-----+-----+-----+
| Pollution | Pollution(0) | ... | Pollution(1) | Pollution(1) |
+-----+-----+-----+-----+
| Smoker | Smoker(0) | ... | Smoker(0) | Smoker(1) |
+-----+-----+-----+-----+
| Cancer(0) | 0.9748427672955975 | ... | 0.25 | 0.0 |
+-----+-----+-----+-----+
| Cancer(1) | 0.025157232704402517 | ... | 0.75 | 1.0 |
+-----+-----+-----+-----+
| Cancer | Cancer(0) | Cancer(1) |
+-----+-----+-----+
| Xray(0) | 0.909967845659164 | 0.19593613933236576 |
+-----+-----+-----+
| Xray(1) | 0.09003215434083602 | 0.8040638606676342 |
+-----+-----+-----+
```

Dr. Monidipa Das, Department of CDS, IISER Kolkata

BN Parameter Learning: Bayesian Estimator



```
# Define a new model with the same structure as the Cancer model.
new_model = DiscreteBayesianNetwork(ebunch=cancer_model.edges())
```

```
print(new_model.nodes)
print(new_model.edges)
for cpd in new_model.get_cpds():
    print(cpd) #no CPD will be printed
```

```
['Pollution', 'Cancer', 'Xray', 'Dyspnoea', 'Smoker']
[('Pollution', 'Cancer'), ('Cancer', 'Xray'),
 ('Cancer', 'Dyspnoea'), ('Smoker', 'Cancer')]
```

```
# Initialize the Bayesian Estimator
from pgmpy.estimators import BayesianEstimator
be_est = BayesianEstimator(model=new_model, data=samples)
```

```
# Estimate all the CPDs for `new_model`
all_cpds = mle_est.get_parameters()
```

```
# Add the estimated CPDs to the model.
new_model.add_cpds(*all_cpds)
for cpd in new_model.get_cpds():
    print(cpd)
```

Dr. Monidipa Das, Department of CDS, IISER Kolkata

BN Parameter Learning: Bayesian Estimator



```
INFO:pgmpy: Datatype (N=numerical, C=Categorical Unordered, O=Categorical
Ordered) inferred from data:
{'Xray': 'C', 'Pollution': 'C', 'Dyspnoea': 'C', 'Cancer': 'C', 'Smoker': 'C'}
```

```
+-----+
| Pollution(0) | 0.992 |
+-----+
| Pollution(1) | 0.008 |
+-----+
```

```
+-----+-----+
| Cancer      | Cancer(0)      | Cancer(1)      |
+-----+-----+
| Dyspnoea(0) | 0.6241379310344828 | 0.2887323943661972 |
+-----+-----+
| Dyspnoea(1) | 0.3758620689655172 | 0.7112676056338029 |
+-----+-----+
```

```
+-----+
| Smoker(0)   | 0.298 |
+-----+
| Smoker(1)   | 0.702 |
+-----+
```

```
+-----+-----+-----+
| Cancer | Cancer(0)      | Cancer(1)      |
+-----+-----+-----+
| Xray(0) | 0.9103448275862069 | 0.20422535211267606 |
+-----+-----+-----+
| Xray(1) | 0.0896551724137931 | 0.795774647887324 |
+-----+-----+-----+
```

```
+-----+-----+-----+-----+
| Pollution | Pollution(0)      | ... | Pollution(1) | Pollution(1) |
+-----+-----+-----+-----+
| Smoker    | Smoker(0)         | ... | Smoker(0)     | Smoker(1)     |
+-----+-----+-----+-----+
| Cancer(0) | 0.9763513513513513 | ... | 0.0           | 0.0           |
+-----+-----+-----+-----+
| Cancer(1) | 0.02364864864864865 | ... | 1.0           | 1.0           |
+-----+-----+-----+-----+
```

Dr. Monidipa Das, Department of CDS, IISER Kolkata

BN Structure Learning using Hill Climbing




```
# Learning the discrete variable Cancer model back
from pgmpy.estimators import HillClimbSearch
samples = cancer_model.simulate(n_samples=int(1e3))
```

```
est = HillClimbSearch(data=samples)
estimated_model =
DiscreteBayesianNetwork(est.estimate(scoring_method="k2",
max_indegree=4, max_iter=int(1e4)))
```

```
print(estimated_model.nodes)
print(estimated_model.edges)
```

```
G=nx.DiGraph()
G.add_nodes_from(estimated_model.nodes)
G.add_edges_from(estimated_model.edges)
pos=nx.spring_layout(G,seed=888)
nx.draw_networkx_nodes(G,
pos,node_size=1000,node_color='lightgreen')
nx.draw_networkx_labels(G, pos,font_size=10)
nx.draw_networkx_edges(G, pos, width=2,arrowsize=30)
plt.show()
```

```
['Xray', 'Pollution', 'Dyspnoea', 'Cancer', 'Smoker']
[('Pollution', 'Smoker'), ('Pollution', 'Cancer'), ('Pollution', 'Xray'),
('Cancer', 'Smoker'), ('Cancer', 'Xray'), ('Cancer', 'Dyspnoea')]
```



Dr. Monidipa Das, Department of CDS, IISER Kolkata

BN Structure Learning using Exhaustive Search



```

from pgmpy.estimators import ExhaustiveSearch
from pgmpy.estimators import BDeu
samples = cancer_model.simulate(n_samples=int(1e3))

# Initialize the BDeuScore scoring method
scoring_method = BDeu(data=samples)
# Initialize ExhaustiveSearch with data and scoring method
est = ExhaustiveSearch(data=samples, scoring_method=scoring_method)
# Estimate the best structure
best_model = DiscreteBayesianNetwork(est.estimate())
print(best_model.nodes)
print(best_model.edges)

G=nx.DiGraph()
G.add_nodes_from(best_model.nodes)
G.add_edges_from(best_model.edges)
pos=nx.spring_layout(G,seed=888)
nx.draw_networkx_nodes(G,
pos,node_size=1000,node_color='lightgreen')
nx.draw_networkx_labels(G, pos,font_size=10)
nx.draw_networkx_edges(G, pos, width=2,arrowsize=30)
plt.show()

```

['Cancer', 'Dyspnoea', 'Pollution', 'Smoker', 'Xray']
 [('Cancer', 'Dyspnoea'), ('Cancer', 'Xray'), ('Pollution', 'Cancer'), ('Smoker', 'Cancer')]

Dr. Monidipa Das, Department of CDS, IISER Kolkata

Linear Gaussian Bayesian Network



```

from pgmpy.models import LinearGaussianBayesianNetwork
from pgmpy.factors.continuous import LinearGaussianCPD

# Define the network structure.
cancer_modelc = LinearGaussianBayesianNetwork(
    [
        ("Pollution", "Cancer"),
        ("Smoker", "Cancer"),
        ("Cancer", "Xray"),
        ("Cancer", "Dyspnoea"),
    ]
)

# Define the CPDs.
cpd_poll = LinearGaussianCPD(variable="Pollution", beta=[0], std=1, evidence=[])
cpd_smoke = LinearGaussianCPD(variable="Smoker", beta=[0], std=1, evidence=[])
cpd_cancer = LinearGaussianCPD(
    variable="Cancer",
    beta=[0, 0.2, 0.4],
    std=1,
    evidence=["Pollution", "Smoker"],
)

```

Dr. Monidipa Das, Department of CDS, IISER Kolkata

Linear Gaussian Bayesian Network



```

cpd_xray = LinearGaussianCPD(
    variable="Xray",
    beta=[0, 0.3],
    std=1,
    evidence=["Cancer"],
)
cpd_dysp = LinearGaussianCPD(
    variable="Dyspnoea",
    beta=[0, 0.5],
    std=1,
    evidence=["Cancer"],
)

# Add the CPDs to the model.
cancer_modelc.add_cpds(cpd_poll, cpd_smoke, cpd_cancer, cpd_xray, cpd_dysp)

# Check if the model is correctly defined.
print(cancer_modelc.check_model())

for cpd in cancer_modelc.cpd:
    print(cpd)

```

```

True
P(Pollution) = N(0; 1)
P(Smoker) = N(0; 1)
P(Cancer | Pollution, Smoker) = N(0.2*Pollution +
0.4*Smoker + 0.0; 1)
P(Xray | Cancer) = N(0.3*Cancer + 0.0; 1)
P(Dyspnoea | Cancer) = N(0.5*Cancer + 0.0; 1)

```

Dr. Monidipa Das, Department of CDS, IISER Kolkata



Questions?

Dr. Monidipa Das, Department of CDS, IISER Kolkata