

Elective Course

Course Code: CS4103

Autumn 2025-26



## Lecture #32

# Artificial Intelligence for Data Science

## Week-9:

### Introduction to Probabilistic Reasoning [Part-IV]

Bayesian Network Inference, Parameter Learning, Structure Learning

Course Instructor:


Dr. Monidipa Das

Assistant Professor

Department of Computational and Data Sciences


Indian Institute of Science Education and Research Kolkata, India 741246

## Inference in Bayesian Networks



- Exact inference

- Inference by enumeration
- Inference by variable elimination



Simple query :

$$\mathbf{P}(B \mid j, m)$$

$$= \mathbf{P}(B, j, m) / P(j, m)$$

$$= \alpha \mathbf{P}(B, j, m)$$

$$= \alpha \sum_e \sum_a \mathbf{P}(B, e, a, j, m)$$



Rewrite full joint entries using product of CPT entries:

$$\mathbf{P}(B \mid j, m)$$


$$= \alpha \sum_e \sum_a \mathbf{P}(B) P(e) \mathbf{P}(a \mid B, e) P(j \mid a) P(m \mid a)$$

$$= \alpha \mathbf{P}(B) \sum_e P(e) \sum_a \mathbf{P}(a \mid B, e) P(j \mid a) P(m \mid a)$$

## Evaluation tree



$$\alpha \mathbf{P}(B) \sum_e P(e) \sum_a \mathbf{P}(a | B, e) P(j | a) P(m | a)$$



Dr. Monidipa Das, Department of CDS, IISER Kolkata

## Inference in Bayesian Networks



- Approximate inference

### Inference by stochastic simulation

Basic idea:

1. Draw  $N$  samples from a sampling distribution  $S$



2. Compute an approximate posterior probability  $\hat{P}$
3. Show this converges to the true probability  $P$

Dr. Monidipa Das, Department of CDS, IISER Kolkata

# Inference by stochastic simulation



## Direct Sampling

- **Basic sampling:** sampling with no evidence
- **Rejection sampling:** reject samples disagreeing with evidence
- **Likelihood weighting:** use evidence to weight samples

## Markov chain simulation

- **Markov chain Monte Carlo (MCMC):** sample from a stochastic process whose stationary distribution is the true posterior

Dr. Monidipa Das, Department of CDS, IISER Kolkata

# Approximate inference using MCMC



- “State” of network = current assignment to all of its variables
- Generate next state by sampling one var. given its Markov Blanket
- Sample each variable in turn, keeping evidence fixed

```

function GIBBS-ASK( $X, e, bn, N$ ) returns an estimate of  $P(X|e)$ 
  local vars:  $\mathbf{N}$ , a vector of counts for each value of  $X$ , initially zero
                $\mathbf{Z}$ , the nonevidence variables in  $bn$ 
                $\mathbf{x}$ , the current state of the network, initially copied from  $e$ 
  initialize  $\mathbf{x}$  with random values for the variables in  $\mathbf{Z}$ 
  for  $j = 1$  to  $N$  do
    for each  $Z_i$  in  $\mathbf{Z}$  do
      set the value of  $Z_i$  in  $\mathbf{x}$  by sampling from  $\mathbf{P}(Z_i \mid MB(Z_i))$ 
       $\mathbf{N}[x] \leftarrow \mathbf{N}[x] + 1$  where  $x$  is the value of  $X$  in  $\mathbf{x}$ 
  return NORMALIZE( $\mathbf{N}$ )
  
```

Dr. Monidipa Das, Department of CDS, IISER Kolkata

# MCMC example




To estimate  $P(\text{Rain} \mid \text{Sprinkler} = \text{true}, \text{WetGrass} = \text{true})$

1. Apply the Gibbs sampling algorithm with *Sprinkler* and *WetGrass* both fixed to *true*
2. Count number of times *Rain* is *true* and *false* in the samples

## Example:

Visit 100 states; 31 have *Rain* = *true*, 69 have *Rain* = *false*

$$\hat{P}(\text{Rain} \mid \text{Sprinkler} = \text{true}, \text{WetGrass} = \text{true}) \\ = \text{NORMALIZE}(\langle 31, 69 \rangle) = \langle 0.31, 0.69 \rangle$$




Dr. Monidipa Das, Department of CDS, IISER Kolkata

# Learning Parameters



- Parameters ( $\theta$ )
  - Probabilities in the CPTs for all the variables in the network
- Learning parameters
  - Infer  $\theta$  from data, given  $G$



Dr. Monidipa Das, Department of CDS, IISER Kolkata

# Learning Parameters



- $G$  is a given DAG over  $N$  variables
- Goal: Estimate  $\theta$  from i.i.d data  $D = X = (x_1, \dots, x_M)$ ,  
where  $M$  is the number of records  
Each record:  $x_m = \{x_m^1, x_m^2, \dots, x_m^N\}$
- Complete Observability (no missing values)

Dr. Monidipa Das, Department of CDS, IISER Kolkata

# Bayes' formula as touchstone




$$\text{prob}(\Theta|\mathcal{X}) = \frac{\text{prob}(\mathcal{X}|\Theta) \cdot \text{prob}(\Theta)}{\text{prob}(\mathcal{X})}$$

$$\text{posterior} = \frac{\text{likelihood} \cdot \text{prior}}{\text{evidence}}$$

Dr. Monidipa Das, Department of CDS, IISER Kolkata

# Parameter Estimation Methods



Dr. Monidipa Das, Department of CDS, IISER Kolkata

## Frequentist vs. Bayesian



Bayesian Method	Frequentist Method
Uses probabilities for both hypotheses and data	Never uses or gives the probability of a hypothesis (no prior or posterior)
Depends on the prior and likelihood of observed data	Depends on the likelihood for both observed and unobserved data.
Requires one to know or construct a 'subjective prior'	Does not require a prior.
Dominated statistical practice before the 20th century	Dominated statistical practice during the 20th century.
May be computationally intensive due to integration over many parameters	Tends to be less computationally intensive.

Dr. Monidipa Das, Department of CDS, IISER Kolkata

## MLE: Maximum Likelihood Estimator



- We seek that value for  $\Theta$  which maximizes the likelihood (i.e.  $prob(X|\Theta)$ )
- We denote such a value of  $\Theta$  by  $\hat{\Theta}_{ML}$
- $\hat{\Theta}_{ML}$  maximizes  $\prod_{\mathbf{x}_i \in \mathcal{X}} prob(\mathbf{x}_i|\Theta)$  (assuming independent observations)
- Simply,  $\hat{\Theta}_{ML}$  maximizes  $\mathcal{L} = \sum_{\mathbf{x}_i \in \mathcal{X}} \log prob(\mathbf{x}_i|\Theta)$
- Hence,

$$\hat{\Theta}_{ML} = \underset{\Theta}{\operatorname{argmax}} \mathcal{L} \quad \frac{\partial \mathcal{L}}{\partial \theta_i} = 0 \quad \forall \theta_i \in \Theta$$

Dr. Monidipa Das, Department of CDS, IISER Kolkata

## MAP: Maximum A Posteriori estimate



- We seek that value for  $\Theta$  which maximizes the posterior (i.e.  $prob(\Theta|X)$ )
- We denote such a value of  $\Theta$  by  $\hat{\Theta}_{MAP}$

$$\begin{aligned} \hat{\Theta}_{MAP} &= \underset{\Theta}{\operatorname{argmax}} prob(\Theta|\mathcal{X}) \quad \boxed{\hat{\Theta}_{MAP} = \underset{\Theta}{\operatorname{argmax}} \left( \sum_{\mathbf{x}_i \in \mathcal{X}} \log prob(\mathbf{x}_i|\Theta) + \log prob(\Theta) \right)} \\ &= \underset{\Theta}{\operatorname{argmax}} \frac{prob(\mathcal{X}|\Theta) \cdot prob(\Theta)}{prob(\mathcal{X})} \\ &= \underset{\Theta}{\operatorname{argmax}} prob(\mathcal{X}|\Theta) \cdot prob(\Theta) \\ &= \underset{\Theta}{\operatorname{argmax}} \prod_{\mathbf{x}_i \in \mathcal{X}} prob(\mathbf{x}_i|\Theta) \cdot prob(\Theta) \end{aligned}$$

Dr. Monidipa Das, Department of CDS, IISER Kolkata

# Bayesian Estimation



- $\hat{\Theta}_B$  maximizes full posterior

$$\text{prob}(\Theta|\mathcal{X}) = \frac{\text{prob}(\mathcal{X}|\Theta) \cdot \text{prob}(\Theta)}{\text{prob}(\mathcal{X})}$$

- The denominator in the Bayes' Rule cannot be ignored.
- The denominator, known as the [probability of evidence](#), is related to the other probabilities that make their appearance in the Bayes' Rule by

$$\text{prob}(\mathcal{X}) = \int_{\Theta} \text{prob}(\mathcal{X}|\Theta) \cdot \text{prob}(\Theta) d\Theta$$

Dr. Monidipa Das, Department of CDS, IISER Kolkata

# MLE vs. MAP vs. Bayesian Estimation



- MLE does NOT allow us to inject our prior beliefs about the likely values for  $\Theta$  in the estimation calculations.
- MAP allows for the fact that the parameter vector  $\Theta$  can take values from a distribution that expresses our prior beliefs regarding the parameters.
- Both MLE and MAP return only single and specific values for the parameter  $\Theta$ .
- Bayesian estimation, by contrast, calculates fully the posterior distribution  $\text{prob}(\Theta|X)$ .


Dr. Monidipa Das, Department of CDS, IISER Kolkata



# Learning Graph Structure



- Structure Learning:
  - inferring  $G$  and  $\theta$  from data



Dr. Monidipa Das, Department of CDS, IISER Kolkata

# Structural Learning Methods




- Constraint Based
  - Test independencies
  - Add edges according to the tests
- Search and Score
  - Define a selection criterion that measures goodness of a model
  - Search in the space of all models (or orders)
- Mix models (recent)
  - Test for almost all independencies
  - Search and scoring

Dr. Monidipa Das, Department of CDS, IISER Kolkata


## Search and Score



- Learning from the data itself
  - Space of possible structures
  - Scoring each structure



$$P(\theta|X) \propto P(\theta).P(X|\theta)$$



Dr. Monidipa Das, Department of CDS, IISER Kolkata


## Search and Score



$$\text{Find } \hat{\mathbf{G}} = \arg \max_G \text{Score}(\mathbf{G})$$

### ■ Heuristic search:

- Greedy local search
- Best-first search
- Simulated annealing



Dr. Monidipa Das, Department of CDS, IISER Kolkata

# Bayesian Score



- Main principle of the Bayesian approach

$$P(G | D) = \frac{P(D | G)P(G)}{P(D)}$$

Diagram labels:

- Marginal likelihood (points to  $P(D | G)$ )
- Prior over structures (points to  $P(G)$ )
- Marginal probability of Data (points to  $P(D)$ )

$P(D)$  does not depend on the network

**Bayesian Score:**  $Score_B(G : D) = \log P(D | G) + \log P(G)$

Dr. Monidipa Das, Department of CDS, IISER Kolkata



## Questions?

Dr. Monidipa Das, Department of CDS, IISER Kolkata