


Elective Course

Course Code: CS4103

Autumn 2025-26



Lecture #39

Artificial Intelligence for Data Science

Week-11:

MACHINE LEARNING (Part VII)

Perceptron and Neural Network

Course Instructor:

Dr. Monidipa Das

Assistant Professor


Department of Computational and Data Sciences

Indian Institute of Science Education and Research Kolkata, India 741246

Perceptron: Introduction (revisit)



- More accepted convention:




Dr. Monidipa Das, Department of CDS, IISER Kolkata

Points to Remember (revisit)






- Most real-world data is **not linearly separable** and will always contain some outliers



How do we implement functions that are not linearly separable?

Dr. Monidipa Das, Department of CDS, IISER Kolkata

Combining Many Linear Classifiers




Dr. Monidipa Das, Department of CDS, IISER Kolkata

Perceptron Network



- Any boolean function of n inputs can be represented by a network of perceptrons containing **1 hidden layer with 2^n perceptrons** and **one output layer containing 1 perceptron**
- Perceptron networks of these forms are called Multilayer Perceptrons (MLP)



Dr. Monidipa Das, Department of CDS, IISER Kolkata


Perceptron: Other Issues



- A hard threshold decides the output (logical 0 or 1)
- Optimization becomes difficult with many perceptrons
- We would like to change the input a little and see how the output changes (iterative methods)
- Desirable Property:**
 - Instead of a hard threshold, a smooth function that is efficient to differentiate
 - So that we can change the inputs a little, observe the corresponding small change in the output, hence compute gradient, etc.
- A perceptron with a smooth non-linear function** is equivalent to a **neuron in NN**

Dr. Monidipa Das, Department of CDS, IISER Kolkata


Neuron Model: Logistic Unit



Sigmoid (logistic) activation function: $g(z) = \frac{1}{1 + e^{-z}}$

Dr. Monidipa Das, Department of CDS, IISER Kolkata

Neural Network



Dr. Monidipa Das, Department of CDS, IISER Kolkata

Feedforward Neural Network Structures



- Model is associated with a directed acyclic graph describing how functions composed
 - E.g., functions $f^{(1)}, f^{(2)}, f^{(3)}$ connected in a chain to form

$$f(x) = f^{(3)} [f^{(2)} [f^{(1)}(x)]]$$
 - $f^{(1)}$ is called the first layer of the network
 - $f^{(2)}$ is called the second layer, etc
- These chain structures are the most commonly used structures of neural networks

Dr. Monidipa Das, Department of CDS, IISER Kolkata

What a Hidden Unit Does



- Accepts a vector of inputs x and computes an affine transformation

$$z = W^T x + b$$
- Computes an element-wise non-linear function $g(z)$
- Most hidden units are distinguished from each other by the choice of activation function $g(z)$
- Design of hidden units is an active research area

Dr. Monidipa Das, Department of CDS, IISER Kolkata

Logistic Sigmoid



- Earlier, most neural networks used logistic sigmoid activation



$$g(z) = \sigma(z)$$

- Or the hyperbolic tangent

$$g(z) = \tanh(z)$$

- These activation functions are closely related because

$$\tanh(z) = 2\sigma(2z) - 1$$



Dr. Monidipa Das, Department of CDS, IISER Kolkata


Rectified Linear Unit (ReLU)



- Rectified linear units use the activation function $g(z) = \max(0, z)$

– They are easy to optimize due to their similarity to linear units

- Only difference with linear units that they output 0 across half their domain
- Derivative is 1 everywhere that the unit is active



Dr. Monidipa Das, Department of CDS, IISER Kolkata

Generalizations of ReLU



- Three methods based on using a non-zero slope α_i when $z_i < 0$:


$$h_i = g(z, \alpha)_i = \max(0, z_i) + \alpha_i \min(0, z_i)$$

1. Leaky ReLU:

- fixes α_i to a small value like 0.01

2. Parametric ReLU or PReLU:

- treats α_i as a parameter



Dr. Monidipa Das, Department of CDS, IISER Kolkata

Is Differentiability necessary?



- Some hidden units are not differentiable at all input points
 - Rectified Linear Unit Function $g(z) = \max\{0, z\}$ is not differentiable at $z=0$
- Does this invalidate use in gradient-based learning?
- In practice gradient descent still performs well enough for these models to be used


Dr. Monidipa Das, Department of CDS, IISER Kolkata

Output Units

15

Types:


1. Linear units: no nonlinearity
2. Sigmoid units
3. Softmax units



Dr. Monidipa Das, Department of CDS, IISER Kolkata

Specific Application Architectures

16



Dr. Monidipa Das, Department of CDS, IISER Kolkata

Architecture for multi-class classification



Pedestrian




Car



Motorcycle



Truck



$$h_{\Theta}(\mathbf{x}) \in \mathbb{R}^K$$

We want:

$$h_{\Theta}(\mathbf{x}) \approx \begin{bmatrix} 1 \\ 0 \\ 0 \\ 0 \end{bmatrix}$$

when pedestrian

$$h_{\Theta}(\mathbf{x}) \approx \begin{bmatrix} 0 \\ 1 \\ 0 \\ 0 \end{bmatrix}$$

when car

$$h_{\Theta}(\mathbf{x}) \approx \begin{bmatrix} 0 \\ 0 \\ 1 \\ 0 \end{bmatrix}$$



when motorcycle

$$h_{\Theta}(\mathbf{x}) \approx \begin{bmatrix} 0 \\ 0 \\ 0 \\ 1 \end{bmatrix}$$


when truck

Dr. Monidipa Das, Department of CDS, IISER Kolkata

An Architecture for Game Design



| Maze Game Recording Output File | | | | | | | |
|---------------------------------|------|------|-------|-------------------------------|------|------|-------|
| Inputs: Wall Directions | | | | Outputs: Game Agent Direction | | | |
| UP | DOWN | LEFT | RIGHT | UP | DOWN | LEFT | RIGHT |
| 1 | 0 | 0 | 0 | 0 | 1 | 0 | 0 |
| 1 | 0 | 1 | 0 | 0 | 1 | 0 | 1 |
| 0 | 1 | 1 | 0 | 1 | 0 | 0 | 1 |
| 0 | 0 | 1 | 0 | 0 | 0 | 0 | 1 |



Dr. Monidipa Das, Department of CDS, IISER Kolkata

Back Propagation Network



- Networks associated with **back propagation algorithm**
- Applied to multilayer feed-forward networks consisting of processing elements with continuous differentiable activation functions
- Training is done in **three stages**
 - Feed-forward of the input training pattern
 - Calculation and back-propagation of the error
 - Updating weights




Dr. Monidipa Das, Department of CDS, IISER Kolkata

Back Propagation Network (BPN)




- Architecture



Dr. Monidipa Das, Department of CDS, IISER Kolkata

BPN Training



To be continued in the next lecture

Dr. Monidipa Das, Department of CDS, IISER Kolkata



Questions?

Dr. Monidipa Das, Department of CDS, IISER Kolkata