1. Write the commands to create the following directory hirarchy: -> DOS_Regdno -> DOSass1-> dir1

```
shubhi@Shubhangini:~$ mkdir DOS_9442
shubhi@Shubhangini:~$ cd DOS_9442
shubhi@Shubhangini:~/DOS_9442$ mkdir DOSass1
shubhi@Shubhangini:~/DOS_9442$ dc DOSass1
Command 'dc' not found, but can be installed with:
sudo apt install dc
shubhi@Shubhangini:~/DOS_9442$ cd DOSass1
shubhi@Shubhangini:~/DOS_9442/DOSass1$ mkdir dir1
shubhi@Shubhangini:~/DOS_9442/DOSass1$ cd dir1
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$
```

2. Write the commands to create another directory with name dir2 in directory DOSass1 and make dir2 as the current working directo

```
shubhi@Shubhangini:~$ cd DOS_9442
shubhi@Shubhangini:~/DOS_9442$ cd DOSass1
shubhi@Shubhangini:~/DOS_9442/DOSass1$ cd dir1
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ cd -
/home/shubhi/DOS_9442/DOSass1
shubhi@Shubhangini:~/DOS_9442/DOSass1$ mkdir dir2
shubhi@Shubhangini:~/DOS_9442/DOSass1$ cd mkdir
-bash: cd: mkdir: No such file or directory
shubhi@Shubhangini:~/DOS_9442/DOSass1$ cd dir2
shubhi@Shubhangini:~/DOS_9442/DOSass1$ cd dir2
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir2$
```

3. Write the command to delete the directory dir2, when DOS Regdno will be the current working directory.

```
shubhi@Shubhangini:~/DOS_9442$ cd DOSass1
shubhi@Shubhangini:~/DOS_9442/DOSass1$ cd dir2
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir2$ cd ../
shubhi@Shubhangini:~/DOS_9442/DOSass1$ cd ../
shubhi@Shubhangini:~/DOS_9442$
```

4. Write the command to create a file named as file1 using cat command inside dir1. Write your name, regdno, branch, semester and section in file1. Then display the content of the file.

```
shubhi@Shubhangini:~/DOS_9442$ cat> file1.txt
Q5>Name:Shubhangini
RegNo.: 2241019442
Branch: CSE
Sem: 5th
Sec: 31
^C
shubhi@Shubhangini:~/DOS_9442$ cat file1.txt
Q5>Name:Shubhangini
RegNo.: 2241019442
Branch: CSE
Sem: 5th
Sec: 31
shubhi@Shubhangini:~/DOS_9442$
```

5. Write the command to create a file named as file2 using cat command inside dir1. Write your semester wise SGPA in file2.

```
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ cat> file2.txt
Q5)Previous was Q4
Sem1: 8
Sem2: 9
Sem3: 9.48
Sem4: 9.66
^C
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ cat file2.txt
Q5)Previous was Q4
Sem1: 8
Sem2: 9
Sem3: 9.48
Sem4: 9.66
```

6. Create a file named as file3 storing content of file1 merged with content of file2.

```
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ cat>file1.txt
This is my File1.
^C
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ cat>file2.txt
This is my File2.
^C
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ cat file1.txt file2.txt>file3.txt
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ cat file3.txt
This is my File1.
This is my File2.
```

7. Write the command to rename file2 as markinfo. (mv – to rename)

```
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ mv file2.txt markinfo
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ ls
file1.txt file3.txt markinfo
```

8. Write the command to copy the content of file1 to reginfo. (cp-Copy)

```
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ cp file1.txt regInfo shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ cat regInfo This is my File1.
```

9. Write the command to display the inode (index Node) values of file1, markinfo, reginfo.

```
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ ls -i 46446 file1.txt 46447 file3.txt 46445 markinfo 46448 regInfo
```

10. Write the command to delete file1. (rm – to remove/delete)

```
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ rm file1.txt
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ ls
file3.txt markinfo regInfo
```

11. Write the command to count the number of lines, words, characters in markinfo.(wc - wordcont)

```
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ wc -l markinfo 1 markinfo
```

12. Write the command to create a file named as Personalinfo inside dir1. Write your name, regdno, address in the file.

```
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ cat>PersonalInfo.txt
Name: Shubhangini
Reg : 2241019442
Add : Jagamara
^C
```

13. Write the command to display the content of markinfo in reverse order.

Command: sort -r filename.txt

```
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ cat>markInfo.txt
1
2
3
4
5
^C
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ sort -r markInfo.txt
5
4
3
2
1
```

14. Check the output of the following command: cmp reginfo personalinfo diff reginfo personalinfo

```
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ cat>regInfo.txt
This is RegInfo
Thank You.^C
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ cat>PerInfo.txt
This is Personal Info
Thank You.^C
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ cmp regInfo PerInfo
cmp: PerInfo: No such file or directory
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ cmp regInfo.txt PerInfo.txt
regInfo.txt PerInfo.txt differ: byte 9, line 1
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ diff regInfo.txt PerInfo.txt
1c1
< This is RegInfo
---
> This is Personal Info
```

15) Write a command to count the number of files in the current working directory and display that number.

```
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ ls | wc -l 7
```

16) Write a command to include all the file names present in a current working directory in a file named as filelist without causing filelist to be included in the names.

```
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ ls | grep -v "FileList">FileList
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ cat FileList
PerInfo.txt
PersonalInfo.txt
file3.txt
markInfo.txt
markinfo
regInfo
regInfo
```

17. Write a command to give write permission to all the users of file reginfo.

```
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$    chmod a+w regInfo.txt
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ ls -l
total 32
-rw-r--r-- 1 shubhi shubhi 81 Jan
                                   7 18:22 FileList
-rw-r--r-- 1 shubhi shubhi 22 Jan
                                   7 18:15 PerInfo.txt
                                   7 17:59 PersonalInfo.txt
-rw-r--r-- 1 shubhi shubhi 50 Jan
   -r--r-- 1 shubhi shubhi 36 Jan
                                   7 17:49 file3.txt
   ·r--r-- 1 shubhi shubhi 10 Jan
                                   7 18:11 markInfo.txt
-rw-r--r-- 1 shubhi shubhi 18 Jan
                                   7 17:49 markinfo
                                   7 17:52 regInfo
-rw-r--r-- 1 shubhi shubhi 18 Jan
-rw-rw-rw- 1 shubhi shubhi 16 Jan
                                   7 18:14 regInfo.txt
```

18. Write a command to discard write permission from group users group users of file reginfo.

```
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ chmod g-w regInfo.tx
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ ls -l
total 32
              shubhi shubhi 81 Jan
-rw-r--r--
                                      7 18:22 FileList
              shubhi shubhi 22 Jan
                                         18:15 PerInfo.txt
-rw-r--r--
            1
rw-r--r-- 1 shubhi shubhi 50 Jan
                                         17:59 PersonalInfo.txt
              shubhi shubhi 36 Jan
                                         17:49 file3.txt
-rw-r--r-- 1
-rw-r--r-- 1 shubhi shubhi 10 Jan
                                         18:11 markInfo.txt
-rw-r--r-- 1 shubhi shubhi 18 Jan
                                      7 17:49 markinfo
rw-r--r-- 1 shubhi shubhi
                             18 Jan
                                         17:52 regInfo
                                      7 18:14 regInfo.txt
-rw-r--rw- 1 shubhi shubhi 16 Jan
```

19. Write the command to set rwx permissions for all the users of file reginfo.

- 7 for the owner (read, write, execute).
- 7 for the group (read, write, execute).
- 7 for others (read, write, execute).

```
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ chmod 777 regInfo.txt
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ ls -l
total 32
-rw-r--r-- 1 shubhi shubhi 81 Jan
                                   7 18:22 FileList
-rw-r--r-- 1 shubhi shubhi 22 Jan
                                   7 18:15 PerInfo.txt
-rw-r--r-- 1 shubhi shubhi 50 Jan
                                   7 17:59 PersonalInfo.txt
                                   7 17:49 file3.txt
-rw-r--r-- 1 shubhi shubhi 36 Jan
-rw-r--r-- 1 shubhi shubhi 10 Jan
                                   7 18:11 markInfo.txt
                                   7 17:49 markinfo
-rw-r--r-- 1 shubhi shubhi 18 Jan
                                   7 17:52 regInfo
rw-r--r-- 1 shubhi shubhi 18 Jan
-rwxrwxrwx 1 shubhi shubhi 16 Jan
                                   7 18:14 regInfo.txt
```

20. Differentiate between following commands:

| Command | Execution Style | Output |
|--------------|-----------------------|---|
| date; pwd | Independent execution | Displays the date, then the current directory |
| `date; pwd | wc -l` | Counts lines only from pwd |
| `(date; pwd) | wc -l` | Groups and counts both commands |

```
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ date;pwd
Tue Jan 7 18:29:58 UTC 2025
/home/shubhi/DOS_9442/DOSass1/dir1
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ date;pwd|wc -l
Tue Jan 7 18:30:12 UTC 2025
1
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ (date;pwd)|wc -l
2
```

21. Interpret the output of the following commmands:

```
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ echo *
FileList PerInfo.txt PersonalInfo.txt file3.txt markInfo.txt markinfo
regInfo regInfo.txt
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ echo ***
FileList PerInfo.txt PersonalInfo.txt file3.txt markInfo.txt markinfo
regInfo regInfo.txt
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ echo '***'
***
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ echo \***
***
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ echo \**\*
***
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ echo \*\*\*
***
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ echo */*
*/*
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ echo Don't do this
> Hey its Shubhangini
> ^C
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ echo Hello # WOrld
shubhi@Shubhanqini:~/DOS_9442/DOSass1/dir1$ echo "Hello # WOrld"
Hello # WOrld
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ echo date
date
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ echo 'date'
date
shubhi@Shubhangini:~/DOS_9442/DOSass1/dir1$ echo 'date'
Tue Jan 7 18:35:20 UTC 2025
```

DOS LAB ASSIGNMENT- 02

1. Write a shell script named as prog for merge the content of files a.txt, b.txt, and c.txt sort them and save the result in a file called result and display the sorted output on the screen.

```
shubhi@Shubhangini:~/DOS_9442$ cat > a.txt
Kumari
^C
shubhi@Shubhangini:~/DOS_9442$ cat > b.txt
Shubhangini
^C
shubhi@Shubhangini:~/DOS_9442$ cat > c.txt
SuperWomen
^C
shubhi@Shubhangini:~/DOS_9442$ sort -n a.txt b.txt c.txt>result
shubhi@Shubhangini:~/DOS_9442$ cat result
Kumari
Shubhangini
SuperWomen
```

2. Write a shell script named as systeminfo that will display the information about the login name of the user, name of the Unix system used by the user, type of the SHELL, Path of current working directory of the user and list of file contain in current working directory.

```
shubhi@Shubhangini:~/DOS_9442$ nano systeminfo.sh
shubhi@Shubhangini:~/DOS_9442$ chmod a+x systeminfo.sh
shubhi@Shubhangini:~/DOS_9442$ ./systeminfo.sh
Login User : shubhi
Unix System: GNU/Linux
Shell type: /bin/bash
PWD: /home/shubhi/DOS_9442
No. of file in thr directory :
total 28
                                                              GNU nano 7.2
                                                                                           systeminfo.sh
drwxr-xr-x 4 shubhi shubhi 4096 Jan
                                      7 17:29 DOSass1
                                                                  "Login User : $USER"
                                                             echo
-rw-r--r-- 1 shubhi shubhi
                                      7 19:12 a.txt
                              8 Jan
                                                             echo
                                                                  "Unix System: $(uname -o)"
-rw-r--r-- 1 shubhi shubhi
                              12 Jan
                                      7 19:12 b.txt
                                                             echo "Shell type: $SHELL"
echo "PWD: $PWD"
                                      7 19:12 c.txt
                              11 Jan
-rw-r--r-- 1 shubhi shubhi
-rw-r--r-- 1 shubhi shubhi
                                      7
                              68
                                        17:42 file1.txt
                                 Jan
                                                             echo "No. of file in thr directory :"
                                      7 19:13 result
                              31
-rw-r--r-- 1 shubhi shubhi
                                 Jan
                                      7 19:35 systeminfo.sh
-rwxr-xr-x 1 shubhi shubhi
                             146
                                Jan
```

3. Write a shell script named as dtcal for displaying both the system date and calendar for specific month, say march 2022, in the given format:-Date: specific date Calender: current calender.

```
shubhi@Shubhangini:~/DOS_9442$ nano dtcl.sh
shubhi@Shubhangini:~/DOS_9442$ chmod a+x dtcl.sh
shubhi@Shubhangini:~/DOS_9442$ ./dtcl.sh
Date: Tue Jan 7 19:50:47 UTC 2025
Calender:
               March 2022
Su Mo Tu We Th Fr Sa
       1
          2 3
               4 5
    7
         9 10 11 12
6
      8
13 14 15 16 17 18 19
                                                  echo "Date: $(date)"
20 21 22 23 24 25 26
                                                  echo "Calender: $(cal 03 2022)"
  28 29 30 31
                                                  ls -l
```

4. Write a shell script named as nvwc which will display the filename and linecount, wordcount and char count of the file dtcal in the following format: Filename: dtcal Line count: - Word count: - Charcout: -

```
hubhi@Shubhangini:<mark>~/DOS_9442$ nano nvwc.sh</mark>
File="dtcl"
                               shubhi@Shubhangini:~/DOS_9442$ chmod a+x nvwc.sh
lc=\$(wc -l < "\$File")
                               shubhi@Shubhangini:~/DOS_9442$ ./nvwc.sh
         -w < "$File")
wc=$(wc
                               ./nvwc.sh: line 2: dtcl: No such file or director
./nvwc.sh: line 3: dtcl: No such file or director
         -c < "$File")
cc=$(wc
                               ./nvwc.sh: line 4: dtcl: No such file or director
echo "File Name: $File"
                               File Name: dtcl
echo "Line Count: $lc"
echo "Word Count: $wc"
                               Line Count:
                               Word Count:
echo "Char count: $cc"
                               Char count:
```

Write a shell script named as nvwc2 which will display the filename and linecount, word count and char count of 5. any file given as argument to nvwc2 in the following format: filename linecount, wordcount, charcount file1 - - -

```
File="$1"
lc=\$(wc -l < "\$File")
wc=\$(wc -w < "\$File")
cc=\$(wc -c < | \$File")
echo "File Name: $File"
echo "Line Count: $lc"
echo "Word Count: $wc"
echo "Char Count: $cc"
                             Same as Q4
```

6. Write a shell script named as darg to display the total number of command line arguments along with the first two arguments. -Modify the script to display all the arguments.

```
GNU nano 7.2
echo "Total Number of args:
echo "1st arg: ${1: -None}"
echo "2nd arg: ${2: -None}"
echo "All Args: $@"
shubhi@Shubhangini:~/DOS_9442$ nano darg.sh
shubhi@Shubhangini:~/DOS_9442$ chmod a+x darg.sh
shubhi@Shubhangini:~/DOS_9442$ ./darg.sh arg1 arg2 arg3
Total Number of args: 3
1st arg: arg1
2nd arg: arg2
All Args: arg1 arg2 arg3
```

7. Write a shell script named as ndisp that will take three command line arguments specifying the value of n, m and a filename and display the first n number of lines and last m number of lines of the file given as argument.

```
shubhi@Shubhangini:~/DOS_9442$ nano ndisp.sh
                                    shubhi@Shubhangini:~/DOS_9442$ chmod a+x ndisp.sh
                                    shubhi@Shubhangini:~/DOS_9442$ cat>myFile
                                    1
                                    2
                                    3
                                    Hey
                                    Shubhi
                                    5
                                    ^C
  GNU nano 7.2
                                    shubhi@Shubhangini:~/DOS_9442$ ./ndisp.sh 2 4 myFile
n="$1"
                                    First 2 lines of myFile:
m="$2"
file="$3"
echo "First $n lines of $file:"
                                    Last 4 lines of myFile:
head -n "$n" "$file"
                                    Hey
echo "Last $m lines of $file:"
                                    Shubhi
tail -n "$m" "$file"
```

Laboratory Assignments 3 Subject: Design Principles of Operating Systems

Subject code: CSE 3249

Assignment 3: Shell Programming using user defined variables, arithmetic operators, conditional statements.

1. Write a shell script **iaop** to perform integer arithmetic on two numbers, where the value of the two numbers will be given during runtime.

```
GNU nano 8.1

echo "enter two numbers"

read num1

read num2

sum=$(($num1 + $num2))

echo "Sum: $sum"

diff=$(( $num1 - $num2))

echo "Difference: $diff"

prod=$(($num1 * $num2))

echo "Product: $prod"

quo=$(($num1 / $num2))

echo "Quotient: $quo"

rem=$(($num1 % $num2))

echo "Remainder: $rem"
```

2. Write a shell script **faop** to perform floating point arithmetic on two numbers, where the value of the two numbers will be given during runtime.

```
GNU nano 8.1

cho "enter two numbers"
read num1
read num2

sum=$(echo "scale=2; $num1 + $num2"| bc)
echo "Sum: $sum"
diff=$(echo "scale=2; $num1 - $num2"| bc)
echo "Difference: $diff"
prod=$(echo "scale=2; $num1 * $num2"| bc)
echo "Product: $prod"
quo=$(echo "scale=2; $num1 / $num2"| bc)
echo "Quotient: $quo"
rem=$(echo "scale=2; $num1 % $num2"| bc)
echo "Remainder: $rem"
```

3. Ramesh's basic salary is input through the keyboard. His dearness allowance is 40% of basic salary, and house rent allowance is 20% of basic salary. Write a program to calculate his gross salary.

```
(munu kali) - [~/Dos/assgn1]
$ nano salary.sh

(munu kali) - [~/Dos/assgn1]
$ chmod +x salary.sh

(munu kali) - [~/Dos/assgn1]
$ ./salary.sh
enter ramesh's basic salary
20000
Your dearness allowance is: 8000.00
Your house rent allowance is: 4000.00
Your gross salary is: 32000.00
```

```
GNU nano 8.1
echo "enter ramesh's basic salary"
read bas_sal
DA=$(echo "scale=2; 0.40 * $bas_sal"| bc)
echo "Your dearness allowance is: $DA"
HRA=$(echo "scale=2; 0.20 * $bas_sal"| bc)
echo "Your house rent allowance is: $HRA"
gross=$(echo "scale=2; $bas_sal + $DA + $HRA" | bc)
echo "Your gross salary is: $gross"
```

4. If a five digit number is input given through the keyboard during runtime, write a program to calculate the sum of its digits.

```
(munu® kali)-[~/Dos/assgn1]
$ chmod +x sumofdigits.sh

(munu® kali)-[~/Dos/assgn1]
$ nano sumofdigits.sh

(munu® kali)-[~/Dos/assgn1]
$ chmod +x sumofdigits.sh

(munu® kali)-[~/Dos/assgn1]
$ ./sumofdigits.sh

Enter a five digit number
12345
Sum : 15
```

```
GNU nano 8.1

Kali Linux mo Kali Tools mo Kali Does mo Kali Forums mo Kali NetHunter mo Exploit DB

echo "Enter a five digit number"

read n

sum=0

while [ $n -gt 0 ]; do

r=$(($n%10))

sum=$(($sum + $r))

n=$(($n/10))

done

echo "Sum : $sum"
```

5. If cost price and selling price of an item is input through the keyboard, write a program to determine whether the seller has made profit or incurred loss. Also determine how much profit was made or loss incurred.

```
(munu@kali)-[~/Dos/assgn1]
$ nano profitloss.sh

(munu@kali)-[~/Dos/assgn1]
$ chmod +x profitloss.sh

(munu@kali)-[~/Dos/assgn1]
$ ./profitloss.sh
enter cost price
200
enter selling price
300
The seller has made a profit of : 100
profit percentage: 50.00 %
```

```
GNU nano 8.1
                                                  profitloss.sh
<mark>e</mark>cho "enter cost price"
read CP
echo "enter selling price"
read SP
profit=$((SP-CP))
loss=$((CP-SP))
if [ $profit -gt 0 ]; then
echo "The seller has made a profit of : $profit"
profit per=$(echo "scale=2; $profit * 100 / $CP" | bc )
echo "profit percentage: $profit_per %"
elif [ $loss -gt 0 ]; then
echo "The seller has made a loss"
loss_per=$(echoo"scale=2; $loss * 100 / $CP" | bc )
echo "Loss percentage: $loss_per %"
else
echo "neither profit nor loss"
```

6. Write a shell script which receives any year from the keyboard and determines, whether the year is a leap year or not. If no argument is supplied the current year should be assumed.

```
GNU nano 8.1

#!/bin/bash
echo "Enter a year : "
read year
if (( ($year % 4 = 0 & $year % 100 ≠ 0) || $year % 400 = 0 )); then
echo "$year is a leap year . "
else
echo "$year is not a leap year . "
```

7. Write a shell script **allow** that will display a message to enter internal mark and percentage in attendance, if the entered mark is greater than equal to 20 and entered percentage in attendance is greater that equal to 75 then display the message Allowed for Semester otherwise display the message Not allowed.

8. Write a shell script **small3** that will compare three numbers passed as command line arguments and display the smallest one.

```
GNU nano 8.1

cho "Enter Number: "
read num1

cho "Enter Number: "
read num2

cho "Enter Number: "
read num3

if [ $num1 -le $num2 ] && [ $num1 -le $num3 ]; then
        echo "Smallest: $num1 "

elif [ $num2 -le $num1 ] && [ $num2 -le $num3 ]; then
        echo "Smallest: $num2 "

else
        echo "Smallest: $num3 "

fi
```

- 9. Write a shell script **check_char** which will display one message to enter a character and according to the character entered it will display appropriate message from the following options:
 - You entered a lower case alphabet
 - You entered an upper case alphabet.
 - You have entered a digit.
 - You have entered a special symbol.
 - You have entered more than one character.

```
(munu kali) - [~/Dos/assgn1]
$ nano check_char.sh

(munu kali) - [~/Dos/assgn1]
$ chmod +x check_char.sh

(munu kali) - [~/Dos/assgn1]
$ ./check_char.sh
Enter A Character:
A
It is of Upper Case
```

10. Write a shell script **class_time** which will display one message to enter a day and according to the day entered it will display the DOS class time along with the room information or the message "No class on day name" or "Holiday" for Sunday.

```
(munu kali) - [~/Dos/assgn1]
$ nano class_time.sh

(munu kali) - [~/Dos/assgn1]
$ chmod +x class_time.sh

(munu kali) - [~/Dos/assgn1]
$ ./class_time.sh
Enter A Day:
monday
DOS class at Room No. 109 at 11:30
```

```
GNU nano 8.1
                                                              class time.sh
echo "Enter A Day:
read day
case "$day" in
   "monday" | "MONDAY")
       echo "DOS class at Room No. 109 at 11:30"
    "tuesday" | "TUESDAY")
       echo "DOS class at Room No. 109 at 10:00"
    "wednesday" | "WEDNESDAY")
       echo "DOS class at Room No. 109 at 12:00"
    "thursday" | "THURSDAY")
       echo "DOS class at Room No. 108 at 09:00"
    "friday" | "FRIDAY")
       echo "DOS class at Room No. 110 at 09:30"
    "saturday" | "SATURDAY")
       echo "DOS class at Room No. 110 at 03:00"
    "sunday" | "SUNDAY")
       echo "Holiday"
       echo "Invalid Day"
        ;;
esac
```

11. Write a shell script **filechk** that will take two file names as command line arguments, and check whether the content of two files are same or not . If contents of two files are same, then it will display the message: Files filename1 and filename2 have same content.

then delete the second file

and display the message: So filename2 is deleted.

Otherwise display the message: Files filename1 and filename2 have different content.

12. Write a shell script **calculator** that will take three command line arguments, where the first argument will specify the first operand, second argument will specify the operator and the third argument will specify the second operand and display the output of the arithmetic operation specified in the following format: op1 operator op2 = result.

If the arguments will be passed in any other sequence, it will display the message:

"Invalid input"

Enter input in following format: op1 operator op2

The symbols to be used for different operators are as follows:

Addition: + Subtraction:
Multiplication: x Division: /

Modulo: % Exponent: '

```
calculator.sh *
GNU nano 8.1
#!/bin/bash
op1=$1
operator=$2
op2=$3
case "$operator" in
   +)
        result=$(echo "$op1 + $op2" | bc -l)
    -)
        result=$(echo "$op1 - $op2" | bc -l)
    x)
        result=$(echo:"$op1 * $op2" | bc -l)
        ;;
    /)
        if [ "$op2" = "0" ]; then
            echo "Error: Division by zero is not allowed"
            exit 1
        result=$(echo "$op1 / $op2" | bc -l)
    %)
        result=$(echo "$op1 % $op2" | bc)
        ;;
    ^)
        result=$(echo "$op1 ^ $op2" | bc -l)
    *)
        echo "Invalid input: Unsupported operator"
        echo "Supported operators are: +, -, x, /, %, ^"
        exit 1
        ;;
echo "$op1 $operator $op2 = $result"
```

Laboratory Assignments 4

Subject: Design Principles of Operating Systems

Subject code: CSE 3249

Assignment 4: Familiarization with Process Management in Linux environment.

Objective of this Assignment:

- To trace the different states of a process during its execution.
- To learn the use of different system calls such as (fork(),vfork(),wait(),execl()) for process handling in Unix/Linux environment.
- 1. Write a C program to create a child process using fork() system call. The child process will print the message "Child" with its process identifier and then continue in an indefinite loop. The parent process will print the message "Parent" with its process identifier and then continue in an indefinite loop.
 - a) Run the program and trace the state of both processes.
 - b) Terminate the child process. Then trace the state of processes.
 - c) Run the program and trace the state of both processes. Terminate the parent process. Then trace the state of processes.
 - d) Modify the program so that the parent process after displaying the message will wait for child process to complete its task. Again run the program and trace the state of both processes.
 - e) Terminate the child process. Then trace the state of processes.
- 2. Trace the output of the following codes:

```
a) int main()
{
    if(fork()==0)
    printf("1");
    else
    printf("2");
    printf("3");
    return 0;
}

b) int main()
{
    if(vfork()==0)
    {
        printf("1");
        _exit(0);
    }
    else
    printf("2");
    printf("2");
    printf("3");
}
```

```
c) int main()
                                                 d) int main()
pid t pid;
                                                 pid t pid;
                                                  int i=5;
int i=5;
pid=fork();
                                                 pid=vfork();
i=i+1;
                                                  i=i+1;
if(pid==0)
                                                 if(pid==0)
printf("Child: %d",i);
                                                 printf("Child: %d",i);
                                                  exit(0);
else
                                                  else
wait(NULL);
                                                 printf("Parent: %d",i);
printf("Parent: %d",i);
return 0;
                                                 return 0;
e) int main()
                                                 f) int main()
pid_t pid;
                                                 pid_t pid;
int i=5;
                                                  int i=5;
pid=fork();
                                                 pid=vfork();
if(pid==0)
                                                 if(pid==0)
i=i+1;
                                                  i=i+1;
printf("Child: %d",i);
                                                 printf("Child: %d",i);
                                                  _exit(0);
else
                                                 else
wait(NULL);
printf("Parent: %d",i);
                                                 printf("Parent: %d",i);
return 0;
                                                 return 0;
```

```
g) int main()
{
    int i=5;
    if(fork()==0)
    {
    printf("Child: %d",i);
    }
    else
    {
    printf("Parent: %d",i);
    }
    return 0;
}

h) int main()
{
    int i=5;
    if(vfork()==0)
    {
    printf("Child: %d",i);
    _exit(0);
    }
    else
    printf("Parent: %d",i);
    }
    return 0;
}
```

```
i) int main()
                                                 j) int main()
if(fork( )==0)
                                                  if(vfork( )==0)
                                                  printf("1");
printf("1");
                                                  exit(0);
else
                                                  else
wait(NULL);
printf("2");
                                                  printf("2");
printf("3");
                                                  printf("3");
return 0;
                                                  return 0;
```

```
k) int main()
                                                 1) int main()
pid tc1;
                                                  pid tc1;
int n=10;
                                                  int n=10;
c1 = fork();
                                                  c1=vfork();
if(c1==0)
                                                  if(c1==0)
printf(" Child\n");
                                                  printf(" Child\n");
n=20;
                                                  n=20;
printf("n=%d \n",n);
                                                  printf("n=%d \n",n);
                                                  exit(0);
else
                                                  else
wait(NULL);
printf("Parent\n");
                                                  printf("Parent\n");
                                                  printf("n=\%d \n",n);
printf("n=\%d \n",n);
return 0;
                                                  return 0;
                                                  }
m) int main()
                                                 n) int main()
int i=5;
                                                  pid t pid;
fork();
                                                  int i=5;
i=i+1;
                                                  pid=vfork();
                                                  if(pid==0)
fork();
printf ( "% d",i);
                                                  printf("Child: %d",i);
return 0;
                                                  _exit(0);
                                                  else
                                                  i=i+1;
                                                  printf("Parent: %d",i);
                                                  return 0;
```

```
}
```

```
p) int main( )
o) int main()
int i=5;
                                                    int i=5;
if(fork()==0)
                                                    if(vfork()==0)
i=i+1;
else
                                                    i=i+1;
                                                    _exit(0);
i=i-1;
printf("%d",i);
return 0;
                                                    else
                                                    i=i-1;
                                                    fprintf(stderr,"%d",i);
                                                    return 0;
                                                    }
q) int main()
                                                   r) int main()
int j,i=5;
                                                    int j,i=5;
for(j=1;j<3;j++)
                                                    for(j=1;j<3;j++)
if(fork()==0)
                                                    if(fork()!=0)
i=i+1;
                                                    i=i-1;
break;
                                                    break;
else
wait(NULL);
                                                    fprintf(stderr,"%d",i);
                                                    return 0;
printf("%d",i);
                                                    }
return 0;
                                                   t) void fun1(){
s) int main()
                                                    fork();
if(fork() == 0)
                                                    fork();
if(fork())
                                                   printf("1\n");
printf("1\n");
return 0;
                                                    int main() {
                                                    fun1();
                                                   printf("1\n");
                                                    return 0;
```

- 3. Write a C program that will create three child process to perform the following operations respectively:
 - First child will copy the content of file1 to file2

- Second child will display the content of file2
- Third child will display the sorted content of file2 in reverse order.
- Each child process being created will display its id and its parent process id with appropriate message.
- The parent process will be delayed for 1 second after creation of each child process. It will display appropriate message with its id after completion of all the child processes.
- 4. Write a C program that will create a child process to generate a Fibonacci series of specified length and store it in an array. The parent process will wait for the child to complete its task and then display the Fibonacci series and then display the prime Fibonacci number in the series along with its position with appropriate message.

```
*q1.c
   Open 🔻
             \oplus
 1 #include<stdio.h>
 2 #include<unistd.h>
 3 #include<sys/wait.h>
 4 int main(){
 5 \text{ pid t } C1 = \text{fork();}
 6 if (C1 ==0)
 8 fprintf(stderr, "Child Process id: %d", getpid());
 9 while(1);
10 }
11 else
12 {
13 fprintf(stderr, "Parent Process id: %d", getpid());
14 while(1);
15 }
16 }
root@DESKTOP-8EIFV6T:~# gcc q1.c
root@DESKTOP-8EIFV6T:~# ./a.out
Parent Process id: 8226Child Process id: 8227
```

```
root@DESKTOP-8EIFV6T:~# ps -al
      UID
                     PPID C PRI
                                   NI ADDR SZ WCHAN
FS
              PID
                                                     TTY
                                                                   TIME CMD
0 R
                                                              00:00:21 a.out
        0
             8226
                      354 99
                              80
                                   0 -
                                          661 -
                                                     pts/0
             8227
                     8226 99
                              80
                                    0 -
                                          661 -
                                                     pts/0
                                                              00:00:21 a.out
4 R
        0
             8311
                     5528
                          0
                              80
                                    0 - 1871 -
                                                              00:00:00 ps
                                                     pts/2
root@DESKTOP-8EIFV6T:~#
```

1(b)

```
root@DESKTOP-8EIFV6T:~# kill -9 8227
root@DESKTOP-8EIFV6T:~# ps -al
F S
      UID
              PID
                     PPID C PRI
                                  NI ADDR SZ WCHAN
                                                    TTY
                                                                 TIME CMD
                                                    pts/0
0 R
        0
             8226
                      354 99 80
                                  0 -
                                         661 -
                                                             00:01:03 a.out
1 Z
                     8226 88 80
                                                    pts/0
        0
             8227
                                   0 -
                                           0 -
                                                             00:00:56 a.out <defunct>
4 R
        Θ
             8480
                     5528 0
                              80
                                   0 - 1871 -
                                                    pts/2
                                                             00:00:00 ps
root@DESKTOP-8EIFV6T:~#
```

1(c)

```
root@DESKTOP-8EIFV6T:~# gcc q1.c
root@DESKTOP-8EIFV6T:~# ./a.out
Parent Process id: 8917Child Process id: 8918
```

```
root@DESKTOP-8EIFV6T:~# kill -9 8917
root@DESKTOP-8EIFV6T:~# ps -al
FS
             PID
                    PPID C PRI NI ADDR SZ WCHAN
                                                  TTY
                                                               TIME CMD
1 R
       0
            8918
                    352 99 80
                                 0 - 661 -
                                                  pts/0
                                                           00:00:39 a.out
4 R
            9077
                    5528 0 80
       0
                                  0 - 1871 -
                                                  pts/2
                                                           00:00:00 ps
root@DESKTOP-8EIFV6T:~#
```

1(d)

```
*q1.c
   Open ▼
             \oplus
 1 #include<stdio.h>
 2 #include<unistd.h>
 3 #include<sys/wait.h>
 4 int main(){
 5 \text{ pid t C1} = \text{fork()};
 6 if (C1 ==0)
 7 {
 8 fprintf(stderr, "Child Process id: %d", getpid());
10 }
11 else
12 {
13 fprintf(stderr, "Parent Process id: %d",getpid());
14 wait(NULL);
15 while(1);
16 }
17 }
```

```
root@DESKTOP-8EIFV6T:~# gcc q1.c
root@DESKTOP-8EIFV6T:~# ./a.out
Parent Process id: 11533Child Process id: 11534
```

```
root@DESKTOP-8EIFV6T:~# ps -al
F S
      UID
             PID
                    PPID C PRI
                                 NI ADDR SZ WCHAN TTY
                                                                TIME CMD
0 S
       0
                                                            00:00:00 a.out
           11533
                     354 0 80
                                  0 - 661 do_wai pts/0
                                                   pts/0
1 R
       0
           11534
                   11533 99
                             80
                                  0 - 661 -
                                                            00:01:08 a.out
4 R
        0
           11803
                    5528 0 80
                                  0 - 1871 -
                                                            00:00:00 ps
                                                   pts/2
```

1(e)

```
root@DESKTOP-8EIFV6T:~# kill -9 11534
root@DESKTOP-8EIFV6T:~# ps -al
F S UID PID PPID C PR
                      PPID C PRI NI ADDR SZ WCHAN
                                                                     TIME CMD
                                                       TTY
0 R
        0
            11533
                       354 1 80
                                    0 -
                                          661 -
                                                       pts/0
                                                                 00:00:01 a.out
4 R
                                     0 - 1871 -
        0
            12096
                      5528 O
                                                       pts/2
                                                                 00:00:00 ps
                               80
root@DESKTOP-8EIFV6T:~#
```

```
q3.c
  Open ▼ 🕦
                                                                                       Save
1 #include<stdio.h>
2 #include<sys/wait.h>
3 #include<unistd.h>
4 int main()
5 if(vfork()=0)
6 {
7
    fprintf(stderr,"\nChild process id :%d\n",getpid(),getppid());
8
    execl("/usr/bin/cp","cp","file1","file2",NULL);
  _exit(0);
}
9
10
    sleep(1);
11
    if(vfork()=0)
12
13 {
14
    fprintf(stderr,"\nChild process id :%d Parent process id :%d\n",getpid(),getppid());
15
    _exit(0);
}
    execl("/usr/bin/cat","cat","file2",NULL);
16
17
18
    sleep(1);
   if(vfork()=0)
19
20 {
21
    fprintf(stderr,"\nChild process id :%d Parent process id :%d\n",getpid(),getppid());
22
    execl("/usr/bin/sort","sort","-r","file2",NULL);
    _exit(0);
}
23
24
25
26
     sleep(1);
27
     fprintf(stderr,"\nParent process id :%d",getpid());
28
29 }
```

```
-(munu⊗ kali)-[~]
  -$ cat file1
1
2
3
4
5
6
   -(munu�kali)-[~]
  s cat file2
1
2
3
4
5
6
```

```
—(munu⊛ kali)-[~]
 -$ gedit q3.c
  —(munu⊛ kali)-[~]
$ gcc q3.c
 —(munu⊛ kali)-[~]
_$ ./a.out
Child process id :7411 Parent process id :7410
Child process id :7420 Parent process id :7410
2
3
4
5
Child process id :7429 Parent process id :7410
5
4
3
2
Parent process id :7410
```

```
Open
1 #include<stdio.h>
2 #include<unistd.h>
3 #include<stdbool.h>
4 int main() {
       int length=10;
       printf("Enter the length : ");
       scanf("%d", &length);
7
8
       int fibArray[length];
9
       if(vfork()=0){
           fibArray[0] = 0;
10
           fibArray[1] = 1;
11
12
           for (int i = 2; i < length; i++) {</pre>
13
               fibArray[i]=fibArray[i-1]+fibArray[i-2];
           }
14
           _exit(0);
15
16
         printf("\n");
17
18
           printf("Fibonacci Series:\n");
19
           for (int i = 0; i < length; i++) {</pre>
                    printf("%d ", fibArray[i]);
20
21
22
           printf("\n");
23
           printf("Prime Fibonacci numbers:\n");
24
           for (int i = 3; i < length; i++) {</pre>
           int isPrime = 1;
25
           for (int j = 2; j * j \leq fibArray[i]; j \leftrightarrow) {
26
           if (fibArray[i] % j = 0)
27
28
               isPrime = 0;
29
           if (isPrime)
30
               printf("%d at index : %d \n", fibArray[i],i);
31
32
33
       return 0;
34 }
```

```
(munu⊗ kali)-[~]
$ gcc q4.c

(munu⊗ kali)-[~]
$ ./a.out
Enter the length : 10

Fibonacci Series:
0 1 1 2 3 5 8 13 21 34
Prime Fibonacci numbers:
2 at index : 3
3 at index : 4
5 at index : 5
13 at index : 7
```

```
1 #include <stdio.h>
2 #include <pthread.h>
3 #include <semaphore.h>
4 #define BUFFER_SIZE 10
5 int buffer[BUFFER_SIZE];
6 int count = 0;
7 sem_t empty, full;
8 pthread_mutex_t mutex;
9 void *producer(void *arg) {
10 for (int i = 1; i \leq 100; i \leftrightarrow) {
11 sem_wait(&empty);
12 pthread_mutex_lock(&mutex);
13 buffer[count++] = i;
14 printf("Produced: %d\n", i);
15 pthread mutex unlock(&mutex);
16 sem_post(&full);
17 }
18 return NULL;
20 void *consumer(void *arg) {
21 for (int i = 1; i \leq 100; i \leftrightarrow) {
22 sem wait(&full);
23 pthread_mutex_lock(&mutex);
24 int item = buffer[--count];
25 printf("Consumed: %d\n", item);
26 pthread_mutex_unlock(&mutex);
27 sem_post(&empty);
28 }
29 return NULL;
30 }
31 int main() {
32 pthread_t prod, cons;
33 sem_init(&empty, 0, BUFFER_SIZE);
34 sem_init(&full, 0, 0);
35 pthread_mutex_init(&mutex, NULL);
36 pthread_create(&prod, NULL, producer, NULL);
37 pthread_create(&cons, NULL, consumer, NULL);
38 pthread_join(prod, NULL);
39 pthread_join(cons, NULL);
40 sem_destroy(&empty);
41 sem_destroy(&full);
42 pthread_mutex_destroy(&mutex);
43 return 0;
```

```
-(munu⊕kali)-[~]
-$ gedit producer_consumer.c
(gedit:5456): Gtk-WARNING **: 19:1
  -(munu⊕kali)-[~]
 -$ chmod +x producer_consumer.c
                                                               Consumed: 73
                                                            55
                                                 Consumed:
  -(munu⊕kali)-[~]
                                                               Consumed:
                                 Consumed: 36
                                                            54
                                                Consumed:
 -$ gcc producer_consumer.c
                                                               Consumed:
                                 Consumed: 35
                                                 Consumed:
                                                            53
                                                                          81
                                                               Produced:
                  Consumed:
                              18 Consumed:
                                                            52
                                                 Consumed:
  -(munu�kali)-[~]
                                                               Produced:
                              17 Consumed:
                  Consumed:
                                                 Consumed:
                                                            51
 -$ ./a.out
                                                               Produced:
                  Consumed:
                                Consumed: 32
                                                 Produced:
                                                            61
Produced: 1
                                                               Produced:
                                                                           84
                              15
                  Consumed:
                                 Consumed: 31
                                                            62
                                                 Produced:
Produced: 2
                  Consumed:
                                                               Produced:
                                 Produced: 41
                                                            63
                                                 Produced:
Produced: 3
                  Consumed:
                              13
                                                               Produced:
                                 Produced: 42
                                                 Produced:
                                                            64
Produced: 4
                  Consumed:
                              12
                                                               Produced:
                                                                           87
                                 Produced: 43
                                                            65
                                                 Produced:
Produced: 5
                  Consumed:
                              11
                                                               Produced:
                                 Produced:
                                                            66
                                                 Produced:
Produced: 6
                              21
                  Produced:
                                                               Produced:
                                 Produced: 45
                                                            67
                                                 Produced:
Produced: 7
                  Produced: 22
                                                               Produced:
                                                                           90
                                 Produced: 46
                                                            68
                                                 Produced:
Produced: 8
                  Produced:
                              23
                                                               Consumed:
                                 Produced: 47
                                                            69
                                                 Produced:
Produced: 9
                              24
                  Produced:
                                                               Consumed:
                                 Produced: 48
                                                 Produced:
                                                            70
Produced: 10
                              25
                  Produced:
                                                               Consumed:
                                 Produced: 49
                                                 Consumed:
Consumed: 10
                  Produced: 26
                                                               Consumed:
                                                            69
                                 Produced:
                                                 Consumed:
Consumed: 9
                  Produced:
                                                               Consumed:
                                                            68
                                 Consumed:
                                             50
                                                 Consumed:
Consumed: 8
                              28
                  Produced:
                                                                           85
                                                               Consumed:
                                                            67
                                 Consumed:
                                                 Consumed:
Consumed: 7
                  Produced:
                              29
                                                               Consumed:
                                 Consumed:
                                                            66
                                                 Consumed:
Consumed: 6
                  Produced:
                              30
                                                               Consumed:
                                                            65
                                 Consumed:
                                                 Consumed:
Consumed: 5
                              30
                  Consumed:
                                                               Consumed:
                              29 Consumed:
                                                            64
                                                 Consumed:
Consumed: 4
                  Consumed:
                                                               Consumed:
                              28 Consumed:
                                                            63
                  Consumed:
                                                 Consumed:
Consumed: 3
                                                               Produced:
                                                                           91
                  Consumed:
                              27 Consumed:
                                                 Consumed:
                                                            62
Consumed: 2
                                                                           92
                                                               Produced:
                              26 Consumed:
                  Consumed:
                                                 Consumed:
                                                            61
Consumed: 1
                                                               Produced:
                              25
                  Consumed:
                                Consumed:
                                                 Produced:
                                                            71
Produced: 11
                                                               Produced:
                  Consumed:
                              24
                                Consumed: 41
                                                            72
                                                 Produced:
Produced: 12
                                                                           95
                                                               Produced:
                              23
                  Consumed:
                                 Produced: 51
                                                            73
                                                 Produced:
Produced: 13
                                                               Produced:
                  Consumed:
                                 Produced:
                                                 Produced:
                                                            74
Produced: 14
                  Consumed:
                                                               Produced:
                                 Produced:
                                             53
                                                            75
                                                 Produced:
Produced: 15
                                                                           98
                              31
                  Produced:
                                                               Produced:
                                 Produced:
                                                            76
                                                 Produced:
Produced: 16
                  Produced:
                                                               Produced:
                                 Produced:
                                             55
                                                 Produced:
                                                            77
Produced: 17
                  Produced:
                                                                           100
                                                               Produced:
                                 Produced:
                                             56
                                                 Produced:
                                                            78
Produced: 18
                  Produced: 34
                                                               Consumed:
                                                                           100
                                                            79
                                 Produced:
                                                 Produced:
Produced: 19
                  Produced:
                              35
                                                               Consumed:
                                                                           99
                                 Produced:
                                             58
                                                 Produced:
                                                            80
                  Produced: 36
                                                                           98
                                                               Consumed:
                                 Produced:
                                            59
                                                 Consumed:
                  Produced:
                              37
                                                               Consumed:
                                                                           97
                                                            79
                                 Produced:
                                            60
                                                 Consumed:
                  Produced: 38
                                                               Consumed:
                                                            78
                                 Consumed:
                                            60
                                                 Consumed:
                  Produced:
                              39
                                                               Consumed:
                                 Consumed:
                                             59
                                                 Consumed:
                  Produced:
                              40
                                                               Consumed:
                                                                           94
                                                            76
                                 Consumed:
                                             58
                                                Consumed:
                  Consumed:
                              40
                                                               Consumed:
                                 Consumed:
                                             57
                                                            75
                                                 Consumed:
                              39
                  Consumed:
                                                               Consumed:
                                 Consumed:
                                             56
                                                 Consumed:
                              38
                  Consumed:
                                                           73 Consumed:
                              37 Consumed:
                                             55
                                                Consumed:
```

Consumed:

```
1 C code:
 2 #include <stdio.h>
 3 #include <pthread.h>
 4 #include <semaphore.h>
 5 sem_t sem_odd, sem_even;
 6 void *print_odd(void *arg) {
 7 for (int i = 1; i \leq 20; i += 2) {
 8 sem_wait(&sem_odd);
 9 printf("%d ", i);
10 sem_post(&sem_even);
11 }
12 return NULL;
13 }
14 void *print_even(void *arg) {
15 for (int i = 2; i \le 20; i += 2) {
16 sem_wait(&sem_even);
17 printf("%d ", i);
18 sem_post(&sem_odd);
19 }
20 return NULL;
21 }
22 int main() {
23 pthread_t odd, even;
24 sem_init(&sem_odd, 0, 1);
25 sem_init(&sem_even, 0, 0);
26 pthread_create(&odd, NULL, print_odd, NULL);
27 pthread_create(&even, NULL, print_even, NULL);
28 pthread_join(odd, NULL);
29 pthread_join(even, NULL);
30 sem_destroy(&sem_odd);
31 sem_destroy(&sem_even);
32 return 0;
33 }
```

```
(munu kali) - [~]
$ gedit altertwothread.c

(gedit:13920): Gtk-WARNING **: 19:34:05.558: Calling org.x

^C

(munu kali) - [~]
$ gcc altertwothread.c

(munu kali) - [~]
$ ./a.out
1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20
```

```
1 #include <stdio.h>
 2 #include <pthread.h>
 3 #include <semaphore.h>
 4 sem_t sem_A, sem_B;
 5 void *print_A(void *arg) {
 6 for (int i = 0; i < 10; i \leftrightarrow) {
 7 sem_wait(&sem_A);
 8 printf("A");
 9 sem_post(&sem_B);
10 }
11 return NULL;
12 }
13 void *print_B(void *arg) {
14 for (int i = 0; i < 10; i \leftrightarrow) {
15 sem_wait(&sem_B);
16 printf("B");
17 sem_post(&sem_A);
18 }
19 return NULL;
20 }
21 int main() {
22 pthread_t thread_A, thread_B;
23 sem_init(&sem_A, 0, 1);
24 sem_init(&sem_B, 0, 0);
25 pthread_create(&thread_A, NULL, print_A, NULL);
26 pthread_create(&thread_B, NULL, print_B, NULL);
27 pthread_join(thread_A, NULL);
28 pthread_join(thread_B, NULL);
29 sem_destroy(&sem_A);
30 sem_destroy(&sem_B);
31 printf("\n");
32 return 0;
33 }
```

```
(munu kali) - [~]
$ gedit alterchar.c

(gedit:15096): Gtk-WARNING **:
^C

(munu kali) - [~]
$ chmod +x alterchar.c

(munu kali) - [~]
$ gcc alterchar.c

(munu kali) - [~]
$ gcc alterchar.c
(munu kali) - [~]
$ gcc alterchar.c
```

```
1 #include <stdio.h>
2 #include <pthread.h>
3 #include <semaphore.h>
4 sem_t sem_countdown, sem_countup;
5 void *countdown(void *arg) {
6 for (int i = 10; i \ge 1; i--) {
7 sem_wait(&sem_countdown);
8 printf("Countdown: %d\n", i);
9 sem_post(&sem_countup);
10 }
11 return NULL;
12 }
13 void *countup(void *arg) {
14 for (int i = 1; i \leq 10; i++) {
15 sem_wait(&sem_countup);
16 printf("Countup: %d\n", i);
17 sem_post(&sem_countdown);
18 }
19 return NULL;
20 }
21 int main() {
22 pthread_t thread_countdown, thread_countup;
23 sem_init(&sem_countdown, 0, 1);
24 sem_init(&sem_countup, 0, 0);
25 pthread_create(&thread_countdown, NULL, countdown, NULL);
26 pthread_create(&thread_countup, NULL, countup, NULL);
27 pthread_join(thread_countdown, NULL);
28 pthread_join(thread_countup, NULL);
29 sem_destroy(&sem_countdown);
30 sem_destroy(&sem_countup);
31 return 0;
32 }
```

```
-(munu�kali)-[~]
 -$ gedit count.c
(gedit:17029): Gtk-<mark>WARNING</mark>
^C
  -(munu⊛ kali)-[~]
-$ chmod +x count.c
  -(munu� kali)-[~]
_$ gcc count.c
  -(munu⊛ kali)-[~]
_$ ./a.out
Countdown: 10
Countup: 1
Countdown:
Countup: 2
Countdown: 8
Countup: 3
Countdown: 7
Countup: 4
Countdown: 6
Countup: 5
Countdown: 5
Countup: 6
Countdown: 4
Countup: 7
Countdown: 3
Countup: 8
Countdown:
Countup: 9
Countdown: 1
Countup: 10
```

```
1 #include <stdio.h>
 2 #include <pthread.h>
 3 #include <semaphore.h>
 4 sem_t sem_A, sem_B, sem_C;
 5 void *print_A(void *arg) {
 6 for (int i = 1; i \leq 20; i += 3) {
 7 sem_wait(&sem_A);
 8 printf("A%d ", i);
 9 sem_post(&sem_B);
10 }
11 return NULL;
12 }
13 void *print_B(void *arg) {
14 for (int i = 2; i \le 20; i += 3) {
15 sem_wait(&sem_B);
16 printf("B%d ", i);
17 sem_post(&sem_C);
18 }
19 return NULL;
20 }
21 void *print_C(void *arg) {
22 for (int i = 3; i \le 20; i += 3) {
23 sem_wait(&sem_C);
24 printf("C%d ", i);
25 sem_post(&sem_A);
26 }
27 return NULL;
28 }
29 int main() {
30 pthread_t thread_A, thread_B, thread_C;
31 sem_init(&sem_A, 0, 1);
32 sem_init(&sem_B, 0, 0);
33 sem_init(&sem_C, 0, 0);
34 pthread_create(&thread_A, NULL, print_A, NULL);
35 pthread_create(&thread_B, NULL, print_B, NULL);
36 pthread_create(&thread_C, NULL, print_C, NULL);
37 pthread_join(thread_A, NULL);
38 pthread_join(thread_B, NULL);
39 pthread_join(thread_C, NULL);
40 sem_destroy(&sem_A);
41 sem_destroy(&sem_B);
42 sem_destroy(&sem_C);
43 printf("\n");
44 return 0;
45
```