

Documentation technique

Référence des paramètres AdminSettings

*Liste exhaustive des sections, des paramètres exposés
et de leur signification.*

À propos de ce document

Cette référence présente **toutes les sections** de la page Administration → Paramètres de la plate-forme Loois / SAWALI Smart Systems, ainsi que les paramètres qu'elles exposent et leur effet attendu. **Les valeurs ne sont pas fournies** : ce document sert de guide d'auto-remplissage. Vous pouvez configurer chaque paramètre au fil de l'eau, selon les modules que vous activez réellement.

Conventions :

- *secret* : champ masqué à l'affichage (*****)
- *E.164* : format international du numéro de téléphone (ex. 225XXXXXXXXXX)
- *bool* : case à cocher
- *enum* : choix dans une liste fermée

Sommaire

1.	Identité & branding	9 param.
2.	URL publique & sécurité globale	5 param.
3.	Approbation WhatsApp des téléchargements (S025)	6 param.
4.	Notification des signataires de PV (S026)	1 param.
5.	Briefing de bienvenue	3 param.
6.	Caisse / Facturation	7 param.
7.	Caissier / RBAC	2 param.
8.	PawaPay (Mobile Money)	5 param.
9.	Stripe	3 param.
10.	Emails (SMTP)	6 param.
11.	WhatsApp Cloud API	6 param.
12.	SMS — Orange / Moov / Telecel / OVH	5 param.
13.	Liluvine PRO (Assistant IA)	6 param.
14.	Régie publicitaire (Ad Banners)	3 param.
15.	Object Storage (S3)	5 param.
16.	Voice Notifications (Voice Monkey)	3 param.
17.	Audit secrets & sécurité avancée	7 param.
18.	RGPD & Anonymisation	3 param.
19.	Webhooks entrants / sortants	6 param.
20.	OpenAI / Gemini / Claude (IA externe)	3 param.
21.	Quotas IA & coûts	2 param.
22.	Voice Studio (TTS/STT)	2 param.
23.	Intégration Meta (Facebook / Messenger / Ads)	4 param.
24.	Google Calendar / Gmail	3 param.
25.	Suivi du registre des suggestions (S021)	1 param.
26.	Diagnostics & maintenance	1 param.

1. Identité & branding

Configuration de l'identité visuelle et SEO de l'instance.

Paramètre	Type	Description
brand_name	string	Nom de marque affiché dans le portail, les emails et les PDFs.
brand_tagline	string	Slogan court accompagnant le nom dans les en-têtes.
brand_logo_url	URL	Logo principal (utilisé dans header, login, briefings).
brand_favicon_url	URL	Favicon servi sous /favicon.ico.
public_meta_description	string	pour le SEO.
public_og_image_url	URL	Image Open Graph (partage social).
public_phone	E.164	Téléphone affiché sur la page Contact publique.
public_email	email	Email public affiché sur la page Contact.
public_address	string	Adresse postale affichée publiquement.

2. URL publique & sécurité globale

Configuration des URLs absolues et secrets globaux.

Paramètre	Type	Description
public_base_url	URL	URL publique utilisée pour les liens absolus dans les cron-jobs (emails, WhatsApp, OAuth).
recaptcha_enabled	bool	Active reCAPTCHA v3 sur les formulaires publics.
recaptcha_site_key	string	Clé publique reCAPTCHA.
recaptcha_secret_key	secret	Clé secrète reCAPTCHA (masquée à l'affichage).
auto_logout_minutes	int 0–120	Délai d'inactivité avant déconnexion automatique. 0 = désactivé. Préréglages 5/10/15/30/60.

3. Approbation WhatsApp des téléchargements (S025)

Workflow d'approbation pour téléchargements externes par utilisateurs non-admin.

Paramètre	Type	Description
download_approval_enabled	bool	Active le workflow : demande WA + jauge d'attente côté utilisateur.
download_approval_what sapp	E.164	Numéro de l'approbateur (recevra les demandes).
download_pending_message	string	Texte affiché dans la jauge en attente (défaut : « En attente d'approbation... »).
download_approval_template_name	string	Nom du template Meta WhatsApp interactif avec 2 boutons QUICK_REPLY. Vide ⇒ fallback texte avec liens magiques.
download_approval_template_lang	code lang	Langue du template Meta (par défaut « fr »).
download_approval_text_body	string	Corps du message texte de fallback. Variables : {requester}, {label}, {approve}, {deny}.

4. Notification des signataires de PV (S026)

Notification automatique des signataires obligatoires d'un PV à sa création.

Paramètre	Type	Description
meeting_signers_notify_channel	enum	Canal de notification : none email wa both. Le PV est envoyé aux signataires de la ligne 1 du formulaire.

5. Briefing de bienvenue

Comportement du briefing affiché à la connexion.

Paramètre	Type	Description
welcome_unread_mode	enum	bounded (recommandé) = ne compte que les messages reçus depuis la dernière visite (ou 7 jours). cumulative = compte tous les messages non lus depuis le début.
welcome_briefing_days_back	int	Période en jours pour les notes/rapports récents (défaut 3).
welcome_show_liluvine_card	bool	Affiche la carte « WhatsApp pris en charge par Liluvine aujourd'hui ». Visible aux admin/superviseur/modérateurs.

6. Caisse / Facturation

Module financier (reçus, factures, dépenses, catalogue).

Paramètre	Type	Description
cash_currency_code	ISO 4217	Devise par défaut (XOF, EUR, USD...).
cash_tax_rate_default	float	Taux de TVA par défaut appliqué aux factures.
cash_legal_form_options	list[string]	Formes juridiques affichées dans le formulaire client (SARL, SA, SAS, EI, ...).
cash_payment_methods	list[string]	Modes de paiement disponibles dans les reçus.
cash_invoice_prefix	string	Préfixe des numéros de facture (par ex. FA-).
cash_receipt_prefix	string	Préfixe des numéros de reçu (par ex. RE-).
cash_company_legal_info	string	Mentions légales reproduites en pied de chaque facture (RCCM, IDU...).

7. Caissier / RBAC

Droits d'accès au module Caisse et au mobile money.

Paramètre	Type	Description
cash_payout_enabled	bool	Active le bouton « Payer (Mobile Money) » dans Caisse pour les Caissiers Admin/Superviseur.
cash_payout_provider	enum	pawapay stripe — fournisseur de décaissement.

8. PawaPay (Mobile Money)

Intégration PawaPay pour les décaissements.

Paramètre	Type	Description
pawapay_environment	enum	sandbox production.
pawapay_api_token	secret	Token API courant (selon environnement).
pawapay_api_token_sandbox	secret	Token sandbox.
pawapay_api_token_production	secret	Token production.
pawapay_callback_secret	secret	Secret signant les callbacks PawaPay.

9. Stripe

Intégration Stripe Checkout pour les abonnements et la Régie publicitaire.

Paramètre	Type	Description
stripe_publishable_key	string	Clé publique Stripe.
stripe_secret_key	secret	Clé secrète Stripe (test ou live).
stripe_webhook_secret	secret	Secret de signature des webhooks Stripe.

10. Emails (SMTP)

Serveur SMTP pour OTP, notifications et brochures.

Paramètre	Type	Description
smtp_host	string	Hôte SMTP (ex: smtp.resend.com).
smtp_port	int	Port (587 STARTTLS, 465 SSL).
smtp_username	string	Identifiant SMTP.
smtp_password	secret	Mot de passe SMTP (masqué).
smtp_from_email	email	Adresse expéditeur par défaut.
smtp_from_name	string	Nom expéditeur affiché.

11. WhatsApp Cloud API

Intégration Meta WhatsApp Business Cloud.

Paramètre	Type	Description
wa_phone_number_id	string	Phone Number ID Meta.
wa_business_account_id	string	WABA ID (compte business).
wa_access_token	secret	Token d'accès permanent.
wa_verify_token	secret	Token de vérification du webhook Meta.
wa_app_id	string	App ID Facebook Developer.
wa_app_secret	secret	App Secret (signature webhook X-Hub-Signature-256).

12. SMS — Orange / Moov / Telecel / OVH

Routeurs SMS multi-opérateurs.

Paramètre	Type	Description
<code>sms_default_provider</code>	enum	orange moov telecel ovh.
<code>sms_orange_*</code>	secrets	Identifiants Orange CI (token, basic_pass, header_value, client_secret).
<code>sms_moov_*</code>	secrets	Identifiants Moov Africa.
<code>sms_telecel_*</code>	secrets	Identifiants Telecel.
<code>sms_ovh_*</code>	secrets	Identifiants OVH (application_secret, consumer_key).

13. Liluvine PRO (Assistant IA)

Configuration de l'assistant IA conversationnel.

Paramètre	Type	Description
<code>liluvine_pro_enabled</code>	bool	Active Liluvine PRO globalement.
<code>liluvine_model</code>	string	Modèle utilisé (Claude Sonnet 4.5, Claude Haiku 4.5...).
<code>liluvine_system_prompt</code>	string	Prompt système global appliqué à toutes les conversations.
<code>liluvine_wa_autoreply_enabled</code>	bool	Active l'autoréponse WhatsApp pilotée par Liluvine.
<code>liluvine_wa_human_takeover_minutes</code>	int	Durée du verrou « Reprendre la main » (défaut 120 min).
<code>liluvine_remote_secret</code>	secret	Secret de l'API console de support distante.

14. Régie publicitaire (Ad Banners)

Module monétisation des bannières publicitaires.

Paramètre	Type	Description
<code>ad_banners_enabled</code>	bool	Active la régie publicitaire.
<code>ad_banners_default_placement</code>	enum	public portal both.
<code>ad_banners_expiration_reminder_days</code>	int	Jours avant expiration pour envoyer le rappel email + WhatsApp.

15. Object Storage (S3)

Stockage objet pour documents et médias.

Paramètre	Type	Description
storage_bucket	string	Nom du bucket S3.
storage_region	string	Région AWS (eu-west-1, ...).
storage_access_key_id	string	Access Key ID.
storage_secret_access_key	secret	Secret Access Key.
storage_public_url_prefix	URL	Préfixe public utilisé pour servir les assets.

16. Voice Notifications (Voice Monkey)

Notifications vocales via Alexa Echo / Voice Monkey.

Paramètre	Type	Description
alexa_enabled	bool	Active les notifications vocales.
alexa_webhook_url	URL	URL du webhook Voice Monkey.
alexa_events	list[enum]	Événements déclencheurs : sms_inbound, wa_inbound, appointment_due, support_load_critical.

17. Audit secrets & sécurité avancée

Audit des modifications de secrets et alertes sécurité.

Paramètre	Type	Description
secret_audit_email_enabled	bool	Email à chaque modification de secret (jamais la valeur, juste WHO/WHEN/WHICH).
secret_audit_email_to	email	Destinataire des notifications d'audit.
incident_banner_enabled	bool	Affiche un bandeau d'incident global en tête du portail.
incident_banner_severity	enum	info warning critical.
incident_banner_message	string	Texte du bandeau d'incident.
incident_banner_link_url	URL	Lien d'information complémentaire.
incident_banner_link_label	string	Libellé du bouton du bandeau.

18. RGPD & Anonymisation

Conformité RGPD et purge automatique des données.

Paramètre	Type	Description
gdpr_auto_anonymize_enabled	bool	Lance un cron quotidien qui anonymise les comptes inactifs.
gdpr_inactive_days_threshold	int	Nombre de jours d'inactivité avant anonymisation (défaut 365).
gdpr_data_retention_days	int	Durée maximale de conservation des logs et messages.

19. Webhooks entrants / sortants

Endpoints webhooks personnalisés (notes, santé, paie n8n).

Paramètre	Type	Description
notes_webhook_url	URL	URL d'un système externe recevant chaque note créée.
notes_webhook_token	secret	Token Bearer pour notes_webhook_url.
notes_webhook_basic_pass	secret	Mot de passe HTTP Basic (alternatif au Bearer).
health_webhook_url	URL	Webhook recevant les rapports de santé quotidiens.
health_webhook_token	secret	Token du webhook santé.
payroll_webhooks_n8n_*	URLs/secrets	Webhooks paie n8n pour bons de paie et IBAN.

20. OpenAI / Gemini / Claude (IA externe)

Clés API IA (compatibles Emergent LLM Key universelle).

Paramètre	Type	Description
openai_api_key	secret	Clé OpenAI (text + vision + Whisper).
openai_chat_api_key	secret	Clé OpenAI dédiée au chat (séparée pour quotas).
emergent_llm_key	secret	Clé universelle Emergent (couvre Claude, Gemini, OpenAI). Si présente, prime sur les clés individuelles.

21. Quotas IA & coûts

Limitation de la consommation IA par tenant.

Paramètre	Type	Description
ai_monthly_budget_eur	float	Budget IA mensuel (en EUR) au-delà duquel l'IA est désactivée.
ai_monthly_warning_threshold_pct	int 0–100	Pourcentage du budget déclenchant un email d'alerte.

22. Voice Studio (TTS/STT)

Studio de notifications vocales internes.

Paramètre	Type	Description
voice_studio_default_voice	string	Voix par défaut pour la synthèse (ElevenLabs).
voice_studio_default_language	code lang	Langue par défaut (fr, en, ...).

23. Intégration Meta (Facebook / Messenger / Ads)

Connexion à l'écosystème Meta complet.

Paramètre	Type	Description
meta_app_id	string	App ID Meta Business.
meta_app_secret	secret	App Secret Meta.
meta_page_id	string	Page Facebook par défaut.
meta_ad_account_id	string	Compte publicitaire Meta pour les rapports Ads.

24. Google Calendar / Gmail

Intégration des agendas et emails Google.

Paramètre	Type	Description
google_client_id	string	OAuth Client ID.
google_client_secret	secret	OAuth Client Secret.
google_calendar_id_primary	string	Calendrier cible pour les RDV synchronisés.

25. Suivi du registre des suggestions (S021)

Visualisation interne du fichier SUGGESTIONS.md.

Paramètre	Type	Description
(pas de paramètres)	—	Page consultable depuis Admin → Suggestions (registre S###). Fichier source : /app/memory/SUGGESTIONS.md. Géré directement par modification du fichier (ou via prompts au support agent).

26. Diagnostics & maintenance

Outils de réparation et de cohérence DB.

Paramètre	Type	Description
(plusieurs sections)	—	Sections « Données orphelines », « Cohérence clients », « Diagnostic client », « Revert retag », « Backfill caissier tenant ». Boutons d'action one-shot — pas de paramètres persistants.

Référence complète des API REST

Tableau exhaustif des endpoints exposés par le backend FastAPI. Pour chaque endpoint, vous trouverez la méthode HTTP, le chemin (préfixé par **/api**), une brève description, les paramètres attendus (chemin et corps), et un exemple d'URL. Ce document est auto-généré à partir de l'OpenAPI live du serveur.

Méthode	Endpoint	Description	Paramètres
GET	/api/	—	—
GET	/api/admin/access-logs	—	user_email:Optional[str], module:Optional[str], q:Optional[str], limit:int
GET	/api/admin/access-logs/export.csv	—	user_email:Optional[str], module:Optional[str]
GET	/api/admin/ad-banners	—	—
POST	/api/admin/ad-banners	—	payload:AdBannerPayload
POST	/api/admin/ad-banners/fix-urls	—	—
POST	/api/admin/ad-banners/run-reminder-cron	—	send_email_fn
DELETE	/api/admin/ad-banners/{banner_id}	—	banner_id:str
PUT	/api/admin/ad-banners/{banner_id}	—	banner_id:str, payload:AdBannerUpdate
POST	/api/admin/ad-banners/{banner_id}/rotate-token	Regenerate the share_token (invalidates previously shared URLs).	banner_id:str
GET	/api/admin/ad-banners/{banner_id}/stats	—	banner_id:str
POST	/api/admin/ad-banners/{banner_id}/toggle-paid	—	banner_id:str
GET	/api/admin/ad-renewal-requests	—	—
POST	/api/admin/ad-renewal-requests/{req_id}/mark-handled	—	req_id:str
GET	/api/admin/ai-costs/monthly	—	months:int
GET	/api/admin/ai-subscriptions	—	—
POST	/api/admin/ai-subscriptions	—	payload:SubscriptionPayload
DELETE	/api/admin/ai-subscriptions/{sub_id}	—	sub_id:str
PUT	/api/admin/ai-subscriptions/{sub_id}	—	sub_id:str, payload:SubscriptionUpdate
POST	/api/admin/ai-subscriptions/{sub_id}/send-reminder	—	sub_id:str
DELETE	/api/admin/api-traces	—	—

Méthode	Endpoint	Description	Paramètres
GET	/api/admin/api-traces	—	user_email:Optional[str], method:Optional[str], status:Optional[int], q:Optional[str], onl
GET	/api/admin/api-traces/export.csv	—	user_email:Optional[str], method:Optional[str], only_errors:bool
GET	/api/admin/appointments	—	—
DELETE	/api/admin/appointments/{appt_id}	—	appt_id:str
PUT	/api/admin/appointments/{appt_id}	—	appt_id:str, payload:AppointmentUpdate
GET	/api/admin/automations	—	—
POST	/api/admin/automations	—	payload:AutomationCreate, admin_user:dict
GET	/api/admin/automations/events	—	—
DELETE	/api/admin/automations/{aid}	—	aid:str
PUT	/api/admin/automations/{aid}	—	aid:str, payload:AutomationUpdate
GET	/api/admin/blacklisted-ips	—	—
POST	/api/admin/blacklisted-ips	—	payload:BlacklistedIPCreate
DELETE	/api/admin/blacklisted-ips/{ip_id}	—	ip_id:str
GET	/api/admin/blog	—	—
POST	/api/admin/blog	—	payload:dict
DELETE	/api/admin/blog/{post_id}	—	post_id:str
GET	/api/admin/blog/{post_id}	—	post_id:str
PUT	/api/admin/blog/{post_id}	—	post_id:str, payload:dict
GET	/api/admin/business-clients	—	—
POST	/api/admin/business-clients	—	payload:BusinessClientPayl
DELETE	/api/admin/business-clients/{cid}	—	cid:str
PATCH	/api/admin/business-clients/{cid}	—	cid:str, payload:BusinessClientPayl
GET	/api/admin/campaign-efficiency	—	days:int
GET	/api/admin/case-studies	—	—
POST	/api/admin/case-studies	—	payload:dict
DELETE	/api/admin/case-studies/{cs_id}	—	cs_id:str

Méthode	Endpoint	Description	Paramètres
PUT	/api/admin/case-studies/{cs_id}	—	cs_id:str, payload:dict
POST	/api/admin/cashier/backfill-tenants	Recompute tenant_id on all Caisse docs using the latest resolution logic.	payload:dict
POST	/api/admin/cashier/qr/rewrite-base-url	—	payload:dict
GET	/api/admin/client-categories	—	—
POST	/api/admin/client-categories	—	payload:ClientCategoryCreate
DELETE	/api/admin/client-categories/{cat_id}	—	cat_id:str
PUT	/api/admin/client-categories/{cat_id}	—	cat_id:str, payload:ClientCategoryUpdate
GET	/api/admin/client-data-diagnostic	—	email:str
GET	/api/admin/clients	List all users that should be visible in the Admin → Clients module.	include_roles:Optional[str], source:Optional[str], sort_by:Optional[str], sort_order:Optional
POST	/api/admin/clients	—	payload:UserCreateAdmin
GET	/api/admin/clients-consistency	Panoramic view of every multi-user company and whether all its members	—
POST	/api/admin/clients-consistency/realign-all	Iter38r-fix9h — Réaligne d'un seul clic tous les utilisateurs détectés	payload:_RealignAllPayload, admin:dict
DELETE	/api/admin/clients/{client_id}	—	client_id:str
GET	/api/admin/clients/{client_id}	—	client_id:str
PUT	/api/admin/clients/{client_id}	—	client_id:str, payload:UserUpdateAdmin
GET	/api/admin/clients/{client_id}/ai-quota	—	client_id:str
PUT	/api/admin/clients/{client_id}/ai-quota	—	client_id:str, payload:QuotaConfig
GET	/api/admin/clients/{client_id}/ai-usage	—	client_id:str, year_month:Optional[str]
GET	/api/admin/clients/{client_id}/ai-usage/export.csv	—	client_id:str, date_from:Optional[str], date_to:Optional[str]
GET	/api/admin/clients/{client_id}/ai-usage/export.pdf	—	client_id:str, date_from:Optional[str], date_to:Optional[str]
GET	/api/admin/clients/{client_id}/features	—	client_id:str
PUT	/api/admin/clients/{client_id}/features	—	client_id:str, payload:ClientFeaturesUpdate

Méthode	Endpoint	Description	Paramètres
GET	/api/admin/clients/{client_id}/notes	—	client_id:str
POST	/api/admin/clients/{client_id}/notes	—	client_id:str, payload:ClientNoteCreate, admin_user:dict
DELETE	/api/admin/clients/{client_id}/notes/{nid}	—	client_id:str, nid:str
POST	/api/admin/clients/{client_id}/set-primary	Designate ONE client as the primary site owner.	client_id:str
GET	/api/admin/clients/{client_id}/tasks	—	client_id:str
POST	/api/admin/clients/{client_id}/tasks	—	client_id:str, payload:ClientTaskCreate, admin_user:dict
DELETE	/api/admin/clients/{client_id}/tasks/{tid}	—	client_id:str, tid:str
PUT	/api/admin/clients/{client_id}/tasks/{tid}	—	client_id:str, tid:str, payload:ClientTaskUpdate
GET	/api/admin/clients/{client_id}/timeline	Unified CRM timeline for a client — aggregates events from 7 collections.	client_id:str, limit:int, types:Optional[str]
POST	/api/admin/clients/{client_id}/unset-primary	—	client_id:str
PUT	/api/admin/clients/{client_id}/whatsapp-cost	Update the WhatsApp unit cost (per outbound message) for a client.	client_id:str, payload:Dict[str, Any]
GET	/api/admin/clients/{client_id}/whatsapp-stats	WhatsApp consumption summary for a client: messages sent OK/KO,	client_id:str
GET	/api/admin/contacts	—	—
POST	/api/admin/contacts/repair-user-contact	—	payload:Dict[str, Any]
POST	/api/admin/contacts/revert-retag	Restore `client_id` ← `client_id_legacy` on every row where the legacy	payload:Optional[Dict[str, Any]]
POST	/api/admin/contacts/{contact_id}/save-as-tracked-user	—	contact_id:str, payload:SaveContactAsTrack
DELETE	/api/admin/content/{slug}	—	slug:str
PUT	/api/admin/content/{slug}	—	slug:str, payload:ContentUpsert
POST	/api/admin/content/{slug}/translate	—	slug:str, payload:dict
GET	/api/admin/countries	—	—
POST	/api/admin/countries	—	payload:CountryPayload
DELETE	/api/admin/countries/{code}	—	code:str
PATCH	/api/admin/countries/{code}	—	code:str, payload:CountryPayload
GET	/api/admin/coupons	—	—

Méthode	Endpoint	Description	Paramètres
POST	/api/admin/coupons	—	payload:CouponCreate
DELETE	/api/admin/coupons/{coupon_id}	—	coupon_id:str
PUT	/api/admin/coupons/{coupon_id}	—	coupon_id:str, payload:Dict[str, Any]
GET	/api/admin/db	—	—
GET	/api/admin/db/{collection}	Generic JSON query over any whitelisted collection.	collection:str, limit:int, sort_by:Optional[str], sort_dir:int
GET	/api/admin/demo/expiry-events	Demo accounts that have expired — admin reviews and decides:	only_unresolved:bool
POST	/api/admin/demo/expiry-events/{ev_id}/resolve	—	ev_id:str
GET	/api/admin/deployments	—	—
POST	/api/admin/deployments	—	payload:DeploymentCreate
DELETE	/api/admin/deployments/{dep_id}	—	dep_id:str
PUT	/api/admin/deployments/{dep_id}	—	dep_id:str, payload:DeploymentUpdate
POST	/api/admin/docs/regenerate/{slug}	—	slug:str
GET	/api/admin/document-categories	—	—
POST	/api/admin/document-categories	—	payload:DocumentCategoryCr
DELETE	/api/admin/document-categories/{cat_id}	—	cat_id:str
PUT	/api/admin/document-categories/{cat_id}	—	cat_id:str, payload:DocumentCategoryUp
GET	/api/admin/document-logs	Returns combined upload + download history. Admin only.	file_id:Optional[str]
GET	/api/admin/documents	—	—
POST	/api/admin/documents	—	payload:DocumentCreate
DELETE	/api/admin/documents/{doc_id}	—	doc_id:str
PUT	/api/admin/documents/{doc_id}	—	doc_id:str, payload:DocumentUpdate
POST	/api/admin/files/backfill	For every file row that has its binary on disk but no `storage_path`,	—
GET	/api/admin/files/orphans	List file rows that are unrecoverable (disk gone + no remote copy).	—
GET	/api/admin/formations	—	—
POST	/api/admin/formations	—	payload:FormationCreate
DELETE	/api/admin/formations/{fid}	—	fid:str

Méthode	Endpoint	Description	Paramètres
PUT	/api/admin/formations/{fid}	—	fid:str, payload:FormationUpdate
GET	/api/admin/formations/{fid}/enrollments	—	fid:str
POST	/api/admin/formations/{fid}/enrollments/{user_id}/credits	—	fid:str, user_id:str, payload:FormationCreditsUp
POST	/api/admin/formations/{fid}/enrollments/{user_id}/state	—	fid:str, user_id:str, payload:FormationStateUpdate
GET	/api/admin/formations/{fid}/modules	—	fid:str
POST	/api/admin/formations/{fid}/modules	—	fid:str, payload:FormationModuleCre
DELETE	/api/admin/formations/{fid}/modules/{mid}	—	fid:str, mid:str
PUT	/api/admin/formations/{fid}/modules/{mid}	—	fid:str, mid:str, payload:FormationModuleUpd
POST	/api/admin/gdpr/anonymize-now	—	—
GET	/api/admin/google/auth-url	—	—
GET	/api/admin/google/callback	—	code:str
POST	/api/admin/google/disconnect	—	—
GET	/api/admin/health-stats	—	window_hours:int
POST	/api/admin/health/auth-check	—	—
GET	/api/admin/health/auth-check/history	—	limit:int
GET	/api/admin/health/auth-check/latest	—	—
POST	/api/admin/health/run-weekly-now	—	—
POST	/api/admin/health/test-email	—	—
POST	/api/admin/health/uptime/run-now	—	—
GET	/api/admin/health/uptime/stats	—	window_hours:int
POST	/api/admin/i18n/translate-empty-bulk	—	payload:Dict[str, Any]
GET	/api/admin/i18n/translate-models	—	—
POST	/api/admin/i18n/translate-suggest	—	payload:Dict[str, Any]
GET	/api/admin/i18n/translations	—	—
POST	/api/admin/i18n/translations	—	payload:TranslationUpsert
GET	/api/admin/i18n/translations.csv	—	—
POST	/api/admin/i18n/translations/bulk	—	payload:TranslationBulkUps
POST	/api/admin/i18n/translations/import-csv	—	file:UploadFile
DELETE	/api/admin/i18n/translations/{key}	—	key:str

Méthode	Endpoint	Description	Paramètres
GET	/api/admin/i18n/translator-score	Daily / monthly word counters + payable amount.	translator_email:Optional[str]
GET	/api/admin/incident-subscribers	—	—
DELETE	/api/admin/incident-subscribers/{sub_id}	—	sub_id:str
GET	/api/admin/incidents	—	limit:int
GET	/api/admin/incidents/export.csv	—	—
DELETE	/api/admin/incidents/{incident_id}	—	incident_id:str
GET	/api/admin/interventions	—	—
POST	/api/admin/interventions	—	payload:InterventionCreate
DELETE	/api/admin/interventions/{int_id}	—	int_id:str
PUT	/api/admin/interventions/{int_id}	—	int_id:str, payload:InterventionUpdate
POST	/api/admin/legal-forms	—	payload:LegalFormPayload
DELETE	/api/admin/legal-forms/{lid}	—	lid:str
POST	/api/admin/liluvine-escalation/test	—	—
GET	/api/admin/liluvine-pro/branding	—	—
PUT	/api/admin/liluvine-pro/branding	—	payload:BrandingPayload
GET	/api/admin/liluvine-pro/bypass-emails	—	—
PATCH	/api/admin/liluvine-pro/bypass-emails	—	payload:BypassPayload
GET	/api/admin/liluvine-pro/coverage-gaps	Return user-image messages where the best Qdrant match is below	days:int, min_score:float, limit:int
GET	/api/admin/liluvine-pro/diagnose	—	email:Optional[str], phone:Optional[str]
POST	/api/admin/liluvine-pro/generate-doc-draft	—	payload:Dict[str, Any]
GET	/api/admin/liluvine-pro/inbound-urls	—	—
GET	/api/admin/liluvine-pro/kb	—	—
POST	/api/admin/liluvine-pro/kb	—	payload:KbEntryCreate
GET	/api/admin/liluvine-pro/kb/ocr-usage	lter38r-fix9k — Monthly OCR usage report (pages + XOF cost).	month:Optional[str], client_id:Optional[str]
POST	/api/admin/liluvine-pro/kb/upload	lter38r-fix9i — `force_ocr` (form, optional) :	file:UploadFile, title:str, force_ocr:Optional[str]
DELETE	/api/admin/liluvine-pro/kb/{eid}	—	eid:str

Méthode	Endpoint	Description	Paramètres
PUT	/api/admin/liluvine-pro/kb/{eid}	—	eid:str, payload:KbEntryUpdate
GET	/api/admin/liluvine-pro/module-acl	—	—
PUT	/api/admin/liluvine-pro/module-acl	—	payload:_ModuleAcLPayload
GET	/api/admin/liluvine-pro/screenshots-history	List the screenshots that clients sent to Liluvine PRO via the	days:int, limit:int
GET	/api/admin/liluvine-pro/sessions-history	—	channel:Optional[str], date_range:Optional[str], q:Optional[str], limit:int
POST	/api/admin/liluvine-pro/sessions/{sid}/release	—	sid:str
POST	/api/admin/liluvine-pro/sessions/{sid}/takeover	—	sid:str, payload:Dict[str, Any]
GET	/api/admin/liluvine-pro/system-prompt	—	—
PUT	/api/admin/liluvine-pro/system-prompt	—	payload:Dict[str, Any]
GET	/api/admin/liluvine-pro/top-screens	Aggregate the most-matched SAWALI screens across all client	days:int, limit:int
GET	/api/admin/liluvine-pro/wa-autoreply	—	—
PUT	/api/admin/liluvine-pro/wa-autoreply	—	payload:AutoreplyConfigPay
GET	/api/admin/liluvine-pro/wa-autoreply/history	—	limit:int
POST	/api/admin/liluvine-weekly-digest/run-now	—	—
POST	/api/admin/liluvine/remote-link	Generate a long-lived signed link to control Liluvine threshold + level	payload:AdminRemoteLinkReq
GET	/api/admin/llm-health	Admin/Superviseur can read the state. The frontend banner uses an	—
POST	/api/admin/llm-health/ping	Force a fresh health probe (admin button).	—
POST	/api/admin/llm-health/test-summary	S033 — Manual budget test: forces a health probe AND returns the	—
GET	/api/admin/llm-health/usage-chart	S-iter39n — Daily consumption chart for the Universal Key.	days:int
GET	/api/admin/media-library	—	—
POST	/api/admin/media-library	—	file:UploadFile, title:str, description:str, kind:Optional[str], public:bool, sort_order:i
DELETE	/api/admin/media-library/{mid}	—	mid:str
PATCH	/api/admin/media-library/{mid}	—	mid:str, payload:dict

Méthode	Endpoint	Description	Paramètres
GET	/api/admin/messaging/audience	Return all contactable recipients (clients with phone/whatsapp + tracked users with phone).	—
POST	/api/admin/messaging/bulk-send	Send the same WhatsApp template to a list of recipients. Returns a per-recipient result.	payload:AdminBulkSendReque, admin_user:dict
GET	/api/admin/messaging/history	—	limit:int
GET	/api/admin/messaging/schedules	—	—
POST	/api/admin/messaging/schedules	—	payload:AdminScheduleCreat, admin_user:dict
DELETE	/api/admin/messaging/schedules/{sid}	—	sid:str
GET	/api/admin/messaging/variable-tokens	List of substitution tokens the admin can insert into template variables.	—
GET	/api/admin/meta/config	—	—
PUT	/api/admin/meta/config	—	payload:MetaConfigUpdate
GET	/api/admin/meta/tracked-roles	—	—
GET	/api/admin/migrate-orphan-data	Inspect what the iter28 orphan-data migration WOULD do (no writes).	—
POST	/api/admin/migrate-orphan-data	Apply the iter28 orphan-data migration. Idempotent — re-running won't	—
GET	/api/admin/newsletter	—	—
GET	/api/admin/newsletter/export	Export CSV de tous les abonnés (séparateur virgule).	—
DELETE	/api/admin/newsletter/{sub_id}	—	sub_id:str
GET	/api/admin/note-service/history	Aggregate the last N Note de Service broadcasts, grouped by source note.	limit:int
POST	/api/admin/note-service/{note_id}/retry-failed	Resend a Note de Service ONLY to recipients whose previous attempt	note_id:str
GET	/api/admin/pawapay/callback-urls	Iter38r-fix2 — Returns the 2 callback URLs to paste into the PawaPay	—
POST	/api/admin/payment-methods	—	payload:PaymentMethodPaylo
DELETE	/api/admin/payment-methods/{pid}	—	pid:str
PATCH	/api/admin/payment-methods/{pid}	—	pid:str, payload:PaymentMethodPaylo
GET	/api/admin/payroll-webhooks/config	—	—
PATCH	/api/admin/payroll-webhooks/config	—	payload:WebhookConfigPaylo
GET	/api/admin/payroll-webhooks/log	—	limit:int
GET	/api/admin/payroll-webhooks/outbound/preview	Returns the JSON that would be sent — useful for review before dispatch.	month:str

Méthode	Endpoint	Description	Paramètres
POST	/api/admin/payroll-webhooks/outbound/test	—	month:str
GET	/api/admin/policies	Return the 3 fixed policy slots with metadata + public share URL.	—
DELETE	/api/admin/policies/{slot}	—	slot:str
POST	/api/admin/policies/{slot}/upload	—	slot:str, file:UploadFile, admin_user:dict
POST	/api/admin/product-categories	—	payload:ProductCategoryPay
DELETE	/api/admin/product-categories/{cid}	—	cid:str
GET	/api/admin/products	—	—
POST	/api/admin/products	—	payload:ProductPayload
DELETE	/api/admin/products/{pid}	—	pid:str
PATCH	/api/admin/products/{pid}	—	pid:str, payload:ProductPayload
GET	/api/admin/profile-requests	Iter34I — List user-submitted requests to update their own profile.	status:str, limit:int
PATCH	/api/admin/profile-requests/{req_id}	Iter34I — Mark a profile-update request as processed (or back to pending)	req_id:str, payload:Dict[str, Any], admin:dict
GET	/api/admin/qdrant/collections	—	—
POST	/api/admin/qdrant/collections	—	payload:dict
DELETE	/api/admin/qdrant/collections/{name}	—	name:str
PATCH	/api/admin/qdrant/collections/{name}	Update collection metadata (enabled_for_liluvine, description).	name:str, payload:dict
GET	/api/admin/qdrant/collections/{name}/points	—	name:str, limit:int
POST	/api/admin/qdrant/collections/{name}/points/image	S041 + P1 (2026-02) — Upload an image, save it in the media	name:str, file:UploadFile, title:str, caption:str, auto_describe:str
POST	/api/admin/qdrant/collections/{name}/points/pdf	—	name:str, file:UploadFile
POST	/api/admin/qdrant/collections/{name}/points/text	—	name:str, payload:dict
POST	/api/admin/qdrant/collections/{name}/points/url	—	name:str, payload:dict
DELETE	/api/admin/qdrant/collections/{name}/points/{pid}	—	name:str, pid:str
POST	/api/admin/qdrant/collections/{name}/search	—	name:str, payload:dict
POST	/api/admin/qdrant/migrate-mongo-kb	One-shot migration : pull all entries from `liluvine_kb_entries`	payload:dict

Méthode	Endpoint	Description	Paramètres
GET	/api/admin/qdrant/storage	S041 — Total estimated Qdrant disk usage vs cluster quota.	—
POST	/api/admin/qdrant/test-connection	—	—
POST	/api/admin/realign-user-to-client	Apply the realign_plan returned by /admin/client-data-diagnostic.	payload:Dict[str, Any]
GET	/api/admin/resolve-company	Resolve the canonical client for a given company name.	company:str
GET	/api/admin/rgpd-preview/{client_id}	Preview what a non-privileged user of `client_id` would see in their	client_id:str
GET	/api/admin/roadmap-actions	List every roadmap action ordered by code asc. Seeds on first call.	—
POST	/api/admin/roadmap-actions	Admin-driven creation of a pending action. Auto-numbered. Default	payload:Dict[str, Any]
DELETE	/api/admin/roadmap-actions/{code}	Only admin-created (non-seed) entries can be deleted to keep the	code:str
PATCH	/api/admin/roadmap-actions/{code}	Admins can edit `observations`, `done`/`status`, and (for their own	code:str, payload:Dict[str, Any]
GET	/api/admin/secrets/audit	Audit trail of every vault export/import action.	—
GET	/api/admin/secrets/change-audit	Audit trail of vault-tracked key changes (no values, only fingerprints).	key:Optional[str], limit:int
POST	/api/admin/secrets/export	Export an AES-256-GCM encrypted bundle of every vaultable setting.	payload:Dict[str, Any]
POST	/api/admin/secrets/import	Restore a previously-exported vault.	file:UploadFile, password:str, dry_run:str, overwrite_filled:str
GET	/api/admin/secrets/keys	List the settings keys saved by the vault, and which of them are	—
GET	/api/admin/settings	—	—
PUT	/api/admin/settings	—	payload:SettingsUpdate
POST	/api/admin/settings/test-url	—	payload:CriticalUrlTestReq
GET	/api/admin/sms/dashboard	—	days:int
POST	/api/admin/sms/test	Send a test SMS using a chosen provider — surfaces the full HTTP response	payload:AdminSmsTestReq
GET	/api/admin/snapshots	List all snapshots ordered by created_at desc.	—
POST	/api/admin/snapshots	Create a new snapshot of all business collections.	payload:Dict[str, Any]
POST	/api/admin/snapshots/auto-run	Trigger the weekly auto-snapshot logic immediately (manual).	—
POST	/api/admin/snapshots/import	Import a snapshot file. mode = 'replace' 'merge'. dry_run='true' to	file:UploadFile, mode:str, dry_run:str, comment:str

Méthode	Endpoint	Description	Paramètres
GET	/api/admin/snapshots/imports	—	—
GET	/api/admin/snapshots/weekly-report-preview	Render the weekly health-report PDF on-demand. Useful for the admin	—
DELETE	/api/admin/snapshots/{snap_id}	—	snap_id:str
PATCH	/api/admin/snapshots/{snap_id}	—	snap_id:str, payload:Dict[str, Any]
GET	/api/admin/snapshots/{snap_id}/download	—	snap_id:str
GET	/api/admin/stripe/webhook-events	—	limit:int
GET	/api/admin/subscriptions/categories	—	—
POST	/api/admin/subscriptions/categories	—	payload:SubscriptionCategory
DELETE	/api/admin/subscriptions/categories/{cat_id}	—	cat_id:str
PUT	/api/admin/subscriptions/categories/{cat_id}	—	cat_id:str, payload:SubscriptionCategory
GET	/api/admin/subscriptions/orders	—	—
GET	/api/admin/subscriptions/plans	—	—
POST	/api/admin/subscriptions/plans	—	payload:SubscriptionPlanCr
DELETE	/api/admin/subscriptions/plans/{plan_id}	—	plan_id:str
PUT	/api/admin/subscriptions/plans/{plan_id}	—	plan_id:str, payload:SubscriptionPlanUpdate
GET	/api/admin/suggestions-registry	—	—
POST	/api/admin/support-load	—	payload:AdminSupportLoadUp
GET	/api/admin/tenant-country	—	—
PATCH	/api/admin/tenant-country	—	payload:TenantCountrySelect
GET	/api/admin/testimonials	—	—
POST	/api/admin/testimonials	Création manuelle d'un témoignage par l'admin.	payload:dict
POST	/api/admin/testimonials/request/{appt_id}	Génère/regénère un feedback_token pour un RDV (le admin peut ensuite copier le lien et l'envoyer).	appt_id:str
DELETE	/api/admin/testimonials/{tid}	—	tid:str
PUT	/api/admin/testimonials/{tid}	Modère ou modifie un témoignage. Champs supportés : status, comment, client_name,	tid:str, payload:dict
GET	/api/admin/tracked-users	—	client_id:Optional[str]

Méthode	Endpoint	Description	Paramètres
POST	/api/admin/tracked-users	—	payload:TrackedUser Create
POST	/api/admin/tracked-users/bulk-transfer	—	payload:BulkTransferTracke, admin_user:dict
DELETE	/api/admin/tracked-users/{tu_id}	—	tu_id:str
PUT	/api/admin/tracked-users/{tu_id}	—	tu_id:str, payload: TrackedUserUpdate
POST	/api/admin/tracked-users/{tu_id}/revoke-password	—	tu_id:str
POST	/api/admin/tracked-users/{tu_id}/set-password	Provision (or reset) a login for a tracked user.	tu_id:str, payload: TrackedUserSetPass
POST	/api/admin/upload	—	file:UploadFile
GET	/api/admin/usage/sms-providers	—	days:int
GET	/api/admin/usage/summary	Aggregate usage metrics per client over the last N days.	days:int
GET	/api/admin/user-activity	Returns:	period:str, company: Optional[str], limit:int
GET	/api/admin/user-activity/heatmap	Returns a 7×24 grid of hit counts (rows = weekdays 0..6 Mon→Sun,	period:str, company: Optional[str]
GET	/api/admin/users/can-cash	—	—
PATCH	/api/admin/users/{uid}/can-cash	—	uid:str, payload:dict
GET	/api/admin/visits	—	limit:int
POST	/api/admin/visits/reset	Resets the publicly displayed visits counter to zero (real visits	payload:Dict[str, Any]
GET	/api/admin/visits/stats	—	—
GET	/api/admin/voice-notifications/catalog	—	—
GET	/api/admin/voice-notifications/config	—	—
PUT	/api/admin/voice-notifications/config	—	payload:Dict[str, Any]
POST	/api/admin/voice-notifications/custom-events	—	payload:Dict[str, Any]
DELETE	/api/admin/voice-notifications/custom-events/{event_key}	—	event_key:str
GET	/api/admin/voice-notifications/log	—	limit:int
GET	/api/admin/voice-notifications/rules	—	—
PUT	/api/admin/voice-notifications/rules/{event_key}	—	event_key:str, payload:Dict[str, Any]
POST	/api/admin/voice-notifications/test	—	payload:Dict[str, Any]
GET	/api/admin/wa-demo/recent	—	limit:int
POST	/api/admin/wa-demo/{user_id}/mark-seen	—	user_id:str
POST	/api/admin/wa-otp/test	—	payload:Dict[str, Any]

Méthode	Endpoint	Description	Paramètres
POST	/api/admin/wa-tasks-digest/run-now	—	—
GET	/api/admin/whatsapp/silence-alerts	List past silence alerts (audit trail).	limit:int
POST	/api/admin/whatsapp/silence-check	Manually run the WhatsApp silence detector (also runs every 4h via cron).	—
GET	/api/admin/whatsapp/template-notes	—	—
DELETE	/api/admin/whatsapp/template-notes/{name}	—	name:str
PUT	/api/admin/whatsapp/template-notes/{name}	—	name:str, payload:WaTemplateNoteUps
GET	/api/admin/whatsapp/templates	List all templates from the configured WABA + merge admin notes (description + availability).	—
POST	/api/admin/whatsapp/templates	Submit a new template to Meta for approval.	payload:WaTemplateCreate
DELETE	/api/admin/whatsapp/templates/{name}	Delete a template by name (deletes ALL languages of this name on the WABA).	name:str
POST	/api/admin/whatsapp/test-config	Validate Meta credentials by probing Graph API for WABA + phone number.	—
DELETE	/api/admin/whatsapp/webhook-logs	Purge all stored webhook payloads.	—
GET	/api/admin/whatsapp/webhook-logs	Iter35a — Read the last `limit` raw webhook payloads received from	limit:int
GET	/api/api-routes	Liste tous les endpoints disponibles (pour la page /api-docs).	—
POST	/api/appointments/public	—	payload:PublicAppointmentR
GET	/api/auth/captcha-config	—	—
POST	/api/auth/change-password	—	payload:ChangePasswordReq
POST	/api/auth/login	—	payload:LoginRequest
GET	/api/auth/me	—	—
POST	/api/auth/resend-otp	—	session_token:str
POST	/api/auth/verify-otp	—	payload:OtpVerifyRequest
POST	/api/auth/wa-otp/request	—	payload:Dict[str, Any]
POST	/api/auth/wa-otp/verify	—	payload:Dict[str, Any]
GET	/api/availability	Return list of free/busy slots for a given date.	date:str
GET	/api/blog	—	tag:Optional[str]
GET	/api/blog/tags	—	—
GET	/api/blog/{slug}	—	slug:str
GET	/api/case-studies	—	—

Méthode	Endpoint	Description	Paramètres
GET	/api/case-studies/{slug}	—	slug:str
GET	/api/cashier/auto-reliance/settings	—	—
PUT	/api/cashier/auto-reliance/settings	—	payload:dict
GET	/api/cashier/expenses	—	month:Optional[str], user_id:Optional[str], status:Optional[str]
POST	/api/cashier/expenses	—	payload:ExpensePayload
GET	/api/cashier/expenses/employees-list	Iter38m — Lightweight list of employees of the current tenant for the	—
GET	/api/cashier/expenses/me/dashboard-card	Sum of MY unjustified expenses + those late-unjustified.	—
GET	/api/cashier/expenses/monthly-summary	—	month:str
DELETE	/api/cashier/expenses/{eid}	—	eid:str
PATCH	/api/cashier/expenses/{eid}	Iter38o — Edit allowed if NOT justified (clôturée):	eid:str, payload:ExpenseUpdatePayload
POST	/api/cashier/expenses/{eid}/justify	Justifies an expense. Refused if past the deadline (unless admin uses force=true).	eid:str, payload:ExpenseJustifyPayload
POST	/api/cashier/expenses/{eid}/unjustify	Admin only — revert justification (e.g. mistake).	eid:str
GET	/api/cashier/exports/invoices.csv	—	kind:Optional[str], status:Optional[str], limit:int, business_client_id:Optional[str]
GET	/api/cashier/exports/invoices.pdf	—	kind:Optional[str], status:Optional[str], limit:int, business_client_id:Optional[str]
GET	/api/cashier/exports/receipts.csv	—	limit:int, business_client_id:Optional[str]
GET	/api/cashier/exports/receipts.pdf	—	limit:int, business_client_id:Optional[str]
POST	/api/cashier/import/business-clients	—	payload:dict
GET	/api/cashier/import/business-clients/fields	—	—
POST	/api/cashier/import/products	—	payload:dict
GET	/api/cashier/import/products/fields	—	—
GET	/api/cashier/invoices	—	kind:Optional[str], status:Optional[str], business_client_id:Optional[str], include_delete

Méthode	Endpoint	Description	Paramètres
POST	/api/cashier/invoices	—	payload:InvoicePayload
DELETE	/api/cashier/invoices/{iid}	—	iid:str, purge:bool
GET	/api/cashier/invoices/{iid}	—	iid:str
PATCH	/api/cashier/invoices/{iid}	—	iid:str, payload:InvoicePatchPayload
POST	/api/cashier/invoices/{iid}/duplicate	—	iid:str
GET	/api/cashier/invoices/{iid}/pdf	—	iid:str
GET	/api/cashier/invoices/{iid}/qr.png	—	iid:str
POST	/api/cashier/invoices/{iid}/receipt	Explicit receipt generation for an ALREADY-paid invoice (reprint).	iid:str, payload:ReceiptPayload
POST	/api/cashier/invoices/{iid}/restore	—	iid:str
POST	/api/cashier/invoices/{iid}/send-whatsapp	—	iid:str, payload:dict
GET	/api/cashier/kpis	—	—
GET	/api/cashier/legal-forms	—	—
GET	/api/cashier/overdue/count	—	grace_days:int
POST	/api/cashier/overdue/relance	—	payload:dict
POST	/api/cashier/overdue/relance-auto-run	Iter36y — Trigger the auto-relance flow manually (admin/superviseur).	—
GET	/api/cashier/overdue/relance-history	—	limit:int
GET	/api/cashier/product-categories	—	—
POST	/api/cashier/products/generate-icon	—	payload:dict
GET	/api/cashier/receipts	—	limit:int, business_client_id:Optional[str], include_deleted:bool
POST	/api/cashier/receipts	—	payload:ReceiptPayload
DELETE	/api/cashier/receipts/{rid}	—	rid:str, purge:bool
GET	/api/cashier/receipts/{rid}	—	rid:str
GET	/api/cashier/receipts/{rid}/pdf	—	rid:str
GET	/api/cashier/receipts/{rid}/qr.png	—	rid:str
POST	/api/cashier/receipts/{rid}/restore	—	rid:str
POST	/api/cashier/receipts/{rid}/send-whatsapp	—	rid:str, payload:dict
GET	/api/cashier/tenant-info	—	—
GET	/api/catalog	—	—
GET	/api/client-categories	—	—
GET	/api/company-info	—	—
POST	/api/contact	—	payload:ContactCreate
GET	/api/content	—	lang:Optional[str]

Méthode	Endpoint	Description	Paramètres
GET	/api/content/{slug}	—	slug:str, lang:Optional[str]
GET	/api/deployments	Public list, grouped by country, with all solutions and total installations.	—
GET	/api/document-categories	—	—
GET	/api/feedback/{token}	Récupère les infos d'un RDV via son feedback_token (formulaire NPS public).	token:str
POST	/api/feedback/{token}	Soumet un témoignage NPS via le feedback_token. payload: {score:int, comment:str, allow_publish:bool}	token:str, payload:dict
GET	/api/files/ai/{tenant_id}/{filename}	—	tenant_id:str, filename:str
GET	/api/files/{file_id}	—	file_id:str
GET	/api/files/{file_path:path}	Iter38r-fix8 — Proxy endpoint serving files from Emergent Object Storage.	file_path:str
GET	/api/health	—	—
GET	/api/hr/absences	—	employee_id:Optional[str], month:Optional[str]
POST	/api/hr/absences	—	payload:AbsencePayload
POST	/api/hr/absences/scan	Auto-detect business days in month with no access_logs entry.	employee_id:str, month:str
DELETE	/api/hr/absences/{aid}	—	aid:str
PATCH	/api/hr/absences/{aid}	—	aid:str, payload:AbsenceUpdate
POST	/api/hr/absences/{aid}/approve	Iter40 — Approve an absence (typically a !absence WA request).	aid:str
POST	/api/hr/absences/{aid}/reject	Iter40 — Reject a pending absence : remove + re-activate user.	aid:str
GET	/api/hr/advances	—	employee_id:Optional[str]
POST	/api/hr/advances	—	payload:AdvancePayload
DELETE	/api/hr/advances/{aid}	—	aid:str
POST	/api/hr/advances/{aid}/approve	Iter40 — Approve a pending advance (typically WA-issued).	aid:str
POST	/api/hr/advances/{aid}/reject	Iter40 — Reject (delete) a pending advance.	aid:str
POST	/api/hr/advances/{aid}/repay	—	aid:str, payload:AdvanceRepayPayload
DELETE	/api/hr/allowances/{aid}	—	aid:str
PATCH	/api/hr/allowances/{aid}	—	aid:str, payload:AllowanceUpdate

Méthode	Endpoint	Description	Paramètres
DELETE	/api/hr/bonuses/{bid}	—	bid:str
PATCH	/api/hr/bonuses/{bid}	—	bid:str, payload:BonusUpdate
GET	/api/hr/dashboard/monthly-presence	Top 10 employees by accumulated hours for the given month.	month:Optional[str]
GET	/api/hr/dashboard/weekly-presence	Top 5 active employees this calendar week (Mon-Sun, UTC).	—
GET	/api/hr/eligible-users	—	—
GET	/api/hr/employees	—	include_deleted:bool
POST	/api/hr/employees	—	payload:EmployeePayload
POST	/api/hr/employees/backfill-matricules	Iter38c — Assign auto-generated matricule to employees missing one (tenant-scoped).	—
DELETE	/api/hr/employees/{eid}	—	eid:str
PATCH	/api/hr/employees/{eid}	—	eid:str, payload:EmployeeUpdate
GET	/api/hr/employees/{eid}/allowances	—	eid:str
POST	/api/hr/employees/{eid}/allowances	—	eid:str, payload:AllowancePayload
POST	/api/hr/employees/{eid}/apply-catalog/{cid}	0-3 — Apply a catalog template to an employee. For allowances,	eid:str, cid:str, amount:Optional[float], bonus_month:Optional[str]
GET	/api/hr/employees/{eid}/bonuses	—	eid:str, month:Optional[str]
POST	/api/hr/employees/{eid}/bonuses	—	eid:str, payload:BonusPayload
GET	/api/hr/employees/{eid}/payslip	—	eid:str, month:str
GET	/api/hr/employees/{eid}/payslip.pdf	—	eid:str, month:str
POST	/api/hr/employees/{eid}/restore	—	eid:str
GET	/api/hr/employees/{eid}/timesheet	—	eid:str, month:str
POST	/api/hr/employees/{src_eid}/copy-pay-items	—	src_eid:str, payload:CopyPayItemsPayload
GET	/api/hr/holidays	—	year:Optional[int]
POST	/api/hr/holidays	—	payload:HolidayPayload
POST	/api/hr/holidays/import	Import known fixed-date holidays for the given year/country.	year:int, country:Optional[str]
DELETE	/api/hr/holidays/{hid}	—	hid:str
PATCH	/api/hr/holidays/{hid}	—	hid:str, payload:HolidayUpdate
GET	/api/hr/pay-catalog	—	kind:Optional[str]

Méthode	Endpoint	Description	Paramètres
POST	/api/hr/pay-catalog	—	payload:PayCatalogItemPayl
DELETE	/api/hr/pay-catalog/{cid}	—	cid:str
PATCH	/api/hr/pay-catalog/{cid}	—	cid:str, payload:PayCatalogItemUpda
GET	/api/hr/settings	—	—
PATCH	/api/hr/settings	—	payload:HrSettingsPayload
GET	/api/hr/taxes	—	—
PUT	/api/hr/taxes	Replace the tenant's taxes (max 5).	payload:TaxesReplacePayloa
GET	/api/i18n/detect	Return {"suggested_lang": "fr en ar"} based on Cloudflare / CDN	—
GET	/api/i18n/languages	—	—
GET	/api/i18n/translations	Return {key: text} for the requested language. Falls back to FR	lang:str
POST	/api/integrations/build-link	—	payload:BuildLinkRequest
GET	/api/integrations/link-actions	List the supported deep-link actions for the admin UI dropdown.	—
GET	/api/integrations/resolve-link	Public endpoint — decode a link token, return its claims so the SPA	t:str
POST	/api/me/access-log	Records a portal page access. Called by the SPA on each route change.	payload:AccessLogCreate
GET	/api/me/account	—	—
GET	/api/me/account-detail	Iter34k — Read-only account profile shown in the user-menu "Mon	—
GET	/api/me/admin-clients	Le client Primaire (Superviseur) voit tous les autres clients ayant le rôle 'admin'.	—
PUT	/api/me/admin-clients/{target_id}	—	target_id:str, payload:UserUpdateAdmin
GET	/api/me/ai-usage	—	—
POST	/api/me/ai/edit-image	—	prompt:str, file:UploadFile
POST	/api/me/ai/generate-image	—	payload:GenerateImagePaylo
POST	/api/me/ai/generate-image-imagen	—	payload:Dict[str, Any]
POST	/api/me/ai/generate-profile-photo	—	payload:ProfilePhotoPayloa
POST	/api/me/ai/generate-video	—	payload:GenerateVideoPaylo
POST	/api/me/ai/generate-video-veo	—	payload:Dict[str, Any]
GET	/api/me/ai/generate-video-veo/{job_id}	—	job_id:str

Méthode	Endpoint	Description	Paramètres
GET	/api/me/ai/history	—	limit:int
GET	/api/me/ai/summaries	List the calling user's saved AI summaries (admins see everything,	limit:int
DELETE	/api/me/ai/summaries/{sid}	—	sid:str
POST	/api/me/ai/summaries/{sid}/to-report	Convert a saved AI summary into a Report (or a Suivi if a client_id is	sid:str, payload: AiSummaryToReport
POST	/api/me/ai/summarize	—	payload: AiSummaryRequest
POST	/api/me/ai/tts-elevenlabs	—	payload: Dict[str, Any]
GET	/api/me/ai/voices	—	—
POST	/api/me/ai/voices/clone	—	name:str, description:str, audio_file: UploadFile
DELETE	/api/me/ai/voices/{voice_id}	—	voice_id:str
POST	/api/me/api-trace	Records one API call from the frontend (mutations only, set up by the axios interceptor).	payload: ApiTraceCreate
GET	/api/me/appointments	All users belonging to the same client see the same set of RDV.	—
POST	/api/me/appointments	—	payload: ClientAppointmentR
DELETE	/api/me/appointments/{appt_id}	—	appt_id:str
PUT	/api/me/appointments/{appt_id}	Client may edit their own upcoming appointments (pending/confirmed).	appt_id:str, payload: AppointmentUpdate
GET	/api/me/branding	Return branding to display in the connected portal sidebar.	—
GET	/api/me/catalog/export.csv	—	days:int, event_type: Optional[str]
GET	/api/me/catalog/history	—	days:int, limit:int, event_type: Optional[str]
POST	/api/me/catalog/quotes/mark-treated	—	payload: MarkQuoteTreatedPa
GET	/api/me/catalog/stats	—	days:int
GET	/api/me/chat/clients	—	—
GET	/api/me/chat/media/{msg_id}	—	msg_id:str
POST	/api/me/chat/messages/{msg_id}/read	—	msg_id:str
GET	/api/me/chat/search	—	q:str, client_id: Optional[str], limit:int
POST	/api/me/chat/transcribe	—	audio: UploadFile, language:str
GET	/api/me/chat/unread-count	—	—
GET	/api/me/chat/{client_id}/members	—	client_id:str

Méthode	Endpoint	Description	Paramètres
GET	/api/me/chat/{client_id}/messages	—	client_id:str, with_user:str, before:Optional[str], limit:int
POST	/api/me/chat/{client_id}/messages	—	client_id:str, payload:SendMessagePayload
POST	/api/me/chat/{client_id}/messages/photo	—	client_id:str, photo:UploadFile, recipient_id:Optional[str], caption:Optional[str], reply_
GET	/api/me/chat/{client_id}/threads	—	client_id:str
POST	/api/me/chat/{client_id}/threads/{thread_key}/mark-all-read	Bulk mark every message of a thread as read for current user.	client_id:str, thread_key:str
GET	/api/me/clients	Minimal client list for elevated users (used in suivis/intervention forms).	—
GET	/api/me/clients-roster	Returns a public-safe roster of clients used to populate the company dropdown	—
GET	/api/me/contact-groups	—	—
POST	/api/me/contact-groups	—	payload:GroupCreate
POST	/api/me/contact-groups/resolve	Expand a (groups, contacts) selection into the unique target list.	payload:ResolvePayload
DELETE	/api/me/contact-groups/{gid}	—	gid:str
PUT	/api/me/contact-groups/{gid}	—	gid:str, payload:GroupUpdate
POST	/api/me/contact-groups/{gid}/contacts	—	gid:str, payload:AddContactsPayload
DELETE	/api/me/contact-groups/{gid}/contacts/{contact_id}	—	gid:str, contact_id:str
GET	/api/me/contact-inbox	Inbox of messages submitted via the public contact form.	—
GET	/api/me/contacts	List ALL contacts of the user's client scope.	—
POST	/api/me/contacts	—	payload:ContactCreate
GET	/api/me/contacts/export.csv	Iter34w — Export the directory as CSV (Excel-compatible, UTF-8 BOM).	—
GET	/api/me/contacts/export.json	—	—
GET	/api/me/contacts/export.pdf	Iter34w — Generate a PDF listing of the visible directory (ReportLab).	—
POST	/api/me/contacts/import-cross-tenant	Create a contact row in the caller's tenant scope from any	payload:CrossTenantImportP
GET	/api/me/contacts/search-cross-tenant	Search a phone number across ALL tenants. Returns sanitized	phone:str
DELETE	/api/me/contacts/{cid}	—	cid:str

Méthode	Endpoint	Description	Paramètres
PUT	/api/me/contacts/{cid}	—	cid:str, payload:ContactUpdate
GET	/api/me/contacts/{cid}/active-ticket	Convenience: returns the non-closed ticket for a contact (if any).	cid:str
GET	/api/me/contacts/{cid}/messages	Return the full WhatsApp conversation for a contact of the directory.	cid:str
POST	/api/me/contacts/{cid}/messages/mark-read	Mark all inbound WA messages of a given contact as read (sets read_by_us_at).	cid:str
DELETE	/api/me/contacts/{cid}/photo	Remove a contact's profile picture (sets photo_url to null).	cid:str
POST	/api/me/contacts/{cid}/photo	Upload a profile picture for a contact (à la WhatsApp avatar). Stored in	cid:str, file:UploadFile
POST	/api/me/contacts/{cid}/ticket	Open a new support ticket from the WhatsApp chat window. Blocks if	cid:str, payload:TicketOpenPayload
POST	/api/me/contacts/{cid}/wa-sync	Read the latest WhatsApp profile name we observed for this contact's	cid:str
POST	/api/me/contacts/{contact_id}/save-as-tracked-user	Same as /admin/contacts/{id}/save-as-tracked-user but also auto-generates a password,	contact_id:str, payload:SaveContactAsTrack
GET	/api/me/dashboard/ticket-stats	Per-user ticket resolution score (only `done` tickets count) over the	days:int
GET	/api/me/dashboard/wa-media-summary	Return a synthesis of WhatsApp inbound media received in the last `days`.	days:int
GET	/api/me/dashboard/wa-reply-stats	Return per-user WhatsApp reply-time aggregates for the trailing window.	days:int
GET	/api/me/demo/status	Iter35h — Frontend uses this endpoint to render the persistent	—
GET	/api/me/documents	RGPD: anonymizes uploaded_by_email/name for non-privileged roles.	—
POST	/api/me/documents	—	payload:DocumentCreate
DELETE	/api/me/documents/{doc_id}	—	doc_id:str
POST	/api/me/download-requests	—	payload:DownloadRequest
GET	/api/me/download-requests/admin/audit	—	status:Optional[str], q:Optional[str], limit:int
GET	/api/me/download-requests/{token}	—	token:str
POST	/api/me/download-requests/{token}/cancel	—	token:str
GET	/api/me/features	Resolve the SMART Communications feature flags for the calling user.	—
GET	/api/me/form-categories	—	—

Méthode	Endpoint	Description	Paramètres
POST	/api/me/form-categories	—	payload:CategoryCreate
DELETE	/api/me/form-categories/{cid}	—	cid:str
PUT	/api/me/form-categories/{cid}	—	cid:str, payload:CategoryUpdate
POST	/api/me/form-categories/{cid}/set-default	—	cid:str
GET	/api/me/formations	—	—
GET	/api/me/formations/{fid}	—	fid:str
POST	/api/me/formations/{fid}/enroll	—	fid:str
POST	/api/me/formations/{fid}/modules/{mid}/ask	Forwards the user's question to the module's external REST API as configured by the admin.	fid:str, mid:str, payload:FormationModuleQueue
POST	/api/me/formations/{fid}/modules/{mid}/visit	Mark a module as visited (call when the page is OPENED).	fid:str, mid:str
POST	/api/me/formations/{fid}/modules/{mid}/visit/{visit_id}/close	Records the duration once the user leaves the module.	fid:str, mid:str, visit_id:str
POST	/api/me/formations/{fid}/stripe/checkout	Create a Stripe Checkout Session for a paid formation.	fid:str, payload:CheckoutPayload
GET	/api/me/forms	List forms: all of the user's client + all public forms from other clients.	—
POST	/api/me/forms	—	payload:FormCreate
GET	/api/me/forms-analytics	Global analytics across all forms the user can see.	date_from:Optional[str], date_to:Optional[str]
GET	/api/me/forms/title-suggestions	—	—
DELETE	/api/me/forms/{form_id}	—	form_id:str
GET	/api/me/forms/{form_id}	—	form_id:str
PUT	/api/me/forms/{form_id}	—	form_id:str, payload:FormUpdate
GET	/api/me/forms/{form_id}/analytics	—	form_id:str, date_from:Optional[str], date_to:Optional[str]
GET	/api/me/forms/{form_id}/analytics/export.csv	CSV export of all submissions for a form (flat answers + metadata).	form_id:str, date_from:Optional[str], date_to:Optional[str]
POST	/api/me/forms/{form_id}/import	Duplicate a public form into the current client's scope (numbered & owned by them).	form_id:str
GET	/api/me/forms/{form_id}/submission	Return the current user's submission for the form (or an empty stub).	form_id:str
POST	/api/me/forms/{form_id}/submission	—	form_id:str, payload:SubmissionSave
GET	/api/me/forms/{form_id}/submissions	List all submissions for a form — owner/admin only.	form_id:str

Méthode	Endpoint	Description	Paramètres
GET	/api/me/forms/{form_id}/submissions-table	—	form_id:str, date_from:Optional[str], date_to:Optional[str], limit:int
POST	/api/me/forms/{form_id}/upload	Per-form file attachment uploader (max 1 Mo). Used by the new "file" field	form_id:str, file:UploadFile
GET	/api/me/gdpr/export	—	—
GET	/api/me/idle-config	—	—
POST	/api/me/inbox/import-contact	Create a contact from an inbox thread that has no matching contact	payload:Dict[str, Any]
POST	/api/me/inbox/mark-read/{channel}/{thread_id}	—	channel:str, thread_id:str, page_id:Optional[str]
POST	/api/me/inbox/send	—	payload:InboxSendPayload
GET	/api/me/inbox/unified	Return up to `limit` threads from WhatsApp + Messenger, recency-sorted.	limit:int
GET	/api/me/inbox/unified/{channel}/{thread_id}	Return ordered messages of a single thread.	channel:str, thread_id:str, page_id:Optional[str], limit:int
GET	/api/me/intervention-reasons	Return the (admin-configurable) list of preset reasons used by the	—
GET	/api/me/interventions	RGPD: anonymizes the technician name for non-privileged roles.	—
POST	/api/me/interventions	—	payload:InterventionCreate
DELETE	/api/me/interventions/{int_id}	—	int_id:str
GET	/api/me/liluvine-pro/autoreply-feed	—	since:Optional[str]
GET	/api/me/liluvine-pro/branding	—	—
POST	/api/me/liluvine-pro/chat	—	payload:ChatMessage
POST	/api/me/liluvine-pro/chat-with-image	—	file:UploadFile, text:str, session_id:Optional[str]
POST	/api/me/liluvine-pro/chat/stream	—	payload:ChatMessage
POST	/api/me/liluvine-pro/request-help	—	payload:Dict[str, Any]
GET	/api/me/liluvine-pro/sessions	—	—
DELETE	/api/me/liluvine-pro/sessions/{sid}	—	sid:str
GET	/api/me/liluvine-pro/sessions/{sid}	—	sid:str
PATCH	/api/me/liluvine-pro/sessions/{sid}	—	sid:str, payload:RenameSession
GET	/api/me/media-library	All media items uploaded by users of the same client. Shared bank.	source:Optional[str]

Méthode	Endpoint	Description	Paramètres
POST	/api/me/media-library	Upload + register a media in the shared client library, returns a stable public URL	file:UploadFile, label:str, target_client_id:str
POST	/api/me/media-library/wa-cleanup	Delete WhatsApp-sourced media library entries whose underlying file is	dry_run:bool
DELETE	/api/me/media-library/{media_id}	—	media_id:str
GET	/api/me/meetings	—	q:Optional[str], limit:int
POST	/api/me/meetings	—	payload:MeetingCreate
DELETE	/api/me/meetings/{mid}	—	mid:str
GET	/api/me/meetings/{mid}	—	mid:str
PUT	/api/me/meetings/{mid}	—	mid:str, payload:MeetingUpdate
GET	/api/me/meetings/{mid}/pdf	—	mid:str
POST	/api/me/meetings/{mid}/sign	—	mid:str
POST	/api/me/meetings/{mid}/unsign	—	mid:str
GET	/api/me/messaging/schedules	List the user's WhatsApp scheduled sends. Admins see everything; portal users	—
POST	/api/me/messaging/schedules	—	payload:MeScheduleCreate
DELETE	/api/me/messaging/schedules/{sid}	—	sid:str
GET	/api/me/messaging/variable-tokens	Portal mirror of variable tokens. Same resolution at send time.	—
GET	/api/me/meta/ads/accounts	—	—
GET	/api/me/meta/ads/accounts/{ad_account_id}/insights	—	ad_account_id:str, date_preset:str
POST	/api/me/meta/ads/campaigns	—	payload:CampaignCreatePayl
POST	/api/me/meta/ads/campaigns/{campaign_id}/status	—	campaign_id:str, payload:CampaignStatusPayl
POST	/api/me/meta/disconnect	—	—
GET	/api/me/meta/messenger/conversations	—	page_id:str, limit:int
POST	/api/me/meta/messenger/send	—	payload:MessengerSendPaylo
GET	/api/me/meta/oauth/callback	—	code:Optional[str], state:Optional[str], error:Optional[str], error_description:Optional[s
GET	/api/me/meta/oauth/url	—	—
GET	/api/me/meta/pages	—	—

Méthode	Endpoint	Description	Paramètres
POST	/api/me/meta/pages/{page_id}/comments/{comment_id}/reply	—	page_id:str, comment_id:str, payload:CommentReplyPayload
POST	/api/me/meta/pages/{page_id}/photos	—	page_id:str, payload:UploadPhotoPayload
GET	/api/me/meta/pages/{page_id}/posts	—	page_id:str, limit:int
POST	/api/me/meta/pages/{page_id}/posts	—	page_id:str, payload:CreatePostPayload
GET	/api/me/meta/pages/{page_id}/posts/{post_id}/comments	—	page_id:str, post_id:str, limit:int
GET	/api/me/meta/status	—	—
GET	/api/me/notes-summary	Returns counts and last update timestamps to display dashboard buttons.	—
GET	/api/me/notes-targets	Iter35m — Return the list of users that a note/task can be addressed to	—
GET	/api/me/notes/{kind}	—	kind:str, author:Optional[str], q:Optional[str], scope:Optional[str]
POST	/api/me/notes/{kind}	—	kind:str, payload:UserNoteCreate
GET	/api/me/notes/{kind}/authors	Distinct authors for the kind — used to populate the filter dropdown.	kind:str
DELETE	/api/me/notes/{kind}/{note_id}	—	kind:str, note_id:str
PUT	/api/me/notes/{kind}/{note_id}	—	kind:str, note_id:str, payload:UserNoteUpdate
POST	/api/me/notes/{kind}/{note_id}/note-de-service	—	kind:str, note_id:str
GET	/api/me/notifications/counts	Return the count of new items per module since the user last visited that module.	—
POST	/api/me/notifications/mark-seen	Mark a module as visited (resets its badge counter to 0).	payload:MarkSeenRequest
GET	/api/me/payment-links	—	—
POST	/api/me/payment-links	—	payload:PaymentLinkCreate
DELETE	/api/me/payment-links/{link_id}	—	link_id:str
PATCH	/api/me/payment-links/{link_id}	—	link_id:str, payload:Dict[str, Any]
GET	/api/me/payments	List the calling user's recent payments. Admin/superviseur see all.	—

Méthode	Endpoint	Description	Paramètres
GET	/api/me/payments-dashboard	—	days:int
POST	/api/me/payments/pawapay/deposit	DEPRECATED (Iter38r) — Replaced by the hosted Payment Page flow because	payload:PawaPayDepositCrea
POST	/api/me/payments/pawapay/payment-page	Iter38r — Initiate a hosted PawaPay Payment Page session.	payload:PawaPayPaymentPage
POST	/api/me/payments/pawapay/payout	—	payload:PayoutCreate
GET	/api/me/payments/pawapay/payout/{pid}	—	pid:str, refresh:bool
GET	/api/me/payments/pawapay/payouts	—	limit:int
GET	/api/me/payments/{deposit_id}	Polling endpoint — refreshes the payment by querying PawaPay if still pending.	deposit_id:str
POST	/api/me/profile-update-request	Iter34k — Submit a free-form request to the admin to correct identity,	payload:Dict[str, Any]
DELETE	/api/me/ratings/{kind}/{target_id}	—	kind:str, target_id:str
POST	/api/me/ratings/{kind}/{target_id}	—	kind:str, target_id:str, payload:RatingCreate
GET	/api/me/recent-activity	Return new activity events for the user's visible scope since the	since:Optional[str], limit:int
POST	/api/me/sms/bulk	—	payload:MeSmsBulkRequest
GET	/api/me/sms/messages	—	limit:int, contact_id:Optional[str]
GET	/api/me/sms/providers	Tell the portal which SMS providers are configured + the default one.	—
GET	/api/me/sms/schedules	—	—
DELETE	/api/me/sms/schedules/{sid}	—	sid:str
POST	/api/me/sms/send	—	payload:MeSmsSendRequest
GET	/api/me/tenant-meta	—	—
GET	/api/me/tenant-users	—	—
GET	/api/me/ticket-motif-templates	—	—
POST	/api/me/ticket-motif-templates	—	payload:TicketMotifTemplat
DELETE	/api/me/ticket-motif-templates/{tpl_id}	—	tpl_id:str
GET	/api/me/tickets	—	status:Optional[str], contact_id:Optional[str], limit:int
POST	/api/me/tickets	Iter38r-fix9o — Quick-create a ticket from the floating bubble.	payload:QuickTicketPayload
GET	/api/me/tickets/cost-summary	Iter37d — Monthly cost aggregate for closed tickets.	months_back:int

Méthode	Endpoint	Description	Paramètres
GET	/api/me/tickets/cost-summary.csv	Iter37e — CSV export du coût mensuel des interventions clôturées.	months_back:int
GET	/api/me/tickets/cost-summary.pdf	Iter37e — PDF export du coût mensuel des interventions clôturées (A4 paysage).	months_back:int
GET	/api/me/tickets/pending-count	Return the number of non-closed tickets in the user's scope.	—
GET	/api/me/tickets/trash	—	limit:int
PATCH	/api/me/tickets/{tid}	—	tid:str, payload:TicketUpdatePayload
POST	/api/me/tickets/{tid}/archive	—	tid:str, payload:Optional[TicketArchive]
POST	/api/me/tickets/{tid}/assign	Assign a ticket to a user (or unassign when user_id is empty).	tid:str, payload:TicketAssignPayload
POST	/api/me/tickets/{tid}/close	—	tid:str, payload:TicketClosePayload
POST	/api/me/tickets/{tid}/reopen	Re-open a closed ticket as a *new* sibling whose number ends with -R{k}.	tid:str, payload:TicketReopenPayload
POST	/api/me/upload	—	file:UploadFile
GET	/api/me/users	—	—
POST	/api/me/wa-import-by-phone	Create a directory contact directly from a phone number (used by the	payload:WaImportByPhoneReq
GET	/api/me/wa-pending-imports	List unknown phone numbers that have written to our WhatsApp Business	—
DELETE	/api/me/wa-pending-imports/{pending_id}	Permanently dismiss a pending WA inbound (won't reappear unless they	pending_id:str
POST	/api/me/wa-pending-imports/{pending_id}/import	Promote a pending WA inbound to a full directory contact. Optionally	pending_id:str, payload:WaPendingImportReq
GET	/api/me/wa-tasks-digest	—	—
PUT	/api/me/wa-tasks-digest	—	payload:Dict[str, Any]
GET	/api/me/welcome-briefing	—	last_seen_at:Optional[str]
POST	/api/me/whatsapp/bulk	Send a Meta-approved WhatsApp template to many CRM contacts at once,	payload:MeWaBulkRequest
GET	/api/me/whatsapp/history	—	limit:int
POST	/api/me/whatsapp/messages/{msg_id}/save-to-library	Register an inbound WhatsApp media in the shared client media library.	msg_id:str, payload:SaveToLibraryRequest
POST	/api/me/whatsapp/send	—	payload:WhatsAppSendRequest
POST	/api/me/whatsapp/send-media	Send a free-form WhatsApp media message inside the Meta 24h window.	to:str, contact_id:Optional[str], tracked_user_id:Optional[str], caption:Optional[str], ad

Méthode	Endpoint	Description	Paramètres
POST	/api/me/whatsapp/send-text	Send a free-form text WhatsApp message — only allowed within the Meta 24h	payload:WhatsAppSendTextRe
GET	/api/me/whatsapp/templates	Portal users: list APPROVED templates + only those marked as available.	—
GET	/api/me/whatsapp/unread	Return per-contact unread counts plus a global total of inbound WA messages	—
GET	/api/meta/webhook	Iter38r-fix3 — Accepts either `meta_webhook_verify_token`	hub_mode:str, hub_challenge:str, hub_verify_token:st r
POST	/api/meta/webhook	Iter38r-fix3 — Detects WhatsApp Cloud payloads	—
POST	/api/newsletter/subscribe	—	payload:dict
POST	/api/newsletter/unsubscribe	—	payload:dict
GET	/api/payment-methods	—	—
GET	/api/payments/stripe/status/{session_id}	Poll the checkout status. Idempotent — enrollment only created	session_id:str
GET	/api/public/ad-banners/active	Return ONE active banner suitable for `placement` (weighted random).	placement:str
GET	/api/public/ad-banners/config	—	—
POST	/api/public/ad-banners/{banner_id}/click	—	banner_id:str, variant:str, modal:int
POST	/api/public/ad-banners/{banner_id}/impression	—	banner_id:str, variant:str, modal:int
GET	/api/public/ads-report/{slug}	Iter38r-fix9y — Public live report for an advertiser. Requires the	slug:str, token:str
POST	/api/public/ads-report/{slug}/ai-plan	—	slug:str, token:str
POST	/api/public/ads-report/{slug}/checkout	Create a Stripe Checkout Session for renewing the campaign.	slug:str, payload:C heckoutPayload, token:str
PUT	/api/public/ads-report/{slug}/media	Self-service media update. The advertiser uploads via the admin	slug:str, payload:M ediaUpdatePayload, token:str
GET	/api/public/ads-report/{slug}/payment-status/{session_id}	Poll endpoint. Confirms the Stripe session and, on first paid	slug:str, session_id:str, token:str
POST	/api/public/ads-report/{slug}/renew	—	slug:str, payload:R enewRequestPayloa, token:str
POST	/api/public/catalog/track	—	payload:CatalogTrac kPayloa
GET	/api/public/coupons/{code}/validate	Validate a coupon for a given XOF amount (UX preview before checkout).	code:str, amount:int
GET	/api/public/docs	—	—

Méthode	Endpoint	Description	Paramètres
GET	/api/public/docs/{slug}	—	slug:str
GET	/api/public/documents	—	—
GET	/api/public/forms/{form_id}	Fetch a public form anonymously — only works when `is_public=True`.	form_id:str
POST	/api/public/forms/{form_id}/submission	—	form_id:str, payload:PublicSubmissionRe
GET	/api/public/incidents	Public timeline of incidents (resolved + ongoing). Used by /uptime page.	limit:int
GET	/api/public/incidents/confirm	—	token:str
POST	/api/public/incidents/subscribe	—	payload:IncidentSubscribeR
GET	/api/public/incidents/unsubscribe	—	token:str
GET	/api/public/invoice-pdf/{token}	—	token:str
GET	/api/public/media-library	All `public=True` media, sorted by sort_order asc then created_at desc.	—
GET	/api/public/og/product/{product_id}	—	product_id:str
GET	/api/public/orders/{order_id}	—	order_id:str
GET	/api/public/pay/{slug}	—	slug:str
POST	/api/public/pay/{slug}/deposit	—	slug:str, payload:PublicPayRequest
GET	/api/public/pay/{slug}/status/{deposit_id}	Polling endpoint for the public payment landing page (no auth).	slug:str, deposit_id:str
GET	/api/public/policies/{slot}	Serve a policy PDF inline so 3rd parties (Google, Facebook...) can verify it.	slot:str
GET	/api/public/products	—	—
POST	/api/public/products/{product_id}/checkout	—	product_id:str, payload:CheckoutRequest
GET	/api/public/receipt-pdf/{token}	—	token:str
GET	/api/public/remote/support/{token}	Inspect the current support load + Liluvine config — gated by HMAC token.	token:str
POST	/api/public/remote/support/{token}	—	token:str, payload:RemoteSupportUpdat
GET	/api/public/status	Public status page data (anyone can fetch). Only public-flagged probes.	window_hours:int
GET	/api/public/subscriptions	Public: returns active plans grouped by category (max 4 categories).	—
POST	/api/public/subscriptions/order	—	payload:SubscriptionOrderC
GET	/api/public/support-load	—	—
GET	/api/public/team-presence	—	—
GET	/api/public/ui-flags	Iter40-route-loader (S051) + Iter40-ui-flags — Tiny anonymous endpoint	—

Méthode	Endpoint	Description	Paramètres
GET	/api/public/verify/{token}	—	token:str
GET	/api/testimonials	Liste les témoignages clients publiés (pour le site public).	—
GET	/api/testimonials/stats	Statistiques NPS publiques (basées uniquement sur les témoignages publiés).	—
POST	/api/track	Enregistre une visite et la transmet (si configuré) à l'API REST externe.	payload:dict
POST	/api/transcribe	Accepts a short audio file (webm/mp3/m4a/wav/ogg, ≤25 Mo) and returns	file:UploadFile, language:str
GET	/api/version	Iter35n — Public version stamp. Surfaced on the login page so users	—
GET	/api/version	Returns the running build's version + last-restart time.	—
GET	/api/visits/count	Total visit counter for the public homepage. Includes admin-tunable offset.	—
GET	/api/visits/trend	Daily visit counts for the last N days (default 7), oldest first.	days:int
POST	/api/voice-notifications/trigger	Used by tracked users or admin to dispatch a voice notification	payload:Dict[str, Any]
GET	/api/wa-action/{token}/{action}	—	token:str, action:str
POST	/api/webhook/stripe	Stripe webhook. Verifies signature, then finalises either a paid	—
POST	/api/webhooks/agenda/{secret}	Inbound webhook from n8n AI Agent. Allows CRUD on appointments using a	secret:str, payload:AgendaWebhookCreat
POST	/api/webhooks/liluvine-pro/{source}/{secret}	—	source:str, secret:str
POST	/api/webhooks/n8n/payroll/{tenant_id}	—	tenant_id:str
POST	/api/webhooks/pawapay/deposits/{secret}	Iter38r-fix2 — PawaPay deposit callback. URL à coller dans le tableau	secret:str
POST	/api/webhooks/pawapay/payouts/{secret}	—	secret:str
POST	/api/webhooks/pawapay/refunds/{secret}	Iter38r-fix2 — PawaPay refund callback. URL à coller dans le tableau	secret:str
POST	/api/webhooks/pawapay/{secret}	Legacy generic PawaPay callback (kept for pre-Iter38r-fix2 configs).	secret:str
GET	/api/webhooks/support-load/{secret}	External webhook to push the current support load (0..7).	secret:str
POST	/api/webhooks/support-load/{secret}	External webhook to push the current support load (0..7).	secret:str
GET	/api/whatsapp/webhook	Meta verifies the webhook via GET with hub.mode=subscribe, hub.verify_token, hub.challenge.	hub_mode:Optional[str], hub_verify_token:Optional[str], hub_challenge:Optional[str]

Méthode	Endpoint	Description	Paramètres
POST	/api/whatsapp/webhook	Receive Meta Cloud API events: new inbound messages + outbound status updates.	—
GET	/docs/oauth2-redirect	—	req: Request
GET	/health	—	—
GET	/healthz	—	—

Nombre total d'API : 766

Toutes les API sont préfixées par **/api** et exigent généralement une authentification Bearer JWT (header Authorization: Bearer <token>). Les endpoints publics (préfixe /api/public/...) sont anonymes.