

# Mobile Forensics

## Lecture 6

Property Lists

# Introduction

- Property List files (\*.plist) are one of the widely used data storage formats used by Apple software .
- Most of the system properties are stored in plists (many of them are located in /Library/Preferences/), but many apps store their configuration in plist-files.
- property lists can be found in various places on Apple systems.
- Property lists offer a structured and efficient way to represent and persist hierarchies of objects to disk

# Binary plist Structure

- Apple disclosed the structure of the binary property list format;
- it is documented in the comments of the Apple-provided open-source `CFBinaryPList.c` and declarations of the `ForFoundationOnly.h`.
- Every binary plist file comprises four sections: a header, an object table, an offset table and a trailer

- Each bplist file begins with an 6-byte header, containing the magic bplist (Hex: 0x62706C697374).
- The header is followed by a 2-byte version
- The most common version on Apple devices is 00, but there are at least two other versions of binary property lists, too; bplist15 or bplist16 occur.

Table 6.1: Structure of a bplist file.

Offset	Size	Description
0x00	6	bplist header (0x62706C697374)
0x06	2	format version
0x08	LEN1	object table
0x08 + LEN1	LEN2	offset table
0x08 + LEN1 + LEN2	32	trailer

- The bplist file ends with a 32-byte long trailer.
- The structure of the trailer is shown in table 6.2.

Table 6.2: Structure of the bplist trailer.

Offset	Length	Description
0x0	5	unused
0x5	1	sort version
0x6	1	size per offset in offset table in bytes
0x7	1	size per object reference in a container
0x8	8	number of objects in object table (big endian)
0x10	8	offset of the first offset in the offset table (big endian)
0x18	8	offset of the offset table (big endian)

- The bytes 0 to 4 of the trailer are unused.
- Byte 5 contains the sort version.
- Byte 6 stores the information of the size in byte of each offset entry in the offset table.
- byte 7 stores the information of the size of each object reference in a container. At offset 0x8, there is an 8-byte entry that saves the number of objects that are encoded inside the object table.
- The following 8 bytes save the offset of the first offset in the offset table (usually zero).
- The last 8 bytes of the trailer denotes the start of the offset table, counting from the start of the bplist.



Table 6.3: Format of object types.

Object	Marker	(Additional Info)	Description
null	0000 0000		
bool	0000 1000		false
bool	0000 1001		true
fill	0000 1111		fill byte
int	0001 nnnn ...		$2^{nnnn}$ bytes (big endian)
real	0010 nnnn ...		$2^{nnnn}$ bytes (big endian)
date	0011 0011 ...		8 byte float (big endian)
data	0100 nnnn [int] ...		nnnn bytes unless 1111 then [int] count followed by bytes
string	0101 nnnn [int] ...		nnnn chars unless 1111 then [int] count followed by bytes
string	0110 nnnn [int] ...		Unicode string, nnnn chars unless 1111 then [int] count followed by bytes
	0111 xxxx		unused
uid	1000 nnnn ...		nnnn+1 bytes
	1001 xxxx		unused
array	1010 nnnn [int] objref*		nnnn entries unless 1111 then [int] count followed by entries
	1011 xxxx		unused
set	1100 nnnn [int] objref*		unused
dict	1101 nnnn [int] keyref*		nnnn entries unless 1111 then [int] count followed by entries
	1110 xxxx		unused
	1111 xxxx		unused

- The marker is the binary representation of a single byte.
- All other objects can be uniquely identified by the marker byte's 4 most significant bits (MSB).
- At the same time, the least significant bits (LSB) of the marker byte denotes sizing information.

# Example

Given is the following plist (Table 6.4) from a MacBook Pro:

Table 6.4: Example plist (object table colored in blue, offset table colored in red, trailer colored in yellow).

62 70 6C 69 73 74 30 30	D2 01 02 03 04 5E 42 61	b p l i s t 0 0	"	^ B a
74 74 65 72 79 48 69 73 74 6F 72 79 5F 10 13 54	6F 74 61 6C 4E 75 6D 62 65 72 6F 66 45 76 65 6E	t t e r y H i s t o r y _	T	
74 73 09 10 0A	08 0D 1C 32 33	o t a l N u m b e r O f E v e n		
01 01 00 00 00 00 00 00 00 00 05 00 00 00 00 00 00	00 00 00 00 00 00 00 00 35	t s -	2 3	
				5

To analyze the bplist in a first step the trailer is marked (here yellow) the trailer comprises the last 32 bytes of the file. Now the trailer can be decoded (result in Table 6.5):

Table 6.5: Decoded example bplist trailer.

Content	Offset	Length	Description
0x00	0x5	1	sort version
0x01	0x6	1	size per offset in offset table
0x01	0x7	1	size per object reference
0x0000000000000005	0x8	8	number of objects in object table
0x0000000000000000	0x10	8	offset of the first offset in offset table
0x0000000000000035	0x18	8	offset of the offset table

- it is clear that the bplist contains five objects in the object table, and the offset table starts at 0x35, whereas the first object-offset starts at  $0x35 + 0x00$ , and each offset has the size of one single byte.

the offsets from the offset table are 0x08, 0x0D, 0x1C, 0x32 and 0x33, which leads to the following four objects from the object table:

1. 0xD2 01 02 03 04
2. 0x5E 42 61 74 74 65 ...
3. 0x5F 10 13 54 6F 74 ...
4. 0x09
5. 0x10 0A


- The first object starts with 0xD2, which is 1101 0010 in binary. The MSB (1101) shows that the object-type is a dictionary.
- The first object starts with 0xD2, which is 1101 0010 in binary. The MSB (1101) shows that the object-type is a dictionary.
- The third object starts with 0x5F, which is 0101 1111 in binary
- The fourth object starts with 0x09, which is 0000 1001 in binary.
- The fifth object starts with 0x10, which is 0001 0000 in binary.

Table 6.6: Decoded example bplist.

dictionary (2 entries)	BatteryHistory	TRUE
	TotalNumberOfEvents	10



Fig. 6.1 shows the same plist file decoded with Apples XCode IDE and confirms the correct decoding.



The image shows a screenshot of the Xcode IDE's interface for editing a property list (plist) file named 'example.plist'. The window title bar includes standard macOS window controls (red, yellow, green buttons) and the file name. Below the title bar is a toolbar with icons for a grid, navigation arrows, and a document icon, followed by the text 'example.plist' and '> No Selection'. The main content area displays a table with three columns: 'Key', 'Type', and 'Value'. The table has three rows: a header row, a row for the 'Root' key (expanded), and two rows for the dictionary items. The 'Root' key is a 'Dictionary' containing '(2 items)'. The first item is 'BatteryHistory' of type 'Boolean' with value 'YES'. The second item is 'TotalNumberOfEvents' of type 'Number' with value '10'. A vertical scrollbar is visible on the right side of the table.

Key	Type	Value
▼ Root	Dictionary	(2 items)
BatteryHistory	Boolean	YES
TotalNumberOfEvents	Number	10

Fig. 6.1: Illustration of the elements of a block group.

# Forensic Tools Supporting plists

- There is quite a bunch of tools supporting the decoding of plist files.
- Most of the tools support binary plists as well as XML property lists.
- if the given property list file is in the binary format, it can be converted to XML first by running on the macOS shell:

```
plutil -convert xml1 file.plist
```

If an XML property list should be converted back this is possible with:

```
plutil -convert binary1 file.plist
```

Key	Type	Value
√ Root	Dictionary	(17 items)
LastSuccessfulDate	Date	2021-05-14T12:48:29Z
AutomaticCheckEnabled	Boolean	0
LastAttemptSystemVersion	String	11.2.2 (20D80)
LastBackgroundCCDSuccessfulDate	Date	2016-09-30T13:05:07Z
AutomaticallyInstallMacOSUpdates	Boolean	0
LastUpdatesAvailable	Number	1
SkipLocalCDN	Boolean	0
LastRecommendedUpdatesAvailable	Number	1
LastAttemptBuildVersion	String	11.2.2 (20D80)
AutomaticDownload	Boolean	0
√ RecommendedUpdates	Array	(1 item)
√ Item 0	Dictionary	(5 items)
Identifier	String	MSU_UPDATE_20E241_patch_11.3.1
MobileSoftwareUpdate	Boolean	1
Display Name	String	macOS Big Sur 11.3.1
Product Key	String	MSU_UPDATE_20E241_patch_11.3.1
Display Version	String	11.3.1
LastFullSuccessfulDate	Date	2021-05-14T12:48:29Z
LastRecommendedMajorOSBundleIdentifier	String	
√ PrimaryLanguages	Array	(2 items)
Item 0	String	de
Item 1	String	de-DE
LastSessionSuccessful	Boolean	1
LastBackgroundSuccessfulDate	Date	2017-07-20T19:07:32Z
LastResultCode	Number	2

Fig. 6.2: View of an example plist in the Xcode editor.




Fig. 6.3: View of an example plist in the Oxygen Forensic Plist Viewer.