Lab Manual

HTML and Javascript

Practical No:- ____

Date:-_____

Name of Student:- _____

Class:-_____   **Roll No:-**_____

Title:

_____

_____

_____

_____

Aim: -

_____

_____

_____

_____

_____

_____

Software Requirement: _____

Hardware Requirement:- _____

Theory:-

CASCADING STYLE SHEETS:-

Inline CSS:-

Inline CSS allows to apply a unique style to one HTML element at a time. Assign CSS to a specific HTML element by using the style attribute with any CSS properties defined within it.

Following example describes CSS style properties for an HTML <p> element in the same line of code.

Use a style attribute to assign CSS styling properties. In this particular case, color and value (blue) apply to the HTML <p> element.

The rules will be applied to that element only.

Syntax:-

        <element style="...style rules....">

Example:-

        <h1 style="color:#36C;> This is inline CSS </h1>

        <p style="color: blue;">This is a paragraph.</p>

<u>Source Code:-</u>

1. Name of File:- inlinestyle.html

```
<html>
<head>
</head>
<body bgcolor="skyblue">
<h1>Student Marks</h1>
<table cellpadding="1" cellspacing="1" border="2" style="background-
color:lightgreen">
<tr style="background-color:pink;line-height:50px;">
<th style="color:darkblue;">Roll No.</th>
<th style="color:darkblue;">Maths</th>
<th style="color:darkblue;">Physics</th>
<th style="color:darkblue;">Chemistry</th>
</tr>
<tr style="text-align:center;">
<td>1</td>
<td>50</td>
<td>75</td>
```

```
<td>60</td>
</tr>
<tr style="text-align:center;">
<td>2</td>
<td>80</td>
<td>85</td>
<td>90</td>
</tr>
<tr style="text-align:center;">
<td>3</td>
<td>70</td>
<td>54</td>
<td>67</td>
</tr>
</body>
</html>
```

Output:-

Conclusion:-

_____

_____

_____

_____