

1. Which of the following pseudo-directories are empty when the system is not running (Select all answers that apply)?

1 / 1 point

☐ /boot

☐ /etc

☒ /sys

✓ Correct

/sys contains only pseudofiles created in memory after system start.

☒ /dev

✓ Correct

/dev contains only pseudofiles created in memory after system start.

☒ /proc

✓ Correct

/proc contains only pseudofiles created in memory after system start.

2. Which of the following statements describes the best practice?

1 / 1 point

☐ The current directory should be appended to the path

☒ The current directory should not be placed in the path

☐ The current directory should be prepended to the path

✓ Correct

3. If **file** does not exist, which command will produce an error?

1 / 1 point

☐ ln -s file file2

☒ ln file file2

✓ Correct

You cannot have a "dangling" hardlink

4. Which command will list the partition information on the first hard disk and then exit?

1 / 1 point

- ☐ **fdisk /dev/sda**
- ☐ **fdisk -l hd1**
- ☒ **fdisk -l /dev/sda**

✓ **Correct**

This will give a report and return to the command line.

5. Which directory trees usually have frequently changing data, and would not be desirable on a partition that is more static? Select all answers that apply.

1 / 1 point

☒ **/tmp**

✓ **Correct**

/tmp is designed for temporary data.

☐ **/bin**

☒ **/home**

✓ **Correct**

/home stores user accounts and data which will change every time the user is on the system.

☒ **/var**

✓ **Correct**

/var is designed for variable, volatile data.

☐ **/usr**