```
L = [5, 6, 3, 8, 12, 0, 21]


print("Length of given list:", len(l))


# b part print the element of given list using
index

print("index of given list:", l.index(0))


# c Adding an element of list

sum = 0

for i in range(len(l)):

   sum = l[i]


print("Sum of list element of", sum)


# d negative index of list

print("negative index of list", l[-1:])


# e Remove of first occurrence

# list1 = ['a','s','r','e']

print("sorted of list", sorted(l))
```

```
data = [2, 3, 6, 1, 7, 9, 3, 90, 5]

mode = max(set(data), key=data.count)

print("Mode:", mode)
```

```
list = [2, 3, 6, 1, 7, 9, 3, 90, 5]

sum1 = 0

for i in range(len(list)):

    sum1 = sum1 + list[i]



mean = sum1 / len(list)

print("Mean of given list:", mean)



# Median of given list

list2 = sorted(list)

print(list2)



mid = len(list2) / 2

print("Median of list", list2.index(5))
```

```
text = ["jammu", "was", "a", "state",
"Delhi", "was", "a", "state"]

text.remove("was")

print(text)
```

```
Y = [[1,2,3],[4,5,6],[7,8,9]]

X = [[3,5,1],[6,8,9],[1,0,2]]



result = [[0,0,0],[0,0,0],[0,0,0]]



for i in range(len(Y)):

   for j in range(len(X)):

      for k in range(len(X)):

         result[i][j] = result[i][j] + Y[i][k] *
X[k][j]



print(result)
```

```
text = ["jammu", "was", "a", "state",
"Delhi", "was", "a", "state"]

for I in range(len(text)):

    if(text[1]==”state”):

        text[i]=”UT”

print(text)
```