

To use an SBCS font that resides in the system, you can specify either a coded font name or a pair of code page name and font character set name. To use a DBCS font that resides in the system, you must specify a coded font name.

Code page

Has an object type *FNTRSC with attribute CDEPAG. A code page has many code points and their corresponding character identifiers. Character identifiers are mapped to corresponding character patterns by a font character set.

Font character set

Has an object type *FNTRSC with attribute FNTCHRSET. A font character set has many character identifiers and their corresponding character patterns.

The WRKFNTRSC command shows you a list of font resources. Most fonts reside in libraries that have names that start with QFNT.

Change Font (Font Type=1): When you choose 1 for the *Font type* prompt, the following display appears.

Change PFD Definition Font

Font number : 1
Font type : 1 Font and character identifier

Type choices, press Enter.

Font:
 Identifier 11 1-65535
 Point size *NONE 0.1-999.9, *NONE

Character identifier:
 Graphic character set . . *SYSVAL 1-32767, *SYSVAL
 Code page 1-32767
 Text 'description' 10 CPI Courier

F3=Exit F5=Refresh F12=Cancel

Using this display, you can change the font identifier, point size, graphic character set, code page, and the description text.

Table 64. Change PFD Definition Font display fields

Field Name	Description
Font number	Shows the font number of the font being changed.
Font type	Shows the font type you specified in the previous display.
Identifier	Specifies the font identifier. You can specify a number from 1 to 65535 for your font.
Point size	Specifies the point size. You can use a value from 0.1 to 999.9 for your point size.
Graphic character set	Specifies the graphic character identifier. You can use a number from 1 to 32767. You can also specify *SYSVAL.