

```

vm2_first_ip      = "192.168.11.205"      # First IP from a consecutive pool of IPs
vm2_image_name    = "xiv_p9_image_rhel76" # The image name
vm2_remote_restart = "true"               # Enable Auto Remote Restart
vm2_storage_name  = "xiv_StoragePool"     # Storage Template
vm2_dockerdisk1   = "64"                  # Docker disk size in GB for ephemeral storage

```

#VM3 configuration (OCP - Workers(App) Nodes)

```

#-----
vm3_number        = "2"                    # Number of VMs
vm3_memory        = "64"                   # Memory GB
vm3_cpu           = "8"                    # Virtual CPU
vm3_vcpu_ratio    = "2"                   # vCPU RATIO 1:2 1 vCPU = 0.5 eCPU (cores)
vm3_name          = "wrknode"              # Hostname prefix
vm3_first_ip      = "192.168.11.208"      # First IP from a consecutive pool of IPs
vm3_image_name    = "xiv_p9_image_rhel76" # The image name
vm3_remote_restart = "false"              # Disable Auto Remote Restart
vm3_storage_name  = "xiv_StoragePool"     # Storage Template
vm3_dockerdisk1   = "128"                 # Docker disk size in GB for ephemeral storage

```

#VM4 configuration (OCP - Load Balancer Node)

```

#-----
vm4_number        = "0"                    # Number of VMs
vm4_memory        = "8"                   # Memory GB
vm4_cpu           = "2"                    # Virtual CPU
vm4_vcpu_ratio    = "4"                   # vCPU RATIO 1:4 1 vCPU = 0.25 eCPU (cores)
vm4_name          = "lbsnode"              # Hostname prefix
vm4_first_ip      = "192.168.11.212"      # First IP from a consecutive pool of IPs
vm4_image_name    = "xiv_p9_image_rhel76" # The image name
vm4_remote_restart = "true"               # Enable Auto Remote Restart

```

Attention: To use an existing network, you need to remove the network.tf file before applying the configuration.

Master-Infrastructure and Worker Nodes have an additional disk DOCKER_DISK_1 for docker-vg.

- Initialize Terraform working directory:

```

cd <PATH> #ocp-aio /ocp-7nodes ocp-3nodes
terraform init
Initializing the backend...
Initializing provider plugins...
The following providers do not have any version constraints in configuration,
so the latest version was installed.
...
Output truncated
...
* provider.null: version = "~> 2.1"
* provider.openstack: version = "~> 1.22"
Terraform has been successfully initialized!
You may now begin working with Terraform. Try running "terraform plan" to see
any changes that are required for your infrastructure. All Terraform commands
should now work.
If you ever set or change modules or backend configuration for Terraform,
rerun this command to reinitialize your working directory. If you forget, other
commands will detect it and remind you to do so if necessary.

```

- Create an execution plan: