

you performed this command last is used. If you specify *PRV for the PAGSEG parameter, it is not necessary to specify a library.

page-segment-name

Specify the name of the page segment to be created.

The possible library values are:

***CURLIB**

The current library for the job is used to create the page segment. If no library is specified as the current library for the job, library QGPL is used.

library-name

Specify the library in which the page segment will be created.

From folder (FRMFLR)

Specifies the name of the folder that contains the PC document to be converted.

The possible values are:

***PRV** Specifies the name of the folder used when you previously created a page segment of the same name.

folder-name

Specify the folder name.

From PC document (FRMDOC)

Specifies the PC document name to be converted.

The possible values are:

***PRV** Specifies the name of the PC document used when you previously created a page segment of the same name.

***PAGSEG**

Specifies that the name of the page segment to be created is the same as the name of the PC document.

PC-document-name

Specify the PC document name that is to be converted.

Change image size (CHGIMGSIZE)

Specifies whether the size of the image in the page segment is changed or not.

The possible values are:

***SAME**

Specifies the same value used for this parameter when you previously created a page segment of the same name. If this is the first page segment, the default value is *NO.

***NO** Specifies not to change the image size.

***YES** Specifies to change the image size.

If you specify *YES, the IMGSIZE and MAPPING parameters will appear, and you can specify the new image size in the page segment and how to map the input image to the size.