

Table 3: Specifications

Operating Conditions	- Temperature: 10-40°C (Heaters must have secondary interlock) - Max Pressure: 1500 torr - Pneumatic Valve Actuation Pressure: 70 to 110 psig
Carrier Gas	0-500 sccm (user supplied MFC) - Filtered to 0.003 µm - Purified to < 1ppb contaminants - Nitrogen or inert gas (NO OXYGEN)
Vapor Pressure	31 torr at 40°C 13 torr at 25°C See Figure 1 for graph
Tools & Supplies Required	- PPE (see SDS) (2) 1/4" SS VCR gaskets no silver plating (Swagelok PN:SS-4-VCR-2-VS) 3/4" and 5/8" wrenches
Required Facilities	- Facility approved abatement system for hydrazine - Hydrazine safety gas monitor - Electrical ground connection - Proper ventilation

How to Order

To place an order for **BRUTE Hydrazine** refer to Table 3 below. Choose the mass of solution desired and contact RASIRC at sales@rasirc.com to order the associated part numbers.

Table 4: BRUTE Hydrazine Vessel Rental

Name	Mass of Solution	Chemistry Part Number	Lid Type	Vessel Part Number
BRUTE Hydrazine Vessel	250g	100723	Standard	100834
	1000g	100825	Standard	100857

About RASIRC

RASIRC specializes in products that generate and deliver gas to fabrication processes. Each unit is a dynamic gas plant in a box—converting common liquid chemistries into safe and reliable gas flow for most processes. RASIRC technology delivers water vapor, hydrogen peroxide gas and hydrazine gas in controlled, repeatable concentrations. RASIRC gas delivery systems, humidifiers, and closed loop humidification systems are critical for many applications in semiconductor, photovoltaic, pharmaceutical, medical, biological, fuel cell, and power industries.

